# FCC RF Test Report

| | | |
|---|---|---|
| APPLICANT | : | MeiG Smart Technology Co., Ltd |
| EQUIPMENT | : | Smart Module |
| BRAND NAME | : | MEIGLink |
| MODEL NAME | : | SLM920 |
| FCC ID | : | 2APJ4-SLM920 |
| STANDARD | : | 47 CFR Part 2, 90(R) |
| CLASSIFICATION | : | PCS Licensed Transmitter (PCB) |
| TEST DATE(S) | : | Aug. 02, 2023 ~ Aug. 09, 2023 |

**We, Sporton International Inc. (Kunshan), would like to declare that the tested sample has been evaluated in accordance with the procedures given in ANSI C63.26 and shown compliance with the applicable technical standards.**

**The test results in this report apply exclusively to the tested model / sample. Without written approval of Sporton International Inc. (Kunshan), the test report shall not be reproduced except in full.**

Jason Jia

**Approved by: Jason Jia**

ACCREDITED
Cert #5145.02

***Sporton International Inc. (Kunshan)***
***No. 1098, Pengxi North Road, Kunshan Economic Development Zone Jiangsu Province 215300 People's Republic of China***

# TABLE OF CONTENTS

**REVISION HISTORY** ..... **3**

**SUMMARY OF TEST RESULT** ..... **4**

**1 GENERAL DESCRIPTION** ..... **5**

1.1 Applicant ..... 5
1.2 Manufacturer ..... 5
1.3 Feature of Equipment Under Test ..... 5
1.4 Maximum ERP Power, and Emission Designator ..... 6
1.5 Testing Site ..... 6
1.6 Test Software ..... 6
1.7 Applied Standards ..... 7

**2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST** ..... **8**

2.1 Test Mode ..... 8
2.2 Connection Diagram of Test System ..... 9
2.3 Support Unit used in test configuration and system ..... 9
2.4 Measurement Results Explanation Example ..... 10
2.5 Frequency List of Low/Middle/High Channels ..... 10

**3 CONDUCTED TEST ITEMS** ..... **11**

3.1 Measuring Instruments ..... 11
3.2 Conducted Output Power and ERP ..... 12
3.3 Peak-to-Average Ratio ..... 13
3.4 Occupied Bandwidth ..... 14
3.5 Conducted Band Edge Measurement ..... 15
3.6 Emission Mask ..... 16
3.7 Conducted Spurious Emission Measurement ..... 17
3.8 Frequency Stability Measurement ..... 18

**4 RADIATED TEST ITEMS** ..... **19**

4.1 Measuring Instruments ..... 19
4.2 Test Setup ..... 19
4.3 Test Result of Radiated Test ..... 20
4.4 Radiated Spurious Emission Measurement ..... 21

**5 LIST OF MEASURING EQUIPMENT** ..... **22**

**6 MEASUREMENT UNCERTAINTY** ..... **23**

**APPENDIX A. TEST RESULTS OF CONDUCTED TEST**

**APPENDIX B. TEST RESULTS OF RADIATED TEST**

**APPENDIX C. TEST SETUP PHOTOGRAPHS**

# REVISION HISTORY

| REPORT NO. | VERSION | DESCRIPTION | ISSUED DATE |
|---|---|---|---|
| FG372609B | Rev. 01 | Initial issue of report | Sep. 06, 2023 |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

# SUMMARY OF TEST RESULT

| Report Section | FCC Rule | Description | Limit | Result | Remark |
|---|---|---|---|---|---|
| 3.2 | §2.1046 | Conducted Output Power | — | Reporting only | - |
| | §90.542 (a)(7) | Effective Radiated Power | ERP < 3Watt | PASS | - |
| 3.3 | - | Peak-to-Average Ratio | — | Reporting only | - |
| 3.4 | §2.1049 | Occupied Bandwidth | — | Reporting only | - |
| 3.5 | §2.1053<br>§90.543 (e)(2)(3) | Conducted Band Edge Measurement | Refer standard | PASS | - |
| 3.6 | §2.1051<br>§90.210(n) | Emission Mask | Mask B | PASS | - |
| 3.7 | §2.1053<br>§90.543 (e)(3) | Conducted Spurious Emission | < $43+10\log_{10}$(P[Watts]) | PASS | - |
| 3.8 | §2.1055<br>§90.539 (e) | Frequency Stability Temperature & Voltage | < ±1.25 ppm | PASS | - |
| 4.4 | §2.1053<br>§90.543 (e)(3)<br>§90.543 (f) | Radiated Spurious Emission | < $43+10\log_{10}$(P[Watts]) | PASS | Under limit 8.08 dB at 1584.00 MHz |

**Conformity Assessment Condition:**

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section “Measurement Uncertainty”

**Disclaimer:**

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

# 1 General Description

## 1.1 Applicant

**MeiG Smart Technology Co., Ltd**
2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

## 1.2 Manufacturer

**MeiG Smart Technology Co., Ltd**
2nd Floor,Office Building,No.5 Lingxia Road,Fenghuang,Fuyong Street,Bao'an District,Shenzhen City.

## 1.3 Feature of Equipment Under Test

| Product Feature | |
|---|---|
| **Equipment** | Smart Module |
| **Brand Name** | MEIGLink |
| **Model Name** | SLM920 |
| **FCC ID** | 2APJ4-SLM920 |
| **Tx Frequency** | LTE Band 14: 788 MHz ~ 798 MHz |
| **Rx Frequency** | LTE Band 14: 758 MHz ~ 768 MHz |
| **Bandwidth** | 5MHz / 10MHz |
| **Maximum Output Power to Antenna** | 23.07 dBm |
| **Antenna Gain** | 3.58 dBi |
| **Type of Modulation** | QPSK / 16QAM / 64QAM / 256QAM |
| **IMEI Code** | Conducted: 860662054883547<br>Radiation: 86066205488350 |
| **HW Version** | V1.03 |
| **SW Version** | V01-T02 |
| **EUT Stage** | Identical Prototype |

**Remark:** The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description.

## 1.4 Maximum Conducted Power and Emission Designator

| LTE Band 14 | | QPSK | | 16QAM/64QAM/256QAM | |
|---|---|---|---|---|---|
| BW (MHz) | Frequency Range (MHz) | Maximum Conducted Power (W) | Emission Designator (99%OBW) | Maximum Conducted Power (W) | Emission Designator (99%OBW) |
| **5** | **790.5~795.5** | 0.2018 | 4M49G7D | 0.1734 | 4M49W7D |
| **10** | **793** | 0.2028 | 8M99G7D | 0.1766 | 8M95W7D |

Note: Based on engineering evaluation, only the maximum bandwidth and the worst modulation test results are shown in the report.

## 1.5 Testing Site

Sporton International Inc. (Kunshan) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.02.

| | | | |
|---|---|---|---|
| **Test Firm** | Sporton International Inc. (Kunshan) | | |
| **Test Site Location** | No. 1098, Pengxi North Road, Kunshan Economic Development Zone<br>Jiangsu Province 215300 People's Republic of China<br>TEL : +86-512-57900158 | | |
| **Test Site No.** | **Sporton Site No.** | **FCC Designation No.** | **FCC Test Firm Registration No.** |
| | 03CH04-KS<br>TH01-KS | CN1257 | 314309 |

## 1.6 Test Software

| Item | Site | Manufacture | Name | Version |
|---|---|---|---|---|
| 1. | TH01-KS | SPORTON | FCC LTE_Ver2.0<br>Auto_china_210503 | 2.0 |
| 2. | 03CH04-KS | AUDIX | E3 | 210616 |

## 1.7 Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 2, Part 90(R)
- ANSI C63.26
- KDB 971168 D01 Power Meas License Digital Systems v03r01
- KDB 412172 D01 Determining ERP and EIRP v01r01

**Remark:**

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.

# 2 Test Configuration of Equipment Under Test

## 2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas License Digital Systems v03r01 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission. (Y Plane)

| Conducted Test Cases | Band | Bandwidth (MHz) | | | | | | Modulation | | | | RB # | | | Test Channel | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | 1.4 | 3 | 5 | 10 | 15 | 20 | QPSK | 16 QAM | 64 QAM | 256 QAM | 1 | Half | Full | L | M | H |
| Max. Output Power | 14 | - | - | V | | - | - | V | V | | | V | | | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | | V | | V | |
| Peak-to-Average Ratio | 14 | - | - | | V | - | - | V | V | V | V | | | V | | V | |
| 26dB and 99% Bandwidth | 14 | - | - | V | | - | - | V | V | | | | | V | | V | |
| | 14 | - | - | | V | - | - | V | V | | | | | V | | V | |
| Conducted Band Edge | 14 | - | - | V | | - | - | V | V | V | V | V | | V | V | | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | | V | V | | V |
| Emission Mask | 14 | - | - | V | | - | - | V | V | V | V | V | | V | V | | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | | V | | V | |
| Conducted Spurious Emission | 14 | - | - | V | | - | - | V | | | | V | | | V | V | V |
| | 14 | - | - | | V | - | - | V | | | | V | | | | V | |
| Frequency Stability | 14 | - | - | | V | - | - | V | | | | | | V | | V | |
| E.R.P | 14 | - | - | V | | - | - | V | V | | | V | | | V | V | V |
| | 14 | - | - | | V | - | - | V | V | V | V | V | | V | | V | |
| Radiated Spurious Emission | 14 | Worst Case | | | | | | | | | | | | | | V | |
| Note | 1. The mark "v " means that this configuration is chosen for testing<br>2. The mark "-" means that this bandwidth is not supported.<br>3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported. | | | | | | | | | | | | | | | | |

## 2.2 Connection Diagram of Test System




This example is connection diagram of EUT test configurations.

. For detail, please refer to test mode configuration and setup photographs for each test item.

## 2.3 Support Unit used in test configuration and system

| Item | Equipment | Trade Name | Model No. | FCC ID | Data Cable | Power Cord |
|---|---|---|---|---|---|---|
| 1. | LTE Base Station | Anritsu | MT8820C | N/A | N/A | Unshielded, 1.8 m |
| 2. | Test Jig | N/A | N/A | N/A | N/A | N/A |
| 3. | Antenna | N/A | N/A | N/A | N/A | N/A |
| 4. | DC Power Supply | GW INSTEK | GPS-3030D | N/A | N/A | Unshielded, 1.8 m |

## 2.4 Measurement Results Explanation Example

**For all conducted test items:**

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss

*Offset = RF cable loss*

Following shows an offset computation example with cable loss 4.8 dB

Example :

*Offset(dB) = RF cable loss(dB)*

= 4.8 (dB)

## 2.5 Frequency List of Low/Middle/High Channels

| LTE Band 14 Channel and Frequency List | | | | |
|---|---|---|---|---|
| **BW [MHz]** | **Channel/Frequency(MHz)** | **Lowest** | **Middle** | **Highest** |
| 10 | Channel | - | 23330 | - |
| | Frequency | - | 793 | - |
| 5 | Channel | 23305 | 23330 | 23355 |
| | Frequency | 790.5 | 793 | 795.5 |

# 3 Conducted Test Items

## 3.1 Measuring Instruments

See list of measuring instruments of this test report.

### 3.1.1 Test Setup

### 3.1.2 Conducted Output Power




### 3.1.3 Peak-to-Average Ratio, Occupied Bandwidth, Conducted Band-Edge, Emission Mask, and Conducted Spurious Emission




### 3.1.4 Frequency Stability




### 3.1.5 Test Result of Conducted Test

Please refer to Appendix A.

## 3.2 Conducted Output Power and ERP

### 3.2.1 Description of the Conducted Output Power Measurement and ERP

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

The ERP of mobile transmitters must not exceed 3 Watts for LTE Band 14.

According to KDB 412172 D01 Power Approach,

EIRP = $P_T + G_T – L_C$, ERP = EIRP -2.15, where

$P_T$ = transmitter output power in dBm

$G_T$ = gain of the transmitting antenna in dBi

$L_C$ = signal attenuation in the connecting cable between the transmitter and antenna in dB

### 3.2.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.2
2. The transmitter output port was connected to the system simulator.
3. Set EUT at maximum power through the system simulator.
4. Select lowest, middle, and highest channels for each band and different modulation.
5. Measure and record the power level from the system simulator.

## 3.3 Peak-to-Average Ratio

### 3.3.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

### 3.3.2 Test Procedures

1. The EUT was connected to spectrum and system simulator via a power divider.
2. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
3. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
4. Record the deviation as Peak to Average Ratio.

## 3.4 Occupied Bandwidth

### 3.4.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

### 3.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.4
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
   (this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “–X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

## 3.5 Conducted Band Edge Measurement

### 3.5.1 Description of Conducted Band Edge Measurement

For operations in the 758-768 MHz and the 788-798 MHz bands

(1) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 76 + 10 log (P) dB in a 6.25 kHz band segment, for base and fixed stations.

(2) On all frequencies between 769-775 MHz and 799-805 MHz, by a factor not less than 65 + 10 log (P) dB in a 6.25 kHz band segment, for mobile and portable stations.

(3) On any frequency between 775-788 MHz, above 805 MHz, and below 758 MHz, by at least 43 + 10 log (P) dB.

### 3.5.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set spectrum analyzer with RMS detector.
5. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
6. Checked that all the results comply with the emission limit line.

   Example:

   The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)

   = P(W)- [43 + 10log(P)] (dB)

   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB) = -13dBm.

# 3.6 Emission Mask

## 3.6.1 Description of Emission Mask

<Emission Mask B>.

For transmitters that are equipped with an audio low-pass filter, the power of any emission must be attenuated below the unmodulated carrier power (P) as follows:

(1) On any frequency removed from the assigned frequency by more than 50 percent, but not more than 100 percent of the authorized bandwidth: At least 25 dB.

(2) On any frequency removed from the assigned frequency by more than 100 percent, but not more than 250 percent of the authorized bandwidth: At least 35 dB.

(3) On any frequency removed from the assigned frequency by more than 250 percent of the authorized bandwidth: At least 43 + 10 log (P) dB.

## 3.6.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
5. Set spectrum analyzer with RMS detector.
6. Taking the record of maximum spurious emission.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

## 3.7 Conducted Spurious Emission Measurement

### 3.7.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30MHz up to a frequency including its $10^{th}$ harmonic.

### 3.7.2 Test Procedures

1. The testing follows ANSI C63.26 section 5.7
2. The EUT was connected to spectrum analyzer and base station via power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's, for under 1GHz RBW = 100kHz, VBW = 300kHz and for above 1GHz RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. Set spectrum analyzer with RMS detector.
8. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
9. The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
   = P(W)- [43 + 10log(P)] (dB)
   = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
   = -13dBm.

## 3.8 Frequency Stability Measurement

### 3.8.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±1.25 ppm of the center frequency.

### 3.8.2 Test Procedures for Temperature Variation

1. The testing follows ANSI C63.26 section 5.6.4
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C. The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

### 3.8.3 Test Procedures for Voltage Variation

1. The testing follows ANSI C63.26 section 5.6.5.
2. The EUT was placed in a temperature chamber at 20±5°C and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value for other than hand carried battery equipment.
4. For hand carried, battery powered equipment, reduce the primary ac or dc supply voltage to the battery operating end point, which shall be specified by the manufacturer.
5. The variation in frequency was measured for the worst case.

# 4 Radiated Test Items

## 4.1 Measuring Instruments

See list of measuring instruments of this test report.

## 4.2 Test Setup

### 4.2.1 For radiated test below 30MHz




### 4.2.2 For radiated test from 30MHz to 1GHz



### 4.2.3 For radiated test above 1GHz




## 4.3 Test Result of Radiated Test

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

Please refer to Appendix B.

## 4.4 Radiated Spurious Emission Measurement

### 4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least 43 + 10 log (P) dB.

For operations in the 758-775 MHz and 788-805 MHz bands, all emissions including harmonics in the band 1559–1610 MHz shall be limited to -70 dBW/MHz equivalent isotropically radiated power (EIRP) for wideband signals, and -80 dBW EIRP for discrete emissions of less than 700 Hz bandwidth. For the purpose of equipment authorization, a transmitter shall be tested with an antenna that is representative of the type that will be used with the equipment in normal operation.

### 4.4.2 Test Procedures

1. The testing follows ANSI C63.26 Section 5.5
2. The EUT was placed on a turntable with 0.8 meter height for frequency below 1GHz and 1.5 meter height for frequency above 1GHz respectively above ground.
3. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
6. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
7. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
8. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
9. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
10. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain
11. ERP (dBm) = EIRP - 2.15
12. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
    The limit line is derived from 43 + 10log(P)dB below the transmitter power P(Watts)
    = P(W)- [43 + 10log(P)] (dB)
    = [30 + 10log(P)] (dBm) - [43 + 10log(P)] (dB)
    = -13dBm.

# 5 List of Measuring Equipment

| Instrument | Manufacturer | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|---|---|---|---|---|---|---|---|---|
| Spectrum Analyzer | R&S | FSV40 | 101040 | 10Hz~40GHz | Oct. 12, 2022 | Aug. 02, 2023 | Oct. 11, 2023 | Conducted (TH01-KS) |
| Power divider | STI | STI08-0055 | - | 0.5~40GHz | NCR | Aug. 02, 2023 | NCR | Conducted (TH01-KS) |
| Temperature & humidity chamber | Hongzhan | LP-150U | H2014011440 | -40~+150°C 20%~95%RH | Jul. 06, 2023 | Aug. 02, 2023 | Jul. 05, 2024 | Conducted (TH01-KS) |
| EXA Spectrum Analyzer | Keysight | N9010B | MY57471079 | 10Hz-44G,MAX 30dB | Oct. 12, 2022 | Aug. 09, 2023 | Oct. 11, 2023 | Radiation (03CH04-KS) |
| Loop Antenna | R&S | HFH2-Z2E | 101125 | 9kHz~30MHz | Sep. 22, 2022 | Aug. 09, 2023 | Sep. 21, 2023 | Radiation (03CH04-KS) |
| Bilog Antenna | TeseQ | CBL6111D | 49922 | 30MHz-1GHz | Apr. 09, 2023 | Aug. 09, 2023 | Apr. 08, 2024 | Radiation (03CH04-KS) |
| Horn Antenna | Schwarzbeck | BBHA9120D | 1284 | 1GHz~18GHz | Oct. 16, 2022 | Aug. 09, 2023 | Oct. 15, 2023 | Radiation (03CH04-KS) |
| Amplifier | SONOMA | 310N | 380827 | 9KHz-1GHz | Jul. 06, 2023 | Aug. 09, 2023 | Jul. 05, 2024 | Radiation (03CH04-KS) |
| high gain Amplifier | EM | EM01G18GA | 060840 | 1Ghz-18Ghz | Oct. 12, 2022 | Aug. 09, 2023 | Oct. 11, 2023 | Radiation (03CH04-KS) |
| Amplifier | Agilent | 8449B | 3008A02370 | 1Ghz-18Ghz | Oct. 12, 2022 | Aug. 09, 2023 | Oct. 11, 2023 | Radiation (03CH04-KS) |
| AC Power Source | Chroma | 61601 | F104090004 | N/A | NCR | Aug. 09, 2023 | NCR | Radiation (03CH04-KS) |
| Turn Table | ChamPro | EM 1000-T | 060762-T | 0~360 degree | NCR | Aug. 09, 2023 | NCR | Radiation (03CH04-KS) |
| Antenna Mast | ChamPro | EM 1000-A | 060762-A | 1 m~4 m | NCR | Aug. 09, 2023 | NCR | Radiation (03CH04-KS) |

NCR: No Calibration Required

# 6 Measurement Uncertainty

The measurement uncertainties shown below were calculated in accordance with the requirements of ANSI 63.26-2015. All the measurement uncertainty value were shown with a coverage K=2 to indicate 95% level of confidence. The measurement data show herein meets or exceeds the CISPR measurement uncertainty values specified in CISPR 16-4-2 and can be compared directly to specified limit to determine compliance.

**Uncertainty of Conducted Measurement**

| Test Item | Uncertainty |
|---|---|
| Conducted Power | ±0.46 dB |
| Conducted Emissions | ±2.26 dB |
| Occupied Channel Bandwidth | ±0.1 % |

**Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)**

| | |
|---|---|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.82 dB |

**Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)**

| | |
|---|---|
| Measuring Uncertainty for a Level of Confidence of 95% (U = 2Uc(y)) | 3.56dB |

---------- THE END ----------

# Appendix A. Test Results of Conducted Test

| Test Engineer : | Simle Wang | Temperature : | 22~23℃ |
|---|---|---|---|
| | | Relative Humidity : | 40~42% |

## Conducted Output Power(Average power) and ERP

| BW [MHz] | Modulation | RB Size | RB Offset | Power Low Ch. / Freq. | Power Middle Ch. / Freq. | Power High Ch. / Freq. | ERP(W) | | |
|---|---|---|---|---|---|---|---|---|---|
| Channel | | | | 23330 | | | | | |
| Frequency (MHz) | | | | 793 | | | | M | |
| 10 | QPSK | 1 | 0 | | 23.07 | | | 0.2818 | |
| 10 | QPSK | 1 | 49 | | 22.80 | | | 0.2649 | |
| 10 | QPSK | 50 | 0 | | 22.06 | | | 0.2234 | |
| 10 | 16QAM | 1 | 0 | | 22.47 | | | 0.2455 | |
| 10 | 64QAM | 1 | 0 | | 22.33 | | | 0.2377 | |
| 10 | 256QAM | 1 | 0 | | 22.31 | | | 0.2366 | |
| Channel | | | | 23305 | 23330 | 23355 | ERP(W) | | |
| Frequency (MHz) | | | | 790.5 | 793 | 795.5 | L | M | H |
| 5 | QPSK | 1 | 0 | 23.03 | 23.05 | 22.92 | 0.2793 | 0.2805 | 0.2723 |
| 5 | 16QAM | 1 | 0 | 22.36 | 22.39 | 22.08 | 0.2393 | 0.2410 | 0.2244 |

# LTE Band 14

## Peak-to-Average Ratio

| Mode | LTE Band 14 / 10MHz | | | | |
|---|---|---|---|---|---|
| Mod. | QPSK | 16QAM | 64QAM | 256QAM | Limit: 13dB |
| RB Size | Full RB | Full RB | Full RB | Full RB | Result |
| Middle CH | 4.46 | 4.43 | 5.77 | 5.77 | PASS |

**LTE Band 14 / 10MHz**

**Middle Channel / Full RB/ QPSK**




**Middle Channel / Full RB/ 16QAM**



## Middle Channel / Full RB/ 64QAM




## Middle Channel / Full RB/ 256QAM



# 26dB Bandwidth

| Mode | LTE Band 14 : 26dB BW(MHz) | |
|---|---|---|
| BW | 5MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 4.82 | 4.89 |
| BW | 10MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 9.75 | 9.81 |

## LTE Band 14

### Middle Channel / 5MHz / QPSK




### Middle Channel / 5MHz / 16QAM




## LTE Band 14

### Middle Channel /10MHz / QPSK




### Middle Channel / 10MHz / 16QAM



# Occupied Bandwidth

| Mode | LTE Band 14 : 99%OBW(MHz) | |
|---|---|---|
| BW | 5MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 4.49 | 4.49 |
| BW | 10MHz | |
| Mod. | QPSK | 16QAM |
| Middle CH | 8.99 | 8.95 |

**LTE Band 14**

**Middle Channel / 5MHz / QPSK**




**Middle Channel / 5MHz / 16QAM**




**LTE Band 14**

**Middle Channel / 10MHz / QPSK**




**Middle Channel / 10MHz / 16QAM**



# Conducted Band Edge

## LTE Band 14 / 5MHz / QPSK

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 755.22278 MHz | -65.55 dBm | -52.55 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 767.92857 MHz | -64.55 dBm | -94.55 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.51049 MHz | -76.50 dBm | -41.50 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -21.39 dBm | -8.39 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.34615 MHz | 19.77 dBm | -10.23 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.19081 MHz | -71.78 dBm | -36.78 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 809.73277 MHz | -64.12 dBm | -51.12 dB |

Date: 2.AUG.2023 14:46:02

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.99401 MHz | -63.14 dBm | -50.14 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 766.07143 MHz | -64.48 dBm | -94.48 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 772.59940 MHz | -76.68 dBm | -41.68 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 786.79870 MHz | -60.14 dBm | -47.14 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.67582 MHz | 18.87 dBm | -11.13 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.01499 MHz | -67.33 dBm | -32.33 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 807.24026 MHz | -64.04 dBm | -51.04 dB |

Date: 2.AUG.2023 15:08:00

### Lowest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 753.52847 MHz | -65.68 dBm | -52.68 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 760.37912 MHz | -64.34 dBm | -94.34 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.01998 MHz | -76.55 dBm | -41.55 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -28.03 dBm | -15.03 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 791.82967 MHz | 6.38 dBm | -23.62 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.50649 MHz | -57.23 dBm | -22.23 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 807.50500 MHz | -64.43 dBm | -51.43 dB |

Date: 2.AUG.2023 14:57:43

### Highest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 750.41958 MHz | -65.63 dBm | -52.63 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 758.68681 MHz | -64.50 dBm | -94.50 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 769.47053 MHz | -76.69 dBm | -41.69 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.83766 MHz | -44.60 dBm | -31.60 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.59890 MHz | 6.01 dBm | -23.99 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.01499 MHz | -45.21 dBm | -10.21 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 809.01349 MHz | -63.85 dBm | -50.85 dB |

Date: 2.AUG.2023 15:14:55

## LTE Band 14 / 5MHz / 16QAM

### Lowest Band Edge /1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.76424 MHz | -65.51 dBm | -52.51 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 767.66484 MHz | -64.38 dBm | -94.38 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.44555 MHz | -76.70 dBm | -41.70 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -21.95 dBm | -8.95 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.35714 MHz | 19.40 dBm | -10.60 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.24476 MHz | -73.17 dBm | -38.17 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.66084 MHz | -64.33 dBm | -51.33 dB |

Date: 2.AUG.2023 14:47:24

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.97802 MHz | -63.51 dBm | -50.51 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 764.95055 MHz | -64.39 dBm | -94.39 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 772.78521 MHz | -76.62 dBm | -41.62 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 784.64286 MHz | -61.11 dBm | -48.11 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.63187 MHz | 18.01 dBm | -11.99 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.80619 MHz | -68.13 dBm | -33.13 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.60190 MHz | -64.20 dBm | -51.20 dB |

Date: 2.AUG.2023 15:09:23

### Lowest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 756.25375 MHz | -65.68 dBm | -52.68 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 761.92857 MHz | -64.50 dBm | -94.50 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.84016 MHz | -76.70 dBm | -41.70 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -28.97 dBm | -15.97 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 792.54396 MHz | 5.86 dBm | -24.14 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.29670 MHz | -56.95 dBm | -21.95 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 807.98951 MHz | -64.31 dBm | -51.31 dB |

Date: 2.AUG.2023 14:59:05

### Highest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 750.11588 MHz | -65.65 dBm | -52.65 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 763.76374 MHz | -64.56 dBm | -94.56 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.34266 MHz | -76.38 dBm | -41.38 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.94156 MHz | -44.12 dBm | -31.12 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.90659 MHz | 5.07 dBm | -24.93 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.02697 MHz | -44.97 dBm | -9.97 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.75175 MHz | -64.46 dBm | -51.46 dB |

Date: 2.AUG.2023 15:16:18

## LTE Band 14 / 5MHz / 64QAM

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 752.88911 MHz | -65.53 dBm | -52.53 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 762.87363 MHz | -64.17 dBm | -94.17 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.89411 MHz | -76.46 dBm | -41.46 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -24.02 dBm | -11.02 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.33516 MHz | 19.22 dBm | -10.78 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.14086 MHz | -73.57 dBm | -38.57 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.55694 MHz | -64.47 dBm | -51.47 dB |

Date: 2.AUG.2023 14:48:47

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.98601 MHz | -63.63 dBm | -50.63 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 759.23626 MHz | -64.29 dBm | -94.29 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.88911 MHz | -76.71 dBm | -41.71 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 784.69481 MHz | -61.17 dBm | -48.17 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.68681 MHz | 17.45 dBm | -12.55 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.80020 MHz | -67.94 dBm | -32.94 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.78072 MHz | -63.95 dBm | -50.95 dB |

Date: 2.AUG.2023 15:10:46

### Lowest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 754.40759 MHz | -65.68 dBm | -52.68 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 767.81868 MHz | -64.49 dBm | -94.49 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.74525 MHz | -76.70 dBm | -41.70 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -28.92 dBm | -15.92 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 792.20330 MHz | 5.70 dBm | -24.30 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.11688 MHz | -57.37 dBm | -22.37 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.77572 MHz | -64.47 dBm | -51.47 dB |

Date: 2.AUG.2023 15:00:28

### Highest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 755.50250 MHz | -65.65 dBm | -52.65 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 764.65385 MHz | -64.53 dBm | -94.53 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.81019 MHz | -76.61 dBm | -41.61 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.88961 MHz | -44.19 dBm | -31.19 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.77473 MHz | 5.21 dBm | -24.79 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.08691 MHz | -45.19 dBm | -10.19 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.15634 MHz | -64.48 dBm | -51.48 dB |

Date: 2.AUG.2023 15:17:42

## LTE Band 14 / 5MHz / 256QAM

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.17283 MHz | -65.55 dBm | -52.55 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 766.53297 MHz | -64.32 dBm | -94.32 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.44456 MHz | -76.57 dBm | -41.57 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -23.06 dBm | -10.06 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.34615 MHz | 19.07 dBm | -10.93 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.24476 MHz | -73.25 dBm | -38.25 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 809.38811 MHz | -64.35 dBm | -51.35 dB |

Date: 2.AUG.2023 14:50:09

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.97003 MHz | -63.47 dBm | -50.47 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 763.85165 MHz | -64.20 dBm | -94.20 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 771.14286 MHz | -76.65 dBm | -41.65 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 784.72078 MHz | -61.22 dBm | -48.22 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.65385 MHz | 18.05 dBm | -11.95 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.77023 MHz | -67.83 dBm | -32.83 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.12138 MHz | -64.44 dBm | -51.44 dB |

Date: 2.AUG.2023 15:12:10

### Lowest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 756.13387 MHz | -65.62 dBm | -52.62 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 760.25824 MHz | -64.40 dBm | -94.40 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.45155 MHz | -76.69 dBm | -41.69 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -29.12 dBm | -16.12 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 792.17033 MHz | 5.60 dBm | -24.40 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.25475 MHz | -57.36 dBm | -22.36 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 807.70979 MHz | -64.50 dBm | -51.50 dB |

Date: 2.AUG.2023 15:01:51

### Highest Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.89211 MHz | -65.64 dBm | -52.64 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 758.23626 MHz | -64.42 dBm | -94.42 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.04396 MHz | -76.64 dBm | -41.64 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.94156 MHz | -44.15 dBm | -31.15 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.78571 MHz | 5.12 dBm | -24.88 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.04496 MHz | -44.78 dBm | -9.78 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.27722 MHz | -63.81 dBm | -50.81 dB |

Date: 2.AUG.2023 15:19:05

## LTE Band 14 / 10MHz / QPSK

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.68432 MHz | -65.62 dBm | -52.62 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 762.19231 MHz | -64.55 dBm | -94.55 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 769.29071 MHz | -76.67 dBm | -41.67 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -35.64 dBm | -22.64 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.60989 MHz | 19.06 dBm | -10.94 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.80220 MHz | -66.00 dBm | -31.00 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 808.31918 MHz | -64.17 dBm | -51.17 dB |

Date: 2.AUG.2023 15:22:38

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.71429 MHz | -63.14 dBm | -50.14 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 765.09341 MHz | -64.23 dBm | -94.23 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.25375 MHz | -76.45 dBm | -41.45 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 779.74675 MHz | -41.75 dBm | -28.75 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.44505 MHz | 18.71 dBm | -11.29 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.83217 MHz | -67.39 dBm | -32.39 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.17732 MHz | -64.26 dBm | -51.26 dB |

Date: 2.AUG.2023 15:28:09

### Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.34665 MHz | -65.65 dBm | -52.65 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 764.37912 MHz | -64.31 dBm | -94.31 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.55345 MHz | -76.45 dBm | -41.45 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -30.25 dBm | -17.25 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.30220 MHz | 3.41 dBm | -26.59 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.05095 MHz | -45.69 dBm | -10.69 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.94156 MHz | -64.57 dBm | -51.57 dB |

Date: 2.AUG.2023 15:33:40

## LTE Band 14 / 10MHz / 16QAM

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.02897 MHz | -65.60 dBm | -52.60 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 766.66484 MHz | -64.54 dBm | -94.54 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 770.03996 MHz | -76.49 dBm | -41.49 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -36.78 dBm | -23.78 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.58791 MHz | 18.28 dBm | -11.72 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.78422 MHz | -68.60 dBm | -33.60 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.44206 MHz | -64.48 dBm | -51.48 dB |

Date: 2.AUG.2023 15:24:01

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.69830 MHz | -63.49 dBm | -50.49 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 759.11538 MHz | -64.46 dBm | -94.46 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.23477 MHz | -76.69 dBm | -41.69 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 779.75974 MHz | -42.31 dBm | -29.31 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.42308 MHz | 19.19 dBm | -10.81 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.00300 MHz | -67.87 dBm | -32.87 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.44605 MHz | -64.20 dBm | -51.20 dB |

Date: 2.AUG.2023 15:29:32

### Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 754.83117 MHz | -65.60 dBm | -52.60 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 764.57692 MHz | -64.43 dBm | -94.43 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 772.20380 MHz | -76.46 dBm | -41.46 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.98052 MHz | -30.51 dBm | -17.51 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 792.36813 MHz | 3.30 dBm | -26.70 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.12887 MHz | -46.14 dBm | -11.14 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.51598 MHz | -64.48 dBm | -51.48 dB |

Date: 2.AUG.2023 15:35:03

## LTE Band 14 / 10MHz / 64QAM

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 756.41359 MHz | -65.60 dBm | -52.60 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 765.80769 MHz | -64.27 dBm | -94.27 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 773.10889 MHz | -76.59 dBm | -41.59 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -38.37 dBm | -25.37 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.58791 MHz | 18.68 dBm | -11.32 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.76024 MHz | -69.17 dBm | -34.17 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.65584 MHz | -64.37 dBm | -51.37 dB |

Date: 2.AUG.2023 15:25:24

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.72228 MHz | -63.45 dBm | -50.45 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 760.91758 MHz | -64.55 dBm | -94.55 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 770.15385 MHz | -76.53 dBm | -41.53 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 779.79870 MHz | -42.62 dBm | -29.62 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.40110 MHz | 18.32 dBm | -11.68 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.08092 MHz | -68.94 dBm | -33.94 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 806.77073 MHz | -64.18 dBm | -51.18 dB |

Date: 2.AUG.2023 15:30:54

### Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 757.64436 MHz | -65.61 dBm | -52.61 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 768.68681 MHz | -64.37 dBm | -94.37 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 774.56543 MHz | -76.46 dBm | -41.46 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.96753 MHz | -31.96 dBm | -18.96 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.60989 MHz | 2.33 dBm | -27.67 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.03896 MHz | -46.14 dBm | -11.14 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 809.03846 MHz | -64.25 dBm | -51.25 dB |

Date: 2.AUG.2023 15:50:15

## LTE Band 14 / 10MHz / 256QAM

### Lowest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 750.72328 MHz | -65.64 dBm | -52.64 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 760.34615 MHz | -64.25 dBm | -94.25 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 772.96503 MHz | -76.76 dBm | -41.76 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.99351 MHz | -37.06 dBm | -24.06 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 788.59890 MHz | 18.83 dBm | -11.17 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 801.77223 MHz | -69.49 dBm | -34.49 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 808.28422 MHz | -64.27 dBm | -51.27 dB |

Date: 2.AUG.2023 15:26:46

### Highest Band Edge / 1 RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.71429 MHz | -63.46 dBm | -50.46 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 758.70879 MHz | -64.22 dBm | -94.22 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 771.86214 MHz | -76.65 dBm | -41.65 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 779.78571 MHz | -42.87 dBm | -29.87 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 797.39011 MHz | 18.12 dBm | -11.88 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.03896 MHz | -69.11 dBm | -34.11 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 809.44306 MHz | -64.08 dBm | -51.08 dB |

Date: 2.AUG.2023 15:32:17

### Band Edge / Full RB




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 750.000 MHz | 758.000 MHz | 100.000 kHz | 751.33866 MHz | -65.58 dBm | -52.58 dB |
| 758.000 MHz | 769.000 MHz | 100.000 kHz | 766.62088 MHz | -64.72 dBm | -94.72 dB |
| 769.000 MHz | 775.000 MHz | 6.250 kHz | 769.78222 MHz | -76.61 dBm | -41.61 dB |
| 775.000 MHz | 788.000 MHz | 100.000 kHz | 787.40909 MHz | -32.06 dBm | -19.06 dB |
| 788.000 MHz | 799.000 MHz | 100.000 kHz | 793.09341 MHz | 2.39 dBm | -27.61 dB |
| 799.000 MHz | 805.000 MHz | 6.250 kHz | 799.05095 MHz | -46.60 dBm | -11.60 dB |
| 805.000 MHz | 810.000 MHz | 100.000 kHz | 805.82168 MHz | -64.50 dBm | -51.50 dB |

Date: 2.AUG.2023 15:48:12

# Conducted Spurious Emission

## LTE Band 14 / 5MHz

### Lowest Channel / QPSK




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 758.000 MHz | 100.000 kHz | 743.26537 MHz | -66.74 dBm | -53.74 dB |
| 805.000 MHz | 1.000 GHz | 100.000 kHz | 972.66492 MHz | -68.48 dBm | -55.48 dB |
| 1.000 GHz | 3.000 GHz | 1.000 MHz | 1.57711 GHz | -46.05 dBm | -33.05 dB |
| 3.000 GHz | 8.000 GHz | 1.000 MHz | 6.99485 GHz | -52.92 dBm | -39.92 dB |

Date: 2.AUG.2023 15:03:55

### Middle Channel / QPSK




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 758.000 MHz | 100.000 kHz | 745.81209 MHz | -66.67 dBm | -53.67 dB |
| 805.000 MHz | 1.000 GHz | 100.000 kHz | 910.78336 MHz | -68.28 dBm | -55.28 dB |
| 1.000 GHz | 3.000 GHz | 1.000 MHz | 1.58210 GHz | -44.05 dBm | -31.05 dB |
| 3.000 GHz | 8.000 GHz | 1.000 MHz | 6.99235 GHz | -52.86 dBm | -39.86 dB |

Date: 2.AUG.2023 15:05:16

### Highest Channel / QPSK




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 758.000 MHz | 100.000 kHz | 748.35882 MHz | -66.19 dBm | -53.19 dB |
| 805.000 MHz | 1.000 GHz | 100.000 kHz | 877.94228 MHz | -68.34 dBm | -55.34 dB |
| 1.000 GHz | 3.000 GHz | 1.000 MHz | 1.58710 GHz | -41.87 dBm | -28.87 dB |
| 3.000 GHz | 8.000 GHz | 1.000 MHz | 6.99535 GHz | -52.68 dBm | -39.68 dB |

Date: 2.AUG.2023 15:06:37

## LTE Band 14 / 10MHz

### Middle Channel / QPSK




Spurious Emissions

| Range Low | Range Up | RBW | Frequency | Power Abs | ΔLimit |
|---|---|---|---|---|---|
| 30.000 MHz | 758.000 MHz | 100.000 kHz | 743.62919 MHz | -65.73 dBm | -52.73 dB |
| 805.000 MHz | 1.000 GHz | 100.000 kHz | 818.59445 MHz | -68.55 dBm | -55.55 dB |
| 1.000 GHz | 3.000 GHz | 1.000 MHz | 1.57761 GHz | -46.46 dBm | -33.46 dB |
| 3.000 GHz | 8.000 GHz | 1.000 MHz | 6.99185 GHz | -52.70 dBm | -39.70 dB |

Date: 2.AUG.2023 15:21:16

# Mask

## LTE Band 14 / 5MHz / QPSK

### Lowest Channel / 1RB







### Lowest Channel / Full RB



## LTE Band 14 / 5MHz / 16QAM

### Lowest Channel / 1RB







### Lowest Channel / Full RB



## LTE Band 14 / 5MHz / 64QAM

### Lowest Channel / 1RB







### Lowest Channel / Full RB



## LTE Band 14 / 5MHz / 256QAM

### Lowest Channel / 1RB







### Lowest Channel / Full RB



## LTE Band 14 / 5MHz / QPSK

### Middle Channel / 1RB







### Middle Channel / Full RB



## LTE Band 14 / 5MHz / 16QAM

### Middle Channel / 1RB







### Middle Channel / Full RB



## LTE Band 14 / 5MHz / 64QAM

### Middle Channel / 1RB







### Middle Channel / Full RB



## LTE Band 14 / 5MHz / 256QAM

### Middle Channel / 1RB







### Middle Channel / Full RB



## LTE Band 14 / 5MHz / QPSK

### Highest Channel / 1RB







### Highest Channel / Full RB



## LTE Band 14 / 5MHz / 16QAM

### Highest Channel / 1RB







### Highest Channel / Full RB



## LTE Band 14 / 5MHz / 64QAM

### Highest Channel / 1RB







### Highest Channel / Full RB



## LTE Band 14 / 5MHz / 256QAM

### Highest Channel / 1RB







### Highest Channel / Full RB



## LTE Band 14 / 10MHz / QPSK

### Middle Channel / 1RB







### Middle Channel / Full RB