

TEST REPORT

Applicant: Aduro Technologies LLC

Address of Applicant: 475 WASHINGTON BLVD, MARINA DEL REY, California
90292, United States

Manufacturer/Factory: Sichuan Aduro Technology CO., LTD

**Address of
Manufacturer/Factory:** Building 23, Area A Meijiarongxiang Electronic Info Industry
Park, Renshou, Meishan, Sichuan, China

Equipment Under Test (EUT)

Product Name: BR30 smart light bulbs

Model No.: 81813-V2

Trade Mark: AduroSmart Eria

FCC ID: 2APKV-518912

Applicable standards: FCC CFR Title 47 Part 15 Subpart C Section 15.247

Date of sample receipt: November 22, 2022

Date of Test: November 23, 2022-April 08, 2024

Date of report issued: April 08, 2024

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:




Robinson Luo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Report No.	Version No.	Date	Description
GTS202211000223F01	00	February 14, 2023	Original
GTS202211000226F01	01	April 08, 2024	Class II permissive change

Prepared By:




Project Engineer

Date:

April 08, 2024

Check By:



Reviewer

Date:

April 08, 2024

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
4.1 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 GENERAL DESCRIPTION OF EUT	5
5.2 TEST MODE	7
5.3 DESCRIPTION OF SUPPORT UNITS	7
5.4 DEVIATION FROM STANDARDS	7
5.5 ABNORMALITIES FROM STANDARD CONDITIONS	7
5.6 TEST FACILITY	7
5.7 TEST LOCATION	7
5.8 ADDITIONAL INSTRUCTIONS	7
6 TEST INSTRUMENTS LIST	8
7 TEST RESULTS AND MEASUREMENT DATA	10
7.1 ANTENNA REQUIREMENT	10
7.2 CONDUCTED EMISSIONS	11
7.3 SPURIOUS EMISSION IN NON-RESTRICTED & RESTRICTED BANDS	14
7.3.1 Radiated Emission Method	14
8 TEST SETUP PHOTO	23
9 EUT CONSTRUCTIONAL DETAILS	23

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	N/A*
Channel Bandwidth	15.247 (a)(2)	N/A*
Power Spectral Density	15.247 (e)	N/A*
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Remarks:

1. Pass: The EUT complies with the essential requirements in the standard.
2. Test according to ANSI C63.10:2013
3. N/A*: Not applicable. This's a Class II permissive change report, all of the changes are not effect to the RF performance, function and power. So the RF conducted test data directly reference the original report number GTS202211000223F01.

4.1 Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz-30MHz	3.1dB	(1)
Radiated Emission	30MHz-200MHz	3.8039dB	(1)
Radiated Emission	200MHz-1GHz	3.9679dB	(1)
Radiated Emission	1GHz-18GHz	4.29dB	(1)
Radiated Emission	18GHz-40GHz	3.30dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	3.44dB	(1)

Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.

5 General Information

5.1 General Description of EUT

Product Info:	BR30 smart light bulbs
Model No.:	81813-V2
Serial No.:	021623000094
Test sample(s) ID:	GTS202211000226-1
Sample(s) Status	Engineer sample
Operation Frequency:	2405MHz~2480MHz
Channel numbers:	16
Channel separation:	5MHz
Modulation type:	O-QPSK
Antenna Type:	PCB Antenna
Antenna gain:	-1.85dBi (Declared by manufacturer)
Power supply:	Input: AC 110-130V, 50/60Hz, 0.095A, 10W

Remark:

1. Antenna gain information provided by the customer
2. The relevant information of the sample is provided by the entrusting company, and the laboratory is not responsible for its authenticity.

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
11	2405MHz	15	2425MHz	19	2445MHz	23	2465MHz
12	2410MHz	16	2430MHz	20	2450MHz	24	2470MHz
13	2415MHz	17	2435MHz	21	2455MHz	25	2475MHz
14	2420MHz	18	2440MHz	22	2460MHz	26	2480MHz

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Channel	Frequency
The lowest channel	2405MHz
The middle channel	2440MHz
The Highest channel	2480MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
-------------------	---

5.3 Description of Support Units

None.

5.4 Deviation from Standards

None.

5.5 Abnormalities from Standard Conditions

None.

5.6 Test Facility

The test facility is recognized, certified, or accredited by the following organizations: • FCC—Registration No.: 381383 Designation Number: CN5029 Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. • ISED —Registration No.: 9079A CAB identifier: CN0091 The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of ISED for radio equipment testing • NVLAP (LAB CODE:600179-0) Global United Technology Services Co., Ltd., is accredited by the National Voluntary Laboratory Accreditation Program (NVLAP).

5.7 Test Location

All tests were performed at:
Global United Technology Services Co., Ltd. Address: No. 123-128, Tower A, Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102 Tel: 0755-27798480 Fax: 0755-27798960

5.8 Additional instructions

Test Software	Special test command provided by manufacturer
Power level setup	Default

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	June 23, 2021	June 22, 2024
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	April 14, 2023	April 13, 2024
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9168	GTS640	March 19, 2023	March 18, 2025
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	BBHA 9120 D	GTS208	April 17, 2023	April 16, 2025
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	GTS575	April 14, 2023	April 13, 2024
8	Loop Antenna	ZHINAN	ZN30900A	GTS534	Nov. 13, 2023	Nov.12, 2024
9	Broadband Preamplifier	SCHWARZBECK	BBV9718	GTS535	April 14, 2023	April 13, 2024
10	Amplifier(1GHz-26.5GHz)	HP	8449B	GTS601	April 14, 2023	April 13, 2024
11	Horn Antenna (18-26.5GHz)	/	UG-598A/U	GTS664	Oct. 29, 2023	Oct. 28, 2024
12	Horn Antenna (26.5-40GHz)	A.H Systems	SAS-573	GTS665	Oct. 29, 2023	Oct. 28, 2024
13	FSV·Signal Analyzer (10Hz-40GHz)	Keysight	FSV-40-N	GTS666	March 12, 2024	March 11, 2025
14	Amplifier	/	LNA-1000-30S	GTS650	April 14, 2023	April 13, 2024
15	CDNE M2+M3-16A	HCT	30MHz-300MHz	GTS692	Nov. 08, 2023	Nov.07, 2024
16	Wideband Amplifier	/	WDA-01004000-15P35	GTS602	April 14, 2023	April 13, 2024
17	Thermo meter	JINCHUANG	GSP-8A	GTS643	April 19, 2023	April 18, 2024
18	RE cable 1	GTS	N/A	GTS675	July 31. 2023	July 30. 2024
19	RE cable 2	GTS	N/A	GTS676	July 31. 2023	July 30. 2024
20	RE cable 3	GTS	N/A	GTS677	July 31. 2023	July 30. 2024
21	RE cable 4	GTS	N/A	GTS678	July 31. 2023	July 30. 2024
22	RE cable 5	GTS	N/A	GTS679	July 31. 2023	July 30. 2024
23	RE cable 6	GTS	N/A	GTS680	July 31. 2023	July 30. 2024
24	RE cable 7	GTS	N/A	GTS681	July 31. 2023	July 30. 2024
25	RE cable 8	GTS	N/A	GTS682	July 31. 2023	July 30. 2024

Conducted Emission						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	July 12, 2022	July 11, 2027
2	EMI Test Receiver	R&S	ESCI 7	GTS552	April 14, 2023	April 13, 2024
3	LISN	ROHDE & SCHWARZ	ENV216	GTS226	April 14, 2023	April 13, 2024
4	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
5	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
6	Thermo meter	JINCHUANG	GSP-8A	GTS642	April 19, 2023	April 18, 2024
7	Absorbing clamp	Elektronik-Feinmechanik	MDS21	GTS229	April 14, 2023	April 13, 2024
8	ISN	SCHWARZBECK	NTFM 8158	GTS565	April 14, 2023	April 13, 2024
9	High voltage probe	SCHWARZBECK	TK9420	GTS537	April 14, 2023	April 13, 2024
10	Antenna end assembly	Weinschel	1870A	GTS560	April 14, 2023	April 13, 2024

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	KUMAO	SF132	GTS647	April 19, 2023	April 18, 2024

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.	
15.247(c) (1)(i) requirement: (i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.	
EUT Antenna:	
The antenna is PCB antenna, reference to the appendix II for details.	


7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207					
Test Method:	ANSI C63.10:2013					
Test Frequency Range:	150KHz to 30MHz					
Class / Severity:	Class B					
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto					
Limit:	Frequency range (MHz)		Limit (dBuV)			
			Quasi-peak		Average	
	0.15-0.5		66 to 56*		56 to 46*	
	0.5-5		56		46	
	5-30		60		50	
* Decreases with the logarithm of the frequency.						
Test setup:	Reference Plane 40cm LISN AUX Equipment 40cm E.U.T 80cm 40cm LISN Filter AC power EMI Receiver Test table/Insulation plane Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data


Pre-scan all test modes, found worst case at 2480MHz, and so only show the test result of 2480MHz

Test mode:	Transmitting mode	Phase Polarity:	Line
------------	-------------------	-----------------	------



Freq	Reading	LISN/ISN	Cable	Level	Limit	Over	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	50.76	10.13	0.01	60.90	65.91	-5.01	QP
0.15	36.15	10.13	0.01	46.29	55.91	-9.62	Average
0.32	32.03	9.98	0.01	42.02	59.80	-17.78	QP
0.32	23.39	9.98	0.01	33.38	49.80	-16.42	Average
0.50	26.45	9.96	0.01	36.42	56.00	-19.58	QP
0.50	17.88	9.96	0.01	27.85	46.00	-18.15	Average
0.63	31.02	9.96	0.02	41.00	56.00	-15.00	QP
0.63	20.54	9.96	0.02	30.52	46.00	-15.48	Average
1.11	28.54	9.94	0.03	38.51	56.00	-17.49	QP
1.11	19.37	9.94	0.03	29.34	46.00	-16.66	Average
3.94	9.04	9.75	0.06	18.85	56.00	-37.15	QP
3.94	-0.28	9.75	0.06	9.53	46.00	-36.47	Average

Test mode:	Transmitting mode	Phase Polarity:	Neutral
------------	-------------------	-----------------	---------




Freq	Reading	LISN/ISN	Cable		Limit	Over	
	level	factor	loss	Level	level	limit	Remark
MHz	dBuV	dB	dB	dBuV	dBuV	dB	
0.15	50.44	10.15	0.01	60.60	65.82	-5.22	QP
0.15	36.04	10.15	0.01	46.20	55.82	-9.62	Average
0.24	35.97	10.02	0.01	46.00	62.22	-16.22	QP
0.24	25.32	10.02	0.01	35.35	52.22	-16.87	Average
0.37	26.67	9.96	0.01	36.64	58.47	-21.83	QP
0.37	18.53	9.96	0.01	28.50	48.47	-19.97	Average
0.63	30.55	9.96	0.02	40.53	56.00	-15.47	QP
0.63	20.19	9.96	0.02	30.17	46.00	-15.83	Average
0.95	29.69	9.96	0.03	39.68	56.00	-16.32	QP
0.95	20.64	9.96	0.03	30.63	46.00	-15.37	Average
2.87	7.97	9.53	0.05	17.55	56.00	-38.45	QP
2.87	0.68	9.53	0.05	10.26	46.00	-35.74	Average



Notes:

1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level = Receiver Read level + LISN Factor + Cable Loss
4. If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.

7.3 Spurious Emission in Non-restricted & restricted Bands

7.3.1 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209				
Test Method:	ANSI C63.10:2013				
Test Frequency Range:	9kHz to 25GHz				
Test site:	Measurement Distance: 3m				
Receiver setup:	Frequency	Detector	RBW	VBW	Value
	9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
	150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
	30MHz-1GHz	Quasi-peak	120KHz	300KHz	Quasi-peak
	Above 1GHz	Peak	1MHz	3MHz	Peak
		Peak	1MHz	10Hz	Average
Note: For Duty cycle ≥ 98%, average detector set as above For Duty cycle < 98%, average detector set as below: VBW ≥ 1 / T					
Limit:	Frequency	Limit (uV/m)	Value	Measurement Distance	
	0.009MHz-0.490MHz	2400/F(KHz)	QP/PK/AV	300m	
	0.490MHz-1.705MHz	24000/F(KHz)	QP	30m	
	1.705MHz-30MHz	30	QP	30m	
	30MHz-88MHz	100	QP	3m	
	88MHz-216MHz	150	QP		
	216MHz-960MHz	200	QP		
	960MHz-1GHz	500	QP		
	Above 1GHz	500	Average		
		5000	Peak		
Test setup:	For radiated emissions from 9kHz to 30MHz				
					

	For radiated emissions from 30MHz to 1GHz  For radiated emissions above 1GHz 
Test Procedure:	1. The EUT was placed on the top of a rotating table (0.8m for below 1G and 1.5m for above 1G) above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or

	average method as specified and then reported in a data sheet.					
Test Instruments:	Refer to section 6.0 for details					
Test mode:	Refer to section 5.2 for details					
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1012mbar
Test voltage:	AC 120V, 60Hz					
Test results:	Pass					

Measurement data:

Remark:


Pre-scan all kind of the place mode (X-axis, Y-axis, Z-axis), and found the Y-axis which it is worse case.

■ 9kHz~30MHz

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.


■ Below 1GHz

Pre-scan all test modes, found worst case at 2480MHz, and so only show the test result of 2480MHz
Horizontal:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamp factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
193.095	50.22	9.57	1.81	30.00	31.60	43.50	-11.90	QP
274.194	41.16	12.45	2.24	30.00	25.85	46.00	-20.15	QP
374.623	37.92	14.95	2.74	30.00	25.61	46.00	-20.39	QP
470.523	38.18	17.08	3.18	30.00	28.44	46.00	-17.56	QP
645.120	29.03	20.01	3.89	30.00	22.93	46.00	-23.07	QP
875.247	24.63	23.62	4.76	30.00	23.01	46.00	-22.99	QP

Vertical:



Freq MHz	Reading level dBuV	Antenna factor dB/m	Cable loss dB	Preamplifier factor dB	level dBuV/m	Limit level dBuV/m	Over limit dB	Remark
125.007	49.98	11.52	1.40	30.00	32.90	43.50	-10.60	QP
190.405	45.23	9.71	1.79	30.00	26.73	43.50	-16.77	QP
270.375	46.62	12.14	2.22	30.00	30.98	46.00	-15.02	QP
374.623	47.08	14.95	2.74	30.00	34.77	46.00	-11.23	QP
416.179	47.14	16.04	2.93	30.00	36.11	46.00	-9.89	QP
465.599	44.54	16.99	3.16	30.00	34.69	46.00	-11.31	QP

■ Above 1GHz

■ Unwanted Emissions in Non-restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4810.00	35.88	31.08	7.30	38.36	35.90	74.00	-38.10	Vertical
7215.00	30.88	35.95	9.44	38.97	37.30	74.00	-36.70	Vertical
9620.00	30.63	37.93	10.01	39.69	38.88	74.00	-35.12	Vertical
4810.00	39.87	31.08	7.30	38.36	39.89	74.00	-34.11	Horizontal
7215.00	32.51	35.95	9.44	38.97	38.93	74.00	-35.07	Horizontal
9620.00	29.91	37.93	10.01	39.69	38.16	74.00	-35.84	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4810.00	24.96	31.08	7.30	38.36	24.98	54.00	-29.02	Vertical
7215.00	19.73	35.95	9.44	38.97	26.15	54.00	-27.85	Vertical
9620.00	18.90	37.93	10.01	39.69	27.15	54.00	-26.85	Vertical
4810.00	29.03	31.08	7.30	38.36	29.05	54.00	-24.95	Horizontal
7215.00	21.81	35.95	9.44	38.97	28.23	54.00	-25.77	Horizontal
9620.00	18.51	37.93	10.01	39.69	26.76	54.00	-27.24	Horizontal

Test channel:				Middle channel				
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	36.34	31.26	7.04	38.38	36.26	74.00	-37.74	Vertical
7320.00	31.19	36.14	9.18	39.00	37.51	74.00	-36.49	Vertical
9760.00	30.90	38.06	10.27	39.73	39.50	74.00	-34.50	Vertical
4880.00	40.43	31.26	7.04	38.38	40.35	74.00	-33.65	Horizontal
7320.00	32.86	36.14	9.18	39.00	39.18	74.00	-34.82	Horizontal
9760.00	30.23	38.06	10.27	39.73	38.83	74.00	-35.17	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	25.35	31.26	7.04	38.38	25.27	54.00	-28.73	Vertical
7320.00	19.99	36.14	9.18	39.00	26.31	54.00	-27.69	Vertical
9760.00	19.13	38.06	10.27	39.73	27.73	54.00	-26.27	Vertical
4880.00	29.47	31.26	7.04	38.38	29.39	54.00	-24.61	Horizontal
7320.00	22.10	36.14	9.18	39.00	28.42	54.00	-25.58	Horizontal
9760.00	18.78	38.06	10.27	39.73	27.38	54.00	-26.62	Horizontal

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	36.18	31.46	6.75	38.39	36.00	74.00	-38.00	Vertical
7440.00	31.08	36.35	9.00	39.03	37.40	74.00	-36.60	Vertical
9920.00	30.80	38.20	10.12	39.77	39.35	74.00	-34.65	Vertical
4960.00	40.23	31.46	6.75	38.39	40.05	74.00	-33.95	Horizontal
7440.00	32.74	36.35	9.00	39.03	39.06	74.00	-34.94	Horizontal
9920.00	30.12	38.20	10.12	39.77	38.67	74.00	-35.33	Horizontal

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	25.26	31.46	6.75	38.39	25.08	54.00	-28.92	Vertical
7440.00	19.93	36.35	9.00	39.03	26.25	54.00	-27.75	Vertical
9920.00	19.07	38.20	10.12	39.77	27.62	54.00	-26.38	Vertical
4960.00	29.37	31.46	6.75	38.39	29.19	54.00	-24.81	Horizontal
7440.00	22.03	36.35	9.00	39.03	28.35	54.00	-25.65	Horizontal
9920.00	18.72	38.20	10.12	39.77	27.27	54.00	-26.73	Horizontal

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

■ Unwanted Emissions in Restricted Frequency Bands

Test channel:	Lowest channel
---------------	----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	46.73	27.17	4.65	38.52	40.03	74.00	-33.97	Horizontal
2390.00	51.07	27.27	4.60	38.56	44.38	74.00	-29.62	Horizontal
2310.00	47.64	27.17	4.65	38.52	40.94	74.00	-33.06	Vertical
2390.00	52.52	27.27	4.60	38.56	45.83	74.00	-28.17	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310.00	36.41	27.17	4.65	38.52	29.71	54.00	-24.29	Horizontal
2390.00	37.87	27.27	4.60	38.56	31.18	54.00	-22.82	Horizontal
2310.00	36.63	27.17	4.65	38.52	29.93	54.00	-24.07	Vertical
2390.00	38.89	27.27	4.60	38.56	32.20	54.00	-21.80	Vertical

Test channel:	Highest channel
---------------	-----------------

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.29	27.38	4.52	38.59	42.60	74.00	-31.40	Horizontal
2500.00	47.73	27.40	4.49	38.60	41.02	74.00	-32.98	Horizontal
2483.50	50.78	27.38	4.52	38.59	44.09	74.00	-29.91	Vertical
2500.00	49.10	27.40	4.49	38.60	42.39	74.00	-31.61	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	37.28	27.38	4.52	38.59	30.59	54.00	-23.41	Horizontal
2500.00	36.73	27.40	4.49	38.60	30.02	54.00	-23.98	Horizontal
2483.50	36.92	27.38	4.52	38.59	30.23	54.00	-23.77	Vertical
2500.00	36.98	27.40	4.49	38.60	30.27	54.00	-23.73	Vertical

Remarks:

1. Final Level = Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor
2. The emission levels of other frequencies are very lower than the limit and not show in test report.

8 Test Setup Photo

Reference to the **appendix I** for details.

9 EUT Constructional Details

Reference to the **appendix II** for details.

-----End-----