FCC Report (WIFI)

Applicant:	Shenzhen Brisk Technology Co.,Ltd.
Address of Applicant:	3, 4/F, 1st Building, Anhaorui Industrial Area, Jian’an Road, Tangwei Village, Fuyong Town, Shenzhen, Guangdong, China
Manufacturer/Factory:	Shenzhen Brisk Technology Co.,Ltd.
Address of Manufacturer/Factory:	3, 4/F, 1st Building, Anhaorui Industrial Area, Jian’an Road, Tangwei Village, Fuyong Town, Shenzhen, Guangdong, China

Equipment Under Test (EUT)

Product Name:	Aroma Diffuser
Model No.:	BK-EG-FD28
Trade mark:	BRISK
FCC ID:	2APL5-BK-EG-FD28
Applicable standards:	FCC CFR Title 47 Part 15 Subpart C Section 15.247
Date of sample receipt:	March 2, 2018
Date of Test:	March 2, 2018- April 19, 2018
Date of report issued:	April 19, 2018
Test Result :	PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:

Robinson Lo
Laboratory Manager

This results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

2 Version

Version No.	Date	Description
00	*April 19, 2018*	*Original*

Prepared By:	***Project Engineer***	***Date:***	*April 19, 2018*
Check By:	***Reviewer***	***Date:***	*April 19, 2018*

3 Contents

Page

1 COVER PAGE 1

2 VERSION 2

3 CONTENTS 3

4 TEST SUMMARY 4

5 GENERAL INFORMATION 5

5.1 GENERAL DESCRIPTION OF EUT 5
5.2 TEST MODE 6
5.3 DESCRIPTION OF SUPPORT UNITS 6
5.4 TEST FACILITY 7
5.5 TEST LOCATION 7
5.6 ADDITIONAL INSTRUCTIONS 8

6 TEST INSTRUMENTS LIST 9

7 TEST RESULTS AND MEASUREMENT DATA 10

7.1 ANTENNA REQUIREMENT 10
7.2 CONDUCTED EMISSIONS 11
7.3 CONDUCTED PEAK OUTPUT POWER 16
7.4 CHANNEL BANDWIDTH 17
7.5 POWER SPECTRAL DENSITY 20
7.6 BAND EDGES 23
7.6.1 Conducted Emission Method 23
7.6.2 Radiated Emission Method 26
7.7 SPURIOUS EMISSION 30
7.7.1 Conducted Emission Method 30
7.7.2 Radiated Emission Method 34

8 TEST SETUP PHOTO 49

9 EUT CONSTRUCTIONAL DETAILS 52

4 Test Summary

Test Item	Section in CFR 47	Result
Antenna requirement	15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	15.207	Pass
Conducted Peak Output Power	15.247 (b)(3)	Pass
Channel Bandwidth	15.247 (a)(2)	Pass
Power Spectral Density	15.247 (e)	Pass
Band Edge	15.247(d)	Pass
Spurious Emission	15.205/15.209	Pass

Pass: The EUT complies with the essential requirements in the standard.

Remark: Test according to ANSI C63.4:2014 and ANSI C63.10:2013.

Measurement Uncertainty

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	9kHz ~ 30MHz	± 4.34dB	(1)
Radiated Emission	30MHz ~ 1000MHz	± 4.24dB	(1)
Radiated Emission	1GHz ~ 26.5GHz	± 4.68dB	(1)
AC Power Line Conducted Emission	0.15MHz ~ 30MHz	± 3.45dB	(1)
Note (1): The measurement uncertainty is for coverage factor of k=2 and a level of confidence of 95%.			

5 General Information

5.1 General Description of EUT

Product Name:	Aroma Diffuser
Model No.:	BK-EG-FD28
Test Model No:	BK-EG-FD28
Remark: All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are color and model name for commercial purpose.	
Sample(s) Status:	Engineer sample
Quantity of tested samples	1
Serial No.:	N/A
Tested Sample(s) ID:	N/A
Hardware Version:	TY WIFI MAIN V1.31MEC PCB
Software Version:	A53A
Operation Frequency:	802.11b/802.11g/802.11n(HT20): 2412MHz~2462MHz (SISO)
Channel numbers:	802.11b/802.11g /802.11n(HT20): 11
Channel separation:	5MHz
Modulation technology:	802.11b: Direct Sequence Spread Spectrum (DSSS) 802.11g/802.11n(HT20): Orthogonal Frequency Division Multiplexing (OFDM)
Antenna Type:	Internal Antenna
Antenna gain:	3.23dBi
Power supply:	DC 24V from adapter input AC 120V, 60Hz

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz		

Note:

In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	**Frequency (MHz)**
	802.11b/802.11g/802.11n(HT20)
Lowest channel	2412MHz
Middle channel	2437MHz
Highest channel	2462MHz

5.2 Test mode

Transmitting mode	Keep the EUT in continuously transmitting mode
Remark: During the test, the dutycycle >98%, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

We have verified the construction and function in typical operation. All the test modes were carried out with the EUT in transmitting operation, which was shown in this test report and defined as follows:

Per-scan all kind of data rate in lowest channel, and found the follow list which it was worst case.

Mode	802.11b	802.11g	802.11n(HT20)
Data rate	1Mbps	6Mbps	6.5Mbps

5.3 Description of Support Units

None.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 381383**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fuly described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 381383, January 08, 2018.

● **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, August 15, 2016.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: No. 301-309, 3/F., Jinyuan Business Building, No.2, Laodong Industrial Zone, Xixiang Road, Baoan District, Shenzhen, Guangdong, China 518102
Tel: 0755-27798480
Fax: 0755-27798960

5.6 Additional instructions

Software (Used for test) from client

Mode	Special software is used. The software provided by client to enable the EUT under transmission condition continuously at specific channel frequencies individually.		
Power level setup in software			
Test Software Name	QRCT—External Licensed		
Test Software Version	2.5.8		
Support Units (Software installation media)	Description	Manufacturer	Model
	LCD TV	PHILIPS	AU1A1212002906
Mode	Channel	Frequency (MHz)	Soft Set
802.11b/g/n(HT20)	CH1	2412	TX level is built-in set parameters and cannot be changed and selected.
	CH6	2437	
	CH11	2462	

Run Software



6 Test Instruments list

Radiated Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	July 03 2015	July 02 2020
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	Spectrum Analyzer	Agilent	E4440A	GTS533	June 28 2017	June 27 2018
4	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	June 28 2017	June 27 2018
5	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	June 28 2017	June 27 2018
6	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 28 2017	June 27 2018
7	Horn Antenna	ETS-LINDGREN	3160	GTS217	June 28 2017	June 27 2018
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial Cable	GTS	N/A	GTS213	June 28 2017	June 27 2018
10	Coaxial Cable	GTS	N/A	GTS211	June 28 2017	June 27 2018
11	Coaxial cable	GTS	N/A	GTS210	June 28 2017	June 27 2018
12	Coaxial Cable	GTS	N/A	GTS212	June 28 2017	June 27 2018
13	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	June 28 2017	June 27 2018
14	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	June 28 2017	June 27 2018
15	Amplifier (18-26GHz)	Rohde & Schwarz	AFS33-18002 650-30-8P-44	GTS218	June 28 2017	June 27 2018
16	Band filter	Amindeon	82346	GTS219	June 28 2017	June 27 2018
17	Power Meter	Anritsu	ML2495A	GTS540	June 28 2017	June 27 2018
18	Power Sensor	Anritsu	MA2411B	GTS541	June 28 2017	June 27 2018

Conducted Emission:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Shielding Room	ZhongYu Electron	7.3(L)x3.1(W)x2.9(H)	GTS252	May16 2014	May15 2019
2	EMI Test Receiver	R&S	ESCI 7	GTS552	June 28 2017	June 27 2018
3	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	June 28 2017	June 27 2018
4	Artificial Mains Network	SCHWARZBECK MESS	NSLK8127	GTS226	June 28 2017	June 27 2018
5	Coaxial Cable	GTS	N/A	GTS227	N/A	N/A
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Thermo meter	KTJ	TA328	GTS233	June 28 2017	June 27 2018

General used equipment:						
Item	**Test Equipment**	**Manufacturer**	**Model No.**	**Inventory No.**	**Cal.Date (mm-dd-yy)**	**Cal.Due date (mm-dd-yy)**
1	Barometer	ChangChun	DYM3	GTS257	June 28 2017	June 27 2018

7 Test results and Measurement Data

7.1 Antenna requirement

Standard requirement:	FCC Part15 C Section 15.203 /247(c)

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

15.247(c) (1)(i) requirement:

(i) Systems operating in the 2400-2483.5 MHz band that is used exclusively for fixed. Point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum conducted output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

E.U.T Antenna:

The antenna is Internal antenna, the best case gain of the antenna is 3.23dBi



7.2 Conducted Emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Class / Severity:	Class B
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto
Limit:	<table><tr><td rowspan="2">Frequency range (MHz)</td><td colspan="2">Limit (dBuV)</td></tr><tr><td>Quasi-peak</td><td>Average</td></tr><tr><td>0.15-0.5</td><td>66 to 56*</td><td>56 to 46*</td></tr><tr><td>0.5-5</td><td>56</td><td>46</td></tr><tr><td>5-30</td><td>60</td><td>50</td></tr></table> * Decreases with the logarithm of the frequency.
Test setup:	 *Remark:* *E.U.T: Equipment Under Test* *LISN: Line Impedence Stabilization Network* *Test table height=0.8m*
Test procedure:	1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10:2013 on conducted measurement.
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Site LAB	Phase:	*L1*	Temperature:	24.9
Limit: FCC Part 15 CLASS B QP	Power:	AC 120V/60Hz	Humidity:	47 %
EUT: Aroma Diffuser				
M/N: BK-EG-FD28				
Mode: wifi mode				
Note: SK02T-2400060U				
Engineer Signature: Lucas				

Conducted Emission Measurement

File :BK-EG-FD28 Data :#1 Date: 2018-3-20 Time: 14:41:21



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1740	42.01	9.73	51.74	64.77	-13.03	QP	
2		0.1740	22.86	9.73	32.59	54.77	-22.18	AVG	
3		0.1860	41.70	9.74	51.44	64.21	-12.77	QP	
4		0.1860	22.26	9.74	32.00	54.21	-22.21	AVG	
5		0.6120	28.02	9.79	37.81	56.00	-18.19	peak	
6	*	2.5170	34.88	9.98	44.86	56.00	-11.14	QP	
7		2.5170	24.16	9.98	34.14	46.00	-11.86	AVG	
8		5.0310	33.63	10.19	43.82	60.00	-16.18	peak	
9		10.0590	29.92	10.35	40.27	60.00	-19.73	peak	

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Site LAB		Phase:	*N*	Temperature:	24.9
Limit: FCC Part 15 CLASS B QP		Power:	AC 120V/60Hz	Humidity:	47 %
EUT: Aroma Diffuser					
M/N: BK-EG-FD28					
Mode: wifi mode					
Note: SK02T-2400060U					
Engineer Signature: Lucas					

Conducted Emission Measurement

File :BK-EG-FD28 Data :#2 Date: 2018-3-20 Time: 14:44:53



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1800	42.31	9.74	52.05	64.49	-12.44	QP	
2		0.1800	23.58	9.74	33.32	54.49	-21.17	AVG	
3	*	2.5200	40.74	9.98	50.72	56.00	-5.28	QP	
4		2.5200	30.05	9.98	40.03	46.00	-5.97	AVG	
5		5.0370	36.61	10.19	46.80	60.00	-13.20	QP	
6		5.0370	26.79	10.19	36.98	50.00	-13.02	AVG	
7		7.5540	30.28	10.28	40.56	60.00	-19.44	peak	
8		10.0680	34.30	10.35	44.65	60.00	-15.35	peak	
9		25.1790	26.46	10.81	37.27	60.00	-22.73	peak	

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Site LAB		Phase:	*L1*	Temperature:	24.9
Limit: FCC Part 15 CLASS B QP		Power:	AC 120V/60Hz	Humidity:	47 %
EUT: Aroma Diffuser					
M/N: BK-EG-FD28					
Mode: wifi mode					
Note: HNBG240060WU					
Engineer Signature:	Lucas				

Conducted Emission Measurement

File :BK-EG-FD28 Data :#11 Date: 2018-3-20 Time: 15:05:12



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1500	35.94	9.73	45.67	66.00	-20.33	peak	
2		0.4410	25.97	9.78	35.75	57.04	-21.29	peak	
3	*	2.5170	39.82	9.98	49.80	56.00	-6.20	QP	
4		2.5170	26.79	9.98	36.77	46.00	-9.23	AVG	
5		5.0340	35.63	10.19	45.82	60.00	-14.18	QP	
6		5.0340	24.08	10.19	34.27	50.00	-15.73	AVG	
7		7.5540	31.26	10.28	41.54	60.00	-18.46	peak	
8		10.0770	35.82	10.35	46.17	60.00	-13.83	peak	

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

Site LAB		Phase:	*N*	Temperature:	24.9
Limit: FCC Part 15 CLASS B QP		Power:	AC 120V/60Hz	Humidity:	47 %
EUT: Aroma Diffuser					
M/N: BK-EG-FD28					
Mode: wifi mode					
Note: HNBG240060WU					
Engineer Signature:	Lucas				

Conducted Emission Measurement

File :BK-EG-FD28 Data :#12 Date: 2018-3-20 Time: 15:08:16



No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Margin		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	2.5200	41.47	9.98	51.45	56.00	-4.55	QP	
2		2.5200	30.73	9.98	40.71	46.00	-5.29	AVG	
3		5.0370	39.00	10.19	49.19	60.00	-10.81	peak	
4		7.5510	33.41	10.28	43.69	60.00	-16.31	peak	
5		10.0740	36.65	10.35	47.00	60.00	-13.00	peak	
6		15.1110	26.24	10.40	36.64	60.00	-23.36	peak	
7		25.1850	28.46	10.81	39.27	60.00	-20.73	peak	

*:Maximum data x:Over limit !:over margin

Note: Measurement=Reading Level+Correc Factor. Factor=(LISN or ISN or PLC or Current Probe)Factor+Cable

*Notes:*An initial pre-scan was performed on the line and neutral lines with peak detector.

1. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
2. Final Level =Receiver Read level + LISN Factor + Cable Loss
3. *If the average limit is met when using a quasi-peak detector receiver, the EUT shall be deemed to meet both limits and measurement with the average detector receiver is unnecessary.*

7.3 Conducted Peak Output Power

Test Requirement:	FCC Part15 C Section 15.247 (b)(3)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	30dBm
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

ANT0:

Test CH	Peak Output Power (dBm)			Limit(dBm)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	12.20	14.64	14.64	30.00	Pass
Middle	11.87	14.98	14.87		
Highest	11.65	13.71	13.66		

7.4 Channel Bandwidth

Test Requirement:	FCC Part15 C Section 15.247 (a)(2)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	>500KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Channel Bandwidth (MHz)			Limit(KHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	7.612	16.42	17.63	>500	Pass
Middle	7.169	16.40	17.61		
Highest	7.387	16.51	17.82		

Test plot as follows:

802.11b	802.11g





Lowest channel





Middle channel





Highest channel

802.11n(HT20)	



Lowest channel



Middle channel



Highest channel

7.5 Power Spectral Density

Test Requirement:	FCC Part15 C Section 15.247 (e)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	8dBm/3KHz
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement Data

Test CH	Power Spectral Density (dBm)			Limit(dBm/3kHz)	Result
	802.11b	802.11g	802.11n(HT20)		
Lowest	-9.883	-13.332	-13.244	8.00	Pass
Middle	-8.879	-11.693	-12.024		
Highest	-7.709	-11.477	-12.523		

Test plot as follows:

802.11b	802.11g
	

Lowest channel

	

Middle channel

	

Highest channel

802.11n(HT20)	



Lowest channel



Middle channel



Highest channel

7.6 Band edges

7.6.1 Conducted Emission Method

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	ANSI C63.10:2013 and KDB558074 D01 DTS Meas Guidance V04
Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.
Test setup:	
Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Test plot as follows:

Test mode: 802.11b



Lowest channel



Highest channel

Test mode: 802.11g



Lowest channel



Highest channel

Test mode: 802.11n(HT20)



Lowest channel



Highest channel

7.6.2 Radiated Emission Method

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10:2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	RMS	1MHz	3MHz	Average

Limit:

Frequency	Limit (dBuV/m @3m)	Value
Above 1GHz	54.00	Average
	74.00	Peak

Test setup:



Test Procedure:

1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
7. The radiation measurements are performed in X, Y, Z axis positioning. And found the Y axis positioning which it is worse case, only the test worst case mode is recorded in the report.

Test Instruments:	Refer to section 6.0 for details
Test mode:	Refer to section 5.2 for details
Test results:	Pass

Measurement data:

Remark: The pre-test were performed on lowest, middle and highest frequencies, only the worst case's (lowest and highest frequencies) data was showed.

Test mode:	802.11b	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	46.02	27.59	5.38	34.01	44.98	74	-29.02	Horizontal
2400.00	51.78	27.58	5.39	34.01	50.74	74	-23.26	Horizontal
2390.00	46.55	27.59	5.38	34.01	45.51	74	-28.49	Vertical
2400.00	50.71	27.58	5.39	34.01	49.67	74	-24.33	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.66	27.59	5.38	34.01	34.62	54	-19.38	Horizontal
2400.00	37.41	27.58	5.39	34.01	36.37	54	-17.63	Horizontal
2390.00	37.01	27.59	5.38	34.01	35.97	54	-18.03	Vertical
2400.00	38.13	27.58	5.39	34.01	37.09	54	-16.91	Vertical

Test mode:	802.11b	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.21	27.53	5.47	33.92	47.29	74	-26.71	Horizontal
2500.00	47.23	27.55	5.49	29.93	50.34	74	-23.66	Horizontal
2483.50	49.74	27.53	5.47	33.92	48.82	74	-25.18	Vertical
2500.00	48.70	27.55	5.49	29.93	51.81	74	-22.19	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.35	27.53	5.47	33.92	38.43	54	-15.57	Horizontal
2500.00	37.21	27.55	5.49	29.93	40.32	54	-13.68	Horizontal
2483.50	40.77	27.53	5.47	33.92	39.85	54	-14.15	Vertical
2500.00	36.98	27.55	5.49	29.93	40.09	54	-13.91	Vertical

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test mode:	802.11g	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	46.27	27.59	5.38	34.01	45.23	74	-28.77	Horizontal
2400.00	51.83	27.58	5.39	34.01	50.79	74	-23.21	Horizontal
2390.00	46.83	27.59	5.38	34.01	45.79	74	-28.21	Vertical
2400.00	50.49	27.58	5.39	34.01	49.45	74	-24.55	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	36.22	27.59	5.38	34.01	35.18	54	-18.82	Horizontal
2400.00	37.45	27.58	5.39	34.01	36.41	54	-17.59	Horizontal
2390.00	36.41	27.59	5.38	34.01	35.37	54	-18.63	Vertical
2400.00	38.51	27.58	5.39	34.01	37.47	54	-16.53	Vertical

Test mode:	802.11g	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	48.66	27.53	5.47	33.92	47.74	74	-26.26	Horizontal
2500.00	47.15	27.55	5.49	29.93	50.26	74	-23.74	Horizontal
2483.50	50.19	27.53	5.47	33.92	49.27	74	-24.73	Vertical
2500.00	48.23	27.55	5.49	29.93	51.34	74	-22.66	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	38.92	27.53	5.47	33.92	38.00	54	-16.00	Horizontal
2500.00	36.44	27.55	5.49	29.93	39.55	54	-14.45	Horizontal
2483.50	40.48	27.53	5.47	33.92	39.56	54	-14.44	Vertical
2500.00	36.69	27.55	5.49	29.93	39.80	54	-14.20	Vertical

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*

Test mode:	802.11n(HT20)	Test channel:	Lowest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	46.73	27.59	5.38	34.01	45.69	74	-28.31	Horizontal
2400.00	51.83	27.58	5.39	34.01	50.79	74	-23.21	Horizontal
2390.00	46.65	27.59	5.38	34.01	45.61	74	-28.39	Vertical
2400.00	50.43	27.58	5.39	34.01	49.39	74	-24.61	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2390.00	35.60	27.59	5.38	34.01	34.56	54	-19.44	Horizontal
2400.00	37.11	27.58	5.39	34.01	36.07	54	-17.93	Horizontal
2390.00	35.88	27.59	5.38	34.01	34.84	54	-19.16	Vertical
2400.00	39.12	27.58	5.39	34.01	38.08	54	-15.92	Vertical

Test mode:	802.11n(HT20)	Test channel:	Highest

Peak value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	49.03	27.53	5.47	33.92	48.11	74	-25.89	Horizontal
2500.00	47.45	27.55	5.49	29.93	50.56	74	-23.44	Horizontal
2483.50	50.51	27.53	5.47	33.92	49.59	74	-24.41	Vertical
2500.00	48.97	27.55	5.49	29.93	52.08	74	-21.92	Vertical

Average value:

Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.50	39.16	27.53	5.47	33.92	38.24	54	-15.76	Horizontal
2500.00	36.12	27.55	5.49	29.93	39.23	54	-14.77	Horizontal
2483.50	41.13	27.53	5.47	33.92	40.21	54	-13.79	Vertical
2500.00	36.10	27.55	5.49	29.93	39.21	54	-14.79	Vertical

Remark:

1. *Final Level =Receiver Read level + Antenna Factor + Cable Loss – Preamplifier Factor*
2. *The emission levels of other frequencies are very lower than the limit and not show in test report.*