

CO-LOCATION RADIO TEST REPORT

Product : Essential Solar Security Camera

Model Name : VMC3090

Series Model : VMC2090

FCC ID : 2APLE2A

Test Regulation : FCC 47 CFR Part 15 Subpart C (Section 15.247)
FCC 47 CFR Part 15 Subpart E (Section 15.407)

Received Date : 2026/3/23

Test Date : 2026/04/01 ~ 2026/05/18

Issued Date : 2026/7/27

Applicant : Arlo Technologies Inc
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

Issued By : Underwriters Laboratories Taiwan Co., Ltd.
Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd.,
Zhudong Township, Hsinchu County, Taiwan



The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report are responsible of the test sample(s) provided by the client only and are not to be used to indicate applicability to other similar products.


Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0



Original Test Report No.: 4792221380-US-R4-V0

Underwriters Laboratories Taiwan Co., Ltd.

Telephone :+886-2-7737-3000

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Table of Contents

1. Attestation of Test Results	4
2. Summary of Test Results	5
3. Test Methodology and Reference Procedures.....	6
4. Facilities and Accreditation	6
5. Measurement Uncertainty	7
6. Equipment under Test.....	8
6.1. Description of EUT	8
6.2. Test Condition.....	9
6.3. Description of Available Antennas	10
6.4. Test Mode Applicability and Tested Channel Detail.....	11
7. Test Equipment	12
8. Description of Test Setup	14
9. Test Results	16
9.1. Conducted Out of Band Emission.....	16
9.2. Radiated Spurious Emission	18
9.3. AC Power Line Conducted Emission	29

1. Attestation of Test Results

APPLICANT: Arlo Technologies Inc
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

MANUFACTURER: Arlo Technologies Inc
5770 Fleet St, Suite 200, Carlsbad, CA 92008 USA

EUT DESCRIPTION: Essential Solar Security Camera

BRAND: Arlo

MODEL: VMC3090

SERIES MODEL: VMC2090

SAMPLE STAGE: Engineering Verification Test Sample

DATE of TESTED: 2026/04/01 ~ 2026/05/18

APPLICABLE STANDARDS	
STANDARD	Test Results
FCC 47 CFR PART 15 Subpart C (Section 15.247)	PASS
FCC 47 CFR PART 15 Subpart E (Section 15.407)	PASS

Underwriters Laboratories Taiwan Co., Ltd. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by Underwriters Laboratories Taiwan Co., Ltd. based on interpretations and/or observations of test results. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by Underwriters Laboratories Taiwan Co., Ltd. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by Underwriters Laboratories Taiwan Co., Ltd. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Prepared By:



James Chan Date : 2026/7/27
Laboratory Test Engineer

Approved and Authorized By:



Eric Lee Date : 2026/7/27
Senior Laboratory Engineer

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

2. Summary of Test Results

Summary of Test Results		
FCC Clause	Test Items	Result
15.205 / 15.209 / 15.247(d) / 15.407(b) (1/2/3/4(i/ii)/9) /15.407(b)(5)(8)	Radiated Spurious Emission	PASS
15.247(d)	Antenna Port Emission	PASS
15.207 15.407(b)(9)	AC Power Conducted Emission	PASS

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

3. Test Methodology and Reference Procedures

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2, KDB558074 D01 Meas Guidance v05r02, KDB 789033 D02 General UNII Test Procedure New Rules v02r01, KDB414788 D01 Radiated Test Site v01r01, ANSI C63.10-2020+Cor.1-2023+C63.10a-2024+Errata to C63.10a-2024.

4. Facilities and Accreditation

Test Location	Underwriters Laboratories Taiwan Co., Ltd.
Address	Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Accreditation Certificate	Underwriters Laboratories Taiwan Co., Ltd. is accredited by TAF, Laboratory Code 3398.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

5. Measurement Uncertainty

For statement of conformity, Simple acceptance (Section 3.1.4 of IEC Guide 115) was applied as decision rule for measurement in this test report.

The following uncertainties have been calculated to provide a confidence level of 95 % using a coverage factor $k=2$.

Determining compliance based on the results of the compliance measurement, not considering measurement instrumentation uncertainty.

Measurement	Frequency	Uncertainty
Conducted disturbance at mains terminals ports	150kHz ~ 30MHz	3.1 dB
RF Conducted	9 kHz - 40GHz	2.7 dB
Radiated disturbance below 30MHz	9 kHz - 30 MHz	1.9 dB
Radiated disturbance below 1 GHz	30MHz ~ 1GHz	5.8 dB
Radiated disturbance above 1 GHz	1GHz ~ 40GHz	4.9 dB

The EUT support table is constructed of high-density Expandable Polystyrene (EPS) with dimensions of $1\text{ m} \times 1.5\text{ m}$.

The Measurement Uncertainty (MU) report is prepared in accordance with CISPR 16-4-2:2011-06; the potential impact of the setup table material has been evaluated and included as a component of the overall uncertainty value.

6. Equipment under Test

6.1. Description of EUT

Product	Essential Solar Security Camera
Brand Name	Arlo
Model Name	VMC3090
Series Model	VMC2090
Normal Voltage	5Vdc from Host 3.62Vdc from a battery

Operating Frequency	BT LE: 2402MHz ~ 2480MHz 2.4G WiFi: 2412MHz ~ 2462MHz 5G WiFi: 5180 ~ 5240MHz, 5260 ~ 5320MHz, 5500 ~ 5720MHz, 5745 ~ 5825MHz
Sample ID	Conducted Test:9586524 Radiated Test:9586525

Note:

1. The models difference table as below:

Model	Difference
VMC3090	2K 2560 x 1440 video resolution
VMC2090	FHD 1920 x 1080 video resolution

All models are electrically identical (Include: circuitry, components, layout, antenna type and gain).

* Based on the information regarding the differences among the models, and after evaluation, Model VMC3090 was selected as the representative model for all final testing.

2. The EUT contains following accessory devices:

Product	Brand	Model	Description
USB Cable	Nienyi	310-50024-01	USB TYPE A-C, 1m
Wall Mount	Arlo	Arlo	SHORT MOUNT, 50x73mm

3. EUT is equipped with a built-in rechargeable battery with the following table:

Brand	Model	Description
Arlo	A-24	LI-ION, 3.62Vdc, 54.408Wh

4. The above EUT information is declared by manufacturer and for more detailed features description, please refer the manufacturer's or user's manual, the laboratory shall not be held responsible.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

6.2. Test Condition

Test Item	Test Site No.	Environmental	Input Power	Test Date	Tested by
Antenna Port Conducted Measurement	SR4	22~26°C/ 60~66%RH	5Vdc	2026/04/21~ 2026/05/06	WaterNil Guan/ Jubo Shen
Radiated Spurious Emission	966-2	22~26°C/ 62~68%RH	5Vdc	2026/04/01~ 2026/05/06	WaterNil Guan/ Jubo Shen
AC power Line Conducted Emission	SR1	24°C/ 59%RH	120Vac/ 60Hz	2026/05/18	Jubo Shen

FCC Test Firm Registration Number: 498077

Sample Calculation:

Antenna Port Conducted Measurement:

- Where relevant, the follow sample calculation is provided:
Result Value (dBm) = Reading Value (dBm) + Attenuator Factor (dB) + Cable Loss (dB).
Example: Result Value (10dBm) = Reading Value (-2dBm) + Attenuator Factor (10dB) + Cable Loss(2dB).
*Test plot only shown the “Result Value”.

Radiated Spurious Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV/m) = Reading Value (dBuV) + Correction Factor (dB/m).
Correction Factor (dB/m) = Antenna Factor (dB/m) + Cable Loss (dB) - Preamp Factor (dB).
Example: Result Value (34.5dBuV/m) = Reading Value (40.1dBuV) + Antenna Factor (18.7dB/m) + Cable Loss (4.2dB) - Preamp Factor (28.5dB).

AC power Line Conducted Emission:

- Where relevant, the follow sample calculation is provided:
Result Value (dBuV) = Reading Value (dBuV) + Correction Factor (dB).
Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).
Example: Result Value (53.7dBuV) = Reading Value (35.1dBuV) + Insertion loss(18.1dB) + Cable loss(0.5dB).

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan
Telephone : +886-2-7737-3000
Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

6.3. Description of Available Antennas

Ant. No.	Transmitter Circuit	Frequency Range	Brand Name	Model Name	Maximum Gain (dBi)	Ant. Type	Connector Type
1	Chain0	2.4~2.4835GHz 5.15~5.85GHz	Arlo	2APLE2A	2.4GHz: 2.6 5GHz: 4.1	Dipole	i-pex(MHF)

Note: The above antenna information was provided from customer and for more detailed features description, please refer the manufacturer's specification or user's manual, the laboratory shall not be held responsible.

6.4. Test Mode Applicability and Tested Channel Detail

Simultaneously transmission condition:

Condition	Technology	
1	BTLE	WLAN (2.4GHz)
2	BTLE	WLAN (5GHz)

Note: The emission of the simultaneous operation has been evaluated and no non-compliance was found.

7. Test Equipment

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Radiated Spurious Emission					
Spectrum Analyzer	Keysight	N9010A	MY56070818	2026/2/9	2027/2/8
EMI Test Receiver	Rohde & Schwarz	ESR7	101754	2025/12/9	2026/12/8
Loop Antenna	ETS lindgren	6502	00213440	2025/11/14	2026/11/13
Trilog-Broadband Antenna with 5dB Attenuator	Schwarzbeck & EMCI	VULB 9168 & N-6-05	774 & AT-N0538	2025/12/23	2026/12/22
Horn Antenna (1-18 GHz)	Schwarzbeck	BBHA 9120 D	01690	2025/11/18	2026/11/17
Horn Antenna (18-40 GHz)	Schwarzbeck	BBHA 9170	781	2025/12/2	2026/12/1
Preamplifier (30-1000 MHz)	EMCI	EMC330E	980405	2025/5/12 2026/4/28	2026/5/11 2027/4/27
Preamplifier (1-18 GHz)	EMCI	EMC051835BE	980406	2025/12/26	2026/12/25
Preamplifier (18-40GHz)	EMCI	EMC184040SEE	980426	2026/3/24	2027/3/23
Cables (9k-18 GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-4 & 170425-2	2025/11/21	2026/11/20
Cables (18-40GHz)	Hanyitek	K1K50-UP0264-K1K50-2500	170214-1 & 170214-2	2025/11/21	2026/11/20

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Equipment List					
Equipment	Manufacturer	Model No.	Serial No.	Cal. Date	Expired date
Antenna Port Conducted Measurement					
Signal Analyzer	Rohde & Schwarz	FSVA3044	101281	2026/2/2	2027/2/1
Signal Analyzer	Rohde & Schwarz	FSV40	101490	2025/6/17	2026/6/16
Attenuator	EMCI	EMC-40ATK2W10	17002	2025/10/28	2026/10/27
USB Power Sensor	Anritsu	MA24408A	12031	2025/6/24	2026/6/23
Temperature & Humidity Test Chamber	GIANT FORCE	GTH-150- 40-CP-AR	MAA1701-010	2026/2/2	2027/2/1
AC power Line Conducted Emission					
EMI Test Receiver	Rohde & Schwarz	ESR7	101753	2025/9/18	2026/9/17
Two-Line V-Network	Rohde & Schwarz	ENV216	102136	2025/5/27	2026/5/26
Impuls-Begrenzer Pulse Limiter	Rohde & Schwarz	ESH3-Z2	102219-Qt	2025/8/27	2026/8/26
Cables	TITAN	CFD200	T0732ACFD 20020A300-2	2025/4/21	2026/4/20
				2026/4/15	2027/4/14

UL Software		
Description	Name	Version
Radiated measurement	e3	6.191211 (V6)
AC power Line Conducted Emission	EZ_EMC	UL-3A1.2

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

8. Description of Test Setup

Tx Mode

Support Equipment

ID	Equipment	Brand Name	Model Name	S/N	Remark
A	Laptop	DELL	Latitude E5470	5M2MWF2	Provided by Lab

I/O Cables

ID	Equipment	Brand Name	Model Name	Length (m)	Remark
1	USB Cable	Nienyi	310-50024-01	1	Supplied by Client

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Setup

Controlled using a bespoke application (Typing RF commands by terminal tool (TeraTerm version 4.94)) on a test Notebook. The application was used to enable a continuous transmission mode and to select the test channels, data rates, modulation schemes and power setting as required.

Setup Diagram for Test



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9. Test Results

9.1. Conducted Out of Band Emission

Requirements

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b) (3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209 (a) is also required.

Test procedure


Measurement Procedure REF

1. Set the RBW = 100 kHz.
2. Set the VBW $\geq$ 300 kHz.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum power level in any 100 kHz band segment within the fundamental EBW.

Measurement Procedure OOBE

1. Set RBW = 100 kHz.
2. Set VBW $\geq$ 300 kHz.
3. Detector = peak.
4. Sweep = auto couple.
5. Trace Mode = max hold.
6. Allow trace to fully stabilize.
7. Use the peak marker function to determine the maximum amplitude level.

Test Setup



The loss between RF output port of the EUT and the input port of the Spectrum Analyzer has been taken into consideration.

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Data



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9.2. Radiated Spurious Emission

Requirements

Radiated emissions which fall in the restricted bands must comply with the radiated emission limits specified as below table. Other emissions shall be at least 20dB below the highest level of the desired power:

Frequency(MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Note:

1. The lower limit shall apply at the transition frequencies.
2. Emission level (dBuV/m) = 20 log Emission level (uV/m).
3. For frequencies above 1000MHz, the field strength limits are based on average detector, however, the peak field strength of any emission shall not exceed the maximum permitted average limits, specified above by more than 20dB under any condition of modulation.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Procedures

[For 9 kHz ~ 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. Parallel, perpendicular, and ground-parallel orientations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 30MHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Note:

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

[For above 30 MHz]

- a. The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. For measurement below 1GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.
- f. The test-receiver system was set to peak and average detects function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Note:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is $\geq 1/T$ (Duty cycle $< 98\%$) or 10Hz (Duty cycle $\geq 98\%$) for Average detection (AV) at frequency above 1GHz, for $1/T$ (Duty cycle $< 98\%$) video bandwidth detail information refer to main report duty cycle test result.
- All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
- Test data of Result value (dBuV/m) = Reading value (dBuV) + Correction Factor (dB/m).
- Test data of Margin(dB) = Result value (dBuV/m) - Limit value (dBuV/m).
- Test data of Correction Factor (dB/m) = Antenna Factor (dBuV/m) + Cable Loss (dB) - Preamp Factor (dB).
- Test data of Notation "@" = Fundamental Frequency
- Test data of Notation "*" = The peak result under 20 dB above and complies with AVG limit, AVG result is deemed to comply with AVG limit.

Test Setup

<Frequency Range 9 kHz ~ 30 MHz>



Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

<Frequency Range 30 MHz ~ 1 GHz >



<Frequency Range above 1 GHz>



For the actual test configuration, please refer to the Setup Configurations.

Test Data

Above 1 GHz

Mode	2.4G 802.11g & BLE 1M	Channel	6 & 19
------	-----------------------	---------	--------

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal	*	4874	38.2	4.4	42.6	74	-31.4	PK
		4880	34.17	4.46	38.63	74	-35.37	PK
		7311	42.4	12.17	54.57	74	-19.43	PK
		7311	25.37	12.17	37.54	54	-16.46	AVG
		7320	35.67	12.19	47.86	74	-26.14	PK
		14485	29.18	27.98	57.16	74	-16.84	PK
		14485	19.7	27.98	47.68	54	-6.32	AVG
		15355	29.67	26.36	56.03	74	-17.97	PK
		15355	20.84	26.36	47.2	54	-6.8	AVG
	*	17059	34.69	5.27	39.96	74	-34.04	PK
		17080	34.36	5.31	39.67	74	-34.33	PK
	*	19496	35.9	3.87	39.77	74	-34.23	PK
		19520	33.89	3.87	37.76	74	-36.24	PK
	*	21933	33.46	6.07	39.53	74	-34.47	PK
		21960	31.33	6.08	37.41	74	-36.59	PK
	*	24370	32.26	11.67	43.93	74	-30.07	PK
		24400	31.92	11.78	43.7	74	-30.3	PK
Vertical	*	4874	49.42	4.4	53.82	74	-20.18	PK
		4880	49.36	4.46	53.82	74	-20.18	PK
		7311	48.18	12.17	60.35	74	-13.65	PK
		7311	39.74	12.17	51.91	54	-2.09	AVG
		7320	39.64	12.19	51.83	74	-22.17	PK
		14485	31.04	27.98	59.02	74	-14.98	PK
		14485	19.62	27.98	47.6	54	-6.4	AVG
		15790	30.58	25.28	55.86	74	-18.14	PK
		15790	21.75	25.28	47.03	54	-6.97	AVG
	*	17059	33.29	5.27	38.56	74	-35.44	PK
		17080	32.91	5.31	38.22	74	-35.78	PK
	*	19496	34.29	3.87	38.16	74	-35.84	PK
		19520	34.78	3.87	38.65	74	-35.35	PK
	*	21933	31.62	6.07	37.69	74	-36.31	PK
		21960	31.5	6.08	37.58	74	-36.42	PK
	*	24370	32	11.67	43.67	74	-30.33	PK
		24400	32.54	11.78	44.32	74	-29.68	PK

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000


Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0


Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19)
Radiated Spurious Emission, Horizontal




Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19)
Radiated Spurious Emission, Vertical



Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19)
Radiated Spurious Emission, Horizontal



Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19)
Radiated Spurious Emission, Vertical



Mode	5G 802.11n(HT20) & BLE 1M	Channel	149 & 19
------	---------------------------	---------	----------

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		4880	35.86	4.46	40.32	74	-33.68	PK
		7320	32.82	12.19	45.01	74	-28.99	PK
	*	11490	30.23	21.49	51.72	74	-22.28	PK
		14470	29.17	27.97	57.14	68.2	-11.06	PK
		14470	19.69	27.97	47.66	54	-6.34	AVG
		15430	29.78	26.08	55.86	74	-18.14	PK
		15430	20.95	26.08	47.03	54	-6.97	AVG
		17080	30.33	5.31	35.64	68.2	-32.56	PK
	*	17235	30.89	5.07	35.96	68.2	-32.24	PK
		19520	33.87	3.87	37.74	74	-36.26	PK
		21960	32.32	6.08	38.4	68.2	-29.8	PK
	*	22980	32.88	8.3	41.18	74	-32.82	PK
		24400	31.8	11.78	43.58	68.2	-24.62	PK
	*	28725	33.38	11.21	44.59	68.2	-23.61	PK
	*	34470	35.14	11.73	46.87	68.2	-21.33	PK
		39568	38.37	17.11	55.48	74	-18.52	PK
		39568	28.53	17.11	45.64	54	-8.36	AVG
Vertical		4880	37.01	4.46	41.47	74	-32.53	PK
		7320	32.03	12.19	44.22	74	-29.78	PK
	*	11490	30.36	21.49	51.85	74	-22.15	PK
		14485	29.22	27.98	57.2	74	-16.8	PK
		14485	19.74	27.98	47.72	54	-6.28	AVG
		15565	29.52	25.63	55.15	74	-18.85	PK
		15565	20.69	25.63	46.32	54	-7.68	AVG
		17080	30.46	5.31	35.77	68.2	-32.43	PK
	*	17235	31.45	5.07	36.52	68.2	-31.68	PK
		19520	32.96	3.87	36.83	74	-37.17	PK
		21960	31.35	6.08	37.43	68.2	-30.77	PK
	*	22980	32.49	8.3	40.79	74	-33.21	PK
		24400	31.61	11.78	43.39	68.2	-24.81	PK
	*	28725	34.25	11.21	45.46	68.2	-22.74	PK
	*	34470	35.53	11.73	47.26	68.2	-20.94	PK
		39616	38.56	17.18	55.74	74	-18.26	PK
		39616	28.72	17.18	45.9	54	-8.1	AVG

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan


Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0


Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Horizontal




Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Vertical




Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Horizontal



Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Vertical




Below 1 GHz


Mode	2.4G 802.11g & BLE 1M	Channel	6 & 19
------	-----------------------	---------	--------

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		82.38	56.35	-26.58	29.77	40	-10.23	PK
		163.86	57.83	-24.52	33.31	43.5	-10.19	PK
		222.06	52.52	-21.61	30.91	46	-15.09	PK
		481.05	39.71	-14.4	25.31	46	-20.69	PK
		747.8	39.1	-8.7	30.4	46	-15.6	PK
		887.48	37.54	-6.79	30.75	46	-15.25	PK
Vertical		31.94	54.92	-24.61	30.31	40	-9.69	PK
		106.63	51.48	-21.94	29.54	43.5	-13.96	PK
		167.74	56.09	-24.4	31.69	43.5	-11.81	PK
		237.58	51.51	-20.39	31.12	46	-14.88	PK
		350.1	42.58	-16.8	25.78	46	-20.22	PK
		596.48	40.38	-11.33	29.05	46	-16.95	PK

Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19) Radiated Spurious Emission, Horizontal



Co-location, 2.4G 802.11g & BLE 1M (Ch 6 & 19) Radiated Spurious Emission, Vertical



Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Mode	5G 802.11n(HT20) & BLE 1M	Channel	149 & 19
------	---------------------------	---------	----------

Polarization	Notation	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
Horizontal		71.71	52.67	-25.43	27.24	40	-12.76	PK
		165.8	56.52	-24.43	32.09	43.5	-11.41	PK
		223.03	53.45	-21.52	31.93	46	-14.07	PK
		543.13	38.89	-13.08	25.81	46	-20.19	PK
		615.88	39.72	-10.86	28.86	46	-17.14	PK
		726.46	39.08	-9.42	29.66	46	-16.34	PK
Vertical		33.88	57.03	-24.25	32.78	40	-7.22	PK
		70.74	57.27	-25.25	32.02	40	-7.98	PK
		220.12	53.18	-21.8	31.38	46	-14.62	PK
		289.96	46.65	-19.07	27.58	46	-18.42	PK
		675.05	37.65	-10.23	27.42	46	-18.58	PK
		927.25	37.24	-6.12	31.12	46	-14.88	PK


Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Horizontal



Co-location, 5G 802.11n(HT20) & BLE 1M (Ch 149 & 19)

Radiated Spurious Emission, Vertical



9 kHz ~ 30 MHz Data:

For 9 kHz to 30 MHz radiated emission have performed all modes of operation were investigated. The amplitude of spurious emissions attenuated more than 20 dB below the permissible value is not required to be report.

No non-compliance noted:

KDB 414788 D01 OATS and Chamber Correlation Justification

- Base on FCC 15.31 (f) (2): measurements may be performed at a distance closer than that specified in the regulations; however, an attempt should be made to avoid making measurements in the near field.

- OATs and chamber correlation testing had been performed and chamber measured test results is the worst case test result.

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

9.3. AC Power Line Conducted Emission

Requirements

Frequency (MHz)	Conducted limit (dBμV)	
	Quasi-peak	Average
0.15 - 0.5	66 - 56	56 - 46
0.50 - 5.0	56	46
5.0 - 30	60	50

Note:

1. The lower limit shall apply at the transition frequencies.
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

Test Procedures

- a. The EUT was placed 0.4 meters from the conducting wall of the shielded room with EUT being connected to the power mains through a line impedance stabilization network (LISN). Other support units were connected to the power mains through another LISN. The two LISNs provide 50 ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Both lines of the power mains connected to the EUT were checked for maximum conducted interference.
- c. The frequency range from 150kHz to 30MHz was searched. Emission levels under (Limit - 20dB) was not recorded.

NOTE:

1. The resolution bandwidth and video bandwidth of test receiver is 9kHz for quasi-peak detection (QP) and average detection (AV) at frequency 0.15MHz-30MHz.
2. All modes of operation were investigated (includes all external accessories) and the worst-case emissions are reported, the other emission levels were low against the limit.
3. Test data of Result value (dBuV) = Reading value (dBuV) + Correction Factor (dB).
4. Test data of Margin(dB) = Result value (dBuV) - Limit value (dBuV).
5. Test data of Correction Factor (dB) = Insertion loss(dB) + Cable loss(dB).

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone :+886-2-7737-3000

Facsimile (FAX) :+886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Test Setup




Note: 1.Support units were connected to second LISN.

For the actual test configuration, please refer to the Setup Configurations.

Test Data

Mode	2.4G 802.11g & BLE 1M	Channel	6 & 19
------	-----------------------	---------	--------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1508	28.47	19.45	47.92	65.96	-18.04	QP
2	0.1508	14.54	19.45	33.99	55.96	-21.97	AVG
3	0.1726	22.19	19.45	41.64	64.83	-23.19	QP
4	0.1726	2.00	19.45	21.45	54.83	-33.38	AVG
5	0.1991	20.52	19.45	39.97	63.65	-23.68	QP
6	0.1991	7.10	19.45	26.55	53.65	-27.10	AVG
7	0.2063	18.59	19.45	38.04	63.35	-25.31	QP
8	0.2063	4.05	19.45	23.50	53.35	-29.85	AVG
9	0.2535	13.08	19.46	32.54	61.64	-29.10	QP
10	0.2535	0.98	19.46	20.44	51.64	-31.20	AVG
11	0.4898	15.70	19.46	35.16	56.17	-21.01	QP
12	0.4898	6.66	19.46	26.12	46.17	-20.05	AVG

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Mode	2.4G 802.11g & BLE 1M	Channel	6 & 19
------	-----------------------	---------	--------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1508	30.25	19.45	49.70	65.96	-16.26	QP
2	0.1508	18.01	19.45	37.46	55.96	-18.50	AVG
3	0.1692	22.28	19.45	41.73	65.00	-23.27	QP
4	0.1692	2.25	19.45	21.70	55.00	-33.30	AVG
5	0.1833	15.49	19.45	34.94	64.33	-29.39	QP
6	0.1833	-1.26	19.45	18.19	54.33	-36.14	AVG
7	0.2037	20.78	19.45	40.23	63.46	-23.23	QP
8	0.2037	7.97	19.45	27.42	53.46	-26.04	AVG
9	0.4750	15.71	19.45	35.16	56.43	-21.27	QP
10	0.4750	2.69	19.45	22.14	46.43	-24.29	AVG
11	0.4907	16.25	19.45	35.70	56.16	-20.46	QP
12	0.4907	6.25	19.45	25.70	46.16	-20.46	AVG

Underwriters Laboratories Taiwan Co., Ltd.


Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948


Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0

Mode	5G 802.11n(HT20) & BLE 1M	Channel	149 & 19
------	---------------------------	---------	----------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1502	28.55	19.45	48.00	65.99	-17.99	QP
2	0.1502	14.25	19.45	33.70	55.99	-22.29	AVG
3	0.1627	21.87	19.45	41.32	65.32	-24.00	QP
4	0.1627	3.88	19.45	23.33	55.32	-31.99	AVG
5	0.1930	19.50	19.45	38.95	63.91	-24.96	QP
6	0.1930	3.26	19.45	22.71	53.91	-31.20	AVG
7	0.2062	17.71	19.45	37.16	63.36	-26.20	QP
8	0.2062	2.05	19.45	21.50	53.36	-31.86	AVG
9	0.4874	15.79	19.46	35.25	56.21	-20.96	QP
10	0.4874	5.83	19.46	25.29	46.21	-20.92	AVG
11	2.1987	10.66	19.51	30.17	56.00	-25.83	QP
12	2.1987	5.70	19.51	25.21	46.00	-20.79	AVG

Mode	5G 802.11n(HT20) & BLE 1M	Channel	149 & 19
------	---------------------------	---------	----------



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1546	26.93	19.45	46.38	65.75	-19.37	QP
2	0.1546	11.07	19.45	30.52	55.75	-25.23	AVG
3	0.1960	21.22	19.45	40.67	63.78	-23.11	QP
4	0.1960	7.37	19.45	26.82	53.78	-26.96	AVG
5	0.4572	14.99	19.45	34.44	56.74	-22.30	QP
6	0.4572	6.24	19.45	25.69	46.74	-21.05	AVG
7	0.4843	17.38	19.45	36.83	56.26	-19.43	QP
8	0.4843	8.34	19.45	27.79	46.26	-18.47	AVG
9	0.4880	17.56	19.45	37.01	56.20	-19.19	QP
10	0.4880	10.74	19.45	30.19	46.20	-16.01	AVG
11	2.3770	10.21	19.51	29.72	56.00	-26.28	QP
12	2.3770	4.65	19.51	24.16	46.00	-21.84	AVG

END OF REPORT

Underwriters Laboratories Taiwan Co., Ltd.

Building A, B and E, No. 372-7, Sec. 4, Zhongxing Rd., Zhudong Township, Hsinchu County, Taiwan

Telephone : +886-2-7737-3000

Facsimile (FAX) : +886-3-583-7948

Doc No: Form-ULID-004737 (DCS:17-EM-F0876) / 7.0