



CFR 47 FCC PART 15 SUBPART E

TEST REPORT

For

Smart Home Bridge

MODEL NUMBER: Bridge-M

REPORT NUMBER: E04A26030071F00504

ISSUE DATE: May 9, 2026

FCC ID:2APN5-BRIDGEM

Prepared for

Shenzhen Sonoff Technologies Co., Ltd.

3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

Prepared by

Guangdong Global Testing Technology Co., Ltd.

**Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park,
Dongguan city, Guangdong, People's Republic of China, 523808**

This report is based on a single evaluation of the submitted sample(s) of the above mentioned product, it does not imply an assessment of the production of the products.

This report shall not be reproduced, except in full, without the written approval of Guangdong Global Testing Technology Co., Ltd.

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	May 9, 2026	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
ON TIME AND DUTY CYCLE	ANSI C63.10-2020, Clause 12.2	None; for reporting purposes only.	Pass
6dB AND 26dB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	KDB 789033 D02 v02r01 Section C.1	FCC Part 15.407 (a)(2)(5)	Pass
CONDUCTED OUTPUT POWER	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	FCC Part 15.407 (a)(1)(2)(3)	Pass
POWER SPECTRAL DENSITY	KDB 789033 D02 v02r01 Section F	FCC Part 15.407 (a)(1)(2)(3)	Pass
AC POWER LINE CONDUCTION EMISSION	ANSI C63.10-2020, Clause 6.2.	FCC 15.207, RSS-GEN Clause 8.8	Pass
RADIATED EMISSIONS AND BAND EDGE MEASUREMENT	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	FCC Part 15.407 (b)(1)(2)(3)(4)(6), FCC Part 15.209/205	Pass
FREQUENCY STABILITY		FCC 15.407 (g)	Pass
DYNAMIC FREQUENCY SELECTION (SLAVE)	KDB 905462 D03 Client Without DFS New Rules v01r02	FCC Part 15.407 (h)	N/A
DYNAMIC FREQUENCY SELECTION (MASTER)	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	FCC Part 15.407 (h)	N/A
ANTENNA REQUIREMENT	N/A	FCC Part 15.203, FCC Part 15.407(a)(1) (2)	Pass

Note:

1. N/A: In this whole report not applicable.

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART E> when <Accuracy Method> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	5
2. TEST METHODOLOGY.....	6
3. FACILITIES AND ACCREDITATION.....	6
4. CALIBRATION AND UNCERTAINTY	7
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>7</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>7</i>
5. EQUIPMENT UNDER TEST	8
5.1. <i>DESCRIPTION OF EUT</i>	<i>8</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>Maximum Conducted Power</i>	<i>9</i>
5.4. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>10</i>
5.5. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>11</i>
5.6. <i>EUT ACCESSORY</i>	<i>12</i>
5.7. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>12</i>
5.8. <i>SETUP DIAGRAM</i>	<i>13</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	14
7. ANTENNA PORT TEST RESULTS	16
7.1. <i>ON TIME AND DUTY CYCLE.....</i>	<i>16</i>
7.2. <i>6dB AND 26dB EMISSION BANDWIDTH.....</i>	<i>17</i>
7.3. <i>CONDUCTED OUTPUT POWER</i>	<i>19</i>
7.4. <i>POWER SPECTRAL DENSITY</i>	<i>21</i>
7.5. <i>FREQUENCY STABILITY.....</i>	<i>23</i>
8. RADIATED TEST RESULTS.....	25
8.1. <i>RADIATED EMISSIONS AND BAND EDGE MEASUREMENT</i>	<i>31</i>
9. AC POWER LINE CONDUCTION EMISSION	51
10. ANTENNA REQUIREMENT	54
11. TEST DATA - Appendix A.....	55

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: Shenzhen Sonoff Technologies Co., Ltd.
Address: 3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

Manufacturer Information

Company Name: Shenzhen Sonoff Technologies Co., Ltd.
Address: 3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

EUT Information

Product Description: Smart Home Bridge
Model: Bridge-M
Series Model: /
Brand: SONOFF
Sample Received Date: March 9, 2026
Sample Status: Normal
Sample ID: A26030071 001
Date of Tested: March 10, 2026 to May 8, 2026

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E	Pass

Prepared By:

Ellie.Yang

Ellie.Yang

Project Engineer

Approved By:

Alan He

Alan He

Laboratory Manager

Checked By:

Alan He

Alan He

Laboratory Manager



2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART E

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	A2LA (Certificate No.: 6947.01) Guangdong Global Testing Technology Co., Ltd. has been assessed and proved to be in compliance with A2LA. FCC (FCC Designation No.: CN1343) Guangdong Global Testing Technology Co., Ltd. has been recognized to perform compliance testing on equipment subject to Supplier's Declaration of Conformity (SDoC) and Certification rules ISED (Company No.: 30714) Guangdong Global Testing Technology Co., Ltd. has been registered and fully described in a report filed with ISED. The Company Number is 30714 and the test lab Conformity Assessment Body Identifier (CABID) is CN0148.
---------------------------	--

Note: All tests measurement facilities use to collect the measurement data are located at Room 101-105, 203-210, Building 1, No.2, Keji 8 Road, Songshan Lake Park, Dongguan city, Guangdong, People's Republic of China, 523808

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Items	k	Uncertainty
Emission Bandwidth	1.96	±9.0 PPM
Conduct Output Power	1.96	± 1.12 dB
Power Spectral Density	1.96	± 2.1 dB
Conducted Spurious Emission	1.96	9 kHz-30 MHz: ± 0.95 dB 30 MHz-1 GHz: ± 1.5 dB 1GHz-12.75GHz: ± 1.8 dB 12.75 GHz-26.5 GHz: ± 2.1dB 26.5 GHz-40 GHz: ± 2.6 dB
Frequency Stability	1.96	±9.0 PPM
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.		

Test Item	Frequency Range	k	U(dB)
Conducted emissions from the AC mains power ports (AMN)	150 kHz ~ 30 MHz	2	3.37
Radiated emissions	9 kHz ~ 30 MHz	2	4.16
Radiated emissions	30 MHz ~ 1 GHz	2	3.79
Radiated emissions	1 GHz ~ 18 GHz	2	5.62
Radiated emissions	18 GHz ~ 40 GHz	2	5.54
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.			

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Smart Home Bridge	
Model	Bridge-M	
Hardware Version	V1.0	
Software Version	V1.0	
Ratings	Type C Input: 5V = 1A	
Power Supply	DC	5V

Frequency Band:	5150 MHz to 5250 MHz (U-NII-1) 5725 MHz to 5850 MHz (U-NII-3)
Frequency Range:	5180 MHz to 5240 MHz 5745 MHz to 5825 MHz
Support Standards:	IEEE 802.11a/n/ac/ax
Type of Modulation:	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n HT20/ac VHT20/ax HE20: 20 MHz IEEE 802.11n HT40/ac VHT40/ax HE40: 40 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS15 IEEE 802.11n-HT40: Up to MCS15 IEEE 802.11ac-VHT20: Up to MCS8 IEEE 802.11ac-VHT40: Up to MCS9 IEEE 802.11ax HE20: Up to MCS11 IEEE 802.11ax HE40: Up to MCS11
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n HT20/ac VHT20/ax HE20 2 for IEEE 802.11n HT40/ac VHT40/ax HE40 5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n HT20/ac VHT20/ax HE20 2 for IEEE 802.11n HT40/ac VHT40/ax HE40
Maximum conducted output power:	U-NII-1 IEEE 802.11a: 15.11 dBm IEEE 802.11n HT20: 13.80 dBm IEEE 802.11n HT40: 12.67 dBm IEEE 802.11ac VHT20: 13.03 dBm IEEE 802.11ac VHT40: 12.66 dBm IEEE 802.11ax HE20: 12.95 dBm IEEE 802.11ax HE40: 11.87 dBm U-NII-3 IEEE 802.11a: 14.22 dBm IEEE 802.11n HT20: 13.21 dBm IEEE 802.11n HT40: 12.41 dBm IEEE 802.11ac VHT20: 12.24 dBm IEEE 802.11ac VHT40: 11.61 dBm IEEE 802.11ax HE20: 12.29 dBm

	IEEE 802.11ax HE40: 11.79 dBm
Antenna Type:	Integral Antenna
Antenna Gain:	2.4 dBi
Normal Test Voltage:	5 Vdc
EUT Test software:	adb
Note:	1.The Antenna Gain was provided by customer, and this information may affect the validity of the results, customer should be responsible for this. 2. The 802.11ax mode of EUT only supports SU, not RU tone.

5.2. CHANNEL LIST

UNII-1 (For Bandwidth=20MHz)		UNII-1 (For Bandwidth=40MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190
40	5200	46	5230
44	5220		
48	5240		

UNII-3 (For Bandwidth=20MHz)		UNII-3 (For Bandwidth=40MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755
153	5765	159	5795
157	5785		
161	5805		
165	5825		

5.3. MAXIMUM CONDUCTED POWER

UNII-1 BAND(FCC)

IEEE Std. 802.11	Frequency (MHz)	Maximum Conducted Power (dBm)	Max EIRP (dBm)
a	5150 ~ 5250	15.11	/
n HT20		13.80	/
n HT40		12.67	/
ac VHT20		13.03	/
ac VHT40		12.66	/
ax HE20		12.95	/
ax HE40		11.87	/

UNII-3 BAND(FCC)

IEEE Std. 802.11	Frequency (MHz)	Maximum Conducted Power (dBm)	Max EIRP (dBm)
a	5725 ~ 5850	14.22	/

n HT20		13.21	/
n HT40		12.41	/
ac VHT20		12.21	/
ac VHT40		11.61	/
ax HE20		12.29	/
ax HE40		11.79	/

5.4. THE WORSE CASE POWER SETTING PARAMETER

The Worse Case Power Setting Parameter	
Test Software	adb

UNII-1

Mode	Rate	Channel	Soft set value
			ANT 1
11a	6M	36	16
		40	16
		48	16
11n HT20	MCS0	36	15
		40	15
		48	15
11n HT40	MCS0	38	14
		46	14
11ac VHT20	MCS0	36	13
		40	13
		48	13
11ac VHT40	MCS0	38	13
		46	13
11ax HE20	MCS0	36	13
		40	13
		48	13
11ax HE40	MCS0	38	13
		46	13

UNII-3

Mode	Rate	Channel	Soft set value
			ANT1
11a	6M	149	18
		157	18
		165	18
11n HT20	MCS0	149	17
		157	18
		165	18
11n HT40	MCS0	151	16
		159	16
11ac VHT20	MCS0	149	16
		157	17
		165	17
11ac VHT40	MCS0	151	15

		159	15
11ax HE20	MCS0	149	16
		157	16
		165	16
		151	15
11ax HE40	MCS0	159	15

THE WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.6.

Worst case Data Rates declared by the customer:

802.11a 20 mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0
802.11ac VHT20 mode: MCS0
802.11ac VHT40 mode: MCS0
802.11ax HE20 mode: MCS0
802.11ax HE40 mode: MCS0

5.5. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency Band	Antenna Type	Max Antenna Gain (dBi)
1	5150-5850	Internal Antenna	2.4

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11n HT20	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11n HT40	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT20	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ac VHT40	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
802.11ax HE20	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.
8802.11ax HE40	☒1TX, 1RX	ANT 1 can be used as transmitting/receiving antenna.

5.6. EUT ACCESSORY

Cable	
Accessory:	USB cable
Model No.:	/
Description:	USB Type-C Plug Cable
Cable Type:	Unshielded without ferrite
Length:	1.4 Meter
Accessory:	Network cable
Model No.:	/
Description:	Network port plug cable
Cable Type:	Unshielded without ferrite
Length:	1 Meter

5.7. SUPPORT UNITS FOR SYSTEM TEST

The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Laptop	Lenovo	Thinkpad T14	PF-3EAKYR	GTG Support
E-2	Adapter	Xiaomi	MDY-11-EX	N/A	GTG Support

The following cables were used to form a representative test configuration during the tests.


Item	Type of cable	Shielded Type	Ferrite Core	Length
C-1	USB cable	Shielded	without ferrite	1.0 m

5.8. SETUP DIAGRAM

AC conducted emission:



Radiated emissions:



6. MEASURING EQUIPMENT AND SOFTWARE USED

Test Equipment of Conducted RF					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Spectrum Analyzer	Rohde & Schwarz	FSV40	102257	2025/08/25	2026/08/24
Spectrum Analyzer	KEYSIGHT	N9020A	MY51285127	2025/08/25	2026/08/24
EXG Analog Signal Generator	KEYSIGHT	N5173B	MY61253075	2025/08/25	2026/08/24
Vector Signal Generator	Rohde & Schwarz	SMM100A	101899	2025/08/25	2026/08/24
RF Control box	MWRF-test	MW100-RFCB	MW220926GTG	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW270	102792	2025/08/25	2026/08/24
Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	103235	2025/08/25	2026/08/24
temperature humidity chamber	Espec	SH-241	SH-241-2014	2025/08/25	2026/08/24
RF Test Software	MWRF-test	MTS8310E (Ver. V2/0)	N/A	N/A	N/A

Test Equipment of Radiated emissions below 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2146	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESCI3	101144	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-9K0130	HYPA21001	2025/08/23	2026/08/22
Biconilog Antenna	Schwarzbeck	VULB 9168	01315	2025/09/20	2028/09/19
Biconilog Antenna	ETS	3142E	00243651	2025/02/22	2028/02/21
Loop Antenna	ETS	6502	00243668	2025/02/22	2028/02/21
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE)	N/A	N/A	N/A

Test Equipment of Radiated emissions above 1GHz					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
3m Semi-anechoic Chamber	ETS	9m*6m*6m	Q2149	2025/08/23	2026/08/22
Spectrum Analyzer	Rohde & Schwarz	FSV40	101413	2025/08/23	2026/08/22
Pre-Amplifier	HzEMC	HPA-1G1850	HYPA21003	2025/08/23	2026/08/22
Horn antenna	ETS	3117	00246069	2025/02/22	2028/02/21
Pre-Amplifier	HzEMC	HPA-184057	HYPA21004	2025/08/23	2026/08/22
Horn antenna	ETS	3116C	00246265	2025/02/22	2028/02/21
RF Filter Bank	HzEMC	HSW-F18	HSWF2218E01	2025/08/23	2026/08/22

RF Filter Bank	HzEMC	HPF18	HPF2218E02	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver.FA-03A2 RE+)	N/A	N/A	N/A

Test Equipment of Conducted emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
Shielded Room	CHENG YU	8m*5m*4m	N/A	2025/08/23	2026/08/22
EMI Test Receiver	Rohde & Schwarz	ESR3	102647	2025/08/23	2026/08/22
LISN/AMN	Rohde & Schwarz	ENV216	102843	2025/08/23	2026/08/22
NNLK 8129 RC	Schwarzbeck	NNLK 8129 RC	5046	2025/08/23	2026/08/22
Test Software	Farad	EZ-EMC (Ver. EMC-con-3A1 1+)	N/A	N/A	N/A

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW $\geq$ EBW if possible; otherwise, set RBW to the largest available value. Set VBW $\geq$ RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	21.3°C	Relative Humidity	59%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.2. 6DB AND 26DB EMISSION BANDWIDTH

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
26 dB Emission Bandwidth	For reporting purposes only.	5250 ~ 5350
26 dB Emission Bandwidth	For reporting purposes only.	5470 ~ 5725
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $> 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

- Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.
- Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion = $5725 - 5710.16 = 14.84$ MHz

Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz


FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion = $5728.2 - 5725 = 3.2$ MHz

TEST SETUP



TEST ENVIRONMENT

Temperature	21.3°C	Relative Humidity	59%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	☐ Outdoor Access Point: 1 W (30 dBm) ☐ Indoor Access Point: 1 W (30 dBm) ☐ Fixed Point-To-Point Access Points: 1 W (30 dBm) ☒ Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed the lesser of 250 mW (24dBm) or 11 dBm + 10 log B, where B is the 26 dB emission bandwidth in megahertz.	5250 ~ 5350 5470 ~ 5725
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method AVGPM-G is a measurement using a gated RF average power meter.

Alternatively, measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Because the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Gate triggering can be implemented in such a way that the sweep of the instrument is only active during the burst period of the device. Any Gate triggering shall be performed on the full power portion of the pulses and care must be taken to ensure that static portions of the pulse are not included in the measurement (ensuring that the trace is averaged over the entire symbol range). All Gate triggered measurements shall be accompanied by a Gate setup plot in the test report.

Method SA-1 (trace averaging with the EUT transmitting at full power throughout each sweep):

- (i) Set span to encompass the entire emission bandwidth (EBW) (or, alternatively, the entire 99% occupied bandwidth) of the signal.
- (ii) Set RBW = 1 MHz.
- (iii) Set VBW $\geq$ 3 MHz.
- (iv) Number of points in sweep $\geq 2 \times \text{span} / \text{RBW}$. (This ensures that bin-to-bin spacing is $\leq \text{RBW}/2$, so that narrowband signals are not lost between frequency bins.)
- (v) Sweep time = auto.
- (vi) Detector = power averaging (rms), if available. Otherwise, use sample detector mode.
- (vii) If transmit duty cycle $< 98\%$, use a video trigger with the trigger level set to enable triggering only on full power pulses. Transmitter must operate at maximum power control level for the entire duration of every sweep. If the EUT transmits continuously (i.e., with no off intervals) or at duty cycle $\geq 98\%$, and if each transmission is entirely at the maximum power control level, then the trigger shall be set to "free run."

- (viii) Trace average at least 100 traces in power averaging (rms) mode.
- (ix) Compute power by integrating the spectrum across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the signal using the instrument's band power measurement function with band limits set equal to the EBW (or occupied bandwidth) band edges. If the instrument does not have a band power function, sum the spectrum levels (in power units) at 1 MHz intervals extending across the EBW (or, alternatively, the entire 99% occupied bandwidth) of the spectrum.


Method PM (Measurement using an RF average power meter):

- (i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:
- The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 - At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.
 - The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.
- (ii) If the transmitter does not transmit continuously, measure the duty cycle, x , of the transmitter output signal as described in II.B.
- (iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.
- (iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25 %).

Method PM-G (Measurement using a gated RF average power meter):

Measurements may be performed using a wideband gated RF power meter provided that the gate parameters are adjusted such that the power is measured only when the EUT is transmitting at its maximum power control level. Since the measurement is made only during the ON time of the transmitter, no duty cycle correction factor is required.

Straddle channel power was measured using spectrum analyzer.

TEST SETUP**TEST ENVIRONMENT**

Temperature	21.3°C	Relative Humidity	59%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	☐ Outdoor Access Point: 17 dBm/MHz ☐ Indoor Access Point: 17 dBm/MHz ☐ Fixed Point-To-Point Access Points: 17 dBm/MHz ☒ Client Devices: 11 dBm/MHz	5150 ~ 5250
	11 dBm/MHz	5250 ~ 5350 5470 ~ 5725
	30 dBm/500kHz	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi.

If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyser and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:


Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

For U-NII-3:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow trace to fully stabilize and Use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add $10 \log (1/x)$, where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP**TEST ENVIRONMENT**

Temperature	21.3°C	Relative Humidity	59%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

7.5. FREQUENCY STABILITY

LIMITS

The frequency of the carrier signal shall be maintained within band of operation.

TEST PROCEDURE


1. The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between -10 °C ~ 40 °C (declared by customer).
2. The temperature was incremented by 10 °C intervals and the unit allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.
3. The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	10 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

4. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup, and at 2 minutes, 5 minutes, and 10 minutes after the EUT is energized.
5. Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

TEST SETUP



TEST ENVIRONMENT

Temperature	21.3°C	Relative Humidity	59%
Atmosphere Pressure	100kPa		

TEST RESULTS

Please refer to section "Test Data" - Appendix A

8. RADIATED TEST RESULTS

LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

²Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISSED RSS-247 6.2.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5250~5350 MHz		
5470~5725 MHz		
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyser

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made

to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.

8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X KHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyser

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2020 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.


Above 1 GHz

The setting of the spectrum analyser

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold


1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1.ON TIME AND DUTY CYCLE.

X axis, Y axis, Z axis positions:



Note 1: For all radiated test, EUT in each of three orthogonal axis emissions had been tested, but only the worst case (X axis) data recorded in the report.

TEST SETUP



TEST ENVIRONMENT


Temperature	22.1℃	Relative Humidity	51%
Atmosphere Pressure	101kPa		

TEST RESULTS**8.1. RADIATED EMISSIONS AND BAND EDGE MEASUREMENT**

Undesirable radiated Spurious Emission below 1GHz (30MHz to 1GHz)

All modes have been tested and the worst result as bellow:


Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa

**Critical_Freqs**

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	227.880	42.98	-20.06	22.92	46.00	23.08	PK+	H
2	335.550	34.56	-16.88	17.68	46.00	28.32	PK+	H
3	408.300	32.73	-13.44	19.29	46.00	26.71	PK+	H
4	600.360	34.32	-9.43	24.89	46.00	21.11	PK+	H
5	835.100	30.77	-5.24	25.53	46.00	20.47	PK+	H
6	950.530	30.57	-2.4	28.17	46.00	17.83	PK+	H

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	239.520	36.05	-19.26	16.79	46.00	29.21	PK+	V
2	459.710	32.22	-13.36	18.86	46.00	27.14	PK+	V
3	587.750	30.68	-9.78	20.90	46.00	25.10	PK+	V
4	699.300	31.98	-7.02	24.96	46.00	21.04	PK+	V
5	929.190	29.10	-2.14	26.96	46.00	19.04	PK+	V
6	998.060	29.40	-2.28	27.12	53.90	26.78	PK+	V

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Undesirable radiated Spurious Emission Above 1GHz (1GHz to 40GHz)

All modes have been tested and the worst result as bellow:

Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5095.000	57.95	-0.8	57.15	74.00	16.85	PK+	H
2	5389.000	55.86	-0.07	55.79	74.00	18.21	PK+	H
3	7405.000	44.75	11.34	56.09	74.00	17.91	PK+	H
4	7951.000	42.17	17.57	59.74	74.00	14.26	PK+	H
5	15551.000	51.69	-2.7	48.99	74.00	25.01	PK+	H
6	17737.000	47.86	-0.68	47.18	74.00	26.82	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5095.000	47.95	-0.8	47.15	53.90	6.75	AVG	H	PASS
2	5389.000	45.86	-0.07	45.79	53.90	8.11	AVG	H	PASS
3	7405.000	34.75	11.34	46.09	53.90	7.81	AVG	H	PASS
4	7951.000	32.17	17.57	49.74	53.90	4.16	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5592.000	53.19	-0.54	52.65	74.00	21.35	PK+	V
2	7069.000	45.73	10.01	55.74	74.00	18.26	PK+	V
3	7412.000	45.27	11.17	56.44	74.00	17.56	PK+	V
4	7986.000	42.90	16.63	59.53	74.00	14.47	PK+	V
5	15536.000	60.00	-2.69	57.31	74.00	16.69	PK+	V
6	17801.000	46.51	0.26	46.77	74.00	27.23	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7069.000	35.73	10.01	45.74	53.90	8.16	AVG	V	PASS
2	7412.000	35.27	11.17	46.44	53.90	7.46	AVG	V	PASS
3	7986.000	32.90	16.63	49.53	53.90	4.37	AVG	V	PASS
4	15536.000	49.34	-2.69	46.65	53.90	7.25	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5200
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5011.000	54.71	-1.78	52.93	74.00	21.07	PK+	H
2	5403.000	52.67	-0.06	52.61	74.00	21.39	PK+	H
3	7041.000	45.71	10.17	55.88	74.00	18.12	PK+	H
4	7391.000	45.10	11.43	56.53	74.00	17.47	PK+	H
5	7951.000	42.00	17.57	59.57	74.00	14.43	PK+	H
6	15600.000	51.24	-2.92	48.32	74.00	25.68	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7041.000	35.71	10.17	45.88	53.90	8.02	AVG	H	PASS
2	7391.000	34.10	11.43	45.53	53.90	8.37	AVG	H	PASS
3	7951.000	31.00	17.57	48.57	53.90	5.33	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5200
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5753.000	53.08	-1.07	52.01	74.00	21.99	PK+	V
2	7013.000	46.77	8.82	55.59	74.00	18.41	PK+	V
3	7419.000	45.99	11	56.99	74.00	17.01	PK+	V
4	7951.000	41.54	17.57	59.11	74.00	14.89	PK+	V
5	13368.000	50.08	-4.29	45.79	74.00	28.21	PK+	V
6	15594.000	59.95	-2.93	57.02	74.00	16.98	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7013.000	36.83	8.82	45.65	53.90	8.25	AVG	V	PASS
2	7419.000	34.98	11	45.98	53.90	7.92	AVG	V	PASS
3	7951.000	31.30	17.57	48.87	53.90	5.03	AVG	V	PASS
4	15594.000	50.58	-2.93	47.65	53.90	6.25	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5240
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5382.000	51.53	-0.08	51.45	74.00	22.55	PK+	V
2	6621.000	46.23	6.7	52.93	74.00	21.07	PK+	V
3	7034.000	45.50	9.79	55.29	74.00	18.71	PK+	V
4	7510.000	45.81	10.51	56.32	74.00	17.68	PK+	V
5	7958.000	43.04	17.34	60.38	74.00	13.62	PK+	V
6	15726.000	57.60	-2.35	55.25	74.00	18.75	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7034.000	34.86	9.79	44.65	53.90	9.25	AVG	V	PASS
2	7510.000	34.36	10.51	44.87	53.90	9.03	AVG	V	PASS
3	7958.000	31.64	17.34	48.98	53.90	4.92	AVG	V	PASS
4	15726.000	50.60	-2.35	48.25	53.90	5.65	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5240
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5032.000	53.32	-1.77	51.55	74.00	22.45	PK+	H
2	5403.000	52.60	-0.06	52.54	74.00	21.46	PK+	H
3	7720.000	44.00	12.69	56.69	74.00	17.31	PK+	H
4	7951.000	41.64	17.57	59.21	74.00	14.79	PK+	H
5	8293.000	52.00	-7.48	44.52	74.00	29.48	PK+	H
6	15725.000	49.06	-2.37	46.69	74.00	27.31	PK+	H

Final_Result


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	7720.000	32.96	12.69	45.65	53.90	8.25	AVG	H	PASS
2	7951.000	31.17	17.57	48.74	53.90	5.16	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Band Edge

All modes have been tested and the worst result as bellow:

Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5139.467	25.33	28.56	53.89	74.00	20.11	PK+	V
2	5150.000	25.99	28.45	54.44	74.00	19.56	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5150.000	21.99	28.45	50.44	54.00	3.56	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5180
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5148.067	37.44	28.48	65.92	74.00	8.08	PK+	H
2	5150.000	31.26	28.45	59.71	74.00	14.29	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5148.067	21.44	28.48	49.92	54.00	4.08	AVG	H	PASS
2	5150.000	22.21	28.45	50.66	54.00	3.34	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5240
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5350.000	27.47	28.99	56.46	74.00	17.54	PK+	H
2	5431.400	30.89	29.39	60.28	74.00	13.72	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5350.000	21.47	28.99	50.46	54.00	3.54	AVG	H	PASS
2	5431.400	20.89	29.39	50.28	54.00	3.72	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5240
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5350.000	23.04	28.99	52.03	74.00	21.97	PK+	V
2	5428.600	24.81	29.38	54.19	74.00	19.81	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5428.600	18.81	29.38	48.19	54.00	5.81	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5745
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	5721.030	39.28	29.27	68.55	122.20	53.65	PK+	H
2	5725.000	40.61	29.24	69.85	122.20	52.35	PK+	H

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5745
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5723.880	37.06	29.25	66.31	122.20	55.89	PK+	V
2	5725.000	34.87	29.24	64.11	122.20	58.09	PK+	V

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5825
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBµV)	Corr. (dB)	Meas. (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Det.	Pol.
1	5850.000	37.17	29.32	66.49	122.20	55.71	PK+	H
2	5853.775	39.04	29.35	68.39	113.59	45.20	PK+	H

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	A-5825
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa




Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5850.000	29.32	29.32	58.64	122.20	63.56	PK+	V
2	5854.165	27.78	29.36	57.14	112.70	55.56	PK+	V

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	N40-5190
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5144.247	30.91	28.52	59.43	74.00	14.57	PK+	V
2	5150.000	28.06	28.45	56.51	74.00	17.49	PK+	V

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5144.247	20.91	28.52	49.43	54.00	4.57	AVG	V	PASS
2	5150.000	20.06	28.45	48.51	54.00	5.49	AVG	V	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	N40-5190
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5141.973	38.53	28.54	67.07	74.00	6.93	PK+	H
2	5150.000	34.50	28.45	62.95	74.00	11.05	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5141.973	21.53	28.54	50.07	54.00	3.93	AVG	H	PASS
2	5150.000	22.50	28.45	50.95	54.00	3.05	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	N40-5230
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs


No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5350.000	25.62	28.99	54.61	74.00	19.39	PK+	H
2	5436.400	29.43	29.41	58.84	74.00	15.16	PK+	H

Final_Result

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.	Verdict
1	5350.000	21.62	28.99	50.61	54.00	3.39	AVG	H	PASS
2	5436.400	21.43	29.41	50.84	54.00	3.16	AVG	H	PASS

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

Mode:	N40-5230
Power:	DC 5V
TE:	Berny
Date	2026/04/07
T/A/P	22.1°C/51%/101Kpa



Critical_Freqs

No.	Freq. (MHz)	Reading (dBμV)	Corr. (dB)	Meas. (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Det.	Pol.
1	5350.000	22.86	28.99	51.85	74.00	22.15	PK+	V
2	5419.500	24.36	29.36	53.72	74.00	20.28	PK+	V

Note: [Margin=Limit-Meas.]; [Meas.=Reading+Corr.]

9. AC POWER LINE CONDUCTION EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a)

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


TEST PROCEDURE

Refer to ANSI C63.10-2020 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2020. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.


TEST SETUP



TEST ENVIRONMENT

Temperature	23.2°C	Relative Humidity	52%
Atmosphere Pressure	100kPa		


TEST RESULTS



Phase: L1

Mode: 5G WIFI

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1635	34.14	9.71	43.85	65.28	-21.43	QP
2	0.1635	7.45	9.71	17.16	55.28	-38.12	AVG
3	0.2084	30.71	9.62	40.33	63.27	-22.94	QP
4	0.2084	5.10	9.62	14.72	53.27	-38.55	AVG
5	0.4110	24.02	9.60	33.62	57.63	-24.01	QP
6	0.4110	8.37	9.60	17.97	47.63	-29.66	AVG
7	0.6090	17.67	9.68	27.35	56.00	-28.65	QP
8	0.6090	-0.32	9.68	9.36	46.00	-36.64	AVG
9	8.2454	14.99	10.05	25.04	60.00	-34.96	QP
10	8.2454	-1.13	10.05	8.92	50.00	-41.08	AVG
11	11.2695	15.72	10.19	25.91	60.00	-34.09	QP
12	11.2695	0.58	10.19	10.77	50.00	-39.23	AVG



Phase: N

Mode: 5G WIFI

No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1590	33.89	9.63	43.52	65.52	-22.00	QP
2	0.1590	7.00	9.63	16.63	55.52	-38.89	AVG
3	0.1905	31.48	9.65	41.13	64.01	-22.88	QP
4	0.1905	5.44	9.65	15.09	54.01	-38.92	AVG
5	0.4110	20.13	9.63	29.76	57.63	-27.87	QP
6	0.4110	1.80	9.63	11.43	47.63	-36.20	AVG
7	0.7935	12.28	9.65	21.93	56.00	-34.07	QP
8	0.7935	-0.63	9.65	9.02	46.00	-36.98	AVG
9	2.2200	10.46	9.68	20.14	56.00	-35.86	QP
10	2.2200	-3.88	9.68	5.80	46.00	-40.20	AVG
11	6.1260	11.82	9.85	21.67	60.00	-38.33	QP
12	6.1260	-2.81	9.85	7.04	50.00	-42.96	AVG

10. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC §15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC §15.407(a)(1)(2)(3)

If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.


DESCRIPTION

Pass


11. TEST DATA - Appendix A

Duty Cycle


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	a	5180	Ant1	86.67	0.62	0.77
NVNT	a	5200	Ant1	87.5	0.58	0.71
NVNT	a	5240	Ant1	81.25	0.9	0.77
NVNT	a	5745	Ant1	86.08	0.65	0.74
NVNT	a	5785	Ant1	86.16	0.65	0.73
NVNT	a	5825	Ant1	86.16	0.65	0.73
NVNT	n20	5180	Ant1	90	0.46	0.79
NVNT	n20	5200	Ant1	88.28	0.54	0.78
NVNT	n20	5240	Ant1	90.14	0.45	0.78
NVNT	n20	5745	Ant1	90.14	0.45	0.78
NVNT	n20	5785	Ant1	85.33	0.69	0.78
NVNT	n20	5825	Ant1	85.91	0.66	0.78
NVNT	n40	5190	Ant1	82.05	0.86	1.56
NVNT	n40	5230	Ant1	82.89	0.81	1.59
NVNT	n40	5755	Ant1	84.21	0.75	1.56
NVNT	n40	5795	Ant1	80.77	0.93	1.59
NVNT	ac20	5180	Ant1	84.87	0.71	0.78
NVNT	ac20	5200	Ant1	90.78	0.42	0.78
NVNT	ac20	5240	Ant1	90.21	0.45	0.78
NVNT	ac20	5745	Ant1	91.49	0.39	0.78
NVNT	ac20	5785	Ant1	82.05	0.86	0.78
NVNT	ac20	5825	Ant1	87.67	0.57	0.78
NVNT	ac40	5190	Ant1	74.12	1.3	1.59
NVNT	ac40	5230	Ant1	77.11	1.13	1.56
NVNT	ac40	5755	Ant1	84.21	0.75	1.56
NVNT	ac40	5795	Ant1	82.89	0.81	1.59
NVNT	ax20	5180	Ant1	82.5	0.84	1.01
NVNT	ax20	5200	Ant1	88.5	0.53	1
NVNT	ax20	5240	Ant1	84.62	0.73	1.01
NVNT	ax20	5745	Ant1	83.19	0.8	1.01
NVNT	ax20	5785	Ant1	84.62	0.73	1.01
NVNT	ax20	5825	Ant1	88.39	0.54	1.01
NVNT	ax40	5190	Ant1	73.61	1.33	1.89
NVNT	ax40	5230	Ant1	74.65	1.27	1.89
NVNT	ax40	5755	Ant1	81.54	0.89	1.89
NVNT	ax40	5795	Ant1	75.36	1.23	1.92




Duty Cycle NVNT a 5180MHz Ant1




Duty Cycle NVNT a 5200MHz Ant1




Duty Cycle NVNT a 5240MHz Ant1




Duty Cycle NVNT a 5745MHz Ant1




Duty Cycle NVNT a 5785MHz Ant1




Duty Cycle NVNT a 5825MHz Ant1




Duty Cycle NVNT n20 5180MHz Ant1




Duty Cycle NVNT n20 5200MHz Ant1




Duty Cycle NVNT n20 5240MHz Ant1




Duty Cycle NVNT n20 5745MHz Ant1




Duty Cycle NVNT n20 5785MHz Ant1




Duty Cycle NVNT n20 5825MHz Ant1




Duty Cycle NVNT n40 5190MHz Ant1




Duty Cycle NVNT n40 5230MHz Ant1




Duty Cycle NVNT n40 5755MHz Ant1




Duty Cycle NVNT n40 5795MHz Ant1




Duty Cycle NVNT ac20 5180MHz Ant1




Duty Cycle NVNT ac20 5200MHz Ant1




Duty Cycle NVNT ac20 5240MHz Ant1




Duty Cycle NVNT ac20 5745MHz Ant1




Duty Cycle NVNT ac20 5785MHz Ant1




Duty Cycle NVNT ac20 5825MHz Ant1




Duty Cycle NVNT ac40 5190MHz Ant1




Duty Cycle NVNT ac40 5230MHz Ant1




Duty Cycle NVNT ac40 5755MHz Ant1




Duty Cycle NVNT ac40 5795MHz Ant1




Duty Cycle NVNT ax20 5180MHz Ant1




Duty Cycle NVNT ax20 5200MHz Ant1




Duty Cycle NVNT ax20 5240MHz Ant1




Duty Cycle NVNT ax20 5745MHz Ant1




Duty Cycle NVNT ax20 5785MHz Ant1




Duty Cycle NVNT ax20 5825MHz Ant1




Duty Cycle NVNT ax40 5190MHz Ant1



Duty Cycle NVNT ax40 5230MHz Ant1



Duty Cycle NVNT ax40 5755MHz Ant1



Duty Cycle NVNT ax40 5795MHz Ant1

Maximum Conducted Output Power


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted(dBm)	Verdict
NVNT	a	5180	Ant1	14.76	14.76	0.02992	24	Pass
NVNT	a	5200	Ant1	14.44	14.44	0.0278	24	Pass
NVNT	a	5240	Ant1	15.11	15.11	0.03243	24	Pass
NVNT	a	5745	Ant1	14.22	14.22	0.02642	30	Pass
NVNT	a	5785	Ant1	14.12	14.12	0.02582	30	Pass
NVNT	a	5825	Ant1	13.97	13.97	0.02495	30	Pass
NVNT	n20	5180	Ant1	13.8	13.8	0.02399	24	Pass
NVNT	n20	5200	Ant1	13.37	13.37	0.02173	24	Pass
NVNT	n20	5240	Ant1	13.08	13.08	0.02032	24	Pass
NVNT	n20	5745	Ant1	13.21	13.21	0.02094	30	Pass
NVNT	n20	5785	Ant1	13.1	13.1	0.02042	30	Pass
NVNT	n20	5825	Ant1	13.09	13.09	0.02037	30	Pass
NVNT	n40	5190	Ant1	12.41	12.41	0.01742	24	Pass
NVNT	n40	5230	Ant1	12.67	12.67	0.01849	24	Pass
NVNT	n40	5755	Ant1	12.41	12.41	0.01742	30	Pass
NVNT	n40	5795	Ant1	11.64	11.64	0.01459	30	Pass
NVNT	ac20	5180	Ant1	12.75	12.75	0.01884	24	Pass
NVNT	ac20	5200	Ant1	12.31	12.31	0.01702	24	Pass
NVNT	ac20	5240	Ant1	13.03	13.03	0.02009	24	Pass
NVNT	ac20	5745	Ant1	12.2	12.2	0.0166	30	Pass
NVNT	ac20	5785	Ant1	12.24	12.24	0.01675	30	Pass
NVNT	ac20	5825	Ant1	12.07	12.07	0.01611	30	Pass
NVNT	ac40	5190	Ant1	12.36	12.36	0.01722	24	Pass
NVNT	ac40	5230	Ant1	12.66	12.66	0.01845	24	Pass
NVNT	ac40	5755	Ant1	11.61	11.61	0.01449	30	Pass
NVNT	ac40	5795	Ant1	10.65	10.65	0.01161	30	Pass
NVNT	ax20	5180	Ant1	12.64	12.64	0.01837	24	Pass
NVNT	ax20	5200	Ant1	12.28	12.28	0.0169	24	Pass
NVNT	ax20	5240	Ant1	12.95	12.95	0.01972	24	Pass
NVNT	ax20	5745	Ant1	12.29	12.29	0.01694	30	Pass
NVNT	ax20	5785	Ant1	11.33	11.33	0.01358	30	Pass
NVNT	ax20	5825	Ant1	11.18	11.18	0.01312	30	Pass
NVNT	ax40	5190	Ant1	11.52	11.52	0.01419	24	Pass
NVNT	ax40	5230	Ant1	11.87	11.87	0.01538	24	Pass
NVNT	ax40	5755	Ant1	11.79	11.79	0.0151	30	Pass
NVNT	ax40	5795	Ant1	11.09	11.09	0.01285	30	Pass

-26dB Bandwidth


Condition	Mode	Frequency (MHz)	Antenna	-26 dB Bandwidth (MHz)
NVNT	a	5180	Ant1	27.46
NVNT	a	5200	Ant1	26.87
NVNT	a	5240	Ant1	25.99
NVNT	n20	5180	Ant1	27.32
NVNT	n20	5200	Ant1	27.17
NVNT	n20	5240	Ant1	27.8
NVNT	n40	5190	Ant1	47.93
NVNT	n40	5230	Ant1	47.78
NVNT	ac20	5180	Ant1	27.45
NVNT	ac20	5200	Ant1	27.84
NVNT	ac20	5240	Ant1	27.94
NVNT	ac40	5190	Ant1	48.01
NVNT	ac40	5230	Ant1	47.89
NVNT	ax20	5180	Ant1	25.66
NVNT	ax20	5200	Ant1	28.53
NVNT	ax20	5240	Ant1	27.7
NVNT	ax40	5190	Ant1	45.09
NVNT	ax40	5230	Ant1	46.15




-26dB Bandwidth NVNT a 5180MHz Ant1




-26dB Bandwidth NVNT a 5200MHz Ant1



-26dB Bandwidth NVNT a 5240MHz Ant1




-26dB Bandwidth NVNT n20 5180MHz Ant1




-26dB Bandwidth NVNT n20 5200MHz Ant1




-26dB Bandwidth NVNT n20 5240MHz Ant1




-26dB Bandwidth NVNT n40 5190MHz Ant1



-26dB Bandwidth NVNT n40 5230MHz Ant1



-26dB Bandwidth NVNT ac20 5180MHz Ant1



-26dB Bandwidth NVNT ac20 5200MHz Ant1