



REPORT No.: SZ26070489W02

TEST REPORT

APPLICANT : Shenzhen Sonoff Technologies Co.,Ltd.

PRODUCT NAME : Matter Over WiFi Human Presence Sensor

MODEL NAME : SNWF-06P24

BRAND NAME : SONOFF

FCC ID : 2APN5-SNWF06P24

STANDARD(S) : 47 CFR Part 15 Subpart C

RECEIPT DATE : 2026-08-05

TEST DATE : 2026-08-10 to 2026-08-28

ISSUE DATE : 2026-09-04



Edited by:

Zeng Xiaoying
Zeng Xiaoying (Rapporteur)

Approved by:

Shen Junsheng
Shen Junsheng (Supervisor)

NOTE: This document is issued by Shenzhen Morlab Communications Technology Co., Ltd., the test report shall not be reproduced except in full without prior written permission of the company. The test results apply only to the particular sample(s) tested and to the specific tests carried out which is available on request for validation and information confirmed at our website.

MORLAB

Shenzhen Morlab Communications Technology Co., Ltd.
FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road,
Block67, BaoAn District, ShenZhen, GuangDong Province, P. R. China

Tel: 86-755-36698555

Http://www.morlab.cn

Fax: 86-755-36698525

E-mail: service@morlab.cn





DIRECTORY

1. Summary of Test Result	4
1.1. Testing Applied Standards	4
1.2. Test Equipment List	5
1.3. Measurement Uncertainty	7
1.4. Testing Laboratory	7
2. General Description	8
2.1. Information of Applicant and Manufacturer	8
2.2. Information of EUT	8
2.3. Channel List of EUT	9
2.4. Test Configuration of EUT	10
2.5. Test Conditions	10
2.6. Test Setup Layout Diagram	11
3. Test Results	14
3.1. Antenna Requirement	14
3.2. Duty Cycle of Test Signal	15
3.3. Maximum Peak and Average Conducted Output Power	16
3.4. 6 dB Bandwidth	17
3.5. Conducted Spurious Emissions and Band Edge	18
3.6. Power Spectral Density	19
3.7. Conducted Emission	20
3.8. Restricted Frequency Bands	21
3.9. Radiated Emission	22
Annex A Test Data and Result	24
Notes	89



REPORT No.: SZ26070489W02

Change History		
Version	Date	Reason for change
1.0	2026-09-04	First edition



1. Summary of Test Result

No.	Section	Description	Test Date	Test Engineer	Result	Remark
1	15.203	Antenna Requirement	N/A	N/A	PASS	/
2	N/A	Duty Cycle of Test Signal	Aug. 10&28, 2026	Lin Haoyang	PASS	/
3	15.247(b)	Maximum Peak Conducted Output Power	Aug. 10&28, 2026	Lin Haoyang	PASS	/
4	15.247(b)	Maximum Average Conducted Output Power	Aug. 10&28, 2026	Lin Haoyang	PASS	/
5	15.247(a)	Bandwidth	Aug. 10&28, 2026	Lin Haoyang	PASS	/
6	15.247(d)	Conducted Spurious Emission and Band Edge	Aug. 10&28, 2026	Lin Haoyang	PASS	/
7	15.247(e)	Power Spectral Density	Aug. 10&28, 2026	Lin Haoyang	PASS	/
8	15.207	Conducted Emission	Aug. 13, 2026	Wang Yapeng	PASS	/
9	15.247(d)	Restricted Frequency Bands	Aug. 06, 2026	Li Hanbin	PASS	/
10	15.209, 15.247(d)	Radiated Emission	Aug. 06&17, 2026	Li Hanbin	PASS	/

Note 1: The tests were performed according to the method of measurements prescribed in ANSI C63.10-2020 and KDB 558074 D01 v05r02.

Note 2: Any additions, deviation, or exclusions from the method shall be noted in the “Remark”.

1.1. Testing Applied Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- 47 CFR Part 15 Subpart C Radio Frequency Devices



1.2. Test Equipment List

1.2.1 Conducted Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
EXA Signal Analyzer	MY53470836	N9010A	Agilent	2025.12.23	2026.12.22
Power Sensor	MY54180008	U2021XA	Agilent	2025.09.03	2026.09.02
Attenuator	MTJ6004-20	VAT-10+	MTJ Cooperation	N/A	N/A
RF Cable (30MHz-26GHz)	CB01	RF01	Morlab	N/A	N/A
SMA Connector	CN01	RF03	HUBER-SUHNER	N/A	N/A

1.2.2 Conducted Emission Test Equipment

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Receiver	101052	ESPI	R&S	2026.05.07	2027.05.06
LISN	103131	ENV 216	R&S	2026.03.18	2027.03.17
RF Coaxial Cable (DC-100MHz)	BNC	MRE04	Qualwave	2026.05.06	2027.05.05

1.2.3 List of Software Used

Description	Manufacturer	Software Version
Test System	MaiWei	2.0.0.0
JS32-RE	Tonscend	5.0.0
TS+ -[JS32-CE]	Tonscend	2.5.0.0

**1.2.4 Radiated Test Equipment**

Equipment	Serial No.	Type	Manufacturer	Cal. Date	Due Date
Signal Analyzer	MY56060145	N9020A	Agilent	2026.04.28	2027.04.27
Test Antenna - Bi-Log	9163-274	VULB 9163	Schwarzbeck	2026.06.28	2027.06.27
Test Antenna - Loop	1519-022	FMZB1519	Schwarzbeck	2026.05.09	2027.05.08
Test Antenna – Horn	01774	BBHA 9120D	Schwarzbeck	2026.05.30	2027.05.29
Test Antenna – Horn	BBHA9170 #773	BBHA9170	Schwarzbeck	2026.05.30	2027.05.29
Preamplifier (10MHz-6GHz)	46732	S10M100L38 02	LUCIX CORP.	2026.05.07	2027.05.06
Preamplifier (2GHz-18GHz)	61171/61172	S020180L32 03	LUCIX CORP.	2026.05.07	2027.05.06
Preamplifier (18GHz-40GHz)	DS77209	DCLNA0118-40C-S	Decentest	2026.05.07	2027.05.06
RF Coaxial Cable (DC-18GHz)	MRE001	PE330	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	MRE002	CLU18	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	MRE003	CLU18	Pasternack	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290045	QA360-40-KK-0.5	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-40GHz)	22290046	QA360-40-KKF-2	Qualwave	2025.09.03	2026.09.02
RF Coaxial Cable (DC-18GHz)	22120181	QA500-18-NN-5	Qualwave	2025.09.03	2026.09.02
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.06.21	2028.06.20
Anechoic Chamber	N/A	9m*6m*6m	CRT	2025.04.19	2028.04.18



1.3. Measurement Uncertainty

Test Items	Uncertainty	Remark
Peak Output Power	$\pm 2.22\text{dB}$	Confidence levels of 95%
Power Spectral Density	$\pm 2.22\text{dB}$	Confidence levels of 95%
Bandwidth	$\pm 5\%$	Confidence levels of 95%
Conducted Spurious Emission	$\pm 2.77\text{dB}$	Confidence levels of 95%
Restricted Frequency Bands	$\pm 5\%$	Confidence levels of 95%
Radiated Emission	$\pm 2.95\text{dB}$	Confidence levels of 95%
Conducted Emission	$\pm 2.44\text{dB}$	Confidence levels of 95%

1.4. Testing Laboratory

Laboratory Name:	Shenzhen Morlab Communications Technology Co., Ltd.
Laboratory Address:	FL.1-3, Building A, FeiYang Science Park, No.8 LongChang Road, Block 67, BaoAn District, ShenZhen, GuangDong Province, P. R. China
Telephone:	+86 755 36698555
Facsimile:	+86 755 36698525
FCC Designation Number:	CN1192
FCC Test Firm Registration Number:	226174



2. General Description

2.1. Information of Applicant and Manufacturer

Applicant:	Shenzhen Sonoff Technologies Co.,Ltd.
Applicant Address:	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China
Manufacturer:	Shenzhen Sonoff Technologies Co.,Ltd.
Manufacturer Address:	3F & 6F, Bldg A, No. 663, Bulong Rd, Shenzhen, Guangdong, China

2.2. Information of EUT

Product Name:	Matter Over WiFi Human Presence Sensor
Sample No.:	2#, 4#, 5#
Hardware Version:	V1.0
Software Version:	V0.1.0
Modulation Technology:	DSSS, OFDM
Modulation Type:	Refer to section 2.4.1
Wireless Technology:	802.11b, 802.11g, 802.11n (HT20)
Operating Frequency Range:	2412MHz-2472MHz
Antenna Type:	Ceramic Antenna
Antenna Gain:	-1.59dBi

Note 1: The EUT description presented in the report are provided by applicant and/or manufacturer, and the test laboratory is not responsible for the accuracy of the information. For a more detailed description, please refer to Specification or User's Manual supplied by the applicant and/or manufacturer.



2.3.Channel List of EUT

Nominal Channel Bandwidth	Channel	Frequency (MHz)	Channel	Frequency (MHz)
20MHz	1	2412	8	2447
	2	2417	9	2452
	3	2422	10	2457
	4	2427	11	2462
	5	2432	12	2467
	6	2437	13	2472
	7	2442		

Note 1: The black bold channels were selected for test.

2.4. Test Configuration of EUT

2.4.1. Modulation Type and Data Rate of EUT

Mode	Bandwidth (MHz)	Modulation Technology	Modulation Type	Data Rate
802.11b	20	DSSS	DBPSK	1/2/5.5/11Mbps
			DQPSK	
			CCK	
802.11g	20	OFDM	BPSK	6/9/12/18/24/36/48/54Mbps
			QPSK	
			16QAM	
			64QAM	
802.11n	20 (HT20)	OFDM	BPSK	MCS0~MCS7
			QPSK	
			16QAM	
			64QAM	

Note1: The worst-case mode (bold face) in all data rates has been determined during the pre-scan, only the test data of the worst-case were recorded in this report.


Note2: The RF signal transmission of EUT is controlled by the build-in engineering mode which is provided by the manufacturer. The recorded power setting value is the maximum that the engineering mode has configuration during testing.

2.5. Test Conditions


Temperature (°C):	15-35
Relative Humidity (%):	30-60
Atmospheric Pressure (kPa):	86-106

2.6. Test Setup Layout Diagram

2.6.1. Conducted Measurement




2.6.2. Conducted Emission Measurement




2.6.3.Radiation Measurement


1) For radiated emissions from 9kHz to 30MHz



2) For radiated emissions from 30MHz to 1GHz



3) For radiated emissions above 1GHz





3. Test Results

3.1. Antenna Requirement

3.1.1. Requirement

According to FCC 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

3.1.2. Test Result

Antenna location	Antenna Type	Coupling Method
☒ Internal ☐ External	☐ FPC Antenna ☐ Spring Antenna ☒ Ceramic Antenna ☐ Integrated Antenna ☐ Dipole Antenna ☐ PCB Antenna ☐ PIFA Antenna ☐ On-board Antenna	☐ I-PEX Connector ☐ SMA Connector ☐ RP-SMA Connector ☐ Metal Shrapnel ☒ Layout

3.2. Duty Cycle of Test Signal

3.2.1. Requirement

Preferably, all measurements of maximum conducted (average) output power will be performed with the EUT transmitting continuously (i.e., with a duty cycle of greater than or equal to 98%). When continuous operation cannot be realized, then the use of sweep triggering/signal gating techniques can be used to ensure that measurements are made only during transmissions at the maximum power control level. Such sweep triggering/signal gating techniques will require knowledge of the minimum transmission duration (T) over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation. Sweep triggering/signal gating techniques can then be used if the measurement/sweep time of the analyzer can be set such that it does not exceed T at any time that data are being acquired (i.e., no transmitter OFF-time is to be considered).

When continuous transmission cannot be achieved and sweep triggering/signal gating cannot be implemented, alternative procedures are provided that can be used to measure the average power; however, they will require an additional measurement of the transmitter duty cycle (D). Within this sub clause, the duty cycle refers to the fraction of time over which the transmitter is ON and is transmitting at its maximum power control level. The duty cycle is considered to be constant if variations are less than $\pm 2\%$; otherwise, the duty cycle is considered to be non constant.

3.2.2. Test Result

Refer to Annex A.1 in this report.



3.3. Maximum Peak and Average Conducted Output Power

3.3.1. Requirement

According to FCC section 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: The maximum conducted output power of the intentional radiator shall not exceed 1 Watt.

3.3.2. Test Procedures

The EUT (Equipment under the test) which is coupled to the USB Wideband Power Sensor; the RF load attached to the EUT antenna terminal is 50Ohm; the path loss as the factor is calibrated to correct the reading.

3.3.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.3.4. Test Result

Refer to Annex A.2 and A.3 in this report.



3.4.6 dB Bandwidth

3.4.1.Requirement

According to FCC section 15.247(a) (2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

3.4.1.Test Procedures

KDB 558074 Section 8.2 was used in order to prove compliance.

3.4.2.Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.4.3.Test Result

Refer to Annex A.4 in this report.



3.5. Conducted Spurious Emissions and Band Edge

3.5.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

3.5.2. Test Procedures

KDB 558074 Section 8.5 and 8.7 was used in order to prove compliance.

3.5.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.5.4. Test Result

Refer to Annex A.5 and A.6 in this report.



3.6. Power Spectral Density

3.6.1. Requirement

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

3.6.2. Test Procedures

The measured power spectral density was calculated by the reading of the spectrum analyzer and calibration. Following is the test procedure for PSD test:

- a) Set analyzer center frequency to channel center frequency
- b) Set span to 1.5 times DTS
- c) Set RBW to 30kHz
- d) Set VBW to 100kHz
- e) Detector = peak
- f) Sweep time = auto couple
- g) Trace mode = max hold
- h) Allow trace to fully stabilize
- i) Use the peak marker function to determine the maximum amplitude level and recorded as PD
- j) Use below formula to calculate the Conducted PSD value that at specified RBW:

Conducted PSD = PD - 10lg(30k/3k)

3.6.3. Test Setup Layout

Refer to chapter 2.6.1 in this report.

3.6.4. Test Result

Refer to Annex A.7 in this report.

3.7. Conducted Emission

3.7.1. Requirement

According to FCC section 15.207, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150kHz to 30MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency Range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
5 - 30	60	50

Note:

- (a) The lower limit shall apply at the band edges.
- (b) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50MHz.

3.7.2. Test Procedures

The Table-top EUT was placed upon a non-metallic table 0.8m above the horizontal metal reference ground plane. EUT was connected to LISN and LISN was connected to reference Ground Plane. EUT was 80cm from LISN. The set-up and test methods were according to ANSI C63.10.

3.7.3. Test Setup Layout

Refer to chapter 2.6.2 in this report.

3.7.4. Test Result

Refer to Annex A.8 in this report.

3.8. Restricted Frequency Bands

3.8.1. Requirement

According to FCC section 15.247(d), in any 100kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in 15.205(a), must also comply with the radiated emission limits specified in 15.209(a).

3.8.2. Test Procedures

The EUT is located in a 3m Semi-Anechoic Chamber; the antenna factors, cable loss and so on of the site as factors are calculated to correct the reading.

For the Test Antenna:

Test Antenna is 3m away from the EUT. Test Antenna height is varied from 1m to 4m above the ground to determine the maximum value of the field strength.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1\text{GHz}$, 100 kHz for $f < 1\text{GHz}$

VBW = 3 MHz

Sweep = auto

Detector function = peak/average

Trace = max hold

Allow the trace to stabilize

3.8.3. Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.8.4. Test Result

Refer to Annex A.9 in this report.

3.9. Radiated Emission

3.9.1. Requirement

According to FCC section 15.247(d), radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength ($\mu\text{V}/\text{m}$)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note1: For above 1000MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.

Note2: For above 1000MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK). In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), also should comply with the radiated emission limits specified in Section 15.209(a)(above table).



3.9.2.Test Procedures

The EUT is placed on a non-conducting table 80 cm above the ground plane for measurement below 1GHz; 1.5 m above the ground plane for measurement above 1GHz. The antenna to EUT distance is 3meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 30MHz, the emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9kHz-90 kHz, 110kHz-490 kHz. Radiated emission limits in these two bands are based on measurements employing an average detector.

For measurements below 1GHz the resolution bandwidth is set to 100kHz for peak detection measurements or 120kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1GHz the resolution bandwidth is set to 1MHz, the video band width is set to 3MHz for peak measurements and as applicable for average measurements.

The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions. For measurements above 1 GHz, keeping the measurement antenna aimed at the source of emissions at each frequency of significant emissions, with polarization oriented for maximum response.

3.9.3.Test Setup Layout

Refer to chapter 2.6.3 in this report.

3.9.4.Test Result


Refer to Annex A.10 in this report.




Annex A Test Data and Result

A.1. Duty Cycle of Test Signal


Condition	Mode	Frequency (MHz)	Antenna	Duty Cycle (%)	Correction Factor (dB)	1/T (kHz)
NVNT	b	2412	Ant1	92.48	0.34	0.99
NVNT	b	2442	Ant1	92.31	0.35	0.99
NVNT	b	2472	Ant1	92.49	0.34	0.99
NVNT	g	2412	Ant1	94.19	0.26	1.62
NVNT	g	2442	Ant1	94.19	0.26	1.62
NVNT	g	2472	Ant1	94.19	0.26	1.62
NVNT	n20	2412	Ant1	94.15	0.26	1.63
NVNT	n20	2442	Ant1	94.15	0.26	1.63
NVNT	n20	2472	Ant1	94.15	0.26	1.63




Duty Cycle NVNT b 2412MHz Ant1




Duty Cycle NVNT b 2442MHz Ant1




Duty Cycle NVNT b 2472MHz Ant1




Duty Cycle NVNT g 2412MHz Ant1




Duty Cycle NVNT g 2442MHz Ant1




Duty Cycle NVNT g 2472MHz Ant1



Duty Cycle NVNT n20 2412MHz Ant1




Duty Cycle NVNT n20 2442MHz Ant1




Duty Cycle NVNT n20 2472MHz Ant1

**A.2. Maximum Peak Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	20.96	0	20.96	0.12474	30	Pass
NVNT	b	2442	Ant1	19.31	0	19.31	0.08531	30	Pass
NVNT	b	2472	Ant1	19.22	0	19.22	0.08356	30	Pass
NVNT	g	2412	Ant1	24.05	0	24.05	0.2541	30	Pass
NVNT	g	2442	Ant1	23.23	0	23.23	0.21038	30	Pass
NVNT	g	2472	Ant1	22.95	0	22.95	0.19724	30	Pass
NVNT	n20	2412	Ant1	22.83	0	22.83	0.19187	30	Pass
NVNT	n20	2442	Ant1	22	0	22	0.15849	30	Pass
NVNT	n20	2472	Ant1	21.59	0	21.59	0.14421	30	Pass




Peak Power NVNT b 2412MHz Ant1



Peak Power NVNT b 2442MHz Ant1




Peak Power NVNT b 2472MHz Ant1




Peak Power NVNT g 2412MHz Ant1




Peak Power NVNT g 2442MHz Ant1




Peak Power NVNT g 2472MHz Ant1



Peak Power NVNT n20 2412MHz Ant1




Peak Power NVNT n20 2442MHz Ant1




**A.3. Maximum Average Conducted Output Power**


Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Duty Factor (dB)	Total Conducted Power (dBm)	Total Conducted Power (W)	Limit Conducted (dBm)	Verdict
NVNT	b	2412	Ant1	17.75	0.34	18.09	0.06442	30	Pass
NVNT	b	2442	Ant1	16.35	0.35	16.7	0.04677	30	Pass
NVNT	b	2472	Ant1	16.17	0.34	16.51	0.04477	30	Pass
NVNT	g	2412	Ant1	16.25	0.26	16.51	0.04477	30	Pass
NVNT	g	2442	Ant1	15.45	0.26	15.71	0.03724	30	Pass
NVNT	g	2472	Ant1	15.16	0.26	15.42	0.03483	30	Pass
NVNT	n20	2412	Ant1	15.1	0.26	15.36	0.03436	30	Pass
NVNT	n20	2442	Ant1	14.23	0.26	14.49	0.02812	30	Pass
NVNT	n20	2472	Ant1	13.97	0.26	14.23	0.02649	30	Pass




Average Power NVNT b 2412MHz Ant1




Average Power NVNT b 2442MHz Ant1




Average Power NVNT b 2472MHz Ant1




Average Power NVNT g 2412MHz Ant1




Average Power NVNT g 2442MHz Ant1




Average Power NVNT g 2472MHz Ant1



Average Power NVNT n20 2412MHz Ant1



Average Power NVNT n20 2442MHz Ant1



**A.4. 6 dB Bandwidth**

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	b	2412	Ant1	10.03	0.5	Pass
NVNT	b	2442	Ant1	9.51	0.5	Pass
NVNT	b	2472	Ant1	10.03	0.5	Pass
NVNT	g	2412	Ant1	16.3	0.5	Pass
NVNT	g	2442	Ant1	16.32	0.5	Pass
NVNT	g	2472	Ant1	16.32	0.5	Pass
NVNT	n20	2412	Ant1	17.29	0.5	Pass
NVNT	n20	2442	Ant1	17.53	0.5	Pass
NVNT	n20	2472	Ant1	16.68	0.5	Pass



-6dB Bandwidth NVNT b 2412MHz Ant1




-6dB Bandwidth NVNT b 2442MHz Ant1




-6dB Bandwidth NVNT b 2472MHz Ant1




-6dB Bandwidth NVNT g 2412MHz Ant1




-6dB Bandwidth NVNT g 2442MHz Ant1




-6dB Bandwidth NVNT g 2472MHz Ant1



-6dB Bandwidth NVNT n20 2412MHz Ant1



-6dB Bandwidth NVNT n20 2442MHz Ant1




**A.5. Conducted Spurious Emissions**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-37.5	-20	Pass
NVNT	b	2442	Ant1	-37.7	-20	Pass
NVNT	b	2472	Ant1	-36.26	-20	Pass
NVNT	g	2412	Ant1	-34.47	-20	Pass
NVNT	g	2442	Ant1	-33.95	-20	Pass
NVNT	g	2472	Ant1	-33.31	-20	Pass
NVNT	n20	2412	Ant1	-33	-20	Pass
NVNT	n20	2442	Ant1	-33.34	-20	Pass
NVNT	n20	2472	Ant1	-31.37	-20	Pass




Tx. Spurious NVNT b 2412MHz Ant1 Ref



Tx. Spurious NVNT b 2412MHz Ant1 Emission




Tx. Spurious NVNT b 2442MHz Ant1 Ref




Tx. Spurious NVNT b 2442MHz Ant1 Emission




Tx. Spurious NVNT b 2472MHz Ant1 Ref




Tx. Spurious NVNT b 2472MHz Ant1 Emission




Tx. Spurious NVNT g 2412MHz Ant1 Ref




Tx. Spurious NVNT g 2412MHz Ant1 Emission




Tx. Spurious NVNT g 2442MHz Ant1 Ref




Tx. Spurious NVNT g 2442MHz Ant1 Emission




Tx. Spurious NVNT g 2472MHz Ant1 Ref




Tx. Spurious NVNT g 2472MHz Ant1 Emission




Tx. Spurious NVNT n20 2412MHz Ant1 Ref




Tx. Spurious NVNT n20 2412MHz Ant1 Emission




Tx. Spurious NVNT n20 2442MHz Ant1 Ref



Tx. Spurious NVNT n20 2442MHz Ant1 Emission



Tx. Spurious NVNT n20 2472MHz Ant1 Ref



Tx. Spurious NVNT n20 2472MHz Ant1 Emission

**A.6. Band Edge**

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	b	2412	Ant1	-44.28	-20	Pass
NVNT	b	2472	Ant1	-45.22	-20	Pass
NVNT	g	2412	Ant1	-34.21	-20	Pass
NVNT	g	2472	Ant1	-33.22	-20	Pass
NVNT	n20	2412	Ant1	-36.26	-20	Pass
NVNT	n20	2472	Ant1	-33.61	-20	Pass




Band Edge NVNT b 2412MHz Ant1 Ref



Band Edge NVNT b 2412MHz Ant1 Emission



Band Edge NVNT b 2472MHz Ant1 Ref




Band Edge NVNT b 2472MHz Ant1 Emission




Band Edge NVNT g 2412MHz Ant1 Ref



Band Edge NVNT g 2412MHz Ant1 Emission




Band Edge NVNT g 2472MHz Ant1 Ref



Band Edge NVNT g 2472MHz Ant1 Emission




Band Edge NVNT n20 2412MHz Ant1 Ref



Band Edge NVNT n20 2412MHz Ant1 Emission





Band Edge NVNT n20 2472MHz Ant1 Ref



Band Edge NVNT n20 2472MHz Ant1 Emission

**A.7. Power Spectral Density**

Condition	Mode	Frequency (MHz)	Antenna	Conducted PSD (dBm/3kHz)	Duty Factor (dB)	Total PSD (dBm/3kHz)	Limit (dBm/3kHz)	Verdict
NVNT	b	2412	Ant1	-1.51	0	-1.51	8	Pass
NVNT	b	2442	Ant1	-3.01	0	-3.01	8	Pass
NVNT	b	2472	Ant1	-3.5	0	-3.5	8	Pass
NVNT	g	2412	Ant1	-9.3	0	-9.3	8	Pass
NVNT	g	2442	Ant1	-10.5	0	-10.5	8	Pass
NVNT	g	2472	Ant1	-10.45	0	-10.45	8	Pass
NVNT	n20	2412	Ant1	-10.37	0	-10.37	8	Pass
NVNT	n20	2442	Ant1	-11.26	0	-11.26	8	Pass
NVNT	n20	2472	Ant1	-11.5	0	-11.5	8	Pass





PSD NVNT b 2472MHz Ant1




PSD NVNT g 2412MHz Ant1




PSD NVNT g 2442MHz Ant1




PSD NVNT g 2472MHz Ant1



PSD NVNT n20 2412MHz Ant1



PSD NVNT n20 2442MHz Ant1



PSD NVNT n20 2472MHz Ant1



A.8. Conducted Emission

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Set RBW=9kHz, VBW=30kHz. Refer to recorded points and plots below.

Note: Both of the test voltage AC 120V/60Hz and AC 230V/50Hz were considered and tested respectively, only the results of the worst case AC 120V/60Hz were recorded in this report.

A. Test Setup:

Test Mode: EUT+Notebook+Notebook adapter+USB cable+Serial port board+WIFI TX

Test voltage: AC 120V/60Hz


The measurement results are obtained as below:

$$E \text{ [dB}\mu\text{V]} = U_R + L_{\text{Cable loss [dB]} + A_{\text{Factor}}$$

U_R : Receiver Reading


A_{Factor} : Voltage division factor of LISN

B. Test Plot:



(L Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1545	49.42	34.14	65.75	55.75	Line	PASS
2	0.2220	38.02	25.01	62.74	52.74		PASS
3	0.7260	30.51	27.38	56.00	46.00		PASS
4	4.8656	24.21	18.55	56.00	46.00		PASS
5	13.8070	31.42	26.06	60.00	50.00		PASS
6	23.8656	28.80	23.73	60.00	50.00		PASS



(N Phase)

No.	Fre. (MHz)	Emission Level (dBμV)		Limit (dBμV)		Power-line	Verdict
		Quai-peak	Average	Quai-peak	Average		
1	0.1635	47.76	31.87	65.28	55.28	Neutral	PASS
2	0.1815	44.51	30.39	64.42	54.42		PASS
3	0.1995	41.01	27.66	63.63	53.63		PASS
4	0.7259	30.87	27.83	56.00	46.00		PASS
5	14.2225	31.38	26.01	60.00	50.00		PASS
6	23.1382	29.34	24.61	60.00	50.00		PASS


A.9. Restricted Frequency Bands

Note 1: Restricted Frequency Bands were performed when antenna was at vertical and horizontal polarity, and only the worse test condition was recorded in this test report.

Note 2 All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.

802.11b Mode


Plot for Channel 1



Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2323.62	9.2	46.44	37.220	54.00	7.56	12	AV	Horizontal	PASS
2338.45	21.8	59.10	37.350	74.00	14.90	166	PK	Horizontal	PASS
2366.16	21.6	59.10	37.470	74.00	14.90	327	PK	Horizontal	PASS
2366.28	9.2	46.71	37.470	54.00	7.29	284	AV	Horizontal	PASS
2385.87	12.2	49.71	37.490	54.00	4.29	318	AV	Horizontal	PASS
2387.21	23.4	60.86	37.490	74.00	13.14	294	PK	Horizontal	PASS



Plot for Channel 13



Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2485.66	12.1	50.38	38.270	54.00	3.62	21	AV	Horizontal	PASS
2487.32	22.8	61.08	38.270	74.00	12.92	336	PK	Horizontal	PASS
2491.52	8.8	47.05	38.260	54.00	6.95	226	AV	Horizontal	PASS
2491.91	21.3	59.55	38.260	74.00	14.45	260	PK	Horizontal	PASS
2495.97	8.7	46.97	38.260	54.00	7.03	324	AV	Horizontal	PASS
2497.50	21.0	59.23	38.250	74.00	14.77	245	PK	Horizontal	PASS



A.10. Radiated Emission

According to ANSI C63.10, because of peak detection will yield amplitudes equal to or greater than amplitudes measured with the quasi-peak (or average) detector, the measurement data from a spectrum analyzer peak detector will represent the worst-case results, if the peak measured value complies with the quasi-peak (or average) limit, it is unnecessary to perform an quasi-peak measurement (or average).

The measurement results are obtained as below:

$$E [\text{dB}\mu\text{V/m}] = U_R + A_T + A_{\text{Factor}} [\text{dB}]; A_T = L_{\text{Cable loss}} [\text{dB}] - G_{\text{preamp}} [\text{dB}]$$

A_T : Total correction Factor except Antenna

U_R : Receiver Reading

G_{preamp} : Preamplifier Gain

A_{Factor} : Antenna Factor at 3m

During the test, the total correction Factor A_T and A_{Factor} were built in test software.

Note1: All radiated emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Note 2: All test modes and bandwidth were considered and evaluated respectively by performing full test, only the worst data were recorded for each bandwidth.


Note 3: For the frequency, which started from 9kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit was not recorded.

Note 4: For the frequency, which started from 18GHz to 10th harmonic of the highest frequency, was pre-scanned and the result which was 20dB lower than the limit was not recorded.




802.11b Mode

Plot for Channel 1




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
51.05	49.7	21.64	-28.070	40.00	18.36	4	PK	Horizontal	PASS
134.72	62.7	30.87	-31.800	43.50	12.63	345	PK	Horizontal	PASS
214.07	63.2	34.26	-28.960	43.50	9.24	60	PK	Horizontal	PASS
301.32	50.7	25.34	-25.350	46.00	20.66	268	PK	Horizontal	PASS
560.23	45.6	26.95	-18.600	46.00	19.05	4	PK	Horizontal	PASS
946.99	38.6	27.53	-11.040	46.00	18.47	143	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2410.28	58.3	63.63	5.370	-	-	311	PK	Horizontal	NA
2411.48	50.3	55.70	5.390	-	-	306	AV	Horizontal	NA
4824.48	55.6	50.62	-4.990	74.00	23.38	200	PK	Horizontal	PASS
4824.48	50.9	45.95	-4.990	54.00	8.05	9	AV	Horizontal	PASS
7234.84	50.0	54.57	4.590	-	-	49	PK	Horizontal	NA
7235.69	42.9	47.51	4.580	-	-	37	AV	Horizontal	NA
12005.83	36.3	50.53	14.230	54.00	3.47	227	AV	Horizontal	PASS
12005.83	40.6	54.84	14.230	74.00	19.16	240	PK	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
32.57	62.8	32.36	-30.470	40.00	7.64	67	PK	Vertical	PASS
56.34	55.6	27.53	-28.020	40.00	12.47	313	PK	Vertical	PASS
104.31	58.8	29.30	-29.520	43.50	14.20	202	PK	Vertical	PASS
213.97	57.4	28.46	-28.980	43.50	15.04	160	PK	Vertical	PASS
530.64	45.0	26.04	-18.910	46.00	19.96	30	PK	Vertical	PASS
976.19	38.4	27.51	-10.930	54.00	26.49	227	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2411.48	47.7	53.06	5.390	-	-	30	AV	Vertical	NA
2411.88	55.4	60.83	5.400	-	-	351	PK	Vertical	NA
4824.05	59.6	54.57	-5.000	74.00	19.43	37	PK	Vertical	PASS
4824.48	54.5	49.55	-4.990	54.00	4.45	50	AV	Vertical	PASS
7236.12	48.6	53.20	4.570	-	-	118	PK	Vertical	NA
7237.41	42.0	46.52	4.550	-	-	105	AV	Vertical	NA
11416.53	40.3	54.40	14.090	74.00	19.60	197	PK	Vertical	PASS
12006.26	35.1	49.36	14.230	54.00	4.64	130	AV	Vertical	PASS

Plot for Channel 7




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
50.18	50.7	22.76	-27.920	40.00	17.24	13	PK	Horizontal	PASS
138.69	63.2	31.11	-32.080	43.50	12.39	335	PK	Horizontal	PASS
214.50	61.0	32.09	-28.900	43.50	11.41	44	PK	Horizontal	PASS
320.00	50.5	25.53	-25.010	46.00	20.47	210	PK	Horizontal	PASS
506.63	46.1	25.70	-20.400	46.00	20.30	3	PK	Horizontal	PASS
988.26	37.6	26.91	-10.710	54.00	27.09	205	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2441.49	41.9	47.78	5.840	-	-	290	AV	Horizontal	NA
2441.89	49.5	55.36	5.850	-	-	65	PK	Horizontal	NA
4884.05	57.2	52.19	-5.020	74.00	21.81	9	PK	Horizontal	PASS
4884.48	52.6	47.56	-5.030	54.00	6.44	330	AV	Horizontal	PASS
7326.98	50.6	54.91	4.320	74.00	19.09	209	PK	Horizontal	PASS
7326.98	44.7	49.03	4.320	54.00	4.97	236	AV	Horizontal	PASS
12005.83	40.6	54.78	14.230	74.00	19.22	224	PK	Horizontal	PASS
12006.26	36.7	50.97	14.230	54.00	3.03	224	AV	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
32.47	63.7	33.18	-30.470	40.00	6.82	174	PK	Vertical	PASS
50.18	55.9	27.93	-27.920	40.00	12.07	325	PK	Vertical	PASS
104.35	59.5	30.02	-29.490	43.50	13.48	9	PK	Vertical	PASS
213.29	55.9	26.81	-29.080	43.50	16.69	189	PK	Vertical	PASS
530.64	43.5	24.61	-18.910	46.00	21.39	60	PK	Vertical	PASS
967.12	38.4	27.14	-11.270	54.00	26.86	127	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)


Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2441.49	40.0	45.87	5.840	-	-	351	AV	Vertical	NA
2441.89	47.9	53.79	5.850	-	-	0	PK	Vertical	NA
4884.05	59.4	54.34	-5.020	74.00	19.66	37	PK	Vertical	PASS
4884.48	55.0	49.93	-5.030	54.00	4.07	64	AV	Vertical	PASS
7325.70	42.5	46.81	4.310	54.00	7.19	118	AV	Vertical	PASS
7325.70	48.6	52.94	4.310	74.00	21.06	118	PK	Vertical	PASS
12005.83	40.8	55.04	14.230	74.00	18.96	293	PK	Vertical	PASS
12006.26	36.3	50.57	14.230	54.00	3.43	118	AV	Vertical	PASS

Plot for Channel 13




(Antenna Horizontal, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
50.27	56.3	28.41	-27.930	40.00	11.59	58	PK	Horizontal	PASS
127.93	68.0	36.31	-31.690	43.50	7.19	63	PK	Horizontal	PASS
144.03	67.0	35.72	-31.270	43.50	7.78	109	PK	Horizontal	PASS
230.36	63.1	35.19	-27.950	46.00	10.81	6	PK	Horizontal	PASS
466.81	54.8	33.03	-21.750	46.00	12.97	6	PK	Horizontal	PASS
990.20	38.0	27.48	-10.510	54.00	26.52	3	PK	Horizontal	PASS




(Antenna Horizontal, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2490.70	35.4	41.27	5.860	54.00	12.73	20	AV	Horizontal	PASS
2494.30	44.5	50.30	5.850	74.00	23.70	20	PK	Horizontal	PASS
4944.06	58.8	53.94	-4.850	74.00	20.06	199	PK	Horizontal	PASS
4944.48	53.5	48.60	-4.850	54.00	5.40	199	AV	Horizontal	PASS
7415.70	44.9	49.64	4.700	54.00	4.36	227	AV	Horizontal	PASS
7415.70	51.7	56.40	4.700	74.00	17.60	240	PK	Horizontal	PASS
12005.40	40.5	54.75	14.230	74.00	19.25	212	PK	Horizontal	PASS
12005.83	36.5	50.70	14.230	54.00	3.30	212	AV	Horizontal	PASS



(Antenna Vertical, 30MHz to 1GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
34.03	63.8	33.90	-29.850	40.00	6.10	50	PK	Vertical	PASS
50.27	63.0	35.02	-27.930	40.00	4.98	306	PK	Vertical	PASS
144.17	64.2	32.95	-31.290	43.50	10.55	46	PK	Vertical	PASS
256.85	62.0	34.48	-27.500	46.00	11.52	86	PK	Vertical	PASS
456.68	56.5	34.95	-21.550	46.00	11.05	281	PK	Vertical	PASS
968.38	40.0	28.55	-11.430	54.00	25.45	46	PK	Vertical	PASS



(Antenna Vertical, 1GHz to 18GHz)

Frequency [MHz]	Reading [dBμV]	Level [dBμV/m]	Factor [dB/m]	Limit [dBμV/m]	Margin [dB]	Angle [°]	Detector	Polarity	Verdict
2473.89	40.7	46.63	5.900	-	-	147	PK	Vertical	NA
2491.10	32.3	38.15	5.860	54.00	15.85	20	AV	Vertical	PASS
4944.06	58.5	53.63	-4.850	74.00	20.37	255	PK	Vertical	PASS
4944.48	53.8	48.93	-4.850	54.00	5.07	269	AV	Vertical	PASS
7414.84	47.9	52.61	4.700	74.00	21.39	108	PK	Vertical	PASS
7418.27	40.7	45.38	4.690	54.00	8.62	81	AV	Vertical	PASS
12006.26	34.1	48.35	14.230	54.00	5.65	121	AV	Vertical	PASS
12495.70	40.0	54.84	14.870	74.00	19.16	269	PK	Vertical	PASS



Notes

1. The report shall have report stamp or our company stamp.
2. The report shall be invalid without all the signatures of the editor and approver.
3. The report shall not be changed.
4. Any objections must be raised to Morlab within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit.
5. Conformity declaration:
 - ☒ Morlab issues a statement of conformity based on the corresponding standards (default)
 - ☐ Morlab issues a statement of conformity based on the applicant requirement
6. Use of uncertainty of measurement for decisions on conformity (decision rule):

No decision rule is specified by the testing standard, when comparing the measurement result with the applicable limit according to the specification in that standard. The decisions on conformity are made without applying the measurement uncertainty ("simple acceptance" decision rule).

————— END OF REPORT —————