FCC Part 15C Test Report

FCC ID: 2APN7KING-A6

Product Name:	WIFI SOCKET
Trademark:	KINGART
Model Name :	KING-A6 KING-A8, KING-A9，KING-F6, KING-F8, KING-F9, KING-J1, KING-J2, KING-J3，KING-K6, KING-K8, KING-K9，KING-S6, KING-S8, KING-S9，KING-T6, KING-T8, KING-T9
Prepared For : Address :	**SHENZHEN KINGART TECHNOLOGY CO., LIMITED** No. 7th Fl, Bao Yi Building, 22-8 Wu Lian Rd, Long Gang District, 518000 Shenzhen, China
Prepared By : Address :	**Shenzhen BCTC Testing Co., Ltd.** BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
Test Date:	Apr. 09 - Apr. 13, 2018
Date of Report :	Apr. 13, 2018
Report No.:	BCTC-LH180400771E

TEST RESULT CERTIFICATION

Applicant's name..... : **SHENZHEN KINGART TECHNOLOGY CO., LIMITED**

Address..... : No. 7th Fl, Bao Yi Building, 22-8 Wu Lian Rd, Long Gang District, 518000 Shenzhen, China

Manufacture's Name..... : **SHENZHEN BIAO WANG TECHNOLOGY CO., LIMITED**

Address..... : No. 4th Fl, C buiding, Chun Yang Industrial Park Zhu Gu Xi Rd, Wu Lian Long Gang District, 518000, Shenzhen, China

Product description

Product name.....: WIFI SOCKET

Trademark.....: KINGART

Model and/or type reference : KING-A6

Standards..... : FCC Part15.247

ANSI C63.10:2013

This device described above has been tested by BCTC, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.

This report shall not be reproduced except in full, without the written approval of BCTC, this document may be altered or revised by BCTC, personal only, and shall be noted in the revision of the document.

Prepared by(Engineer):	Eric Yang	
Reviewer(Supervisor):	Jade Yang	
Approved(Manager):	Carson Zhang	

Table of Contents

Page

1 . SUMMARY OF TEST RESULTS 6
1.1 TEST FACILITY 7
1.2 MEASUREMENT UNCERTAINTY 7
2 . GENERAL INFORMATION 8
2.1 GENERAL DESCRIPTION OF EUT 8
2.2 DESCRIPTION OF TEST MODES 9
2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED 10
2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE) 10
2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
3 . EMC EMISSION TEST 12
3.1 CONDUCTED EMISSION MEASUREMENT 12
3.1.1 POWER LINE CONDUCTED EMISSION LIMITS 12
3.1.2 TEST PROCEDURE 12
3.1.3 DEVIATION FROM TEST STANDARD 12
3.1.4 TEST SETUP 13
3.1.5 EUT OPERATING CONDITIONS 13
3.1.6 TEST RESULTS 14
3.2 RADIATED EMISSION MEASUREMENT 15
3.2.1 RADIATED EMISSION LIMITS 16
3.2.2 TEST PROCEDURE 16
3.2.3 DEVIATION FROM TEST STANDARD 17
3.2.4 TEST SETUP 17
3.2.5 EUT OPERATING CONDITIONS 18
3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ) 19
3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ) 20
3.2.8 TEST RESULTS (1GHZ~25GHZ) 22
3.3 RADIATED BAND EMISSION MEASUREMENT 25
3.3.1 TEST REQUIREMENT: 25
3.3.2 TEST PROCEDURE 25
3.3.3 DEVIATION FROM TEST STANDARD 26
3.3.4 TEST SETUP 26
3.3.5 EUT OPERATING CONDITIONS 26
4 . POWER SPECTRAL DENSITY TEST 28
4.1 APPLIED PROCEDURES / LIMIT 28

Table of Contents

Page

4.1.1 TEST PROCEDURE 28
4.1.2 DEVIATION FROM STANDARD 28
4.1.3 TEST SETUP 28
4.1.4 EUT OPERATION CONDITIONS 28
4.1.5 TEST RESULTS 29

5 . BANDWIDTH TEST 35

5.1 APPLIED PROCEDURES / LIMIT 35
5.1.1 TEST PROCEDURE 35
5.1.2 DEVIATION FROM STANDARD 35
5.1.3 TEST SETUP 35
5.1.4 EUT OPERATION CONDITIONS 35
5.1.5 TEST RESULTS 36

6 . PEAK OUTPUT POWER TEST 42

6.1 APPLIED PROCEDURES/LIMIT 42

6.1.1 TEST PROCEDURE 42
6.1.2 DEVIATION FROM STANDARD 42
6.1.3 TEST SETUP 42
6.1.4 EUT OPERATION CONDITIONS 42
6.1.5 TEST RESULTS 43

7 . 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE 44
7.1 APPLICABLE STANDARD 44
7.2 TEST PROCEDURE 44
7.3 DEVIATION FROM STANDARD 44
7.4 TEST SETUP 44
7.5 EUT OPERATION CONDITIONS 44
7.1 TEST RESULTS 44

8 . DUTY CYCLE OF TEST SIGNAL 51

8.1 STANDARD REQUIREMENT 51

8.2 FORMULA: 51

9 . ANTENNA REQUIREMENT 53

9.1 STANDARD REQUIREMENT 53

9.2 EUT ANTENNA 53

10 . EUT TEST PHOTO 54

Table of Contents

Page

11 . EUT PHOTO 56
APPENDIX-PHOTOGRAPHS OF EUT CONSTRUCTIONAL DETAILS

1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C			
Standard Section	Test Item	Judgment	Remark
15.207	Conducted Emission	PASS	
15.247 (a)(2)	6dB Bandwidth	PASS	
15.247 (b)	Peak Output Power	PASS	
15.247 (d)	Radiated Spurious Emission	PASS	
15.247 (e)	Power Spectral Density	PASS	
15.205	Restricted Band of Operation	PASS	
15.247 (d)	Band Edge (Out of Band Emissions)	PASS	
15.203	Antenna Requirement	PASS	

NOTE:

(1)” N/A” denotes test is not applicable in this Test Report

1.1 TEST FACILITY

Shenzhen BCTC Testing Co., Ltd.
Add. : BCTC Building & 1-2F, East of B Building, Pengzhou Industrial, Fuyuan 1st Road, Qiaotou Community, Fuyong Street, Bao'an District, Shenzhen, China
FCC Test Firm Registration Number: 712850
IC Registered No.: 23583

1.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement **y ± U**，where expended uncertainty **U** is based on a standard uncertainty multiplied by a coverage factor of **k=2**，providing a level of confidence of approximately **95** %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power,conducted	±0.16dB
3	Spurious emissions,conducted	±0.21dB
4	All emissions,radiated(<1G)	±4.68dB
5	All emissions,radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

2. GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

<table>
<tr><td>Equipment</td><td>WIFI SOCKET</td></tr>
<tr><td>Trade Name</td><td>KINGART</td></tr>
<tr><td>Model Name</td><td>KING-A6
KING-A8, KING-A9，KING-F6, KING-F8, KING-F9， KING-J1, KING-J2, KING-J3，KING-K6, KING-K8, KING-K9，KING-S6, KING-S8, KING-S9，KING-T6, KING-T8, KING-T9</td></tr>
<tr><td>Model Difference</td><td>All the model are the same circuit and RF module, except model names and color.</td></tr>
<tr><td>Product Description</td><td><table>
<tr><td>Operation Frequency:</td><td>802.11b/g/n20MHz:2412~2462 MHz</td></tr>
<tr><td>Modulation Type:</td><td>WIFI: OFDM/DSSS</td></tr>
<tr><td>Bit Rate of Transmitter</td><td>802.11b:11/5.5/2/1 Mbps
802.11g:54/48/36/24/18/12/9/6Mbps
802.11n Up to 75Mbps</td></tr>
<tr><td>Number Of Channel</td><td>802.11b/g/n20MHz:11 CH</td></tr>
<tr><td>Antenna Designation:</td><td>Please see Note 3.</td></tr>
</table>Based on the application, features, or specification exhibited in User's Manual, the EUT is considered as an ITE/Computing Device. More details of EUT technical specification, please refer to the User's Manual.</td></tr>
<tr><td>Channel List</td><td>Please refer to the Note 2.</td></tr>
<tr><td>Power</td><td>AC 100-240V 50/60Hz</td></tr>
<tr><td>hardware version</td><td>--</td></tr>
<tr><td>Software version</td><td>--</td></tr>
<tr><td>Serial number</td><td>--</td></tr>
<tr><td>Connecting I/O Port(s)</td><td>Please refer to the User's Manual</td></tr>
</table>

Note:

1. For a more detailed features description, please refer to the manufacturer’s specifications or the User's Manual.

2.

Channel List for 802.11b/g/n(20)							
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
01	2412	04	2427	07	2442	10	2457
02	2417	05	2432	08	2447	11	2462
03	2422	06	2437	09	2452		

3.

Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Gain (dBi)	NOTE
1	N/A	N/A	PCB Antenna	1.0	

2.2 DESCRIPTION OF TEST MODES

Pretest Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11
Mode 4	Link Mode

Conducted Emission	
Final Test Mode	Description
Mode 4	Link Mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	802.11b CH1/ CH6/ CH11
Mode 2	802.11g CH1/ CH6/ CH11
Mode 3	802.11n20 CH1/ CH6/ CH11

Note:

(1) The measurements are performed at all Bit Rate of Transmitter, the worst data was reported.

2.3 BLOCK DIGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED

Emission Test



2.4 DESCRIPTION OF SUPPORT UNITS(CONDUCTED MODE)

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	WIFI SOCKET	KINGART	KING-A6	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:

(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

2.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	Agilent	E4407B	MY45108040	2017.08.27	2018.08.26
2	Test Receiver (9kHz-7GHz)	R&S	ESPI	101318	2017.08.27	2018.08.26
3	Bilog Antenna (30MHz-1GHz)	R&S	VULB 9168	VULB91 68-438	2017.08.27	2018.08.26
4	Horn Antenna (1GHz-18GHz)	SCHWARZBECK	BBHA9120D	1201	2017.09.03	2018.09.02
5	Horn Antenna (14GHz-40GHz)	SCHWARZBECK	BBHA 9170	9170-181	2017.09.03	2018.09.02
6	Amplifier (9KHz-6GHz)	SCHWARZBECK	BBV9744	9744-0037	2017.08.27	2018.08.26
7	Amplifier (1GHz-18GHz)	SCHWARZBECK	BBV9718	9718-309	2017.08.27	2018.08.26
8	Amplifier (18GHz-40GHz)	SCHWARZBECK	BBV 9721	9721-205	2017.08.27	2018.08.26
9	Loop Antenna (9KHz-30MHz)	SCHWARZBECK	FMZB1519B	00014	2017.09.03	2018.09.02
10	RF cables1 (9kHz-1GHz)	R&S	R203	R20X	2017.08.27	2018.08.26
11	RF cables2 (1GHz-40GHz)	R&S	R204	R21X	2017.08.27	2018.08.26
12	Antenna connector	Florida RF Labs	N/A	RF 01#	2017.08.27	2018.08.26
13	Power Metter	ANRITSU	ML2487A	6K00001568	2017.08.27	2018.08.26
14	Power Sensor (AV)	ANRITSU	ML2491A	030989	2017.08.27	2018.08.26
15	Signal Analyzer 9kHz-26.5GHz	Agilent	N9010A	MY48030494	2017.08.27	2018.08.26
16	Test Receiver 20kHz-40GHz	R&S	ESU 40	100376	2017.08.27	2018.08.26
17	D.C. Power Supply	LongWei	PS-305D	010964729	2017.08.27	2018.08.26

Conduction Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Test Receiver	R&S	ESCI	1166.5950K03-101165-ha	2017.08.27	2018.08.26
2	LISN	SCHWARZBECK	NSLK8127	8127739	2017.08.27	2018.08.26
3	LISN	R&S	NSLK8126	8126487	2017.08.27	2018.08.26
4	RF cables	R&S	R204	R20X	2017.08.27	2018.08.26
5	Attenuator	R&S	ESH3-Z2	143206	2017.08.27	2018.08.26

3. EMC EMISSION TEST

3.1 CONDUCTED EMISSION MEASUREMENT

3.1.1 POWER LINE CONDUCTED EMISSION Limits (Frequency Range 150KHz-30MHz)

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) The tighter limit applies at the band edges.

(2) The limit of " * " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz

3.1.2 TEST PROCEDURE

a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.

c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

d. LISN at least 80 cm from nearest part of EUT chassis.

e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

3.1.3 DEVIATION FROM TEST STANDARD

No deviation

3.1.4 TEST SETUP



Note: 1.Support units were connected to second LISN.
2.Both of LISNs (AMN) are 80 cm from EUT and at least 80 from other units and other metal planes

3.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 240V, the worst voltage was AC 120V and the data recording in the report.

3.1.6 TEST RESULTS

Temperature：	25 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	L
Test Voltage ：	AC 120V/60Hz	Test Mode：	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.1651	50.04	9.66	59.70	65.20	-5.50	QP	
2	*	0.1651	41.20	9.66	50.86	55.20	-4.34	AVG	
3		0.2717	40.56	9.66	50.22	61.07	-10.85	QP	
4		0.2717	34.29	9.66	43.95	51.07	-7.12	AVG	
5		0.5370	34.63	9.68	44.31	56.00	-11.69	QP	
6		0.5370	27.63	9.68	37.31	46.00	-8.69	AVG	
7		1.7475	27.50	9.70	37.20	56.00	-18.80	QP	
8		1.7475	18.41	9.70	28.11	46.00	-17.89	AVG	
9		5.6940	17.68	9.76	27.44	60.00	-32.56	QP	
10		5.6940	8.85	9.76	18.61	50.00	-31.39	AVG	
11		28.8960	21.87	9.86	31.73	60.00	-28.27	QP	
12		28.8960	7.93	9.86	17.79	50.00	-32.21	AVG	

Temperature：	25 ℃	Relative Humidity：	54%
Pressure：	1010hPa	Phase：	N
Test Voltage ：	AC 120V/60Hz	Test Mode：	Mode 4



Remark:
1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1	*	0.1595	52.25	9.67	61.92	65.49	-3.57	QP	
2		0.1595	40.12	9.67	49.79	55.49	-5.70	AVG	
3		0.3054	42.31	9.66	51.97	60.09	-8.12	QP	
4		0.3054	35.25	9.66	44.91	50.09	-5.18	AVG	
5		0.9195	30.27	9.69	39.96	56.00	-16.04	QP	
6		0.9195	23.59	9.69	33.28	46.00	-12.72	AVG	
7		2.4180	26.50	9.72	36.22	56.00	-19.78	QP	
8		2.4180	14.96	9.72	24.68	46.00	-21.32	AVG	
9		4.8480	19.45	9.74	29.19	56.00	-26.81	QP	
10		4.8480	8.70	9.74	18.44	46.00	-27.56	AVG	
11		28.8825	20.19	9.86	30.05	60.00	-29.95	QP	
12		28.8825	6.96	9.86	16.82	50.00	-33.18	AVG	

3.2 RADIATED EMISSION MEASUREMENT

3.2.1 RADIATED EMISSION LIMITS (Frequency Range 9kHz-1000MHz)

20dBc in any 100 kHz bandwidth outside the operating frequency band. In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	1000 MHz
Stop Frequency	25GHz
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / *10Hz* for Average

Receiver Parameter	Setting
Attenuation	Auto
Start ~ Stop Frequency	9kHz~150kHz / RB 200Hz for QP
Start ~ Stop Frequency	150kHz~30MHz / RB 9kHz for QP
Start ~ Stop Frequency	30MHz~1000MHz / RB 120kHz for QP

3.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.2.3 DEVIATION FROM TEST STANDARD

No deviation

3.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



3.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

3.2.6 TEST RESULTS (BETWEEN 9KHZ – 30 MHZ)

Temperature:	20℃	Relative Humidtity:	48%
Pressure:	1010 hPa	Test Voltage :	AC 120V/60Hz
Test Mode :	Mode 4	Polarization :	--

Freq.	Reading	Limit	Margin	State
(MHz)	(dBuV/m)	(dBuV/m)	(dB)	P/F
--	--	--	--	PASS
--	--	--	--	PASS

NOTE:

The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.
Distance extrapolation factor =40 log (specific distance/test distance)(dB);
Limit line = specific limits(dBuv) + distance extrapolation factor.

3.2.7 TEST RESULTS (BETWEEN 30MHZ – 1GHZ)

Temperature：	26℃	Relative Humidity：	54%
Pressure：	1010 hPa	Polarization：	Horizontal
Test Voltage ：	AC 120V/60Hz		
Test Mode ：	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	43.2017	32.72	-14.29	18.43	40.00	-21.57	QP
2		52.2079	27.68	-14.32	13.36	40.00	-26.64	QP
3		147.4036	37.45	-19.10	18.35	43.50	-25.15	QP
4		319.9370	37.05	-13.62	23.43	46.00	-22.57	QP
5		483.9094	31.05	-10.10	20.95	46.00	-25.05	QP
6		742.2587	23.48	-5.03	18.45	46.00	-27.55	QP

Temperature：	26℃	Relative Humidity：	54%
Pressure：	1010 hPa	Polarization：	Vertical
Test Voltage ：	AC 120V/60Hz		
Test Mode ：	Mode 4		



Remark:
Factor = Antenna Factor + Cable Loss – Pre-amplifier.

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1	*	38.4809	47.67	-15.26	32.41	40.00	-7.59	QP
2		48.1626	42.49	-13.98	28.51	40.00	-11.49	QP
3		69.8450	37.93	-17.56	20.37	40.00	-19.63	QP
4		160.9089	33.36	-19.03	14.33	43.50	-29.17	QP
5		241.6763	29.47	-15.45	14.02	46.00	-31.98	QP
6		480.5276	34.78	-10.28	24.50	46.00	-21.50	QP

3.2.8 TEST RESULTS (1GHZ~25GHZ)

802.11b

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	66.40	39.55	7.85	25.66	60.36	74.00	-13.64	PK
V	4824.00	48.52	39.55	7.85	25.66	42.48	54.00	-11.52	AV
V	7236.00	66.61	38.33	7.52	24.55	60.35	74.00	-13.65	PK
V	7236.00	47.62	38.33	7.52	24.55	41.36	54.00	-12.64	AV
V	15450.00	44.62	35.23	6.75	26.59	42.73	74.00	-31.27	PK
H	4824.00	67.01	39.55	7.85	25.66	60.97	74.00	-13.03	PK
H	4824.00	49.48	39.55	7.85	25.66	43.44	54.00	-10.56	AV
H	7236.00	67.24	38.33	7.52	23.55	59.98	74.00	-14.02	PK
H	7236.00	44.43	38.33	7.52	23.22	36.84	54.00	-17.16	AV
H	15450.00	46.84	35.45	6.75	27.88	46.02	74.00	-27.98	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	67.39	38.89	7.57	25.45	61.52	74.00	-12.48	PK
V	4874.00	50.25	38.89	7.57	25.45	44.38	54.00	-9.62	AV
V	7311.00	66.76	38.78	7.35	24.78	60.11	74.00	-13.89	PK
V	7311.00	47.29	38.78	7.35	24.78	40.64	54.00	-13.36	AV
V	15450.00	46.09	35.89	6.42	26.47	43.09	74.00	-30.91	PK
H	4874.00	65.47	38.89	7.57	25.45	59.60	74.00	-14.40	PK
H	4874.00	48.66	38.89	7.57	25.45	42.79	54.00	-11.21	AV
H	7311.00	68.72	38.78	7.35	24.78	62.07	74.00	-11.93	PK
H	7311.00	47.94	38.78	7.35	24.78	41.29	54.00	-12.71	AV
H	15450.00	44.66	36.68	6.42	26.65	41.05	74.00	-32.95	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	66.52	38.75	7.46	25.45	60.68	74.00	-13.32	PK
V	4924.00	49.47	38.75	7.46	25.45	43.63	54.00	-10.37	AV
V	7386.00	65.35	38.65	7.22	24.78	58.70	74.00	-15.30	PK
V	7386.00	47.83	38.65	7.22	24.78	41.18	54.00	-12.82	AV
V	15450.00	46.16	35.58	6.35	26.47	43.40	74.00	-30.60	PK
H	4924.00	63.78	38.75	7.46	25.45	57.94	74.00	-16.06	PK
H	4924.00	48.29	38.75	7.46	25.45	42.45	54.00	-11.55	AV
H	7386.00	68.35	38.65	7.22	24.78	61.70	74.00	-12.30	PK
H	7386.00	46.61	38.65	7.22	24.78	39.96	54.00	-14.04	AV
H	15450.00	45.76	36.42	6.32	26.65	42.31	74.00	-31.69	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11g

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	66.04	39.55	7.85	25.66	60.00	74.00	-14.00	PK
V	4824.00	48.26	39.55	7.85	25.66	42.22	54.00	-11.78	AV
V	7236.00	66.25	38.33	7.52	24.55	59.99	74.00	-14.01	PK
V	7236.00	47.36	38.33	7.52	24.55	41.10	54.00	-12.90	AV
V	15450.00	44.38	35.23	6.75	26.59	42.49	74.00	-31.51	PK
H	4824.00	66.65	39.55	7.85	25.66	60.61	74.00	-13.39	PK
H	4824.00	49.21	39.55	7.85	25.66	43.17	54.00	-10.83	AV
H	7236.00	66.87	38.33	7.52	23.55	59.61	74.00	-14.39	PK
H	7236.00	44.19	38.33	7.52	23.22	36.60	54.00	-17.40	AV
H	15450.00	46.59	35.45	6.75	27.88	45.77	74.00	-28.23	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	67.03	38.89	7.57	25.45	61.16	74.00	-12.84	PK
V	4874.00	49.97	38.89	7.57	25.45	44.10	54.00	-9.90	AV
V	7311.00	66.40	38.78	7.35	24.78	59.75	74.00	-14.25	PK
V	7311.00	47.03	38.78	7.35	24.78	40.38	54.00	-13.62	AV
V	15450.00	45.84	35.89	6.42	26.47	42.84	74.00	-31.16	PK
H	4874.00	65.11	38.89	7.57	25.45	59.24	74.00	-14.76	PK
H	4874.00	48.39	38.89	7.57	25.45	42.52	54.00	-11.48	AV
H	7311.00	68.34	38.78	7.35	24.78	61.69	74.00	-12.31	PK
H	7311.00	47.68	38.78	7.35	24.78	41.03	54.00	-12.97	AV
H	15450.00	44.42	36.68	6.42	26.65	40.81	74.00	-33.19	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	66.15	38.75	7.46	25.45	60.31	74.00	-13.69	PK
V	4924.00	49.20	38.75	7.46	25.45	43.36	54.00	-10.64	AV
V	7386.00	65.00	38.65	7.22	24.78	58.35	74.00	-15.65	PK
V	7386.00	47.57	38.65	7.22	24.78	40.92	54.00	-13.08	AV
V	15450.00	45.91	35.58	6.35	26.47	43.15	74.00	-30.85	PK
H	4924.00	63.44	38.75	7.46	25.45	57.60	74.00	-16.40	PK
H	4924.00	48.03	38.75	7.46	25.45	42.19	54.00	-11.81	AV
H	7386.00	67.98	38.65	7.22	24.78	61.33	74.00	-12.67	PK
H	7386.00	46.36	38.65	7.22	24.78	39.71	54.00	-14.29	AV
H	15450.00	45.51	36.42	6.32	26.65	42.06	74.00	-31.94	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

802.11n(20MHz)

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2412MHz									
V	4824.00	65.34	39.55	7.85	25.66	59.30	74.00	-14.70	PK
V	4824.00	47.75	39.55	7.85	25.66	41.71	54.00	-12.29	AV
V	7236.00	65.55	38.33	7.52	24.55	59.29	74.00	-14.71	PK
V	7236.00	46.86	38.33	7.52	24.55	40.60	54.00	-13.40	AV
V	15450.00	43.91	35.23	6.75	26.59	42.02	74.00	-31.98	PK
H	4824.00	65.94	39.55	7.85	25.66	59.90	74.00	-14.10	PK
H	4824.00	48.69	39.55	7.85	25.66	42.65	54.00	-11.35	AV
H	7236.00	66.16	38.33	7.52	23.55	58.90	74.00	-15.10	PK
H	7236.00	43.72	38.33	7.52	23.22	36.13	54.00	-17.87	AV
H	15450.00	46.09	35.45	6.75	27.88	45.27	74.00	-28.73	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2437MHz									
V	4874.00	66.32	38.89	7.57	25.45	60.45	74.00	-13.55	PK
V	4874.00	49.45	38.89	7.57	25.45	43.58	54.00	-10.42	AV
V	7311.00	65.70	38.78	7.35	24.78	59.05	74.00	-14.95	PK
V	7311.00	46.53	38.78	7.35	24.78	39.88	54.00	-14.12	AV
V	15450.00	45.36	35.89	6.42	26.47	42.36	74.00	-31.64	PK
H	4874.00	64.43	38.89	7.57	25.45	58.56	74.00	-15.44	PK
H	4874.00	47.88	38.89	7.57	25.45	42.01	54.00	-11.99	AV
H	7311.00	67.62	38.78	7.35	24.78	60.97	74.00	-13.03	PK
H	7311.00	47.17	38.78	7.35	24.78	40.52	54.00	-13.48	AV
H	15450.00	43.95	36.68	6.42	26.65	40.34	74.00	-33.66	PK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel: 2462MHz									
V	4924.00	65.45	38.75	7.46	25.45	59.61	74.00	-14.39	PK
V	4924.00	48.68	38.75	7.46	25.45	42.84	54.00	-11.16	AV
V	7386.00	64.31	38.65	7.22	24.78	57.66	74.00	-16.34	PK
V	7386.00	47.07	38.65	7.22	24.78	40.42	54.00	-13.58	AV
V	15450.00	45.42	35.58	6.35	26.47	42.66	74.00	-31.34	PK
H	4924.00	62.76	38.75	7.46	25.45	56.92	74.00	-17.08	PK
H	4924.00	47.52	38.75	7.46	25.45	41.68	54.00	-12.32	AV
H	7386.00	67.26	38.65	7.22	24.78	60.61	74.00	-13.39	PK
H	7386.00	45.87	38.65	7.22	24.78	39.22	54.00	-14.78	AV
H	15450.00	45.03	36.42	6.32	26.65	41.58	74.00	-32.42	PK

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,

Margin= Emission Level - Limit

2. If peak below the average limit, the average emission was no test.

3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

3.3 RADIATED BAND EMISSION MEASUREMENT

3.3.1 TEST REQUIREMENT:

FCC Part15 C Section 15.209 and 15.205

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Class B (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

3.3.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.

e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

3.3.3 DEVIATION FROM TEST STANDARD

No deviation

3.3.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



3.3.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

3.3.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission evel (dBuV/m)	Limits (dBuV/m)		Result
							PK	PK	AV	
802.11b	**Low Channel 2412MHz**									
	H	2390.00	56.64	38.06	7.42	20.15	46.15	74.00	54.00	PASS
	H	2400.00	61.55	38.06	7.42	20.15	51.06	74.00	54.00	PASS
	V	2390.00	60.40	38.06	7.42	20.15	49.91	74.00	54.00	PASS
	V	2400.00	62.77	38.06	7.42	20.15	52.28	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.36	38.17	7.45	20.54	51.18	74.00	54.00	PASS
	H	2485.50	58.94	38.17	7.45	20.54	48.76	74.00	54.00	PASS
	V	2483.50	61.85	38.20	7.45	20.54	51.64	74.00	54.00	PASS
	V	2485.50	59.75	38.20	7.45	20.54	49.54	74.00	54.00	PASS
802.11g	**Low Channel 2412MHz**									
	H	2390.00	59.48	38.06	7.42	20.15	48.99	74.00	54.00	PASS
	H	2400.00	62.29	38.06	7.42	20.15	51.80	74.00	54.00	PASS
	V	2390.00	59.63	38.06	7.42	20.15	49.14	74.00	54.00	PASS
	V	2400.00	61.19	38.06	7.42	20.15	50.70	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	61.17	38.17	7.45	20.54	50.99	74.00	54.00	PASS
	H	2485.50	58.46	38.17	7.45	20.54	48.28	74.00	54.00	PASS
	V	2483.50	62.26	38.20	7.45	20.54	52.05	74.00	54.00	PASS
	V	2485.50	57.03	38.20	7.45	20.54	46.82	74.00	54.00	PASS
802.11n20	**Low Channel 2412MHz**									
	H	2390.00	60.34	38.06	7.42	20.15	49.85	74.00	54.00	PASS
	H	2400.00	62.86	38.06	7.42	20.15	52.37	74.00	54.00	PASS
	V	2390.00	59.58	38.06	7.42	20.15	49.09	74.00	54.00	PASS
	V	2400.00	62.13	38.06	7.42	20.15	51.64	74.00	54.00	PASS
	High Channel 2462MHz									
	H	2483.50	59.96	38.17	7.45	20.54	49.78	74.00	54.00	PASS
	H	2485.50	59.51	38.17	7.45	20.54	49.33	74.00	54.00	PASS
	V	2483.50	61.29	38.20	7.45	20.54	51.08	74.00	54.00	PASS
	V	2485.50	60.05	38.20	7.45	20.54	49.84	74.00	54.00	PASS

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit
2. If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

4. POWER SPECTRAL DENSITY TEST

4.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247	Power Spectral Density	8 dBm (in any 3KHz)	2400-2483.5	PASS

4.1.1 TEST PROCEDURE

1. Set analyzer center frequency to DTS channel center frequency.
2. Set the span to 1.5 times the DTS bandwidth.
3. Set the RBW to: 3 kHz ≤ RBW ≤ 100 kHz.
4. Set the VBW ≥ 3 x RBW.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

4.1.2 DEVIATION FROM STANDARD

No deviation.

4.1.3 TEST SETUP



4.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.1 Unless otherwise a special operating condition is specified in the follows during the testing.
Note: Power Spectral Density(dBm)=Reading+Cable Loss

4.1.5 TEST RESULTS

Temperature：	25℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX b Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-9.326	8	PASS
2437 MHz	-9.801	8	PASS
2462 MHz	-9.51	8	PASS

TX CH01



TX CH06



TX CH11



Temperature：	25℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX g Mode		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-14.12	8	PASS
2437 MHz	-13.55	8	PASS
2462 MHz	-13.92	8	PASS

TX CH01



TX CH06



TX CH11



Temperature：	25℃	Relative Humidity：	60%
Pressure：	1015 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX n Mode(20M)		

Frequency	Power Spectral Density(dBm)	Limit (dBm)	Result
2412 MHz	-13.54	8	PASS
2437 MHz	-13.5	8	PASS
2462 MHz	-14.85	8	PASS

TX CH01



TX CH06



TX CH11



5. BANDWIDTH TEST

5.1 APPLIED PROCEDURES / LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(a)(2)	Bandwidth	>= 500KHz (6dB bandwidth)	2400-2483.5	PASS

5.1.1 TEST PROCEDURE

1. Set RBW = 100 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

5.1.2 DEVIATION FROM STANDARD

No deviation.

5.1.3 TEST SETUP



5.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

5.1.5 TEST RESULTS

Temperature：	25℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX b Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	8.108	500	Pass
2437	8.557	500	Pass
2462	8.572	500	Pass

TX CH 01



TX CH 06



TX CH 11



Temperature：	25℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX g Mode		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	16.383	500	Pass
2437	16.363	500	Pass
2462	16.350	500	Pass

TX CH 01



TX CH 06



TX CH 11



Temperature：	25℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	AC 120V/60Hz
Test Mode ：	TX n Mode(20M)		

Frequency (MHz)	6dB bandwidth (MHz)	Limit (kHz)	Result
2412	17.511	500	Pass
2437	17.234	500	Pass
2462	17.169	500	Pass

TX CH 01



TX CH 06



TX CH 11



6. PEAK OUTPUT POWER TEST

6.1 APPLIED PROCEDURES/LIMIT

FCC Part15 (15.247) , Subpart C				
Section	Test Item	Limit	Frequency Range (MHz)	Result
15.247(b)(3)	Peak Output Power	1 watt or 30dBm	2400-2483.5	PASS

6.1.1 TEST PROCEDURE

a. The EUT was directly connected to the Power meter

6.1.2 DEVIATION FROM STANDARD

No deviation.

6.1.3 TEST SETUP



6.1.4 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

6.1.5 TEST RESULTS

Temperature：	25℃	Relative Humidity：	60%
Pressure：	1012 hPa	Test Voltage ：	AC 120V/60Hz

	Frequency	Maximum Conducted Output Power(PK)	LIMIT
	(MHz)	(dBm)	dBm
802.11b	2412	14.64	30
	2437	14.87	30
	2462	14.27	30
802.11g	2412	13.22	30
	2437	13.66	30
	2462	13.07	30
802.11n20	2412	13.08	30
	2437	12.99	30
	2462	12.84	30

7. 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE

7.1 APPLICABLE STANDARD

in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator in operating, the radio frequency power that is produced by the intentional radiator shall be at least 20dB below that in the 100kHz bandwidth within the band that contains the highest level of the desired power, In addition, radiated emissions which fall in the restricted bands, as defined in§15.205(a), must also comply with the radiated emission limits specified in15.209(a).

7.2 TEST PROCEDURE

Using the following spectrum analyzer setting:

a) Set the RBW = 100KHz.
b) Set the VBW = 300KHz.
c) Sweep time = auto couple.
d) Detector function = peak.
e) Trace mode = max hold.
f) Allow trace to fully stabilize.

7.3 DEVIATION FROM STANDARD

No deviation.

7.4 TEST SETUP

7.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

7.1 TEST RESULTS

802.11b: Band Edge, Left Side



802.11b: Band Edge, Right Side



802.11g: Band Edge, Left Side



802.11g: Band Edge, Right Side



802.11n-HT20: Band Edge, Left Side



802.11n-HT20: Band Edge, Right Side



CONDUCTED EMISSION MEASUREMENT

802.11b

Low Channel 2412MHz





Middle Channel 2437MHz





High Channel 2462MHz





802.11g

Low Channel 2412MHz





Middle Channel 2437MHz





High Channel 2462MHz





802.11n20

Low Channel 2412MHz





Middle Channel 2437MHz





High Channel 2462MHz





8. DUTY CYCLE OF TEST SIGNAL

8.1 STANDARD REQUIREMENT

Pre-analysis Check: While conducting average power measurement, duty cycle of each mode shall be checked to ensure its duty cycle in order to compensate for the loss due to insufficient ratio of duty cycle.

All duty cycle is pre-scanned, and result as obtained below shows only the most representative ones where duty cycle is conducted as the given transmission with given virtual operation that expresses the percentage.

8.2 FORMULA:

Duty Cycle = Ton / (Ton+Toff)

Measurement Procedure:

1. Set span = Zero
2. RBW = 8MHz
3. VBW = 8MHz,
4. Detector = Peak

Duty Cycle:

	Duty Cycle	Duty Fator (dB)
802.11b	1	0
802.11g	1	0
802.11n(HT20)	1	0

802.11b



802.11g



802.11n(HT20)



9. ANTENNA REQUIREMENT

9.1 STANDARD REQUIREMENT

15.203 requirement: For intentional device, according to 15.203: an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

9.2 EUT ANTENNA

The EUT antenna is PCB Antenna, It comply with the standard requirement.

10. EUT TEST PHOTO

Conducted Measurement Photos

Radiated Measurement Photos





11. EUT PHOTO





※※※※※ **END OF REPORT** ※※※※※