

MPE TEST REPORT

Applicant Gosuncn Technology Group Co., Ltd.
FCC ID 2APNR-GL103G
Product Tracker
Brand GOSUNCN
Model GL103G
Report No. EFTA25110228-IE-04-M1V1
Issue Date March 10, 2026

Eurofins TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC 47 CFR Part 1 §1.1310, §2.1091**. The test results show that the equipment tested can demonstrate compliance with the requirements as documented in this report.



Prepared by: Wei Fangying



Approved by: Xu Kai

Eurofins TA Technology (Shanghai) Co., Ltd.

Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000

Version	Revision Description	Issue Date
Rev.0	Initial issue of report.	February 4, 2026
Rev.1	Updated data.	March 10, 2026
Note: This revised report (Report No.: EFTA25110228-IE-04-M1V1) supersedes and replaces the previously issued report (Report No.: EFTA25110228-IE-04-M1). Please discard or destroy the previously issued report and dispose of it accordingly.		

Table of Contents

1	Test Laboratory	4
1.1	Notes of the Test Report.....	4
1.2	Test Facility	4
1.3	Testing Location.....	4
1.4	Laboratory Environment	4
2	Description of Equipment Under Test	5
3	Maximum Tune up and Antenna Gain	7
4	MPE Limit.....	8
5	RF Exposure Evaluation Result.....	10
	ANNEX A: The EUT Appearance	12

1 Test Laboratory

1.1 Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **Eurofins TA Technology (Shanghai) Co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

1.2 Test Facility

FCC (Designation number: CN1179, Test Firm Registration Number: 446626)

Eurofins TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform measurements.

1.3 Testing Location

Company: Eurofins TA Technology (Shanghai) Co., Ltd.
Address: Building 3, No.145, Jintang Rd, Pudong Shanghai, P.R.China
City: Shanghai
Post code: 201201
Country: P. R. China
Contact: Xu Kai
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <https://www.eurofins.com/electrical-and-electronics>
E-mail: Kain.Xu@cpt.eurofinscn.com

1.4 Laboratory Environment

Temperature	Min. = 18°C, Max. = 25°C
Relative humidity	Min. = 20%, Max. = 80%
Ground system resistance	< 0.5 Ω
Ambient noise is checked and found very low and in compliance with requirement of standards. Reflection of surrounding objects is minimized and in compliance with requirement of standards.	

2 Description of Equipment Under Test

Client Information

Applicant	Gosuncn Technology Group Co., Ltd.
Applicant address	6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China. 510530
Manufacturer	Gosuncn Technology Group Co., Ltd.
Manufacturer address	6F, 2819 KaiChuang Blvd., Science Town, Huangpu District, Guangzhou City, Guangdong, China. 510530

General Technologies

EUT Description			
Model	GL103G		
Lab Internal SN	251117-24-001		
Hardware Version	GL103_MB_C		
Software Version	MCU GL103V3.0.0B03		
Frequency	Band	TX (MHz)	RX (MHz)
	NB-IOT Band 2	1850 ~ 1910	1930 ~ 1990
	NB-IOT Band 4	1710 ~ 1755	2110 ~ 2155
	NB-IOT Band 5	824 ~ 849	869 ~ 894
	NB-IOT Band 12	699 ~ 716	729 ~ 746
	NB-IOT Band 13	777 ~ 787	746 ~ 756
	NB-IOT Band 25	1850 ~ 1915	1930 ~ 1995
	NB-IOT Band 66	1710 ~ 1780	2110 ~ 2180
	NB-IOT Band 71	663 ~ 698	617 ~ 652
	NB-IOT Band 85	698 ~ 716	728 ~ 746
	LTE-M Band 2	1850 ~ 1910	1930 ~ 1990
	LTE-M Band 4	1710 ~ 1755	2110 ~ 2155
	LTE-M Band 5	824 ~ 849	869 ~ 894
	LTE-M Band 12	699 ~ 716	729 ~ 746
	LTE-M Band 13	777 ~ 787	746 ~ 756
	LTE-M Band 25	1850 ~ 1915	1930 ~ 1995
	LTE-M Band 26	814 ~ 849	859 ~ 894
	LTE-M Band 66	1710 ~ 1780	2110 ~ 2180
	LTE-M Band 85	698 ~ 716	728 ~ 746

	Bluetooth (Low Energy)	2400 ~ 2483.5	2400 ~ 2483.5
Date of Testing	November 25, 2025 ~ December 3, 2025		
Date of Sample Received	November 17, 2025		
Note: 1. The EUT is sent from the applicant to Eurofins TA and the information of the EUT is declared by the applicant. 2. All indications of Pass/Fail in this report are opinions expressed by Eurofins TA Technology (Shanghai) Co., Ltd. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only.			

3 Maximum Tune up and Antenna Gain

The numeric gain (G) of the antenna with a gain specified in dB is determined by

$$\text{Numeric gain (G)} = 10^{(\text{antenna gain}/10)}$$

The maximum tune-up and gain for each band are as follows:

Band	Maximum Tune up Tolerance		Antenna Gain (dBi)	Numeric Gain
	(dBm)	(mW)		
NB-IOT Band 2	22.00	158.49	2.71	1.87
NB-IOT Band 4	22.00	158.49	0.78	1.20
NB-IOT Band 5	22.00	158.49	-2.67	0.54
NB-IOT Band 12	22.00	158.49	-9.71	0.11
NB-IOT Band 13	22.00	158.49	-5.22	0.30
NB-IOT Band 25	22.00	158.49	2.71	1.87
NB-IOT Band 66	22.00	158.49	1.12	1.29
NB-IOT Band 71	22.00	158.49	-10.27	0.09
NB-IOT Band 85	22.00	158.49	-9.71	0.11
LTE-M Band 2	22.00	158.49	2.71	1.87
LTE-M Band 4	22.00	158.49	0.78	1.20
LTE-M Band 5	22.00	158.49	-2.67	0.54
LTE-M Band 12	22.00	158.49	-9.71	0.11
LTE-M Band 13	22.00	158.49	-5.22	0.30
LTE-M Band 25	22.00	158.49	2.71	1.87
LTE-M Band 26	22.00	158.49	-2.67	0.54
LTE-M Band 66	22.00	158.49	1.12	1.29
LTE-M Band 85	22.00	158.49	-9.71	0.11
Bluetooth LE	5.00	3.16	-0.61	0.87

4 MPE Limit

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) LIMITS FOR OCCUPATIONAL/CONTROLLED EXPOSURE				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1.0	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) LIMITS FOR GENERAL POPULATION/UNCONTROLLED EXPOSURE				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1.0	<30

*f = frequency in MHz. * = Plane-wave equivalent power density.*

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

The maximum permissible exposure for 300~1500 MHz is $f/1500$, for 1500~100,000MHz is 1.0. So

Band	The Maximum Permissible Exposure (mW/cm ²)
NB-IOT Band 2	1.000
NB-IOT Band 4	1.000
NB-IOT Band 5	0.549
NB-IOT Band 12	0.466
NB-IOT Band 13	0.518
NB-IOT Band 25	1.000
NB-IOT Band 66	1.000
NB-IOT Band 71	0.442
NB-IOT Band 85	0.468
LTE-M Band 2	1.000
LTE-M Band 4	1.000
LTE-M Band 5	0.549
LTE-M Band 12	0.466
LTE-M Band 13	0.518
LTE-M Band 25	1.000
LTE-M Band 26	0.543
LTE-M Band 66	1.000
LTE-M Band 85	0.468
Bluetooth LE	1.000

5 RF Exposure Evaluation Result

RF exposure evaluation method is based on KDB 447498 D01, this calculation is based on the conducted power, maximum power and antenna gain with provides the minimum separation distance. The formula shown below is from OET Bulletin 65 Edition 97-01 Per KDB 447498 D01:

$$S = PG / 4\pi R^2$$

Where: S = power density (in appropriate units, e.g. mW/cm²)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

Band	Maximum Tune up (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)	PG (mW)	Result (mW/cm ²)	Limit Value (mW/cm ²)	The MPE Ratio
NB-IOT Band 2	22.000	2.710	24.710	295.801	0.059	1.000	0.059
NB-IOT Band 4	22.000	0.780	22.780	189.671	0.038	1.000	0.038
NB-IOT Band 5	22.000	-2.670	19.330	85.704	0.017	0.549	0.031
NB-IOT Band 12	22.000	-9.710	12.290	16.943	0.003	0.466	0.007
NB-IOT Band 13	22.000	-5.220	16.780	47.643	0.009	0.518	0.018
NB-IOT Band 25	22.000	2.710	24.710	295.801	0.059	1.000	0.059
NB-IOT Band 66	22.000	1.120	23.120	205.116	0.041	1.000	0.041
NB-IOT Band 71	22.000	-10.270	11.730	14.894	0.003	0.442	0.007
NB-IOT Band 85	22.000	-9.710	12.290	16.943	0.003	0.468	0.007
LTE-M Band 2	22.000	2.710	24.710	295.801	0.059	1.000	0.059
LTE-M Band 4	22.000	0.780	22.780	189.671	0.038	1.000	0.038
LTE-M Band 5	22.000	-2.670	19.330	85.704	0.017	0.549	0.031
LTE-M Band 12	22.000	-9.710	12.290	16.943	0.003	0.466	0.007
LTE-M Band 13	22.000	-5.220	16.780	47.643	0.009	0.518	0.018
LTE-M Band 25	22.000	2.710	24.710	295.801	0.059	1.000	0.059
LTE-M Band 26	22.000	-2.670	19.330	85.704	0.017	0.543	0.031
LTE-M Band 66	22.000	1.120	23.120	205.116	0.041	1.000	0.041
LTE-M Band 85	22.000	-9.710	12.290	16.943	0.003	0.468	0.007
Bluetooth LE	5.000	-0.610	4.390	2.748	0.001	1.000	0.001

Note: R = 20cm

$\pi = 3.1416$

The MPE Ratio = Mac Result÷Limit Value

This device only supports simultaneous transmission via WWAN Bluetooth LE.

So, the simultaneous transmitting antenna pairs as below:

TER = WWAN Antenna MPE Ratio + Bluetooth LE Antenna MPE Ratio = 0.059 + 0.001 = 0.060 < 1.

So, the limit is kept.

Note: For this device, minimum separation distance is 20cm, even if calculations indicate MPE distance is less.

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

ANNEX A: The EUT Appearance

The EUT Appearance are submitted separately.

*****END OF REPORT *****