

Shandong Neon King Electronics Co., Ltd.

RF TEST REPORT

Report Type:

FCC Part 15.247 & ISSED RSS-247 RF report

Model:

SNKSS-O-3A

REPORT NUMBER:

180800495SHA-001

ISSUE DATE:

September 7, 2018

DOCUMENT CONTROL NUMBER:

TTRF15.247-03_V1 © 2018 Intertek



Applicant: Shandong Neon King Electronics Co., Ltd.
At the intersection of Jinyuan Road and 104 Road, Weishan
Economic Development Zone, Weishan County, Jining City,
Shandong, China

Manufacturer: Shandong Neon King Electronics Co., Ltd.
At the intersection of Jinyuan Road and 104 Road, Weishan
Economic Development Zone, Weishan County, Jining City,
Shandong, China

Manufacturing site: Shandong Neon King Electronics Co., Ltd.
At the intersection of Jinyuan Road and 104 Road, Weishan
Economic Development Zone, Weishan County, Jining City,
Shandong, China

FCC ID: 2APPP-00003

IC: 23037-00003

SUMMARY:

The equipment complies with the requirements according to the following standard(s) or Specification:

47CFR Part 15 (2017): Radio Frequency Devices (Subpart C)

ANSI C63.10 (2013): American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices

RSS-247 Issue 2 (February 2017): Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices

RSS-Gen Issue 5 (April 2018): General Requirements for Compliance of Radio Apparatus

PREPARED BY:**REVIEWED BY:**

Project Engineer
Eric Li



Reviewer
Daniel Zhao

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

Content

REVISION HISTORY.....	5
MEASUREMENT RESULT SUMMARY.....	6
1 GENERAL INFORMATION	7
1.1 DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	7
1.2 TECHNICAL SPECIFICATION	7
1.3 DESCRIPTION OF TEST FACILITY	11
2 TEST SPECIFICATIONS.....	12
2.1 STANDARDS OR SPECIFICATION	12
2.2 MODE OF OPERATION DURING THE TEST.....	12
2.3 TEST SOFTWARE LIST	13
2.4 TEST PERIPHERALS LIST	13
2.5 TEST ENVIRONMENT CONDITION:.....	13
2.6 INSTRUMENT LIST	14
2.7 MEASUREMENT UNCERTAINTY	15
3 MINIMUM 6DB BANDWIDTH.....	16
3.1 LIMIT	16
3.2 MEASUREMENT PROCEDURE	16
3.3 TEST CONFIGURATION	16
3.4 TEST RESULTS OF MINIMUM 6DB BANDWIDTH	16
4 MAXIMUM CONDUCTED OUTPUT POWER AND E.I.R.P.....	17
4.1 LIMIT	17
4.2 MEASUREMENT PROCEDURE	17
4.3 TEST CONFIGURATION	17
4.4 TEST RESULTS OF MAXIMUM CONDUCTED OUTPUT POWER	17
5 POWER SPECTRUM DENSITY	18
5.1 LIMIT	18
5.2 MEASUREMENT PROCEDURE	18
5.3 TEST CONFIGURATION	19
5.4 TEST RESULTS OF POWER SPECTRUM DENSITY	19
6 EMISSION OUTSIDE THE FREQUENCY BAND	20
6.1 LIMIT	20
6.2 MEASUREMENT PROCEDURE	20
6.3 TEST CONFIGURATION	21
6.4 THE RESULTS OF EMISSION OUTSIDE THE FREQUENCY BAND	21
7 RADIATED EMISSIONS IN RESTRICTED FREQUENCY BANDS.....	22
7.1 LIMIT	22
7.2 MEASUREMENT PROCEDURE	22
7.3 TEST CONFIGURATION	24
7.4 TEST RESULTS OF RADIATED EMISSIONS	26
8 POWER LINE CONDUCTED EMISSION.....	30
8.1 LIMIT	30
8.2 TEST CONFIGURATION	30
8.3 MEASUREMENT PROCEDURE	31

8.4	TEST RESULTS OF POWER LINE CONDUCTED EMISSION.....	32
9	OCCUPIED BANDWIDTH.....	34
9.1	LIMIT	34
9.2	MEASUREMENT PROCEDURE	34
9.3	TEST CONFIGURATION	34
9.4	THE RESULTS OF OCCUPIED BANDWIDTH	34
10	ANTENNA REQUIREMENT	35
	APPENDIX A: TEST RESULTS	36

Revision History

Report No.	Version	Description	Issued Date
180800495SHA-001	Rev. 01	Initial issue of report	September 7, 2018

Measurement result summary

TEST ITEM	FCC REFERENCE	IC REFERENCE	RESULT
Minimum 6dB Bandwidth	15.247(a)(2)	RSS-247 Issue 2 Clause 5.2	Pass
Maximum conducted output power and e.i.r.p.	15.247(b)(3)	RSS-247 Issue 2 Clause 5.4	Pass
Power spectrum density	15.247(e)	RSS-247 Issue 2 Clause 5.2	Pass
Emission outside the frequency band	15.247(d)	RSS-247 Issue 2 Clause 5.5	Pass
Radiated Emissions in restricted frequency bands	15.247(d), 15.205&15.209	RSS-Gen Issue 5 Clause 8.9&8.10	Pass
Power line conducted emission	15.207(a)	RSS-Gen Issue 5 Clause 8.8	Pass
Occupied bandwidth	-	RSS-Gen Issue 5 Clause 6.6	Tested
Antenna requirement	15.203	-	Pass

Notes: 1: NA =Not Applicable

1 GENERAL INFORMATION

1.1 Description of Equipment Under Test (EUT)

Product name:	INDOOR/OUTDOOR DECORATIVE LIGHTING STRING
Type/Model:	SNKSS-O-3A
Adding Model(s):	Please see the following page
Description of EUT:	The EUT is an DECORATIVE LIGHTING STRING, which supports WIFI function, all of the models have the same RF module and circuit except for the model designations, the number of lamp and power. we tested the model SNKSS-O-3A as representative and listed the results in this report.
Rating:	120V 60Hz
EUT type:	☒ Table top ☐ Floor standing
Software Version:	/
Hardware Version:	/
Sample received date:	2018-8-28
Date of test:	2018-8-30~2018-9-6

1.2 Technical Specification

Frequency Range:	2400MHz ~ 2483.5MHz
Support Standards:	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n-HT20
Type of Modulation:	IEEE 802.11b: DSSS (CCK, DQPSK, DBPSK) IEEE 802.11g: OFDM (64-QAM, 16-QAM, QPSK, BPSK) IEEE 802.11n-HT20: OFDM (64-QAM, 16-QAM, QPSK, BPSK)
Channel Number:	11 Channels for 802.11b, 802.11g and 802.11n(HT20)
Data Rate:	IEEE 802.11b: Up to 11 Mbps IEEE 802.11g: Up to 54 Mbps IEEE 802.11n-HT20: Up to MCS7
Channel Separation:	5 MHz

Adding Models list:

Example showing model designation:

(C) LNK S O - 50 / 2 N - A - H - C - SU
A B C D E F G H I J

A =	CLNK description: CSA Certified lighting strings made by Shandong Neon King Electronic Co., Ltd., approved by ETL. LNK description: UL Certified lighting strings made by Shandong Neon King Electronic Co., Ltd., approved by ETL.
B =	"S" indicates Basic style lampholder; "A" indicates LP-A style lampholder; "B" indicates LP-B style lampholder; "SC" indicates C9 style lampholder.
C =	"O" for outdoor use; "I" for indoor use.
D =	total number of lights
E =	number of circuits
F =	"I" for icicle strings, "N" for net light strings, "C" for curtain lighting strings or blank for straight string configuration
G =	LED color/voltage: "A" for 2 V LEDs, "B" for 3 V LEDs, or "C" for a combination of 2 V and 3 V LEDs, "D" for double colors change LEDs, "E" for triple colors change LEDs.
H =	"H" for diffuser type, refer to sec. 4.0 Item 13-19.
I =	"C" for lighting strings with controller SNKSS-I-2B or SNKSS-O-3, "CA" with controller SNKSS-O-3A, or blank for strings without controller.
J =	"SU" for lighting strings with special use connector, or blank for strings without special use connector.

Models specification (120V 60Hz):

Model No.	Total No. of Lamps	No. of Circuits Total	Input Current, A	Input Power, W
X-20/1	20	1	0.30	36
X-40/2	40	2	0.32	38.4
X-60/3	60	3	0.34	40.8
X-80/4	80	4	0.36	43.2
X-100/5	100	5	0.38	45.6
X-120/6	120	6	0.40	48
X-140/7	140	7	0.42	50.4
X-160/8	160	8	0.44	52.8
X-180/9	180	9	0.46	55.2
X-25/1	25	1	0.30	36
X-50/2	50	2	0.32	38.4

TEST REPORT

Report No.: 180800495SHA-001

X-75/3	75	3	0.34	40.8
X-100/4	100	4	0.36	43.2
X-125/5	125	5	0.38	45.6
X-150/6	150	6	0.40	48
X-175/7	175	7	0.42	50.4
X-200/8	200	8	0.44	52.8
X-225/9	225	9	0.46	55.2
X-30/1	30	1	0.30	36
X-60/2	60	2	0.32	38.4
X-90/3	90	3	0.34	40.8
X-120/4	120	4	0.36	43.2
X-150/5	150	5	0.38	45.6
X-180/6	180	6	0.40	48
X-210/7	210	7	0.42	50.4
X-240/8	240	8	0.44	52.8
X-270/9	270	9	0.46	55.2
X-35/1	35	1	0.30	36
X-70/2	70	2	0.32	38.4
X-105/3	105	3	0.34	40.8
X-140/4	140	4	0.36	43.2
X-175/5	175	5	0.38	45.6
X-210/6	210	6	0.40	48
X-245/7	245	7	0.42	50.4
X-280/8	280	8	0.44	52.8
X-315/9	315	9	0.46	55.2
X-40/1	40	1	0.30	36
X-80/2	80	2	0.32	38.4
X-120/3	120	3	0.34	40.8
X-160/4	160	4	0.36	43.2
X-200/5	200	5	0.38	45.6
X-240/6	240	6	0.40	48
X-280/7	280	7	0.42	50.4
X-320/8	320	8	0.44	52.8
X-360/9	360	9	0.46	55.2
X-45/1	45	1	0.30	36
X-90/2	90	2	0.32	38.4
X-135/3	135	3	0.34	40.8
X-180/4	180	4	0.36	43.2
X-225/5	225	5	0.38	45.6
X-270/6	270	6	0.40	48
X-315/7	315	7	0.42	50.4
X-360/8	360	8	0.44	52.8
X-405/9	405	9	0.46	55.2
X-50/1	50	1	0.30	36

TEST REPORT

Report No.: 180800495SHA-001

X-100/2	100	2	0.32	38.4
X-150/3	150	3	0.34	40.8
X-200/4	200	4	0.36	43.2
X-250/5	250	5	0.38	45.6
X-300/6	300	6	0.40	48
X-350/7	350	7	0.42	50.4
X-400/8	400	8	0.44	52.8
X-450/9	450	9	0.46	55.2

“X” shall be replaced by the Series and indicated in MODEL NOMENCLATURE. (See model designation)

1.3 Antenna information

Antenna No.	Model	Antenna type	Antenna Gain	Note
1	/	PCB	5.3dBi	

1.4 Description of Test Facility

Name:	Intertek Testing Services Shanghai
Address:	Building 86, No. 1198 Qinzhou Road(North), Shanghai 200233, P.R. China
Telephone:	86 21 61278200
Telefax:	86 21 54262353

The test facility is recognized, certified, or accredited by these organizations:	CNAS Accreditation Lab Registration No. CNAS L0139
	FCC Accredited Lab Designation Number: CN1175
	IC Registration Lab Registration code No.: 2042B-1
	VCCI Registration Lab Registration No.: R-4243, G-845, C-4723, T-2252
	NVLAP Accreditation Lab NVLAP LAB CODE: 200849-0
	A2LA Accreditation Lab Certificate Number: 3309.02

2 TEST SPECIFICATIONS

2.1 Standards or specification

47CFR Part 15 (2017)
ANSI C63.10 (2013)
RSS-247 Issue 2 (February 2017)
RSS-Gen Issue 5 (April 2018)
KDB 558074 (v04)

2.2 Mode of operation during the test

While testing transmitting mode of EUT, the internal modulation and continuously transmission was applied.

The lowest, middle and highest channel were tested as representatives.

Frequency Band (MHz)	Mode	Lowest (MHz)	Middle (MHz)	Highest (MHz)
2400-2483.5	802.11b	2412	2437	2462
	802.11g	2412	2437	2462
	802.11n(HT20)	2412	2437	2462

Data rate VS Power:

The pre-scan for the conducted power with all rates in each modulation and bands was used, and the worst case was found and used in all test cases. After this pre-scan, we choose the following table of the data rate as the worst case.

Frequency Band (MHz)	Mode	Worst case data rate
2400-2483.5	802.11b	1Mbps
	802.11g	6Mbps
	802.11n(HT20)	MCS0

There have the following test mode:

Radiated test mode:

Mode 1: EUT transmitted signal with internal antenna;

Conducted test mode:

Mode 2: EUT transmitted signal from PCBA RF port connected to SA directly;

We have verified all testing modes, and chose the worst mode 1 for radiated test and mode 2 for conducted test as representatively to list the results in this report.

2.3 Test software list

Test Items	Software	Manufacturer	Version
Conducted emission	ESxS-K1	R&S	V2.1.0
Radiated emission	ES-K1	R&S	V1.71

2.4 Test peripherals list

Item No.	Name	Brand and Model	Description
1	Laptop computer	DELL, Latitude E5470	FCC DoC approval

2.5 Test environment condition:

Test items	Temperature	Humidity
Minimum 6dB Bandwidth	25°C	52% RH
Maximum conducted output power and e.i.r.p.		
Power spectrum density		
Emission outside the frequency band		
Occupied bandwidth		
Radiated Emissions in restricted frequency bands	24°C	55% RH
Power line conducted emission	24°C	52% RH

2.6 Instrument list

Conducted Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESCS 30	EC 2107	2018-10-18
☒	A.M.N.	R&S	ESH2-Z5	EC 3119	2018-12-01
☒	Shielded room	Zhongyu	-	EC 2838	2019-01-08
Radiated Emission					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Test Receiver	R&S	ESIB 26	EC 3045	2018-10-18
☒	Bilog Antenna	TESEQ	CBL 6112D	EC 4206	2019-05-30
☒	Horn antenna	R&S	HF 906	EC 3049	2018-09-22
☒	Horn antenna	ETS	3117	EC 4792-1	2019-08-23
☒	Horn antenna	TOYO	HAP18-26W	EC 4792-3	2020-07-09
☒	Pre-amplifier	R&S	Pre-amp 18	EC5881	2019-06-19
☒	Semi-anechoic chamber	Albatross project	-	EC 3048	2018-09-08
RF test					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	PXA Signal Analyzer	Keysight	N9030A	EC 5338	2018-09-10
☒	Power sensor	Agilent	U2021XA	EC 5338-1	2019-03-03
☒	Vector Signal Generator	Agilent	N5182B	EC 5175	2019-03-06
☒	MXG Analog Signal Generator	Agilent	N5181A	EC 5338-2	2019-03-03
☒	Test Receiver	R&S	ESCI 7	EC 4501	2019-02-23
Additional instrument					
Used	Equipment	Manufacturer	Type	Internal no.	Due date
☒	Therom-Hygrograph	ZJ1-2A	S.M.I.F.	EC 3323	2019-06-14
☒	Pressure meter	YM3	Shanghai Mengde	EC 3320	2019-06-28

2.7 Measurement uncertainty

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Test item	Measurement uncertainty
Maximum peak output power	$\pm 0.74\text{dB}$
Radiated Emissions in restricted frequency bands below 1GHz	$\pm 4.90\text{dB}$
Radiated Emissions in restricted frequency bands above 1GHz	$\pm 5.02\text{dB}$
Emission outside the frequency band	$\pm 2.89\text{dB}$
Power line conducted emission	$\pm 3.19\text{dB}$

3 Minimum 6dB bandwidth

Test result: Pass

3.1 Limit


For systems using digital modulation techniques that may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz and 5725 - 5850 MHz bands, the minimum 6 dB bandwidth shall be at least 500 kHz.

3.2 Measurement Procedure

The minimum 6dB bandwidth is measured using the Spectrum Analyzer according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance" (clause 8.2) for compliance requirements.

- a) Set RBW = 100 kHz.
- b) Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
- c) Detector = Peak.
- d) Trace mode = max hold.
- e) Sweep = auto couple.
- f) Allow the trace to stabilize.
- g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

3.3 Test Configuration



3.4 Test Results of Minimum 6dB bandwidth

Please refer to Appendix A

4 Maximum conducted output power and e.i.r.p.

Test result: Pass

4.1 Limit


For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands:
1 W. (The e.i.r.p. shall not exceed 4 W)

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 30dBm and 30+ (6 –antenna gain-beam forming gain).

4.2 Measurement Procedure

The EUT was tested according to DTS test procedure of “KDB558074 D01 DTS Meas Guidance” (clause 9.1.3) for compliance requirements.

4.3 Test Configuration



4.4 Test Results of Maximum conducted output power

Please refer to Appendix A

5 Power spectrum density

Test result: Pass

5.1 Limit

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8dBm in any 3 kHz band during any time interval of continuous transmission.

If the transmitting antenna of directional gain greater than 6dBi is used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi. If there have a beam forming type, the limit should be the minimum of 8dBm/MHz and $8 + (6 - \text{antenna gain} - \text{beam forming gain})$.


5.2 Measurement Procedure

The power output was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance" (clause 10.2) for compliance requirements.

This procedure shall be used if maximum peak conducted output power was used to demonstrate compliance, and is optional if the maximum conducted (average) output power was used to demonstrate compliance.

- a) Set analyzer center frequency to DTS channel center frequency.
- b) Set the span to $1.5 \times \text{DTS bandwidth}$.
- c) Set the RBW to: $3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}$.
- d) Set the VBW $\geq 3 \times \text{RBW}$.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum amplitude level within the RBW.
- j) If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

5.3 Test Configuration



5.4 Test Results of Power spectrum density

Please refer to Appendix A

6 Emission outside the frequency band

Test result: Pass

6.1 Limit

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power.

6.2 Measurement Procedure

The EUT was tested according to DTS test procedure of "KDB558074 D01 DTS Meas Guidance" (clause 11.0) for compliance requirements.

Reference level measurement

Establish a reference level by using the following procedure:


- a) Set instrument center frequency to DTS channel center frequency.
- b) Set the span to ≥ 1.5 times the DTS bandwidth.
- c) Set the RBW = 100 kHz.
- d) Set the VBW $\geq 3 \times$ RBW.
- e) Detector = peak.
- f) Sweep time = auto couple.
- g) Trace mode = max hold.
- h) Allow trace to fully stabilize.
- i) Use the peak marker function to determine the maximum PSD level.

Emission level measurement

- a) Set the center frequency and span to encompass frequency range to be measured.
- b) Set the RBW = 100 kHz.
- c) Set the VBW $\geq 3 \times$ RBW.
- d) Detector = peak.
- e) Sweep time = auto couple.
- f) Trace mode = max hold.
- g) Allow trace to fully stabilize.
- h) Use the peak marker function to determine the maximum amplitude level.

Ensure that the amplitude of all unwanted emissions outside of the authorized frequency band (excluding restricted frequency bands) are attenuated by at least the minimum requirements specified in 11.1 a) or 11.1 b). Report the three highest emissions relative to the limit.

6.3 Test Configuration



6.4 The results of Emission outside the frequency band

Please refer to Appendix A

7 Radiated Emissions in restricted frequency bands

Test result: Pass

7.1 Limit

The radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified showed as below:

Frequencies (MHz)	Field Strength (microvolts/meter)	Measurement Distance (meters)
0.009 ~ 0.490	2400/F(kHz)	300
0.490 ~ 1.705	24000/F(kHz)	30
1.705 ~ 30.0	30	30
30 ~ 88	100	3
88 ~ 216	150	3
216 ~ 960	200	3
Above 960	500	3

7.2 Measurement Procedure

For Radiated emission below 30MHz:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter chamber room. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- Both X and Y axes of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Quasi-Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.

NOTE:

- The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 9kHz at frequency below 30MHz.

For Radiated emission above 30MHz:


- a) The EUT was placed on the top of a rotating table 0.8 meters (for 30MHz ~ 1GHz) / 1.5 meters (for above 1GHz) above the ground at 3 meter chamber room for test. The table was rotated 360 degrees to determine the position of the highest radiation.
- b) The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c) The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d) For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e) The test-receiver system was set to quasi-peak detect function and specified bandwidth with maximum hold mode when the test frequency is below 1 GHz.
- f) The test-receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1 GHz. If the peak reading value also meets average limit, measurement with the average detector is unnecessary.

Note:


- 1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120kHz for Quasi-peak detection (QP) at frequency below 1GHz.
- 2. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 3 MHz for Peak detection (PK) at frequency above 1GHz.
- 3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is $\geq 1/T$ (Duty cycle < 98%) or 3 x RBW (Duty cycle $\geq$ 98%) for Average detection (AV) at frequency above 1GHz.
- 4. All modes of operation were investigated and the worst-case emissions are reported


7.3 Test Configuration

For Radiated emission below 30MHz:



For Radiated emission 30MHz to 1GHz:





For Radiated emission above 1GHz:

7.4 Test Results of Radiated Emissions

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line per 15.31(o) was not reported.

EUT was tested with Bluetooth on and off, and the worst data was listed in the report.

The worst waveform from 30MHz to 1000MHz is listed as below:



Test data below 1GHz

Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
H	142.75	33.10	12.20	43.50	10.40	PK
H	160.24	27.90	11.10	43.50	15.60	PK
H	191.34	26.90	10.80	43.50	16.60	PK
H	319.64	36.50	15.30	46.00	9.50	PK
H	399.34	29.90	17.50	46.00	16.10	PK
H	931.96	32.70	23.80	46.00	13.30	PK
V	30.00	31.40	18.60	40.00	8.60	PK
V	49.44	30.30	8.80	40.00	9.70	PK
V	78.60	33.60	7.60	40.00	6.40	PK
V	121.36	32.40	13.20	43.50	11.10	PK
V	160.24	33.10	11.10	43.50	10.40	PK
V	601.50	31.70	20.80	46.00	14.30	PK

Test result above 1GHz:

The emission was conducted from 1GHz to 25GHz

802.11b

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2387.84	53.56	35.00	74.00	20.44	PK
	V	2387.84	52.10	34.20	74.00	21.90	PK
	H	4824.54	48.40	-3.60	74.00	25.60	PK
M	H	4875.90	49.80	-3.50	74.00	24.20	PK
	V	4875.90	50.20	-3.50	74.00	23.80	PK
H	H	2483.50	43.37	34.80	74.00	30.63	PK
	V	2483.50	42.60	34.80	74.00	31.40	PK
	V	4923.80	50.60	-3.30	74.00	23.40	PK

802.11g

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2388.48	56.80	34.20	74.00	17.20	PK
	H	2388.48	47.20	34.20	54.00	6.80	AV
	V	2389.20	60.20	34.20	74.00	13.80	PK
	V	2389.20	43.50	34.20	54.00	10.50	AV
	V	4830.80	45.70	3.70	74	28.30	PK
M	H	4873.60	46.20	-3.60	74.00	27.80	PK
	V	4873.50	46.20	-3.60	74.00	27.80	PK
H	H	2483.50	60.13	34.80	74.00	13.87	PK
	H	2483.50	47.60	34.80	54.00	6.40	AV
	V	2483.50	58.70	34.80	74.00	15.30	PK
	V	2483.50	46.30	34.80	54.00	7.70	AV
	V	4924.10	46.90	1.78	74.00	27.10	PK

802.11n(HT20)

CH	Antenna	Frequency (MHz)	Corrected Reading (dBuV/m)	Correct Factor (dB/m)	Limit (dBuV/m)	Margin (dB)	Detector
L	H	2390.00	66.92	34.20	74.00	7.08	PK
	H	2390.00	49.50	34.20	54.00	4.50	PK
	V	2390.00	63.02	34.20	74.00	10.98	PK
	V	2390.00	46.50	34.20	54.00	7.50	PK
	H	4824.60	47.20	-3.60	74.00	26.80	PK
M	H	4874.20	46.60	-3.60	74.00	27.40	PK
	V	4874.20	47.60	-3.60	74.00	26.40	PK
H	H	2483.50	65.94	34.80	74.00	8.06	PK
	H	2483.50	47.00	34.80	54.00	7.00	AV
	V	2483.50	62.50	34.80	74.00	11.50	PK
	V	2483.50	46.00	34.80	54.00	8.00	AV
	V	4923.80	47.50	-1.78	74.00	26.50	PK

Remark: 1. Correct Factor = Antenna Factor + Cable Loss (+ Amplifier, for higher than 1GHz), the value was added to Original Receiver Reading by the software automatically.
2. Corrected Reading = Original Receiver Reading + Correct Factor
3. Margin = Limit - Corrected Reading
4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

Example: Assuming Antenna Factor = 30.20dB/m, Cable Loss = 2.00dB,
Gain of Preamplifier = 32.00dB, Original Receiver Reading = 10.00dBuV,
Limit = 40.00dBuV/m.
Then Correct Factor = $30.20 + 2.00 - 32.00 = 0.20\text{dB/m}$;
Corrected Reading = $10\text{dBuV} + 0.20\text{dB/m} = 10.20\text{dBuV/m}$;
Margin = $40.00\text{dBuV/m} - 10.20\text{dBuV/m} = 29.80\text{dB}$.

8 Power line conducted emission


Test result: Pass

8.1 Limit

Frequency of Emission (MHz)	Conducted Limit (dBuV)	
	QP	AV
0.15-0.5	66 to 56*	56 to 46 *
0.5-5	56	46
5-30	60	50

* Decreases with the logarithm of the frequency.

8.2 Test Configuration



8.3 Measurement Procedure


Measured levels of ac power-line conducted emission shall be the emission voltages from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), where permitted, terminated into a 50 Ω measuring instrument. All emission voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord by the use of mating plugs and receptacles on the LISN, if used. Equipment shall be tested with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended by the manufacturer. For those measurements using a LISN, the 50 Ω measuring port is terminated by a measuring instrument having 50 Ω input impedance. All other ports are terminated in 50 Ω loads.

Tabletop devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.

The bandwidth of the test receiver is set at 9 kHz.

8.4 Test Results of Power line conducted emission


Test Curve:



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.19	55.51	63.91	8.40	35.47	53.91	18.44
0.24	53.55	62.02	8.47	33.97	52.02	18.05
0.27	53.79	61.03	7.24	34.01	51.03	17.02
0.31	51.95	60.07	8.12	33.10	50.07	16.97
0.32	51.21	59.63	8.42	32.63	49.63	17.00
0.43	46.09	57.28	11.19	29.83	47.28	17.45

Test Curve:



Test Data:

Frequency (MHz)	Quasi-peak			Average		
	level dB(μV)	Limit dB(μV)	Margin (dB)	level dB(μV)	limit dB(μV)	Margin (dB)
0.16	58.17	65.67	7.50	37.76	55.67	17.91
0.20	57.07	63.68	6.61	37.14	53.68	16.54
0.23	54.77	62.35	7.58	39.52	52.35	12.83
0.31	52.07	59.93	7.86	34.19	49.93	15.74
0.35	50.07	59.04	8.97	32.47	49.04	16.57
0.41	49.91	57.71	7.80	32.63	47.71	15.08

Remark: 1. Correct Factor = LISN Factor + Cable Loss, the value was added to Original Receiver Reading by the software automatically.

2. Corrected Reading = Original Receiver Reading + Correct Factor

3. Margin = Limit - Corrected Reading

4. If the PK Corrected Reading is lower than AV limit, the AV test can be elided.

9 Occupied Bandwidth

Test result: **Tested**

9.1 Limit

None


9.2 Measurement Procedure

The occupied bandwidth per RSS-Gen Issue 4 Clause 6.6 was measured using the Spectrum Analyzer.

The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts.

The resolution bandwidth (RBW) shall be in the range of 1% to 5% of the occupied bandwidth (OBW) and video bandwidth (VBW) shall be approximately 3x RBW.

9.3 Test Configuration



9.4 The results of Occupied Bandwidth

Please refer to Appendix A

10 Antenna requirement

Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

Result:

EUT uses permanently attached antenna to the intentional radiator, so it can comply with the provisions of this section.

Appendix A: Test results

1. RF Output Power

1.1 Test Result and Data

WLAN Peak Output Power						
Mode	Test Frequency (MHz)	Ant	Max Power (dBm)	Limit (dBm)	EIRP (dBm)	Result
802.11b	2412	Ant0	20.85	30	26.15	Pass
802.11b	2437	Ant0	20.86	30	26.16	Pass
802.11b	2462	Ant0	21.15	30	26.45	Pass
802.11g	2412	Ant0	21.26	30	26.56	Pass
802.11g	2437	Ant0	21.37	30	26.67	Pass
802.11g	2462	Ant0	21.31	30	26.61	Pass
802.11n (HT20)	2412	Ant0	20.19	30	25.49	Pass
802.11n (HT20)	2437	Ant0	20.64	30	25.94	Pass
802.11n (HT20)	2462	Ant0	21.43	30	26.73	Pass

Conclusion: The maximum EIRP = $21.43\text{dBm} + 5.30\text{dBi} = 26.73\text{dBm} = 0.471\text{W}$ which is lower than the limit of 4W listed in RSS-247.

1.2 Test Plots


None


2. Minimum 6dB bandwidth

2.1 Test Data

WLAN Occupied 6dB Bandwidth				
Mode	Test Frequency (MHz)	Ant	Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	8.12	Pass
802.11b	2437	Ant0	8.13	Pass
802.11b	2462	Ant0	8.13	Pass
802.11g	2412	Ant0	16.38	Pass
802.11g	2437	Ant0	16.38	Pass
802.11g	2462	Ant0	16.37	Pass
802.11n (HT20)	2412	Ant0	17.62	Pass
802.11n (HT20)	2437	Ant0	17.61	Pass
802.11n (HT20)	2462	Ant0	17.61	Pass

2.2 Test Plots






3. Occupied Bandwidth

3.1 Test Data

WLAN 99% Occupied Bandwidth				
Mode	Test Frequency (MHz)	Ant	99% Occupied Bandwidth (MHz)	Result
802.11b	2412	Ant0	11.242	Pass
802.11b	2437	Ant0	11.212	Pass
802.11b	2462	Ant0	11.636	Pass
802.11g	2412	Ant0	17.593	Pass
802.11g	2437	Ant0	17.514	Pass
802.11g	2462	Ant0	17.631	Pass
802.11n (HT20)	2412	Ant0	18.564	Pass
802.11n (HT20)	2437	Ant0	18.612	Pass
802.11n (HT20)	2462	Ant0	18.642	Pass

3.2 Test Plots






4. Power spectrum density

4.1 Test Data

WLAN PEAK Power Spectral Density						
Mode	Test Frequency (MHz)	Ant	PSD (dBm)	RBW (kHz)	Limit (dBm)	Result
802.11b	2412	Ant0	2.425	100	8	Pass
802.11b	2437	Ant0	1.977	100	8	Pass
802.11b	2462	Ant0	2.641	100	8	Pass
802.11g	2412	Ant0	-0.661	100	8	Pass
802.11g	2437	Ant0	0.842	100	8	Pass
802.11g	2462	Ant0	1.233	100	8	Pass
802.11n (HT20)	2412	Ant0	1.659	100	8	Pass
802.11n (HT20)	2437	Ant0	1.566	100	8	Pass
802.11n (HT20)	2462	Ant0	0.410	100	8	Pass

4.2 Test Plot





5. Emission outside the frequency band

5.1 Test Data

WLAN Transmitter Spurious Emission						
Mode	Test Frequency (MHz)	Ant	Plot No.	Frequency Range	Emission (dBm)	Result
802.11b	2412	Ant0	1	Reference Level	3.10	Pass
802.11b	2412	Ant0	2	Band Edge	-37.75	Pass
802.11b	2412	Ant0	3	30MHz~2310MHz	-48.01	Pass
802.11b	2412	Ant0	4	2500MHz~5000MHz	-23.96	Pass
802.11b	2412	Ant0	5	5000MHz~25000MHz	-36.34	Pass
802.11b	2437	Ant0	1	Reference Level	2.61	Pass
802.11b	2437	Ant0	2	Band Edge	-51.27	Pass
802.11b	2437	Ant0	3	30MHz~2310MHz	-39.84	Pass
802.11b	2437	Ant0	4	2500MHz~5000MHz	-24.72	Pass
802.11b	2437	Ant0	5	5000MHz~25000MHz	-38.32	Pass
802.11b	2462	Ant0	1	Reference Level	2.60	Pass
802.11b	2462	Ant0	2	Band Edge	-42.99	Pass
802.11b	2462	Ant0	3	30MHz~2310MHz	-47.98	Pass
802.11b	2462	Ant0	4	2500MHz~5000MHz	-24.78	Pass
802.11b	2462	Ant0	5	5000MHz~25000MHz	-39.07	Pass
802.11g	2412	Ant0	1	Reference Level	-0.78	Pass
802.11g	2412	Ant0	2	Band Edge	-27.72	Pass
802.11g	2412	Ant0	3	30MHz~2310MHz	-50.30	Pass
802.11g	2412	Ant0	4	2500MHz~5000MHz	-37.96	Pass
802.11g	2412	Ant0	5	5000MHz~25000MHz	-37.18	Pass
802.11g	2437	Ant0	1	Reference Level	1.69	Pass
802.11g	2437	Ant0	2	Band Edge	-45.93	Pass
802.11g	2437	Ant0	3	30MHz~2310MHz	-44.46	Pass
802.11g	2437	Ant0	4	2500MHz~5000MHz	-31.99	Pass
802.11g	2437	Ant0	5	5000MHz~25000MHz	-38.00	Pass
802.11g	2462	Ant0	1	Reference Level	1.53	Pass


TEST REPORT

Report No.: 180800495SHA-001


802.11g	2462	Ant0	2	Band Edge	-42.71	Pass
802.11g	2462	Ant0	3	30MHz~2310MHz	-50.54	Pass
802.11g	2462	Ant0	4	2500MHz~5000MHz	-32.04	Pass
802.11g	2462	Ant0	5	5000MHz~25000MHz	-35.09	Pass
802.11n (HT20)	2412	Ant0	1	Reference Level	1.70	Pass
802.11n (HT20)	2412	Ant0	2	Band Edge	-25.43	Pass
802.11n (HT20)	2412	Ant0	3	30MHz~2310MHz	-50.38	Pass
802.11n (HT20)	2412	Ant0	4	2500MHz~5000MHz	-33.20	Pass
802.11n (HT20)	2412	Ant0	5	5000MHz~25000MHz	-33.43	Pass
802.11n (HT20)	2437	Ant0	1	Reference Level	1.57	Pass
802.11n (HT20)	2437	Ant0	2	Band Edge	-46.23	Pass
802.11n (HT20)	2437	Ant0	3	30MHz~2310MHz	-49.87	Pass
802.11n (HT20)	2437	Ant0	4	2500MHz~5000MHz	-34.36	Pass
802.11n (HT20)	2437	Ant0	5	5000MHz~25000MHz	-35.28	Pass
802.11n (HT20)	2462	Ant0	1	Reference Level	1.54	Pass
802.11n (HT20)	2462	Ant0	2	Band Edge	-41.96	Pass
802.11n (HT20)	2462	Ant0	3	30MHz~2310MHz	-45.82	Pass
802.11n (HT20)	2462	Ant0	4	2500MHz~5000MHz	-32.08	Pass
802.11n (HT20)	2462	Ant0	5	5000MHz~25000MHz	-36.35	Pass

9.2 Test Plots


802.11b,2412MHz,Ant0,Plot 1,Reference Level




802.11b,2412MHz,Ant0,Plot 2,Band Edge




802.11b,2412MHz,Ant0,Plot 3,30MHz~2310MHz



802.11b,2412MHz,Ant0,Plot 4,2500MHz~5000MHz



802.11b,2412MHz,Ant0,Plot 5,5000MHz~25000MHz



802.11b,2437MHz,Ant0,Plot 1,Reference Level

