



TEST REPORT

Applicant: OnPoint Systems, LLC

Address: 7 Perimeter Rd. Manchester NH 03103 United States

Equipment Type: SpotOn GPS Fence

Model Name: SOF-11-0001

Brand Name: SpotOn Fence™

FCC ID: 2APPWSOF11

ISED Number: 24233-SOF11

Test Standard: 47 CFR Part 15 Subpart B
ICES-003 Issue 7
ANSI C63.4-2014

Sample Arrival Date: Sep. 03, 2025

Test Date: Sep. 08, 2025

Date of Issue: Nov. 17, 2025

ISSUED BY:

Shanghai Tejet Communications Technology Co., Ltd. Testing Center

Prepared by: Xiang Jibin

Reviewed by: Huang Chengkun

Approved by: Zhang Yanqing
(Laboratory Manager)

Xiang Jibin

Huang Chengkun

Zhang Yanqing

Revision History

Version	Issue Date	Revisions Content
<u>Rev. 01</u>	<u>Nov. 17, 2025</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1 GENERAL INFORMATION	4
1.1 Test Laboratory	4
1.2 Test Location	4
2 PRODUCT INFORMATION	5
2.1 Applicant Information	5
2.2 Manufacturer Information	5
2.3 General Description for Equipment under Test (EUT)	5
2.4 Ancillary Equipment	6
2.5 Technical Information	6
3 SUMMARY OF TEST RESULTS	7
3.1 Test Standards	7
3.2 Verdict	7
3.3 Decision Rule	7
3.4 Test Uncertainty	7
4 GENERAL TEST CONFIGURATIONS	8
4.1 Test Enclosure List	8
4.2 Test Configurations	8
4.3 Test Setups	9
5 TEST ITEMS	11
5.1 Emission Tests	11
5.1.1 Radiated emission	11
5.1.2 Conducted emission	14
ANNEX A TEST RESULTS AND TEST EQUIPMENT LIST	15
A.1 Radiated emission	15
A.2 Conducted emission	22

ANNEX B TEST SETUP PHOTOS	25
ANNEX C EUT EXTERNAL PHOTOS	25
ANNEX D EUT INTERNAL PHOTOS	25

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Address	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China

1.2 Test Location

Name	Shanghai Tejet Communications Technology Co., Ltd. Testing Center
Location	1-2/F., Building 1, No.222, Xuanlan Road, Xuanqiao, Pudong New District, Shanghai, China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1352. The laboratory has been listed by Industry Canada to perform electromagnetic emission measurements. The recognition numbers of test site are 29671.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	OnPoint Systems, LLC
Address	7 Perimeter Rd. Manchester NH 03103 United States

2.2 Manufacturer Information

Manufacturer	OnPoint Systems, LLC
Address	7 Perimeter Rd. Manchester NH 03103 United States

2.3 General Description for Equipment under Test (EUT)

Equipment Type	SpotOn GPS Fence
Model Name Under Test	SOF-11-0001
Series Model Name	N/A
Description of Model Name Differentiation	N/A
Hardware Version	SOF-11-0001
Software Version	V1.1.0.0
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Ancillary Equipment

Ancillary Equipment 1	Magnetic Charger	
	Brand Name	N/A
	Model No.	N/A
	Serial No.	N/A
	Rated Input	N/A
	Rated Output	N/A
Ancillary Equipment 2	Battery	
	Brand Name	N/A
	Model No.	GJ 142851
	Serial No.	N/A
	Capacity	2200 mAh
	Rated Voltage	3.7 V
	Limit Charge Voltage	N/A

2.5 Technical Information

Network and wireless connectivity	4G Network LTE CAT-M Band 2/4/5/12/13/25/26/66 LTE NB-IoT Band 2/4/5/12/13/17/25/66 UWB,BLE,2.4GWIFI,5GWIFI,GPS
Classification of equipment	Class B
Highest frequency generated or used in the device or on which the device operates or tunes(MHz)	7987.2 MHz

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15 Subpart B	Unintentional Radiators
2	ICES-003 Issue 7	Information Technology Equipment (Including Digital Apparatus)
3	ANSI C63.4-2014	American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz

3.2 Verdict

No.	Description	FCC Rule	ISED Rule	Test Verdict	Remark
1	Radiated Emission	15.109	ICES-003, 3.2.2	Pass	--
2	Conducted Emission, AC Ports	15.107	ICES-003, 3.2.1	Pass	--

3.3 Decision Rule

- ☐ No Need
- ☒ Use General conformity decision rule (Consider uncertainty or not ☒ No ☐ Yes)
- ☐ Use Special Conformity Decision Rule (Consider uncertainty or not ☐ No ☐ Yes)

3.4 Test Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

Measurement	Value
Conducted emissions (150 kHz-30 MHz)-AMN	2.6 dB
Radiated emissions (30 MHz-1 GHz)-966#1	4.2 dB
Radiated emissions (1 GHz-18 GHz)-966#1	5.3 dB
Radiated emissions (18 GHz-40 GHz) -966#1	5.6 dB

4 GENERAL TEST CONFIGURATIONS

4.1 Test Enclosure List

Description	Manufacturer	Model	Serial No.	Length	Description	Use
USB Cable	N/A	N/A	N/A	N/A	N/A	☒
Adapter	N/A	N/A	N/A	N/A	N/A	☒


4.2 Test Configurations

All test modes of EUT are listed in the table below.


Test Mode Configuration	Description
Mode 1	<u>The Full System Test Mode</u> EUT + USB Cable + Adapter +Magnetic Charger

4.3 Test Setups


Test Setup 1



Radiated Emission (30 MHz-1 GHz)



Radiated Emission (above 1 GHz)

Test Setup 2

Conducted emission, AC ports

5 TEST ITEMS

5.1 Emission Tests

5.1.1 Radiated emission

5.1.1.1 Limit

FCC:

Frequency range (MHz)	Class B (at 3 m)		Class A (at 3 m)
	Field Strength ($\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)	Field Strength (dB $\mu\text{V/m}$)
30 - 88	100	40	49.5
88 - 216	150	43.5	54
216 - 960	200	46	56.9
Above 960	500	54	60

Note:

- 1) Field Strength (dB $\mu\text{V/m}$) = $20 \cdot \log [\text{Field Strength } (\mu\text{V/m})]$.
- 2) In the emission tables above, the tighter limit applies at the band edges.
- 3) The limits using ANSI C63.4-2014.
- 4) For 30-1000 MHz, the CISPR quasi-peak is employed.

For above 1000 MHz, according to the requirements of FCC 15.35, unless otherwise specified, the limit on peak radio frequency emissions is 20 dB above the maximum permitted average emission limit applicable to the equipment under test.

Frequency range (GHz)	Class B (at 3 m)			Class A (at 3 m)	
	Field Strength ($\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)	Field Strength Average (dB $\mu\text{V/m}$)	Field Strength Peak (dB $\mu\text{V/m}$)
1 - F_M	500	54	74	60	80

Note 1: The highest measurement frequency, F_M , in GHz, shall be determined as next Table.

Note 2: Average Class A limit at 3m L_{3m} is determined by the following conversion formula:

$$L_{3m} = L_{10m} + 20 \cdot \log(d_{10m}/d_{3m})$$

Where:

L_{3m} is Average Class A limit at 3m;

L_{10m} is Average Class A limit at 10m;

d_{10m} is Measurement distance in 10m;

d_{3m} is Measurement distance in 3m.

For this case: $L_{3m} = 49.5 + 20 \cdot \log(10/3) = 60$ (dB $\mu\text{V/m}$).

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1 GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2 GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5 GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ or 40 GHz, whichever is lower.
Note: F_X is Highest frequency generated or used in the device or on which the device operates or tunes.	

ISED:

Frequency range (MHz)	Class A (at 3 m) Quasi-peak (dB μ V/m)	Class B (at 3 m) Quasi-peak (dB μ V/m)
30 - 88	50.0	40.0
88 - 216	54.0	43.5
216 - 230	56.9	46.0
230 - 960	57.0	47.0
960 - 1000	60.0	54.0
Note: The more stringent limit applies at transition frequencies.		

Frequency range (GHz)	Class A (3 m) Average (dB μ V/m)	Class A (3 m) Peak (dB μ V/m)	Class B (3 m) Average (dB μ V/m)	Class B (3 m) Peak (dB μ V/m)
1 - F_M	60	80	54	74
Note: 1. The highest measurement frequency, F_M , in GHz, shall be determined as next Table. 2. The measurement bandwidth shall be 1 MHz or greater. 3. These limit levels apply for a measurement distance of 3 m. If using a different measurement distance, the measured levels shall be extrapolated to the 3 m limit distance using a factor of 20 dB per decade of distance. The measurement distance shall place the measurement antenna in the far field of the ITE or digital apparatus under test. 4. The test site shall have been validated at the distance used for radiated emission measurements on the ITE or digital apparatus under test				

Highest internal frequency (F_X)	Highest measurement frequency (F_M)
$F_X \leq 108 \text{ MHz}$	1GHz
$108 \text{ MHz} \leq F_X \leq 500 \text{ MHz}$	2GHz
$500 \text{ MHz} \leq F_X \leq 1 \text{ GHz}$	5GHz
$F_X \geq 1 \text{ GHz}$	$5 * F_X$ up to a maximum of 40 GHz
Note: F_X is the highest fundamental frequency generated and/or used in the ITE or digital apparatus under test.	

5.1.1.2 Test setup

Please refer to 4.2 section description of test setup of test setup 1. The photo of test setup please refer to ANNEX B.

5.1.1.3 Test procedure

1. The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);
2. All Radiated Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.
3. An initial pre-scan was performed in the chamber using the EMI Receiver in peak detection mode. Quasi-peak measurements were conducted based on the peak sweep graph. The EUT was measured by Bi-Log antenna with 2 orthogonal polarities.
4. The measurement frequency range is from 30 MHz to the 5th harmonic of the maximum frequency of the EUT internal source. The Turn Table is actuated to turn from 0° to 360° , and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.
5. Use the following spectrum analyzer settings:
 Span = wide enough to fully capture the emission being measured
 RBW = 1 MHz for $f \geq 1 \text{ GHz}$, 100 kHz for $f < 1 \text{ GHz}$
 VBW $\geq$ RBW
 Sweep = auto
 Detector function = peak for $f < 1 \text{ GHz}$, peak & RMS Average for $f \geq 1 \text{ GHz}$
 Trace = max hold

5.1.1.4 Test result and test equipment list

Please refer to ANNEX A.1.

Note:

1. Results (dB μ V/m) = Reading (dB μ V/m) + Factor (dB/m)

The reading level is calculated by software which is not shown in the sheet

2. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) – Amplifier Gain (dB)
3. Margin = Limit – Results

5.1.2 Conducted emission

5.1.2.1 Limit

Frequency range (MHz)	Class A		Class B	
	Quasi-peak (dB μ V)	Average (dB μ V)	Quasi-peak (dB μ V)	Average (dB μ V)
0.15 - 0.50	79	66	66 to 56	56 to 46
0.50 - 5	73	60	56	46
5 - 30	73	60	60	50

Note:

- 1) The lower limit shall apply at the band edges.
- 2) The limit decreases linearly with the logarithm of the frequency in the range 0.15 - 0.50 MHz.
- 3) The limit using ANSI C63.4.

5.1.2.2 Test setup

Please refer to 4.2 section description of test setup of test setup 2. The photo of test setup please refer to ANNEX B.

5.1.2.3 Test procedure

1. The test employing the methods of measurement described in the publication referenced in Section 3(b) (ANSI C63.4);
2. The EUT is connected to the power mains through a LISN which provides 50 Ω /50 μ H of coupling impedance for the measuring instrument. The test frequency range is from 150 kHz to 30 MHz. The maximum conducted interference is searched using Peak (PK), Quasi-peak (QP) and Average (AV) detectors; the emission levels that are more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed.
3. Use the following spectrum analyzer settings:
 RBW = 9 kHz
 VBW $\geq$ RBW
 Sweep = 10ms
 Detector function = Peak & Average
 Trace = max hold

5.1.2.4 Test result and test equipment list

Please refer to ANNEX A.2.

Note:

1. Results (dB μ V) = Reading (dB μ V) + Factor (dB)

The reading level is calculated by software which is not shown in the sheet

2. Factor = Insertion loss + Cable loss

3. Margin = Limit – Results

ANNEX A TEST RESULTS AND TEST EQUIPMENT LIST

A.1 Radiated emission

Note 1: Measurements shall be made with a quasi-peak measuring receiver in the frequency range 30 MHz to 1000 MHz. To reduce the testing time, a peak measuring receiver may be used instead of a quasi-peak measuring receiver. In case of dispute, measurement with a quasi-peak measuring receiver will take precedence.

Note 2: The FCC limit is stricter than the IC and only reflects FCC Radiated Emission test data.


Note 3: The Radiated Emission is required to be investigated to the upper frequency of 5th harmonic of the highest internal frequency of EUT or 40 GHz, whichever is lower. The test results above 18GHz are only noise and are not recorded in the report.

Sample No.	SC-SH2560048-S12	Temperature	23.9°C
Humidity	50%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Liu Yabo	Test Date	2025.09.08

Test Mode 1

A.1.1 Test Antenna Vertical, 30 MHz – 1 GHz (FCC)


RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	41.300	18.69	-25.61	40.0	21.31	Peak	41.00	100	Vertical	Pass
2	96.008	28.39	-26.76	43.5	15.11	Peak	47.00	100	Vertical	Pass
3	191.990	35.38	-26.44	43.5	8.12	Peak	331.00	100	Vertical	Pass
4	264.158	38.54	-24.54	46.0	7.46	Peak	22.00	200	Vertical	Pass
5	407.815	26.77	-20.66	46.0	19.23	Peak	186.00	100	Vertical	Pass
6	915.804	30.41	-9.76	46.0	15.59	Peak	2.00	100	Vertical	Pass

A.1.2 Test Antenna Horizontal, 30 MHz – 1 GHz (FCC)

RE Test case_FCC Part 15B_FCC Part 15B Class B 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	66.326	16.33	-27.91	40.0	23.67	Peak	45.00	100	Horizontal	Pass
2	95.863	26.99	-26.79	43.5	16.51	Peak	355.00	200	Horizontal	Pass
3	179.914	32.04	-28.07	43.5	11.46	Peak	271.00	200	Horizontal	Pass
4	191.844	33.45	-26.48	43.5	10.05	Peak	242.00	200	Horizontal	Pass
5	263.903	43.36	-24.55	46.0	2.64	Peak	172.00	100	Horizontal	N/A
5*	263.903	40.79	-24.55	46.0	5.21	QP	172.00	100	Horizontal	Pass
6	287.923	37.14	-23.85	46.0	8.86	Peak	172.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	BH-EMC-L127	2025.02.12	2026.02.11	☒
Test Antenna-Bi-Log	SCHWARZB ECK	VULB 9163	BH-EMC-L132	2024.03.11	2027.03.10	☒
Anechoic Chamber	YiHeng	9m*6m*6m	BH-EMC-L001	2024.04.18	2027.04.17	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V21.919	/		☒

Sample No.	SC-SH2560048-S12	Temperature	23.9°C
Humidity	50%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Liu Yabo	Test Date	2025.09.08

Test Mode 1

A.1.3 Test Antenna Vertical, 1 GHz – 18 GHz


RE Test case FCC Part 15B FCC Part 15B Class B 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1139.100	39.21	-15.54	74.0	34.79	Peak	335.00	100	Vertical	Pass
1**	1139.100	28.24	-15.54	54.0	25.76	AV	335.00	100	Vertical	Pass
2	2033.400	40.82	-13.44	74.0	33.18	Peak	26.00	100	Vertical	Pass
2**	2033.400	31.38	-13.44	54.0	22.62	AV	26.00	100	Vertical	Pass
3	3432.250	47.80	-5.08	74.0	26.20	Peak	199.00	100	Vertical	Pass
3**	3432.250	38.28	-5.08	54.0	15.72	AV	199.00	100	Vertical	Pass
4	6019.250	52.00	-0.32	74.0	22.00	Peak	166.00	100	Vertical	Pass
4**	6019.250	40.04	-0.32	54.0	13.96	AV	166.00	100	Vertical	Pass
5	9318.000	45.65	-5.23	74.0	28.35	Peak	8.00	100	Vertical	Pass
5**	9318.000	36.49	-5.23	54.0	17.51	AV	8.00	100	Vertical	Pass
6	14287.500	47.50	-2.74	74.0	26.50	Peak	233.00	100	Vertical	Pass
6**	14287.500	37.05	-2.74	54.0	16.95	AV	233.00	100	Vertical	Pass

A.1.4 Test Antenna Horizontal, 1 GHz – 18 GHz

RE Test case_FCC Part 15B_FCC Part 15B Class B 1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1279.600	38.67	-15.87	74.0	35.33	Peak	319.00	100	Horizontal	Pass
1**	1279.600	28.35	-15.87	54.0	25.65	AV	319.00	100	Horizontal	Pass
2	2621.100	43.88	-10.05	74.0	30.12	Peak	277.00	100	Horizontal	Pass
2**	2621.100	33.02	-10.05	54.0	20.98	AV	277.00	100	Horizontal	Pass
3	4902.000	48.77	-2.20	74.0	25.23	Peak	95.00	100	Horizontal	Pass
3**	4902.000	38.50	-2.20	54.0	15.50	AV	95.00	100	Horizontal	Pass
4	7346.500	53.03	1.10	74.0	20.97	Peak	112.00	100	Horizontal	Pass
4**	7346.500	42.13	1.10	54.0	11.87	AV	112.00	100	Horizontal	Pass
5	10135.000	46.15	-3.91	74.0	27.85	Peak	216.00	100	Horizontal	Pass
5**	10135.000	35.97	-3.91	54.0	18.03	AV	216.00	100	Horizontal	Pass
6	15273.500	47.47	-1.42	74.0	26.53	Peak	156.00	100	Horizontal	Pass
6**	15273.500	37.65	-1.42	54.0	16.35	AV	156.00	100	Horizontal	Pass


Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	BH-EMC-L127	2025.02.12	2026.02.11	☒
EMI Receiver	KEYSIGHT	N9010B	BH-EMC-L099	2025.02.12	2026.02.11	☒
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	BH-EMC-L111	2024.03.11	2027.03.10	☒
Test Antenna-Horn	A-INFO	LB-180400-KF	BH-EMC-L061	2024.03.11	2027.03.10	☒
Anechoic Chamber	YiHeng	9m*6m*6m	BH-EMC-L001	2024.04.18	2027.04.17	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V21.919	/		☒

A.2 Conducted emission

Note: Devices subject to Part 15 must be tested for all available U.S. voltages and frequencies (such as a nominal 120 VAC, 50/60 Hz and 240 VAC, 50/60 Hz) for which the device is capable of operation. So, The configuration 120 VAC, 60 Hz and 240 VAC, 50 Hz were tested respectively, but only the worst configuration (120 VAC, 60 Hz) shown here.

Sample No.	SC-SH2560048-S12	Temperature	23.1°C
Humidity	51%RH	Test Voltage	AC 120V/60Hz
Test Engineer	Xiang Jibin	Test Date	2025.09.08


A.2.1 AC ports - L Phase



No.	Frequency (MHz)	Results (dBUV)	Factor (dB)	Limit (dBUV)	Margin (dB)	Detector	Line	Verdict
1	0.164	41.93	10.07	65.26	23.33	Peak	L	Pass
1**	0.164	26.34	10.07	55.26	28.92	AV	L	Pass
2	0.518	42.18	10.16	56.00	13.82	Peak	L	Pass
2**	0.518	31.88	10.16	46.00	14.12	AV	L	Pass
3	1.590	33.38	10.28	56.00	22.62	Peak	L	Pass
3**	1.590	20.93	10.28	46.00	25.07	AV	L	Pass
4	3.652	31.22	10.41	56.00	24.78	Peak	L	Pass
4**	3.652	19.72	10.41	46.00	26.28	AV	L	Pass
5	7.316	31.06	10.74	60.00	28.94	Peak	L	Pass
5**	7.316	20.13	10.74	50.00	29.87	AV	L	Pass
6	13.978	36.37	11.13	60.00	23.63	Peak	L	Pass
6**	13.978	26.44	11.13	50.00	23.56	AV	L	Pass

A.2.2 AC ports - N Phase

CE Test case_FCC_CE_FCC PART 15B_Class B



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.150	39.42	10.15	66.00	26.58	Peak	N	Pass
1**	0.150	23.39	10.15	56.00	32.61	AV	N	Pass
2	0.524	40.02	10.18	56.00	15.98	Peak	N	Pass
2**	0.524	25.27	10.18	46.00	20.73	AV	N	Pass
3	1.212	33.19	10.25	56.00	22.81	Peak	N	Pass
3**	1.212	20.57	10.25	46.00	25.43	AV	N	Pass
4	3.276	33.29	10.32	56.00	22.71	Peak	N	Pass
4**	3.276	19.69	10.32	46.00	26.31	AV	N	Pass
5	5.804	33.07	10.51	60.00	26.93	Peak	N	Pass
5**	5.804	20.29	10.51	50.00	29.71	AV	N	Pass
6	14.958	36.77	11.12	60.00	23.23	Peak	N	Pass
6**	14.958	25.36	11.12	50.00	24.64	AV	N	Pass

Equipment Information						
Equipment Name	Manufacturer	Model	Equipment No.	Cal. Date	Cal. Due	Use
EMI Receiver	KEYSIGHT	N9038A	TJEMC144	2025.02.11	2026.02.10	☒
LISN	SCHWARZBECK	NSLK 8127	BH-EMC-L011	2025.02.11	2026.02.10	☒
10dB Limiter	SCHWARZBECK	VTSD 9561-F	BH-EMC-L014	2025.02.11	2026.02.10	☒
Shielded Room	YiHeng	4.1m*4.0m *3.2m	BH-EMC-L006	2024.02.22	2027.02.21	☒
Description	Manufacturer	Name	Version	/		Use
Test Software	BALUN	BL410-E	V19.618	/		☒

ANNEX B TEST SETUP PHOTOS

Please refer the document “BL-SH2580953-AE.PDF”.

ANNEX C EUT EXTERNAL PHOTOS

Please refer the document “BL-SH2580953-AW.PDF”.

ANNEX D EUT INTERNAL PHOTOS

Please refer the document “BL-SH2580953-AI.PDF”.

Statement

1. The Testing Center guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. For the report with Accreditation Symbol, the items marked with "☆" are not within the accredited scope.
3. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the test report stamp.
4. The test data and results are only valid for the tested samples provided by the customer.
5. This report shall not be partially reproduced without the written permission of the Testing Center.
6. Any objection shall be raised to the Testing Center within 30 days after receiving the report.

--END OF REPORT--