

TEST REPORT

Applicant Name : Fanvil Technology Co., LTD.
Address : 10/F Block A, Dualshine Global Science Innovation Honglang
North 2nd Road, Bao'an District, Shenzhen, 518101, China
Report Number : SZNS220429-17654E-RF-00B
FCC ID: 2APPZ-X5UV2

Test Standard (s)

FCC PART 15.247


Sample Description

Product Type: IP Phone
Model No.: X5U V2
Multiple Model(s) No.: X5U (Please refer to DOS for Model difference)
Trade Mark: 
Date Received: 2022/04/29
Report Date: 2022/06/08

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:



Ting Lü
EMC Engineer

Approved By:



Robert Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

TABLE OF CONTENTS

GENERAL INFORMATION	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	8
EXTERNAL I/O CABLE	8
SUMMARY OF TEST RESULTS	12
TEST EQUIPMENT LIST	13
FCC §15.247 (I) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)	15
FCC §15.203 - ANTENNA REQUIREMENT	16
APPLICABLE STANDARD	16
ANTENNA CONNECTOR CONSTRUCTION	16
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	17
APPLICABLE STANDARD	17
EUT SETUP	17
EMI TEST RECEIVER SETUP	17
TEST PROCEDURE	17
CORRECTED FACTOR & MARGIN CALCULATION	18
TEST DATA	18
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	23
APPLICABLE STANDARD	23
EUT SETUP	23
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	24
TEST PROCEDURE	24
FACTOR & MARGIN CALCULATION	24
TEST DATA	24
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH	32
APPLICABLE STANDARD	32
TEST PROCEDURE	32
TEST DATA	32
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	35

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE38
 APPLICABLE STANDARD38
 TEST PROCEDURE38
 TEST DATA38
FCC §15.247(E) - POWER SPECTRAL DENSITY.....40
 APPLICABLE STANDARD40
 TEST PROCEDURE40
 TEST DATA40

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE: 2402-2480MHz
Maximum Conducted Peak Output Power	BLE:4.29dBm
Modulation Technique	BLE: GFSK
Antenna Specification*	2.7dBi (provided by the applicant)
Voltage Range	DC 5V from adapter or DC 48V from POE
Sample serial number	RE&CE: SZNS220429-17654E-RF-S1; RF:SZNS220429-17654E-RF-S2 (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.73dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.66dB
	30MHz - 1GHz	4.28dB
	1GHz - 18GHz	4.98dB
	18GHz - 26.5GHz	5.06dB
	26.5GHz - 40GHz	4.72dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 4297.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For BLE mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.


EUT Exercise Software

“MP Tool”* exercise software was used, and the power level is 31*. The software and power level was provided by the manufacturer.

Duty cycle

Mode	T _{on} (ms)	T _{on+off} (ms)	Duty Cycle (%)
BLE 1M	2.925	3.766	77.67

BLE-1M



Date: 30.MAY.2022 18:04:02

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
DELL	NoteBook	Latitude E4710	PC201911252059
HUAWEI	Router	WS5100	A4933FEF1D01
TECNO	Adapter	U050TSA	AH07015321906
Xilang	Headphone	Unknown	Earphone
Sandisk	USB flash disk	Unknown	USB flash disk
GOSPELL	POE Adapter	G0720-480-050	212701319

External I/O Cable


Cable Description	Length (m)	From/Port	To
Un-shielding Detachable RJ45 Cable	8.0	EUT	Notebook
Unshielded detachable AC cable	1.0	LISN	POE
Un-shielded detachable RJ45 Cable	8.0	EUT	Router
Un-shielded detachable RJ11 Cable	1.2	EUT	Earphone
Unshielded detachable DC cable	1.2	EUT	Adapter
Un-shielded detachable RJ45 Cable	8.0	Router	POE
Un-shielded detachable RJ45 Cable	0.8	EUT	POE

Block Diagram of Test Setup


For conducted emission (Adapter power supply):




For conducted emission (POE power supply):




For radiated emission below 1 GHz (POE power supply):



For radiated emission below 1 GHz (Adapter power supply):



For radiated emission above 1 GHz:



SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
FCC §15.247 (i), §2.1091	Maximum Permissible Exposure(MPE)	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2021/12/13	2022/12/12
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2021/12/13	2022/12/12
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2021/12/13	2022/12/12
Unknown	RF Coaxial Cable	No.17	N0350	2021/12/14	2022/12/13
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2021/12/13	2022/12/12
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2021/12/13	2022/12/12
SONOMA INSTRUMENT	Amplifier	310 N	186131	2021/11/09	2022/11/08
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2021/11/09	2022/11/08
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2021/11/11	2022/11/10
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	9120D-1067	2020/01/05	2023/01/04
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2020/01/05	2023/01/04
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.11	N1000	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.12	N040	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.13	N300	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.14	N800	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.15	N600	2021/12/14	2022/12/13
Unknown	RF Coaxial Cable	No.16	N650	2021/12/14	2022/12/13
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2021/12/14	2022/12/13

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde & Schwarz	Spectrum Analyzer	FSV-40	101948	2021/12/13	2022/12/12
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2021/12/14	2022/12/13
Unknown	RF Cable	Unknown	Unknown	Each time	/

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

For worst case:

Frequency (MHz)	Maximum Antenna Gain		Tune up conducted power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2402-2480	2.7	1.86	4.5	2.82	20	0.001	1

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna which was permanently attached, and the maximum antenna gain is 2.7dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



- Note: 1. Support units were connected to second LISN.
 2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Corrected Factor & Margin Calculation

The Transd factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions


Temperature:	23 °C
Relative Humidity:	52 %
ATM Pressure:	101.0 kPa

The testing was performed by Jason on 2022-06-06.

EUT operation mode: Transmitting (Worst case is high channel)


POE:

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.154	9.80	22.83	32.63	55.79	-23.16	Average
2	0.154	9.80	36.96	46.76	65.79	-19.03	QP
3	0.200	9.80	18.86	28.66	53.61	-24.95	Average
4	0.200	9.80	30.05	39.85	63.61	-23.76	QP
5	0.325	9.80	20.46	30.26	49.58	-19.32	Average
6	0.325	9.80	27.60	37.40	59.58	-22.18	QP
7	1.893	9.82	9.02	18.84	46.00	-27.16	Average
8	1.893	9.82	15.82	25.64	56.00	-30.36	QP
9	3.749	9.84	12.61	22.45	46.00	-23.55	Average
10	3.749	9.84	19.70	29.54	56.00	-26.46	QP
11	5.088	9.85	10.89	20.74	50.00	-29.26	Average
12	5.088	9.85	19.22	29.07	60.00	-30.93	QP


AC 120V/60 Hz, Neutral



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.168	9.80	23.11	32.91	55.04	-22.13	Average
2	0.168	9.80	35.56	45.36	65.04	-19.68	QP
3	0.211	9.80	16.14	25.94	53.17	-27.23	Average
4	0.211	9.80	28.67	38.47	63.17	-24.70	QP
5	0.316	9.80	18.94	28.74	49.81	-21.07	Average
6	0.316	9.80	25.69	35.49	59.81	-24.32	QP
7	0.622	9.81	9.69	19.50	46.00	-26.50	Average
8	0.622	9.81	16.17	25.98	56.00	-30.02	QP
9	3.792	9.84	12.01	21.85	46.00	-24.15	Average
10	3.792	9.84	19.71	29.55	56.00	-26.45	QP
11	5.326	9.90	13.42	23.32	50.00	-26.68	Average
12	5.326	9.90	20.39	30.29	60.00	-29.71	QP


Adapter:

AC 120V/60 Hz, Line



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.199	9.80	3.39	13.19	53.64	-40.45	Average
2	0.199	9.80	9.68	19.48	63.64	-44.16	QP
3	0.233	9.80	5.30	15.10	52.35	-37.25	Average
4	0.233	9.80	9.73	19.53	62.35	-42.82	QP
5	0.415	9.80	21.34	31.14	47.55	-16.41	Average
6	0.415	9.80	23.53	33.33	57.55	-24.22	QP
7	1.447	9.81	5.31	15.12	46.00	-30.88	Average
8	1.447	9.81	9.08	18.89	56.00	-37.11	QP
9	3.033	9.83	5.72	15.55	46.00	-30.45	Average
10	3.033	9.83	8.49	18.32	56.00	-37.68	QP
11	7.738	9.88	7.49	17.37	50.00	-32.63	Average
12	7.738	9.88	11.74	21.62	60.00	-38.38	QP



AC 120V/60 Hz, Neutral



	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.156	9.80	8.52	18.32	55.66	-37.34	Average
2	0.156	9.80	14.35	24.15	65.66	-41.51	QP
3	0.240	9.80	9.76	19.56	52.09	-32.53	Average
4	0.240	9.80	13.58	23.38	62.09	-38.71	QP
5	0.416	9.80	26.49	36.29	47.53	-11.24	Average
6	0.416	9.80	28.48	38.28	57.53	-19.25	QP
7	0.851	9.81	17.15	26.96	46.00	-19.04	Average
8	0.851	9.81	18.92	28.73	56.00	-27.27	QP
9	2.791	9.83	11.29	21.12	46.00	-24.88	Average
10	2.791	9.83	15.91	25.74	56.00	-30.26	QP
11	7.329	9.97	9.58	19.55	50.00	-30.45	Average
12	7.329	9.97	16.69	26.66	60.00	-33.34	QP

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**

FCC §15.247 (d); §15.209; §15.205;

EUT Setup**Below 1 GHz:****Above 1GHz:**

The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level / Corrected Amplitude} - \text{Limit} \\ \text{Level / Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	25.1~29 °C
Relative Humidity:	54~68 %
ATM Pressure:	101.0 kPa


The testing was performed by Leo on 2022-06-06 for below 1GHz, and Leo from 2022-05-26 to 2022-06-07 for above 1GHz.

EUT operation mode: Transmitting(Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes orientation was recorded)

30MHz-1GHz: (worst case is High channel)

POE:

Horizontal:



Site : chamber

Condition: 3m HORIZONTAL


Job No. : SZNS220429-17654E-RF

Test Mode: BLE

Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	85.448	-15.44	35.06	19.62	40.00	-20.38	Peak
2	142.950	-15.52	40.45	24.93	43.50	-18.57	Peak
3	273.114	-10.03	45.01	34.98	46.00	-11.02	Peak
4	325.026	-8.27	43.42	35.15	46.00	-10.85	Peak
5	351.092	-7.34	42.44	35.10	46.00	-10.90	Peak
6	377.094	-7.22	41.13	33.91	46.00	-12.09	Peak

Vertical




Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220429-17654E-RF
 Test Mode: BLE
 Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	37.796	-10.85	41.56	30.71	40.00	-9.29	Peak
2	52.002	-9.97	39.17	29.20	40.00	-10.80	Peak
3	143.012	-15.52	47.04	31.52	43.50	-11.98	Peak
4	272.995	-10.04	42.37	32.33	46.00	-13.67	Peak
5	326.453	-8.18	39.70	31.52	46.00	-14.48	Peak
6	377.094	-7.22	38.78	31.56	46.00	-14.44	Peak

Adapter:


Horizontal:



Site : chamber
 Condition: 3m HORIZONTAL
 Job No. : SZNS220429-17654E-RF
 Test Mode: BLE
 Note : Adapter

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	87.265	-14.80	39.69	24.89	40.00	-15.11	Peak
2	105.272	-11.86	38.31	26.45	43.50	-17.05	Peak
3	143.012	-15.52	45.41	29.89	43.50	-13.61	Peak
4	272.995	-10.04	46.04	36.00	46.00	-10.00	Peak
5	292.186	-9.29	42.81	33.52	46.00	-12.48	Peak
6	377.094	-7.22	41.92	34.70	46.00	-11.30	Peak

Vertical



Site : chamber
 Condition: 3m VERTICAL
 Job No. : SZNS220429-17654E-RF
 Test Mode: BLE
 Note : Adpter

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	33.548	-11.93	43.87	31.94	40.00	-8.06	Peak
2	52.025	-9.98	38.27	28.29	40.00	-11.71	Peak
3	143.012	-15.52	43.85	28.33	43.50	-15.17	Peak
4	158.946	-14.36	39.70	25.34	43.50	-18.16	Peak
5	377.094	-7.22	38.54	31.32	46.00	-14.68	Peak
6	403.073	-6.73	38.67	31.94	46.00	-14.06	Peak

Above 1GHz: (the worst case is adapter)

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/AV		Height (m)	Polar (H/V)				
Low Channel 2402 MHz									
2310	67.78	PK	43	1.3	H	-7.24	60.54	74	-13.46
2310	54.37	AV	43	1.3	H	-7.24	47.13	54	-6.87
2310	66.76	PK	201	1.4	V	-7.24	59.52	74	-14.48
2310	54.46	AV	201	1.4	V	-7.24	47.22	54	-6.78
2390	67.84	PK	261	1.5	H	-7.22	60.62	74	-13.38
2390	55.47	AV	261	1.5	H	-7.22	48.25	54	-5.75
2390	68.16	PK	49	1.6	V	-7.22	60.94	74	-13.06
2390	55.57	AV	49	1.6	V	-7.22	48.35	54	-5.65
4804	54.34	PK	246	1.6	H	-3.51	50.83	74	-23.17
4804	55.60	PK	242	2.1	V	-3.51	52.09	74	-21.91
Middle Channel 2440MHz									
4880	54.18	PK	114	2.2	H	-3.38	50.8	74	-23.20
4880	54.69	PK	262	1.8	V	-3.38	51.31	74	-22.69
High Channel 2480MHz									
2483.5	68.88	PK	175	2.2	H	-7.20	61.68	74	-12.32
2483.5	56.31	AV	175	2.2	H	-7.20	49.11	54	-4.89
2483.5	68.57	PK	131	1.4	V	-7.20	61.37	74	-12.63
2483.5	56.41	AV	131	1.4	V	-7.20	49.21	54	-4.79
2500	68.50	PK	40	2.5	H	-7.18	61.32	74	-12.68
2500	56.13	AV	40	2.5	H	-7.18	48.95	54	-5.05
2500	68.58	PK	140	1.1	V	-7.18	61.4	74	-12.60
2500	55.88	AV	140	1.1	V	-7.18	48.7	54	-5.30
4960	52.87	PK	80	1.4	H	-3.01	49.86	74	-24.14
4960	54.36	PK	89	1.3	V	-3.01	51.35	74	-22.65

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Corrected Factor + Reading

Margin = Corrected. Amplitude - Limit


The other spurious emission which is 20dB to the limit or in noise floor was not recorded.

The test result of peak was less than the limit of average, so just peak value were recorded.


Pre-scan plots for Low channel

1-18GHz

Horizontal:




Vertical:




18-25GHz

Horizontal:



Vertical:




FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa


The testing was performed by Ting Lu on 2022-05-30.

EUT operation mode: Transmitting

Test Result: Compliant..


Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	Limit (kHz)
BLE 1M			
Low	2402	0.663	≥500
Middle	2440	0.651	≥500
High	2480	0.654	≥500

6dB Bandwidth, Low Channel




Date: 30.MAY.2022 17:09:57

6dB Bandwidth, Middle Channel



Date: 30.MAY.2022 17:08:05

6dB Bandwidth, High Channel



Date: 30.MAY.2022 17:11:54


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	28.1 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa


The testing was performed by Ting Lu on 2022-05-30.

EUT operation mode: Transmitting

Test Result: Compliant.


Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1M			
Low	2402	2.24	30
Middle	2440	2.85	30
High	2480	4.29	30

Low Channel




Date: 30.MAY.2022 17:04:04

Middle Channel



Date: 30.MAY.2022 17:05:11

High Channel



Date: 30.MAY.2022 17:02:33


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.



Test Data

Environmental Conditions


Temperature:	28.1 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lu on 2022-05-30.

EUT operation mode: Transmitting


Test Result: Compliant.

Band Edge, Left Side



Date: 30.MAY.2022 17:19:48

Band Edge, Right Side



Date: 30.MAY.2022 17:16:16


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions


Temperature:	28.1 °C
Relative Humidity:	57 %
ATM Pressure:	101.0 kPa

The testing was performed by Ting Lu on 2022-05-30.

EUT operation mode: Transmitting


Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M			
Low	2402	-11.95	≤ 8
Middle	2440	-12.64	≤ 8
High	2480	-10.53	≤ 8

Power Spectral Density, Low Channel




Date: 30.MAY.2022 17:25:27

Power Spectral Density, Middle Channel



Date: 30.MAY.2022 17:45:29

Power Spectral Density, High Channel



***** END OF REPORT *****