

TEST REPORT

Applicant Name : Fanvil Technology Co., LTD.
Address : 10/F Block A, Dualshine Global Science Innovation Honglang
North 2nd Road, Bao'an District, Shenzhen, 518101, China
Report Number : RA230424-21726E-RF-00A
FCC ID: 2APPZ-Y501WY

Test Standard (s)

FCC PART 15.247

Sample Description


Product Type: SIP Intercom/SIP Care Intercom
Model No.: Y501W-Y
Multiple Model(s) No.: Y501W, A10W, A10W-E
Trade Mark: 
Date Received: 2023/04/24
Report Date: 2023/06/03

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:



Dave Liang
EMC Engineer



Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY	6
SYSTEM TEST CONFIGURATION	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	7
EUT EXERCISE SOFTWARE	7
DUTY CYCLE	7
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION	13
FCC §15.203 - ANTENNA REQUIREMENT.....	14
APPLICABLE STANDARD	14
ANTENNA CONNECTOR CONSTRUCTION	14
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	15
APPLICABLE STANDARD	15
EUT SETUP	15
EMI TEST RECEIVER SETUP.....	15
TEST PROCEDURE	15
FACTOR & OVER LIMIT CALCULATION.....	16
TEST DATA	16
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS	21
APPLICABLE STANDARD	21
EUT SETUP	21
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	22
TEST PROCEDURE	22
FACTOR & OVER LIMIT/MARGIN CALCULATION	22
TEST DATA	22
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	33
APPLICABLE STANDARD	33
TEST PROCEDURE	33
TEST DATA	33
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	34
APPLICABLE STANDARD	34
TEST PROCEDURE	34
TEST DATA	34

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	35
APPLICABLE STANDARD	35
TEST PROCEDURE	35
TEST DATA	35
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	37
APPENDIX	38
APPENDIX A: DTS BANDWIDTH	38
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	45
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	52
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	53
APPENDIX E: BAND EDGE MEASUREMENTS.....	60
APPENDIX F: DUTY CYCLE	64

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230424-21726E-RF-00A	Original Report	2023/06/03

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product Type	SIP Intercom/SIP Care Intercom
Model No.	Y501W-Y
Multiple Model(s) No.	Y501W, A10W, A10W-E (The model differences please refer to DOS)
Frequency Range	Wi-Fi: 2412-2462MHz
Maximum Conducted Output Power	16.18dBm
Modulation Technique	DSSS, OFDM
Antenna Specification*	2.9dBi (provided by the applicant)
Voltage Range	DC 48V from POE or DC 12V
Sample serial number	251K_1 for Conducted and Radiated Emissions Test 251K_2 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.06dB
	30MHz - 1GHz	5.08dB
	1GHz - 18GHz	4.96dB
	18GHz - 26.5GHz	5.16dB
	26.5GHz - 40GHz	4.64dB
Temperature		1℃
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4 GHz Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT40 mode was tested with Channel 3, 6 and 9.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“SecureCRTportable.exe”* software was used to test and power level as below:

Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	80	80	80
802.11g	6Mbps	90	90	90
802.11n-HT20	MCS0	90	90	90
802.11n-HT40	MCS0	80	80	80

The software and power level was provided by applicant.

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
Lenovo	NoteBook	T430	23447YC
GOSPELL	POE	G0720-480-050	212701319
Unknown	Battery (DC 12V)	Unknown	Unknown
TP-link	Adapter	T120100-2C1	N/A


External I/O Cable

Cable Description	Length (m)	From/Port	To
Un-shielding Detachable AC Cable	1.0	LISN/ AC Mains	POE/ Receptacle
Un-shielding Detachable DC Cable	1.0	Adapter	EUT
Un-shielding Detachable network Cable	1.0	POE	EUT
Un-shielding Detachable network Cable	10.0	EUT/POE	NoteBook
Un-shielding Detachable DC Cable	1.5	Battery	EUT


Block Diagram of Test Setup

Powered by POE

For conducted emission




For Radiated Emissions:




Powered from DC12V

For conducted emission



For Radiated Emissions:



Note: the support table edge was flush with center of turntable

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §2.1091	MPE-BASED EXEMPTION	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ENV216	101314	2022/11/25	2023/11/24
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 191218 (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software:e3 191218 (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/1 8G-10SS	5	2022/11/25	2023/11/24
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
Agilent	Power Sensor	U2021XA	MY5425003	2023/02/25	2024/02/24
WEINSCHHEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (I) & §1.1307 (B) (3) & §2.1091- MPE-BASED EXEMPTION

Applicable Standard

According to subpart 1.1307 (b) (3) and subpart 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

According to KDB 447498 D04 Interim General RF Exposure Guidance

MPE-Based Exemption:

General frequency and separation-distance dependent MPE-based effective radiated power(ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table 1 to § 1.1307(b)(3)(i)(C) - Single RF Sources Subject to Routine Environmental Evaluation

RF Source frequency (MHz)	Threshold ERP (watts)
0.3-1.34	$1,920 R^2$.
1.34-30	$3,450 R^2/f^2$.
30-300	$3.83 R^2$.
300-1,500	$0.0128 R^2 f$.
1,500-100,000	$19.2 R^2$.

R is the minimum separation distance in meters

f = frequency in MHz

Result

Mode	Frequency (MHz)	Tune up conducted power	Antenna Gain		ERP		Evaluation Distance (m)	ERP Limit (W)
		(dBm)	(dBi)	(dBd)	(dBm)	(W)		
2.4G Wi-Fi	2412-2462	16.5	2.9	0.75	17.25	0.053	0.2	0.768
5G Wi-Fi	5150-5250	16.0	3.5	1.35	17.35	0.054	0.2	0.768
	5725-5850	16.0	3.5	1.35	17.35	0.054	0.2	0.768

Note: 1. The tune up conducted power and antenna gain was declared by the applicant.
 2. The 2.4G/5G Wi-Fi cannot Simultaneous transmitting
 3. 0dBd=2.15dBi

To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliant.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an internal antenna arrangement, which was permanently attached and the antenna gain is 2.9dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the device was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Over Limit Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over Limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a over limit of -7 dB means the emission is 7 dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{level} - \text{Limit} \\ \text{Level} &= \text{reading level} + \text{Factor}\end{aligned}$$

Test Data

Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa


The testing was performed by Jerry Wu on 2023-05-17 and 2023-06-02.

EUT operation mode: Transmitting

Wi-Fi: (Worst case is 802.11b mode, Low Channel)


Powered by POE:

AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : RA230424-21726E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.165	10.35	30.43	40.78	55.22	-14.44	Average
2	0.165	10.35	40.76	51.11	65.22	-14.11	QP
3	0.216	10.31	25.14	35.45	52.95	-17.50	Average
4	0.216	10.31	33.70	44.01	62.95	-18.94	QP
5	0.480	10.55	35.36	45.91	46.33	-0.42	Average
6	0.480	10.55	40.73	51.28	56.33	-5.05	QP
7	0.634	10.64	22.11	32.75	46.00	-13.25	Average
8	0.634	10.64	27.89	38.53	56.00	-17.47	QP
9	2.414	10.44	21.41	31.85	46.00	-14.15	Average
10	2.414	10.44	26.18	36.62	56.00	-19.38	QP
11	7.233	10.62	22.04	32.66	50.00	-17.34	Average
12	7.233	10.62	26.41	37.03	60.00	-22.97	QP


AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA230424-21726E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.153	10.27	31.86	42.13	55.81	-13.68	Average
2	0.153	10.27	41.51	51.78	65.81	-14.03	QP
3	0.222	10.30	23.84	34.14	52.73	-18.59	Average
4	0.222	10.30	32.80	43.10	62.73	-19.63	QP
5	0.479	10.46	35.53	45.99	46.35	-0.36	Average
6	0.479	10.46	40.74	51.20	56.35	-5.15	QP
7	0.591	10.47	23.14	33.61	46.00	-12.39	Average
8	0.591	10.47	28.62	39.09	56.00	-16.91	QP
9	2.414	10.51	22.40	32.91	46.00	-13.09	Average
10	2.414	10.51	26.70	37.21	56.00	-18.79	QP
11	18.971	10.21	22.40	32.61	50.00	-17.39	Average
12	18.971	10.21	26.27	36.48	60.00	-23.52	QP


Powered from DC 12V port:

AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : RA230424-21726E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.188	10.30	14.34	24.64	54.14	-29.50	Average
2	0.188	10.30	29.58	39.88	64.14	-24.26	QP
3	0.241	10.34	13.79	24.13	52.04	-27.91	Average
4	0.241	10.34	24.82	35.16	62.04	-26.88	QP
5	0.500	10.57	30.04	40.61	46.00	-5.39	Average
6	0.500	10.57	36.31	46.88	56.00	-9.12	QP
7	0.514	10.58	27.91	38.49	46.00	-7.51	Average
8	0.514	10.58	37.16	47.74	56.00	-8.26	QP
9	2.675	10.46	13.62	24.08	46.00	-21.92	Average
10	2.675	10.46	22.39	32.85	56.00	-23.15	QP
11	5.447	10.57	11.59	22.16	50.00	-27.84	Average
12	5.447	10.57	18.79	29.36	60.00	-30.64	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA230424-21726E-RF
 Mode : 2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.194	10.29	18.15	28.44	53.88	-25.44	Average
2	0.194	10.29	31.38	41.67	63.88	-22.21	QP
3	0.237	10.32	19.41	29.73	52.22	-22.49	Average
4	0.237	10.32	29.29	39.61	62.22	-22.61	QP
5	0.499	10.47	20.70	31.17	46.02	-14.85	Average
6	0.499	10.47	30.32	40.79	56.02	-15.23	QP
7	0.510	10.47	20.65	31.12	46.00	-14.88	Average
8	0.510	10.47	31.30	41.77	56.00	-14.23	QP
9	2.557	10.51	2.71	13.22	46.00	-32.78	Average
10	2.557	10.51	14.63	25.14	56.00	-30.86	QP
11	29.901	10.22	6.63	16.85	50.00	-33.15	Average
12	29.901	10.22	14.66	24.88	60.00	-35.12	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission performed in the 3 meters, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Over Limit/Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit or Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an over limit/margin of -7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\begin{aligned} \text{Margin/Over Limit} &= \text{Corrected Amplitude/Level-Limit} \\ \text{Corrected Amplitude/Level} &= \text{Reading} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.3 °C
Relative Humidity:	51~56 %
ATM Pressure:	101.0 kPa

The testing was performed by Jimi Zheng on 2023-05-17 for below 1GHz and by Jason Liu on 2023-05-12 for above 1GHz.


EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes of orientation was recorded)

30MHz-1GHz: (Worst case is 802.11b mode, middle Channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.


Powered by POE:

Horizontal



Site : chamber
Condition: 3m HORIZONTAL
Job No. : RA230424-21726E-RF
Test Mode: 2.4G WIFI Transmitting
Note : POE


Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.415	-10.25	31.64	21.39	40.00	-18.61 Peak
2	181.681	-12.57	45.58	33.01	43.50	-10.49 Peak
3	280.269	-9.57	42.59	33.02	46.00	-12.98 Peak
4	355.272	-7.50	36.42	28.92	46.00	-17.08 Peak
5	416.362	-6.20	36.06	29.86	46.00	-16.14 Peak
6	769.760	-0.20	29.84	29.64	46.00	-16.36 Peak

Vertical

Site : chamber
Condition: 3m VERTICAL
Job No. : RA230424-21726E-RF
Test Mode: 2.4G WIFI Transmitting
Note : POE

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	33.357	-11.96	44.67	32.71	40.00	-7.29	Peak
2	51.458	-9.95	43.87	33.92	40.00	-6.08	QP
3	78.551	-16.66	48.06	31.40	40.00	-8.60	Peak
4	121.176	-13.77	46.22	32.45	43.50	-11.05	Peak
5	203.969	-11.74	40.94	29.20	43.50	-14.30	Peak
6	433.305	-5.73	36.52	30.79	46.00	-15.21	Peak

Powered from DC 12V:

Horizontal

Site : chamber

Condition: 3m HORIZONTAL


Job No. : RA230424-21726E-RF

Test Mode: 2.4G WIFI Transmitting

Note : DC 12V

	Freq	Factor	Read Level	Level	Limit	Over	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	36.621	-11.08	29.62	18.54	40.00	-21.46	Peak
2	57.443	-9.99	28.98	18.99	40.00	-21.01	Peak
3	104.903	-11.82	27.84	16.02	43.50	-27.48	Peak
4	247.465	-10.66	30.09	19.43	46.00	-26.57	Peak
5	569.111	-3.85	31.98	28.13	46.00	-17.87	Peak
6	925.756	1.78	29.05	30.83	46.00	-15.17	Peak

Vertical



Site : chamber
Condition: 3m VERTICAL
Job No. : RA230424-21726E-RF
Test Mode: 2.4G WIFI Transmitting
Note : DC 12V

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	33.489	-11.94	34.53	22.59	40.00	-17.41	Peak
2	107.888	-11.99	28.46	16.47	43.50	-27.03	Peak
3	148.441	-15.36	33.71	18.35	43.50	-25.15	Peak
4	247.248	-10.65	31.45	20.80	46.00	-25.20	Peak
5	551.190	-4.05	37.45	33.40	46.00	-12.60	Peak
6	909.268	1.66	29.10	30.76	46.00	-15.24	Peak

1-25 GHz: (worst case powered by POE)

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11b									
Low Channel(2412MHz)									
2387.28	68.03	PK	124	2.3	H	-10.71	57.32	74	-16.68
2387.28	54.40	Ave.	124	2.3	H	-10.71	43.69	54	-10.31
2387.16	67.22	PK	333	2.1	V	-10.71	56.51	74	-17.49
2387.16	53.34	Ave.	333	2.1	V	-10.71	42.63	54	-11.37
2390	67.48	PK	209	1.8	H	-10.70	56.78	74	-17.22
2390	53.52	Ave.	209	1.8	H	-10.70	42.82	54	-11.18
2390	65.88	PK	238	1.9	V	-10.70	55.18	74	-18.82
2390	51.90	Ave.	238	1.9	V	-10.70	41.20	54	-12.80
4824	63.11	PK	154	1.3	H	-6.10	57.01	74	-16.99
4824	55.70	Ave.	154	1.3	H	-6.10	49.60	54	-4.40
4824	62.02	PK	196	1.7	V	-6.10	55.92	74	-18.08
4824	54.18	Ave.	196	1.7	V	-6.10	48.08	54	-5.92
Middle Channel(2437MHz)									
4874	62.73	PK	134	1.3	H	-5.95	56.78	74	-17.22
4874	54.25	AV	134	1.3	H	-5.95	48.3	54	-5.7
4874	61.36	PK	309	2.1	V	-5.95	55.41	74	-18.59
4874	53.07	AV	309	2.1	V	-5.95	47.12	54	-6.88
High Channel(2462 MHz)									
2483.5	67.72	PK	240	1.2	H	-10.55	57.17	74	-16.83
2483.5	53.94	Ave.	240	1.2	H	-10.55	43.39	54	-10.61
2483.5	66.27	PK	123	2.1	V	-10.55	55.72	74	-18.28
2483.5	53.19	Ave.	123	2.1	V	-10.55	42.64	54	-11.36
2488.78	68.57	PK	60	1.7	H	-10.51	58.06	74	-15.94
2488.78	55.13	Ave.	60	1.7	H	-10.51	44.62	54	-9.38
2488.62	67.70	PK	134	2.3	V	-10.51	57.19	74	-16.81
2488.62	54.49	Ave.	134	2.3	V	-10.51	43.98	54	-10.02
4924	61.82	PK	233	1.1	H	-5.67	56.15	74	-17.85
4924	53.83	AV	233	1.1	H	-5.67	48.16	54	-5.84
4924	60.01	PK	246	1.9	V	-5.67	54.34	74	-19.66
4924	52.74	AV	246	1.9	V	-5.67	47.07	54	-6.93

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11g									
Low Channel(2412MHz)									
2389.83	77.18	PK	256	1.4	H	-10.70	66.48	74	-7.52
2389.83	57.70	Ave.	256	1.4	H	-10.70	47.00	54	-7.00
2389.94	75.11	PK	308	1.9	V	-10.70	64.41	74	-9.59
2389.94	54.87	Ave.	308	1.9	V	-10.70	44.17	54	-9.83
2390	76.47	PK	237	1.6	H	-10.70	65.77	74	-8.23
2390	55.82	Ave.	237	1.6	H	-10.70	45.12	54	-8.88
2390	74.20	PK	334	1.8	V	-10.70	63.50	74	-10.50
2390	53.84	Ave.	334	1.8	V	-10.70	43.14	54	-10.86
4824	60.11	PK	159	1.8	H	-6.10	54.01	74	-19.99
4824	45.62	Ave.	159	1.8	H	-6.10	39.52	54	-14.48
4824	60.03	PK	149	2	V	-6.10	53.93	74	-20.07
4824	45.08	Ave.	149	2	V	-6.10	38.98	54	-15.02
Middle Channel(2437MHz)									
4874	60.06	PK	68	1.4	H	-5.95	54.11	74	-19.89
4874	45.63	Ave.	68	1.4	H	-5.95	39.68	54	-14.32
4874	59.85	PK	312	1.1	V	-5.95	53.9	74	-20.10
4874	45.17	Ave.	312	1.1	V	-5.95	39.22	54	-14.78
High Channel(2462MHz)									
2483.5	74.31	PK	39	2.4	H	-10.55	63.76	74	-10.24
2483.5	57.73	Ave.	39	2.4	H	-10.55	47.18	54	-6.82
2483.5	72.16	PK	61	1.7	V	-10.55	61.61	74	-12.39
2483.5	55.11	Ave.	61	1.7	V	-10.55	44.56	54	-9.44
2483.51	75.05	PK	68	1.2	H	-10.55	64.5	74	-9.50
2483.51	58.06	Ave.	68	1.2	H	-10.55	47.51	54	-6.49
2483.77	73.37	PK	199	1.5	V	-10.55	62.82	74	-11.18
2483.77	55.98	Ave.	199	1.5	V	-10.55	45.43	54	-8.57
4924	59.49	PK	157	2.1	H	-5.67	53.82	74	-20.18
4924	45.21	Ave.	157	2.1	H	-5.67	39.54	54	-14.46
4924	59.07	PK	297	1.9	V	-5.67	53.40	74	-20.60
4924	44.95	Ave.	297	1.9	V	-5.67	39.28	54	-14.72

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n20									
Low Channel(2412MHz)									
2389.92	74.14	PK	11	1.6	H	-10.70	63.44	74	-10.56
2389.92	59.02	Ave.	11	1.6	H	-10.70	48.32	54	-5.68
2389.68	68.33	PK	223	1.3	V	-10.70	57.63	74	-16.37
2389.68	54.78	Ave.	223	1.3	V	-10.70	44.08	54	-9.92
2390	74.87	PK	235	1.6	H	-10.70	64.17	74	-9.83
2390	59.05	Ave.	235	1.6	H	-10.70	48.35	54	-5.65
2390	67.92	PK	330	2.5	V	-10.70	57.22	74	-16.78
2390	54.93	Ave.	330	2.5	V	-10.70	44.23	54	-9.77
4824	61.38	PK	158	1.3	H	-6.10	55.28	74	-18.72
4824	47.16	Ave.	158	1.3	H	-6.10	41.06	54	-12.94
4824	60.97	PK	36	1.7	V	-6.10	54.87	74	-19.13
4824	46.71	Ave.	36	1.7	V	-6.10	40.61	54	-13.39
Middle Channel(2437MHz)									
4874	61.06	PK	98	1.3	H	-5.95	55.11	74	-18.89
4874	46.65	Ave.	98	1.3	H	-5.95	40.7	54	-13.30
4874	60.60	PK	50	1.8	V	-5.95	54.65	74	-19.35
4874	46.29	Ave.	50	1.8	V	-5.95	40.34	54	-13.66
High Channel(2462MHz)									
2483.5	73.04	PK	323	1.2	H	-10.55	62.49	74	-11.51
2483.5	58.36	Ave.	323	1.2	H	-10.55	47.81	54	-6.19
2483.5	72.79	PK	50	2.2	V	-10.55	62.24	74	-11.76
2483.5	57.91	Ave.	50	2.2	V	-10.55	47.36	54	-6.64
2483.78	74.67	PK	20	2	H	-10.55	64.12	74	-9.88
2483.78	59.48	Ave.	20	2	H	-10.55	48.93	54	-5.07
2484.27	74.21	PK	58	1.1	V	-10.54	63.67	74	-10.33
2484.27	59.02	Ave.	58	1.1	V	-10.54	48.48	54	-5.52
4924	60.38	PK	0	2.3	H	-5.67	54.71	74	-19.29
4924	45.92	Ave.	0	2.3	H	-5.67	40.25	54	-13.75
4924	60.05	PK	44	1.6	V	-5.67	54.38	74	-19.62
4924	45.61	Ave.	44	1.6	V	-5.67	39.94	54	-14.06

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave.		Height (m)	Polar (H/V)				
802.11n40									
Low Channel(2422MHz)									
2388.92	80.51	PK	280	2.4	H	-10.70	69.81	74	-4.19
2388.92	60.76	Ave.	280	2.4	H	-10.70	50.06	54	-3.94
2389.25	80.02	PK	103	1.3	V	-10.70	69.32	74	-4.68
2389.25	60.28	Ave.	103	1.3	V	-10.70	49.58	54	-4.42
2390	78.60	PK	138	1	H	-10.70	67.90	74	-6.10
2390	59.67	Ave.	138	1	H	-10.70	48.97	54	-5.03
2390	78.09	PK	287	2.4	V	-10.70	67.39	74	-6.61
2390	59.15	Ave.	287	2.4	V	-10.70	48.45	54	-5.55
4844	60.90	PK	192	2.2	H	-6.09	54.81	74	-19.19
4844	46.81	Ave.	192	2.2	H	-6.09	40.72	54	-13.28
4844	60.62	PK	195	1.7	V	-6.09	54.53	74	-19.47
4844	46.47	Ave.	195	1.7	V	-6.09	40.38	54	-13.62
Middle Channel(2437MHz)									
4874	60.64	PK	254	2.5	H	-5.95	54.69	74	-19.31
4874	46.60	Ave.	254	2.5	H	-5.95	40.65	54	-13.35
4874	60.42	PK	237	2.2	V	-5.95	54.47	74	-19.53
4874	46.37	Ave.	237	2.2	V	-5.95	40.42	54	-13.58
High Channel(2452MHz)									
2483.5	74.15	PK	282	2.1	H	-10.55	63.6	74	-10.40
2483.5	60.96	Ave.	282	2.1	H	-10.55	50.41	54	-3.59
2483.5	73.79	PK	202	1.5	V	-10.55	63.24	74	-10.76
2483.5	60.68	Ave.	202	1.5	V	-10.55	50.13	54	-3.87
2487.78	75.74	PK	113	1.9	H	-10.52	65.22	74	-8.78
2487.78	61.51	Ave.	113	1.9	H	-10.52	50.99	54	-3.01
2486.69	75.19	PK	269	1.9	V	-10.52	64.67	74	-9.33
2486.69	61.10	Ave.	269	1.9	V	-10.52	50.58	54	-3.42
4904	60.11	PK	71	1.1	H	-5.77	54.34	74	-19.66
4904	46.38	Ave.	71	1.1	H	-5.77	40.61	54	-13.39
4904	59.82	PK	309	2.4	V	-5.77	54.05	74	-19.95
4904	46.14	Ave.	309	2.4	V	-5.77	40.37	54	-13.63

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude= Factor + Reading


Margin = Corrected Amplitude - Limit

The other spurious emission which is 20dB below to the limit was not recorded.


1-18 GHz:

Pre-scan Plots:

802.11 B Low Channel
Horizontal




Vertical




18 -25GHz:

Pre-scan Plots:

802.11 B Low Channel
Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH


Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	23.3℃
Relative Humidity:	61 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-14.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER


Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

Test Method: ANSI C63.10-2013 11.9.2.3.2

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	23.3℃
Relative Humidity:	61 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-14.

EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix.


FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	23.3℃
Relative Humidity:	61 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-14.

EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:

Please refer to the Appendix.

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.3 Method Ave.GPSD-1

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):


1. Set instrument center frequency to DTS channel center frequency.
2. Set span to at least 1.5 times the OBW.
3. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{BW}$.
5. Detector = power averaging (rms) or sample detector (when rms not available)
6. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
7. Sweep time = auto couple.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level.
10. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

Test Method: ANSI C63.10-2013 Clause 11.10.5 Method Ave.GPSD-2

The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than $\pm 2\%$):

1. Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{BW}$.
6. Detector = power averaging (rms) or sample detector (when rms not available)
7. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
8. Sweep time = auto couple.
9. Do not use sweep triggering; allow sweep to “free run.”
10. Employ trace averaging (rms) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the

minimum measurement point requirement as the RBW is reduced).



Test Data

Environmental Conditions

Temperature:	23.3℃
Relative Humidity:	61 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-14 and 2023-05-26.

EUT operation mode: Transmitting


Test Result: Compliant. Please refer to the Appendix.


APPENDIX

Appendix A: DTS Bandwidth Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.08	2407.44	2416.52	0.5	PASS
		2437	10.04	2431.96	2442.00	0.5	PASS
		2462	10.04	2456.96	2467.00	0.5	PASS
11G	Ant1	2412	15.12	2404.44	2419.56	0.5	PASS
		2437	15.12	2429.44	2444.56	0.5	PASS
		2462	15.12	2454.44	2469.56	0.5	PASS
11N20SISO	Ant1	2412	15.12	2404.44	2419.56	0.5	PASS
		2437	15.12	2429.44	2444.56	0.5	PASS
		2462	15.08	2454.44	2469.52	0.5	PASS
11N40SISO	Ant1	2422	31.36	2405.68	2437.04	0.5	PASS
		2437	31.36	2420.68	2452.04	0.5	PASS
		2452	31.36	2435.68	2467.04	0.5	PASS

Test Graphs






11G_Ant1_2437





Date: 14, MAY, 2023 00:05:57


11G_Ant1_2462



Date: 14, MAY, 2023 00:07:50







**Appendix B: Occupied Channel Bandwidth
Test Result**

Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	13.866	2405.047	2418.913	---	---
		2437	14.026	2429.967	2443.993	---	---
		2462	13.866	2455.047	2468.913	---	---
11G	Ant1	2412	16.943	2403.528	2420.472	---	---
		2437	16.703	2428.608	2445.312	---	---
		2462	16.703	2453.688	2470.392	---	---
11N20SISO	Ant1	2412	17.622	2403.169	2420.791	---	---
		2437	17.822	2428.009	2445.831	---	---
		2462	17.742	2453.089	2470.831	---	---
11N40SISO	Ant1	2422	35.245	2404.338	2439.582	---	---
		2437	35.405	2419.258	2454.662	---	---
		2452	35.325	2434.338	2469.662	---	---


Test Graphs




11B_Ant1_2462



11G_Ant1_2412




11G_Ant1_2437





Date: 14, MAY, 2023 00:06:08


11G_Ant1_2462



Date: 14, MAY, 2023 00:08:01







**Appendix C: Maximum conducted output power
Test Result**


Test Mode	Antenna	Frequency[MHz]	Average Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	15.68	≤30.00	PASS
		2437	16.18	≤30.00	PASS
		2462	14.78	≤30.00	PASS
11G	Ant1	2412	15.99	≤30.00	PASS
		2437	14.77	≤30.00	PASS
		2462	14.25	≤30.00	PASS
11N20SISO	Ant1	2412	15.77	≤30.00	PASS
		2437	14.48	≤30.00	PASS
		2462	13.98	≤30.00	PASS
11N40SISO	Ant1	2422	13.49	≤30.00	PASS
		2437	12.30	≤30.00	PASS
		2452	11.75	≤30.00	PASS

Appendix D: Maximum power spectral density Test Result


Test Mode	Antenna	Frequency[MHz]	Result [dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.31	≤8.00	PASS
		2437	-16.19	≤8.00	PASS
		2462	-17.20	≤8.00	PASS
11G	Ant1	2412	-14.40	≤8.00	PASS
		2437	-15.81	≤8.00	PASS
		2462	-16.19	≤8.00	PASS
11N20SISO	Ant1	2412	-14.55	≤8.00	PASS
		2437	-15.58	≤8.00	PASS
		2462	-16.42	≤8.00	PASS
11N40SISO	Ant1	2422	-24.9	≤8.00	PASS
		2437	-25.55	≤8.00	PASS
		2452	-26.18	≤8.00	PASS

Note: the unit of result for N40 mode is dBm/10kHz
The duty cycle factor has added to the plots.


Test Graphs





11B_Ant1_2437





11B_Ant1_2462
















Appendix E: Band edge measurements


Test Graphs





11G Ant1 Low 2412



11G Ant1 High 2462







Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Frequency[MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Duty Cycle Factor[dB]	1/T Minimum VBW(kHz)
11B	Ant1	2437	12.42	12.83	96.80	0.14	0.08
11G	Ant1	2437	2.06	2.22	92.79	0.32	0.49
11N20SISO	Ant1	2437	1.93	2.12	91.04	0.41	0.52
11N40SISO	Ant1	2437	0.94	1.15	81.74	0.88	1.06

Test Graphs



