

RF Exposure Evaluation Report

APPLICANT : CHEP
EQUIPMENT : Asset Tracker
BRAND NAME : CHEP
MODEL NAME : Gen 4 Ultra Wide, Gen 4 Ultra Wide QP
FCC ID : 2APRD-GEN4WIDE
STANDARD : 47 CFR Part 2.1091
FCC KDB 447498 D01 v06

The product evaluation date was started from Dec. 18, 2025 and completed on Dec. 18, 2025. We, Sporton International Inc. (Shenzhen), would like to declare that the device has been evaluated in accordance with 47 CFR Part 2.1091 and FCC KDB 447498 D01 v06, and pass the limit. Without written approval of Sporton International Inc. (Shenzhen), the test report shall not be reproduced except in full.

Hank Huang



Approved by: Hank Huang

Sporton International Inc. (Shenzhen)

***1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055
People's Republic of China***



Table of Contents

1. ADMINISTRATION DATA	4
1.1. Testing Laboratory	4
2. DESCRIPTION OF EQUIPMENT UNDER TEST (EUT)	5
3. MAXIMUM RF AVERAGE OUTPUT TUNE UP POWER AMONG PRODUCTION UNITS	6
4. RF EXPOSURE LIMIT INTRODUCTION	8
5. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION	9
5.1. Standalone Power Density Calculation	9



Revision History

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FA5O2210	Rev. 01	Initial issue of report	Dec. 23, 2025



1. Administration Data

1.1. Testing Laboratory

Sporton International Inc. (Shenzhen) is accredited to ISO/IEC 17025:2017 by American Association for Laboratory Accreditation with Certificate Number 5145.01.

Testing Laboratory			
Test Firm	Sporton International Inc. (Shenzhen)		
Test Site Location	1/F, 2/F, Bldg 5, Shiling Industrial Zone, Xinwei Village, Xili, Nanshan, Shenzhen, 518055 People's Republic of China TEL: +86-755-86379589 FAX: +86-755-86379595		
Test Site No.	Sporton Site No.	FCC Designation No.	FCC Test Firm Registration No.
	SAR01-SZ	CN1256	421272

Applicant	
Company Name	CHEP
Address	2901 Tasman Drive Suite 101 Santa Clara, CA 95054

Manufacturer	
Company Name	MINEWING VIET NAM ELECTRONICS CO., LTD
Address	Lot CN-09, Hoa Phu Industrial Park, Xuan Cam Commune, Bac Ninh Province, Vietnam



2. Description of Equipment Under Test (EUT)

Product Feature & Specification	
EUT Type	Asset Tracker
Brand Name	CHEP
Model Name	Gen 4 Ultra Wide, Gen 4 Ultra Wide QP
FCC ID	2APRD-GEN4WIDE
Wireless Technology and Frequency Range	GSM850: 824 MHz ~ 849 MHz GSM1900: 1850 MHz ~ 1910 MHz LTE Category M1: LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 26 : 814 MHz ~ 849 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 85: 698 MHz ~ 716 MHz NB-IOT Category NB2: LTE Band 2 : 1850 MHz ~ 1910 MHz LTE Band 4 : 1710 MHz ~ 1755 MHz LTE Band 5 : 824 MHz ~ 849 MHz LTE Band 12 : 699 MHz ~ 716 MHz LTE Band 13 : 777 MHz ~ 787 MHz LTE Band 25 : 1850 MHz ~ 1915 MHz LTE Band 66 : 1710 MHz ~ 1780 MHz LTE Band 71: 663 MHz ~ 698 MHz LTE Band 85: 698 MHz ~ 716 MHz WLAN 2.4GHz Band: 2412 MHz ~ 2462 MHz Bluetooth: 2402 MHz ~ 2480 MHz
Mode	GPRS/EGPRS LTE: QPSK, 16QAM WLAN 2.4GHz 802.11b/g/n HT20/HT40 Bluetooth LE
Antenna Gain	GSM850: 1.6 dBi GSM1900: 3.5 dBi LTE Band 2 : 3.5 dBi LTE Band 4 : 3.5 dBi LTE Band 5 : 1.6 dBi LTE Band 12 : 0.4 dBi LTE Band 13 : 0.4 dBi LTE Band 25 : 3.5 dBi LTE Band 26 : 1.6 dBi LTE Band 66: 3.5 dBi LTE Band 71 : 0.4 dBi LTE Band 85 : 0.4 dBi Bluetooth: 2.8 dBi WLAN2.4GHz: -2.5 dBi
Antenna Type	WWAN : Chip Antenna Bluetooth : PCB Antenna
EUT Stage	Production Unit
Remark: 1. The above EUT's information was declared by manufacturer. Please refer to the specifications or user's manual for more detailed description. 2. There are two samples, the differences could be referred to the Product Equality Declaration which is exhibit separately, and the differences do not affect the MPE analysis results.	

Comments and Explanations:

1. The declared of product specification for EUT presented in the report are provided by the manufacturer, and the manufacturer takes all the responsibilities for the accuracy of product specification.
2. The maximum RF output tune up power, antenna gain also the safe distance used for evaluate RF exposure were declared by manufacturer.

3. Maximum RF average output tune up power among production units

<GSM>

Mode	Burst average power(dBm)	
	GSM 850	GSM 1900
GPRS (GMSK, 1 Tx slot)	33.00	29.50
GPRS (GMSK, 2 Tx slots)	32.00	28.50
GPRS (GMSK, 3 Tx slots)	30.00	26.50
GPRS (GMSK, 4 Tx slots)	29.00	25.50
EDGE (8PSK, 1 Tx slot)	27.00	26.50
EDGE (8PSK, 2 Tx slots)	26.00	25.50
EDGE (8PSK, 3 Tx slots)	24.50	23.00
EDGE (8PSK, 4 Tx slots)	23.00	22.00

<LTE>

Mode		Maximum Average power(dBm)
LTE	Band 2	21.50
	Band 4	21.50
	Band 5	21.50
	Band 12	21.50
	Band 13	21.50
	Band 25	19.50
	Band 26	21.50
	Band 66	21.50
	Band 71	21.50
	Band 85	21.50

**<2.4GHz WLAN>**

Frequency	Mode	Maximum Average Power (dBm)
WLAN 2.4GHz	802.11b	15.50
	802.11g	15.50
	802.11n-HT20	15.50
	802.11n-HT40	14.50

<Bluetooth>

Frequency	Mode	Maximum Average Power (dBm)
Bluetooth	LE	1.00



4. RF Exposure Limit Introduction

According to ANSI/IEEE C95.1-1992, the criteria listed in Table 1 shall be used to evaluate the environmental impact of human exposure to radio frequency (RF) radiation as specified in §1.1310.

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3.0-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500			f/300	6
1500-100,000			5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500			f/1500	30
1500-100,000			1.0	30

The MPE was calculated at 20 cm to show compliance with the power density limit.

The following formula was used to calculate the Power Density:

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = Power Density

P = Output Power at Antenna Terminals

G = Gain of Transmit Antenna (linear gain)

R = Distance from Transmitting Antenna



5. Radio Frequency Radiation Exposure Evaluation

5.1. Standalone Power Density Calculation

Band	Frequency (MHz)	Antenna Gain (dBi)	Maximum Power (dBm)	Maximum EIRP (dBm)	Maximum EIRP (W)	Average EIRP (mW)	Power Density at 20cm (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit
GPRS 850 (1 Tx slot)	824.0	1.60	33.00	34.600	2.884	363.078	0.072	0.549	0.132
GPRS 850 (2 Tx slots)	824.0	1.60	32.00	33.600	2.291	575.440	0.115	0.549	0.209
GPRS 850 (3 Tx slots)	824.0	1.60	30.00	31.600	1.445	542.001	0.108	0.549	0.196
GPRS 850 (4 Tx slots)	824.0	1.60	29.00	30.600	1.148	575.440	0.115	0.549	0.209
EGPRS 850 (1 Tx slot)	824.0	1.60	27.00	28.600	0.724	91.201	0.018	0.549	0.033
EGPRS 850 (2 Tx slots)	824.0	1.60	26.00	27.600	0.575	144.544	0.029	0.549	0.052
EGPRS 850 (3 Tx slots)	824.0	1.60	24.50	26.100	0.407	152.757	0.030	0.549	0.055
EGPRS 850 (4 Tx slots)	824.0	1.60	23.00	24.600	0.288	144.544	0.029	0.549	0.052
GPRS 1900 (1 Tx slot)	1850.0	3.50	29.50	33.000	1.995	251.189	0.050	1.000	0.050
GPRS 1900 (2 Tx slots)	1850.0	3.50	28.50	32.000	1.585	398.107	0.079	1.000	0.079
GPRS 1900 (3 Tx slots)	1850.0	3.50	26.50	30.000	1.000	374.973	0.075	1.000	0.075
GPRS 1900 (4 Tx slots)	1850.0	3.50	25.50	29.000	0.794	398.107	0.079	1.000	0.079
EGPRS 1900 (1 Tx slot)	1850.0	3.50	26.50	30.000	1.000	125.893	0.025	1.000	0.025
EGPRS 1900 (2 Tx slots)	1850.0	3.50	25.50	29.000	0.794	199.526	0.040	1.000	0.040
EGPRS 1900 (3 Tx slots)	1850.0	3.50	23.00	26.500	0.447	167.494	0.033	1.000	0.033
EGPRS 1900 (4 Tx slots)	1850.0	3.50	22.00	25.500	0.355	177.828	0.035	1.000	0.035
LTE Band 2	1850.0	3.50	21.50	25.000	0.316	316.228	0.063	1.000	0.063
LTE Band 4	1710.0	3.50	21.50	25.000	0.316	316.228	0.063	1.000	0.063
LTE Band 5	824.0	1.60	21.50	23.100	0.204	204.174	0.041	0.549	0.074
LTE Band 12	699.0	0.40	21.50	21.900	0.155	154.882	0.031	0.466	0.066
LTE Band 13	777.0	0.40	21.50	21.900	0.155	154.882	0.031	0.518	0.060
LTE Band 25	1850.0	3.50	19.50	23.000	0.200	199.526	0.040	1.000	0.040
LTE Band 26	814.0	1.60	21.50	23.100	0.204	204.174	0.041	0.543	0.075
LTE Band 66	1710.0	3.50	21.50	25.000	0.316	316.228	0.063	1.000	0.063
LTE Band 71	663.0	0.40	21.50	21.900	0.155	154.882	0.031	0.442	0.070
LTE Band 85	698.0	0.40	21.50	21.900	0.155	154.882	0.031	0.465	0.066
Bluetooth	2402.0	2.80	1.00	3.800	0.002	2.399	0.000	1.000	0.000
2.4GHz WLAN	2412.0	-2.50	15.50	13.000	0.020	19.953	0.004	1.000	0.004

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum RF output tune up power and the maximum antenna gain of all antennas among same frequency WWAN bands to perform MPE calculation conservatively.
3. According to the EUT characteristic, WWAN and WLAN 2.4GHz/Bluetooth can't transmit simultaneously.
4. According to the EUT characteristic, WLAN 2.4GHz and Bluetooth can't transmit simultaneously.

Conclusion:

According to 47 CFR §2.1091, the RF exposure analysis concludes that the RF Exposure is FCC compliant.

-----THE END-----