

RF EXPOSURE EVALUATION

EUT Specification

FCC ID	2APRE-JHANC631FPLUS
EUT Name	Headphone
Model	JH-ANC631F Plus
Series Model	/
Model Difference	/
Antenna gain (Max)	-0.59 dBi
Operation Frequency	2402-2480MHz
Classification Per Stipulated Test Standard	§ 15.247(i), § 2.1093
Modulation	BR + EDR: GFSK, $\pi/4$ -DQPSK, 8DPSK BLE: GFSK
Max. output power	BR + EDR: 0.62 dBm(1.153mW) BLE: 2.02 dBm(1.592mW)

Test Requirement:

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances* ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f_{\text{(GHz)}}}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR,²⁴ where

- $f_{\text{(GHz)}}$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 5) in section 4.1 is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by §2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

One antenna is available for the EUT. The minimum separation distance is 5mm.

BR + EDR:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR	Verdict
2402	3DH5	0.62	1±1	2	0.491266	3	PASS

BLE:

Transmit Frequency (MHz)	Mode	Measured Power (dBm)	Tune up Power (dBm)	Max tune up power(dBm)	Calculation Result	1-g SAR	Verdict
2402	BLE	2.02	2±1	3	0.618467	3	PASS

Note: No need for SAR test

Signature:



Shawn Wen

Date: 2025-10-10