

FCC RF EXPOSURE REPORT

FCC ID: 2APRZ-FILTER

Project No. : 2203C186
Equipment : Bluetooth USB dual-mode conference machine
Brand Name : AUDEZE
Test Model : FILTER
Series Model : N/A
Applicant : Audeze LLC.
Address : 3410 S. Susan Street, Santa Ana CA 92704, U.S.A
Manufacturer : Audeze LLC.
Address : 3410 S. Susan Street, Santa Ana CA 92704, U.S.A
Factory : lone Electronic technology co.,ltd.
Address : Yong Jun Er Rd,Jin Qian Ling Ind District,Jitigang,Huang Jiang Town,Dong Guan,Guang Dong Province,China.
Date of Receipt : Apr. 20, 2022
Date of Test : May 12, 2022 ~ Aug. 02, 2022
Issued Date : Aug. 24, 2022
Report Version : R00
Test Sample : Engineering Sample No.: DG2022051217
Standard(s) : FCC Guidelines for Human Exposure IEEE C95.1 & FCC Part 2.1091
FCC Title 47 Part 2.1091

The above equipment has been tested and found compliance with the requirement of the relative standards by BTL Inc.

Nick Chen

Prepared by : Nick Chen

Chay. Cai

Approved by : Chay Cai



TESTING CERT #5123.02

BTL Inc.

No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

Tel: +86-769-8318-3000 Web: www.newbtl.com Service mail: btl_qa@newbtl.com

REPORT ISSUED HISTORY

Report No.	Version	Description	Issued Date	Note
BTL-FCCP-3-2203C186	R00	Original Report	Aug. 24, 2022	Valid

1. TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No. 3 Jinshagang 1st Rd. Shixia, Dalang Town Dongguan City, Guangdong 523792 People's Republic of China.

BTL's Registration Number for FCC: 357015

BTL's Designation Number for FCC: CN1240

2. MPE CALCULATION METHOD

Calculation Method of RF Safety Distance:

$$S = \frac{PG}{4\pi r^2} = \frac{EIRP}{4\pi r^2}$$

where:

S = power density

P = power input to the antenna

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna

Table for Filed Antenna:

Ant.	Brand	P/N	Antenna Type	Connector	Gain(dBi)
1		H2U38D1E1B0100	Chip	N/A	1.5

Note:

The antenna gain is provided by the manufacturer.

3. TEST RESULTS

For BT:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.5	1.4125	8.54	7.1450	0.00201	1	Complies

For LE:

Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Max. Peak Output Power (mW)	Power Density (S) (mW/cm ²)	Limit of Power Density (S) (mW/cm ²)	Test Result
1.5	1.4125	8.71	7.4302	0.00209	1	Complies

Note: The calculated distance is 20 cm.

End of Test Report