FCC Part 15C
Measurement and Test Report

For

E-safe Technology Limited

Room 210, Block B, Baoyuan huafeng Economic Building, Xixiang Avenue,

Bao'an District, Shenzhen, Guangdong China

FCC ID: 2APT2WL-03

FCC Rule(s):	FCC Part 15.247
Product Description:	Smart Light
Tested Model:	WL-03
Report No.:	STR18058005I-2
Sample Receipt Date:	2018-05-23
Tested Date:	2018-05-23 to 2018-06-19
Issued Date:	2018-06-19
Tested By:	Mike Shi/ Engineer
Reviewed By:	Silin Chen / EMC Manager
Approved & Authorized By:	Jandy So / PSQ Manager

Prepared By:

Shenzhen SEM Test Technology Co., Ltd.
1/F, Building A, Hongwei Industrial Park, Liuxian 2nd Road,
Bao'an District, Shenzhen, P.R.C.（518101）
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Website: www.semtest.com.cn

Note: This test report is limited to the above client company and the product model only. It may not be duplicated without prior permitted by Shenzhen SEM.Test Technology Co., Ltd.

TABLE OF CONTENTS

1. GENERAL INFORMATION 4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) 4
1.2 TEST STANDARDS 6
1.3 TEST METHODOLOGY 6
1.4 TEST FACILITY 6
1.5 EUT SETUP AND TEST MODE 7
1.6 MEASUREMENT UNCERTAINTY 8
1.7 TEST EQUIPMENT LIST AND DETAILS 8
2. SUMMARY OF TEST RESULTS 10
3. RF EXPOSURE 11
3.1 STANDARD APPLICABLE 11
3.2 TEST RESULT 11
4. ANTENNA REQUIREMENT 12
4.1 STANDARD APPLICABLE 12
4.2 EVALUATION INFORMATION 12
5. FREQUENCY HOPPING SYSTEM REQUIREMENTS 13
5.1 STANDARD APPLICABLE 13
5.2 FREQUENCY HOPPING SYSTEM 13
5.3 EUT PSEUDORANDOM FREQUENCY HOPPING SEQUENCE 14
6. QUANTITY OF HOPPING CHANNELS AND CHANNEL SEPARATION 15
6.1 STANDARD APPLICABLE 15
6.2 TEST PROCEDURE 15
6.3 ENVIRONMENTAL CONDITIONS 15
6.4 SUMMARY OF TEST RESULTS/PLOTS 16
7. DWELL TIME OF HOPPING CHANNEL 20
7.1 STANDARD APPLICABLE 20
7.2 TEST PROCEDURE 20
7.3 ENVIRONMENTAL CONDITIONS 20
7.4 SUMMARY OF TEST RESULTS/PLOTS 21
8. 20DB BANDWIDTH 31
8.1 STANDARD APPLICABLE 31
8.2 TEST PROCEDURE 31
8.3 ENVIRONMENTAL CONDITIONS 32
8.4 SUMMARY OF TEST RESULTS/PLOTS 32
9. RF OUTPUT POWER 36
9.1 STANDARD APPLICABLE 36
9.2 TEST PROCEDURE 36
9.3 ENVIRONMENTAL CONDITIONS 36
9.4 SUMMARY OF TEST RESULTS/PLOTS 36
10. FIELD STRENGTH OF SPURIOUS EMISSIONS 41
10.1 STANDARD APPLICABLE 41
10.2 TEST PROCEDURE 41
10.3 CORRECTED AMPLITUDE & MARGIN CALCULATION 42
10.4 ENVIRONMENTAL CONDITIONS 42
10.5 SUMMARY OF TEST RESULTS/PLOTS 43
11. OUT OF BAND EMISSIONS 50
11.1 STANDARD APPLICABLE 50
11.2 TEST PROCEDURE 50
11.3 ENVIRONMENTAL CONDITIONS 51
11.4 SUMMARY OF TEST RESULTS/PLOTS 52
12. CONDUCTED EMISSIONS 58

12.1 TEST PROCEDURE 58
12.2 BASIC TEST SETUP BLOCK DIAGRAM 58
12.3 ENVIRONMENTAL CONDITIONS 58
12.4 TEST RECEIVER SETUP 59
12.5 SUMMARY OF TEST RESULTS/PLOTS 59
12.6 CONDUCTED EMISSIONS TEST DATA 59

1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

Client Information

Applicant:	E-safe Technology Limited
Address of applicant:	Room 210,Block B,Baoyuan huafeng Economic Building, Xixiang Avenue, Bao'an District, Shenzhen, Guangdong China
Manufacturer:	E-safe Technology Limited
Address of manufacturer:	Room 210,Block B, Baoyuan huafeng Economic Building, Xixiang Avenue, Bao'an District, Shenzhen, Guangdong China

General Description of EUT	
Product Name:	Smart Light
Brand Name:	E-safe
Model No.:	WL-03
Adding Model(s):	WL-03W
Rated Voltage:	Power Port:DC12V
Battery Capacity:	/
Power Adapter:	Model:NLB100120W1A5S58 Input:AC100-240V~50/60Hz 0.35A MAX Ouput:DC12V,1000mA
Software Version:	ac69_sdk_V2012_p1
Hardware Version:	2018.05.03
Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model WL-03, but the circuit and the electronic construction do not change, declared by the manufacturer.	

Technical Characteristics of EUT	
Bluetooth Version:	V4.1 (BDR/EDR mode)
Frequency Range:	2402-2480MHz
RF Output Power:	-3.71dBm (Conducted)
Data Rate:	1Mbps, 2Mbps
Modulation:	GFSK, Pi/4 QDPSK
Quantity of Channels:	79
Channel Separation:	1MHz
Type of Antenna:	PCB Antenna
Antenna Gain:	0dBi
Lowest Internal Frequency:	32.768 kHz

1.2 Test Standards

The following report is prepared on behalf of the E-safe Technology Limited in accordance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

The objective is to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 of the Federal Communication Commissions rules.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product, which result in lowering the emission, should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard for Testing Unlicensed Wireless Devices, and ANSI C63.4-2014, American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the range of 9 kHz to 40 GHz.

1.4 Test Facility

FCC – Registration No.: 125990
Shenzhen SEM Test Technology Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A
The 3m Semi-anechoic chamber of Shenzhen SEM.Test Technology Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.

1.5 EUT Setup and Test Mode

The EUT was operated in the engineering mode to fix the Tx frequency that was for the purpose of the measurements. All testing shall be performed under maximum output power condition, and to measure its highest possible emissions level, more detailed description as follows:

Test Mode List		
Test Mode	Description	Remark
TM1	Low Channel	2402MHz
TM2	Middle Channel	2441MHz
TM3	High Channel	2480MHz
TM4	Hopping	2402-2480MHz

Modulation Configure			
Modulation	Packet	Packet Type	Packet Size
GFSK	DH1	4	27
	DH3	11	183
	DH5	15	339
Pi/4 DQPSK	2DH1	20	54
	2DH3	26	367
	2DH5	30	679
Normal mode: the Bluetooth has been tested on the modulation of GFSK, (Pi/4)DQPSK, compliance test and record the worst case.			

Accessories Equipment List and Details			
Description	**Manufacturer**	**Model No.**	**Serial Number**
iPhone6 Plus	Apple	MGAJ2ZP/A	FK1PQ4JBG5QW
Accessories Cable List and Details			
Cable Description	**Length (m)**	**Shielded/Unshielded**	**With Core/Without Core**
/	/	/	/
EUT Cable List and Details			
Cable Description	**Length (m)**	**Shielded/Unshielded**	**With Core/Without Core**
DC Cable	1.5	Unshielded	Without Core

1.6 Measurement Uncertainty

Measurement uncertainty		
Parameter	Conditions	Uncertainty
RF Output Power	Conducted	±0.42dB
Occupied Bandwidth	Conducted	±1.5%
Conducted Spurious Emission	Conducted	±2.17dB
Conducted Emissions	Conducted	9-150kHz ±3.74dB
		0.15-30MHz ±3.34dB
Transmitter Spurious Emissions	Radiated	30-200MHz ±4.52dB
		0.2-1GHz ±5.56dB
		1-6GHz ±3.84dB
		6-18GHz ±3.92dB

1.7 Test Equipment List and Details

No.	Description	Manufacturer	Model	Serial No.	Cal Date	Due Date
SEMT-1072	Spectrum Analyzer	Agilent	E4407B	MY41440400	2018-05-22	2019-05-21
SEMT-1031	Spectrum Analyzer	Rohde & Schwarz	FSP30	836079/035	2018-05-22	2019-05-21
SEMT-1007	EMI Test Receiver	Rohde & Schwarz	ESVB	825471/005	2018-05-22	2019-05-21
SEMT-1008	Amplifier	Agilent	8447F	3113A06717	2018-05-22	2019-05-21
SEMT-1043	Amplifier	C&D	PAP-1G18	2002	2018-05-22	2019-05-21
SEMT-1011	Broadband Antenna	Schwarz beck	VULB9163	9163-333	2017-06-08	2020-06-07
SEMT-1042	Horn Antenna	ETS	3117	00086197	2017-06-08	2020-06-07
SEMT-1121	Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170582	2017-06-08	2020-06-07
SEMT-1069	Loop Antenna	Schwarz beck	FMZB 1516	9773	2017-06-08	2020-06-07
SEMT-1001	EMI Test Receiver	Rohde & Schwarz	ESPI	101611	2018-05-22	2019-05-21
SEMT-1003	L.I.S.N	Schwarz beck	NSLK8126	8126-224	2018-05-22	2019-05-21
SEMT-1002	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100911	2018-05-22	2019-05-21
SEMT-1168	Pre-amplifier	Direction Systems Inc.	PAP-0126	14141-12838	2018-05-22	2019-05-21
SEMT-1169	Pre-amplifier	Direction Systems Inc.	PAP-2640	14145-14153	2018-05-22	2019-05-21
SEMT-1163	Spectrum Analyzer	Rohde & Schwarz	FSP40	100612	2018-05-22	2019-05-21
SEMT-1170	DRG Horn Antenna	A.H. SYSTEMS	SAS-574	571	2018-03-19	2021-03-18
SEMT-1166	Power Limiter	Agilent	N9356B	MY45450376	2018-05-22	2019-05-21

SEMT-1048	RF Limiter	ATTEN	AT-BSF-2400~2500	/	2018-05-22	2019-05-21
SEMT-1076	RF Switcher	Top Precision	RCS03-A2	/	2018-05-22	2019-05-21
SEMT-C001	Cable	Zheng DI	LL142-07-07-10M(A)	/	2018-03-19	2019-03-18
SEMT-C002	Cable	Zheng DI	ZT40-2.92J-2.92J-6M	/	2018-03-19	2019-03-18
SEMT-C003	Cable	Zheng DI	ZT40-2.92J-2.92J-2.5M	/	2018-03-19	2019-03-18
SEMT-C004	Cable	Zheng DI	2M0RFC	/	2018-03-19	2019-03-18
SEMT-C005	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18
SEMT-C006	Cable	Zheng DI	1M0RFC	/	2018-03-19	2019-03-18

2. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test Item	Result
§ 2.1093	RF Exposure	Compliant
§ 15.203; § 15.247(b)(4)(i)	Antenna Requirement	Compliant
§15.205	Restricted Band of Operation	Compliant
§ 15.207(a)	Conducted Emission	Compliant
§ 15.209(a)	Radiated Spurious Emissions	Compliant
§ 15.247(a)(1)(iii)	Quantity of Hopping Channel	Compliant
§ 15.247(a)(1)	Channel Separation	Compliant
§ 15.247(a)(1)(iii)	Time of Occupancy (Dwell time)	Compliant
§ 15.247(a)	20dB Bandwidth	Compliant
§ 15.247(b)(1)	RF Power Output	Compliant
§ 15.247(d)	Band Edge (Out of Band Emissions)	Compliant
§ 15.247(a)(1)	Frequency Hopping Sequence	Compliant
§ 15.247(g), (h)	Frequency Hopping System	Compliant

N/A: not applicable

3. RF Exposure

3.1 Standard Applicable

According to § 1.1307 and § 2.1093, the portable transmitter must comply the RF exposure requirements.

3.2 Test Result

This product complied with the requirement of the RF exposure, please see the RF Exposure Report.

4. Antenna Requirement

4.1 Standard Applicable

According to FCC Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

4.2 Evaluation Information

This product has a PCB antenna, fulfill the requirement of this section.

5. Frequency Hopping System Requirements

5.1 Standard Applicable

According to FCC Part 15.247(a)(1), The system shall hop to channel frequencies that are selected at the system hopping rate from a pseudo randomly ordered list of hopping frequencies. Each frequency must be used equally on the average by each transmitter. The system receivers shall have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shall shift frequencies in synchronization with the transmitted signals.

(g) Frequency hopping spread spectrum systems are not required to employ all available hopping channels during each transmission. However, the system, consisting of both the transmitter and the receiver, must be designed to comply with all of the regulations in this section should the transmitter be presented with a continuous data (or information) stream. In addition, a system employing short transmission bursts must comply with the definition of a frequency hopping system and must distribute its transmissions over the minimum number of hopping channels specified in this section.

(h) The incorporation of intelligence within a frequency hopping spread spectrum system that permits the system to recognize other users within the spectrum band so that it individually and independently chooses and adapts its hopsets to avoid hopping on occupied channels is permitted. The coordination of frequency hopping systems in any other manner for the express purpose of avoiding the simultaneous occupancy of individual hopping frequencies by multiple transmitters is not permitted.

5.2 Frequency Hopping System

This transmitter device is frequency hopping device, and complies with FCC part 15.247 rule.

This device uses Bluetooth radio which operates in 2400-2483.5 MHz band. Bluetooth uses a radio technology called frequency-hopping spread spectrum, which chops up the data being sent and transmits chunks of it on up to 79 bands (1 MHz each; centred from 2402 to 2480 MHz) in the range 2,400-2,483.5 MHz. The transmitter switches hop frequencies 1,600 times per second to assure a high degree of data security. All Bluetooth devices participating in a given piconet are synchronized to the frequency-hopping channel for the piconet. The frequency hopping sequence is determined by the master's device address and the phase of the hopping sequence (the frequency to hop at a specific time) is determined by the master's internal clock. Therefore, all slaves in a piconet must know the master's device address and must synchronize their clocks with the master's clock.

Adaptive Frequency Hopping (AFH) was introduced in the Bluetooth specification to provide an effective way for a Bluetooth radio to counteract normal interference. AFH identifies "bad" channels, where either other wireless devices are interfering with the Bluetooth signal or the Bluetooth signal is interfering with another device. The AFH-enabled Bluetooth device will then communicate with other devices within its piconet to share details of any identified bad channels. The devices will then switch to alternative available "good" channels, away from the areas of interference, thus having no impact on the bandwidth used.

This device was tested with an bluetooth system receiver to check that the device maintained hopping synchronization, and the device complied with these requirements for DA 00-705 and FCC Part 15.247 rule.

5.3 EUT Pseudorandom Frequency Hopping Sequence

Pseudorandom Frequency Hopping Sequence Table as below:
Channel: 08, 24, 40, 56, 40, 56, 72, 09, 01, 09, 33, 41, 33, 41, 65, 73, 53, 69, 06, 22, 04, 20, 36, 52, 38, 46, 70, 78, 68, 76, 21, 29, 10, 26, 42, 58, 44, 60, 76, 13, 03, 11, 35, 43, 37, 45, 69, 77, 55, 71, 08, 24, 08, 24, 40, 56, 40, 48, 72, 01, 72, 01, 25, 33, 12, 28, 44, 60, 42, 58, 74, 11, 05, 13, 37, 45 etc.

The system receiver have input bandwidths that match the hopping channel bandwidths of their corresponding transmitters and shift frequencies in synchronization with the transmitted signals.

6. Quantity of Hopping Channels and Channel Separation

6.1 Standard Applicable

According to FCC 15.247(a)(1), frequency hopping systems operating in the 2400-2483.5 MHz band may have hopping channel carrier frequencies that are separated by 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, and frequency hopping systems in the 2400-2483.5 MHz band shall use at least 15 channels.

6.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.3, the number of hopping frequencies test method as follows.

a) Span: The frequency band of operation. Depending on the number of channels the device supports, it may be necessary to divide the frequency range of operation across multiple spans, to allow the individual channels to be clearly seen.
b) RBW: To identify clearly the individual channels, set the RBW to less than 30% of the channel spacing or the 20 dB bandwidth, whichever is smaller.
c) VBW ⩾ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.

According to ANSI C63.10-2013 section 7.8.2, the EUT shall have its hopping function enabled, the Carrier frequency separation test method as follows:

a) Span: Wide enough to capture the peaks of two adjacent channels.
b) RBW: Start with the RBW set to approximately 30% of the channel spacing; adjust as necessary to best identify the center of each individual channel.
c) Video (or average) bandwidth (VBW) ⩾ RBW.
d) Sweep: Auto.
e) Detector function: Peak.
f) Trace: Max hold.
g) Allow the trace to stabilize.
Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

6.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

6.4 Summary of Test Results/Plots

No. of Channel = 79



For GFSK mode

Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



Channel Spacing (High CH=1MHz)



For Pi/4 DQPSK mode

Channel Spacing (Low CH=1MHz)



Channel Spacing (Middle CH=1MHz)



Channel Spacing (High CH=1MHz)



7. Dwell Time of Hopping Channel

7.1 Standard Applicable

According to 15.247(a)(1)(iii), Frequency hopping systems in the 2400–2483.5 MHz band shall use at least 15 channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed.

7.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.4, the dwell time of a hopping channel test method as follows.

a) Span: Zero span, centered on a hopping channel.
b) RBW shall be ≤ channel spacing and where possible RBW should be set >> 1 / T, where T is the expected dwell time per channel.
c) Sweep: As necessary to capture the entire dwell time per hopping channel; where possible use a video trigger and trigger delay so that the transmitted signal starts a little to the right of the start
of the plot. The trigger level might need slight adjustment to prevent triggering when the system hops on an adjacent channel; a second plot might be needed with a longer sweep time to show two successive hops on a channel.
d) Detector function: Peak.
e) Trace: Max hold.

Use the marker-delta function to determine the transmit time per hop. If this value varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation in transmit time.
Repeat the measurement using a longer sweep time to determine the number of hops over the period specified in the requirements. The sweep time shall be equal to, or less than, the period specified in the requirements. Determine the number of hops over the sweep time and calculate the total number of hops in the period specified in the requirements, using the following equation:
(Number of hops in the period specified in the requirements) =
(number of hops on spectrum analyzer) × (period specified in the requirements / analyzer sweep time)
The average time of occupancy is calculated from the transmit time per hop multiplied by the number of hops in the period specified in the requirements. If the number of hops in a specific time varies with different modes of operation (data rate, modulation format, number of hopping channels, etc.), then repeat this test for each variation.
The measured transmit time and time between hops shall be consistent with the values described in the operational description for the EUT.

7.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

7.4 Summary of Test Results/Plots

The dwell time within a period in data mode is independent from the packet type (packet length).
Test data is corrected with the worse case, which the packet length is DH1, DH3, and DH5.

The test period: T = 0.4 Second * 79 Channel = 31.6 s
Dwell time = time slot length * (Hopping rate / Number of hopping channels) * Period

Modulation	Test Channel	Packet	Time Slot Length	Dwell Time	Limit
			ms	ms	ms
GFSK	2402MHz	DH1	0.44	140.80	400
		DH3	1.70	272.00	400
		DH5	2.95	314.67	400
	2441MHz	DH1	0.44	140.80	400
		DH3	1.71	273.60	400
		DH5	2.95	314.67	400
	2480MHz	DH1	0.44	140.80	400
		DH3	1.71	273.60	400
		DH5	2.94	313.60	400
Pi/4 DQPSK	2402MHz	2DH1	0.46	147.20	400
		2DH3	1.71	273.60	400
		2DH5	2.97	316.80	400
	2441MHz	2DH1	0.45	144.00	400
		2DH3	1.71	273.60	400
		2DH5	2.97	316.80	400
	2480MHz	2DH1	0.44	140.80	400
		2DH3	1.69	270.40	400
		2DH5	2.97	316.80	400

Please refer to the test plots as below:

DH1 time slot (Low, Middle, High Channels)







DH3 time slot (Low, Middle, High Channels)




Agilent
R T
Mkr1 Δ 1.71 ms
-2.049 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Center
2.441000000 GHz
Center 2.441 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Freq/Channel
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
1.00000000 MHz
Auto
Man
Freq Offset
0.00000000 Hz
Signal Track
On
Off
Scale Type
Log
Lin


Agilent
R T
Mkr1 Δ 1.71 ms
-1.913 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Marker Δ
1.710000000 ms
-1.913 dB
Center 2.48 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref
Delta
Span Pair
Span
Center
Off
More
1 of 2

DH5 time slot (Low, Middle, High Channels)







2DH1 time slot (Low, Middle, High Channels)




Agilent
R T
Mkr1 Δ 450 µs
-0.523 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Center 2.441 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2


Agilent
R T
Mkr1 Δ 440 µs
-1.549 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Marker Δ
440.0000000 µs
-1.549 dB
Center 2.48 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2

2DH3 time slot (Low, Middle, High Channels)







2DH5 time slot (Low, Middle, High Channels)




Agilent
R T
Mkr1 Δ 2.97 ms
-0.048 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Center
2.441000000 GHz
Center 2.441 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Unable to save file
Freq/Channel
Center Freq
2.44100000 GHz
Start Freq
2.44100000 GHz
Stop Freq
2.44100000 GHz
CF Step
1.00000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin


Agilent
R T
Mkr1 Δ 2.97 ms
0.619 dB
Ref 10 dBm
#Atten 20 dB
Peak
Log
10
dB/
Offst
1
dB
W1 S2
S3 VS
AA
Marker Δ
2.970000000 ms
0.619 dB
Center 2.48 GHz
Span 0 Hz
Res BW 1 MHz
#VBW 3 MHz
Sweep 4 ms (401 pts)
Unable to save file
Marker
Select Marker
1 2 3 4
Normal
Delta
Delta Pair
(Tracking Ref)
Ref Delta
Span Pair
Span Center
Off
More
1 of 2

8. 20dB Bandwidth

8.1 Standard Applicable

According to 15.247(a) and 15.215(c). 20dB bandwidth is recommended that the fundamental emission be kept within at least the central 80% of the permitted band in order to minimize the possibility of out-of-band operation.

8.2 Test Procedure

According to ANSI C63.10-2013 section 6.9.2, the 20dB bandwidth test method as follows.

a) The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the EMI receiver or spectrum analyzer shall be between two times and five times the OBW.
b) The nominal IF filter bandwidth (3 dB RBW) shall be in the range of 1% to 5% of the OBW and video bandwidth (VBW) shall be approximately three times RBW, unless otherwise specified by the applicable requirement.
c) Set the reference level of the instrument as required, keeping the signal from exceeding the maximum input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level.
d) Steps a) through c) might require iteration to adjust within the specified tolerances.
e) The dynamic range of the instrument at the selected RBW shall be more than 10 dB below the target "−xx dB down" requirement; that is, if the requirement calls for measuring the −20 dB OBW, the instrument noise floor at the selected RBW shall be at least 30 dB below the reference value.
f) Set detection mode to peak and trace mode to max hold.
g) Determine the reference value: Set the EUT to transmit an unmodulated carrier or modulated signal, as applicable. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace (this is the reference value).
h) Determine the "−xx dB down amplitude" using [(reference value) − xx]. Alternatively, this calculation may be made by using the marker-delta function of the instrument.
i) If the reference value is determined by an unmodulated carrier, then turn the EUT modulation ON, and either clear the existing trace or start a new trace on the spectrum analyzer and allow the new trace to stabilize. Otherwise, the trace from step g) shall be used for step j).
j) Place two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the "−xx dB down amplitude" determined in step h). If a marker is below this "−xx dB down amplitude" value, then it shall be as close as possible to this value. The occupied bandwidth is the frequency difference between the two markers. Alternatively, set a marker at the lowest frequency of the envelope of the spectral display, such that the marker is at or slightly below the "−xx dB down amplitude" determined in step h). Reset the marker-delta function and move the marker to the other side of the emission until the delta marker amplitude is at the same level as the reference marker amplitude. The marker-delta frequency reading at this point is the specified emission bandwidth.
k) The occupied bandwidth shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

8.3 Environmental Conditions

Temperature:	24°C
Relative Humidity:	56%
ATM Pressure:	1018 mbar

8.4 Summary of Test Results/Plots

Test Mode	Test Channel MHz	20 dB Bandwidth kHz	99% Bandwidth kHz	Result
GFSK	2402	794.809	824.5376	Pass
	2441	851.682	845.4562	Pass
	2480	786.610	822.3408	Pass
Pi/4 DQPSK	2402	1255.000	1163.8000	Pass
	2441	1242.000	1184.0000	Pass
	2480	1277.000	1180.7000	Pass

For GFSK

Low Channel:



Middle Channel:



High Channel:



For Pi/4 DQPSK

Low Channel:



Middle Channel:



High Channel:



9. RF Output Power

9.1 Standard Applicable

According to 15.247(b)(1). For frequency hopping systems operating in the 2400–2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725–5850 MHz band: 1 watt. For all other frequency hopping systems in the 2400–2483.5 MHz band: 0.125 watts.

9.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.5, the output power test method as follows.
Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
This is an RF-conducted test to evaluate maximum peak output power. Use a direct connection between the antenna port of the unlicensed wireless device and the spectrum analyzer, through suitable attenuation. The hopping shall be disabled for this test:

a) Use the following spectrum analyzer settings:
   1) Span: Approximately five times the 20 dB bandwidth, centered on a hopping channel.
   2) RBW > 20 dB bandwidth of the emission being measured.
   3) VBW ⩾ RBW.
   4) Sweep: Auto.
   5) Detector function: Peak.
   6) Trace: Max hold.

b) Allow trace to stabilize.
c) Use the marker-to-peak function to set the marker to the peak of the emission.
d) The indicated level is the peak output power, after any corrections for external attenuators and cables.
e) A plot of the test results and setup description shall be included in the test report.

9.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

9.4 Summary of Test Results/Plots

For GFSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-6.52	0.22	1000
Middle Channel	2441	-5.61	0.27	1000
High Channel	2480	-4.94	0.32	1000

For Pi/4 QDPSK

Channel	Frequency MHz	Measured Value dBm	Output Power mW	Limit mW
Low Channel	2402	-5.34	0.29	1000
Middle Channel	2441	-4.40	0.36	1000
High Channel	2480	-3.71	0.43	1000

Note: the antenna gain of 0dBi less than 6dBi maximum permission antenna gain value based on 1 watt peak output power limit.

For GFSK

Low Channel



Middle Channel



High Channel



For Pi/4 QDPSK

Low Channel



Middle Channel



High Channel



10. Field Strength of Spurious Emissions

10.1 Standard Applicable

According to §15.247(d), in any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

The emission limit in this paragraph is based on measurement instrumentation employing an average detector. The provisions in §15.35 for limiting peak emissions apply. Spurious Radiated Emissions measurements starting below or at the lowest crystal frequency.

10.2 Test Procedure

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.205 15.247(a) and FCC Part 15.209 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.
The spacing between the peripherals was 10 cm.





Frequency :9kHz-30MHz	Frequency :30MHz-1GHz	Frequency :Above 1GHz
RBW=10KHz,	RBW=120KHz,	RBW=1MHz,
VBW =30KHz	VBW=300KHz	VBW=3MHz(Peak), 10Hz(AV)
Sweep time= Auto	Sweep time= Auto	Sweep time= Auto
Trace = max hold	Trace = max hold	Trace = max hold
Detector function = peak	Detector function = peak, QP	Detector function = peak, AV

10.3 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and the Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Ant. Factor + Cable Loss – Ampl. Gain

The "**Margin**" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -6dBμV means the emission is 6dBμV below the maximum limit. The equation for margin calculation is as follows:

Margin = Corr. Ampl. – FCC Part 15 Limit

10.4 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56%
ATM Pressure:	1012 mbar

10.5 Summary of Test Results/Plots

According to the data below, the FCC Part 15.205, 15.209 and 15.247 standards, and had the worst cases:

Note: this EUT was tested in 3 orthogonal positions and the worst case position data was reported. All test modes (different data rate and different modulation) are performed, but only the worst case is recorded in this report.

Plot of Radiated Emissions Test Data (30MHz to 1GHz)

EUT: *Smart Light*
Tested Model: *WL-03*
Operating Condition: *Transmitting Low Channel (2402MHz)*
Comment: *Power Port:DC12V*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	155.9101	45.39	-18.96	26.43	43.50	-17.07	215	100	peak
2	216.7828	47.24	-14.54	32.70	46.00	-13.30	95	100	peak
3	297.2241	38.21	-9.69	28.52	46.00	-17.48	291	100	peak
4	383.9318	43.30	-8.64	34.66	46.00	-11.34	99	100	peak
5	480.5276	39.05	-6.84	32.21	46.00	-13.79	121	100	peak
6	672.8445	37.75	-0.77	36.98	46.00	-9.02	112	100	peak

Test Specification: *Vertical*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	45.8553	47.04	-16.50	30.54	40.00	-9.46	286	100	peak
2	73.6170	56.88	-19.13	37.75	40.00	-2.25	99	100	peak
3	119.8556	52.73	-16.67	36.06	43.50	-7.44	158	100	peak
4	131.2965	54.27	-17.61	36.66	43.50	-6.84	120	100	peak
5	218.3085	54.23	-14.20	40.03	46.00	-5.97	90	100	peak
6	672.8445	42.91	-0.77	42.14	46.00	-3.86	221	100	peak

Operating Condition: *Transmitting Middle Channel (2441MHz)*
Comment: *Power Port:DC12V*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	64.2075	33.26	-17.41	15.85	40.00	-24.15	147	100	peak
2	155.9101	47.73	-18.96	28.77	43.50	-14.73	274	100	peak
3	215.2678	46.90	-14.88	32.02	43.50	-11.48	56	100	peak
4	296.1836	38.18	-9.72	28.46	46.00	-17.54	186	100	peak
5	480.5276	38.58	-6.84	31.74	46.00	-14.26	64	100	peak
6	672.8445	35.64	-0.77	34.87	46.00	-11.13	92	100	peak

Test Specification: *Vertical*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	36.6375	47.74	-17.05	30.69	40.00	-9.31	316	100	peak
2	73.1025	57.17	-19.07	38.10	40.00	-1.90	184	100	peak
3	126.7723	54.18	-17.23	36.95	43.50	-6.55	99	100	peak
4	216.7828	55.00	-14.54	40.46	46.00	-5.54	138	100	peak
5	576.6443	38.74	-4.14	34.60	46.00	-11.40	190	100	peak
6	672.8445	41.63	-0.77	40.86	46.00	-5.14	309	100	peak

Operating Condition: *Transmitting High Channel (2480MHz)*
Comment: *Power Port:DC12V*

Test Specification: *Horizontal*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	55.8047	33.90	-16.51	17.39	40.00	-22.61	82	100	peak
2	154.8205	49.92	-18.92	31.00	43.50	-12.50	149	100	peak
3	216.0240	45.85	-14.70	31.15	46.00	-14.85	101	100	peak
4	293.0842	37.57	-9.83	27.74	46.00	-18.26	129	100	peak
5	524.5541	30.22	-5.20	25.02	46.00	-20.98	326	100	peak
6	734.4913	26.87	-0.18	26.69	46.00	-19.31	324	100	peak

Test Specification: *Vertical*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Degree	Height	Remark
	(MHz)	(dBuV/m)	dB/m	(dBuV/m)	(dBuV/m)	(dB)	( )	(cm)	
1	37.0249	47.52	-17.00	30.52	40.00	-9.48	309	100	peak
2	72.8466	56.84	-19.04	37.80	40.00	-2.20	154	100	peak
3	129.4678	53.79	-17.45	36.34	43.50	-7.16	73	100	peak
4	216.7828	54.52	-14.54	39.98	46.00	-6.02	211	100	peak
5	576.6443	38.24	-4.14	34.10	46.00	-11.90	178	100	peak
6	672.8445	43.21	-0.77	42.44	46.00	-3.56	132	100	peak

Spurious Emissions Above 1GHz

Frequency	Reading	Correct	Result	Limit	Margin	Polar	Detector
(MHz)	(dBuV/m)	dB	(dBuV/m)	(dBuV/m)	(dB)	H/V	
Low Channel-2402MHz							
4804	62.11	-3.59	58.52	74	-15.48	H	PK
4804	43.81	-3.59	40.22	54	-13.78	H	AV
7206	56.81	-0.52	56.29	74	-17.71	H	PK
7206	44.10	-0.52	43.58	54	-10.42	H	AV
4804	67.45	-3.59	63.86	74	-10.14	V	PK
4804	50.07	-3.59	46.48	54	-7.52	V	AV
7206	62.16	-0.52	61.64	74	-12.36	V	PK
7206	44.54	-0.52	44.02	54	-9.98	V	AV
Middle Channel-2441MHz							
4882	62.01	-3.49	58.52	74	-15.48	H	PK
4882	40.46	-3.49	36.97	54	-17.03	H	AV
7323	57.79	-0.47	57.32	74	-16.68	H	PK
7323	43.19	-0.47	42.72	54	-11.28	H	AV
4882	64.01	-3.49	60.52	74	-13.48	V	PK
4882	49.36	-3.49	45.87	54	-8.13	V	AV
7323	67.26	-0.47	66.79	74	-7.21	V	PK
7323	46.15	-0.47	45.68	54	-8.32	V	AV
High Channel-2480MHz							
4960	55.26	-3.41	51.85	74	-22.15	H	PK
4960	43.34	-3.41	39.93	54	-14.07	H	AV
7440	52.67	-0.42	52.25	74	-21.75	H	PK
7440	39.53	-0.42	39.11	54	-14.89	H	AV
4960	64.19	-3.41	60.78	74	-13.22	V	PK
4960	48.37	-3.41	44.96	54	-9.04	V	AV
7440	61.06	-0.42	60.64	74	-13.36	V	PK
7440	44.62	-0.42	44.20	54	-9.80	V	AV

Note: Testing is carried out with frequency rang 9kHz to the tenth harmonics, other than listed in the table above are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.

11. Out of Band Emissions

11.1 Standard Applicable

According to §15.247 (d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a).

11.2 Test Procedure

According to ANSI C63.10-2013 section 7.8.6, the Band-edge measurements for RF conducted emissions test method as follows.

a) Connect the EMI receiver or spectrum analyzer to the EUT using an appropriate RF cable connected to the EUT output. Configure the spectrum analyzer settings as described in step e) (be sure to enter all losses between the unlicensed wireless device output and the spectrum analyzer).
b) Set the EUT to the lowest frequency channel (for the hopping on test, the hopping sequence shall include the lowest frequency channel).
c) Set the EUT to operate at maximum output power and 100% duty cycle, or equivalent “normal mode of operation” as specified in 6.10.3.
d) If using the radiated method, then use the applicable procedure(s) of 6.4, 6.5, or 6.6, and orient the EUT and measurement antenna positions to produce the highest emission level.
e) Perform the test as follows:

1) Span: Wide enough to capture the peak level of the emission operating on the channel closest to the band edge, as well as any modulation products that fall outside of the authorized band of operation.
2) Reference level: As required to keep the signal from exceeding the maximum instrument input mixer level for linear operation. In general, the peak of the spectral envelope shall be more than [10 log (OBW/RBW)] below the reference level. Specific guidance is given in 4.1.5.2.
3) Attenuation: Auto (at least 10 dB preferred).
4) Sweep time: Coupled.
5) Resolution bandwidth: 100 kHz.
6) Video bandwidth: 300 kHz.
7) Detector: Peak.
8) Trace: Max hold.

f) Allow the trace to stabilize. For the test with the hopping function turned ON, this can take several minutes to achieve a reasonable probability of intercepting any emissions due to oscillator overshoot.
g) Set the marker on the emission at the band edge, or on the highest modulation product outside of the band, if this level is greater than that at the band edge. Enable the marker-delta function, and then use the marker-to-peak

function to move the marker to the peak of the in-band emission.
h) Repeat step c) through step e) for every applicable modulation.
i) Set the EUT to the highest frequency channel (for the hopping on test, the hopping sequence shall include the highest frequency channel) and repeat step c) through step d).
j) The band-edge measurement shall be reported by providing plot(s) of the measuring instrument display; the plot axes and the scale units per division shall be clearly labeled. Tabular data may be reported in addition to the plot(s).

Restricted-band band-edge test method please refers to ANSI C63.10-2013 section 6.10.5. The emission must comply with the 15.209 limit for fall in the restricted bands listed in section 15.205. Note that the method of measurement KDB publication number: 913591 may be used for the radiated band-edge measurements.

According to ANSI C63.10-2013 section 7.8.8, Conducted spurious emissions shall be measured for the transmit frequency, per 5.5 and 5.6, and at the maximum transmit powers.
Connect the primary antenna port through an attenuator to the spectrum analyzer input; in the results, account for all losses between the unlicensed wireless device output and the spectrum analyzer. The instrument shall span 30 MHz to 10 times the operating frequency in GHz, with a resolution bandwidth of 100 kHz, video bandwidth of 300 kHz, and a coupled sweep time with a peak detector. The band 30 MHz to the highest frequency may be split into smaller spans, as long as the entire spectrum is covered.

11.3 Environmental Conditions

Temperature:	24°C
Relative Humidity:	56%
ATM Pressure:	1011 mbar

11.4 Summary of Test Results/Plots

Bandedge (Radiated)
Lowest Bandedge
Horizontal (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2310.000	40.38	-6.38	34.00	54.00	-20.00	Average Detector
	2310.000	51.85	-6.38	45.47	74.00	-28.53	Peak Detector
2	2390.000	39.99	-7.26	32.73	54.00	-21.27	Average Detector
	2390.000	54.34	-7.26	47.08	74.00	-26.92	Peak Detector
3	2402.047	79.92	-7.39	72.53	/	/	Average Detector
	2402.047	92.98	-7.39	85.59	/	/	Peak Detector

Highest Bandedge

Horizontal (Worst case)



No.	Frequency	Reading	Correct	Result	Limit	Margin	Remark
	(MHz)	(dBuV/m)	Factor(dB)	(dBuV/m)	(dBuV/m)	(dB)	
1	2480.080	81.82	-7.28	74.54	/	/	Average Detector
	2480.254	95.23	-7.28	87.95	/	/	Peak Detector
2	2483.500	49.93	-7.28	42.65	54.00	-11.35	Average Detector
	2483.500	57.08	-7.28	49.80	74.00	-24.20	Peak Detector
3	2500.000	39.58	-7.25	32.33	54.00	-21.67	Average Detector
	2500.000	51.53	-7.25	44.28	74.00	-29.72	Peak Detector

Worst mode DH1
Bandedge (Conducted)
Lowest





Middle Channel





Highest


Agilent
R T
Mkr1 2.48002 GHz
Ref 10 dBm
#Atten 20 dB
-5.057 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-25.1
dBm
Center
2.483500000 GHz
Center 2.483 GHz
Span 12 MHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 4 ms (401 pts)
Marker Trace Type X Axis Amplitude
1 (1) Freq 2.48002 GHz -5.057 dBm
2 (1) Freq 2.48350 GHz -53.66 dBm
Freq/Channel
Center Freq
2.48350000 GHz
Start Freq
2.47750000 GHz
Stop Freq
2.48950000 GHz
CF Step
1.20000000 MHz
Auto Man
Freq Offset
0.00000000 Hz
Signal Track
On Off
Scale Type
Log Lin


Agilent
R T
Mkr1 4.964 GHz
Ref 10 dBm
#Atten 20 dB
-53.82 dBm
Peak
Log
10
dB/
Offst
1
dB
Dl
-25.1
dBm
M1 S2
S3 FC
AA
Marker
4.964300000 GHz
-53.82 dBm
Start 30 MHz
Stop 26 GHz
#Res BW 100 kHz
#VBW 300 kHz
Sweep 2.691 s (1001 pts)
Peak Search
Meas Tools
Next Peak
Next Pk Right
Next Pk Left
Min Search
Pk-Pk Search
More
1 of 2

Bandedge with Hopping on:
Lowest Bandedge



Highest Bandedge



12. Conducted Emissions

12.1 Test Procedure

The setup of EUT is according with per ANSI C63.4-2014 measurement procedure. The specification used was with the FCC Part 15.207 Limit.
The external I/O cables were draped along the test table and formed a bundle 30 to 40 cm long in the middle.
The spacing between the peripherals was 10 cm.

12.2 Basic Test Setup Block Diagram



12.3 Environmental Conditions

Temperature:	24 °C
Relative Humidity:	56%
ATM Pressure:	1012 mbar

12.4 Test Receiver Setup

During the conducted emission test, the test receiver was set with the following configurations:

Start Frequency ..... 150 kHz
Stop Frequency ..... 30 MHz
Sweep Speed ..... Auto
IF Bandwidth..... 10 kHz
Quasi-Peak Adapter Bandwidth ..... 9 kHz
Quasi-Peak Adapter Mode ..... Normal

12.5 Summary of Test Results/Plots

According to the data in section 12.6, the EUT complied with the FCC Part 15.207 Conducted margin for this device, with the *worst* margin reading of:

-9.81 dB at 0.1580 MHz in the **Neutral** mode**, QP** detector, **0.15-30MHz**

12.6 Conducted Emissions Test Data

Plot of Conducted Emissions Test Data

EUT: *Smart Light*
Tested Model: *WL-03*
Operating Condition: *BT Transmitting*
Comment: *AC120V 60Hz*

Test Specification: *Neutral*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1*	0.1580	45.92	9.84	55.76	65.57	-9.81	QP
2	0.1900	43.07	9.81	52.88	64.04	-11.16	QP
3	0.2260	39.83	9.80	49.63	62.60	-12.97	QP
4	0.3740	25.11	9.80	34.91	48.41	-13.50	AVG
5	1.1260	21.18	9.76	30.94	46.00	-15.06	AVG
6	1.8740	23.69	9.74	33.43	46.00	-12.57	AVG

Test Specification: *Line*



No.	Frequency	Reading	Correct	Result	Limit	Margin	Detector
	(MHz)	(dBuV)	(dB/m)	(dBuV)	(dBuV)	(dB)	
1*	0.1660	45.20	9.83	55.03	65.16	-10.13	QP
2	0.1860	43.11	9.81	52.92	64.21	-11.29	QP
3	0.2060	41.80	9.80	51.60	63.37	-11.77	QP
4	0.5580	19.89	9.80	29.69	46.00	-16.31	AVG
5	1.1260	19.86	9.76	29.62	46.00	-16.38	AVG
6	2.6260	19.88	9.72	29.60	46.00	-16.40	AVG

******* END OF REPORT *******