

FCC PART 15E TEST REPORT FOR CERTIFICATION
On Behalf of

Hunan Greatwall Computer System Co., Ltd

8"Android Tablet

Model Number: 100011885

FCC ID: 2APUQW829


Prepared for:	Hunan Greatwall Computer System Co., Ltd
	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist.,
	Zhuzhou, Hu'nan
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
	Tel: 86-769-83081888-808

Report Number:	ESTE-R2004081-1
Date of Test:	Aug. 13~Sep. 01, 2020
Date of Report:	Sep. 02, 2020

TABLE OF CONTENTS

Description	Page
TEST REPORT VERIFICATION	3
1. GENERAL INFORMATION.....	4
1.1. Description of Device (EUT)	4
1.1. Difference between Model Numbers.....	5
1.2. The antenna information for EUT	5
2. SUMMARY OF TEST	6
2.1. Summary of test result.....	6
2.2. Test Facilities.....	7
2.3. Measurement uncertainty for EST Technology Co., Ltd.	8
2.4. Assistant equipment used for test	8
2.5. Block Diagram.....	8
2.6. Test Mode.....	9
2.7. Channel List.....	10
2.8. Power Setting of Test Software	11
2.9. Test Equipment List	12
3. UNWANTED EMISSIONS AND BAND EDGE	13
3.1. Limit	13
3.2. Test Setup	14
3.3. Spectrum Analyzer Setting.....	15
3.4. Test Procedure	16
3.5. Test Result	17
4. AC POWER LINE CONDUCTED EMISSIONS	23
4.1. Limit	23
4.2. Test Setup	23
4.3. Spectrum Analyzer Setting.....	23
4.4. Test Procedure	23
4.5. Test Result	24
5. TEST SETUP PHOTO.....	36
6. EUT PHOTO	38

EST Technology Co., Ltd.

Applicant:	Hunan Greatwall Computer System Co., Ltd		
Address:	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist., Zhuzhou, Hu'nan		
Manufacturer:	Hunan Greatwall Computer System Co.,Ltd		
Address:	Hu'nan Greatwall Industrial Park,Xiangyun Middle Rd.,Tianyuan Dist.,Zhuzhou, Hu'nan		
E.U.T:	8"Android Tablet		
Model Number:	100011885		
Power Supply:	DC 5V From Adapter Input AC 100-240V~50/60Hz DC 3.8V From Battery		
Trade Name:	onn.	Serial No.:	-----
Date of Receipt:	Aug. 13, 2020	Date of Test:	Aug. 13~Sep. 01, 2020
Test Specification:	FCC Part 15 Subpart E 15.407 ANSI C63.10:2013 FCC KDB 789033 D02 General UNII Test Procedures New Rules v02r01 FCC KDB 662911 D01 Multiple Transmitter Output v02r01		
Test Result:	The device described above is tested by EST Technology Co., Ltd. The measurement results were contained in this test report and EST Technology Co., Ltd. was assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT to be technically compliance with the FCC Rules and Regulations Part 15 Subpart E requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of EST Technology Co., Ltd.		
Prepared by:	Reviewed by:	Date: Sep. 02, 2020 Approved by:	
 Ring Yang/ Assistant	 Seven Wang/ Engineer	 Iceman Hu / Manager	
Other Aspects:	Because only the replace the power management chip PMU and add supply power, so just re-tested spurious emissions(30-1000MHz) 、conducted Emissions, other test item needn't re-tested, test data refer to test report " ESTE-R2004081"		
Abbreviations: OK/P=passed fail/F=failed n.a/N=not applicable E.U.T=equipment under tested			
This test report is based on a single evaluation of one sample of above mentioned products ,It is not permitted to be duplicated in extracts without written approval of EST Technology Co., Ltd.			

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

FCC ID	:	2APUQW829
Product Name	:	8"Android Tablet
Model Number	:	100011885
Software Version	:	F732M.Q0.V3.18.CC-V03.8168.64-7420
Hardware Version	:	F732U2.0
Operation frequency	:	U-NII-1: 5150 MHz~5250 MHz U-NII-2A: 5250 MHz~5350 MHz U-NII-2C: 5470 MHz~5725 MHz U-NII-3: 5725 MHz~5850 MHz
Number of channel	:	U-NII-1: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2A: IEEE 802.11a / n HT20 / ac VHT20: 4 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel. U-NII-2C: IEEE 802.11a / n HT20 / ac VHT20: 11 Channels; IEEE 802.11n HT40 / ac VHT40: 5 Channels; IEEE 802.11ac VHT80: 2 Channel. U-NII-3: IEEE 802.11a / n HT20 / ac VHT20: 5 Channels; IEEE 802.11n HT40 / ac VHT40: 2 Channels; IEEE 802.11ac VHT80: 1 Channel.
Modulation	:	OFDM(QPSK, BPSK, 16-QAM, 64-QAM,256-QAM)
Transmit Data Rate	:	IEEE 802.11a: 54, 48, 36, 24, 18, 12, 9, 6Mbps; IEEE 802.11n: up 150Mbps; IEEE 802.11ac: up to 433.3Mbps;
Channels Spacing	:	IEEE 802.11a: 20MHz; IEEE 802.11n HT20: 20MHz; IEEE 802.11n HT40: 40MHz; IEEE 802.11ac VHT20: 20MHz; IEEE 802.11ac VHT40: 40MHz; IEEE 802.11ac VHT80: 80MHz;

Transmit Power	:	U-NII-1	IEEE 802.11a: 11.79dBm IEEE 802.11n HT20: 11.63dBm IEEE 802.11n HT40: 11.05dBm IEEE 802.11ac VHT20: 11.7dBm IEEE 802.11ac VHT40: 11.16dBm IEEE 802.11ac VHT80: 10.93dBm
		U-NII-2A	IEEE 802.11a: 11.86dBm IEEE 802.11n HT20: 11.76dBm IEEE 802.11n HT40: 11.08dBm IEEE 802.11ac VHT20: 11.31dBm IEEE 802.11ac VHT40: 11.08dBm IEEE 802.11ac VHT80: 10.91dBm
		U-NII-2C	IEEE 802.11a: 10.75dBm IEEE 802.11n HT20: 10.57dBm IEEE 802.11n HT40: 10.01dBm IEEE 802.11ac VHT20: 10.1dBm IEEE 802.11ac VHT40: 9.94dBm IEEE 802.11ac VHT80: 9.47dBm
		U-NII-3	IEEE 802.11a: 9.85dBm IEEE 802.11n HT20: 9.83dBm IEEE 802.11n HT40: 8.88dBm IEEE 802.11ac VHT20: 9.17dBm IEEE 802.11ac VHT40: 8.89dBm IEEE 802.11ac VHT80: 8.46dBm
Sample Type	:	Prototype production	

Note:

For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.

1.1. Difference between Model Numbers

Model Number	main board	DDR	EMMC	MPU
100011885	1	RS512M32LZ4D2ANP_75BT 2G/4die 3733Mbps 10*14.5mm FBGA200 RS	MEMA032G 32GB 1.8V/HS400/EMMC5.1 200MHz 153-FBGA ISOCOM	MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP
	2	MDXC1016G-M2 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 FORESEE	LTMZ0007HF-DAB1-SM Leahkinn	
	3	RS512M32LM4D2BDS-53BT 2GB(512*32) 3200Mbps 10*14.5mm FBGA200 RS	EMMC32G-TA28 32GB 1.8V 200MHz 153-FBGA Kingston	

Note: Default is A mainboard, reported to the DDR,EMMC and MPU combination for 2 and 3

1.2. The antenna information for EUT

Ant No.	Brand	Model Name	Antenna Type	Connector	Gain (dBi)
1	N/A	N/A	Internal	N/A	2.2

2. SUMMARY OF TEST

2.1. Summary of test result

Report Section	Description of Test Item	FCC Standard Section	Results
3	6dB Bandwidth & 26dB Bandwidth & 99% Occupied Bandwidth	15.407(a) 15.407(e)	N/A
4	Maximum Conducted Output Power	15.407(a)	N/A
5	Peak Power Spectral Density	15.407(a)	N/A
6	Unwanted Emissions and Band Edge	15.205 15.209 15.407(b)	PASS
7	Frequency Stability	15.407(g)	N/A
8	AC Power Line Conducted Emissions	15.207 15.407(b)(6)	PASS
9	Antenna Requirement	15.203	N/A

Note:

(1) "N/A" denotes test is not applicable in this test report

2.2. Test Facilities

EMC Lab : Certificated by CNAS, CHINA
 Registration No.: L5288
 This Certificate is valid until: November 12, 2023

Certificated by FCC, USA
 Designation Number: CN1215
 This Certificate is valid until: January 31, 2022

Certificated by A2LA, USA
 Registration No.: 4366.01
 This Certificate is valid until: January 31, 2022

Certificated by Industry Canada
 CAB identifier No.: CN0035
 This Certificate is valid until: January 31, 2022

Certificated by VCCI, Japan
 Registration No.: C-14103; T-20073; R-13663;
 R-20103; G-20097
 Date of registration: Apr. 20, 2020
 This Certificate is valid until: Apr. 19, 2023

Certificated by TUV Rheinland, Germany
 Registration No.: UA 50413872 0001
 Date of registration: July 31, 2018

Certificated by Intertek
 Registration No.: 2011-RTL-L2-64
 Date of registration: November 08, 2018

Name of Firm : EST Technology Co., Ltd.

Site Location : Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China

2.3. Measurement uncertainty for EST Technology Co., Ltd.

Test Item	Uncertainty
Uncertainty for Conduction emission test	2.54dB
Uncertainty for Radiation Emission test (30MHz-1GHz)	3.62
Uncertainty for Radiation Emission test (1GHz to 18GHz)	4.86
Uncertainty for spurious emissions test (18GHz to 40GHz)	4.67
Uncertainty for radio frequency	7×10^{-8}
Uncertainty for conducted RF Power	0.20dB
Uncertainty for Power density test	0.26dB
Temperature	$\pm 0.6^{\circ}\text{C}$
Humidity	$\pm 4.0\%$
Volatage DC	$\pm 1.0\%$
Volatage (AC, <10KHz)	$\pm 1.5\%$

Note:

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.


2.4. Assistant equipment used for test

Item	Equipment	Brand	Model Name/Type No.	FCC ID	Series No.
A	Adapter	onn.	GDA0101H-U0500200	-	-

Item	Shielded Type	Ferrite Core	Length	Note
1	NO	NO	1m	DC Cable

2.5. Block Diagram

For radiated emissions test: EUT was placed on a turn table, which is 0.8 (or 1.5) meter high above ground.



2.6. Test Mode

Pre-scan has been combined all possible modulations and data rates to determine the worst case test mode, the worst case test mode was selected for the final test as listed below.

Test Item	Test Mode	Channel	Modulation	Data rate
Unwanted Emissions Below 1GHz	IEEE 802.11a	100	OFDM	6Mbps
AC Power Line Conducted Emissions	IEEE 802.11a	100	OFDM	6Mbps

Note:

1. In radiated measurement, the EUT had been pre-scan on the positioned of each 3 axis(X,Y,Z), the worst case was found when positioned on **X-plane**.

2.7. Channel List

Band	Mode	Channel	Frequency (MHz)
U-NII-1	IEEE 802.11a & n HT20 & ac VHT20	36	5180
		40	5200
		44	5220
		48	5240
	IEEE 802.11n HT40 & ac VHT40	38	5190
		46	5230
	IEEE 802.11ac VHT80	42	5210
U-NII-2A	IEEE 802.11a & n HT20 & ac VHT20	52	5260
		56	5280
		60	5300
		64	5320
	IEEE 802.11n HT40 & ac VHT40	54	5270
		62	5310
	IEEE 802.11ac VHT80	58	5290
U-NII-2C	IEEE 802.11a & n HT20 & ac VHT20	100	5500
		104	5520
		108	5540
		112	5560
		116	5580
		120	5600
		124	5620
		128	5640
		132	5660
		136	5680
	IEEE 802.11n HT40 & ac VHT40	140	5700
		102	5510
		110	5550
		118	5590
		126	5630
	IEEE 802.11ac VHT80	134	5670
		106	5530
		122	5610
U-NII-3	IEEE 802.11a & n HT20 & ac VHT20	149	5745
		153	5765
		157	5785
		161	5805
		165	5825
	IEEE 802.11n HT40 & ac VHT40	151	5755
		159	5795
	IEEE 802.11ac VHT80	155	5775

2.8. Power Setting of Test Software

Software Name	N/A		
U-NII-1			
Frequency(MHz)	5180	5200	5240
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5190	5230	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5210		
IEEE 802.11ac VHT80 Setting	Default		
U-NII-2A			
Frequency(MHz)	5260	5300	5320
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5270	5310	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5290		
IEEE 802.11ac VHT80 Setting	Default		
U-NII-2C			
Frequency(MHz)	5500	5580	5700
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5510	5590	5670
IEEE 802.11n HT40 Setting	Default	Default	Default
IEEE 802.11ac VHT40 Setting	Default	Default	Default
Frequency(MHz)	5530	5610	
IEEE 802.11ac VHT80 Setting	Default	Default	
U-NII-3			
Frequency(MHz)	5745	5785	5825
IEEE 802.11a Setting	Default	Default	Default
IEEE 802.11n HT20 Setting	Default	Default	Default
IEEE 802.11ac VHT20 Setting	Default	Default	Default
Frequency(MHz)	5755	5795	
IEEE 802.11n HT40 Setting	Default	Default	
IEEE 802.11ac VHT40 Setting	Default	Default	
Frequency(MHz)	5775		
IEEE 802.11ac VHT80 Setting	Default		

2.9. Test Equipment List

For conducted emission test						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESHS30	EST-E001	LISAI	June 13,20	1 Year
Artificial Mains Network	Rohde & Schwarz	ENV216	EST-E002	LISAI	June 13,20	1 Year
Pulse Limiter	Rohde & Schwarz	ESH3-Z2	EST-E078	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A

For radiated emissions test (30MHz-1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
EMI Test Receiver	Rohde & Schwarz	ESR7	EST-E047	LISAI	June 13,20	1 Year
Bilog Antenna	Teseq	CBL 6111D	EST-E034	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
30-1000MHz Cable	N/A	EST-002	N/A	N/A	N/A	N/A

For radiated emission test(Above 1000MHz)						
Equipment	Manufacturer	Model No.	Serial No.	Calibration Body	Last Cal.	Next Cal.
Horn Antenna	SCHWARZB ECK	BBHA9120D	EST-E031	LISAI	June 13,20	1 Year
Signal Amplifier	SCHWARZB ECK	BBV9718	EST-E032	LISAI	June 13,20	1 Year
Spectrum Analyzer	Rohde &Schwarz	FSV40	EST-E069	LISAI	June 13,20	1 Year
Test Software	Audix	e3-6.111221a	N/A	N/A	N/A	N/A
Above 1GHz Cable	N/A	EST-003	N/A	N/A	N/A	N/A

3. UNWANTED EMISSIONS AND BAND EDGE

3.1. Limit

The maximum emissions outside of the frequency bands of operation shall be attenuated in accordance with the following limits:

- (1) For transmitters operating in the 5.15-5.25 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (2) For transmitters operating in the 5.25-5.35 GHz band: All emissions outside of the 5.15-5.35 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (3) For transmitters operating in the 5.47-5.725 GHz band: All emissions outside of the 5.47-5.725 GHz band shall not exceed an e.i.r.p. of -27 dBm/MHz.
- (4) For transmitters operating in the 5.725-5.85 GHz band: All emissions shall be limited to a level of -27 dBm/MHz at 75 MHz or more above or below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above or below the band edge, and from 25 MHz above or below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above or below the band edge, and from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.

The unwanted emissions which fall in Restricted bands shall not exceed the field strength levels specified in the following table:

15.209 Radiated emission limits

Frequency (MHz)	Field Strength(μ V/m)	Distance(m)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

15.205 Restricted frequency band


MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 - 156.52525	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.7 - 156.9	2690 - 2900	22.01 - 23.12
8.41425 - 8.41475	162.0125 - 167.17	3260 - 3267	23.6 - 24.0
12.29 - 12.293	167.72 - 173.2	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	240 - 285	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	322 - 335.4	3600 - 4400	(²)

Note:

1. $\text{dB}\mu\text{V/m} = 20\text{Log}(\mu\text{V/m})$
2. Above 1GHz the formula is used to convert the EIRP to field strength

$$E[\text{dB}\mu\text{V/m}] = \text{EIRP}[\text{dBm}] - 20 \log(d[\text{m}]) + 104.77,$$
 where E is field strength and d is distance at which the field strength limit is specified in the applicable requirements.
 for example, $3\text{m field strength}(\text{dB}\mu\text{V/m}) = \text{EIRP} - 20\log(3) + 104.77 = \text{EIRP} + 95.2$

3.2. Test Setup



3.3. Spectrum Analyzer Setting

For 9KHz-150KHz

Spectrum Parameters	Setting
RBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
VBW	300Hz(for Peak&AVG)/CISPR 200Hz(for QP)
Start frequency	9KHz
Stop frequency	150KHz
Sweep Time	Auto
Detector	PEAK/QP/AVG
Trace Mode	Max Hold

Note : For 9KHz-90KHz&110KHz-150KHz,the detector is average,other frequency is CISPR QP detector.

For 150KHz-30MHz

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

Note : For 150KHz-490KHz,the detector is average,other frequency is CISPR QP detector.

For 30MHz-1GHz

Spectrum Parameters	Setting
RBW	120KHz
VBW	300KHz
Start frequency	30MHz
Stop frequency	1GHz
Sweep Time	Auto
Detector	QP
Trace Mode	Max Hold

For Above 1GHz

Spectrum Parameters	Setting	
RBW	1MHz	
VBW	PEAK Measurement	AVG Measurement
	3MHz	Duty cycle $\geq$ 98%,VBW=10Hz Duty cycle<98%,VBW $\geq$ 1/T Video bandwidth mode=RMS (power averaging)
Start frequency	1GHz	
Stop frequency	40GHz	
Sweep Time	Auto	
Detector	PEAK	
Trace Mode	Max Hold	

Note : T is the on-time time of the duty cycle,when EUT transmit continuously with maximum output power,unit is seconds. reference section 2.7 for the on-time time.

3.4. Test Procedure


- a. EUT was placed on a turn table, which is 0.8 meter high above ground for below 1GHz test, and which is 1.5 meter high above ground for above 1GHz test.
- b. EUT is set 3 meters away from the receiving antenna, which is mounted on a antenna tower.
- c. Set the EUT transmit continuously with maximum output power.
- d. The turn table can rotate 360 degrees to determine the position of the maximum emission level.
- e. The antenna can be moved up and down between 1 meter and 4 meters to find out the maximum emission level. Both horizontal and vertical polarization of the antenna are set on test.
- f. Spectrum analyzer setting parameters in accordance with section 6.3.
- g. Repeat above procedures until all channels were measured.
- h. Record the results in the test report.

3.5. Test Result

Radiated Emissions Below 1GHz

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Site no. : 3# 966 Chamber Data no. : 97
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32L24D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	38.730	12.50	0.20	9.36	22.06	40.00	17.94	QP
2	185.200	9.20	1.23	10.27	20.70	43.50	22.80	QP
3	705.120	21.70	3.30	2.30	27.30	46.00	18.70	QP
4	817.640	23.28	3.70	3.60	30.58	46.00	15.42	QP
5	851.590	23.26	3.72	3.65	30.63	46.00	15.37	QP
6	950.530	24.61	4.54	4.03	33.18	46.00	12.82	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 98

File: \\Emc-966-1\test data\2020\RF\CHANGCHENG\100011885.EM6 (118)

Date: 2020-08-24



Site no. : 3# 966 Chamber Data no. : 98
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2';Humi:56%;Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.60	0.14	2.72	20.46	40.00	19.54	QP
2	204.600	8.60	1.32	10.21	20.13	43.50	23.37	QP
3	716.760	21.70	3.43	3.04	28.17	46.00	17.83	QP
4	791.450	22.72	3.56	2.76	29.04	46.00	16.96	QP
5	832.190	23.42	3.71	3.19	30.32	46.00	15.68	QP
6	944.710	24.50	4.44	2.95	31.89	46.00	14.11	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 105

File: \\Emc-966-1\\test data\\2020\\RF\\C\\CHANGCHENG\\100011885.EM6 (118)

Date: 2020-08-24



Site no. : 3# 966 Chamber Data no. : 105
 Dis. / Ant. : 3m 37062 Ant. pol. : VERTICAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2'; Humi:56%; Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTMZ0007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.60	0.14	7.68	25.42	40.00	14.58	QP
2	47.460	9.60	0.29	13.32	23.21	40.00	16.79	QP
3	163.860	10.66	1.16	13.73	25.55	43.50	17.95	QP
4	181.320	9.44	1.22	13.38	24.04	43.50	19.46	QP
5	899.120	23.90	3.88	2.71	30.49	46.00	15.51	QP
6	956.350	24.66	4.59	2.97	32.22	46.00	13.78	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 106

File: \\Emc-966-1\\test data\\2020\\RF\\C\\CHANGCHENG\\100011885.EM6 (118)

Date: 2020-08-24



Site no. : 3# 966 Chamber Data no. : 106
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2';Humi:56%;Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTMZ0007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	30.970	17.60	0.14	3.44	21.18	40.00	18.82	QP
2	185.200	9.20	1.23	10.98	21.41	43.50	22.09	QP
3	211.390	8.84	1.37	11.63	21.84	43.50	21.66	QP
4	728.400	21.70	3.53	2.00	27.23	46.00	18.77	QP
5	849.650	23.10	3.72	3.42	30.24	46.00	15.76	QP
6	937.920	24.34	4.31	2.85	31.50	46.00	14.50	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 113

File: \\Emc-966-1\test data\2020\RF\CHANGCHENG\100011885.EM6 (118)

Date: 2020-08-25




Site no. : 3# 966 Chamber Data no. : 113
 Dis. / Ant. : 3m 37062 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15 B(3M)
 Env. / Ins. : Temp:25.2';Humi:56%;Press:101.52kPa
 Engineer : Blank
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	ANT Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	84.320	8.16	0.74	11.02	19.92	40.00	20.08	QP
2	553.800	19.32	2.86	2.90	25.08	46.00	20.92	QP
3	671.170	21.70	3.22	3.04	27.96	46.00	18.04	QP
4	793.390	22.76	3.55	6.52	32.83	46.00	13.17	QP
5	833.160	23.43	3.71	5.38	32.52	46.00	13.48	QP
6	958.290	24.68	4.60	1.76	31.04	46.00	14.96	QP

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading.
 2. Margin= Limit - Emission Level.
 3. The emission levels that are 20dB below the official limit are not reported.

EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878



Note:

1. The amplitude of 9KHz to 30MHz spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.
2. All channels had been pre-test, only the worst case was reported.

4. AC POWER LINE CONDUCTED EMISSIONS


4.1. Limit

Frequency			Maximum RF Line Voltage	
			Quasi-Peak Level dB(μ V)	Average Level dB(μ V)
150kHz	~	500kHz	66 ~ 56*	56 ~ 46*
500kHz	~	5MHz	56	46
5MHz	~	30MHz	60	50

Notes:

1. * Decreasing linearly with logarithm of frequency.
2. The lower limit shall apply at the transition frequencies.

4.2. Test Setup



4.3. Spectrum Analyzer Setting

Spectrum Parameters	Setting
RBW	9KHz
VBW	9KHz
Start frequency	150KHz
Stop frequency	30MHz
Sweep Time	Auto
Detector	QP/AVG
Trace Mode	Max Hold

4.4. Test Procedure

- a. The EUT was placed on a non-metallic table, 80cm above the ground plane.
- b. The EUT Power connected to the power mains through a line impedance stabilization network.
- c. Provides a 50 ohm coupling impedance for the EUT (Please refer the block diagram of the test setup and photographs).
- d. Set the EUT transmit continuously with maximum output power.
- e. Spectrum analyzer setting parameters in accordance with section 8.3.
- f. The AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to ANSI C63.10: 2013 on Conducted Emission Test.
- g. Record the results in the test report.

4.5. Test Result


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 170

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 169

Site no : 844 Shield Room Data no. : 170
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.4148	9.64	9.92	16.82	36.38	47.55	11.17	Average
2	0.4148	9.64	9.92	22.94	42.50	57.55	15.05	QP
3	0.4612	9.65	9.92	17.94	37.51	46.67	9.16	Average
4	0.4612	9.65	9.92	23.53	43.10	56.67	13.57	QP
5	0.4994	9.65	9.92	15.57	35.14	46.01	10.87	Average
6	0.4994	9.65	9.92	21.78	41.35	56.01	14.66	QP
7	0.7430	9.69	9.93	11.29	30.91	46.00	15.09	Average
8	0.7430	9.69	9.93	20.48	40.10	56.00	15.90	QP
9	1.1352	9.75	9.94	8.19	27.88	46.00	18.12	Average
10	1.1352	9.75	9.94	21.54	41.23	56.00	14.77	QP
11	1.5767	9.78	9.95	6.28	26.01	46.00	19.99	Average
12	1.5767	9.78	9.95	19.48	39.21	56.00	16.79	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 172

File: \\Emc-ce-1\Test data\2020\RF\C\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 171

Site no : 844 Shield Room Data no. : 172
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3771	9.72	9.92	5.07	24.71	48.34	23.63	Average
2	0.3771	9.72	9.92	16.74	36.38	58.34	21.96	QP
3	0.4148	9.72	9.92	10.02	29.66	47.55	17.89	Average
4	0.4148	9.72	9.92	18.32	37.96	57.55	19.59	QP
5	0.4564	9.72	9.92	17.37	37.01	46.76	9.75	Average
6	0.4564	9.72	9.92	24.48	44.12	56.76	12.64	QP
7	0.8393	9.72	9.93	6.60	26.25	46.00	19.75	Average
8	0.8393	9.72	9.93	17.78	37.43	56.00	18.57	QP
9	1.1719	9.73	9.94	6.24	25.91	46.00	20.09	Average
10	1.1719	9.73	9.94	18.47	38.14	56.00	17.86	QP
11	2.6221	9.75	9.97	1.54	21.26	46.00	24.74	Average
12	2.6221	9.75	9.97	15.64	35.36	56.00	20.64	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 174

File: \\Emc-ce-1\Test data\2020\RF\C\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 173

Site no : 844 Shield Room Data no. : 174
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3356	9.72	9.92	3.41	23.05	49.31	26.26	Average
2	0.3356	9.72	9.92	16.63	36.27	59.31	23.04	QP
3	0.4237	9.72	9.92	11.14	30.78	47.37	16.59	Average
4	0.4237	9.72	9.92	23.42	43.06	57.37	14.31	QP
5	0.4686	9.72	9.92	10.07	29.71	46.54	16.83	Average
6	0.4686	9.72	9.92	24.35	43.99	56.54	12.55	QP
7	0.5101	9.72	9.92	3.87	23.51	46.00	22.49	Average
8	0.5101	9.72	9.92	16.33	35.97	56.00	20.03	QP
9	0.8850	9.72	9.93	3.66	23.31	46.00	22.69	Average
10	0.8850	9.72	9.93	13.76	33.41	56.00	22.59	QP
11	1.3029	9.73	9.94	2.43	22.10	46.00	23.90	Average
12	1.3029	9.73	9.94	13.69	33.36	56.00	22.64	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 176

File: \\Emc-ce-1\Test data\2020\RF\IC\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 175

Site no : 844 Shield Room Data no. : 176
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LZ4D2ANP_75BT 2G
 EMMC:MEMA032G 32GB 1.8V
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1668	9.61	9.69	6.65	25.95	55.12	29.17	Average
2	0.1668	9.61	9.69	21.74	41.04	65.12	24.08	QP
3	0.3374	9.63	9.92	6.70	26.25	49.27	23.02	Average
4	0.3374	9.63	9.92	16.83	36.38	59.27	22.89	QP
5	0.4237	9.64	9.92	14.73	34.29	47.37	13.08	Average
6	0.4237	9.64	9.92	21.85	41.41	57.37	15.96	QP
7	0.4637	9.65	9.92	12.67	32.24	46.63	14.39	Average
8	0.4637	9.65	9.92	20.73	40.30	56.63	16.33	QP
9	0.5020	9.65	9.92	10.73	30.30	46.00	15.70	Average
10	0.5020	9.65	9.92	16.85	36.42	56.00	19.58	QP
11	0.8850	9.72	9.93	5.97	25.62	46.00	20.38	Average
12	0.8850	9.72	9.93	17.46	37.11	56.00	18.89	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 202

File: \\Emc-ce-1\Test data\2020\RF\C\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 201

Site no : 844 Shield Room Data no. : 202
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.2072	9.73	9.84	7.21	26.78	53.32	26.54	Average
2	0.2072	9.73	9.84	23.57	43.14	63.32	20.18	QP
3	0.3410	9.72	9.92	5.10	24.74	49.18	24.44	Average
4	0.3410	9.72	9.92	19.66	39.30	59.18	19.88	QP
5	0.3832	9.72	9.92	5.40	25.04	48.21	23.17	Average
6	0.3832	9.72	9.92	16.58	36.22	58.21	21.99	QP
7	0.4260	9.72	9.92	8.89	28.53	47.33	18.80	Average
8	0.4260	9.72	9.92	18.64	38.28	57.33	19.05	QP
9	0.4661	9.72	9.92	9.84	29.48	46.58	17.10	Average
10	0.4661	9.72	9.92	20.74	40.38	56.58	16.20	QP
11	0.8528	9.72	9.93	1.60	21.25	46.00	24.75	Average
12	0.8528	9.72	9.93	16.77	36.42	56.00	19.58	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.


2. Margin=Limit - Emission Level.

3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 204

File: \\Emc-ce-1\Test data\2020\RF\C\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 203

Site no : 844 Shield Room Data no. : 204
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.2971	9.62	9.92	11.81	31.35	50.32	18.97	Average
2	0.2971	9.62	9.92	18.71	38.25	60.32	22.07	QP
3	0.4215	9.64	9.92	14.38	33.94	47.42	13.48	Average
4	0.4215	9.64	9.92	18.57	38.13	57.42	19.29	QP
5	0.4612	9.65	9.92	18.34	37.91	46.67	8.76	Average
6	0.4612	9.65	9.92	24.45	44.02	56.67	12.65	QP
7	0.5020	9.65	9.92	13.47	33.04	46.00	12.96	Average
8	0.5020	9.65	9.92	21.58	41.15	56.00	14.85	QP
9	0.6271	9.67	9.92	8.77	28.36	46.00	17.64	Average
10	0.6271	9.67	9.92	21.88	41.47	56.00	14.53	QP
11	1.0997	9.74	9.94	19.78	39.46	46.00	6.54	Average
12	1.0997	9.74	9.94	8.55	28.23	56.00	27.77	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 206

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 205

Site no : 844 Shield Room Data no. : 206
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1740	9.73	9.77	5.21	24.71	54.77	30.06	Average
2	0.1740	9.73	9.77	23.36	42.86	64.77	21.91	QP
3	0.3356	9.72	9.92	1.14	20.78	49.31	28.53	Average
4	0.3356	9.72	9.92	16.46	36.10	59.31	23.21	QP
5	0.4260	9.72	9.92	10.52	30.16	47.33	17.17	Average
6	0.4260	9.72	9.92	19.45	39.09	57.33	18.24	QP
7	0.4686	9.72	9.92	12.45	32.09	46.54	14.45	Average
8	0.4686	9.72	9.92	23.67	43.31	56.54	13.23	QP
9	0.5074	9.72	9.92	4.69	24.33	46.00	21.67	Average
10	0.5074	9.72	9.92	13.80	33.44	56.00	22.56	QP
11	0.8045	9.72	9.93	1.69	21.34	46.00	24.66	Average
12	0.8045	9.72	9.93	14.88	34.53	56.00	21.47	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 208

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 207

Site no : 844 Shield Room Data no. : 208
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:MDXC1016G-M2 2GB
 EMMC:LTM20007HF-DAB1-SM
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJJP

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.1806	9.62	9.77	9.74	29.13	54.46	25.33	Average
2	0.1806	9.62	9.77	23.85	43.24	64.46	21.22	QP
3	0.4193	9.64	9.92	16.82	36.38	47.46	11.08	Average
4	0.4193	9.64	9.92	23.45	43.01	57.46	14.45	QP
5	0.4711	9.65	9.92	13.83	33.40	46.49	13.09	Average
6	0.4711	9.65	9.92	23.56	43.13	56.49	13.36	QP
7	0.5182	9.65	9.92	11.34	30.91	46.00	15.09	Average
8	0.5182	9.65	9.92	20.58	40.15	56.00	15.85	QP
9	0.7918	9.70	9.93	6.77	26.40	46.00	19.60	Average
10	0.7918	9.70	9.93	17.88	37.51	56.00	18.49	QP
11	0.8850	9.72	9.93	7.17	26.82	46.00	19.18	Average
12	0.8850	9.72	9.93	16.58	36.23	56.00	19.77	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 234

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 233

Site no : 844 Shield Room Data no. : 234
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3832	9.64	9.92	11.96	31.52	48.21	16.69	Average
2	0.3832	9.64	9.92	17.84	37.40	58.21	20.81	QP
3	0.4215	9.64	9.92	16.68	36.24	47.42	11.18	Average
4	0.4215	9.64	9.92	22.59	42.15	57.42	15.27	QP
5	0.4612	9.65	9.92	18.09	37.66	46.67	9.01	Average
6	0.4612	9.65	9.92	24.35	43.92	56.67	12.75	QP
7	0.4967	9.65	9.92	14.24	33.81	46.05	12.24	Average
8	0.4967	9.65	9.92	22.38	41.95	56.05	14.10	QP
9	0.8438	9.71	9.93	10.80	30.44	46.00	15.56	Average
10	0.8438	9.71	9.93	16.67	36.31	56.00	19.69	QP
11	1.6105	9.79	9.95	6.47	26.21	46.00	19.79	Average
12	1.6105	9.79	9.95	16.74	36.48	56.00	19.52	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 236

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 235

Site no : 844 Shield Room Data no. : 236
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 240V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF


	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3832	9.72	9.92	4.72	24.36	48.21	23.85	Average
2	0.3832	9.72	9.92	16.85	36.49	58.21	21.72	QP
3	0.4237	9.72	9.92	12.92	32.56	47.37	14.81	Average
4	0.4237	9.72	9.92	18.73	38.37	57.37	19.00	QP
5	0.4612	9.72	9.92	13.97	33.61	46.67	13.06	Average
6	0.4612	9.72	9.92	26.82	46.46	56.67	10.21	QP
7	0.4915	9.72	9.92	10.73	30.37	46.14	15.77	Average
8	0.4915	9.72	9.92	15.33	34.97	56.14	21.17	QP
9	0.7670	9.72	9.93	2.82	22.47	46.00	23.53	Average
10	0.7670	9.72	9.93	16.75	36.40	56.00	19.60	QP
11	1.1907	9.73	9.94	3.27	22.94	46.00	23.06	Average
12	1.1907	9.73	9.94	21.38	41.05	56.00	14.95	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

Data: 238

File: \\Emc-ce-1\Test data\2020\RF\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 237

Site no : 844 Shield Room Data no. : 238
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : LINE
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3410	9.72	9.92	2.54	22.18	49.18	27.00	Average
2	0.3410	9.72	9.92	13.37	33.01	59.18	26.17	QP
3	0.4215	9.72	9.92	13.25	32.89	47.42	14.53	Average
4	0.4215	9.72	9.92	20.36	40.00	57.42	17.42	QP
5	0.4637	9.72	9.92	11.05	30.69	46.63	15.94	Average
6	0.4637	9.72	9.92	22.45	42.09	56.63	14.54	QP
7	0.5020	9.72	9.92	3.00	22.64	46.00	23.36	Average
8	0.5020	9.72	9.92	16.24	35.88	56.00	20.12	QP
9	0.8944	9.72	9.94	5.45	25.11	46.00	20.89	Average
10	0.8944	9.72	9.94	18.59	38.25	56.00	17.75	QP
11	1.1292	9.73	9.94	4.50	24.17	46.00	21.83	Average
12	1.1292	9.73	9.94	14.67	34.34	56.00	21.66	QP

Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.


EST Technology

Chilingxiang, Qishantou, Santun,
Houjie, Dongguan, Guangdong, China
Tel: +86-769-83081888
Fax: +86-769-83081878

Data: 240

File: \\Emc-ce-1\Test data\2020\RF\C\CHANGCHENG.EM6 (256)

Date: 2020-08-27



Trace: 239



Site no : 844 Shield Room Data no. : 240
 Env. / Ins. : Temp:23.5°C Humi:58% Press:101.50kPa LINE Phase : NEUTRAL
 Limit : FCC PART 15B QP
 Engineer : ZSX
 EUT : 8"Android Tablet
 Power : DC 5V From Adapter Input AC 120V/60Hz
 M/N : 100011885
 Test Mode : TX Mode
 DDR:RS512M32LM4D2BDS-53BT 2GB
 EMMC:EMMC32G-TA28 32GB
 MEDIATEK MT6357ARU 2010-ANSHDCMJ3JJF

	Freq. (MHz)	LISN Factor (dB)	Cable Loss (dB)	Reading (dBuV)	Emission Level (dBuV)	Limits (dBuV)	Margin (dB)	Remark
1	0.3428	9.63	9.92	6.46	26.01	49.13	23.12	Average
2	0.3428	9.63	9.92	14.55	34.10	59.13	25.03	QP
3	0.4215	9.64	9.92	15.76	35.32	47.42	12.10	Average
4	0.4215	9.64	9.92	21.85	41.41	57.42	16.01	QP
5	0.4637	9.65	9.92	13.59	33.16	46.63	13.47	Average
6	0.4637	9.65	9.92	23.64	43.21	56.63	13.42	QP
7	0.5020	9.65	9.92	9.08	28.65	46.00	17.35	Average
8	0.5020	9.65	9.92	20.44	40.01	56.00	15.99	QP
9	0.8850	9.72	9.93	7.93	27.58	46.00	18.42	Average
10	0.8850	9.72	9.93	17.51	37.16	56.00	18.84	QP
11	1.0824	9.74	9.94	4.27	23.95	46.00	22.05	Average
12	1.0824	9.74	9.94	14.55	34.23	56.00	21.77	QP


Remarks: 1. Emission Level= LISN Factor + Cable Loss + Reading.
 2. Margin=Limit - Emission Level.
 3. If the average limit is met when using a quasi-peak detector,
 the EUT shall be deemed to meet both limits and measurement
 with average detector is unnecessary.

5. TEST SETUP PHOTO

Conducted Test



Radiated Test (Below 1GHz)




6. EUT PHOTO

External Photos



M/N: 100011885



External Photos
M/N: 100011885



External Photos
M/N: 100011885



Power Supply



Power Supply



Mainboard Model No.: RS512M32LZ4D2ANP_75BT 2G & MEMA032G 32GB 1.8V


Internal Photos
M/N: 100011885



Internal Photos
M/N: 100011885




Internal Photos
M/N: 100011885




Mainboard Model No.: MDXC1016G-M2 2GB & LTMZ0007HF-DAB1-SM

Internal Photos

M/N: 100011885





Internal Photos
M/N: 100011885





Mainboard Model No.: RS512M32LM4D2BDS-53BT 2GB & EMMC32G-TA28 32GB

Internal Photos

M/N: 100011885



Internal Photos
M/N: 100011885



End of Test Report