FCC TEST REPORT
FCC ID:2APUR-K21

Report Number.....:	ZKT-2106242855E
Date of Test.....	Jun. 15, 2021 to Jun. 28, 2021
Date of issue.....:	Jun. 28, 2021
Total number of pages.....	75
Test Result .....:	PASS
Testing Laboratory..... :	**Shenzhen ZKT Technology Co., Ltd.**
Address ..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Applicant's name .....:	**Shenzhen Musen Technology Co., Ltd**
Address ..... :	Unit 2389, 23/F, Block C Electronic Technology Building, Huafa North Road, Futian District, Shenzhen, China
Manufacturer's name .....:	**Shenzhen Musen Technology Co., Ltd**
Address ..... :	Unit 2389, 23/F, Block C Electronic Technology Building, Huafa North Road, Futian District, Shenzhen, China
Test specification:	
Standard.....:	FCC CFR Title 47 Part 15 Subpart C Section 15.247 ANSI C63.10:2013
Test procedure..... :	/
Non-standard test method .....:	N/A
Test Report Form No.....:	TRF-EL-112_V0
Test Report Form(s) Originator.....:	ZKT Testing
Master TRF .....:	Dated: 2021-04-22

This device described above has been tested by ZKT, and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.
This report shall not be reproduced except in full, without the written approval of ZKT, this document may be altered or revised by ZKT, personal only, and shall be noted in the revision of the document.

Product name..... :	Wireless Headphones
Trademark .....:	N/A
Model/Type reference..... :	K21 MS-K10,MS-K11,MS-K13,MS-K14,MS-K16,MS-K17,MS-K19,MS-K20,MS-K21,MS-K22,AKZ-K23,AKZ-K24,AKZ-K25,AKZ-K26,AKZ-K27,AKZ-K28,AKZ-K29,AKZ-K30,GM-C1,GM-C3,GM-C4,AKZ-MAX10,AKZ-MAX11,AKZ-T55,MS-771,MS-881,MS-991
Ratings..... :	Input: DC 5V or DC 3.7V Battery

Testing procedure and testing location:

Testing Laboratory.....:	Shenzhen ZKT Technology Co., Ltd.
Address..... :	1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China
Tested by (name + signature).....:	Alen He
Reviewer (name + signature)..... :	Joe Liu
Approved (name + signature)..... :	Lake Xie

Table of Contents

Page
1. VERSION 5
2. TEST SUMMARY 6
2.1 TEST FACILITY 7
2.2 MEASUREMENT UNCERTAINTY 7
3. GENERAL INFORMATION 8
3.1 GENERAL DESCRIPTION OF EUT 8
3.2 Test Setup Configuration 9
3.3 Support Equipment 9
3.4 Test Mode 10
3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS 11
4. EMC EMISSION TEST 12
4.1 Conducted emissions 12
4.1.1 POWER LINE CONDUCTED EMISSION Limits 12
4.1.2 TEST PROCEDURE 12
4.1.3 DEVIATION FROM TEST STANDARD 12
4.1.4 TEST SETUP 13
4.1.5 EUT OPERATING CONDITIONS 13
4.1.6 Test Result 14
4.2 Radiated emissions 16
4.2.1 Radiated Emission Limits 16
4.2.2 TEST PROCEDURE 16
4.2.3 DEVIATION FROM TEST STANDARD 17
4.2.4 TEST SETUP 17
4.2.5 EUT OPERATING CONDITIONS 18
4.2.6 TEST RESULTS 19
5. RADIATED BAND EMISSION MEASUREMENT 28
5.1 Test Requirement: 28
5.2 TEST PROCEDURE 28
5.3 DEVIATION FROM TEST STANDARD 29
5.4 TEST SETUP 29
5.5 EUT OPERATING CONDITIONS 29
5.6 TEST RESULT 30
6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION 32
6.1 Limit 32
6.2 Test Setup 32
6.3 Test procedure 32
6.4 DEVIATION FROM STANDARD 32
6.5 Test Result 33
7. 20DB&99% BANDWIDTH 45
7.1 Test Setup 45
7.2 Limit 45
7.3 Test procedure 45
7.4 DEVIATION FROM STANDARD 45

7.5 Test Result..... 45
8. MAXIMUM PEAK OUTPUT POWER..... 52
8.1 Block Diagram Of Test Setup..... 52
8.2 Limit..... 52
8.3 Test procedure..... 52
8.4 DEVIATION FROM STANDARD..... 52
8.5 Test Result..... 52
9. HOPPING CHANNEL SEPARATION..... 58
9.1 Test Setup..... 58
9.2 Test procedure..... 58
9.3 DEVIATION FROM STANDARD..... 58
9.4 Test Result..... 59
10.NUMBER OF HOPPING FREQUENCY..... 64
10.1 Test Setup..... 64
10.2 Test procedure..... 64
10.3 DEVIATION FROM STANDARD..... 64
10.4 Test Result..... 65
11. DWELL TIME..... 67
11.1 Test Setup..... 67
11.2 Test procedure..... 67
11.3 DEVIATION FROM STANDARD..... 67
11.4 Test Result..... 68
12. ANTENNA REQUIREMENT..... 74
13. TEST SETUP PHOTO..... 75
14. EUT CONSTRUCTIONAL DETAILS..... 75

1. VERSION

Report No.	Version	Description	Approved
ZKT-2106242855E	Rev.01	Initial issue of report	Jun. 28, 2021

2. TEST SUMMARY

Test procedures according to the technical standards:

FCC Part15 (15.247) , Subpart C RSS-247 Issue 2: February 2017			
Standard Section	Test Item	Result	Remark
15.203/15.247 (c) RSS-Gen 6.8	Antenna Requirement	PASS	
15.207	AC Power Line Conducted Emission	PASS	
15.247 (b)(1) RSS-247.5.4(b)	Conducted Peak Output Power	PASS	
15.247 (a)(1) RSS-247.5.1(a) RSS-Gen.6.7	20dB Occupied Bandwidth 99% OCB	PASS	
15.247 (a)(1) RSS-247.5.1(b)	Carrier Frequencies Separation	PASS	
15.247 (a)(1)(iii) RSS-247.5.1(d)	Hopping Channel Number	PASS	
15.247 (a)(1)(iii) RSS-247.5.1(d)	Dwell Time	PASS	
15.205/15.209 RSS-Gen.6.13	Radiated Emission	PASS	
15.247(d) RSS-247 5.5	Band Edge	PASS	

NOTE:

(1)" N/A" denotes test is not applicable in this Test Report

2.1 TEST FACILITY

Shenzhen ZKT Technology Co., Ltd.
Add. : 1/F, No. 101, Building B, No. 6, Tangwei Community Industrial Avenue, Fuhai Street, Bao'an District, Shenzhen, China

FCC Test Firm Registration Number: 692225
Designation Number: CN1299
IC Registered No.: 27033
Designation Number: CN0110

2.2 MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ± U,where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2,providing a level of confidence of approximately 95 %。

No.	Item	Uncertainty
1	Conducted Emission Test	±1.38dB
2	RF power conducted	±0.16dB
3	Spurious emissions conducted	±0.21dB
4	All emissions radiated(<1G)	±4.68dB
5	All emissions radiated(>1G)	±4.89dB
6	Temperature	±0.5°C
7	Humidity	±2%

3. GENERAL INFORMATION

3.1 GENERAL DESCRIPTION OF EUT

Product Name:	Wireless Headphones
Model No.:	K21 MS-K10,MS-K11,MS-K13,MS-K14,MS-K16,MS-K17,MS-K19,MS-K20,MS-K21,MS-K22,AKZ-K23,AKZ-K24,AKZ-K25,AKZ-K26,AKZ-K27,AKZ-K28,AKZ-K29,AKZ-K30,GM-C1,GM-C3,GM-C4,AKZ-MAX10,AKZ-MAX11, AKZ-T55,MS-771,MS-881,MS-991
Model Different.:	Only for different model name.
Serial No.:	N/A
Hardware Version:	H1.0
Software Version:	S1.0
Sample(s) Status:	Engineer sample
Channel numbers:	79
Channel separation:	2402MHz~2480MHz
Modulation technology:	GFSK, π/4-DQPSK, 8-DPSK
Antenna Type:	PCB Antenna
Antenna gain:	0dBi
Power supply:	Input: DC 5V or DC 3.7V Battery

Operation Frequency each of channel							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2402MHz	21	2422MHz	41	2442MHz	61	2462MHz
2	2403MHz	22	2423MHz	42	2443MHz	62	2463MHz
3	2404MHz	23	2424MHz	43	2444MHz	63	2464MHz
4	2405MHz	24	2425MHz	44	2445MHz	64	2465MHz
5	2406MHz	25	2426MHz	45	2446MHz	65	2466MHz
6	2407MHz	26	2427MHz	46	2447MHz	66	2467MHz
7	2408MHz	27	2428MHz	47	2448MHz	67	2468MHz
8	2409MHz	28	2429MHz	48	2449MHz	68	2469MHz
9	2410MHz	29	2430MHz	49	2450MHz	69	2470MHz
10	2411MHz	30	2431MHz	50	2451MHz	70	2471MHz
11	2412MHz	31	2432MHz	51	2452MHz	71	2472MHz
12	2413MHz	32	2433MHz	52	2453MHz	72	2473MHz
13	2414MHz	33	2434MHz	53	2454MHz	73	2474MHz
14	2415MHz	34	2435MHz	54	2455MHz	74	2475MHz
15	2416MHz	35	2436MHz	55	2456MHz	75	2476MHz
16	2417MHz	36	2437MHz	56	2457MHz	76	2477MHz
17	2418MHz	37	2438MHz	57	2458MHz	77	2478MHz

18	2419MHz	38	2439MHz	58	2459MHz	78	2479MHz
19	2420MHz	39	2440MHz	59	2460MHz	79	2480MHz
20	2421MHz	40	2441MHz	60	2461MHz		

Note:
In section 15.31(m), regards to the operating frequency range over 10 MHz, the Lowest frequency, the middle frequency, and the highest frequency of channel were selected to perform the test, and the selected channel see below:

Test channel	Frequency
The lowest channel	2402MHz
The middle channel	2441MHz
The Highest channel	2480MHz

3.2 Test Setup Configuration

Conducted Emission

AC Line — EUT

Radiated Emission

EUT

Conducted Spurious

EUT

3.3 Support Equipment

The EUT has been tested as an independent unit together with other necessary accessories or support units. The following support units or accessories were used to form a representative test configuration during the tests.

Item	Equipment	Mfr/Brand	Model/Type No.	Series No.	Note
E-1	Wireless Headphones	N/A	K21	N/A	EUT

Item	Shielded Type	Ferrite Core	Length	Note

Note:
(1) The support equipment was authorized by Declaration of Confirmation.
(2) For detachable type I/O cable should be specified the length in cm in『Length』column.

3.4 Test Mode

Transmitting mode	Keep the EUT in continuously transmitting mode.
Remark: During the test, the test voltage was tuned from 85% to 115% of the nominal rated supply voltage, and found that the worst case was under the nominal rated supply condition. So the report just shows that condition's data.	

Test Software	Realtek Test Tool
Power level setup	<7dBm

3.5 EQUIPMENTS LIST FOR ALL TEST ITEMS

Radiation Test equipment

Item	Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	Spectrum Analyzer (9kHz-26.5GHz)	KEYSIGHT	9020A	MY45109572	Sep. 22, 2020	Sep. 21, 2021
2	Spectrum Analyzer (1GHz-40GHz)	Agilent	E4446A	100363	Sep. 22, 2020	Sep. 21, 2021
3	Test Receiver (9kHz-7GHz)	R&S	ESCI7	101169	Sep. 22, 2020	Sep. 21, 2021
4	Bilog Antenna (30MHz-1400MHz)	Schwarzbeck	VULB9168	00877	Sep. 22, 2020	Sep. 21, 2021
5	Horn Antenna (1GHz-18GHz)	SCHWARZBEC K	BBHA9120D	1541	Sep. 22, 2020	Sep. 21, 2021
6	Horn Antenna (18GHz-40GHz)	A.H. System	SAS-574	588	Sep. 22, 2020	Sep. 21, 2021
7	Amplifier (30-1000MHz)	EM Electronics	EM330 Amplifier	N/A	Sep. 22, 2020	Sep. 21, 2021
8	Amplifier (1GHz-40GHz)	全聚达	DLE-161	097	Sep. 22, 2020	Sep. 21, 2021
9	Loop Antenna (9KHz-30MHz)	SCHWARZBEC K	FMZB1519B	014	Sep. 22, 2020	Sep. 21, 2021
10	RF cables1 (9kHz-30MHz)	N/A	9kHz-30MHz	N/A	Sep. 22, 2020	Sep. 21, 2021
11	RF cables2 (30MHz-1GHz)	N/A	30MHz-1GHz	N/A	Sep. 22, 2020	Sep. 21, 2021
12	RF cables3 (1GHz-40GHz)	N/A	1GHz-40GHz	N/A	Sep. 22, 2020	Sep. 21, 2021
13	CMW500 Test	R&S	CMW500	106504	Sep. 22, 2020	Sep. 21, 2021
14	ESG Signal Generator	Agilent	E4421B	GB40051203	Sep. 22, 2020	Sep. 21, 2021
15	Signal Generator	Agilent	N5182A	MY47420215	Sep. 22, 2020	Sep. 21, 2021
16	D.C. Power Supply	LongWei	TPR-6405D	\	\	\
17	Software	Frad	EZ-EMC	FA-03A2 RE	\	\

Conduction Test equipment

Item	Kind of Equipment	Manufacturer	Type No.	Serial No.	Last calibration	Calibrated until
1	LISN	R&S	ENV216	101471	Sep. 22, 2020	Sep. 21, 2021
2	LISN	CYBERTEK	EM5040A	E1850400149	Sep. 22, 2020	Sep. 21, 2021
3	Test Cable	N/A	C01	N/A	Sep. 22, 2020	Sep. 21, 2021
4	Test Cable	N/A	C02	N/A	Sep. 22, 2020	Sep. 21, 2021
5	EMI Test Receiver	R&S	ESRP3	101946	Sep. 22, 2020	Sep. 21, 2021
6	Absorbing Clamp	DZ	ZN23201	N/A	Sep. 22, 2020	Sep. 21, 2021

4. EMC EMISSION TEST

4.1 Conducted emissions

Test Requirement:	FCC Part15 C Section 15.207
Test Method:	ANSI C63.10:2013
Test Frequency Range:	150KHz to 30MHz
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto

4.1.1 POWER LINE CONDUCTED EMISSION Limits

FREQUENCY (MHz)	Limit (dBuV)		Standard
	Quasi-peak	Average	
0.15 -0.5	66 - 56 *	56 - 46 *	FCC
0.50 -5.0	56.00	46.00	FCC
5.0 -30.0	60.00	50.00	FCC

Note:

(1) *Decreases with the logarithm of the frequency.

4.1.2 TEST PROCEDURE

a. The EUT was placed 0.1 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
b. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
d. LISN at least 80 cm from nearest part of EUT chassis.
e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

4.1.3 DEVIATION FROM TEST STANDARD

No deviation

4.1.4 TEST SETUP



4.1.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

We pretest AC 120V and AC 230V, the worst voltage was AC 120V and the data recording in the report.

4.1.6 Test Result

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	L
Test Voltage :	DC 3.7V Battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1995	42.97	11.93	54.90	63.63	-8.73	QP	P	
2	0.1997	28.08	11.93	40.01	53.62	-13.61	AVG	P	
3	0.2895	34.66	11.51	46.17	60.54	-14.37	QP	P	
4	0.2895	14.44	11.51	25.95	50.54	-24.59	AVG	P	
5	0.5055	31.40	10.54	41.94	56.00	-14.06	QP	P	
6	0.5144	18.78	10.54	29.32	46.00	-16.68	AVG	P	
7	0.7710	13.98	10.49	24.47	46.00	-21.53	AVG	P	
8	0.7980	29.03	10.48	39.51	56.00	-16.49	QP	P	
9	2.7825	30.69	9.99	40.68	56.00	-15.32	QP	P	
10	2.7825	11.88	9.99	21.87	46.00	-24.13	AVG	P	
11	15.9135	26.57	9.29	35.86	50.00	-14.14	AVG	P	
12	15.9855	42.26	9.30	51.56	60.00	-8.44	QP	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Phase :	N
Test Voltage :	DC 3.7V Battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector	P/F	Remark
1	0.1905	42.36	12.13	54.49	64.01	-9.52	QP	P	
2	0.1995	24.77	11.93	36.70	53.63	-16.93	AVG	P	
3	0.2940	33.64	11.49	45.13	60.41	-15.28	QP	P	
4	0.2940	16.52	11.49	28.01	50.41	-22.40	AVG	P	
5	0.5144	31.93	10.54	42.47	56.00	-13.53	QP	P	
6	0.5144	19.35	10.54	29.89	46.00	-16.11	AVG	P	
7	2.5755	31.29	10.05	41.34	56.00	-14.66	QP	P	
8	2.5755	10.84	10.05	20.89	46.00	-25.11	AVG	P	
9	11.8905	31.27	8.72	39.99	60.00	-20.01	QP	P	
10	11.8905	17.56	8.72	26.28	50.00	-23.72	AVG	P	
11	15.5445	42.74	9.24	51.98	60.00	-8.02	QP	P	
12	15.9225	27.16	9.29	36.45	50.00	-13.55	AVG	P	

Notes:
1.An initial pre-scan was performed on the line and neutral lines with peak detector.
2.Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3.Mesurement Level = Reading level + Correct Factor

4.2 Radiated emissions

Test Requirement:	FCC Part15 C Section 15.209
Test Method:	ANSI C63.10:2013
Test Frequency Range:	9kHz to 25GHz
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
9KHz-150KHz	Quasi-peak	200Hz	600Hz	Quasi-peak
150KHz-30MHz	Quasi-peak	9KHz	30KHz	Quasi-peak
30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak
Above 1GHz	Peak	1MHz	3MHz	Peak
	Peak	1MHz	10Hz	Average

4.2.1 Radiated Emission Limits

Frequencies (MHz)	Field Strength (micorvolts/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

LIMITS OF RADIATED EMISSION MEASUREMENT

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

4.2.2 TEST PROCEDURE

Below 1GHz test procedure as below:

a. The EUT was placed on the top of a rotating table 0.1 meters above the ground at a 3 meter semi-anechoic camber. The table was rotated 360 degrees to determine the position of the highest radiation.

b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.

c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.

d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:

g. Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
h. Test the EUT in the lowest channel ,the middle channel ,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

4.2.3 DEVIATION FROM TEST STANDARD

No deviation

4.2.4 TEST SETUP

（A）Radiated Emission Test-Up Frequency Below 30MHz



（B）Radiated Emission Test-Up Frequency 30MHz~1GHz



（C）Radiated Emission Test-Up Frequency Above 1GHz



4.2.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.4 Unless otherwise a special operating condition is specified in the follows during the testing.

4.2.6 TEST RESULTS

Between 9KHz – 30MHz

The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o) & RSS-Gen 6.13, the test result no need to reported.

Between 30MHz – 1GHz

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101 kPa	Polarization:	Horizontal
Test Voltage:	DC 3.7V Battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	102.3597	51.26	-21.27	29.99	43.50	-13.51	QP
2	195.8220	55.12	-21.49	33.63	43.50	-9.87	QP
3	391.4082	59.12	-17.32	41.80	46.00	-4.20	QP
4	487.3151	56.47	-14.02	42.45	46.00	-3.55	QP
5	782.3453	48.69	-6.29	42.40	46.00	-3.60	QP
6	982.6200	48.65	-2.31	46.34	54.00	-7.66	QP

Temperature:	26℃	Relative Humidity:	54%
Pressure:	101kPa	Polarization:	Vertical
Test Voltage:	DC 3.7V Battery		



No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	97.1148	40.91	-19.93	20.98	43.50	-22.52	QP
2	131.9889	41.14	-17.91	23.23	43.50	-20.27	QP
3	199.2855	55.08	-19.75	35.33	43.50	-8.17	QP
4	293.0842	61.22	-18.00	43.22	46.00	-2.78	QP
5	487.3151	55.16	-14.26	40.90	46.00	-5.10	QP
6	876.7829	51.75	-8.98	42.77	46.00	-3.23	QP

Remarks:
1.Final Level =Receiver Read level + Antenna Factor + Cable Loss
2.The emission levels of other frequencies are very lower than the limit and not show in test report.
3.The test data shows only the worst case GFSK mode

1GHz~25GHz

GFSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	53.26	30.55	5.77	24.66	53.14	74.00	-20.86	Pk
V	4804.00	44.69	30.55	5.77	24.66	44.57	54.00	-9.43	AV
V	7206.00	53.68	30.33	6.32	24.55	54.22	74.00	-19.78	Pk
V	7206.00	44.23	30.33	6.32	24.55	44.77	54.00	-9.23	AV
V	9608.00	52.36	30.85	7.45	24.69	53.65	74.00	-20.35	Pk
V	9608.00	43.12	30.85	7.45	24.69	44.41	54.00	-9.59	AV
V	12010.00	53.69	31.02	8.99	25.57	57.23	74.00	-16.77	Pk
V	12010.00	44.25	31.02	8.99	25.57	47.79	54.00	-6.21	AV
H	4804.00	54.36	30.55	5.77	24.66	54.24	74.00	-19.76	Pk
H	4804.00	43.59	30.55	5.77	24.66	43.47	54.00	-10.53	AV
H	7206.00	52.33	30.33	6.32	24.55	52.87	74.00	-21.13	Pk
H	7206.00	42.68	30.33	6.32	24.55	43.22	54.00	-10.78	AV
H	9608.00	53.27	30.85	7.45	24.69	54.56	74.00	-19.44	Pk
H	9608.00	43.58	30.85	7.45	24.69	44.87	54.00	-9.13	AV
H	12010.00	51.27	31.02	8.99	25.57	54.81	74.00	-19.19	Pk
H	12010.00	42.55	31.02	8.99	25.57	46.09	54.00	-7.91	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	53.66	30.55	5.77	24.66	53.54	74.00	-20.46	Pk
V	4882.00	44.58	30.55	5.77	24.66	44.46	54.00	-9.54	AV
V	7323.00	52.29	30.33	6.32	24.55	52.83	74.00	-21.17	Pk
V	7323.00	43.85	30.33	6.32	24.55	44.39	54.00	-9.61	AV
V	9764.00	53.16	30.85	7.45	24.69	54.45	74.00	-19.55	Pk
V	9764.00	44.65	30.85	7.45	24.69	45.94	54.00	-8.06	AV
V	12205.00	52.11	31.02	8.99	25.57	55.65	74.00	-18.35	Pk
V	12205.00	42.36	31.02	8.99	25.57	45.9	54.00	-8.1	AV
H	4882.00	53.16	30.55	5.77	24.66	53.04	74.00	-20.96	Pk
H	4882.00	43.28	30.55	5.77	24.66	43.16	54.00	-10.84	AV
H	7323.00	51.64	30.33	6.32	24.55	52.18	74.00	-21.82	Pk
H	7323.00	43.25	30.33	6.32	24.55	43.79	54.00	-10.21	AV
H	9764.00	53.26	30.85	7.45	24.69	54.55	74.00	-19.45	Pk
H	9764.00	42.69	30.85	7.45	24.69	43.98	54.00	-10.02	AV
H	12205.00	52.68	31.02	8.99	25.57	56.22	74.00	-17.78	Pk
H	12205.00	42.69	31.02	8.99	25.57	46.23	54.00	-7.77	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	53.65	30.55	5.77	24.66	53.53	74.00	-20.47	Pk
V	4960.00	43.62	30.55	5.77	24.66	43.5	54.00	-10.5	AV
V	7440.00	53.22	30.33	6.32	24.55	53.76	74.00	-20.24	Pk
V	7440.00	42.17	30.33	6.32	24.55	42.71	54.00	-11.29	AV
V	9920.00	52.67	30.85	7.45	24.69	53.96	74.00	-20.04	Pk
V	9920.00	42.11	30.85	7.45	24.69	43.4	54.00	-10.6	AV
V	12400.00	52.63	31.02	8.99	25.57	56.17	74.00	-17.83	Pk
V	12400.00	43.58	31.02	8.99	25.57	47.12	54.00	-6.88	AV
H	4960.00	52.22	30.55	5.77	24.66	52.1	74.00	-21.9	Pk
H	4960.00	45.62	30.55	5.77	24.66	45.5	54.00	-8.5	AV
H	7440.00	52.69	30.33	6.32	24.55	53.23	74.00	-20.77	Pk
H	7440.00	43.74	30.33	6.32	24.55	44.28	54.00	-9.72	AV
H	9920.00	51.29	30.85	7.45	24.69	52.58	74.00	-21.42	Pk
H	9920.00	42.65	30.85	7.45	24.69	43.94	54.00	-10.06	AV
H	12400.00	53.28	31.02	8.99	25.57	56.82	74.00	-17.18	Pk
H	12400.00	43.29	31.02	8.99	25.57	46.83	54.00	-7.17	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

π/4-DQPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	51.22	30.55	5.77	24.66	51.10	74.00	-22.90	Pk
V	4804.00	42.39	30.55	5.77	24.66	42.27	54.00	-11.73	AV
V	7206.00	49.98	30.33	6.32	24.55	50.52	74.00	-23.48	Pk
V	7206.00	41.25	30.33	6.32	24.55	41.79	54.00	-12.21	AV
V	9608.00	50.24	30.85	7.45	24.69	51.53	74.00	-22.47	Pk
V	9608.00	42.08	30.85	7.45	24.69	43.37	54.00	-10.63	AV
V	12010.00	51.22	31.02	8.99	25.57	54.76	74.00	-19.24	Pk
V	12010.00	41.98	31.02	8.99	25.57	45.52	54.00	-8.48	AV
H	4804.00	52.15	30.55	5.77	24.66	52.03	74.00	-21.97	Pk
H	4804.00	42.69	30.55	5.77	24.66	42.57	54.00	-11.43	AV
H	7206.00	50.49	30.33	6.32	24.55	51.03	74.00	-22.97	Pk
H	7206.00	41.75	30.33	6.32	24.55	42.29	54.00	-11.71	AV
H	9608.00	50.49	30.85	7.45	24.69	51.78	74.00	-22.22	Pk
H	9608.00	41.75	30.85	7.45	24.69	43.04	54.00	-10.96	AV
H	12010.00	50.49	31.02	8.99	25.57	54.03	74.00	-19.97	Pk
H	12010.00	41.69	31.02	8.99	25.57	45.23	54.00	-8.77	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	51.21	30.55	5.77	24.66	51.09	74.00	-22.91	Pk
V	4882.00	42.32	30.55	5.77	24.66	42.20	54.00	-11.80	AV
V	7323.00	49.04	30.33	6.32	24.55	49.58	74.00	-24.42	Pk
V	7323.00	41.08	30.33	6.32	24.55	41.62	54.00	-12.38	AV
V	9764.00	49.65	30.85	7.45	24.69	50.94	74.00	-23.06	Pk
V	9764.00	41.08	30.85	7.45	24.69	42.37	54.00	-11.63	AV
V	12205.00	50.12	31.02	8.99	25.57	53.66	74.00	-20.34	Pk
V	12205.00	41.08	31.02	8.99	25.57	44.62	54.00	-9.38	AV
H	4882.00	51.87	30.55	5.77	24.66	51.75	74.00	-22.25	Pk
H	4882.00	42.11	30.55	5.77	24.66	41.99	54.00	-12.01	AV
H	7323.00	52.58	30.33	6.32	24.55	53.12	74.00	-20.88	Pk
H	7323.00	42.69	30.33	6.32	24.55	43.23	54.00	-10.77	AV
H	9764.00	52.58	30.85	7.45	24.69	53.87	74.00	-20.13	Pk
H	9764.00	42.65	30.85	7.45	24.69	43.94	54.00	-10.06	AV
H	12205.00	53.08	31.02	8.99	25.57	56.62	74.00	-17.38	Pk
H	12205.00	43.62	31.02	8.99	25.57	47.16	54.00	-6.84	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	51.23	30.55	5.77	24.66	51.11	74.00	-22.89	Pk
V	4960.00	41.68	30.55	5.77	24.66	41.56	54.00	-12.44	AV
V	7440.00	52.74	30.33	6.32	24.55	53.28	74.00	-20.72	Pk
V	7440.00	42.65	30.33	6.32	24.55	43.19	54.00	-10.81	AV
V	9920.00	52.74	30.85	7.45	24.69	54.03	74.00	-19.97	Pk
V	9920.00	43.11	30.85	7.45	24.69	44.40	54.00	-9.60	AV

V	12400.00	53.14	31.02	8.99	25.57	56.68	74.00	-17.32	Pk
V	12400.00	43.65	31.02	8.99	25.57	47.19	54.00	-6.81	AV
H	4960.00	50.32	30.55	5.77	24.66	50.20	74.00	-23.80	Pk
H	4960.00	41.28	30.55	5.77	24.66	41.16	54.00	-12.84	AV
H	7440.00	51.32	30.33	6.32	24.55	51.86	74.00	-22.14	Pk
H	7440.00	42.58	30.33	6.32	24.55	43.12	54.00	-10.88	AV
H	9920.00	52.51	30.85	7.45	24.69	53.80	74.00	-20.20	Pk
H	9920.00	43.62	30.85	7.45	24.69	44.91	54.00	-9.09	AV
H	12400.00	52.14	31.02	8.99	25.57	55.68	74.00	-18.32	Pk
H	12400.00	42.65	31.02	8.99	25.57	46.19	54.00	-7.81	AV

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

8-DPSK

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Low Channel:2402MHz									
V	4804.00	51.36	30.55	5.77	24.66	51.24	74.00	-22.76	Pk
V	4804.00	41.55	30.55	5.77	24.66	41.43	54.00	-12.57	AV
V	7206.00	49.65	30.33	6.32	24.55	50.19	74.00	-23.81	Pk
V	7206.00	42.02	30.33	6.32	24.55	42.56	54.00	-11.44	AV
V	9608.00	50.13	30.85	7.45	24.69	51.42	74.00	-22.58	Pk
V	9608.00	41.62	30.85	7.45	24.69	42.91	54.00	-11.09	AV
V	12010.00	50.11	31.02	8.99	25.57	53.65	74.00	-20.35	Pk
V	12010.00	41.35	31.02	8.99	25.57	44.89	54.00	-9.11	AV
H	4804.00	51.65	30.55	5.77	24.66	51.53	74.00	-22.47	Pk
H	4804.00	42.18	30.55	5.77	24.66	42.06	54.00	-11.94	AV
H	7206.00	51.03	30.33	6.32	24.55	51.57	74.00	-22.43	Pk
H	7206.00	41.71	30.33	6.32	24.55	42.25	54.00	-11.75	AV
H	9608.00	50.42	30.85	7.45	24.69	51.71	74.00	-22.29	Pk
H	9608.00	41.25	30.85	7.45	24.69	42.54	54.00	-11.46	AV
H	12010.00	51.33	31.02	8.99	25.57	54.87	74.00	-19.13	Pk
H	12010.00	42.16	31.02	8.99	25.57	45.70	54.00	-8.30	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
Middle Channel:2441MHz									
V	4882.00	50.31	30.55	5.77	24.66	50.19	74.00	-23.81	Pk
V	4882.00	41.20	30.55	5.77	24.66	41.08	54.00	-12.92	AV
V	7323.00	49.01	30.33	6.32	24.55	49.55	74.00	-24.45	Pk
V	7323.00	41.03	30.33	6.32	24.55	41.57	54.00	-12.43	AV
V	9764.00	49.09	30.85	7.45	24.69	50.38	74.00	-23.62	Pk
V	9764.00	41.05	30.85	7.45	24.69	42.34	54.00	-11.66	AV
V	12205.00	49.07	31.02	8.99	25.57	52.61	74.00	-21.39	Pk
V	12205.00	41.06	31.02	8.99	25.57	44.6	54.00	-9.4	AV
H	4882.00	51.57	30.55	5.77	24.66	51.45	74.00	-22.55	Pk
H	4882.00	41.33	30.55	5.77	24.66	41.21	54.00	-12.79	AV
H	7323.00	52.28	30.33	6.32	24.55	52.82	74.00	-21.18	Pk
H	7323.00	41.11	30.33	6.32	24.55	41.65	54.00	-12.35	AV
H	9764.00	52.48	30.85	7.45	24.69	53.77	74.00	-20.23	Pk
H	9764.00	41.11	30.85	7.45	24.69	42.4	54.00	-11.6	AV
H	12205.00	53.03	31.02	8.99	25.57	56.57	74.00	-17.43	Pk
H	12205.00	41.11	31.02	8.99	25.57	44.65	54.00	-9.35	AV

Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Detector Type
High Channel:2480MHz									
V	4960.00	51.22	30.55	5.77	24.66	51.10	74.00	-23.92	Pk
V	4960.00	41.68	30.55	5.77	24.66	41.56	54.00	-12.42	AV
V	7440.00	51.65	30.33	6.32	24.55	52.19	74.00	-20.92	Pk
V	7440.00	42.04	30.33	6.32	24.55	42.58	54.00	-11.42	AV
V	9920.00	52.95	30.85	7.45	24.69	54.24	74.00	-19.57	Pk
V	9920.00	43.11	30.85	7.45	24.69	44.40	54.00	-9.63	AV
V	12400.00	53.14	31.02	8.99	25.57	56.68	74.00	-17.32	Pk

V	12400.00	42.75	31.02	8.99	25.57	46.29	54.00	-8.78	AV
H	4960.00	50.22	30.55	5.77	24.66	50.10	74.00	-23.90	Pk
H	4960.00	41.89	30.55	5.77	24.66	41.77	54.00	-12.23	AV
H	7440.00	52.11	30.33	6.32	24.55	52.65	74.00	-21.35	Pk
H	7440.00	42.31	30.33	6.32	24.55	42.85	54.00	-11.25	AV
H	9920.00	51.27	30.85	7.45	24.69	52.56	74.00	-20.30	Pk
H	9920.00	42.32	30.85	7.45	24.69	43.61	54.00	-10.46	AV
H	12400.00	52.31	31.02	8.99	25.57	55.85	74.00	-18.15	Pk
H	12400.00	43.21	31.02	8.99	25.57	46.75	54.00	-8.21	AV

Remark:

1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier,
   Margin= Emission Level - Limit
2. If peak below the average limit, the average emission was no test.
3. The amplitude of spurious emissions which are attenuated by more than 20dB below the permissible value has no need to be reported.

5. RADIATED BAND EMISSION MEASUREMENT

5.1 Test Requirement:

Test Requirement:	FCC Part15 C Section 15.209 and 15.205
Test Method:	ANSI C63.10: 2013
Test Frequency Range:	All of the restrict bands were tested, only the worst band's (2310MHz to 2500MHz) data was showed.
Test site:	Measurement Distance: 3m
Receiver setup:	

Frequency	Detector	RBW	VBW	Value
Above 1GHz	Peak	1MHz	3MHz	Peak
	Average	1MHz	3MHz	Average

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

FREQUENCY (MHz)	Limit (dBuV/m) (at 3M)	
	PEAK	AVERAGE
Above 1000	74	54

Notes:

(1) The limit for radiated test was performed according to FCC PART 15C.

(2) The tighter limit applies at the band edges.

(3) Emission level (dBuV/m)=20log Emission level (uV/m).

Spectrum Parameter	Setting
Attenuation	Auto
Start Frequency	2300MHz
Stop Frequency	2520
RB / VB (emission in restricted band)	1 MHz / 1 MHz for Peak, 1 MHz / 10Hz for Average

5.2 TEST PROCEDURE

Above 1GHz test procedure as below:

a. 1. The EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
c. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading.
e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
f. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
g. Test the EUT in the lowest channel,the Highest channel

Note:

Both horizontal and vertical antenna polarities were tested
and performed pretest to three orthogonal axis. The worst case emissions were reported

5.3 DEVIATION FROM TEST STANDARD

No deviation

5.4 TEST SETUP

Radiated Emission Test-Up Frequency Above 1GHz



5.5 EUT OPERATING CONDITIONS

The EUT tested system was configured as the statements of 2.3 Unless otherwise a special operating condition is specified in the follows during the testing.

5.6 TEST RESULT

	Polar (H/V)	Frequency (MHz)	Meter Reading (dBuV)	Pre-amplifier (dB)	Cable Loss (dB)	Antenna Factor (dB/m)	Emission level (dBuV/m)	Limit (dBuV/m)	Detector Type	Result
GFSK	Low Channel: 2402MHz									
	H	2390.00	59.33	30.22	4.85	23.98	57.94	74.00	PK	PASS
	H	2390.00	51.23	30.22	4.85	23.98	49.84	54.00	AV	PASS
	H	2400.00	60.32	30.22	4.85	23.98	58.93	74.00	PK	PASS
	H	2400.00	51.36	30.22	4.85	23.98	49.97	54.00	AV	PASS
	V	2390.00	59.87	30.22	4.85	23.98	58.48	74.00	PK	PASS
	V	2390.00	51.26	30.22	4.85	23.98	49.87	54.00	AV	PASS
	V	2400.00	60.32	30.22	4.85	23.98	58.93	74.00	PK	PASS
	V	2400.00	51.37	30.22	4.85	23.98	49.98	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	59.32	30.22	4.85	23.98	57.93	74.00	PK	PASS
	H	2485.50	50.95	30.22	4.85	23.98	49.56	54.00	AV	PASS
	H	2483.50	60.37	30.22	4.85	23.98	58.98	74.00	PK	PASS
	H	2485.50	52.12	30.22	4.85	23.98	50.73	54.00	AV	PASS
	V	2483.50	61.27	30.22	4.85	23.98	59.88	74.00	PK	PASS
	V	2485.50	51.85	30.22	4.85	23.98	50.46	54.00	AV	PASS
	V	2483.50	60.22	30.22	4.85	23.98	58.83	74.00	PK	PASS
	V	2485.50	52.17	30.22	4.85	23.98	50.78	54.00	AV	PASS
π/4-DQPSK	Low Channel: 2402MHz									
	H	2390.00	59.21	30.22	4.85	23.98	57.82	74.00	PK	PASS
	H	2390.00	51.27	30.22	4.85	23.98	49.88	54.00	AV	PASS
	H	2400.00	60.28	30.22	4.85	23.98	58.89	74.00	PK	PASS
	H	2400.00	51.22	30.22	4.85	23.98	49.83	54.00	AV	PASS
	V	2390.00	59.63	30.22	4.85	23.98	58.24	74.00	PK	PASS
	V	2390.00	51.13	30.22	4.85	23.98	49.74	54.00	AV	PASS
	V	2400.00	60.32	30.22	4.85	23.98	58.93	74.00	PK	PASS
	V	2400.00	51.24	30.22	4.85	23.98	49.85	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	59.63	30.22	4.85	23.98	58.24	74.00	PK	PASS
	H	2485.50	52.16	30.22	4.85	23.98	50.77	54.00	AV	PASS
	H	2483.50	60.15	30.22	4.85	23.98	58.76	74.00	PK	PASS
	H	2485.50	50.21	30.22	4.85	23.98	48.82	54.00	AV	PASS
	V	2483.50	59.23	30.22	4.85	23.98	57.84	74.00	PK	PASS
	V	2485.50	51.16	30.22	4.85	23.98	49.77	54.00	AV	PASS
	V	2483.50	60.12	30.22	4.85	23.98	58.73	74.00	PK	PASS
	V	2485.50	51.33	30.22	4.85	23.98	49.94	54.00	AV	PASS
8-DPSK	Low Channel: 2402MHz									
	H	2390.00	59.36	30.22	4.85	23.98	57.97	74.00	PK	PASS
	H	2390.00	50.12	30.22	4.85	23.98	48.73	54.00	AV	PASS
	H	2400.00	60.35	30.22	4.85	23.98	58.96	74.00	PK	PASS
	H	2400.00	51.24	30.22	4.85	23.98	49.85	54.00	AV	PASS
	V	2390.00	60.22	30.22	4.85	23.98	58.83	74.00	PK	PASS
	V	2390.00	50.16	30.22	4.85	23.98	48.77	54.00	AV	PASS
	V	2400.00	61.23	30.22	4.85	23.98	59.84	74.00	PK	PASS
	V	2400.00	52.17	30.22	4.85	23.98	50.78	54.00	AV	PASS
	High Channel: 2480MHz									
	H	2483.50	61.25	30.22	4.85	23.98	59.86	74.00	PK	PASS
	H	2485.50	52.16	30.22	4.85	23.98	50.77	54.00	AV	PASS
	H	2483.50	61.03	30.22	4.85	23.98	59.64	74.00	PK	PASS
	H	2485.50	51.85	30.22	4.85	23.98	50.46	54.00	AV	PASS
	V	2483.50	61.43	30.22	4.85	23.98	60.04	74.00	PK	PASS
	V	2485.50	52.12	30.22	4.85	23.98	50.73	54.00	AV	PASS

	V	2483.50	61.35	30.22	4.85	23.98	59.96	74.00	PK	PASS
	V	2485.50	52.17	30.22	4.85	23.98	50.78	54.00	AV	PASS

Remark:
1. Emission Level = Meter Reading + Antenna Factor + Cable Loss – Pre-amplifier, Margin= Emission Level - Limit

6. CONDUCTED BAND EDGE AND SPURIOUS EMISSION

Test Requirement:	FCC Part15 C Section 15.247 (d)
Test Method:	KDB558074 D0115.247 Meas Guidancev05r02

6.1 Limit

Regulation 15.247 (d),In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

6.2 Test Setup

6.3 Test procedure

Using the following spectrum analyzer setting:
A) Set the RBW = 100KHz.
B) Set the VBW = 300KHz.
C) Sweep time = auto couple.
D) Detector function = peak.
E) Trace mode = max hold.
F) Allow trace to fully stabilize.

6.4 DEVIATION FROM STANDARD

No deviation.

6.5 Test Result

GFSK mode:

Test channel:	Lowest channel



30MHz~26.5GHz

Test channel:	Middle channel



30MHz~26.5GHz

Test channel:	Highest channel



30MHz~26.5GHz

π/4-DQPSK mode:

Test channel:	Lowest channel



30MHz~26.5GHz

Test channel:	Middle channel



30MHz~26.5GHz

Test channel:	Highest channel



30MHz~26.5GHz

8-DPSK mode:

Test channel:	Lowest channel



30MHz~26.5GHz

Test channel:	Middle channel



30MHz~26.5GHz

Test channel:	Highest channel



30MHz~26.5GHz

GFSK No-hopping Band edge-left side



GFSK Hopping Band edge-left side



GFSK No-hopping Band edge-right side



GFSK Hopping Band edge-right side



π/4-DQPSK No-hopping Band edge-left side



π/4-DQPSK Hopping Band edge-left side



π/4-DQPSK No-hopping Band edge-right side



π/4-DQPSK Hopping Band edge-right side



8-DPSK No-hopping Band edge-left side



8-DPSK Hopping Band edge-left side



8-DPSK No-hopping Band edge-right side



8-DPSK Hopping Band edge-right side



7. 20DB&99% BANDWIDTH

Test Requirement:	FCC Part15 C Section 15.247 (a)(1)
Test Method:	ANSI C63.10:2013

7.1 Test Setup



7.2 Limit

N/A

7.3 Test procedure

1. Set RBW = 30 kHz.
2. Set the video bandwidth (VBW) ≥ 3 x RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

7.4 DEVIATION FROM STANDARD

No deviation.

7.5 Test Result

Mode	Test channel	20dB Emission Bandwidth (MHz)	99%Bandwidth (MHz)	Result
GFSK	Lowest	0.869	0.838	Pass
	Middle	0.954	0.850	
	Highest	0.828	0.833	
π/4-DQPSK	Lowest	1.429	1.339	Pass
	Middle	1.376	1.329	
	Highest	1.424	1.343	
8-DPSK	Lowest	1.476	1.358	Pass
	Middle	1.450	1.342	
	Highest	1.421	1.335	

Test plots

GFSK Low Channel

GFSK Middle Channel

GFSK High Channel

π/4-DQPSK Low Channel



π/4-DQPSK Middle Channel



π/4-DQPSK High Channel



8-DPSK Low Channel