

# TEST REPORT

Applicant Name : Zultys, Inc.  
Address : 785 Lucerne Drive, Sunnyvale, California, 94085, United States  
Report Number : SZ1210916-48531E-RF-00D  
FCC ID: 2APWA-ZIP47GE  
IC 4478A-ZIP47GE

## Test Standard (s)

FCC PART 15.407; RSS-247, ISSUE 2, FEBRUARY 2017 Dynamic Frequency Selection

## Sample Description

Product Type: Gigabit SIP IP Phone  
Model No.: ZIP 47GE  
Multiple Model(s) No.: N/A  
Trade Mark: Zultys  
Date Received: 2021/09/16  
Date of Test: 2021/10/27  
Report Date: 2021/11/10

|              |       |
|--------------|-------|
| Test Result: | Pass* |
|--------------|-------|

\* In the configuration tested, the EUT complied with the standards above.

## Prepared and Checked By:



Fan Yang  
EMC Engineer

## Approved By:



Candy Li  
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "★".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "★". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

## Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China  
Tel: +86 755-26503290 Fax: +86 755-26503396 Web: www.atc-lab.com

## **TABLE OF CONTENTS**

|                                                                           |           |
|---------------------------------------------------------------------------|-----------|
| <b>GENERAL INFORMATION.....</b>                                           | <b>3</b>  |
| PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT) .....                  | 3         |
| OBJECTIVE .....                                                           | 3         |
| TEST METHODOLOGY .....                                                    | 3         |
| TEST FACILITY .....                                                       | 4         |
| <b>SYSTEM TEST CONFIGURATION.....</b>                                     | <b>5</b>  |
| DESCRIPTION OF TEST CONFIGURATION .....                                   | 5         |
| EUT EXERCISE SOFTWARE .....                                               | 5         |
| EQUIPMENT MODIFICATIONS .....                                             | 5         |
| SUPPORT EQUIPMENT LIST AND DETAILS .....                                  | 5         |
| EXTERNAL I/O CABLE.....                                                   | 5         |
| <b>SUMMARY OF TEST RESULTS.....</b>                                       | <b>6</b>  |
| <b>TEST EQUIPMENT LIST .....</b>                                          | <b>7</b>  |
| <b>APPLICABLE STANDARDS.....</b>                                          | <b>8</b>  |
| DFS REQUIREMENT .....                                                     | 8         |
| DFS MEASUREMENT SYSTEM .....                                              | 12        |
| SYSTEM BLOCK DIAGRAM.....                                                 | 12        |
| CONDUCTED METHOD .....                                                    | 13        |
| RADIATED METHOD.....                                                      | 14        |
| TEST PROCEDURE .....                                                      | 14        |
| <b>TEST RESULTS.....</b>                                                  | <b>15</b> |
| DESCRIPTION OF EUT .....                                                  | 15        |
| RADAR WAVEFORM CALIBRATION .....                                          | 15        |
| TEST DATA .....                                                           | 15        |
| <b>CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME .....</b>      | <b>16</b> |
| TEST PROCEDURE .....                                                      | 16        |
| TEST DATA .....                                                           | 16        |
| <b>NON-OCCUPANCY PERIOD.....</b>                                          | <b>17</b> |
| TEST PROCEDURE .....                                                      | 17        |
| TEST DATA .....                                                           | 17        |
| <b>APPENDIX .....</b>                                                     | <b>18</b> |
| APPENDIX A: DFS DETECTION THRESHOLDS .....                                | 18        |
| APPENDIX B: CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME ..... | 19        |
| APPENDIX C: NON-OCCUPANCY PERIOD .....                                    | 20        |

## GENERAL INFORMATION

### Product Description for Equipment under Test (EUT)

|                                        |                                                                                                      |
|----------------------------------------|------------------------------------------------------------------------------------------------------|
| Product                                | Gigabit SIP IP Phone                                                                                 |
| Tested Model                           | ZIP 47GE                                                                                             |
| HVIN                                   | ZIP 47GE                                                                                             |
| Frequency Range                        | 5GHz Wi-Fi: 5250-5350 MHz; 5470-5725MHz<br>Note: frequency range 5600-5650MHz can't be use in Canada |
| Mode                                   | 802.11a/n20                                                                                          |
| Maximum Conducted Average Output Power | 5250-5350MHz: 10.81dBm<br>5470-5725MHz: 10.56dBm                                                     |
| Modulation Technique                   | OFDM                                                                                                 |
| Antenna Specification*                 | 3 dBi (It is provided by the applicant)                                                              |
| Voltage Range                          | DC48V from POE or DC5V from adapter                                                                  |
| Sample serial number                   | SZ1210916-48531E-RF-S2 (Assigned by ATC)                                                             |
| Received date                          | 2021-09-16                                                                                           |
| Sample/EUT Status                      | Good condition                                                                                       |
| Adapter 1 information                  | Model: NSA10EU-05020002<br>Input: AC 100-240V, 50/60Hz, 0.5A<br>Output: DC 5V, 2.0A                  |
| Adapter 2 information                  | Model: OH-1015A0502000U4-UL<br>Input: AC 100-240V, 50/60Hz, 0.5A<br>Output: DC 5V, 2.0A              |

### Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts E of the Federal Communications Commission's rules, and RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada..

The objective is to determine compliance with FCC Part 15, Subpart E, section 15.407 Dynamic Frequency Selection (DFS) for devices operating in the bands 5250-5350 MHz, 5470-5725 MHz.

The objective is to determine compliance with Dynamic Frequency Selection (DFS) of the RSS-247, Issue 2, February 2017 of the Innovation, Science and Economic Development Canada for devices operating in the bands 5250-5350 MHz, 5470-5600MHz and 5650-5725 MHz.

### Test Methodology

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02.  
Each test item follows test standards and with no deviation.

## Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the 1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

Listed by Innovation, Science and Economic Development Canada (ISED), the Registration Number is 5077A.

## SYSTEM TEST CONFIGURATION

### Description of Test Configuration

The EUT was configured for testing in an engineering mode which was provided by the manufacturer.

### EUT Exercise Software

“Lantest” software was used.

### Equipment Modifications

N/A

### Support Equipment List and Details

| Manufacturer | Description               | Model          | Serial Number            |
|--------------|---------------------------|----------------|--------------------------|
| DELL         | PC                        | 67CTQ12        | 1350545499398            |
| DELL         | Monitor                   | REV A00        | CN-0JH6ND-74445-45E-D0GL |
| Lenovo       | Mouse                     | M120Pro        | 31099145JK049889         |
| DELL         | KeyBoard                  | L100           | CN0RH6565890855000E      |
| GOSPELL      | POE                       | G0720-480-050  | 212701319                |
| DELL         | Laptop                    | Latitude E4710 | PC201911252059           |
| Grandstream  | Router(FCC ID:YZZGWN7660) | GWN7660        | 259LAT9M123E850C         |

### External I/O Cable

| Cable Description | Shielding Type | Ferrite Core | Length (m) | From Port       | To     |
|-------------------|----------------|--------------|------------|-----------------|--------|
| RJ45 Cable        | no             | no           | 1.5        | POE             | Router |
| RJ45 Cable        | no             | no           | 1.5        | POE             | PC     |
| USB Cable         | no             | no           | 0.5        | EUT             | Laptop |
| RF Cable          | no             | no           | 0.5        | RF Contorl unit | Router |
| RF Cable          | no             | no           | 0.5        | RF Contorl unit | EUT    |
| USB Cable         | no             | no           | 1.2        | Mouse           | PC     |
| USB Cable         | no             | no           | 1.2        | KeyBoard        | PC     |
| VGA Cable         | no             | no           | 1.0        | Monitor         | PC     |

## SUMMARY OF TEST RESULTS

The following result table represents the list of measurements required under the CFR §47 Part 15.407(h), RSS-247 Issue 2 §6.3 and KDB: 905462 D02 UNII DFS Compliance Procedures New Rules v02

| Items                          | Description of Test                           | Result         |
|--------------------------------|-----------------------------------------------|----------------|
| Detection Bandwidth            | UNII Detection Bandwidth                      | Not Applicable |
| Performance Requirements Check | Initial Channel Availability Check Time (CAC) | Not Applicable |
|                                | Radar Burst at the Beginning of the CAC       | Not Applicable |
|                                | Radar Burst at the End of the CAC             | Not Applicable |
| In-Service Monitoring          | Channel Move Time                             | Compliant      |
|                                | Channel Closing Transmission Time             | Compliant      |
|                                | Non-Occupancy Period                          | Compliant      |
| Radar Detection                | Statistical Performance Check                 | Not Applicable |

Not Applicable: EUT is client without Radar detection

**TEST EQUIPMENT LIST**

| Manufacturer    | Description                  | Model                | Serial Number      | Calibration Date | Calibration Due Date |
|-----------------|------------------------------|----------------------|--------------------|------------------|----------------------|
| Rohde & Schwarz | Spectrum Analyzer            | FSV-40               | 101495             | 2020/12/24       | 2021/12/23           |
| Rohde & Schwarz | Open Switch and Control Unit | OSP120 +<br>OSP-B157 | 101244 +<br>100866 | 2020/12/24       | 2021/12/23           |
| AGILENT         | Vector Signal Generator      | N5182A               | MY50143401         | 2021/01/04       | 2022/01/03           |

\* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

## APPLICABLE STANDARDS

### DFS Requirement

CFR §47 Part 15.407(h) & RSS-247, Issue 2, February 2017 section 6.3

FCC KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02

**Table 1: Applicability of DFS Requirements Prior to Use of a Channel**

| Requirement                            | Operational Mode |                                |                             |
|----------------------------------------|------------------|--------------------------------|-----------------------------|
|                                        | Master           | Client Without Radar Detection | Client With Radar Detection |
| <i>Non-Occupancy Period</i>            | Yes              | Not required                   | Yes                         |
| <i>DFS Detection Threshold</i>         | Yes              | Not required                   | Yes                         |
| <i>Channel Availability Check Time</i> | Yes              | Not required                   | Not required                |
| <i>U-NII Detection Bandwidth</i>       | Yes              | Not required                   | Yes                         |

**Table 2: Applicability of DFS requirements during normal operation**

| Requirement                              | Operational Mode                             |                                |
|------------------------------------------|----------------------------------------------|--------------------------------|
|                                          | Master Device or Client with Radar Detection | Client Without Radar Detection |
| <i>DFS Detection Threshold</i>           | Yes                                          | Not required                   |
| <i>Channel Closing Transmission Time</i> | Yes                                          | Yes                            |
| <i>Channel Move Time</i>                 | Yes                                          | Yes                            |
| <i>U-NII Detection Bandwidth</i>         | Yes                                          | Not required                   |

| Additional requirements for devices with multiple bandwidth modes                                                                                                                                                                                                                                                                                            | Master Device or Client with Radar Detection | Client Without Radar Detection                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------|
| <i>U-NII Detection Bandwidth and Statistical Performance Check</i>                                                                                                                                                                                                                                                                                           | All BW modes must be tested                  | Not required                                         |
| <i>Channel Move Time and Channel Closing Transmission Time</i>                                                                                                                                                                                                                                                                                               | Test using widest BW mode available          | Test using the widest BW mode available for the link |
| <i>All other tests</i>                                                                                                                                                                                                                                                                                                                                       | Any single BW mode                           | Not required                                         |
| <b>Note:</b> Frequencies selected for statistical performance check (Section 7.8.4) should include several frequencies within the radar detection bandwidth and frequencies near the edge of the radar detection bandwidth. For 802.11 devices it is suggested to select frequencies in each of the bonded 20 MHz channels and the channel center frequency. |                                              |                                                      |

**Table 3: DFS Detection Thresholds for Master Devices and Client Devices With Radar Detection**

| Maximum Transmit Power                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Value<br>(See Notes 1, 2, and 3) |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------|
| EIRP $\geq$ 200 milliwatt                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | -64 dBm                          |
| EIRP < 200 milliwatt and<br>power spectral density < 10 dBm/MHz                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | -62 dBm                          |
| EIRP < 200 milliwatt that do not meet the power spectral<br>density requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                              | -64 dBm                          |
| <p><b>Note 1:</b> This is the level at the input of the receiver assuming a 0 dBi receive antenna.</p> <p><b>Note 2:</b> Throughout these test procedures an additional 1 dB has been added to the amplitude of the test transmission waveforms to account for variations in measurement equipment. This will ensure that the test signal is at or above the detection threshold level to trigger a DFS response.</p> <p><b>Note 3:</b> EIRP is based on the highest antenna gain. For MIMO devices refer to KDB Publication 662911 D01.</p> |                                  |

**Table 4: DFS Response Requirement Values**

| Parameter                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Value                                                                                                                 |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <i>Non-occupancy period</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Minimum 30 minutes                                                                                                    |
| <i>Channel Availability Check Time</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 60 seconds                                                                                                            |
| <i>Channel Move Time</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 10 seconds<br>See Note 1.                                                                                             |
| <i>Channel Closing Transmission Time</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 200 milliseconds + an<br>aggregate of 60<br>milliseconds over<br>remaining 10 second<br>period.<br>See Notes 1 and 2. |
| <i>U-NII Detection Bandwidth</i>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | Minimum 100% of the U-<br>NII 99% transmission<br>power bandwidth. See<br>Note 3.                                     |
| <p><b>Note 1:</b> <i>Channel Move Time</i> and the <i>Channel Closing Transmission Time</i> should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst.</p> <p><b>Note 2:</b> The <i>Channel Closing Transmission Time</i> is comprised of 200 milliseconds starting at the beginning of the <i>Channel Move Time</i> plus any additional intermittent control signals required to facilitate a <i>Channel</i> move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.</p> <p><b>Note 3:</b> During the <i>U-NII Detection Bandwidth</i> detection test, radar type 0 should be used. For each frequency step the minimum percentage of detection is 90 percent. Measurements are performed with no data traffic.</p> |                                                                                                                       |

**Table 5 – Short Pulse Radar Test Waveforms**

| Radar Type                                                                                                                                  | Pulse Width (μsec) | PRI (μsec)                                                                                                                                                                                                                                                 | Number of Pulses                                                                                                              | Minimum Percentage of Successful Detection | Minimum Number of Trials |
|---------------------------------------------------------------------------------------------------------------------------------------------|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------|--------------------------|
| 0                                                                                                                                           | 1                  | 1428                                                                                                                                                                                                                                                       | 18                                                                                                                            | See Note 1                                 | See Note 1               |
| 1                                                                                                                                           | 1                  | Test A: 15 unique PRI values randomly selected from the list of 23 PRI values in Table 5a<br>Test B: 15 unique PRI values randomly selected within the range of 518-3066 μsec, with a minimum increment of 1 μsec, excluding PRI values selected in Test A | Roundup $\left\{ \left( \frac{1}{360} \right) \cdot \left( \frac{19 \cdot 10^6}{\text{PRI}_{\mu\text{sec}}} \right) \right\}$ | 60%                                        | 30                       |
| 2                                                                                                                                           | 1-5                | 150-230                                                                                                                                                                                                                                                    | 23-29                                                                                                                         | 60%                                        | 30                       |
| 3                                                                                                                                           | 6-10               | 200-500                                                                                                                                                                                                                                                    | 16-18                                                                                                                         | 60%                                        | 30                       |
| 4                                                                                                                                           | 11-20              | 200-500                                                                                                                                                                                                                                                    | 12-16                                                                                                                         | 60%                                        | 30                       |
| Aggregate (Radar Types 1-4)                                                                                                                 |                    |                                                                                                                                                                                                                                                            |                                                                                                                               | 80%                                        | 120                      |
| <b>Note 1:</b> Short Pulse Radar Type 0 should be used for the detection bandwidth test, channel move time, and channel closing time tests. |                    |                                                                                                                                                                                                                                                            |                                                                                                                               |                                            |                          |

A minimum of 30 unique waveforms are required for each of the Short Pulse Radar Types 2 through 4. If more than 30 waveforms are used for Short Pulse Radar Types 2 through 4, then each additional waveform must also be unique and not repeated from the previous waveforms. If more than 30 waveforms are used for Short Pulse Radar Type 1, then each additional waveform is generated with Test B and must also be unique and not repeated from the previous waveforms in Tests A or B.

For example if in Short Pulse Radar Type 1 Test B a PRI of 3066 usec is selected, the number of pulses

would be  $\text{Roundup} \left\{ \left( \frac{1}{360} \right) \cdot \left( \frac{19 \cdot 10^6}{3066} \right) \right\} = \text{Roundup} \{17.2\} = 18$ .

**Table 5a - Pulse Repetition Intervals Values for Test A**

| <b>Pulse Repetition Frequency Number</b> | <b>Pulse Repetition Frequency (Pulses Per Second)</b> | <b>Pulse Repetition Interval (Microseconds)</b> |
|------------------------------------------|-------------------------------------------------------|-------------------------------------------------|
| 1                                        | 1930.5                                                | 518                                             |
| 2                                        | 1858.7                                                | 538                                             |
| 3                                        | 1792.1                                                | 558                                             |
| 4                                        | 1730.1                                                | 578                                             |
| 5                                        | 1672.2                                                | 598                                             |
| 6                                        | 1618.1                                                | 618                                             |
| 7                                        | 1567.4                                                | 638                                             |
| 8                                        | 1519.8                                                | 658                                             |
| 9                                        | 1474.9                                                | 678                                             |
| 10                                       | 1432.7                                                | 698                                             |
| 11                                       | 1392.8                                                | 718                                             |
| 12                                       | 1355                                                  | 738                                             |
| 13                                       | 1319.3                                                | 758                                             |
| 14                                       | 1285.3                                                | 778                                             |
| 15                                       | 1253.1                                                | 798                                             |
| 16                                       | 1222.5                                                | 818                                             |
| 17                                       | 1193.3                                                | 838                                             |
| 18                                       | 1165.6                                                | 858                                             |
| 19                                       | 1139                                                  | 878                                             |
| 20                                       | 1113.6                                                | 898                                             |
| 21                                       | 1089.3                                                | 918                                             |
| 22                                       | 1066.1                                                | 938                                             |
| 23                                       | 326.2                                                 | 3066                                            |

The aggregate is the average of the percentage of successful detections of Short Pulse Radar Types 1-4. For example, the following table indicates how to compute the aggregate of percentage of successful detections.

| <b>Radar Type</b>                                    | <b>Number of Trials</b> | <b>Number of Successful Detections</b> | <b>Minimum Percentage of Successful Detection</b> |
|------------------------------------------------------|-------------------------|----------------------------------------|---------------------------------------------------|
| 1                                                    | 35                      | 29                                     | 82.9%                                             |
| 2                                                    | 30                      | 18                                     | 60%                                               |
| 3                                                    | 30                      | 27                                     | 90%                                               |
| 4                                                    | 50                      | 44                                     | 88%                                               |
| Aggregate $(82.9\% + 60\% + 90\% + 88\%)/4 = 80.2\%$ |                         |                                        |                                                   |

**Table 6 – Long Pulse Radar Test Waveform**

| Radar Type | Pulse Width (μsec) | Chirp Width (MHz) | PRI (μsec) | Number of Pulses per Burst | Number of Bursts | Minimum Percentage of Successful Detection | Minimum Number of Trials |
|------------|--------------------|-------------------|------------|----------------------------|------------------|--------------------------------------------|--------------------------|
| 5          | 50-100             | 5-20              | 1000-2000  | 1-3                        | 8-20             | 80%                                        | 30                       |


**Table 7 – Frequency Hopping Radar Test Waveform**



| Radar Type | Pulse Width (μsec) | PRI (μsec) | Pulses per Hop | Hopping Rate (kHz) | Hopping Sequence Length (msec) | Minimum Percentage of Successful Detection | Minimum Number of Trials |
|------------|--------------------|------------|----------------|--------------------|--------------------------------|--------------------------------------------|--------------------------|
| 6          | 1                  | 333        | 9              | 0.333              | 300                            | 70%                                        | 30                       |


## DFS Measurement System

ATC DFS measurement system consists of two subsystems: (1) The radar signal generating subsystem and (2) the traffic monitoring subsystem.

## System Block Diagram




**Conducted Method****Setup for Master with injection at the Master****Setup for Client with injection at the Master**



**Setup for Client with injection at the Client**

### Radiated Method



### Test Procedure


A spectrum analyzer is used as a monitor verifies that the EUT status including Channel Closing Transmission Time and Channel Move Time, and does not transmit on a Channel during the Non-Occupancy Period after the diction and Channel move. It is also used to monitor EUT transmissions during the Channel Availability Check Time.

## TEST RESULTS

### Description of EUT

The calibrated radiated DFS detection threshold level is set to -62 dBm.

### Radar Waveform Calibration



### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 46 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Fan Yang on 2021-10-27.*

*EUT operation mode: Transmitting*

#### Test Result: Pass

*Please refer to the Appendix.*

## CHANNEL MOVE TIME AND CHANNEL CLOSING TRANSMISSION TIME

### Test Procedure

Channel Move Time and the Channel Closing Transmission Time should be performed with Radar Type 0. The measurement timing begins at the end of the Radar Type 0 burst. repeat using a long pulse radar type5 waveform.

The Channel Closing Transmission Time is comprised of 200 milliseconds starting at the beginning of the Channel Move Time plus any additional intermittent control signals required to facilitate a Channel move (an aggregate of 60 milliseconds) during the remainder of the 10 second period. The aggregate duration of control signals will not count quiet periods in between transmissions.

The aggregate channel closing transmission time is calculated as follows:

Aggregate Transmission Time =  $N \times \text{Dwell Time}$

N is the number of spectrum analyzer bins showing a device transmission Dwell Time is the dwell time per bin (i.e.  $\text{Dwell Time} = S/B$ , S is the sweep time and B is the number of bin, i.e. 8192)

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 27 °C     |
| Relative Humidity: | 46 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Fan Yang on 2021-10-27.*

*EUT operation mode: Transmitting*

#### Test Result: Pass

*Please refer to the Appendix.*

## NON-OCCUPANCY PERIOD

---

### Test Procedure

Measure the EUT for more than 30 minutes following the channel close/move time to verify that the EUT does not resume any transmissions on this channel. Provide one plot to demonstrate no transmission on the channel for the non-occupancy period (30 minutes observation time)

### Test Data

#### Environmental Conditions

|                    |           |
|--------------------|-----------|
| Temperature:       | 24 °C     |
| Relative Humidity: | 56 %      |
| ATM Pressure:      | 101.0 kPa |

*The testing was performed by Fan Yang on 2021-10-27.*

*EUT operation mode: Transmitting*

#### Test Result: Pass


*Please refer to the Appendix.*

## APPENDIX

### Appendix A: DFS Detection Thresholds Test Result

| Test Mode | Channel | Radar Type | Result | Limit[dbm] | Verdict |
|-----------|---------|------------|--------|------------|---------|
| 11N20SISO | 5260    | Type0      | -62.07 | -62        | PASS    |
|           | 5500    | Type0      | -62.23 | -62        | PASS    |


### Test Graphs



## Appendix B: Channel Move Time and Channel Closing Transmission Time Test Result

| Test Mode | Channel | CCT[ms] | Limit[ms] | CMT[ms] | Limit[ms] | Verdict |
|-----------|---------|---------|-----------|---------|-----------|---------|
| 11N20SISO | 5260    | 200+2.6 | 200+60    | 495.3   | 10000     | PASS    |
|           | 5500    | 200+3.9 | 200+60    | 432.9   | 10000     | PASS    |

### Test Graphs




Appendix C: Non-Occupancy Period

Test Result

| Test Mode | Channel | Result         | Limit[s] | Verdict |
|-----------|---------|----------------|----------|---------|
| 11N20SISO | 5260    | see test graph | ≥1800    | PASS    |

Test Graphs



\*\*\*\*\* END OF REPORT \*\*\*\*\*