



TEST REPORT

Applicant Name : KRIPTO MOBILE CORPORATION
Address : 7640 NW 25TH ST STE 101 MIAMI Florida United States 33122
Report Number : RA230413-19132E-RF-00B
FCC ID: 2APX7K69

Test Standard (s)

FCC PART 15.247

Sample Description

Product Type: 4G Smart Phone
Model No.: K69
Multiple Model(s) No.: N/A
Trade Mark: KRIP
Date Received: 2023/04/13
Report Date: 2023/05/24

Test Result:	Pass*
--------------	-------

* In the configuration tested, the EUT complied with the standards above.

Prepared and Checked By:

Approved By:

Andy Yu

Andy Yu
EMC Engineer

Candy Li

Candy Li
EMC Engineer

Note: This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk "*".

Shenzhen Accurate Technology Co., Ltd. is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk "*". Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

Shenzhen Accurate Technology Co., Ltd.

1/F., Building A, Changyuan New Material Port, Science & Industry Park, Nanshan District, Shenzhen, Guangdong, P.R. China
Tel: +86 755-26503290 Fax: +86 755-26503290 Web: www.atc-lab.com

TABLE OF CONTENTS

DOCUMENT REVISION HISTORY	4
GENERAL INFORMATION.....	5
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	5
OBJECTIVE	5
TEST METHODOLOGY	5
MEASUREMENT UNCERTAINTY.....	6
SYSTEM TEST CONFIGURATION.....	7
DESCRIPTION OF TEST CONFIGURATION	7
EQUIPMENT MODIFICATIONS	8
EUT EXERCISE SOFTWARE	8
DUTY CYCLE	8
SUPPORT EQUIPMENT LIST AND DETAILS	9
EXTERNAL I/O CABLE.....	9
SUMMARY OF TEST RESULTS	11
TEST EQUIPMENT LIST	12
FCC§15.247 (I), §1.1307 (B) &§2.1093 – RF EXPOSURE	14
APPLICABLE STANDARD	14
FCC §15.203 - ANTENNA REQUIREMENT.....	15
APPLICABLE STANDARD	15
ANTENNA CONNECTOR CONSTRUCTION	15
FCC §15.207 (A) – AC LINE CONDUCTED EMISSIONS	16
APPLICABLE STANDARD	16
EUT SETUP	16
EMI TEST RECEIVER SETUP.....	16
TEST PROCEDURE	16
FACTOR & MARGIN CALCULATION	17
TEST DATA	17
FCC §15.209, §15.205 & §15.247(D) - SPURIOUS EMISSIONS.....	20
APPLICABLE STANDARD	20
EUT SETUP	20
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	21
TEST PROCEDURE	21
FACTOR & MARGIN CALCULATION	21
TEST DATA	21
FCC §15.247(A) (2) – 6 DB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH	31
APPLICABLE STANDARD	31
TEST PROCEDURE	31
TEST DATA	31
FCC §15.247(B) (3) - MAXIMUM CONDUCTED OUTPUT POWER	36
APPLICABLE STANDARD	36
TEST PROCEDURE	36
TEST DATA	36

FCC §15.247(D) – 100 KHZ BANDWIDTH OF FREQUENCY BAND EDGE	40
APPLICABLE STANDARD	40
TEST PROCEDURE	40
TEST DATA	41
FCC §15.247(E) - POWER SPECTRAL DENSITY.....	43
APPLICABLE STANDARD	43
TEST PROCEDURE	43
TEST DATA	44
APPENDIX WI-FI.....	47
APPENDIX A: DTS BANDWIDTH	47
APPENDIX B: OCCUPIED CHANNEL BANDWIDTH	54
APPENDIX C: MAXIMUM CONDUCTED OUTPUT POWER	61
APPENDIX D: MAXIMUM POWER SPECTRAL DENSITY	62
APPENDIX E: BAND EDGE MEASUREMENTS.....	69
APPENDIX F: DUTY CYCLE	73

DOCUMENT REVISION HISTORY

Revision Number	Report Number	Description of Revision	Date of Revision
0	RA230413-19132E-RF-00B	Original Report	2023-05-24

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Frequency Range	BLE 1M: 2402-2480MHz Wi-Fi: 2412-2462MHz
Maximum Conducted Output Power	BLE: -6.30dBm (peak) Wi-Fi: 15.50dBm (Average)
Modulation Technique	BLE: GFSK Wi-Fi: DSSS, OFDM
Antenna Specification*	-1.1dBi (provided by the applicant)
Voltage Range	DC 3.87V from battery or DC 5V from adapter
Test Sample serial number	24LB_1 for Conducted and Radiated Emissions Test 24LB_4 for RF Conducted Test (Assigned by ATC)
Sample/EUT Status	Good condition
Adapter information	Model: C69 Input: AC 100-240V, 50/60Hz, 0.3A Output: DC 5.0V, 2.0A

Objective

This test report is in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.207, 15.209 and 15.247 rules.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Shenzhen Accurate Technology Co., Ltd. The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		5%
RF Frequency		0.082×10^{-7}
RF output power, conducted		0.71dB
Unwanted Emission, conducted		1.6dB
AC Power Lines Conducted Emissions		2.72dB
Emissions, Radiated	9kHz - 30MHz	2.06dB
	30MHz - 1GHz	5.08dB
	1GHz - 18GHz	4.96dB
	18GHz - 26.5GHz	5.16dB
	26.5GHz - 40GHz	4.64dB
Temperature		1°C
Humidity		6%
Supply voltages		0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Shenzhen Accurate Technology Co., Ltd. to collect test data is located on the Floor 1, KuMaKe Building, Dongzhou Community, Guangming Street, Guangming District, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 708358, the FCC Designation No.: CN1189. Accredited by American Association for Laboratory Accreditation (A2LA) The Certificate Number is 429 7.01.

The lab has been recognized by Innovation, Science and Economic Development Canada to test to Canadian radio equipment requirements, the CAB identifier: CN0016. The Registration Number is 30241.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 2.4 GHz Wi-Fi mode, total 11 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	/	/
6	2437	/	/
7	2442	/	/

802.11b, 802.11g and 802.11n-HT20 mode was tested with Channel 1, 6 and 11.

802.11n-HT 40 mode was tested with Channel 3, 6 and 9.

For BLE 1M mode, 40 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
0	2402	20	2442
1	2404	21	2444
2	2406	22	2446
3	2408	23	2448
4	2410	24	2450
5	2412	25	2452
6	2414	26	2454
7	2416	27	2456
8	2418	28	2458
9	2420	29	2460
10	2422	30	2462
11	2424	31	2464
12	2426	32	2466
13	2428	33	2468
14	2430	34	2470
15	2432	35	2472
16	2434	36	2474
17	2436	37	2476
18	2438	38	2478
19	2440	39	2480

EUT was tested with Channel 0, 19 and 39.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

EUT was testing in engineering mode. The device was tested with the worst case was performed as below and the power level was provided by applicant.


Mode	Data rate	Power Level*		
		Low Channel	Middle Channel	High Channel
802.11b	1Mbps	16	16	16
802.11g	6Mbps	9	9	9
802.11n-HT20	MCS0	9	9	9
802.11n-HT40	MCS0	9	9	9
BLE	1Mbps	Default	Default	Default

Duty cycle

Test Result: Compliant. Please refer to the Appendix Wi-Fi and test plots as follows:

Mode	Ton (ms)	Ton+off (ms)	Duty Cycle (%)	Duty Cycle Factor [dBm]	1/T (kHz)	VBW (kHz)
BLE 1M	1.64	1.88	87.23	0.59	0.61	1.0

BLE 1M



Date: 3.MAY.2023 09:43:58

Support Equipment List and Details


Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable


Cable Description	Length (m)	From Port	To
Un-shielding Un-Detachable AC Cable	1.0	LISN	Receptacle
Un-shielding Detachable USB Cable	1.0	EUT	Adapter

Block Diagram of Test Setup

For conducted emission:



For Radiated Emissions:



Note: the support table edge was flush with center of turntable

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1) & §2.1093	RF Exposure	Compliant
§15.203	Antenna Requirement	Compliant
§15.207 (a)	AC Line Conducted Emissions	Compliant
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliant
§15.247 (a)(2)	6 dB Emission Bandwidth & Occupied Bandwidth	Compliant
§15.247(b)(3)	Maximum Conducted Output Power	Compliant
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliant
§15.247(e)	Power Spectral Density	Compliant

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Conducted Emissions Test					
Rohde& Schwarz	EMI Test Receiver	ESCI	100784	2022/11/25	2023/11/24
Rohde & Schwarz	L.I.S.N.	ESH3-Z5	100305	2022/12/01	2023/11/30
Anritsu Corp	50 Coaxial Switch	MP59B	6100237248	2022/12/07	2023/12/06
Unknown	RF Coaxial Cable	No.17	N0350	2022/11/25	2023/11/24
Conducted Emission Test Software: e3 19821b (V9)					
Radiated Emissions Test					
Rohde& Schwarz	Test Receiver	ESR	102725	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV40	101949	2022/11/25	2023/11/24
SONOMA INSTRUMENT	Amplifier	310 N	186131	2022/11/08	2023/11/07
A.H. Systems, inc.	Preamplifier	PAM-0118P	135	2022/11/08	2023/11/07
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2022/11/08	2023/11/07
Schwarzbeck	Bilog Antenna	VULB9163	9163-323	2021/07/06	2024/07/05
Schwarzbeck	Horn Antenna	BBHA9120D	837	2023/02/22	2026/02/21
Schwarzbeck	HORN ANTENNA	BBHA9170	9170-359	2022/12/26	2025/12/25
Radiated Emission Test Software: e3 19821b (V9)					
Unknown	RF Coaxial Cable	No.10	N050	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.11	N1000	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.12	N040	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.13	N300	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.14	N800	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.15	N600	2022/11/25	2023/11/24
Unknown	RF Coaxial Cable	No.16	N650	2022/11/25	2023/11/24
Wainwright	High Pass Filter	WHKX3.6/18 G-10SS	5	2022/11/25	2023/11/24

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
RF Conducted Test					
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101590	2022/11/25	2023/11/24
Tonscend	RF Control Unit	JS0806-2	19G8060182	2022/10/24	2023/10/23
WEINSCHTEL	10dB Attenuator	5324	AU 3842	2022/11/25	2023/11/24
Rohde&Schwarz	Spectrum Analyzer	FSV-40	101948	2022/11/25	2023/11/24
WEINSCHTEL	3dB Attenuator	Unknown	F-03-EM121	2022/11/25	2023/11/24
Agilent	Power Sensor	U2021XA	MY5425003	2023/02/25	2024/02/24
Unknown	RF Coaxial Cable	No.31	RF-01	Each time	

* **Statement of Traceability:** Shenzhen Accurate Technology Co., Ltd. attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC§15.247 (i), §1.1307 (b) &§2.1093 – RF EXPOSURE

Applicable Standard

According to FCC §2.1093 and §1.1307(b) (1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 General RF Exposure Guidance

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

1. $f(\text{GHz})$ is the RF channel transmit frequency in GHz.
2. Power and distance are rounded to the nearest mW and mm before calculation.
3. The result is rounded to one decimal place for comparison.
4. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test Exclusion.

Measurement Result

For BLE:

Mode	Frequency (MHz)	Max tune-up conducted power* (dBm)	Max tune-up conducted power* (mW)	Distance (mm)	Calculated value	Threshold (1-g SAR)	SAR Test Exclusion
BLE	2402-2480	-6.0	0.25	5	0.1	3.0	Yes

Note: The tune-up power was declared by the applicant.

Result: No Standalone SAR test is required

For Wi-Fi mode, please refer to SAR report: Please refer to SAR test report: CR230419132-20.

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.
- c. Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has one internal antenna arrangement, which was permanently attached, the antenna gain for is -1.1dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliant.

FCC §15.207 (a) – AC LINE CONDUCTED EMISSIONS

Applicable Standard

FCC§15.207

EUT Setup



Note: 1. Support units were connected to second LISN.
2. Both of LISNs (AMN) 80 cm from EUT and at the least 80 cm from other units and other metal planes support units.

The setup of EUT is according with per ANSI C63.10-2013 measurement procedure. The specification used was with the FCC Part 15.207 limits.

The spacing between the peripherals was 10 cm.

EMI Test Receiver Setup

The EMI test receiver was set to investigate the spectrum from 150 kHz to 30 MHz.

During the conducted emission test, the EMI test receiver was set with the following configurations:

Frequency Range	IF B/W
150 kHz – 30 MHz	9 kHz

Test Procedure

During the conducted emission test, the adapter was connected to the outlet of the LISN.

Maximizing procedure was performed on the six (6) highest emissions of the EUT.

All final data was recorded in the Quasi-peak and average detection mode.

Factor & Margin Calculation

The factor is calculated by adding LISN VDF (Voltage Division Factor) and Cable Loss. The basic equation is as follows:

$$\text{Factor} = \text{LISN VDF} + \text{Cable Loss}$$

The “**Over limit**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over limit of -7 dB means the emission is 7 dB below the limit. The equation for calculation is as follows:

$$\begin{aligned}\text{Over Limit} &= \text{Level} - \text{Limit} \\ \text{Level} &= \text{Read Level} + \text{Factor}\end{aligned}$$

Test Data


Environmental Conditions

Temperature:	23 °C
Relative Humidity:	49 %
ATM Pressure:	101.0 kPa

The testing was performed by Jerry Wu on 2023-05-11.


EUT operation mode: Transmitting (Worst case is 802.11b, middle channel)

AC 120V/60 Hz, Line



Site : Shielding Room
 Condition: Line
 Job No. : RA230413-19132E-RF
 Mode : Charging+2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.172	10.33	19.47	29.80	54.87	-25.07	Average
2	0.172	10.33	28.73	39.06	64.87	-25.81	QP
3	0.221	10.31	17.45	27.76	52.77	-25.01	Average
4	0.221	10.31	28.36	38.67	62.77	-24.10	QP
5	0.467	10.55	17.04	27.59	46.56	-18.97	Average
6	0.467	10.55	28.87	39.42	56.56	-17.14	QP
7	0.587	10.62	13.49	24.11	46.00	-21.89	Average
8	0.587	10.62	31.12	41.74	56.00	-14.26	QP
9	2.212	10.41	7.53	17.94	46.00	-28.06	Average
10	2.212	10.41	19.15	29.56	56.00	-26.44	QP
11	10.139	10.60	21.05	31.65	50.00	-18.35	Average
12	10.139	10.60	30.27	40.87	60.00	-19.13	QP

AC 120V/60 Hz, Neutral

Site : Shielding Room
 Condition: Neutral
 Job No. : RA230413-19132E-RF
 Mode : Charging+2.4G WIFI Transmitting
 Power : AC 120V 60Hz

	Freq	Factor	Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB	dBuV	dBuV	dBuV	dB	
1	0.174	10.28	15.95	26.23	54.75	-28.52	Average
2	0.174	10.28	25.42	35.70	64.75	-29.05	QP
3	0.235	10.32	14.32	24.64	52.28	-27.64	Average
4	0.235	10.32	22.57	32.89	62.28	-29.39	QP
5	0.473	10.45	17.99	28.44	46.46	-18.02	Average
6	0.473	10.45	28.41	38.86	56.46	-17.60	QP
7	0.591	10.47	16.54	27.01	46.00	-18.99	Average
8	0.591	10.47	31.30	41.77	56.00	-14.23	QP
9	2.119	10.50	10.97	21.47	46.00	-24.53	Average
10	2.119	10.50	21.72	32.22	56.00	-23.78	QP
11	10.349	10.67	18.93	29.60	50.00	-20.40	Average
12	10.349	10.67	28.22	38.89	60.00	-21.11	QP


FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS

Applicable Standard


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Factor & Margin Calculation

The Factor is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain. The basic equation is as follows:

$$\text{Factor} = \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Over Limit/Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, an Over Limit/margin of -7dB means the emission is 7dB below the limit. The equation for calculation is as follows:

$$\begin{aligned} \text{Over Limit/Margin} &= \text{Level} / \text{Corrected Amplitude} - \text{Limit} \\ \text{Level} / \text{Corrected Amplitude} &= \text{Read Level} + \text{Factor} \end{aligned}$$

Test Data

Environmental Conditions

Temperature:	24~25.3 °C
Relative Humidity:	56~57 %
ATM Pressure:	101kPa


The testing was performed by Jimi Zheng on 2023-05-11 for below 1GHz and Zeki Ma on 2023-04-26 for above 1GHz.

EUT operation mode: Transmitting (Pre-scan in the X,Y and Z axes of orientation, the worst case X-axes of orientation was recorded)

30MHz-1GHz: (Worst case is 802.11b, middle channel)

Note: When the test result of peak was less than the limit of QP more than 6dB, just peak value were recorded.

Horizontal:



Site : chamber


Condition: 3m HORIZONTAL

Job No. : RA230413-19132E-RF

Test Mode: Charging+2.4G WIFI Transmitting

	Freq Factor		Read Level	Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	55.293	-10.26	37.04	26.78	40.00	-13.22	Peak
2	77.729	-16.58	45.08	28.50	40.00	-11.50	Peak
3	136.879	-15.19	44.95	29.76	43.50	-13.74	Peak
4	190.238	-11.54	43.76	32.22	43.50	-11.28	Peak
5	319.797	-8.46	41.04	32.58	46.00	-13.42	Peak
6	628.099	-2.19	35.32	33.13	46.00	-12.87	Peak

Vertical



Site : chamber

Condition: 3m VERTICAL

Job No. : RA230413-19132E-RF

Test Mode: Charging+2.4G WIFI Transmitting

	Freq Factor		Read Level	Limit Level	Limit Line	Over Limit	Remark
	MHz	dB/m	dBuV	dBuV/m	dBuV/m	dB	
1	38.414	-10.72	46.10	35.38	40.00	-4.62	QP
2	51.323	-9.96	43.62	33.66	40.00	-6.34	Peak
3	79.975	-16.79	48.01	31.22	40.00	-8.78	Peak
4	139.667	-15.43	44.70	29.27	43.50	-14.23	Peak
5	193.179	-11.29	40.49	29.20	43.50	-14.30	Peak
6	322.471	-8.36	37.27	28.91	46.00	-17.09	Peak

1-25 GHz:

BLE 1M:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
Low Channel 2402MHz									
2334.3	66.31	PK	15	2.2	H	-10.62	55.69	74	-18.31
2334.3	53.30	AV	15	2.2	H	-10.62	42.68	54	-11.32
2384.5	68.09	PK	127	2.1	V	-10.71	57.38	74	-16.62
2384.5	54.18	AV	127	2.1	V	-10.71	43.47	54	-10.53
2390	65.21	PK	231	1.6	H	-10.70	54.51	74	-19.49
2390	53.71	AV	231	1.6	H	-10.70	43.01	54	-10.99
2390	64.90	PK	359	2.4	V	-10.70	54.20	74	-19.80
2390	54.04	AV	359	2.4	V	-10.70	43.34	54	-10.66
4804	59.61	PK	207	1.6	H	-6.11	53.50	74	-20.50
4804	59.27	PK	351	1.7	V	-6.11	53.16	74	-20.84
Middle Channel 2440MHz									
4880	59.23	PK	18	1	H	-5.91	53.32	74	-20.68
4880	58.36	PK	186	2.3	V	-5.91	52.45	74	-21.55
High Channel 2480MHz									
2483.5	65.55	PK	52	2.4	H	-10.55	55	74	-19.00
2483.5	53.94	AV	52	2.4	H	-10.55	43.39	54	-10.61
2483.5	65.59	PK	111	1.1	V	-10.55	55.04	74	-18.96
2483.5	53.93	AV	111	1.1	V	-10.55	43.38	54	-10.62
2494	67.53	PK	343	1.1	H	-10.47	57.06	74	-16.94
2494	54.71	AV	343	1.1	H	-10.47	44.24	54	-9.76
2491.06	67.82	PK	83	1.7	V	-10.49	57.33	74	-16.67
2491.06	54.77	AV	83	1.7	V	-10.49	44.28	54	-9.72
4960	58.02	PK	50	1.4	H	-5.47	52.55	74	-21.45
4960	57.78	PK	42	1.4	V	-5.47	52.31	74	-21.69

Wi-Fi:

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11b									
Low Channel 2412MHz									
2310	63.38	PK	127	1.2	H	-10.32	53.06	74	-20.94
2310	50.50	AV	127	1.2	H	-10.32	40.18	54	-13.82
2310	63.19	PK	194	2.4	V	-10.32	52.87	74	-21.13
2310	50.36	AV	194	2.4	V	-10.32	40.04	54	-13.96
2390	66.53	PK	185	1.6	H	-10.62	55.91	74	-18.09
2390	53.20	AV	185	1.6	H	-10.62	42.58	54	-11.42
2390	66.11	PK	314	1.1	V	-10.62	55.49	74	-18.51
2390	52.94	AV	314	1.1	V	-10.62	42.32	54	-11.68
4824	61.33	PK	121	1.7	H	-5.55	55.78	74	-18.22
4824	51.27	AV	121	1.7	H	-5.55	45.72	54	-8.28
4824	62.68	PK	61	1.2	V	-5.55	57.13	74	-16.87
4824	52.76	AV	61	1.2	V	-5.55	47.21	54	-6.79
Middle Channel 2437MHz									
4874	61.70	PK	345	1.7	H	-5.29	56.41	74	-17.59
4874	51.61	AV	345	1.7	H	-5.29	46.32	54	-7.68
4874	63.52	PK	215	1.6	V	-5.29	58.23	74	-15.77
4874	53.89	AV	215	1.6	V	-5.29	48.6	54	-5.40
High Channel 2462MHz									
2483.5	66.13	PK	345	2.3	H	-10.46	55.67	74	-18.33
2483.5	56.09	AV	345	2.3	H	-10.46	45.63	54	-8.37
2483.5	67.96	PK	41	1.7	V	-10.46	57.5	74	-16.50
2483.5	56.98	AV	41	1.7	V	-10.46	46.52	54	-7.48
2486.6	68.01	PK	219	1.5	H	-10.44	57.57	74	-16.43
2486.6	55.38	AV	219	1.5	H	-10.44	44.94	54	-9.06
2484.8	67.69	PK	296	1.7	V	-10.45	57.24	74	-16.76
2484.8	56.72	AV	296	1.7	V	-10.45	46.27	54	-7.73
4924	61.93	PK	348	1.2	H	-5.03	56.90	74	-17.10
4924	51.85	AV	348	1.2	H	-5.03	46.82	54	-7.18
4924	64.24	PK	344	2.3	V	-5.03	59.21	74	-14.79
4924	54.17	AV	344	2.3	V	-5.03	49.14	54	-4.86

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11g									
Low Channel 2412MHz									
2310	63.98	PK	173	1.5	H	-10.32	53.66	74	-20.34
2310	51.39	AV	173	1.5	H	-10.32	41.07	54	-12.93
2310	63.81	PK	277	2.3	V	-10.32	53.49	74	-20.51
2310	51.24	AV	277	2.3	V	-10.32	40.92	54	-13.08
2390	79.04	PK	335	1.1	H	-10.62	68.42	74	-5.58
2390	59.41	AV	335	1.1	H	-10.62	48.79	54	-5.21
2390	75.89	PK	86	1.1	V	-10.62	65.27	74	-8.73
2390	57.65	AV	86	1.1	V	-10.62	47.03	54	-6.97
4824	60.08	PK	238	1.5	H	-5.55	54.53	74	-19.47
4824	45.10	AV	238	1.5	H	-5.55	39.55	54	-14.45
4824	61.92	PK	294	1.6	V	-5.55	56.37	74	-17.63
4824	45.71	AV	294	1.6	V	-5.55	40.16	54	-13.84
Middle Channel 2437MHz									
4874	59.68	PK	132	1.2	H	-5.29	54.39	74	-19.61
4874	44.87	AV	132	1.2	H	-5.29	39.58	54	-14.42
4874	61.52	PK	164	1.9	V	-5.29	56.23	74	-17.77
4874	45.43	AV	164	1.9	V	-5.29	40.14	54	-13.86
High Channel 2462MHz									
2483.5	80.59	PK	328	2.1	H	-10.46	70.13	74	-3.87
2483.5	60.63	AV	328	2.1	H	-10.46	50.17	54	-3.83
2483.5	78.26	PK	6	1.4	V	-10.46	67.8	74	-6.20
2483.5	59.15	AV	6	1.4	V	-10.46	48.69	54	-5.31
2500	65.74	PK	40	2.3	H	-10.32	55.42	74	-18.58
2500	53.03	AV	40	2.3	H	-10.32	42.71	54	-11.29
2500	65.56	PK	244	2.1	V	-10.32	55.24	74	-18.76
2500	52.88	AV	244	2.1	V	-10.32	42.56	54	-11.44
4924	59.16	PK	90	1.7	H	-5.03	54.13	74	-19.87
4924	44.35	AV	90	1.7	H	-5.03	39.32	54	-14.68
4924	60.07	PK	99	1.9	V	-5.03	55.04	74	-18.96
4924	44.88	AV	99	1.9	V	-5.03	39.85	54	-14.15

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n20									
Low Channel 2412MHz									
2310	64.51	PK	34	2	H	-10.32	54.19	74	-19.81
2310	51.58	AV	34	2	H	-10.32	41.26	54	-12.74
2310	64.36	PK	14	2	V	-10.32	54.04	74	-19.96
2310	51.42	AV	14	2	V	-10.32	41.10	54	-12.90
2390	80.10	PK	121	1.3	H	-10.62	69.48	74	-4.52
2390	60.38	AV	121	1.3	H	-10.62	49.76	54	-4.24
2390	77.23	PK	131	1.7	V	-10.62	66.61	74	-7.39
2390	58.69	AV	131	1.7	V	-10.62	48.07	54	-5.93
4824	60.24	PK	107	2.3	H	-5.55	54.69	74	-19.31
4824	45.21	AV	107	2.3	H	-5.55	39.66	54	-14.34
4824	62.17	PK	298	1.5	V	-5.55	56.62	74	-17.38
4824	45.92	AV	298	1.5	V	-5.55	40.37	54	-13.63
Middle Channel 2437MHz									
4874	59.83	PK	298	2.3	H	-5.29	54.54	74	-19.46
4874	44.94	AV	298	2.3	H	-5.29	39.65	54	-14.35
4874	61.66	PK	243	1.6	V	-5.29	56.37	74	-17.63
4874	45.62	AV	243	1.6	V	-5.29	40.33	54	-13.67
High Channel 2462MHz									
2483.5	81.18	PK	213	1.1	H	-10.46	70.72	74	-3.28
2483.5	61.32	AV	213	1.1	H	-10.46	50.86	54	-3.14
2483.5	79.14	PK	249	1.4	V	-10.46	68.68	74	-5.32
2483.5	60.58	AV	249	1.4	V	-10.46	50.12	54	-3.88
2500	66.06	PK	34	2.1	H	-10.32	55.74	74	-18.26
2500	53.19	AV	34	2.1	H	-10.32	42.87	54	-11.13
2500	65.81	PK	299	2.2	V	-10.32	55.49	74	-18.51
2500	53.05	AV	299	2.2	V	-10.32	42.73	54	-11.27
4924	59.27	PK	204	1.8	H	-5.03	54.24	74	-19.76
4924	44.42	AV	204	1.8	H	-5.03	39.39	54	-14.61
4924	60.13	PK	15	1.5	V	-5.03	55.10	74	-18.90
4924	44.94	AV	15	1.5	V	-5.03	39.91	54	-14.09

Frequency (MHz)	Receiver		Turntable Angle Degree	Rx Antenna		Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/Ave		Height (m)	Polar (H/V)				
802.11n40									
Low Channel 2422MHz									
2310	64.90	PK	0	1.2	H	-10.32	54.58	74	-19.42
2310	51.76	AV	0	1.2	H	-10.32	41.44	54	-12.56
2310	64.78	PK	17	1.9	V	-10.32	54.46	74	-19.54
2310	51.64	AV	17	1.9	V	-10.32	41.32	54	-12.68
2390	80.71	PK	46	1.2	H	-10.62	70.09	74	-3.91
2390	60.90	AV	46	1.2	H	-10.62	50.28	54	-3.72
2390	79.15	PK	304	1.4	V	-10.62	68.53	74	-5.47
2390	60.04	AV	304	1.4	V	-10.62	49.42	54	-4.58
4844	59.72	PK	306	1.5	H	-5.52	54.20	74	-19.80
4844	45.01	AV	306	1.5	H	-5.52	39.49	54	-14.51
4844	60.90	PK	9	1.3	V	-5.52	55.38	74	-18.62
4844	45.65	AV	9	1.3	V	-5.52	40.13	54	-13.87
Middle Channel 2437MHz									
4874	59.40	PK	283	2.3	H	-5.29	54.11	74	-19.89
4874	44.77	AV	283	2.3	H	-5.29	39.48	54	-14.52
4874	60.29	PK	336	1.1	V	-5.29	55	74	-19.00
4874	45.52	AV	336	1.1	V	-5.29	40.23	54	-13.77
High Channel 2452MHz									
2483.5	81.43	PK	32	1.7	H	-10.46	70.97	74	-3.03
2483.5	61.25	AV	32	1.7	H	-10.46	50.79	54	-3.21
2483.5	79.66	PK	63	1.7	V	-10.46	69.2	74	-4.80
2483.5	60.17	AV	63	1.7	V	-10.46	49.71	54	-4.29
2500	66.15	PK	353	2.3	H	-10.32	55.83	74	-18.17
2500	53.38	AV	353	2.3	H	-10.32	43.06	54	-10.94
2500	66.04	PK	93	1.5	V	-10.32	55.72	74	-18.28
2500	53.23	AV	93	1.5	V	-10.32	42.91	54	-11.09
4904	58.91	PK	327	1.5	H	-5.06	53.85	74	-20.15
4904	44.36	AV	327	1.5	H	-5.06	39.30	54	-14.70
4904	59.67	PK	252	1.3	V	-5.06	54.61	74	-19.39
4904	45.13	AV	252	1.3	V	-5.06	40.07	54	-13.93

Note:

Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor

Corrected Amplitude = Factor + Reading


Margin = Corrected. Amplitude - Limit

The other spurious emission which is in the noise floor level was not recorded.


1-18 GHz:

Pre-scan for 802.11b, High Channel

Horizontal




Vertical




18 -25GHz:

Pre-scan for 802.11b, High Channel

Horizontal



Vertical



FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH & OCCUPIED BANDWIDTH

Applicable Standard


Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure


Test Method: ANSI C63.10-2013 Clause 11.8.1 & Clause 6.9.3

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.

For Wi-Fi:



For BLE:



Test Data

Environmental Conditions

Temperature:	23.2~26 °C
Relative Humidity:	52~62 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-03 and 2023-05-17.


EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and test plots as follows:

Channel	Frequency (MHz)	6 dB Emission Bandwidth (MHz)	99% Occupied Bandwidth (MHz)	Limit (kHz)
BLE 1M				
Low	2402	0.669	1.010	≥ 500
Middle	2440	0.671	1.007	≥ 500
High	2480	0.672	1.007	≥ 500


6dB Bandwidth:
BLE1M:

Low Channel




Date: 3.MAY.2023 09:45:47

Middle Channel



Date: 3.MAY.2023 09:52:24


High Channel



Date: 3.MAY.2023 09:52:36


OBW

Low Channel




Date: 3.MAY.2023 09:45:12

Middle Channel



Date: 3.MAY.2023 09:48:54

High Channel



Date: 3.MAY.2023 09:42:41

FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard


According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure


Test Method: ANSI C63.10-2013 Clause 11.9.1.1 for BLE & Clause 11.9.2.3.2 for Wi-Fi

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.

For Wi-Fi mode:



For BLE mode:



Test Data

Environmental Conditions

Temperature:	23.2~26 °C
Relative Humidity:	52~62 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-03 and 2023-05-17.


EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and test plots as follows:

Channel	Frequency (MHz)	Max Conducted Peak Output Power (dBm)	Limit (dBm)
BLE 1M			
Low	2402	-6.42	30
Middle	2440	-6.78	30
High	2480	-6.30	30


BLE1M:

Low Channel




Date: 3.MAY.2023 09:44:37

Middle Channel



Date: 3.MAY.2023 09:48:06



Date: 3.MAY.2023 09:42:20

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE

Applicable Standard


In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure


Test Method: ANSI C63.10-2013 Clause 11.11

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

For Wi-Fi:



For BLE:



Test Data**Environmental Conditions**

Temperature:	23.2~26 °C
Relative Humidity:	52~62 %
ATM Pressure:	101.0 kPa

The testing was performed by Jacob Huang on 2023-05-03 and 2023-05-17.


EUT operation mode: Transmitting

Test Result: Compliant.

Conducted Band Edge Result:


Please refer to the Appendix Wi-Fi and test plots as follows:

BLE 1M mode Left Side



Date: 3.MAY.2023 09:46:34

BLE 1M mode Right Side



Date: 3.MAY.2023 09:53:23

FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

Test Method: ANSI C63.10-2013 Clause 11.10.2

Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.

1. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
2. Set the VBW $\geq 3 \times \text{RBW}$.
3. Set the span to 1.5 times the DTS bandwidth.
4. Detector = peak.
5. Sweep time = auto couple.
6. Trace mode = max hold.
7. Allow trace to fully stabilize.
8. Use the peak marker function to determine the maximum amplitude level within the RBW.
9. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.

Test Method: ANSI C63.10-2013 Clause 11.10.3 Method Ave.GPSD-1

The following procedure may be used when the maximum (average) conducted output power was used to determine compliance to the fundamental output power limit. This is the baseline method for determining the maximum (average) conducted PSD level. If the instrument has a power averaging (rms) detector, then it must be used; otherwise, use the sample detector. The EUT must be configured to transmit continuously ($D \geq 98\%$), or else sweep triggering/signal gating must be implemented to ensure that measurements are made only when the EUT is transmitting at its maximum power control level (no transmitter OFF time to be considered):


1. Set instrument center frequency to DTS channel center frequency.
2. Set span to at least 1.5 times the OBW.
3. Set the RBW to: $3\text{kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
4. Set the VBW $\geq 3 \times \text{BW}$.
5. Detector = power averaging (rms) or sample detector (when rms not available)
6. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
7. Sweep time = auto couple.
8. Employ trace averaging (rms) mode over a minimum of 100 traces.
9. Use the peak marker function to determine the maximum amplitude level.
10. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

Test Method: ANSI C63.10-2013 Clause 11.10.5 Method Ave.GPSD-2


The following procedure is applicable when the EUT cannot be configured to transmit continuously (i.e., $D < 98\%$), when sweep triggering/signal gating cannot be used to measure only when the EUT is transmitting at its maximum power control level, and when the transmission duty cycle is constant (i.e., duty cycle variations are less than $\pm 2\%$):

1. Measure the duty cycle (D) of the transmitter output signal as described in 11.6.
2. Set instrument center frequency to DTS channel center frequency.
3. Set span to at least 1.5 times the OBW.
4. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
5. Set the VBW $\geq 3 \times \text{BW}$.
6. Detector = power averaging (rms) or sample detector (when rms not available)
7. Ensure that the number of measurement points in the sweep $\geq [2 \times \text{span} / \text{RBW}]$.
8. Sweep time = auto couple.
9. Do not use sweep triggering; allow sweep to “free run.”
10. Employ trace averaging (rms) mode over a minimum of 100 traces.
11. Use the peak marker function to determine the maximum amplitude level.
12. Add $[10 \log (1 / D)]$, where D is the duty cycle measured in step a), to the measured PSD to compute the average PSD during the actual transmission time.
13. If the measured value exceeds requirement, then reduce RBW (but no less than 3 kHz) and repeat (note that this may require zooming in on the emission of interest and reducing the span to meet the minimum measurement point requirement as the RBW is reduced).

For Wi-Fi:



For BLE:



Test Data

Environmental Conditions

Temperature:	23.2~26 °C
Relative Humidity:	52~62 %
ATM Pressure:	101.0 kPa

The testing was performed by Bob Liao on 2023-05-03 and 2023-05-23.


EUT operation mode: Transmitting

Test Result: Compliant. Please refer to the Appendix Wi-Fi and test plots as follows:

Channel	Frequency (MHz)	PSD (dBm/3kHz)	Limit (dBm/3kHz)
BLE 1M			
Low	2402	-23.07	≤8
Middle	2440	-24.14	≤8
High	2480	-23.01	≤8


BLE 1M mode:

Power Spectral Density, Low Channel




Date: 3.MAY.2023 09:59:06

Power Spectral Density, Middle Channel



Date: 3.MAY.2023 09:55:09

Power Spectral Density, High Channel




Date: 3.MAY.2023 09:50:11

APPENDIX Wi-Fi


Appendix A: DTS Bandwidth Test Result


Test Mode	Antenna	Frequency[MHz]	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.52	2407.48	2417.00	0.5	PASS
		2437	9.56	2431.96	2441.52	0.5	PASS
		2462	9.56	2457.44	2467.00	0.5	PASS
11G	Ant1	2412	16.36	2403.80	2420.16	0.5	PASS
		2437	16.08	2429.08	2445.16	0.5	PASS
		2462	16.32	2453.80	2470.12	0.5	PASS
11N20SISO	Ant1	2412	17.44	2403.20	2420.64	0.5	PASS
		2437	17.12	2428.20	2445.32	0.5	PASS
		2462	16.20	2454.44	2470.64	0.5	PASS
11N40SISO	Ant1	2422	35.12	2404.40	2439.52	0.5	PASS
		2437	35.60	2418.92	2454.52	0.5	PASS
		2452	35.68	2434.40	2470.08	0.5	PASS


Test Graphs

















**Appendix B: Occupied Channel Bandwidth
Test Result**


Test Mode	Antenna	Channel Frequency[MHz]	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	12.428	2405.966	2418.394	---	---
		2437	12.308	2430.686	2442.994	---	---
		2462	13.347	2455.766	2469.113	---	---
11G	Ant1	2412	17.582	2403.049	2420.631	---	---
		2437	17.383	2428.329	2445.711	---	---
		2462	17.542	2453.129	2470.671	---	---
11N20SISO	Ant1	2412	18.701	2402.250	2420.951	---	---
		2437	18.182	2427.609	2445.791	---	---
		2462	17.902	2453.129	2471.031	---	---
11N40SISO	Ant1	2422	36.044	2403.778	2439.822	---	---
		2437	36.923	2418.139	2455.062	---	---
		2452	37.403	2433.299	2470.701	---	---

Test Graphs







11G_Ant1_2437




11G_Ant1_2462









**Appendix C: Maximum conducted output power
Test Result**

TestMode	Antenna	Frequency[MHz]	Set Power	Average Power[dBm]	Conducted Limit[dBm]	Verdict
11B	Ant1	2412	---	15.50	≤30.00	PASS
		2437	---	14.10	≤30.00	PASS
		2462	---	15.01	≤30.00	PASS
11G	Ant1	2412	---	11.91	≤30.00	PASS
		2437	---	10.57	≤30.00	PASS
		2462	---	11.41	≤30.00	PASS
11N20SISO	Ant1	2412	---	9.61	≤30.00	PASS
		2437	---	7.80	≤30.00	PASS
		2462	---	7.08	≤30.00	PASS
11N40SISO	Ant1	2422	---	8.81	≤30.00	PASS
		2437	---	8.79	≤30.00	PASS
		2452	---	7.07	≤30.00	PASS


**Appendix D: Maximum power spectral density
Test Result**

Test Mode	Antenna	Frequency[MHz]	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-16.34	≤8.00	PASS
		2437	-18.26	≤8.00	PASS
		2462	-17.23	≤8.00	PASS
11G	Ant1	2412	-22.27	≤8.00	PASS
		2437	-23.42	≤8.00	PASS
		2462	-22.06	≤8.00	PASS
11N20SISO	Ant1	2412	-24.68	≤8.00	PASS
		2437	-26.96	≤8.00	PASS
		2462	-26.93	≤8.00	PASS
11N40SISO	Ant1	2422	-22.35	≤8.00	PASS
		2437	-21.62	≤8.00	PASS
		2452	-23.24	≤8.00	PASS


Note: 1. the unit of Result for 802.11N40 mode is dBm/10kHz.

2. The duty cycle factor of 802.11g/n is compensated in the graph


Test Graphs




11B_Ant1_2462




11G_Ant1_2412





11G_Ant1_2437




11G_Ant1_2462













Appendix E: Band edge measurements
Test Graphs









Appendix F: Duty Cycle Test Result

Test Mode	Antenna	Frequency [MHz]	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]	Duty Cycle Factor [dBm]	1/T (kHz)	VBW (kHz)
11B	Ant1	2437	8.36	8.52	98.12	/	/	/
11G	Ant1	2437	1.39	1.55	89.68	0.47	0.72	1.0
11N20SISO	Ant1	2437	1.16	1.56	74.36	1.29	0.86	1.0
11N40SISO	Ant1	2437	0.56	0.76	73.68	1.33	1.79	3.0

Test Graphs





***** END OF REPORT *****