

# **FCC ID: 2APXS2643337592508**

## **RF EXPOSURE EVALUATION**

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

| Frequency range (MHz)                                          | Electric field strength (V/m) | Magnetic field strength (A/m) | Power density (mW/cm <sup>2</sup> ) | Averaging time (minutes) |
|----------------------------------------------------------------|-------------------------------|-------------------------------|-------------------------------------|--------------------------|
| <b>(A) Limits for Occupational/Controlled Exposure</b>         |                               |                               |                                     |                          |
| 0.3-3.0                                                        | 614                           | 1.63                          | *100                                | 6                        |
| 3.0-30                                                         | 1842/f                        | 4.89/f                        | *900/f <sup>2</sup>                 | 6                        |
| 30-300                                                         | 61.4                          | 0.163                         | 1.0                                 | 6                        |
| 300-1,500                                                      |                               |                               | f/300                               | 6                        |
| 1,500-100,000                                                  |                               |                               | 5                                   | 6                        |
| <b>(B) Limits for General Population/Uncontrolled Exposure</b> |                               |                               |                                     |                          |
| 0.3-1.34                                                       | 614                           | 1.63                          | *100                                | 30                       |
| 1.34-30                                                        | 824/f                         | 2.19/f                        | *180/f <sup>2</sup>                 | 30                       |
| 30-300                                                         | 27.5                          | 0.073                         | 0.2                                 | 30                       |
| 300-1,500                                                      |                               |                               | f/1500                              | 30                       |
| 1,500-100,000                                                  |                               |                               | 1.0                                 | 30                       |

f = frequency in MHz \* = Plane-wave equivalent power density

## **MPE Calculation Method**

$$E \text{ (V/m)} = \frac{\sqrt{30 * P * G}}{d} \quad \text{Power Density: } Pd \text{ (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric field (V/m)

P = Average RF output power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 * P * G}{377 * D^2}$$

From the EUT RF output power, the minimum mobile separation distance, d=0.2m, as well as the gain of the used antenna, the RF power density can be obtained.

**MAX OUTPUT POWER**

WIFI:

| Test Channel        | Frequency (MHz) | Power Setting | Average Output Power (dBm) | Maximum Output Power (dBm) | LIMIT (dBm) | Verdict |
|---------------------|-----------------|---------------|----------------------------|----------------------------|-------------|---------|
| <b>802.11b</b>      |                 |               |                            |                            |             |         |
| 1                   | 2412            | Default       | 14.8                       | 14.8                       | 30          | PASS    |
| 6                   | 2437            | Default       | 15.5                       | 15.5                       | 30          | PASS    |
| 11                  | 2462            | Default       | 15.7                       | 15.7                       | 30          | PASS    |
| <b>802.11g</b>      |                 |               |                            |                            |             |         |
| 1                   | 2412            | Default       | 15.2                       | 15.2                       | 30          | PASS    |
| 6                   | 2437            | Default       | 15.2                       | 15.2                       | 30          | PASS    |
| 11                  | 2462            | Default       | 15.5                       | 15.5                       | 30          | PASS    |
| <b>802.11n HT20</b> |                 |               |                            |                            |             |         |
| 1                   | 2412            | Default       | 15.1                       | 15.1                       | 30          | PASS    |
| 6                   | 2437            | Default       | 15.4                       | 15.4                       | 30          | PASS    |
| 11                  | 2462            | Default       | 15.4                       | 15.4                       | 30          | PASS    |
| <b>802.11n HT40</b> |                 |               |                            |                            |             |         |
| 3                   | 2422            | Default       | 15.0                       | 15.0                       | 30          | PASS    |
| 6                   | 2437            | Default       | 15.4                       | 15.4                       | 30          | PASS    |
| 9                   | 2452            | Default       | 15.5                       | 15.5                       | 30          | PASS    |

## Measurement Result

Operation Frequency: WIFI 802.11b/g/n HT20: 2412-2462MHz, 2422-2452MHz for 802.11n(HT40);

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: PCB On-board PIFA Antenna

Antenna gain: 2dBi,

R=20cm

802.11b/g/n:

| Channel Freq. (MHz) | modulation  | conducted power | Tune-up power (dBm) | Max           |        | Antenna |         | Evaluation result | Power density |
|---------------------|-------------|-----------------|---------------------|---------------|--------|---------|---------|-------------------|---------------|
|                     |             | (dBm)           |                     | tune-up power |        | Gain    |         | (mW/cm2 )         | (mW/cm2)      |
|                     |             |                 |                     | (dBm)         | (mW)   | (dBi)   | Numeric |                   |               |
| 2412                | 802.11b     | 14.8            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2437                |             | 15.5            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2462                |             | 15.7            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2412                | 802.11g     | 15.2            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2437                |             | 15.2            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2462                |             | 15.5            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2412                | 802.11n H20 | 15.1            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2437                |             | 15.1            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2462                |             | 15.4            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2422                | 802.11n H40 | 15              | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2437                |             | 15.4            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |
| 2452                |             | 15.5            | 15±1                | 16            | 39.811 | 2.00    | 1.58    | 0.0126            | 1             |

### Conclusion:

For the max result :  $0.0126 \leq 1.0$  for Max Power Density, compliance the RF Exposure.

Jason chen

Signature:

Date: 2018-6-11

**NAME AND TITLE** (Please print or type): Jason Chen/Manager

**COMPANY** (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.