

RF EXPOSURE REPORT

Product: Telematics Box

Model Name: LEC014

FCC ID: 2APY7LEC014

Applicant: Guangxi Liugong Machinery Co., Ltd.

Address: No.1 Liutai Road, Liuzhou, Guangxi P.R.China

Manufacturer: Guangxi Liugong Machinery Co., Ltd.

Address: No.1 Liutai Road, Liuzhou, Guangxi P.R.China

Prepared by: BV 7Layers Communications Technology (Shenzhen) Co. Ltd

Lab Location: No.B102, Dazu Chuangxin Mansion, North of Beihuan Avenue,
North Area, Hi-Tech Industrial Park, Nanshan District,
Shenzhen, Guangdong, China

TEL: +86 755 8869 6566

FAX: +86 755 8869 6577

E-MAIL: customerservice.dg@cn.bureauveritas.com

Report No.: SA180611W007

Received Date: Jun. 11, 2018

Test Date: Jun. 18, 2018 ~ Jul. 16, 2018

Issued Date: Jul. 17, 2018

This report should not be used by the client to claim product certification, approval, or endorsement by A2LA or any government agencies.

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



Test Report No.: SA180611W007

TABLE OF CONTENTS

RF EXPOSURE REPORT	1
RELEASE CONTROL RECORD	3
1 CERTIFICATION	4
2 GENERAL INFORMATION	5
2.1 GENERAL DESCRIPTION OF EUT	5
3 RF EXPOSURE	6
3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)	6
3.2 MPE CALCULATION FORMULA	6
3.3 CLASSIFICATION	6
3.4 CONDUCTED POWER	7
3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER	9



Test Report No.: SA180611W007

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
SA180611W007	Original release	Jul. 17, 2018



Test Report No.: SA180611W007

1 CERTIFICATION

PRODUCT: Telematics Box

BRAND NAME:  **LIUGONG**

MODEL NAME: LEC014

APPLICANT: Guangxi Liugong Machinery Co., Ltd.

TESTED: Jun. 18, 2018 ~ Jul. 16, 2018

TEST SAMPLE: Production Unit

STANDARDS: FCC Part 2 (Section 2.1091)

FCC OET Bulletin 65, Supplement C (01-01)

KDB 447498 D01 General RF Exposure Guidance v06

IEEE C95.1

The above equipment has been tested by **BV 7Layers Communications Technology (Shenzhen) Co. Ltd** and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's EMC characteristics under the conditions specified in this report.

PREPARED BY :  , **DATE:** Jul. 17, 2018
(Roger Li / Engineer)

APPROVED BY :  , **DATE:** Jul. 17, 2018
(Sam Tung / Manager)



2 GENERAL INFORMATION

2.1 GENERAL DESCRIPTION OF EUT

PRODUCT	Telematics Box	
MODEL NAME	LEC014	
NOMINAL VOLTAGE	DC 24V	
OPERATING TEMPERATURE RANGE	-30 ~ 65°C	
MODULATION TYPE	GPS/BDS	C/A code
	GSM	GMSK, 8PSK
	WCDMA	BPSK/QPSK
OPERATING FREQUENCY	GPS	1575.42MHz
	BDS	1561.098MHz
	GSM	824.2MHz ~ 848.8MHz (FOR GSM 850) 1850.2MHz ~ 1909.8MHz (FOR GSM 1900)
	WCDMA	1852.4MHz ~ 1907.6MHz (FOR WCDMA Band 2) 826.4MHz ~ 846.6MHz (FOR WCDMA Band 5)
ANTENNA GAIN	GSM850	Fixed Internal antenna with 1.2dBi gain
	GSM1900	Fixed Internal antenna with 3.57dBi gain
	WCDMA 850	Fixed Internal antenna with 1.2dBi gain
	WCDMA 1900	Fixed Internal antenna with 3.57dBi gain
HW VERSION	V103	
SW VERSION	V1.0.0	
I/O PORTS	Refer to user's manual	
CABLE SUPPLIED	N/A	

NOTE:

- For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.
- There were Sample A & B for this project, the only difference is the Port, and Sample A was tested in this report:

SAMPLE	EUT CONFIGURATION INFORMATION
A	Port (16 Ping)
B	Port (12 Ping)

- For the test results, the EUT had been tested with all conditions. But only the worst case was shown in test report.

3 RF EXPOSURE

3.1 LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3.2 MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

3.3 CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.

3.4 CONDUCTED POWER

Band	GSM850		
Channel	128	189	251
Frequency (MHz)	824.2	836.4	848.8
GPRS 8	31.95	31.97	31.78
GPRS 10	30.82	30.84	30.65
GPRS 11	29.19	29.21	29.02
GPRS 12	27.70	27.72	27.53
EDGE 8 (MCS9)	25.33	25.35	25.16
EDGE 10 (MCS9)	25.23	25.25	25.06
EDGE 11 (MCS9)	24.80	24.82	24.63
EDGE 12 (MCS9)	24.76	24.78	24.59

Band	GSM1900		
Channel	512	661	810
Frequency (MHz)	1850.2	1880.0	1909.8
GPRS 8	28.16	27.83	27.74
GPRS 10	28.08	27.75	27.66
GPRS 11	27.98	27.65	27.56
GPRS 12	27.88	27.55	27.46
EDGE 8 (MCS9)	24.57	24.24	24.15
EDGE 10 (MCS9)	24.54	24.21	24.12
EDGE 11 (MCS9)	24.17	23.84	23.75
EDGE 12 (MCS9)	23.98	23.65	23.56

Band	WCDMA II		
Channel	9262	9400	9538
Frequency (MHz)	1852.4	1880.0	1907.6
RMC 12.2K	21.87	22.58	21.82
HSPA			
HSDPA Subtest-1	20.82	21.48	20.75
HSDPA Subtest-2	20.69	21.35	20.62
HSDPA Subtest-3	20.25	20.89	20.18
HSDPA Subtest-4	20.20	20.84	20.12
HSUPA Subtest-1	20.76	21.42	20.69
HSUPA Subtest-2	18.70	19.27	18.59
HSUPA Subtest-3	19.78	20.40	19.69
HSUPA Subtest-4	18.74	19.31	18.64
HSUPA Subtest-5	20.74	21.40	20.67

Band	WCDMA V		
Channel	4132	4182	4233
Frequency (MHz)	826.4	836.4	846.6
RMC 12.2K	23.41	22.43	22.81
HSPA			
HSDPA Subtest-1	22.34	21.41	21.75
HSDPA Subtest-2	22.20	21.28	21.62
HSDPA Subtest-3	21.76	20.85	21.19
HSDPA Subtest-4	21.71	20.80	21.14
HSUPA Subtest-1	22.27	21.35	21.69
HSUPA Subtest-2	20.17	19.34	19.62
HSUPA Subtest-3	21.27	20.39	20.71
HSUPA Subtest-4	20.21	19.38	19.66
HSUPA Subtest-5	22.25	21.33	21.67

3.5 CALCULATION RESULT OF MAXIMUM CONDUCTED POWER

TUNE-UP POWER TABLE

Band	Frequency (MHz)	Operating Mode	Tune-Up Power And Tolerance (dBm)
GSM850	836.4	GPRS8	31.5± 1.0
GSM1900	1850.2	GPRS8	27.5± 1.0
WCDMA Band II	1880	RMC12.2K	22.0 ± 1.0
WCDMA Band V	826.4	RMC12.2K	22.5 ± 1.0

GSM

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (dBm)	E.I.R.P Power (mW)/8	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
GSM850	836.4	GPRS8	1.2	32.5	33.70	293.029	0.058	0.56	PASS
GSM1900	1850.2	GPRS8	3.57	28.5	32.07	201.331	0.040	1.00	PASS

WCDMA

Band	Frequency (MHz)	Operating Mode	Antenna Gain (dBi)	Tune-up Power (dBm)	E.I.R.P Power (dBm)	E.I.R.P Power (mW)	Power Density (mW/cm ²)	limit (mW/cm ²)	PASS / FAIL
WCDMA II	1880	RMC12.2K	3.57	23.0	26.57	453.942	0.090	1.00	PASS
WCDMA V	826.4	RMC12.2K	1.2	23.5	24.70	295.121	0.059	0.55	PASS

--END--