

FCC RF Exposure Evaluation

Report Number:

F251879E2

Equipment under Test (EUT):

WBS

Applicant:

eologix sensor technology flexco

Manufacturer:

eologix sensor technology flexco



Deutsche
Akkreditierungsstelle
D-PL-17186-01-00

References

- [1] **CFR 47 Rule part 1** Practice and Procedure
- [2] **CFR 47 Rule part 2** Frequency Allocations and Radio Treaty Matters; General Rules and Regulations
- [3] **KDB 447498 D04 Interim General RF Exposure Guidance v01**

Assessed and
written by:

A handwritten signature in blue ink, appearing to read 'S. KREHS'.

Sebastian KREHS
10.08.2026

Signature

Reviewed and
approved by:

A handwritten signature in blue ink, appearing to read 'B. ROHDE'.

Bernward ROHDE
12.08.2026

Signature

This evaluation report is only valid in its original form.

Any reproduction of its contents in extracts without written permission of the accredited test laboratory NMI TESTLAB GmbH is prohibited.

The results herein refer only to the evaluated sample. NMI TESTLAB GmbH is not responsible for any generalisations or conclusions drawn from these results concerning further samples. Any modification of the evaluated samples is prohibited and leads to the invalidity of this evaluation report. Each page necessarily contains the NMI TESTLAB Logo and the REPORT NUMBER.

Contents:

Page

1	Identification.....	4
1.1	Applicant	4
1.2	Manufacturer	4
1.3	Test Laboratory	4
1.4	EUT (Equipment under Test)	5
1.5	Technical Data of Equipment	5
2	Evaluation Methods	7
2.1	RF exposure test exemptions for single sources	7
2.2	RF exposure test exemptions for simultaneous transmission sources	10
3	Results of evaluation.....	12
3.1	Used evaluation methods	12
3.2	Evaluation Distance	12
3.3	MPE calculation results.....	12
4	Conclusion.....	13
5	Report History	13

1 Identification

1.1 Applicant

Name:	eologix sensor technology flexco
Address:	Waagner-Biro-Str. 124, 8020 Graz
Country:	Austria
Name for contact purposes:	Mr. Michael MOSER
Phone:	+43-316-931215-100
eMail address:	office@eologix-ping.com

1.2 Manufacturer

Name:	eologix sensor technology flexco
Address:	Waagner-Biro-Str. 124, 8020 Graz
Country:	Austria
Name for contact purposes:	Mr. Michael MOSER
Phone:	+43-316-931215-100
eMail address:	office@eologix-ping.com

1.3 Test Laboratory

The evaluation was carried out by: **NMI TESTLAB GmbH formerly PHOENIX TESTLAB GmbH**
Königswinkel 10
32825 Blomberg
Germany

accredited by **Deutsche Akkreditierungsstelle GmbH (DAkkS)** according to DIN EN ISO/IEC 17025:2018.
The accreditation is only valid for the scope of accreditation listed in the annex of the certificate D-PL-17186-01-00. FCC Test Firm Designation Number DE0004, FCC Test Firm Registration Number 469623, CAB Identifier DE0003 and ISED# 3469A.

1.4 EUT (Equipment under Test)

Test object: *	WBS – Wireless Blade Sensor for Wind Turbines
Model name: *	WBS
Model number: *	Version 4
Order number: *	-
FCC ID: *	2APYI-WBSU26
Serial number: *	FE20F8
PCB identifier: *	WBS
Hardware version: *	WBS26
Software version: *	WBS26-W913-26

* Declared by the applicant

1.5 Technical Data of Equipment

General EUT data			
Power supply EUT: *	Energy buffer charged by integrated photovoltaic cells. For testing a power supply was connected.		
Supply voltage EUT: *	$U_{nom} = 3.3 \text{ V}_{DC}$	$U_{min} = 3.0 \text{ V}_{DC}$	$U_{max} = 3.6 \text{ V}_{DC}$
Temperature range: *	-40 °C to +60 °C		
Lowest / highest internal frequency: *	DC to 913.2 MHz		

* Declared by the applicant

Radio part	
Fulfil radio specification: * ¹	Proprietary
Radio chip: * ¹	STM32WL55
Antenna type: * ¹	Internal antenna: Meander line trace antenna
Antenna name: * ¹	Internal antenna: NA
Antenna gain: * ²	Internal antenna: 5.07 dBi (typical)
Antenna connector: * ¹	Internal antenna: - (none)
Type of modulation: * ¹	2-FSK
Operating frequency range: * ¹	913 MHz
Number of channels: * ¹	1

*¹ Declared by the applicant

*² based on the antenna data sheet provided by the applicant

2 Evaluation Methods

2.1 RF exposure test exemptions for single sources

2.1.1 General Exemption CFR 47 §1.1307(b)(3)(i)(A)

The available maximum time-averaged power is no more than 1 mW, regardless of separation distance. This exemption may not be used in conjunction with other exemption criteria other than those in paragraph (b)(3)(ii)(A) of this section. Medical implant devices may only use this exemption and that in paragraph (b)(3)(ii)(A);

2.1.2 SAR Based Exemption CFR 47 §1.1307(b)(3)(i)(B)

The available maximum time-averaged power of effective radiated power (ERP), whichever is greater, is less than or equal to the threshold P_{th} (mW) described in the following formula. This method shall only be used at separation distances (cm) from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz inclusive.

For the following separation distances [d] and frequency ranges P_{th} is given by the following formulas

	0.5 cm ≤ d ≤ 20cm	20 cm < d ≤ 40 cm
0.3 GHz ≤ f < 1.5 GHz	$P_{th}(mW) = ERP_{20cm} \left(\frac{d}{20} \right)^x$ $ERP_{20cm}(mW) = 2040f$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$	$P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm}(mW) = 2040f$
1.5 GHz ≤ f ≤ 6 GHz	$P_{th}(mW) = ERP_{20cm} \left(\frac{d}{20} \right)^x$ $ERP_{20cm}(mW) = 3060$ $x = -\log_{10} \left(\frac{60}{ERP_{20cm}\sqrt{f}} \right)$	$P_{th}(mW) = ERP_{20cm}$ $ERP_{20cm}(mW) = 3060$

Relaxation for extremities according to 2.1.1 [3]

Finally, when 10-g extremity SAR applies, SAR test exemption may be considered by applying a factor of 2.5 to the SAR-based exemption thresholds.

2.1.3 MPE Based Exemption CFR 47 §1.1307(b)(3)(i)(C)

By using Table 1 and the minimum separation distance (d in meters) from the body of a nearby person for the frequency (f in MHz) at which the source operates, the ERP (watts) is no more than the calculated value prescribed for that frequency. For the exemption in Table 1 to apply, d must be at least $\lambda/2\pi$, where λ is the free-space operating wavelength in meters. If the ERP of a single RF source is not easily obtained, then the available maximum time-averaged power may be used in lieu of ERP if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole (1.64 linear value).

RF Source frequency [MHz]	Threshold ERP [W]
0.3 - 1.34	$1920 d^2$
1.34 - 30	$3450 d^2/f^2$
30 - 300	$3.83 d^2$
300 - 1500	$0.0128 d^2/f$
1500 - 100000	$19.2 d^2$

d : Minimal separation distance from antenna to the user

2.1.4 Stand-alone MPE evaluation limits

The human exposure to RF emissions from such devices could be evaluated based on the MPE limits adopted by the FCC for electric and magnetic field strength and / or power density. The limits for General Population / Uncontrolled Exposure are given in the following table from CFR 47 §1.1310(e)1:

Frequency range [MHz]	Electric field strength (E) [V/m]	Magnetic field strength (H) [A/m]	Power density (S) [mW/cm ²]	Averaging time [min]
(i)Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	*(100)	≤6
3.0 – 30	1842/f	4.89/f	*(900/f ²)	<6
30 – 300	61.4	0.163	1.0	<6
300 – 1,500			f/300	<6
1,500 – 100,000			5	<6
(ii)Limits for General Population / Uncontrolled Exposure				
0.3 – 1.34	614	1.63	*(100)	< 30
1.34 – 30	824/f	2.19/f	*(180/f ²)	< 30
30 – 300	27.5	0.073	0.2	< 30
300 – 1500			f/1500	< 30
1500 – 100,000			1.0	< 30

Note: f = frequency in MHz; * Plane – wave equivalent power density

The power density is calculated as follows:

$$S = \frac{P \cdot G \cdot D}{4 \cdot \pi \cdot d^2}$$

Where:

P: conducted power

G: Antenna gain (linear)

D: Duty Cycle

d: Minimal separation distance from antenna to the user

2.2 RF exposure test exemptions for simultaneous transmission sources

2.2.1 1 mW Test Exemption for simultaneous transmission sources

As discussed in CFR 47 §1.1307(b)(3)(ii)(A) [1] the 1 mW exemption intended for single transmitters may be also applied to simultaneous transmission conditions, within the same host device, according one of the following criteria:

- When the maximum available power of each individual transmitting antenna with the same time averaging period is ≤ 1 mW, and the nearest parts of the antenna structures of the simultaneously operating transmitters are separated by at least 2 cm
- When the aggregate maximum available power of all transmitting antennas is ≤ 1 mW in the same time-averaging period

This exemption may not be combined with any other exemption.

2.2.2 Simultaneous transmission SAR based and MPE based test exemptions

Although this is not a module integration in the sense of product approval, the procedure for simultaneous transmission specified in KDB 447498 D04 Interim General RF Exposure Guidance v01 [3] in chapter 2.2 was taken into account:

According to the RF exposure KDB 447498 D04 General RF Exposure Guidance v01 [3] in chapter 2.2.2: This case is described in detail in CFR 47 §1.1307(b)(3)(ii)(B) and covers the situations where both SAR-based and MPE-based exemption may be considered for test exemption in fixed, mobile, or portable device exposure conditions. For these cases, a device with multiple RF sources transmitting simultaneously will be considered an RF exempt device if the condition of the following formular is satisfied.

$$\sum_{i=1}^a \frac{P_i}{P_{th,i}} + \sum_{j=1}^b \frac{ERP_j}{ERP_{th,j}} + \sum_{k=1}^c \frac{Evaluated_k}{Exposure\ Limit_k} \leq 1$$

For these test exemptions to apply, the maximum output power, duty factor, and other applicable parameters used in the standalone ERP determination tests, must be the same, or corresponding to a more conservative choice, than those required for simultaneous transmission.

Simultaneous transmission MPE test exclusion applies when the sum of the MPE ratios for all simultaneously transmitting antennas incorporated in a host device is ≤ 1.0 , according to calculated/estimated, numerically modelled, or measured field strengths or power density. The MPE ratio of each antenna is determined at the minimum test separation distance required by the operating configurations and exposure conditions of the host device, according to the ratio of field strengths or power density to the MPE limit at the test frequency.

2.2.3 Test exemption based on the SAR to Peak Location Separation Ratio

When the ERP-based condition in the previous section does not apply, a test exemption may be still applicable based on the SAR to peak location separation ratio (SPLSR) procedure.

In this case, the simultaneously transmitting antennas in each operating mode and exposure condition combination must be considered one pair at a time to determine the SPLSR that qualifies for the additional test exemption.

This ratio is defined as:

$$SPLSR = (SAR_1 + SAR_2)^{\frac{1.5}{R_i}}$$

Where: SAR₁ and SAR₂ = highest reported SAR or estimated SAR values for the two sources in the pair i, and R_i is their distance in mm.

When SPLSR ≤ 0.04 (rounded to two decimal digits), for all antenna pairs in the configuration, then the device qualifies for 1 g SAR test exemption.

When 10 g SAR applies (e.g. for extremities) the corresponding test exemption condition is SPLSR ≤ 0.10. If any antenna pair does not qualify for simultaneous transmission SAR test exemption, then the device must be tested for SAR compliance, according to the enlarged zoom scan and volume scan post-processing procedures in KDB Pub. 865664 D01.

3 Results of evaluation

3.1 Used evaluation methods

RF Exposure test exemptions for single sources			
Used	Method	See sub-clause	Comment
☐	General Exemption acc. CFR 47 §1.1307(b)(3)(i)(A)	2.1.1	-
☐	SAR Based Exemption acc. CFR 47 §1.1307(b)(3)(i)(B)	2.1.2	-
☐	MPE Based Exemption acc. CFR 47 §1.1307(b)(3)(i)(C)	0	-
☒	MPE Calculation	2.1.4	-

RF Exposure test exemptions for simultaneous transmission sources			
Used	Method	See sub-clause	Comment
☒	Not applicable	-	No simultaneous possible
☐	1 mW test Exemption acc. 2.2.1 [3]	2.2.1	-
☐	SAR Based Exemption acc. 2.2.2 [3]	2.2.2	-
☐	MPE Based Exemption acc. 2.2.2 [3]	2.2.2	-
☐	SAR to Peak location separation ratio acc. 2.2.3 [3]	2.2.3	-

3.2 Evaluation Distance

The EUT has been assessed at a 20 cm distance as declared by the applicant.

3.3 MPE calculation results

As declared by the applicant, a tune-up of +3 dB was used.

P _{con} [dBm] incl. tune-up	P _{con} [mW] incl. tune-up	Antenna gain [dBi]	Cable attenuation [dB]	P _{e.i.r.p} [dBm]	P _{e.i.r.p} [mW]	P _{e.r.p} [dBm]	P _{e.r.p} [mW]
3.70	2.34	5.07	0.00	8.77	7.53	6.62	4.59
Frequency [MHz]	P _{e.i.r.p} [mW]	Duty cycle D %	Distance d [cm]	S [mW/cm ²]	S _{limit} [mW/cm ²]	Result	
913.000	7.53	100	20.0	0.001	1.000	exempted	

The power value has been extracted from RF test report F251879E1 issued by NMI TESTLAB GmbH.

The antenna gain value has been taken from the antenna data sheets provided by the applicant.

4 Conclusion

The EUT is compliant to the limits given in CFR 47 § 1.1310(e)(1) in a separation distance of 20 cm.

5 Report History

Report Number	Date	Comment
F251879E2	10.08.2026	Initial evaluation report
-	-	-
-	-	-

----- end of evaluation report -----