

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Table Reader

Model No.: 1762

Trade Name: BlueSupra

Issued to

YOKE Industrial Corp.

#39,33rd Road, Taichung Industrial Park, Taichung 407, Taiwan, R.O.C

Issued by

Compliance Certification Services Inc.

Wugu Laboratory

No.11, Wugong 6th Rd., Wugu Dist.,

New Taipei City, Taiwan. (R.O.C.)

Issued Date: November 13, 2020

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: T200918W02-RP

Page: 2 / 35
Rev.: 01

Revision History

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		November 06, 2020		Initial Issue	ALL	May Lin
01		November 13, 2020		See the following Note Rev. (01)	P.19-22	May Lin

Rev (01):

1. Added the remark.



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. TEST METHODOLOGY	6
3.1 EUT CONFIGURATION.....	6
3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	6
3.3 DESCRIPTION OF TEST MODES	8
4. TEST SUMMARY.....	9
5. INSTRUMENT CALIBRATION.....	10
5.1 MEASURING INSTRUMENT CALIBRATION	10
5.2 MEASUREMENT EQUIPMENT USED	10
5.3 MEASUREMENT UNCERTAINTY	11
6. FACILITIES AND ACCREDITATIONS.....	12
6.1 FACILITIES.....	12
6.2 EQUIPMENT	12
7. SETUP OF EQUIPMENT UNDER TEST	13
7.1 SETUP CONFIGURATION OF EUT	13
7.2 SUPPORT EQUIPMENT	13
8. FCC PART 15.225 REQUIREMENTS.....	14
8.1 OCCUPIED BANDWIDTH (99%) AND 20 DB BANDWIDTH.....	14
8.2 RADIATED EMISSIONS	16
8.3 FREQUENCY STABILITY.....	29
8.4 POWERLINE CONDUCTED EMISSIONS	32
APPENDIX I PHOTOGRAPHS OF TEST SETUP.....	A-1



Report No.: T200918W02-RP

Page: 4 / 35
Rev.: 01

1. TEST RESULT CERTIFICATION

Applicant: YOKE Industrial Corp.
#39,33rd Road, Taichung Industrial Park, Taichung 407,
Taiwan, R.O.C

Manufacturer: YOKE Industrial Corp.
#39,33rd Road, Taichung Industrial Park, Taichung 407,
Taiwan, R.O.C

Equipment Under Test: Table Reader

Trade Name: BlueSupra

Model No.: 1762

Date of Test: September 24 ~ 30, 2020

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

Statements of Conformity
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.225.

The test results of this report relate only to the tested sample identified in this report.

Approved by:

Kevin Tsai
Deputy Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Table Reader
Trade	BlueSupra
Model No.	1762
Model Discrepancy	N/A
Received Date	September 18, 2020
Power Supply	EUT Power by Host System
Frequency Range	13.56MHz
Modulation Technique	ASK
Number of Channels	1 Channel

Remark: The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47 Part 15.207, 15.209, 15.225.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6



- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.3 DESCRIPTION OF TEST MODES

The EUT had been tested under engineering test mode condition and the EUT staying in continuous transmitting mode.

All modes and data rates were investigated and it was determined that ISO 14443A/B and ISO 18092 Type y, 106/212/424/848 kbps.

All data rates were investigated and it was determined that 106 Kbps was considered worst-case. Therefore, all testing was performed in 106 Kbps mode.

3.3.1 The worst mode of measurement

Radiated Emission Measurement	
Test Condition	Band edge, Emission for Unwanted and Fundamental
Power supply Mode	Mode 1: EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Position	☐ Placed in fixed position. ☒ Placed in fixed position at X-Plane (E2-Plane) ☐ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Host System
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis X and two polarity, for radiated measurement. The worst case(X-Plane) were recorded in this report.
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.



Report No.: T200918W02-RP

Page: 9 / 35
Rev.: 01

4. TEST SUMMARY

FCC Standard Sec.	Chapter	Test Item	Result
15.203	2	Antenna Requirement	Pass
15.215	8.1	Occupied Bandwidth (99%) and 20dB Bandwidth	Pass
15.209	8.2	Radiated Emissions	Pass
15.225	8.3	Frequency Stability	Pass
15.207	8.4	AC Power-line Conducted Emission	Pass

5. INSTRUMENT CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

5.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
Coaxial Cable	Woken	WC12	CC003	06/29/2020	06/28/2021
Signal Analyzer	R&S	FSV 40	101073	09/17/2020	09/16/2021
Thermostatic/ Humidity Chamber	TAICHY	MHG-150LF	930619	10/04/2019	10/03/2020
Software	N/A				

Wugu 966 Chamber A					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/24/2020	07/23/2021
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/25/2020	02/24/2021
Digital Thermo- Hygro Meter	WISEWIND	1206	D07	01/15/2020	01/14/2021
Loop Ant	COM-POWER	AL-130	121051	03/27/2020	03/26/2021
Pre-Amplifier	EMEC	EM330	060609	02/25/2020	02/24/2021
PSA Series Spectrum Analyzer	Agilent	E4446A	MY46180323	07/24/2020	07/23/2021
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

AC Conducted Emissions Test Site					
Name of Equipment	Manufacturer	Model	S/N	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/29/2020	06/28/2021
EMI Test Receiver	R&S	ESCI	100064	07/17/2020	07/16/2021
LISN	SCHAFFNER	NNB 41	03/10013	02/13/2020	02/12/2021
Software	EZ-EMC(CCS-3A1-CE)				

Remark:

- Each piece of equipment is scheduled for calibration once a year and Precision Dipole is scheduled for calibration once three years.
- N.C.R. = No Calibration Request.

5.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 20dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 30M~200M	+/- 4.12
3M Semi Anechoic Chamber / 200M~1000M	+/- 4.68
3M Semi Anechoic Chamber / 1G~8G	+/- 5.18
3M Semi Anechoic Chamber / 8G~18G	+/- 5.47
3M Semi Anechoic Chamber / 18G~26G	+/- 3.81
3M Semi Anechoic Chamber / 26G~40G	+/- 3.87

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

6. FACILITIES AND ACCREDITATIONS

6.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☐ No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10: 2013 and CISPR Publication 22.

6.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, bucolical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.

Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



7. SETUP OF EQUIPMENT UNDER TEST

7.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix I for the actual connections between EUT and support equipment.

7.2 SUPPORT EQUIPMENT

No.	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	NB(J)	TOSHIBA	PT345T-00L002	N/A	PD97260H	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.


8. FCC PART 15.225 REQUIREMENTS

8.1 OCCUPIED BANDWIDTH (99%) AND 20 DB BANDWIDTH

TEST LIMIT

According to §15.215(c),

TEST CONFIGURATION



TEST PROCEDURE

Test method Refer as ANSI C63.10-2013, 6.9.2 and ANSI C63.10-2013, 6.9.3,

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. SA set RBW = 1kHz, VBW = 3kHz and Detector = Peak, to measurement 20dB Bandwidth.
4. SA set RBW = 1% ~ 5% OBW, VBW = three times the RBW and Detector = Peak, to measurement 99% Bandwidth.
5. Record the max. reading.

TEST RESULTS


No non-compliance noted

Test Condition	Frequency (MHz)	Occupied Bandwidth 99% (kHz)	20 dB Bandwidth (kHz)
NFC	13.56	2.0984	2.489

Report No.: T200918W02-RP

Test Plot

20 dB BANDWIDTH & BANDWIDTH (99%)



Date: 28 SEP 2020 17:16:33

8.2 RADIATED EMISSIONS

LIMIT

According to §15.225

- (a) The field strength of any emissions within the band 13.553 – 13.567 MHz shall not exceed 15,848 microvolts / meter at 30 meters.
- (b) Within the bands 13.410 – 13.553 MHz and 13.567 -13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts / meter at 30 meters.
- (c) Within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz the field strength of any emissions shall not exceed 106 microvolts / meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110 – 14.010 MHz and shall not exceed the general radiated emission limits in §15.209.


According to §15.225, except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μ V/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3


** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.

Test Configuration

9kHz ~ 30MHz



30MHz ~ 1GHz



TEST PROCEDURE

For 9kHz ~ 30MHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, The center of the loop shall be 1 m above the ground then to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Set the spectrum analyzer in the following setting as:
9KHz-490KHz : RBW=200Hz / VBW=1kHz / Sweep=AUTO
490KHz-30MHz : RBW=10kHz / VBW=30kHz / Sweep=AUTO
6. Repeat above procedures until the measurements for all frequencies are complete.


For 30MHz ~ 1GHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

Remark :

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open area test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Operation Mode:	Main	Test Date:	September 30, 2020
Temperature:	24.2°C	Tested by:	Jerry Chang
Humidity:	40 % RH	Polarity:	Ver.




No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
1	13.56	Peak	75.10	15.34	90.44	124.00	-33.56

Remark:

1. Radiated emissions measured were made with an instrument using peak detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
3. Limit @3m (dBuV/m) = 20*log(Limit @30m (uV)) + 40*log(30m/3m)

Operation Mode: Main
Temperature: 24.2°C
Humidity: 40 % RH

Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Hor.




No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.56	Peak	77.46	15.34	92.80	124.00	-31.20

Remark:

1. Radiated emissions measured were made with an instrument using peak detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
3. Limit @3m (dBuV/m) = 20*log(Limit @30m (uV)) + 40log(30m/3m)

Operation Mode: Mask
Temperature: 24.2°C
Humidity: 40 % RH

Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Ver.




No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.38	Peak	42.05	15.35	57.40	80.54	-23.14
2	13.55	Peak	62.36	15.34	77.70	90.47	-12.77
3	13.57	Peak	64.01	15.34	79.35	90.47	-11.12
4	13.77	Peak	41.49	15.33	56.82	80.50	-23.68

Remark:

1. Radiated emissions measured were made with an instrument using peak detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
3. Limit @3m (dBuV/m) = 20*log(Limit @30m (uV)) + 40log(30m/3m)

Operation Mode:	Mask	Test Date:	September 30, 2020
Temperature:	24.2°C	Tested by:	Jerry Chang
Humidity:	40 % RH	Polarity:	Hor.




No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.40	Peak	41.17	15.35	56.52	80.54	-24.02
2	13.55	Peak	62.13	15.34	77.47	90.47	-13.00
3	13.57	Peak	63.93	15.34	79.27	90.47	-11.20
4	13.77	Peak	40.80	15.33	56.13	80.50	-24.37

Remark:

1. Radiated emissions measured were made with an instrument using peak detector mode.
2. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
3. Limit @3m (dBuV/m) = 20*log(Limit @30m (uV)) + 40log(30m/3m)

Operation Mode: Normal Link
Temperature: 24.2°C
Humidity: 40 % RH


Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Ver.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	34.85	Peak	40.89	-6.07	34.82	40.00	-5.18
2	207.51	Peak	40.87	-11.80	29.07	43.50	-14.43
3	285.11	Peak	36.09	-8.74	27.35	46.00	-18.65
4	517.91	Peak	27.69	-3.11	24.58	46.00	-21.42
5	807.94	Peak	25.97	1.82	27.79	46.00	-18.21
6	946.65	Peak	25.19	4.13	29.32	46.00	-16.68

Operation Mode: Normal Link
Temperature: 24.2°C
Humidity: 40 % RH

Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Hor.




No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	114.39	Peak	39.98	-9.66	30.32	43.50	-13.18
2	207.51	Peak	47.86	-11.80	36.06	43.50	-7.44
3	285.11	Peak	43.09	-8.74	34.35	46.00	-11.65
4	527.61	Peak	29.79	-2.90	26.89	46.00	-19.11
5	662.44	Peak	26.82	-0.61	26.21	46.00	-19.79
6	948.59	Peak	27.05	4.34	31.39	46.00	-14.61

9kHz ~ 30MHz

Operation Mode: TX mode
Temperature: 24.2°C
Humidity: 40 % RH


Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Ver.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	0.55	Peak	40.29	13.87	54.16	72.82	-18.66
2	1.36	Peak	29.29	14.05	43.34	64.94	-21.60
3	7.42	Peak	16.43	15.28	31.71	69.54	-37.83
4	10.00	Peak	13.43	15.55	28.98	69.54	-40.56
5	23.16	Peak	13.89	14.33	28.22	69.54	-41.32
6	26.70	Peak	11.97	13.60	25.57	69.54	-43.97

Operation Mode: TX mode
Temperature: 24.2°C
Humidity: 40 % RH

Test Date: September 30, 2020
Tested by: Jerry Chang
Polarity: Hor.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	0.55	Peak	40.77	13.87	54.64	72.82	-18.18
2	4.75	Peak	17.54	14.86	32.40	69.54	-37.14
3	9.16	Peak	14.38	15.47	29.85	69.54	-39.69
4	18.00	Peak	11.82	15.15	26.97	69.54	-42.57
5	24.00	Peak	13.80	14.15	27.95	69.54	-41.59
6	28.14	Peak	11.68	13.33	25.01	69.54	-44.53



Report No.: T200918W02-RP

Page: 27 / 35
Rev.: 01


30MHz ~ 1GHz

Operation Mode: TX mode
Temperature: 24.2°C
Humidity: 40 % RH


Test Date: September 30, 2020
Tested by: Jerry Chang

Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB	Antenna Pol. (V/H)
34.85	Peak	41.09	-6.07	35.02	40.00	-4.98	V
212.36	Peak	45.55	-11.92	33.63	43.50	-9.87	V
333.61	Peak	37.18	-7.80	29.38	46.00	-16.62	V
544.10	Peak	30.90	-2.40	28.50	46.00	-17.50	V
764.29	Peak	31.71	1.03	32.74	46.00	-13.26	V
949.56	Peak	31.14	4.44	35.58	46.00	-10.42	V
34.85	Peak	30.78	-6.07	24.71	40.00	-15.29	H
125.06	Peak	37.79	-9.07	28.72	43.50	-14.78	H
212.36	Peak	47.41	-11.92	35.49	43.50	-8.01	H
285.11	Peak	38.05	-8.74	29.31	46.00	-16.69	H
551.86	Peak	29.73	-2.47	27.26	46.00	-18.74	H
936.95	Peak	26.39	3.57	29.96	46.00	-16.04	H

Vertical



Horizontal




8.3 FREQUENCY STABILITY

LIMIT

According to §15.225(e), the frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Configuration

Temperature and Voltage Measurement (under normal and extreme test conditions)





TEST PROCEDURE

1. Turn the EUT off, and place it inside the environmental temperature chamber.
2. Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
3. Set the spectrum analyzer as RBW=1kHz, VBW = RBW, Span = 200kHz, Sweep = auto.
4. Turn the EUT on and record the operating frequency at startup and two, five, and ten minutes after the EUT is energized.
5. Switch off the EUT and Lower the chamber temperature by not more than 10 °C and allow the temperature inside the chamber to stabilize.
6. Mark the peak frequency and measure the frequency tolerance using frequency counter function.
7. Repeat step 4 through step 6 down to the lowest specified temperature.

TEST RESULTS

No non-compliance noted.



Report No.: T200918W02-RP

Page: 31 / 35
Rev.: 01

TEST DATA

Temperature: 24°C

Test Date: September 29, 2020

Humidity: 50% RH

Tested by: Jane Wang

Condition			Frequency Error (ppm)									
Temperature	Modulation Mode	Test Freq.	0 min	2 min	5 min	10 min	0 min	2 min	5 min	10 min	Limit (ppm)	Result
			Normal									
T _{25°C} V _{max}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass
T _{25°C} V _{min}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
			Extreme									
T _{70°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass
T _{60°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{50°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{40°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{30°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{20°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{10°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{0°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{-10°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass
T _{-20°C} V _{nom}	CW	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass

Remark: V_{nom}: 5
V_{max}: 5.75
V_{min}: 4.25

8.4 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.



Report No.: T200918W02-RP


Page: 33 / 35
Rev.: 01

TEST RESULTS

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.


TEST DATA

Test Mode:	Mode 1	Test Date	September 24, 2020
Phase:	Line	Test Engineer	Rick Lee
Temp/Hum	24(°C) / 50%RH		



No.	Frequency	QuasiPeak reading	Average reading	Correction factor	QuasiPeak result	Average result	QuasiPeak limit	Average limit	QuasiPeak margin	Average margin	Remark
	(MHz)	(dBuV)	(dBuV)	(dB)	(dBuV)	(dBuV)	(dBuV)	(dBuV)	(dB)	(dB)	
1*	0.2500	25.70	19.76	10.21	35.91	29.97	61.76	51.76	-25.85	-21.79	Pass
2	0.3900	20.74	13.61	10.22	30.96	23.83	58.06	48.06	-27.10	-24.23	Pass
3	0.9660	18.99	11.23	10.24	29.23	21.47	56.00	46.00	-26.77	-24.53	Pass
4	2.8780	18.54	8.79	10.28	28.82	19.07	56.00	46.00	-27.18	-26.93	Pass
5	3.3740	16.40	6.70	10.29	26.69	16.99	56.00	46.00	-29.31	-29.01	Pass
6	11.8180	24.14	17.02	10.40	34.54	27.42	60.00	50.00	-25.46	-22.58	Pass

Test Mode:	Mode 1	Test Date	September 24, 2020
Phase:	Neutral	Test Engineer	Rick Lee
Temp/Hum	24(°C) / 50%RH		



No.	Frequency (MHz)	QuasiPeak reading (dBuV)	Average reading (dBuV)	Correction factor (dB)	QuasiPeak result (dBuV)	Average result (dBuV)	QuasiPeak limit (dBuV)	Average limit (dBuV)	QuasiPeak margin (dB)	Average margin (dB)	Remark
1	0.3180	28.55	18.13	10.19	38.74	28.32	59.76	49.76	-21.02	-21.44	Pass
2*	0.3860	30.77	19.23	10.19	40.96	29.42	58.15	48.15	-17.19	-18.73	Pass
3	0.4860	27.18	17.43	10.19	37.37	27.62	56.24	46.24	-18.87	-18.62	Pass
4	1.0380	19.68	11.65	10.21	29.89	21.86	56.00	46.00	-26.11	-24.14	Pass
5	1.1580	22.21	13.03	10.21	32.42	23.24	56.00	46.00	-23.58	-22.76	Pass
6	1.9900	18.80	10.70	10.22	29.02	20.92	56.00	46.00	-26.98	-25.08	Pass

--End of Test Report--