

TEST REPORT

Product Name : Translator Earbuds
Brand Mark : Timekettle
Model No. : M3
Extension model : L1, L2, L3, S1, S2, S3, X1, X2, X3
Report Number : BLA-EMC-202205-A4806
FCC ID : 2AQ2G-M3
Date of Sample Receipt : 2022/5/19
Date of Test : 2022/5/19 to 2022/6/30
Date of Issue : 2022/6/30
Test Standard : 47 CFR Part 1.1307, Part 2.1093, KDB 447498
Test Result : Pass

Prepared for:

Shenzhen Timekettle Technologies Co., Ltd
Room 402, Building 3B, Minqi Science Park, Nanshan
District, Shenzhen, Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyao Sub-District, Baoan District,
Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by:

Jozu
Blue Zhong

Approved by:

Review by:

Sueels

Date:

2022/6/30



REPORT REVISE RECORD

Version No.	Date	Description
00	2022/6/30	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	4
2	GENERAL INFORMATION	5
3	GENERAL DESCRIPTION OF E.U.T.	5
4	LABORATORY LOCATION	6
5	RF EXPOSURE COMPLIANCE REQUIREMENT	7
5.1	STANDARD REQUIREMENT	7
5.2	LIMITS	7
5.3	EUT RF EXPOSURE	7

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
RF Exposure	47 CFR Part 1.1307, Part 2.1093, KDB 447498	CFR 47 Part 2.1093	CFR 47 Part 2.1093	Pass

2 GENERAL INFORMATION

Applicant	Shenzhen Timekettle Technologies Co., Ltd
Address	Room 402, Building 3B, Minqi Science Park, Nanshan District, Shenzhen, Guangdong, China
Manufacturer	Guangdong Mingyang Smart Technology Co., Ltd
Address	Room 413, Hongdu Business Building Building A, Anle Industrial Area. Haile Community Xinan Street, Baoan District Shenzhen. China
Factory	Guangdong Mingyang Smart Technology Co., Ltd
Address	Building 1, No.111 Nanjiang Road, Humen Town, Dongguan City, Guangdong Province
Product Name	Translator Earbuds
Test Model No.	M3
Extension model	L1, L2, L3, S1, S2, S3, X1, X2, X3
Note	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.2
Software Version	V1.3.4

BLE

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi(Provided by the applicant)

BDR+EDR

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK, pi/4DQPSK, 8DPSK
Channel Spacing:	1MHz
Number of Channels:	79
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi(Provided by the applicant)

NOTE : This report is only for left earphone.

4 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province,
China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

5 RF EXPOSURE COMPLIANCE REQUIREMENT

5.1 STANDARD REQUIREMENT

According to KDB447498D01 General RF Exposure Guidance v06

Standalone SAR test exclusion considerations

Unless specifically required by the published RF exposure KDB procedures, standalone 1-g head or body and 10-g extremity SAR evaluation for general population exposure conditions, by measurement or numerical simulation, is not required when the corresponding SAR Exclusion Threshold condition, listed below, is satisfied.

5.2 LIMITS

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW})/(\text{min. test separation distance, mm})] \cdot$

$\sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

$f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation¹⁷

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion

5.3 EUT RF EXPOSURE

Operational Mode: EDR (8-DPSK worst case)						
Channel	Maximum Peak Conducted Output Power (dBm)	Tune up tolerance (dB)	Maximum tune-up Power		Calculated value	Exclusion threshold
			(dBm)	(mW)		
2402MHz	2.537	±1	3.537	2.26	0.70	3.0
2441MHz	3.259	±1	4.259	2.67	0.83	
2480MHz	2.867	±1	3.867	2.44	0.77	
						3.0
Operational Mode: BLE						
2402 MHz	0.912	±1	1.912	1.55	0.48	
2442 MHz	2.617	±1	3.617	2.30	0.72	
2480 MHz	2.542	±1	3.542	2.26	0.71	
Conclusion: the calculated value ≤3.0, SAR is exempted.						

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia