TEST REPORT

Product Name	:	Translator Earbuds
Brand Mark	:	Timekettle
Model No.	:	M3
Extension model	:	L1, L2, L3, S1, S2, S3, X1, X2, X3
Report Number	:	BLA-EMC-202205-A4804
FCC ID	:	2AQ2G-M3
Date of Sample Receipt	:	2022/5/19
Date of Test	:	2022/5/19 to 2022/6/24
Date of Issue	:	2022/6/24
Test Standard	:	47 CFR Part 15, Subpart C 15.247
Test Result	:	Pass

Prepared for:

Shenzhen Timekettle Technologies Co., Ltd
Room 402, Building 3B, Minqi Science Park, Nanshan District, Shenzhen,Guangdong, China

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
TEL: +86-755-23059481

Compiled by: Review by:
Approved by: Date: 2022/6/24

REPORT REVISE RECORD

Version No.	Date	Description
00	2022/6/24	Original

BlueAsia

TABLE OF CONTENTS

1 TEST SUMMARY 5
2 GENERAL INFORMATION 6
3 GENERAL DESCRIPTION OF E.U.T. 6
4 TEST ENVIRONMENT 7
5 TEST MODE 7
6 MEASUREMENT UNCERTAINTY 7
7 DESCRIPTION OF SUPPORT UNIT 8
8 LABORATORY LOCATION 8
9 TEST INSTRUMENTS LIST 9
10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ) 12
10.1 LIMITS 12
10.2 BLOCK DIAGRAM OF TEST SETUP 12
10.3 PROCEDURE 12
10.4 TEST DATA 14
11 CONDUCTED BAND EDGES MEASUREMENT 16
11.1 LIMITS 16
11.2 BLOCK DIAGRAM OF TEST SETUP 16
11.3 TEST DATA 17
12 RADIATED SPURIOUS EMISSIONS 18
12.1 LIMITS 18
12.2 BLOCK DIAGRAM OF TEST SETUP 19
12.3 PROCEDURE 19
12.4 TEST DATA 21
13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS 29
13.1 LIMITS 29
13.2 BLOCK DIAGRAM OF TEST SETUP 30
13.3 PROCEDURE 30
13.4 TEST DATA 32
14 CONDUCTED SPURIOUS EMISSIONS 36
14.1 LIMITS 36

BlueAsia

14.2 BLOCK DIAGRAM OF TEST SETUP 36
14.3 TEST DATA 37

15 POWER SPECTRUM DENSITY 38

15.1 LIMITS 38
15.2 BLOCK DIAGRAM OF TEST SETUP 38
15.3 TEST DATA 38

16 CONDUCTED PEAK OUTPUT POWER 39

16.1 LIMITS 39
16.2 BLOCK DIAGRAM OF TEST SETUP 39
16.3 TEST DATA 40

17 MINIMUM 6DB BANDWIDTH 41

17.1 LIMITS 41
17.2 BLOCK DIAGRAM OF TEST SETUP 41
17.3 TEST DATA 41

18 ANTENNA REQUIREMENT 42

18.1 CONCLUSION 42

19 APPENDIX 43

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 58

APPENDIX B: PHOTOGRAPHS OF EUT 60

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

BlueAsia

2 GENERAL INFORMATION

Applicant	Shenzhen Timekettle Technologies Co., Ltd
Address	Room 402, Building 3B, Minqi Science Park, Nanshan District, Shenzhen,Guangdong, China
Manufacturer	Guangdong Mingyang Smart Technology Co.,Ltd
Address	Room 413， Hongdu Business BuildingBuilding A， Anle Industrial Area. Haile Community Xinan Street，Baoan DistrictShenzhen. China
Factory	Guangdong Mingyang Smart Technology Co.,Ltd
Address	Building 1, No.111 Nanjiang Road, Humen Town, Dongguan City, Guangdong Province
Product Name	Translator Earbuds
Test Model No.	M3
Extension model	L1, L2, L3, S1, S2, S3, X1, X2, X3
Note	All above models are identical in the same PCB layout, interior structure and electrical circuits. The differences are model name for commercial purpose.

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	V1.2
Software Version	V1.3.4

Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Chip Antenna
Antenna Gain:	2.5dBi(Provided by the applicant)

NOTE ： This report is only for right earphone.

BlueAsia

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode
Remark:Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

BlueAsia

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter (UGREEN)	UGREEN	CD112	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

BlueAsia

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Shield room	SKET	833	N/A	25/11/2020	24/11/2023
Receiver	R&S	ESPI3	101082	24/9/2021	23/9/2022
LISN	R&S	ENV216	3560.6550.15	24/9/2021	23/9/2022
LISN	AT	AT166-2	AKK1806000003	26/9/2021	25/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Radiated Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022

BlueAsia

Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Radiated Emissions which fall in the restricted bands					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Chamber	SKET	966	N/A	10/11/2020	9/11/2023
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Receiver	R&S	ESR7	101199	24/9/2021	23/9/2022
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	26/9/2020	25/9/2022
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	26/9/2020	25/9/2022
Amplifier	SKET	LNPA-0118-45	N/A	24/9/2021	23/9/2022
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	26/9/2020	25/9/2022

Test Equipment Of Conducted Spurious Emissions					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Power Spectrum Density					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**

BlueAsia

Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Conducted Peak Output Power					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	**Manufacturer**	**Model**	**S/N**	**Cal.Date**	**Cal.Due**
Spectrum	R&S	FSP40	100817	24/9/2021	23/9/2022
Spectrum	Agilent	N9020A	MY49100060	24/9/2021	23/9/2022
Signal Generator	Agilent	N5182A	MY49060650	24/9/2021	23/9/2022
Signal Generator	Agilent	E8257D	MY44320250	24/9/2021	23/9/2022

BlueAsia

10 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

10.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dBμV)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50
*Decreases with the logarithm of the frequency.		

10.2 BLOCK DIAGRAM OF TEST SETUP



10.3 PROCEDURE

1) The mains terminal disturbance voltage test was conducted in a shielded room.
2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.
Remark: LISN=Read Level+ Cable Loss+ LISN Factor

BlueAsia

10.4 TEST DATA

[TestMode: TX]; [Line: Line] ;[Power:AC120V/60Hz]



Site
Phase: *L1*
Temperature: (C)
Limit: FCC Class B Conduction(QP)
Power:
Humidity: %RH
EUT: headset
M/N: M3
Mode: BLE TX mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.7580	19.29	9.89	29.18	56.00	-26.82	QP	
2	*	0.7580	13.65	9.89	23.54	46.00	-22.46	AVG	
3		1.3580	12.68	9.93	22.61	56.00	-33.39	QP	
4		1.3580	10.02	9.93	19.95	46.00	-26.05	AVG	
5		2.9700	8.54	9.97	18.51	56.00	-37.49	QP	
6		2.9700	3.58	9.97	13.55	46.00	-32.45	AVG	
7		6.5100	8.89	10.08	18.97	60.00	-41.03	QP	
8		6.5100	3.09	10.08	13.17	50.00	-36.83	AVG	
9		12.1059	15.29	10.27	25.56	60.00	-34.44	QP	
10		12.1059	7.85	10.27	18.12	50.00	-31.88	AVG	
11		17.9940	8.54	10.41	18.95	60.00	-41.05	QP	
12		17.9940	2.08	10.41	12.49	50.00	-37.51	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX]; [Line: Nutral] ;[Power:AC120V/60Hz]

Conducted Emission Measurement

Project No.: CE Data :#4 2022/6/2 14:03:33



Site Phase: N Temperature: (C)
Limit: FCC Class B Conduction(QP) Power: Humidity: %RH
EUT: headset
M/N: M3
Mode: BLE TX mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB	dBuV	dBuV	dB	Detector	Comment
1		0.5500	16.46	9.80	26.26	56.00	-29.74	QP	
2		0.5500	11.40	9.80	21.20	46.00	-24.80	AVG	
3		0.7620	17.47	9.82	27.29	56.00	-28.71	QP	
4	*	0.7620	11.80	9.82	21.62	46.00	-24.38	AVG	
5		1.5859	11.85	9.85	21.70	56.00	-34.30	QP	
6		1.5859	6.87	9.85	16.72	46.00	-29.28	AVG	
7		4.1420	5.70	9.91	15.61	56.00	-40.39	QP	
8		4.1420	-0.04	9.91	9.87	46.00	-36.13	AVG	
9		12.3820	12.63	10.24	22.87	60.00	-37.13	QP	
10		12.3820	4.52	10.24	14.76	50.00	-35.24	AVG	
11		17.6380	8.43	10.37	18.80	60.00	-41.20	QP	
12		17.6380	1.01	10.37	11.38	50.00	-38.62	AVG	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

11 CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

11.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

11.2 BLOCK DIAGRAM OF TEST SETUP



11.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

12 RADIATED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

12.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

12.2 BLOCK DIAGRAM OF TEST SETUP







12.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.

Remark:
1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level =Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor
3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. fundamental frequency is blocked by filter, and only spurious emission is shown.
4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

12.4 TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]



Site
Limit: FCC Part15 RE-Class B_30-1000MHz
EUT: headset
M/N: M3
Mode: BLE TX mode
Note:

Polarization: ***Horizontal***
Power:
Distance:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	54.2608	0.23	23.61	23.84	40.00	-16.16	peak	150	64	P	
2	151.0663	5.94	23.87	29.81	43.50	-13.69	peak	150	256	P	
3	192.4183	15.04	21.59	36.63	43.50	-6.87	peak	150	192	P	
4 *	276.1234	15.55	24.08	39.63	46.00	-6.37	peak	150	31	P	
5	370.7022	6.15	27.00	33.15	46.00	-12.85	peak	150	71	P	
6	869.1300	-0.49	36.41	35.92	46.00	-10.08	peak	150	273	P	

*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]



Site
Limit: FCC Part15 RE-Class B_30-1000MHz
EUT: headset
M/N: M3
Mode: BLE TX mode
Note:

Polarization: *Vertical*
Power:
Distance:

Temperature: (C)
Humidity: %RH

No.	Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Azimuth (deg.)	P/F	Remark
1	30.6377	5.77	22.16	27.93	40.00	-12.07	peak	150	103	P	
2	117.7724	10.58	22.79	33.37	43.50	-10.13	peak	150	91	P	
3	180.0164	11.83	22.11	33.94	43.50	-9.56	peak	150	37	P	
4	297.2238	6.35	24.51	30.86	46.00	-15.14	peak	150	306	P	
5	370.7022	7.68	27.00	34.68	46.00	-11.32	peak	150	186	P	
6 *	699.3044	5.31	33.18	38.49	46.00	-7.51	peak	150	287	P	

*:Maximum data x:Over limit !:over margin

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-L
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2402.000	40.67	-0.93	39.74	74.00	-34.26	peak	
2		3867.000	43.10	6.82	49.92	74.00	-24.08	peak	
3		4804.000	39.73	3.71	43.44	74.00	-30.56	peak	
4		7206.000	39.25	5.96	45.21	74.00	-28.79	peak	
5		9608.000	38.51	9.29	47.80	74.00	-26.20	peak	
6	*	11234.250	39.08	12.00	51.08	74.00	-22.92	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-L
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2402.000	43.88	-0.93	42.95	74.00	-31.05	peak	
2		3808.250	42.22	7.55	49.77	74.00	-24.23	peak	
3		4804.000	40.30	3.71	44.01	74.00	-29.99	peak	
4		7206.000	39.39	5.96	45.35	74.00	-28.65	peak	
5		9608.000	37.70	9.29	46.99	74.00	-27.01	peak	
6	*	11751.250	39.41	11.66	51.07	74.00	-22.93	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX mid channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-M
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2442.000	40.42	-1.09	39.33	74.00	-34.67	peak	
2		3855.250	42.81	6.97	49.78	74.00	-24.22	peak	
3		4884.000	40.21	3.34	43.55	74.00	-30.45	peak	
4		7326.000	38.82	6.44	45.26	74.00	-28.74	peak	
5		9768.000	36.65	9.63	46.28	74.00	-27.72	peak	
6	*	11328.250	39.23	11.86	51.09	74.00	-22.91	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX mid cahnnel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-M
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2442.000	41.15	-1.09	40.06	74.00	-33.94	peak	
2		3808.250	42.17	7.55	49.72	74.00	-24.28	peak	
3		4884.000	41.05	3.34	44.39	74.00	-29.61	peak	
4		7326.000	39.99	6.44	46.43	74.00	-27.57	peak	
5		9768.000	36.83	9.63	46.46	74.00	-27.54	peak	
6	*	11210.750	39.48	12.03	51.51	74.00	-22.49	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-H
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2480.000	42.01	-1.26	40.75	74.00	-33.25	peak	
2		3784.750	42.99	7.65	50.64	74.00	-23.36	peak	
3		4960.000	39.11	3.75	42.86	74.00	-31.14	peak	
4		7440.000	38.94	6.86	45.80	74.00	-28.20	peak	
5		9920.000	36.37	10.16	46.53	74.00	-27.47	peak	
6	*	11363.500	38.94	11.81	50.75	74.00	-23.25	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high cahnnel]; [Polarity: Vertical]



Site
Polarization: *Vertical*
Temperature: (C)
Limit: FCC Part15 (PK)
Power:
Humidity: %RH
EUT: headset
M/N: M3
Mode: BLE TX-H
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2480.000	41.46	-1.26	40.20	74.00	-33.80	peak	
2		3843.500	42.83	7.12	49.95	74.00	-24.05	peak	
3		4960.000	39.88	3.75	43.63	74.00	-30.37	peak	
4		7440.000	38.76	6.86	45.62	74.00	-28.38	peak	
5		9920.000	36.82	10.16	46.98	74.00	-27.02	peak	
6	*	11316.500	39.64	11.88	51.52	74.00	-22.48	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

13 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

13.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BlueAsia

13.2 BLOCK DIAGRAM OF TEST SETUP







13.3 PROCEDURE

a. For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
b. For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
c. The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
d. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
e. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
f. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
g. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
j. Repeat above procedures until all frequencies measured was complete.
Remark 1: Level= Read Level+ Cable Loss+ Antenna Factor- Preamp Factor
Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

13.4 TEST DATA

[TestMode: TX low channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-L
Note:

Polarization: *Horizontal*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	41.41	-3.93	37.48	74.00	-36.52	peak	
2	*	2390.000	42.47	-3.58	38.89	74.00	-35.11	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX low channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-L
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1		2310.000	42.37	-3.93	38.44	74.00	-35.56	peak	
2	*	2390.000	43.66	-3.58	40.08	74.00	-33.92	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Horizontal]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-H
Note:

Polarization: ***Horizontal***
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	51.62	-3.14	48.48	74.00	-25.52	peak	
2		2500.000	42.47	-3.08	39.39	74.00	-34.61	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

[TestMode: TX high channel]; [Polarity: Vertical]



Site
Limit: FCC Part15 (PK)
EUT: headset
M/N: M3
Mode: BLE TX-H
Note:

Polarization: *Vertical*
Power:

Temperature: (C)
Humidity: %RH

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	Comment
1	*	2483.500	43.18	-3.14	40.04	74.00	-33.96	peak	
2		2500.000	42.53	-3.08	39.45	74.00	-34.55	peak	

*:Maximum data x:Over limit !:over margin (Reference Only

Test Result: Pass

14 CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

14.1 LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

14.2 BLOCK DIAGRAM OF TEST SETUP



14.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

15 POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

15.1 LIMITS

Limit:	≤8dBm in any 3 kHz band during any time interval of continuous transmission

15.2 BLOCK DIAGRAM OF TEST SETUP



15.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

16 CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

16.1 LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥50 hopping channels
	0.25 for 25≤ hopping channels <50
	1 for digital modulation
2400-2483.5	1 for ≥75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

16.2 BLOCK DIAGRAM OF TEST SETUP



16.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

17 MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25℃
Humidity	55%

17.1 LIMITS

Limit:	≥500 kHz

17.2 BLOCK DIAGRAM OF TEST SETUP



17.3 TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

18 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A

18.1 CONCLUSION

Standard Requirement:
An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:
The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2.5dBi.



19 APPENDIX

Maximum Conducted Output Power

Condition	Mode	Frequency (MHz)	Antenna	Conducted Power (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	0.87	30	Pass
NVNT	BLE	2442	Ant1	3.238	30	Pass
NVNT	BLE	2480	Ant1	2.695	30	Pass

Power NVNT BLE 2402MHz Ant1



Power NVNT BLE 2442MHz Ant1



Power NVNT BLE 2480MHz Ant1



-6dB Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	-6 dB Bandwidth (MHz)	Limit -6 dB Bandwidth (MHz)	Verdict
NVNT	BLE	2402	Ant1	0.656	0.5	Pass
NVNT	BLE	2442	Ant1	0.654	0.5	Pass
NVNT	BLE	2480	Ant1	0.643	0.5	Pass

-6dB Bandwidth NVNT BLE 2402MHz Ant1



-6dB Bandwidth NVNT BLE 2442MHz Ant1



-6dB Bandwidth NVNT BLE 2480MHz Ant1



Occupied Channel Bandwidth

Condition	Mode	Frequency (MHz)	Antenna	99% OBW (MHz)
NVNT	BLE	2402	Ant1	1.010367404
NVNT	BLE	2442	Ant1	1.009782353
NVNT	BLE	2480	Ant1	1.007877739

OBW NVNT BLE 2402MHz Ant1



OBW NVNT BLE 2442MHz Ant1



OBW NVNT BLE 2480MHz Ant1



Maximum Power Spectral Density Level

Condition	Mode	Frequency (MHz)	Antenna	Max PSD (dBm)	Limit (dBm)	Verdict
NVNT	BLE	2402	Ant1	-9.875	8	Pass
NVNT	BLE	2442	Ant1	-9.318	8	Pass
NVNT	BLE	2480	Ant1	-8.929	8	Pass

PSD NVNT BLE 2402MHz Ant1

PSD NVNT BLE 2442MHz Ant1

PSD NVNT BLE 2480MHz Ant1

Band Edge

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-54.18	-30	Pass
NVNT	BLE	2480	Ant1	-52.68	-30	Pass

Band Edge NVNT BLE 2402MHz Ant1 Ref



Band Edge NVNT BLE 2402MHz Ant1 Emission



Band Edge NVNT BLE 2480MHz Ant1 Ref



Band Edge NVNT BLE 2480MHz Ant1 Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 2.526000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 100/100
08:51:46 PM Jun 23, 2022
Ref Offset 2.58 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.480 0 GHz
-0.491 dBm
-30.56 dBm
Start 2.47600 GHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 2.57600 GHz
Sweep 9.600 ms (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.480 0 GHz -0.491 dBm
2 N 1 f 2.483 5 GHz -56.456 dBm
3 N 1 f 2.500 0 GHz -58.036 dBm
4 N 1 f 2.483 9 GHz -53.247 dBm
MSG
STATUS

Conducted RF Spurious Emission

Condition	Mode	Frequency (MHz)	Antenna	Max Value (dBc)	Limit (dBc)	Verdict
NVNT	BLE	2402	Ant1	-39.66	-30	Pass
NVNT	BLE	2442	Ant1	-42.02	-30	Pass
NVNT	BLE	2480	Ant1	-39.67	-30	Pass

Tx. Spurious NVNT BLE 2402MHz Ant1 Ref



Tx. Spurious NVNT BLE 2402MHz Ant1 Emission

Tx. Spurious NVNT BLE 2442MHz Ant1 Ref



Tx. Spurious NVNT BLE 2442MHz Ant1 Emission



Tx. Spurious NVNT BLE 2480MHz Ant1 Ref



Tx. Spurious NVNT BLE 2480MHz Ant1 Emission


Agilent Spectrum Analyzer - Swept SA
Center Freq 13.265000000 GHz
PNO: Fast
IFGain:Low
Trig: Free Run
#Atten: 30 dB
Avg Type: Log-Pwr
Avg|Hold: 10/10
08:49:25 PM Jun 23, 2022
Ref Offset 2.58 dB
10 dB/div
Ref 20.00 dBm
Log
Mkr1 2.492 GHz
-1.918 dBm
-30.51 dBm
Start 30 MHz
#Res BW 100 kHz
#VBW 300 kHz
Stop 26.50 GHz
Sweep 2.530 s (1001 pts)
MKR MODE TRC SCL X Y FUNCTION FUNCTION WIDTH FUNCTION VALUE
1 N 1 f 2.492 GHz -1.918 dBm
2 N 1 f 4.953 GHz -40.174 dBm
3 N 1 f 4.953 GHz -40.174 dBm
4 N 1 f 7.547 GHz -55.185 dBm
5 N 1 f 10.036 GHz -55.886 dBm
MSG
STATUS

APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Conducted Emissions at AC Power Line (150kHz-30MHz)



BlueAsia

Radiated Spurious Emissions



APPENDIX B: PHOTOGRAPHS OF EUT

Reference to the test report No. BLA-EMC-202205-A4801

----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia