

Rogers Labs, a division of The Compatibility Center LLC

7915 Nieman Rd.
Lenexa, KS 66214
Phone / Fax (913) 660-0666

47CFR, PART 15C - Intentional Radiators
47CFR Paragraph 15.212, 15.247 and
Industry Canada RSS-247 Issue 4 and RSS-GEN Issue 5
Application For Module Grant of Certification
Model: HALOW1
902-928 MHz Digital Transmission System (DTS)

FCC ID: 2AQ2Q-HALOW1

IC: 27013-HALOW1

CARGT Inc.

9825 Widmer Road
Lenexa, KS 66215

Test Report Number: 250514

Test Date: May14, 2025 – January 13, 2026

Authorized Signatory: 

Patrick Powell

Rogers Labs, a division of The Compatibility Center LLC

FCC Designation: US5305

ISED Registration: 3041A

This report shall not be reproduced except in full, without the written approval of the laboratory. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the U.S. Government.

TABLE OF CONTENTS.....	2
REVISIONS.....	5
EXECUTIVE SUMMARY	5
OPINION / INTERPRETATION OF RESULTS	6
EQUIPMENT TESTED.....	9
Equipment Operational Modes.....	9
Channel Number Summary	10
Antenna Configuration Summary	11
Worst Case Antenna Selection	11
Equipment Function	12
Equipment Configuration.....	12
APPLICATION FOR CERTIFICATION.....	13
TEST SITE LOCATIONS	14
UNITS OF MEASUREMENTS	15
ENVIRONMENTAL CONDITIONS.....	16
TEST SOFTWARE.....	16
STATEMENT OF MODIFICATIONS AND DEVIATIONS	16
APPLICABLE STANDARDS	16
INTENTIONAL RADIATORS.....	17
Antenna Requirements	17
Test Procedures	18
AC Line Conducted Emission Test Procedure	18
Radiated Emission Procedure	18
Antenna Port Conducted Emission Test Procedure	18

Diagram 1 Test arrangement for power-line conducted emissions.....	19
Diagram 2 Test arrangement for radiated emissions of tabletop equipment.....	20
Diagram 3 Test arrangement for radiated emissions tested in Semi-Anechoic Chamber (SAC).....	21
Diagram 4 Test arrangement for Antenna Port Conducted emissions.....	22
Restricted Bands of Operation.....	23
Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1, 802.11ah 1MHz	23
Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 2, 802.11ah 2MHz	25
Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 3, 802.11ah 4MHz	26
Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 4, 802.11ah 8MHz	27
Summary of Results for Radiated Emissions in Restricted Bands	27
AC Line Conducted EMI Procedure	28
Figure 1 AC Line Conducted Emissions Data L1	29
Figure 2 AC Line Conducted Emissions Data L2	30
Table 5 AC Line Conducted Emissions Data L1	31
Table 6 AC Line Conducted Emissions Data L2.....	31
Summary of Results for AC Line Conducted Emissions.....	31
General Radiated Emissions Procedure.....	32
Figure 3 Plot of Screen Room Exploratory Radiated Emissions	33
Figure 4 Plot of Screen Room Exploratory Radiated Emissions	34
Figure 5 Plot of Screen Room Exploratory Radiated Emissions	35
Figure 6 Plot of Screen Room Exploratory Radiated Emissions	36
Figure 7 Plot of Screen Room Exploratory Radiated Emissions	37
Figure 8 Plot of Screen Room Exploratory Radiated Emissions	38
Figure 9 Plot of Screen Room Exploratory Radiated Emissions	39
Table 7 General Radiated Emissions Data – Worst Case (Horizontal Polarization)	40
Table 8 General Radiated Emissions Data – Worst Case (Vertical Polarization).....	40
Summary of Results for General Radiated Emissions.....	40
Operation in the Band 902 - 928 MHz.....	41
Figure 10 Plot of Transmitter Operation in 902-928 MHz Mode 1, 802.11ah 1MHz	42
Figure 11 Plot of Transmitter Operation in 902-928 MHz Mode 2, 802.11ah 2MHz	43
Figure 12 Plot of Transmitter Operation in 902-928 MHz Mode 3, 802.11ah 4MHz	44
Figure 13 Plot of Transmitter Operation in 902-928 MHz Mode 4, 802.11ah 8MHz	45
Figure 14 Plot of Emissions Low Band Edge Mode 1, 802.11ah 1MHz.....	46

Figure 15 Plot of Emissions Low Band Edge Mode 2, 802.11ah 2MHz.....	47
Figure 16 Plot of Emissions Low Band Edge Mode 3, 802.11ah 4MHz.....	48
Figure 17 Plot of Emissions Low Band Edge Mode 4, 802.11ah 8MHz.....	49
Figure 18 Plot of Transmitter Emissions High Band Edge Mode 1, 802.11ah 1MHz.....	50
Figure 19 Plot of Transmitter Emissions High Band Edge Mode 2, 802.11ah 2MHz.....	51
Figure 20 Plot of Transmitter Emissions High Band Edge Mode 3, 802.11ah 4MHz.....	52
Figure 21 Plot of Transmitter Emissions High Band Edge Mode 4, 802.11ah 8MHz.....	53
Figure 22 Plot of 6-dB Occupied Bandwidth Mode 1, 802.11ah 1MHz	54
Figure 23 Plot of 99% Occupied Bandwidth Mode 1, 802.11ah 1MHz	55
Figure 24 Plot of 6-dB Occupied Bandwidth Mode 2, 802.11ah 2MHz	56
Figure 25 Plot of 99% Occupied Bandwidth Mode 2, 802.11ah 2MHz	57
Figure 26 Plot of 6-dB Occupied Bandwidth Mode 3, 802.11ah 4MHz	58
Figure 27 Plot of 99% Occupied Bandwidth Mode 3, 802.11ah 4MHz	59
Figure 28 Plot of 6-dB Occupied Bandwidth Mode 4, 802.11ah 8MHz	60
Figure 29 Plot of 99% Occupied Bandwidth Mode 4, 802.11ah 8MHz	61
Figure 30 Plot of Transmitter Power Spectral Density Mode 1, 802.11ah 1MHz.....	62
Figure 31 Plot of Transmitter Power Spectral Density Mode 2, 802.11ah 2MHz.....	63
Figure 32 Plot of Transmitter Power Spectral Density Mode 3, 802.11ah 4MHz.....	64
Figure 33 Plot of Transmitter Power Spectral Density Mode 4, 802.11ah 8MHz.....	65
Transmitter Emissions Data.....	66
Table 9 Transmitter Radiated Emissions Mode 1, 802.11ah 1MHz	66
Table 10 Transmitter Radiated Emissions Mode 2, 802.11ah 2MHz	67
Table 11 Transmitter Radiated Emissions Mode 3, 802.11ah 4MHz	68
Table 12 Transmitter Radiated Emissions Mode 4, 802.11ah 8MHz	69
Table 13 Transmitter Antenna Port Conducted Data modes 1 through 4	70
Summary of Results for Transmitter Radiated Emissions of Intentional Radiator.....	71
Frequency Stability	71
ANNEX.....	72
Annex A Measurement Uncertainty Calculations.....	73
Annex B Test Equipment.....	74
Annex C Laboratory Certificate of Accreditation.....	78

Revisions

Revision 1 Issued February 24, 2026 – Initial release

Executive Summary

The following information is submitted for consideration in obtaining Grant of Certification for License Exempt Digital Transmission System Intentional Radiator operating under Code of Federal Regulations Title 47 (47CFR) Part 15C paragraph 15.247, Industry Canada RSS-247 Issue 4, and RSS-GEN Issue 5, operation in the 902-928 MHz band.

Name of Applicant: CARGT Inc.
 9825 Widmer Road
 Lenexa, KS 66215

HVIN / PMN: HALOW1

FCC ID: 2AQ2Q-HALOW1 IC: 27013-HALOW1

Operating Frequency Range: 903.5 – 926.5 MHz

HVIN# HALOW1 was chosen for transmitter configuration testing and used for final measurements.

Operational communication modes 1 through 4:

Mode	Power (Watts)	99% OBW (kHz)	6-dB OBW (kHz)
802.11ah – 1MHz	0.344	865.5	798.0
802.11ah – 2MHz	0.420	1,802.5	1,712.5
802.11ah – 4MHz	0.435	3,865.0	3,597.5
802.11ah – 8MHz	0.508	7,660.0	7,537.9

This report addresses EUT Operations as Digital Transmission System using transmitter modulations in modes 1 through 4. Note, the production module has no integral antenna. Its antenna port connection is via solder balls on the package. A limited list of antennas are approved for use by any host manufacturer integrating this module. Maximum gain of these antennas is 3.6 dBi.

Opinion / Interpretation of Results

Tests Performed	Margin (dB)	Results
Restricted Band Emissions 15.205, RSS-GEN, RSS-247	-15.7	Complies
AC Line Emissions as per 47CFR 15.207, RSS-GEN 8.8	-6.13	Complies
Radiated Emissions 47 CFR 15.209, RSS-GEN 8.9	-0.7	Complies
Harmonic Emissions per 47CFR 15.247, RSS-247	-11.8	Complies
Power Spectral Density per 47CFR 15.247, RSS-247	-1.1	Complies

Tests performed include:

47CFR 15.247

(a) (2) Systems using digital modulation techniques may operate in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

(b) The maximum peak conducted output power of the intentional radiator shall not exceed the following:

(3) For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one-Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the *maximum conducted output power* is the highest total transmit power occurring in any mode.

(d) In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

(e) For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

6. Requirements for frequency hopping systems, digital transmission systems and hybrid systems operating in the bands 902-928 MHz, 2400-2483.5 MHz and 5725-5850MHz

This section sets out the requirements for frequency hopping systems (FHS), digital transmission systems (DTS) and hybrid systems.

6.3 Digital transmission systems (DTS)

DTS include systems that employ digital modulation techniques resulting in spectral characteristics similar to direct sequence systems.

DTS operating in the band 5725-5850 MHz shall meet the requirements of section 7 of this document.

6.3.1 Bandwidth and conducted power spectral density

The following applies to the bands 902-928 MHz and 2400-2483.5 MHz:

- a) the minimum 6 dB bandwidth shall be 500 kHz.
- b) the transmitter power spectral density conducted from the transmitter to the antenna(s) shall not be greater than 8 dBm/3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of section 6.3.2 The power spectral density shall be determined using the same method as is used to determine the maximum conducted output power.

6.3.2 Transmitter output power and e.i.r.p. requirements

For DTS operating in the band 902-928 MHz, the maximum peak conducted output power shall not exceed 1 W, and the e.i.r.p. shall not exceed 4 W.

For DTS operating in the band 2400-2483.5 MHz, the maximum peak conducted output power shall not exceed 1 W, and the e.i.r.p. shall not exceed 4 W, except as provided in section 6.5 a) and b).

As an alternative to a peak power measurement, compliance can be based on a measurement of the maximum conducted output power.

6.6 Unwanted Emissions

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum device, digitally modulated device, or hybrid system is operating, the RF power that is produced shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power – based on either an RF conducted or a radiated measurement – provided that the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of root-mean-square averaging over a time interval, as permitted under section 6.3.2, the attenuation required shall be 30 dB instead of 20 dB. Attenuation below the general field strength limits specified in RSS-Gen is not required.

Equipment Tested

Model: HALOW1

CARGT Inc.

9825 Widmer Road

Lenexa, KS 66215

<u>Equipment</u>	<u>Model / PN</u>	<u>Serial Number</u>
EUT #1 Radiated	HALOW1	N/A
EUT #2 Antenna Port Conducted	HALOW1	N/A
Test Fixture carrier board	012-00326-00	N/A
Host Adapter (M.2)	012-00375-00	N/A
A/C Adapter	Model: 1230	N/A
USB to RJ45 adapter	UE306	Y238014005865
Ethernet cable	N/A	N/A

Test results in this report relate only to the items tested. Worst-case configuration data recorded in this report.

All antennas operate within the same frequency band(s) and are connected to the only RF transmitter chain.

Software (FVIN): rel_1_14_1_2024_Dec_05 or newer

Equipment Operational Modes

Mode	Transmitter Operation
1	802.11ah – 1MHz
2	802.11ah – 2MHz
3	802.11ah – 4MHz
4	802.11ah – 8MHz

Channel Number Summary

Channel List	OFDM 1M		OFDM 2M		OFDM 4M		OFDM 8M	
	CH	Freq.(MHz)	CH	Freq.(MHz)	CH	Freq.(MHz)	CH	Freq.(MHz)
	3	903.5	6	905	8	906	12	908
	5	904.5	10	907	16	910	28	916
	7	905.5	14	909	24	914	44	924
	9	906.5	18	911	32	918		
	11	907.5	22	913	40	922		
	13	908.5	26	915	48	926		
	15	909.5	30	917				
	17	910.5	34	919				
	19	911.5	38	921				
	21	912.5	42	923				
	23	913.5	46	925				
	25	914.5						
	27	915.5						
	29	916.5						
	31	917.5						
	33	918.5						
	35	919.5						
	37	920.5						
	39	921.5						
	41	922.5						
	43	923.5						
	45	924.5						
47	925.5							
49	926.5							

Antenna Configuration Summary

The module supports four antenna options as shown below:

Antenna #	Type	Peak Gain (dBi)	Impedence (Ohms)	Location	Connector
1	Flexible Printed Circuit (FPC)	-0.90	50	External	u.FL (host)
2	Dipole	1.2	50	External	SMA (host)
3	Omni	3	50	External	NMO (host)
4	Flexible Printed Circuit (FPC)	3.6	50	External	u.FL (host)

- This radio transmitter has been authorized per FCC and ISSED regulations and operation with antennas from the above list with the maximum permissible gain indicated. There are options for use of similar style and lessor gain antennas without additional authorization. Use of higher gain antennas requires additional authorization.
- An integration guide is supplied with the module to specify exactly how customers are to integrate these antennas so that they work exactly as tested here.
- Using the approved list of antennas, the module complies with both 15.247 and RSS-247 EIRP limits.

Worst Case Antenna Selection

All required radiated emissions tests were performed using the worst-case antenna configuration for each test category. Antennas that did not produce worst-case emissions were not retested in accordance with FCC §2.947.


Summary as follows:

Test	Worst-Case Antenna
General radiated spurious emissions	Antenna #3 (3dBi Omni)
Restricted Band emissions	Antenna #2 (1.2dBi dipole)
Band-edge emissions	Conducted Antenna Port
Transmitter Spurious	Antenna #4 (3.6dBi Omni)

Equipment Function

The EUT device is a solder down module containing a WiFi Halow (802.11ah) transmitter that is connected by soldered pads to a carrier PCB designed by the end customer but required to follow implementation instructions from the device's module certification holder. Power and data interface to a host processor on the end customer's carrier board via device soldered pads. The Halow transmitter is connected to an approved antenna via soldered pads on the module to an appropriately (as specified in the integration guide) terminated signal path on the customer's carrier board. The carrier board also provides the correct connector for mating to the chosen antenna.

Equipment Configuration



Application for Certification

- (1) Manufacturer: CARGT Inc.
9825 Widmer Road
Lenexa, KS 66215
- (2) Identification: HVIN: HALOW1
FCC ID: 2AQ2Q-HALOW1 IC: 27013-HALOW1
- (3) Instruction Book:
Refer to Exhibit for Instruction Manual.
- (4) Description of Circuit Functions:
Refer to Exhibit of Operational Description.
- (5) Block Diagram with Frequencies:
Refer to Exhibit of Operational Description.
- (6) Report of Measurements:
Report of measurements follows in this Report.
- (7) Photographs: Construction, Component Placement, etc.:
Refer to Exhibit for photographs of equipment.
- (8) List of Peripheral Equipment Necessary for operation. The equipment operates from external direct current power provided from host system. The EUT provides interface ports for power, loads and communications as presented in this filing.
- (9) Transition Provisions of 47CFR 15.37 are not requested.
- (10) Not Applicable. The unit is not a scanning receiver.
- (11) Not Applicable. The EUT does not operate in the 59 – 64 GHz frequency band.
- (12) The equipment is not software defined and this section is not applicable.
- (13) Applications for certification of U-NII devices in the 5.15-5.35 GHz and the 5.47-5.85 GHz bands must include a high-level operational description of the security procedures that control the radio frequency operating parameters and ensure that unauthorized modifications cannot be made. This requirement is not applicable to his DTS device.
- (14) Contain at least one drawing or photograph showing the test set-up for each of the required types of tests applicable to the device for which certification is requested. These drawings or photographs must show enough detail to confirm other information contained in the test report. Any photographs used must be focused originals without glare or dark spots and must clearly show the test configuration used. This information is provided in this report and Test Setup Exhibits provided with the application filing.

Test Site Locations

Conducted EMI AC line conducted emissions testing performed in a shielded screen room located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS.

Antenna port Antenna port conducted emissions testing was performed in a shielded screen room located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS.

Radiated EMI The radiated emissions tests were performed at the 3 meters Semi-Anechoic Chamber (SAC) located at Rogers Labs, a division of The Compatibility Center LLC, 7915 Nieman Rd., Lenexa, KS.

Registered Site information: FCC Site: US5305, ISED: 3041A, CAB Identifier: US0096

NVLAP Accreditation Lab code 200087-0

Units of Measurements

AC Line Conducted EMI Data presented in dB μ V; dB referenced to one microvolt
Antenna port Conducted Data presented in dBm; dB referenced to one milliwatt
Radiated EMI Data presented in dB μ V/m; dB referenced to one microvolt per meter

Radiated Sample Calculations:

RFS = Radiated Field Strength, FSM = Field Strength Measured

A.F. = Receive antenna factor, *Losses* = misc. losses in system, *G_R* = amplification gains

RFS dB μ V/m = FSM (dB μ V) + A.F. (dB/m) + Losses (dB) - G_R (dB)

Note: measurement distance may vary depending on regulation or test standard.

Antenna Port Conducted Sample Calculations:

EIRP = equivalent isotropically radiated power (in same units as P_R)

P_{meas} = measured conducted power level (dBW or dBm)

P_R = Antenna Port Conducted power level (dBW or dBm)

L_C = cable losses (dB), *L_{atten}* = Attenuator losses (dB)

G_{ANT} = declared EUT antenna gain (dBi)

P_R = P_{meas} - L_C - L_{atten}

EIRP = P_R + G_{ANT}

AC Line Conducted Sample Calculations:

L_{LISN} = LISN loss (dB)

AC = AC Line Emission (dB μ V)

P_{AC} = P_{meas} - L_{LISN} - L_C - L_{atten}

Note: These *correction factors* are already included in the measurements reported by our spectrum analyzer / receivers so above are only samples of how the results are calculated.

Frequency: 9 kHz-30 MHz	Frequency: 30 MHz- 1 GHZ	Frequency: Above 1 GHz
Loop Antenna	Broadband Biconilog	Horn
RBW = 9 kHz	RBW = 120 kHz	RBW = 1 MHz
VBW = 30 kHz	VBW = 500 kHz	VBW = 3 MHz
Sweep time = Auto	Sweep time = Auto	Sweep time = Auto
Detector = PK, QP	Detector = PK, QP	Detector = PK, AV
Antenna Height 1m	Antenna Height 1-4m	Antenna Height 1-4m

Environmental Conditions

Ambient Temperature	22.3° C
Relative Humidity	46.0 %
Atmospheric Pressure	1000.3 mb

Test Software

Test Software List			
Description	Manufacturer	Model	Version
Automated EMC testing software system	ETS Lindgren	Tile!	7.9.1.1

The above software is sometimes used in acquiring test data for our reports.

Statement of Modifications and Deviations

No modifications to the EUT were required for the equipment to demonstrate compliance with the 47CFR Part 15C, Industry Canada RSS-247 Issue 4, and RSS-GEN Issue 5 emission requirements. There were no deviations to the specifications.

Applicable Standards

The following information is submitted in accordance with the eCFR (electronic Title 47 Code of Federal Regulations) (47CFR), dated May 5, 2025: Part 2, Subpart J, Part 15C Paragraph 15.247, 15.212, RSS-247 Issue 4, and RSS-GEN Issue 5. Test procedures used are the established Methods of Measurement of Radio-Noise Emissions as described in ANSI C63.10-2020+Cor. 1-2023+C63.10a-2024+Errata to C63.10a-2024. This report documents compliance for the EUT operations as Digital Transmission Systems operation.

Intentional Radiators

The following information is submitted supporting compliance with the requirements of 47CFR, Subpart C, paragraph 15.247, Industry Canada RSS-247 Issue 4, and RSS-GEN Issue 5.

Antenna Requirements

According to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

This module conforms to these requirements.

Test Procedures

AC Line Conducted Emission Test Procedure

Testing for the AC line-conducted emissions were performed as required in CFR47 15B, RSS-GEN, and directed in ANSI C63.4-2014 (for unintentional radiators) or ANSI C63.10-2020 (for intentional radiators). The test setup, including the EUT, was arranged in the test configurations as presented during testing. The test configuration was placed on a 1 x 1.5-meter bench, 0.8 meters high located in a screen room. The power lines of the system were isolated from the power source using a standard LISN with a 50- μ Hy choke. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor internal to the LISN. The LISN was positioned on the floor beneath the wooden bench supporting the EUT. The power lines and cables were draped over the back edge of the table. Refer to diagram one showing typical test arrangement and photographs in the test setup exhibit for EUT placement used during testing.


Radiated Emission Procedure

Radiated emissions testing was performed as required in 47CFR 15C, RSS-247 Issue 4, RSS-GEN and specified in ANSI C63.10-2020. The EUT was placed on a rotating 0.9 x 1.2-meter platform, elevated as required above the ground plane at a distance of 3 meters from the FSM antenna. EMI energy was maximized by equipment placement permitting orientation in three orthogonal axes, raising, and lowering the FSM antenna, changing the antenna polarization, and by rotating the turntable. Each emission was maximized before data was taken and recorded. The frequency spectrum from 9 kHz to 25,000 MHz was searched for emissions during preliminary investigation. Refer to diagrams two and three showing typical test setup. Refer to photographs in the test setup exhibits for specific EUT placement during testing.

Antenna Port Conducted Emission Test Procedure

The EUT was assembled as required for operation placed on a benchtop. This configuration provided the ability to connect test equipment to the provided test antenna port. Antenna Port conducted emissions testing was performed presented in the regulations and specified in ANSI C63.10-2020. Testing was completed on a laboratory bench in a shielded room. The active antenna port of the device was connected to appropriate attenuation and either a spectrum analyzer or a power meter. Refer to diagram 4 showing typical test arrangement and photographs in the test setup exhibits for specific EUT placement during testing.


Diagram 2 Test arrangement for radiated emissions of tabletop equipment



1. A LISN is optional for radiated measurements between 30 MHz and 1000 MHz but not allowed for measurements below 30 MHz and above 1000 MHz (see 6.3.1). If used, then connect EUT to one LISN. Unused LISN measuring port connectors shall be terminated in 50 Ω loads. The LISN may be placed on top of, or immediately beneath, the reference ground plane (see 6.2.2 and 6.2.3.2).
 - 1.1. LISN spaced at least 80 cm from the nearest part of the EUT chassis.
2. Antenna can be integral or detachable, depending on the EUT (see 6.3.1).
3. Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 cm to 40 cm long (see 6.3.1).
4. For emission measurements at or below 1 GHz, the table height shall be 80 cm. For emission measurements above 1 GHz, the table height shall be 1.5 m for measurements, except as otherwise specified (see 6.3.1 and 6.6.3.1).

Diagram 3 Test arrangement for radiated emissions tested in Semi-Anechoic Chamber (SAC)

Below 1 GHz



Above 1 GHz:





Diagram 4 Test arrangement for Antenna Port Conducted emissions



Restricted Bands of Operation

Spurious emissions falling in the restricted frequency bands of operation were measured at the SAC. The EUT utilizes frequency, determining circuitry, which generates harmonics falling in the restricted bands. Emissions were investigated at the SAC, using appropriate antennas or pyramidal horns, amplification stages, and a spectrum analyzer. Peak and average amplitudes of frequencies above 1000 MHz were compared to the required limits with worst-case data presented below. Test procedures of ANSI C63.10-2020 were used during testing. No other significant emission was observed which fell into the restricted bands of operation. Computed emission values consider the received radiated field strength, receive antenna correction factor, amplifier gain stage, and test system cable losses.

As previously stated, restricted band testing was performed with the worst case Antenna #2 and shown below in Tables 1 through 4.

Table 1 Radiated Emissions in Restricted Frequency Bands Data Mode 1, 802.11ah 1MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2710.5	45.4	32.7	45.0	32.1	54.0	-21.3	-21.9
2746.5	45.3	32.1	46.5	33.3	54.0	-21.9	-20.7
2779.5	50.1	32.7	47.6	32.7	54.0	-21.3	-21.3
3614.0	46.3	33.1	46.5	32.9	54.0	-20.9	-21.1
3662.0	47.1	34.1	47.0	34.1	54.0	-19.9	-19.9
3706.0	47.5	34.6	47.7	34.6	54.0	-19.4	-19.4
4517.5	47.4	34.3	48.4	34.3	54.0	-19.7	-19.7
4577.5	48.2	35.0	48.3	34.9	54.0	-19.0	-19.1
4632.5	49.0	35.5	48.6	35.4	54.0	-18.5	-18.6
5421.0	50.7	37.1	50.7	37.1	54.0	-16.9	-16.9

5493.0	51.0	37.7	50.6	37.7	54.0	-16.3	-16.3
5559.0	50.3	37.5	51.0	37.5	54.0	-16.5	-16.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 2 Radiated Emissions in Restricted Frequency Bands Data Mode 2, 802.11ah 2MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2715.0	45.9	32.2	46.2	32.5	54.0	-21.8	-21.5
2745.0	46.1	32.5	45.4	32.1	54.0	-21.5	-21.9
2775.0	45.2	32.4	45.6	32.4	54.0	-21.6	-21.6
3620.0	46.4	33.5	46.3	33.4	54.0	-20.5	-20.6
3660.0	47.2	34.2	47.2	34.2	54.0	-19.8	-19.8
3700.0	47.3	34.1	47.0	34.1	54.0	-19.9	-19.9
4525.0	47.8	34.7	47.8	34.7	54.0	-19.3	-19.3
4575.0	48.5	35.0	47.9	35.0	54.0	-19.0	-19.0
4625.0	49.4	35.9	49.9	35.9	54.0	-18.1	-18.1
5430.0	50.2	37.1	50.7	37.1	54.0	-16.9	-16.9
5490.0	51.3	37.6	50.9	37.6	54.0	-16.4	-16.4
2715.0	45.9	32.2	46.2	32.5	54.0	-17.0	-17.0

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 3 Radiated Emissions in Restricted Frequency Bands Data Mode 3, 802.11ah 4MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2718.0	45.4	32.2	45.6	32.3	54.0	-21.8	-21.7
2742.0	45.5	32.3	45.5	32.1	54.0	-21.7	-21.9
2778.0	46.0	32.3	45.3	32.3	54.0	-21.7	-21.7
3624.0	47.0	33.7	47.3	33.6	54.0	-20.3	-20.4
3656.0	47.2	34.5	47.5	34.4	54.0	-19.5	-19.6
3704.0	47.8	34.4	47.4	34.3	54.0	-19.6	-19.7
4530.0	49.0	34.9	48.1	34.9	54.0	-19.1	-19.1
4570.0	48.8	35.3	49.5	35.3	54.0	-18.7	-18.7
4630.0	48.0	35.5	48.2	35.5	54.0	-18.5	-18.5
5436.0	50.4	37.0	49.7	37.0	54.0	-17.0	-17.0
5484.0	50.3	37.3	49.6	37.2	54.0	-16.7	-16.8
5556.0	50.2	37.3	50.6	37.3	54.0	-16.7	-16.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 4 Radiated Emissions in Restricted Frequency Bands Data Mode 4, 802.11ah 8MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
2724.0	45.8	32.3	45.1	32.3	54.0	-21.7	-21.7
2748.0	45.8	32.2	45.6	31.9	54.0	-21.8	-22.1
2772.0	46.1	32.3	45.6	32.2	54.0	-21.7	-21.8
3632.0	47.5	34.3	47.3	34.2	54.0	-19.7	-19.8
3664.0	46.5	33.9	47.3	33.9	54.0	-20.1	-20.1
3696.0	46.4	33.7	47.1	33.7	54.0	-20.3	-20.3
4540.0	48.5	35.6	48.8	35.6	54.0	-18.4	-18.4
4580.0	47.3	34.7	47.8	34.7	54.0	-19.3	-19.3
4620.0	49.1	36.3	49.7	36.3	54.0	-17.7	-17.7
5448.0	51.2	38.3	49.5	36.5	54.0	-15.7	-17.5
5496.0	50.6	37.7	50.4	37.7	54.0	-16.3	-16.3
5544.0	50.0	36.6	49.8	36.6	54.0	-17.4	-17.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for Radiated Emissions in Restricted Bands


The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C and RSS-247 Issue 4 Intentional Radiator requirements. The EUT demonstrated a worst-case minimum margin of -15.7 dB below the emissions requirements in restricted frequency bands. Peak, Quasi-peak, and average amplitudes were checked for compliance with the regulations. Worst-case emissions are reported with other emissions found in the restricted frequency bands at least 20 dB below the requirements.

AC Line Conducted EMI Procedure

The EUT was arranged in typical equipment configurations as offered by manufacturer and presented above in equipment configuration. AC Line Conducted emission testing was performed with the EUT placed on a 1 x 1.5-meter bench 80 cm above the conducting ground plane, floor of a screen room. The bench was positioned 40 cm away from the wall of the screen room. The LISN was positioned on the floor of the screen room 80-cm from the rear of the EUT. Testing for the AC line-conducted emissions followed the procedures of ANSI C63.10-2020. The EUT was configured as presented in the AC Line conducted configurations as directed by the manufacturer and presented above in equipment configuration. The AC adapter for the EUT was connected to the LISN for AC line-conducted emissions testing. A second LISN was positioned on the floor of the screen room 80-cm from the rear of the supporting equipment of the test configuration. All power cords except the EUT were then powered from the second LISN. EMI was coupled to the spectrum analyzer through a 0.1 μ F capacitor, internal to the LISN. Power line conducted emissions testing was carried out individually for each current carrying conductor of the EUT. The excess length of lead between the system and the LISN receptacle was folded back and forth to form a bundle not exceeding 40 cm in length. The screen room, conducting ground plane, analyzer, and LISN were bonded together to the protective earth ground. Preliminary testing was performed to identify the frequencies of each of the emissions, which demonstrated the highest amplitudes. The cables were repositioned to obtain maximum amplitude of measured EMI level. Once the worst-case configuration was identified, plots were made of the EMI from 0.15 MHz to 30 MHz and data recorded.


Refer to data in tables 5 and 6 and plots in figures 1 and 2 related to worst case Configuration #2 EUT–laptop connected AC Line conducted emissions.

Figure 1 AC Line Conducted Emissions Data L1



Other emissions present had amplitudes at least 20 dB below the limit.

Figure 2 AC Line Conducted Emissions Data L2



Other emissions present had amplitudes at least 20 dB below the limit.

Table 5 AC Line Conducted Emissions Data L1

Trace	Frequency	Level (dBμV)	Detector	Delta Limit/dB
1	154.000000000 kHz	45.14	Quasi Peak	-20.64
1	182.000000000 kHz	44.12	Quasi Peak	-20.27
2	182.000000000 kHz	34.08	Average	-20.31
2	218.000000000 kHz	33.82	Average	-19.07
1	226.000000000 kHz	42.84	Quasi Peak	-19.76
2	258.000000000 kHz	37.35	Average	-14.15
1	270.000000000 kHz	42.46	Quasi Peak	-18.66
2	294.000000000 kHz	43.35	Average	-7.06
1	294.000000000 kHz	49.05	Quasi Peak	-11.36
2	330.000000000 kHz	40.79	Average	-8.66
2	474.000000000 kHz	28.56	Average	-17.88
1	882.000000000 kHz	32.20	Quasi Peak	-23.80

Other emissions present had amplitudes at least 20 dB below the limit.

Table 6 AC Line Conducted Emissions Data L2

Trace	Frequency	Level (dBμV)	Detector	Delta Limit/dB
2	150.000000000 kHz	35.87	Average	-20.13
1	154.000000000 kHz	43.22	Quasi Peak	-22.56
1	162.000000000 kHz	39.68	Quasi Peak	-25.68
1	186.000000000 kHz	43.84	Quasi Peak	-20.37
1	234.000000000 kHz	40.50	Quasi Peak	-21.80
2	258.000000000 kHz	38.36	Average	-13.14
1	270.000000000 kHz	42.77	Quasi Peak	-18.34
2	294.000000000 kHz	44.28	Average	-6.13
1	294.000000000 kHz	49.10	Quasi Peak	-11.31
2	326.000000000 kHz	39.25	Average	-10.31
2	434.000000000 kHz	27.75	Average	-19.42
2	12.251900000 MHz	26.23	Average	-23.77

Other emissions present had amplitudes at least 20 dB below the limit.

Summary of Results for AC Line Conducted Emissions

The EUT demonstrated compliance with the AC Line Conducted Emissions requirements of 47CFR Part 15C, RSS-247 and RSS-Gen. The EUT configuration #2 demonstrated a minimum margin of -6.13 dB below the requirement. Other emissions were present with amplitudes at least 20 dB below the limit and worst-case amplitudes recorded.

General Radiated Emissions Procedure


Testing for the radiated emissions were performed as specified in CFR47 15B, RSS-GEN, and directed in ANSI C63.10-2020. For testing purposes, the EUT was arranged as presented in the applicable configuration diagrams above and operated through all modes as presented.

Exploratory radiated emissions measurements were performed in the SAC chamber or screen room, finding maximized emissions over frequency, EUT orientation, antenna height and polarity. This data is then used to focus the final radiated emissions measurements on these maximized points.

Final radiated emissions data were taken with the EUT located in the SAC at distance of 3 meters between the EUT and the receiving antenna. The frequency spectrum from 9 kHz to 9.265 GHz (tenth harmonic of highest fundamental frequency) was searched for radiated emissions. Proactively, the spectrum up to 40 GHz was investigated despite not being required (results shown in Figures 8 and 9). Measured emission levels were maximized by EUT placement on the table, changing cable location, rotating the turntable through 360 degrees, varying the antenna height between 1 and 4 meters above the ground plane and changing antenna position between horizontal and vertical polarization. Antennas used were Loop, Biconical, Broadband Biconilog, Log Periodic, and Double Ridge or Pyramidal Horns and mixers above 1 GHz.


As previously stated, general spurious radiated emissions testing was performed with the worst case Antenna #3 and shown below in Figures 3 through 7 and Tables 7 and 8.

Figure 3 Plot of Screen Room Exploratory Radiated Emissions



Note: As table 7 below shows, the peak here was investigated during final measurements and found to be below the limit.

Figure 4 Plot of Screen Room Exploratory Radiated Emissions



Note: As table 7 below shows, the peak here was investigated during final measurements and found to be below the limit.

Figure 5 Plot of Screen Room Exploratory Radiated Emissions




Figure 6 Plot of Screen Room Exploratory Radiated Emissions




Figure 7 Plot of Screen Room Exploratory Radiated Emissions




Figure 8 Plot of Screen Room Exploratory Radiated Emissions




Figure 9 Plot of Screen Room Exploratory Radiated Emissions




Table 7 General Radiated Emissions Data – Worst Case (Horizontal Polarization)

Frequency (MHz)	Peak (dBμV/m)	Quasi-Peak (dBμV/m)	Limit @ 3m (dBμV/m)	Margin (dBm)
150.0	27.5	26.9	40.0	-13.1
215.2	37.1	33.7	40.0	-6.3
220.3	44.1	39.3	40.0	-0.7
232.4	50.1	46.0	47.0	-1.0
500.0	20.0	18.1	47.0	-28.9
750.0	42.7	40.4	47.0	-6.6

Table 8 General Radiated Emissions Data – Worst Case (Vertical Polarization)

Frequency (MHz)	Peak (dBμV/m)	Quasi-Peak (dBμV/m)	Limit @ 3m (dBμV/m)	Margin (dBm)
150.0	39.3	38.6	40.0	-1.5
220.0	43.1	38.3	40.0	-1.7
234.9	50.0	45.0	47.0	-2.0
450.0	41.5	40.5	47.0	-6.5
500.0	44.2	42.8	47.0	-4.2
950.9	37.8	32.3	47.0	-14.7

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency range below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Summary of Results for General Radiated Emissions

The EUT demonstrated compliance with the radiated emissions requirements of 47CFR Part 15C paragraph 15.209, RSS-247 Issue 4, and RSS-GEN Issue 5 Intentional Radiators. The EUT configuration demonstrated a minimum margin of -0.7 dB below the requirements. Other emissions were present with amplitudes at least 20 dB below the Limits.

Operation in the Band 902 - 928 MHz

Test procedures of ANSI C63.10-2020 paragraph 6, and KDB 558074 were used during transmitter testing. Test sample EUT #2 Antenna Port Conducted was provided for testing antenna port conducted emissions. The transmitter peak and average power was measured at the antenna port using a wideband RF power meter as described in KDB 558074 and ANSI C63.10-2020. Average power measured did not include any time intervals during which the transmitter was off or transmitting at a reduced power level. The peak Power Spectral Density (PKPSD) was measured as defined in KDB 558074 and ANSI C63.10-2020. DTS Emission bandwidth was measured as described in KDB 558074 and ANSI C63.10-2020. The amplitude of each harmonic and general radiated emission was measured on the SAC at distance of 3 meters from the FSM antenna (radiated emission testing was performed on EUT #1 Radiated representative of production equipment with integral antenna). The EUT was positioned on supporting turntable elevated as required above the ground plane, at a distance of 3 meters from the FSM antenna. Radiated emission investigations were performed from 9 kHz to 9.265 GHz (tenth harmonic of highest fundamental frequency). Each radiated emission was maximized by varying the FSM antenna height and polarization, and by rotating the turntable. The worst-case amplitude of each emission was then recorded from the analyzer display. The peak and quasi-peak amplitude of frequencies below 1000 MHz were measured using a spectrum analyzer. The peak and average amplitude of frequencies above 1000 MHz were measured using a spectrum analyzer. A Loop antenna was used for measuring emissions from 0.009 to 30 MHz, Biconilog Antenna for 30 to 1000 MHz, Double-Ridge, and/or Pyramidal Horn Antennas from 1 GHz to 25 GHz. Radiated Emissions were measured in dBμV/m @ 3 meters. Plots were taken of transmitter performance (using EUT Antenna Port Conducted #2) for reference in this and other documentation. See figures 10 through 33 for these antenna port conducted results.

Worst case margins for radiated data were seen with antenna #4. See tables 9 through 13 for this radiated data.

Figure 10 Plot of Transmitter Operation in 902-928 MHz Mode 1, 802.11ah 1MHz




Figure 11 Plot of Transmitter Operation in 902-928 MHz Mode 2, 802.11ah 2MHz




Figure 12 Plot of Transmitter Operation in 902-928 MHz Mode 3, 802.11ah 4MHz




Figure 13 Plot of Transmitter Operation in 902-928 MHz Mode 4, 802.11ah 8MHz




Figure 14 Plot of Emissions Low Band Edge Mode 1, 802.11ah 1MHz




Figure 15 Plot of Emissions Low Band Edge Mode 2, 802.11ah 2MHz




Figure 16 Plot of Emissions Low Band Edge Mode 3, 802.11ah 4MHz




Figure 17 Plot of Emissions Low Band Edge Mode 4, 802.11ah 8MHz




Figure 18 Plot of Transmitter Emissions High Band Edge Mode 1, 802.11ah 1MHz




Figure 19 Plot of Transmitter Emissions High Band Edge Mode 2, 802.11ah 2MHz




Figure 20 Plot of Transmitter Emissions High Band Edge Mode 3, 802.11ah 4MHz




Figure 21 Plot of Transmitter Emissions High Band Edge Mode 4, 802.11ah 8MHz




Figure 22 Plot of 6-dB Occupied Bandwidth Mode 1, 802.11ah 1MHz




Figure 23 Plot of 99% Occupied Bandwidth Mode 1, 802.11ah 1MHz




Figure 24 Plot of 6-dB Occupied Bandwidth Mode 2, 802.11ah 2MHz




Figure 25 Plot of 99% Occupied Bandwidth Mode 2, 802.11ah 2MHz




Figure 26 Plot of 6-dB Occupied Bandwidth Mode 3, 802.11ah 4MHz




Figure 27 Plot of 99% Occupied Bandwidth Mode 3, 802.11ah 4MHz




Figure 28 Plot of 6-dB Occupied Bandwidth Mode 4, 802.11ah 8MHz




Figure 29 Plot of 99% Occupied Bandwidth Mode 4, 802.11ah 8MHz




Figure 30 Plot of Transmitter Power Spectral Density Mode 1, 802.11ah 1MHz




Figure 31 Plot of Transmitter Power Spectral Density Mode 2, 802.11ah 2MHz




Figure 32 Plot of Transmitter Power Spectral Density Mode 3, 802.11ah 4MHz





Figure 33 Plot of Transmitter Power Spectral Density Mode 4, 802.11ah 8MHz



Transmitter Emissions Data

Below radiated emission data was taken using Antenna #4 as it was found to be worst case margin.

Table 9 Transmitter Radiated Emissions Mode 1, 802.11ah 1MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
903.5	--	--	--	--	--	--	--
1807.0	47.3	33.7	44.2	30.4	54.0	-20.3	-23.6
2710.5	46.9	31.8	45.3	31.8	54.0	-22.2	-22.2
3614.0	46.0	33.1	46.3	33.0	54.0	-20.9	-21.0
4517.5	48.1	34.5	47.4	34.5	54.0	-19.5	-19.5
5421.0	49.9	36.3	50.0	36.3	54.0	-17.7	-17.7
6324.5	51.4	38.5	51.3	38.6	54.0	-15.5	-15.4
915.5	--	--	--	--	--	--	--
1831.0	53.2	37.2	45.4	31.3	54.0	-16.8	-22.7
2746.5	47.0	31.7	44.3	31.8	54.0	-22.3	-22.2
3662.0	47.4	33.8	46.9	33.7	54.0	-20.2	-20.3
4577.5	48.4	34.9	48.0	34.8	54.0	-19.1	-19.2
5493.0	50.5	37.3	50.5	37.3	54.0	-16.7	-16.7
6408.5	51.8	38.6	52.3	38.9	54.0	-15.4	-15.1
926.5	--	--	--	--	--	--	--
1853.0	56.5	39.3	52.4	36.1	54.0	-14.7	-17.9
2779.5	46.1	32.1	46.5	32.1	54.0	-21.9	-21.9
3706.0	48.0	34.3	47.9	34.3	54.0	-19.7	-19.7
4632.5	48.5	35.2	48.2	35.2	54.0	-18.8	-18.8
5559.0	50.7	37.0	50.4	37.0	54.0	-17.0	-17.0
6485.5	52.1	38.5	51.9	38.5	54.0	-15.5	-15.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 10 Transmitter Radiated Emissions Mode 2, 802.11ah 2MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
905.00	--	--	--	--	--	--	--
1810.00	51.0	37.0	45.5	32.0	54.0	-17.0	-22.0
2715.00	45.1	31.9	45.7	32.1	54.0	-22.1	-21.9
3620.00	47.4	33.2	46.1	33.1	54.0	-20.8	-20.9
4525.00	49.3	34.6	47.9	34.6	54.0	-19.4	-19.4
5430.00	50.2	36.5	49.6	36.5	54.0	-17.5	-17.5
6335.00	51.7	38.4	51.4	38.6	54.0	-15.6	-15.4
2437.0	--	--	--	--	--	--	--
4874.0	54.7	39.8	48.1	33.3	54.0	-14.2	-20.7
7311.0	45.0	31.7	45.1	31.9	54.0	-22.3	-22.1
9748.0	46.5	33.8	46.4	33.8	54.0	-20.2	-20.2
12185.0	48.3	34.9	47.7	34.9	54.0	-19.1	-19.1
14622.0	50.1	37.2	50.3	37.2	54.0	-16.8	-16.8
17059.0	51.5	38.6	52.3	39.2	54.0	-15.4	-14.8
2462.0	--	--	--	--	--	--	--
4924.0	57.4	42.2	52.9	38.1	54.0	-11.8	-15.9
7386.0	45.2	32.0	45.4	32.1	54.0	-22.0	-21.9
9848.0	46.7	33.8	46.6	33.8	54.0	-20.2	-20.2
12310.0	48.3	35.6	49.1	35.6	54.0	-18.4	-18.4
14772.0	49.6	36.6	49.4	36.6	54.0	-17.4	-17.4
17234.0	52.0	38.6	51.9	38.6	54.0	-15.4	-15.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 11 Transmitter Radiated Emissions Mode 3, 802.11ah 4MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
906.00	--	--	--	--	--	--	--
1812.00	51.3	36.4	45.2	31.5	54.0	-17.6	-22.5
2718.00	55.1	32.3	46.9	32.3	54.0	-21.7	-21.7
3624.00	47.8	33.7	46.5	33.5	54.0	-20.3	-20.5
4530.00	48.8	35.0	47.9	34.8	54.0	-19.0	-19.2
5436.00	50.2	36.7	50.7	36.6	54.0	-17.3	-17.4
6342.00	52.1	38.4	51.9	38.4	54.0	-15.6	-15.6
914.00	--	--	--	--	--	--	--
1828.00	53.1	38.3	47.1	32.6	54.0	-15.7	-21.4
2742.00	52.4	31.9	48.0	32.0	54.0	-22.1	-22.0
3656.00	47.7	34.2	47.1	34.1	54.0	-19.8	-19.9
4570.00	48.1	35.1	48.2	35.1	54.0	-18.9	-18.9
5484.00	50.0	37.0	49.9	36.9	54.0	-17.0	-17.1
6398.00	51.5	38.7	51.9	39.0	54.0	-15.3	-15.0
926.00	--	--	--	--	--	--	--
1852.00	54.2	38.3	50.5	35.0	54.0	-15.7	-19.0
2778.00	50.6	32.1	50.0	32.0	54.0	-21.9	-22.0
3704.00	47.7	34.1	47.2	34.0	54.0	-19.9	-20.0
4630.00	48.2	35.2	48.3	35.2	54.0	-18.8	-18.8
5556.00	50.1	36.8	50.0	36.8	54.0	-17.2	-17.2
6482.00	51.6	38.5	51.6	38.5	54.0	-15.5	-15.5

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 12 Transmitter Radiated Emissions Mode 4, 802.11ah 8MHz

Frequency in MHz	Horizontal Peak (dBμV/m)	Horizontal Average (dBμV/m)	Vertical Peak (dBμV/m)	Vertical Average (dBμV/m)	Limit @ 3m (dBμV/m)	Horizontal Margin (dB)	Vertical Margin (dB)
908.00	--	--	--	--	--	--	--
1816.00	48.1	32.0	44.3	29.7	54.0	-22.0	-24.3
2724.00	45.0	32.0	45.2	32.0	54.0	-22.0	-22.0
3632.00	46.7	33.8	46.9	33.8	54.0	-20.2	-20.2
4540.00	48.2	35.3	48.5	35.3	54.0	-18.7	-18.7
5448.00	49.1	36.0	49.3	36.0	54.0	-18.0	-18.0
6356.00	50.9	37.8	50.9	37.8	54.0	-16.2	-16.2
916.00	--	--	--	--	--	--	--
1832.00	52.2	34.1	45.4	30.1	54.0	-19.9	-23.9
2748.00	44.9	31.5	44.9	31.6	54.0	-22.5	-22.4
3664.00	46.5	33.5	46.6	33.5	54.0	-20.5	-20.5
4580.00	47.1	34.4	47.9	34.4	54.0	-19.6	-19.6
5496.00	50.4	37.2	50.4	37.3	54.0	-16.8	-16.7
6412.00	51.2	38.3	51.4	38.4	54.0	-15.7	-15.6
924.00	--	--	--	--	--	--	--
1848.00	52.8	34.8	48.2	31.9	54.0	-19.2	-22.1
2772.00	45.0	31.8	44.6	31.8	54.0	-22.2	-22.2
3696.00	46.5	33.4	46.7	33.4	54.0	-20.6	-20.6
4620.00	49.0	35.9	49.1	35.9	54.0	-18.1	-18.1
5544.00	49.7	36.2	48.8	36.2	54.0	-17.8	-17.8
6468.00	52.2	38.6	51.5	38.6	54.0	-15.4	-15.4

Other emissions present had amplitudes at least 20 dB below the limit. Peak and Quasi-Peak amplitude emissions are recorded for frequency below 1000 MHz. Peak and Average amplitude emissions are recorded for frequency range above 1000 MHz.

Table 13 Transmitter Antenna Port Conducted Data modes 1 through 4

Frequency MHz	Antenna Port Average Output Power (Watts)	99% Occupied Bandwidth (kHz)	6-dB Occupied Bandwidth (kHz)	Peak Power Spectral Density (dBm)
Mode 1, 802.11ah 1MHz				
903.5	0.344	864.0	798.0	6.9
915.5	0.312	865.5	795.0	6.5
926.5	0.328	864.0	790.5	6.3
Mode 2, 802.11ah 2MHz				
905.0	0.420	1,802.5	1,711.3	4.4
915.0	0.404	1,797.5	1,696.3	4.2
925.0	0.395	1,800.0	1,712.5	4.2
Mode 3, 802.11ah 4MHz				
906.0	0.435	3,865.0	3,573.7	2.4
914.0	0.428	3,772.5	3,597.5	2.4
926.0	0.392	3,620.0	3,585.3	-0.9
Mode 4, 802.11ah 8MHz				
908.0	0.513	7,650.0	7,500.0	0.4
916.0	0.494	7,660.0	7,537.9	-0.4
924.0	0.468	7,555.0	7,528.8	-2.1

Summary of Results for Transmitter Radiated Emissions of Intentional Radiator

The EUT demonstrated compliance with the radiated and conducted emission requirements of 47CFR Subpart 15C Paragraph 15.247, RSS-247 Issue 4 and RSS-GEN Issue 5 emission requirements for Digital Transmission Systems. The highest average output power measured at the antenna port for modes 1 through 4 was 0.513 Watts. The highest peak power spectral density measured at the antenna port for modes 1 through 4 presented a minimum margin of -1.1 dB below the requirements. The EUT demonstrated a minimum margin of -11.8 dB below the harmonic emissions requirements. There were no other significantly measurable emissions in the restricted bands other than those recorded in this report. Other emissions were present with amplitudes at least 20 dB below the requirements. There were no other deviations or exceptions to the requirements.

Frequency Stability

Frequency stability of the transmitter was checked over extreme conditions and found to stay within the 902.0 to 928.0 MHz band under all conditions.

Parameter	Worst Case (MHz)	Result
f _{LO}	903.054	PASSES
f _{HI}	927.780	PASSES

Annex

- Annex A Measurement Uncertainty Calculations
- Annex B Test Equipment
- Annex C Laboratory Certificate of Accreditation

Annex A Measurement Uncertainty Calculations

The measurement uncertainty was calculated for all measurements listed in this test report according To CISPR 16–4. Result of measurement uncertainty calculations are recorded below. Component and process variability of production devices similar to those tested may result in additional deviations. The manufacturer has the sole responsibility of continued compliance.

Measurement	Expanded Measurement Uncertainty $U_{(lab)}$
3 Meter Horizontal 0.009-1000 MHz Measurements	4.16
3 Meter Vertical 0.009-1000 MHz Measurements	4.33
3 Meter Measurements 1-18 GHz	5.46
3 Meter Measurements 18-40 GHz	5.16
10 Meter Horizontal Measurements 0.009-1000 MHz	4.15
10 Meter Vertical Measurements 0.009-1000 MHz	4.32
AC Line Conducted	1.75
Antenna Port Conducted power	1.17
Frequency Stability	1.00E-11
Temperature	1.6°C
Humidity	3%

Annex B Test Equipment

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
☒ LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/20/2025	3/20/2026
☐ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	9/9/2025	9/9/2026
☒ Antenna	Com Power	AL-130 (121055)	.001-30 MHz	9/2/2025	9/2/2026
☐ Antenna:	EMCO	6509	.001-30 MHz	9/16/2024	9/16/2026
☒ Antenna	ARA	BCD-235-B (169)	20-350MHz	9/2/2025	9/2/2026
☒ Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	9/2/2025	9/2/2026
☐ Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	9/16/2024	9/16/2026
☒ Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/17/2025	3/17/2027
☒ Antenna	Com Power	AH-118 (10110)	1-18 GHz	9/16/2024	9/16/2026
☒ Antenna	Com Power	AH-1840 (101046)	18-40 GHz	3/17/2025	3/17/2027
☒ Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	7/9/2025	7/9/2026
☒ Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/21/2025	1/21/2026
☐ Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
☐ Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	9/9/2025	9/9/2026
☐ Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	9/9/2025	9/9/2026
☒ Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	9/9/2025	9/9/2026
☒ Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	9/9/2025	9/9/2026
☒ Pwr Sensor	Rohde & Schwarz	NRP33T	0.05-33 GHz	9/9/2025	9/9/2026
☒ Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/19/2025	3/19/2026
☐ RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/21/2025	3/21/2026
☒ Weather station	Davis	6152 (A70927D44N)		1/23/2026	1/23/2027

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
☒ Frequency Counter: Leader		LDC-825 (8060153)		3/19/2025	3/19/2026
☐ ISN	Com-Power	Model ISN T-8 (600111)		3/19/2025	3/19/2026
☒ LISN:	Com-Power	Model LI-220A		9/16/2024	9/16/2026
☐ LISN:	Com-Power	Model LI-550C		9/16/2024	9/16/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303072)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L1M)(281183)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(4M)(281184)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(317546)	9kHz-40 GHz	9/9/2025	9/9/2026
☒ Cable	Time Microwave	4M-750HF290-750 (L4M)	9kHz-24 GHz	9/9/2025	9/9/2026
☒ Cable	Mini-Circuits	KBL-2M-LOW+ (23090329)	9kHz-40 GHz	3/22/2025	3/22/2026
☒ Analyzer	HP	8562A (3051A05950)	9kHz-125GHz	3/20/2025	3/20/2026
☐ Antenna:	Solar	9229-1 & 9230-1		2/5/2025	2/5/2026
☐ CDN:	Com-Power	Model CDN M325E		9/16/2024	9/16/2026
☐ Oscilloscope Scope: Tektronix		MDO 4104		2/5/2025	2/5/2026
☐ EMC Transient Generator HVT		TR 3000		2/5/2025	2/5/2026
☐ AC Power Source (Ametech, California Instruments)				2/5/2025	2/5/2026
☒ Field Intensity Meter: EFM-018				2/5/2025	2/5/2026
☒ ESD Simulator: MZ-15				2/5/2025	2/5/2026
☐ Injection Clamp Luthi Model EM101				not required	
☐ R.F. Power Amp ACS 230-50W				not required	
☐ R.F. Power Amp EIN Model: A301				not required	
☐ R.F. Power Amp A.R. Model: 10W 1010M7				not required	
☐ R.F. Power Amp A.R. Model: 50U1000				not required	
☒ Temperature Chamber				not required	
☒ Shielded Room				not required	

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
☒ LISN	FCC	FCC-LISN-50-25-10(1PA) (160611)	.15-30MHz	3/20/2025	3/20/2026
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(303073)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303069)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Belden	RG-58 (L1-CAT3-11509)	9kHz-30 MHz	9/16/2024	9/16/2025
☐ Cable	Belden	RG-58 (L2-CAT3-11509)	9kHz-30 MHz	9/16/2024	9/16/2025
☒ Antenna	Com Power	AL-130 (121055)	.001-30 MHz	9/16/2024	9/16/2025
☐ Antenna:	EMCO	6509	.001-30 MHz	9/16/2024	9/16/2026
☒ Antenna	ARA	BCD-235-B (169)	20-350MHz	9/16/2024	9/16/2025
☒ Antenna	Sunol	JB-6 (A100709)	30-1000 MHz	9/16/2024	9/16/2025
☐ Antenna	ETS-Lindgren	3147 (40582)	200-1000MHz	9/16/2024	9/16/2026
☒ Antenna	ETS-Lindgren	3117 (200389)	1-18 GHz	3/17/2025	3/17/2027
☒ Antenna	Com Power	AH-118 (10110)	1-18 GHz	9/16/2024	9/16/2026
☒ Antenna	Com Power	AH-1840 (101046)	18-40 GHz	3/17/2025	3/17/2027
☒ Analyzer	Rohde & Schwarz	ESU40 (100108)	20Hz-40GHz	7/9/2025	7/9/2026
☒ Analyzer	Rohde & Schwarz	ESW44 (101534)	20Hz-44GHz	1/21/2025	1/21/2026
☐ Analyzer	Rohde & Schwarz	FS-Z60, 90, 140, and 220	40GHz-220GHz	12/22/2017	12/22/2027
☐ Amplifier	Com-Power	PA-010 (171003)	100Hz-30MHz	9/16/2024	9/16/2025
☐ Amplifier	Com-Power	CPPA-102 (01254)	1-1000 MHz	9/16/2024	9/16/2025
☒ Amplifier	Com-Power	PAM-118A (551014)	0.5-18 GHz	9/16/2024	9/16/2025
☒ Amplifier	Com-Power	PAM-840A (461328)	18-40 GHz	9/16/2024	9/16/2025
☒ Pwr Sensor	Rohde & Schwarz	NRP33T	0.05-33 GHz	9/26/2023	9/26/2025
☒ Generator	Rohde & Schwarz	SMBV100A6 (260771)	20Hz-6 GHz	3/19/2025	3/19/2026
☐ RF Filter	Micro-Tronics	BRC50722 (009).9G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ RF Filter	Micro-Tronics	HPM50117 (063) 3G HPF	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRM50702 (172) 2G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50703 (G102) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☒ RF Filter	Micro-Tronics	BRC50705 (024) 5G notch	30-18000 MHz	3/21/2025	3/21/2026
☐ Attenuator	Fairview	SA6NFN100W-40 (1625)	30-18000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1445)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-3W2+ (1735)	30-6000 MHz	3/21/2025	3/21/2026
☒ Attenuator	Mini-Circuits	VAT-6W2+ (1438)	30-6000 MHz	3/21/2025	3/21/2026
☒ Weather station	Davis	6152 (A70927D44N)		11/4/2024	11/4/2025

<u>Equipment</u>	<u>Manufacturer</u>	<u>Model (SN)</u>	<u>Band</u>	<u>Cal Date(m/d/y)</u>	<u>Due</u>
☒ Frequency Counter: Leader		LDC-825 (8060153)		3/19/2025	3/19/2026
☐ ISN	Com-Power	Model ISN T-8 (600111)		3/19/2025	3/19/2026
☐ LISN:	Com-Power	Model LI-220A		9/16/2024	9/16/2026
☒ LISN:	Com-Power	Model LI-550C		9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(1.5M)(303072)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L1M)(281183)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(4M)(281184)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Huber & Suhner Inc.	Sucoflex102ea(L10M)(317546)	9kHz-40 GHz	9/16/2024	9/16/2025
☒ Cable	Time Microwave	4M-750HF290-750 (L4M)	9kHz-24 GHz	9/16/2024	9/16/2025
☒ Cable	Mini-Circuits	KBL-2M-LOW+ (23090329)	9kHz-40 GHz	3/22/2025	3/22/2026
☒ Analyzer	HP	8562A (3051A05950)	9kHz-125GHz	3/20/2025	3/20/2026
☐ Antenna:	Solar	9229-1 & 9230-1		2/5/2025	2/5/2026
☐ CDN:	Com-Power	Model CDN M325E		9/16/2024	9/16/2026
☐ Oscilloscope Scope: Tektronix		MDO 4104		2/5/2025	2/5/2026
☐ EMC Transient Generator HVT		TR 3000		2/5/2025	2/5/2026
☐ AC Power Source (Ametech, California Instruments)				2/5/2025	2/5/2026
☒ Field Intensity Meter: EFM-018				2/5/2025	2/5/2026
☒ ESD Simulator: MZ-15				2/5/2025	2/5/2026
☐ Injection Clamp Luthi Model EM101				not required	
☐ R.F. Power Amp ACS 230-50W				not required	
☐ R.F. Power Amp EIN Model: A301				not required	
☐ R.F. Power Amp A.R. Model: 10W 1010M7				not required	
☐ R.F. Power Amp A.R. Model: 50U1000				not required	
☒ Temperature Chamber				not required	
☒ Shielded Room				not required	
POSSIBLY USE FOR GARMIN GPS TESTING					
☐ GNSS Sig Gen SG80K, SN: GNSS-00952				not required	

Annex C Laboratory Certificate of Accreditation

United States Department of Commerce
National Institute of Standards and Technology



Certificate of Accreditation to ISO/IEC 17025:2017

NVLAP LAB CODE: 200087-0

Rogers Labs, a division of The Compatibility Center LLC
Lenexa, KS

*is accredited by the National Voluntary Laboratory Accreditation Program for specific services,
listed on the Scope of Accreditation, for:*

Electromagnetic Compatibility & Telecommunications

*This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2017.
This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality
management system (refer to joint ISO-ILAC-IAF Communique on ISO/IEC 17025).*

2025-03-11 through 2026-03-31
Effective Dates




For the National Voluntary Laboratory Accreditation Program

Rogers Labs, a division of The Compatibility Center LLC
7915 Nieman Road FCC ID: 2AQ2Q-HALOW1 IC: 27013-HALOW1
Lenexa, KS 66214 Test: 250514
Phone/Fax: (913) 660-0666 Test to: 47CFR 15C, RSS-Gen RSS-247
Revision 1 File: CARGT HaLow DTS TstRpt 250514 r1

CARGT Inc.
PMN: HALOW1
SN's: N/A
Date: February 25, 2026
Page 78 of 78