



FCC PART 15.247

TEST REPORT

For

Shenzhen VanTop Technology & Innovation Co., Ltd.

502, 5th Flr. BLDG 4, MinQi Technology Park, No. 65 Lishan Road, Taoyuan Street,
Nanshan District, Shenzhen, China

FCC ID: 2AQ3A-A10Q2420

Report Type: Original Report	Product Type: R/C QUADCOPTER
Report Number: RSZ200608008-00B	
Report Date: 2020-08-14	
Reviewed By: RF Engineer	Nancy Wang 
Prepared By: Bay Area Compliance Laboratories Corp. (Shenzhen) 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China Tel: +86-755-33320018 Fax: +86-755-33320008 www.baclcorp.com.cn	

Note: This report must not be used by the customer to claim product certification, approval, or endorsement by A2LA* or any agency of the Federal Government. This report may contain data that are not covered by the A2LA accreditation and are marked with an asterisk “★”.

BACL is not responsible for the authenticity of any test data provided by the applicant. Data included from the applicant that may affect test results are marked with an asterisk “*”. Customer model name, addresses, names, trademarks etc. are not considered data.

This report cannot be reproduced except in full, without prior written approval of the Company. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested. This report is valid only with a valid digital signature. The digital signature may be available only under the Adobe software above version 7.0.

TABLE OF CONTENTS

GENERAL INFORMATION.....	4
PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT)	4
OBJECTIVE	4
RELATED SUBMITTAL(S)/GRANT(S).....	4
TEST METHODOLOGY	4
MEASUREMENT UNCERTAINTY	5
SYSTEM TEST CONFIGURATION.....	6
DESCRIPTION OF TEST CONFIGURATION	6
EQUIPMENT MODIFICATIONS	6
EUT EXERCISE SOFTWARE	6
DUTY CYCLE	7
SUPPORT EQUIPMENT LIST AND DETAILS	7
EXTERNAL I/O CABLE.....	7
BLOCK DIAGRAM OF TEST SETUP	7
SUMMARY OF TEST RESULTS.....	8
TEST EQUIPMENT LIST	9
FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE).....	10
APPLICABLE STANDARD	10
RESULT	10
FCC §15.203 - ANTENNA REQUIREMENT.....	11
APPLICABLE STANDARD	11
ANTENNA CONNECTOR CONSTRUCTION	11
FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS.....	12
APPLICABLE STANDARD	12
EUT SETUP.....	12
EMI TEST RECEIVER & SPECTRUM ANALYZER SETUP	13
TEST PROCEDURE	13
CORRECTED AMPLITUDE & MARGIN CALCULATION	13
TEST DATA	13
FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH.....	22
APPLICABLE STANDARD	22
TEST PROCEDURE	22
TEST DATA	22
FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER.....	23
APPLICABLE STANDARD	23
TEST PROCEDURE	23
TEST DATA	23
FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE.....	24
APPLICABLE STANDARD	24
TEST PROCEDURE	24
TEST DATA	24

FCC §15.247(e) - POWER SPECTRAL DENSITY	25
APPLICABLE STANDARD	25
TEST PROCEDURE	25
TEST DATA	25
APPENDIX	26
APPENDIX A: DTS BANDWIDTH	26
APPENDIX B: MAXIMUM CONDUCTED OUTPUT POWER	30
APPENDIX C: MAXIMUM POWER SPECTRAL DENSITY	31
APPENDIX D: BAND EDGE MEASUREMENTS	35
APPENDIX E: DUTY CYCLE	38

GENERAL INFORMATION

Product Description for Equipment under Test (EUT)

Product	R/C QUADCOPTER
Tested Model	A10
Multiple Models	A30, A32, A35, A36, A37, A38, SP100, SP160, SP180, SP220, SP270, SP380
Model Difference	Refer to the DoS letter
Frequency Range	Wi-Fi: 2412~2472MHz
Maximum Conducted Peak Output Power	Wi-Fi: 10.73dBm(802.11b), 12.91dBm(802.11g),12.77dBm(802.11n-HT20)
Modulation Technique	Wi-Fi: DSSS, OFDM
Antenna Specification	Integral Antenna 0.8 dBi
Voltage Range	DC 3.7V from battery
Date of Test	2020/06/29~2020/08/14
Sample serial number	RSZ200608008-RF-S1 (Assigned by BACL, Shenzhen)
Received date	2020/06/08
Sample/EUT Status	Good condition

Objective

This report is prepared on behalf of *Shenzhen VanTop Technology & Innovation Co., Ltd.* in accordance with Part 2-Subpart J, Part 15-Subparts A and C of the Federal Communication Commission's rules.

The tests were performed in order to determine compliance with FCC Part 15, Subpart C, and section 15.203, 15.205, 15.209 and 15.247 rules.

Related Submittal(s)/Grant(s)

Part of system submission with FCC ID: 2AQ3A-A10R2420.

Test Methodology

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

And KDB 558074 D01 15.247 Meas Guidance v05r02.

All emissions measurement was performed at Bay Area Compliance Laboratories Corp. (Shenzhen). The radiated testing was performed at an antenna-to-EUT distance of 3 meters.

Measurement Uncertainty

Parameter		Uncertainty
Occupied Channel Bandwidth		±5%
RF Output Power with Power meter		±0.73dB
RF conducted test with spectrum		±1.6dB
AC Power Lines Conducted Emissions		±1.95dB
Emissions, Radiated	Below 1GHz	±4.75dB
	Above 1GHz	±4.88dB
Temperature		±1 °C
Humidity		±6%
Supply voltages		±0.4%

Note: The extended uncertainty given in this report is obtained by combining the standard uncertainty times the coverage factor K with the 95% confidence interval. Otherwise required by the applicant or Product Regulations, Decision Rule in this report did not consider the uncertainty.

Test Facility

The test site used by Bay Area Compliance Laboratories Corp. (Shenzhen) to collect test data is located on the 6/F., West Wing, Third Phase of Wanli Industrial Building, Shihua Road, Futian Free Trade Zone, Shenzhen, Guangdong, China.

The test site has been approved by the FCC under the KDB 974614 D01 and is listed in the FCC Public Access Link (PAL) database, FCC Registration No.: 342867, the FCC Designation No.: CN1221.

The test site has been registered with ISED Canada under ISED Canada Registration Number 3062B.

SYSTEM TEST CONFIGURATION

Description of Test Configuration

For 802.11b, 802.11g and 802.11n-HT20 mode, 13 channels are provided to testing:

Channel	Frequency (MHz)	Channel	Frequency (MHz)
1	2412	8	2447
2	2417	9	2452
3	2422	10	2457
4	2427	11	2462
5	2432	12	2467
6	2437	13	2472
7	2442	/	/

For 802.11b, 802.11g, EUT was tested with Channel 1, 2, 7 and 13.

For 802.11n-HT20 mode, EUT was tested with Channel 1, 7 and 13.

Equipment Modifications

No modification was made to the EUT tested.

EUT Exercise Software

“fcc show” software was used.

The device was tested with the worst case was performed as below:

Mode	Data rate	Power level			
		Low channel	2417MHz	Middle channel	High channel
802.11b	1 Mbps	28	35	35	35
802.11g	6 Mbps	35	45	45	45
802.11n-HT20	MCS0	40	/	45	45

Duty cycle


Test Result: Compliant. Please refer to the Appendix.

Support Equipment List and Details

Manufacturer	Description	Model	Serial Number
/	/	/	/

External I/O Cable

Cable Description	Length (m)	From Port	To
/	/	/	/

Block Diagram of Test Setup

SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
§15.247 (i), §1.1307 (b) (1)& §2.1091	Maximum Permissible exposure (MPE)	Compliance
§15.203	Antenna Requirement	Compliance
§15.207 (a)	AC Line Conducted Emissions	Not Applicable
§15.205, §15.209, §15.247(d)	Spurious Emissions	Compliance
§15.247 (a)(2)	6 dB Emission Bandwidth	Compliance
§15.247(b)(3)	Maximum Conducted Output Power	Compliance
§15.247(d)	100 kHz Bandwidth of Frequency Band Edge	Compliance
§15.247(e)	Power Spectral Density	Compliance

Not Applicable: The EUT was powered by battery only.

TEST EQUIPMENT LIST

Manufacturer	Description	Model	Serial Number	Calibration Date	Calibration Due Date
Radiated Emission Test					
R&S	EMI Test Receiver	ESR3	102455	2019/7/9	2020/7/8
Sonoma instrument	Pre-amplifier	310 N	186238	2020/4/20	2021/4/20
Sunol Sciences	Broadband Antenna	JB1	A040904-1	2017/12/22	2020/12/21
Unknown	Cable 2	RF Cable 2	F-03-EM197	2019/11/29	2020/11/28
Unknown	Cable	Chamber Cable 1	F-03-EM236	2019/11/29	2020/11/28
Rohde & Schwarz	Auto test software	EMC 32	V9.10	NCR	NCR
Rohde & Schwarz	Spectrum Analyzer	FSV40-N	102259	2019/7/22	2020/7/21
COM-POWER	Pre-amplifier	PA-122	181919	2019/11/29	2020/11/28
Quinstar	Amplifier	QLW-18405536-J0	15964001002	2019/11/29	2020/11/28
Sunol Sciences	Horn Antenna	DRH-118	A052604	2017/12/22	2020/12/21
Insulted Wire Inc.	RF Cable	SPS-2503-3150	02222010	2019/11/29	2020/11/28
Unknown	RF Cable	W1101-EQ1 OUT	F-19-EM005	2019/11/29	2020/11/28
SNSD	Band Reject filter	BSF2402-2480MN-0898-001	2.4G filter	2020/4/20	2021/4/20
Ducommun Technologies	Horn antenna	ARH-4223-02	1007726-02 1304	2017/12/6	2020/12/5
RF Conducted Test					
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2019/7/10	2020/7/9
Tonscend Corporation	RF control Unit	JS0806-2	19D8060154	2020/7/10	2021/7/9
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2019/7/22	2020/7/21
Rohde & Schwarz	Signal and Spectrum Analyzer	FSV40	101473	2020/7/22	2021/7/21
Unknown	RF Cable	Unknown	2301 276	2019/11/29	2020/11/28

* **Statement of Traceability:** Bay Area Compliance Laboratories Corp. (Shenzhen) attests that all calibrations have been performed in accordance to requirements that traceable to National Primary Standards and International System of Units (SI).

FCC §15.247 (i) & §1.1307 (b) (1) & §2.1091- MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Applicable Standard

According to subpart 15.247 (i) and subpart 1.1307 (b)(1), 2.1091 systems operating under the provisions of this section shall be operated in a manner that ensures the public is not exposed to RF energy level in excess of the communication guidelines.

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (Minutes)
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	/	/	f/1500	30
1500-100,000	/	/	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Result

Calculated Formulary:

Predication of MPE limit at a given distance

$$S = \frac{PG}{4\pi R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = power input to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Frequency (MHz)	Antenna Gain		Max Tune-up Conducted Power		Evaluation Distance (cm)	Power Density (mW/cm ²)	MPE Limit (mW/cm ²)
	(dBi)	(numeric)	(dBm)	(mW)			
2412-2472	0.8	1.2	13.0	19.95	20	0.005	1

Note: To maintain compliance with the FCC's RF exposure guidelines, place the equipment at least 20cm from nearby persons.

Result: Compliance

FCC §15.203 - ANTENNA REQUIREMENT

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
 - b. Antenna must use a unique type of connector to attach to the EUT.
- Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has an integral antenna arrangement, which was permanently attached and the antenna gain is 0.8dBi, fulfill the requirement of this section. Please refer to the EUT photos.


Result: Compliance.

FCC §15.209, §15.205 & §15.247(d) - SPURIOUS EMISSIONS**Applicable Standard**


FCC §15.247 (d); §15.209; §15.205;

EUT Setup

Below 1 GHz:



Above 1GHz:



The radiated emission tests were performed in the 3 meters test site, using the setup accordance with the ANSI C63.10-2013. The specification used was the FCC 15.209, and FCC 15.247 limits.

EMI Test Receiver & Spectrum Analyzer Setup

The system was investigated from 30 MHz to 25 GHz.

During the radiated emission test, the EMI test receiver & Spectrum Analyzer Setup were set with the following configurations:

Frequency Range	RBW	Video B/W	IF B/W	Measurement
30 MHz – 1000 MHz	100 kHz	300 kHz	120 kHz	QP
Above 1 GHz	1MHz	3 MHz	/	PK
	1MHz	10 Hz ^{Note 1}	/	Average
	1MHz	> 1/T ^{Note 2}	/	Average

Note 1: when duty cycle is no less than 98%

Note 2: when duty cycle is less than 98%

Test Procedure

Maximizing procedure was performed on the highest emissions to ensure that the EUT complied with all installation combinations.

Data was recorded in Quasi-peak detection mode for frequency range of 30 MHz-1 GHz, peak and Average detection modes for frequencies above 1 GHz.

Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Loss, and subtracting the Amplifier Gain from the Meter Reading. The basic equation is as follows:

$$\text{Corrected Amplitude} = \text{Meter Reading} + \text{Antenna Factor} + \text{Cable Loss} - \text{Amplifier Gain}$$

The “**Margin**” column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of 7dB means the emission is 7dB below the limit. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Limit} - \text{Corrected Amplitude}$$

Test Data


Environmental Conditions

Temperature:	26 °C
Relative Humidity:	60 %
ATM Pressure:	101.0 kPa

The testing was performed by Charlie Cha on 2020-07-05 for below 1GHz and by Leven Gan on 2020-06-29 for above 1GHz.

EUT operation mode: Transmitting (Worst case at 802.11n20 mode, Low channel)

30 MHz~1 GHz:



Frequency (MHz)	Corrected Amplitude (dBμV/m)	Antenna height (cm)	Antenna Polarity	Turntable position (degree)	Correction Factor (dB/m)	Limit (dBμV/m)	Margin (dB)
190.402000	34.65	166.0	V	285.0	-15.1	43.50	8.85
193.558625	34.99	377.0	V	236.0	-14.7	43.50	8.51
585.674125	37.90	119.0	V	95.0	-2.3	46.00	8.10
595.314375	39.56	108.0	V	356.0	-1.8	46.00	6.44
764.840375	40.41	212.0	H	201.0	0.3	46.00	5.59
846.014250	40.25	258.0	H	177.0	3.0	46.00	5.75

1 GHz-25 GHz:**802.11b Mode:**

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2388.79	28.31	PK	163	2.2	H	31.87	60.18	74	13.82
2388.79	13.56	Ave.	163	2.2	H	31.87	45.43	54	8.57
2484.53	27.83	PK	3	1.9	H	32.13	59.96	74	14.04
2484.53	13.45	Ave.	3	1.9	H	32.13	45.58	54	8.42
4824.00	52.55	PK	105	2.4	H	6.28	58.83	74	15.17
4824.00	45.20	Ave.	105	2.4	H	6.28	51.48	54	2.52
2417MHz									
2389.79	28.61	PK	358	2.0	H	31.87	60.48	74	13.52
2389.79	14.28	Ave.	358	2.0	H	31.87	46.15	54	7.85
2484.56	27.86	PK	295	2.3	H	32.13	59.99	74	14.01
2484.56	14.41	Ave.	295	2.3	H	32.13	46.54	54	7.46
4834.00	52.14	PK	163	1.7	H	5.40	57.54	74	16.46
4834.00	45.39	Ave.	163	1.7	H	5.40	50.79	54	3.21
Middle Channel (2442 MHz)									
4884.00	52.99	PK	237	2.0	H	6.76	59.75	74	14.25
4884.00	45.04	Ave.	237	2.0	H	6.76	51.80	54	2.20
High Channel (2472 MHz)									
2378.86	27.46	PK	237	1.3	H	31.87	59.33	74	14.67
2378.86	13.57	Ave.	237	1.3	H	31.87	45.44	54	8.56
2483.70	28.85	PK	308	1.2	H	32.13	60.98	74	13.02
2483.70	13.69	Ave.	308	1.2	H	32.13	45.82	54	8.18
4944.00	52.33	PK	323	1.8	H	6.76	59.09	74	14.91
4944.00	44.51	Ave.	323	1.8	H	6.76	51.27	54	2.73

802.11g Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2388.76	28.92	PK	223	1.7	H	31.87	60.79	74	13.21
2388.76	14.12	Ave.	223	1.7	H	31.87	45.99	54	8.01
2484.27	28.45	PK	354	1.0	H	32.13	60.58	74	13.42
2484.27	14.03	Ave.	354	1.0	H	32.13	46.16	54	7.84
4824.00	53.33	PK	117	2.2	H	6.28	59.61	74	14.39
4824.00	44.90	Ave.	117	2.2	H	6.28	51.18	54	2.82
2417MHz									
2389.24	28.82	PK	14	1.7	H	31.87	60.69	74	13.31
2389.24	13.74	Ave.	14	1.7	H	31.87	45.61	54	8.39
2484.91	28.06	PK	124	2.4	H	32.13	60.19	74	13.81
2484.91	14.01	Ave.	124	2.4	H	32.13	46.14	54	7.86
4834.00	52.29	PK	289	1.7	H	5.40	57.69	74	16.31
4834.00	45.42	Ave.	289	1.7	H	5.40	50.82	54	3.18
Middle Channel (2442 MHz)									
4884.00	51.57	PK	172	1.2	H	6.76	58.33	74	15.67
4884.00	43.92	Ave.	172	1.2	H	6.76	50.68	54	3.32
High Channel (2472 MHz)									
2389.74	28.28	PK	331	1.9	H	31.87	60.15	74	13.85
2389.74	14.11	Ave.	331	1.9	H	31.87	45.98	54	8.02
2483.51	39.55	PK	205	1.6	H	32.13	71.68	74	2.32
2483.51	17.47	Ave.	205	1.6	H	32.13	49.60	54	4.40
4944.00	46.32	PK	347	1.6	H	6.76	53.08	74	20.92
4944.00	39.50	Ave.	347	1.6	H	6.76	46.26	54	7.74

802.11n-HT20 Mode:

Frequency (MHz)	Receiver		Turntable Degree	Rx Antenna		Corrected Factor (dB/m)	Corrected Amplitude (dBμV/m)	Limit (dBμV/m)	Margin (dB)
	Reading (dBμV)	PK/QP/Ave.		Height (m)	Polar (H/V)				
Low Channel (2412 MHz)									
2388.94	31.04	PK	252	1.6	H	31.87	62.91	74	11.09
2388.94	14.27	Ave.	252	1.6	H	31.87	46.14	54	7.86
2484.11	28.24	PK	38	1.5	H	32.13	60.37	74	13.63
2484.11	14.05	AV	38	1.5	H	32.13	46.18	54	7.82
4824.00	53.49	PK	172	1.6	H	6.28	59.77	74	14.23
4824.00	45.02	Ave.	172	1.6	H	6.28	51.30	54	2.70
Middle Channel (2442 MHz)									
4884.00	53.58	PK	349	1.8	H	6.76	60.34	74	13.66
4884.00	44.43	Ave.	349	1.8	H	6.76	51.19	54	2.81
High Channel (2472 MHz)									
2389.64	28.41	PK	261	1.2	H	31.87	60.28	74	13.72
2389.64	14.17	Ave.	261	1.2	H	31.87	46.04	54	7.96
2483.58	39.49	PK	336	1.2	H	32.13	71.62	74	2.38
2483.58	17.32	Ave.	336	1.2	H	32.13	49.45	54	4.55
4944.00	47.37	PK	70	2.3	H	6.76	54.13	74	19.87
4944.00	40.13	Ave.	70	2.3	H	6.76	46.89	54	7.11

Note:

Corrected Factor = Antenna factor (RX) + Cable Loss – Amplifier Factor


Corrected Amplitude = Corrected Factor + Reading

Margin = Limit - Corrected. Amplitude


The other spurious emission which is 20dB to the limit was not recorded.

And for the pre-scan is performed with the 2400-2483.5MHz band filter.

**Pre-scan with 802.11b Mode, middle channel
Horizontal**




Date: 29.JUN.2020 19:32:42




Date: 29.JUN.2020 20:21:32

Vertical




Date: 29.JUN.2020 19:40:17




Date: 29.JUN.2020 20:28:39

Pre-scan for Average Horizontal




Date: 29.JUN.2020 19:35:38




Date: 29.JUN.2020 20:25:11

Vertical



Date: 29.JUN.2020 19:44:02



Date: 29.JUN.2020 20:32:03


FCC §15.247(a) (2) – 6 dB EMISSION BANDWIDTH

Applicable Standard

Systems using digital modulation techniques may operate in the 902–928 MHz, 2400–2483.5 MHz, and 5725–5850 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect it to measurement instrument. Then set it to any one convenient frequency within its operating range. Set a reference level on the measuring instrument equal to the highest peak value.
3. Measure the frequency difference of two frequencies that were attenuated 6 dB from the reference level. Record the frequency difference as the emission bandwidth.
4. Repeat above procedures until all frequencies measured were complete.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Gavin Guo on 2020-07-01.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix.


FCC §15.247(b) (3) - MAXIMUM CONDUCTED OUTPUT POWER

Applicable Standard

According to FCC §15.247(b) (3), for systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.

Test Procedure

1. Place the EUT on a bench and set it in transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to one test equipment.
3. Add a correction factor to the display.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Gavin Guo on 2020-07-01.

EUT operation mode: Transmitting


Test Result Compliant. Please refer to the Appendix.

FCC §15.247(d) – 100 kHz BANDWIDTH OF FREQUENCY BAND EDGE**Applicable Standard**

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Test Procedure

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Position the EUT without connection to measurement instrument. Turn on the EUT and connect its antenna terminal to measurement instrument via a low loss cable. Then set it to any one measured frequency within its operating range, and make sure the instrument is operated in its linear range.
3. Set RBW to 100 kHz and VBW of spectrum analyzer to 300 kHz with a convenient frequency span including 100 kHz bandwidth from band edge.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.

**Test Data****Environmental Conditions**

Temperature:	25 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Gavin Guo on 2020-07-01 and 2020-08-14.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix.


FCC §15.247(e) - POWER SPECTRAL DENSITY

Applicable Standard

For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.

Test Procedure

1. Use this procedure when the maximum peak conducted output power in the fundamental emission is used to demonstrate compliance.
2. Set the RBW to: $3\text{ kHz} \leq \text{RBW} \leq 100\text{ kHz}$.
3. Set the VBW $\geq 3 \times \text{RBW}$.
4. Set the span to 1.5 times the DTS bandwidth.
5. Detector = peak.
6. Sweep time = auto couple.
7. Trace mode = max hold.
8. Allow trace to fully stabilize.
9. Use the peak marker function to determine the maximum amplitude level within the RBW.
10. If measured value exceeds limit, reduce RBW (no less than 3 kHz) and repeat.



Test Data

Environmental Conditions

Temperature:	25 °C
Relative Humidity:	54 %
ATM Pressure:	101.0 kPa

The testing was performed by Gavin Guo on 2020-07-01.

EUT operation mode: Transmitting

Test Result Compliant. Please refer to the Appendix.

APPENDIX


Appendix A: DTS Bandwidth

Test Result


TestMode	Antenna	Channel	DTS BW [MHz]	Limit[MHz]	Verdict
11B	Ant1	2412	9.120	0.5	PASS
		2442	9.120	0.5	PASS
		2472	9.120	0.5	PASS
11G	Ant1	2412	16.480	0.5	PASS
		2442	16.440	0.5	PASS
		2472	16.400	0.5	PASS
11N20SISO	Ant1	2412	17.680	0.5	PASS
		2442	17.440	0.5	PASS
		2472	17.600	0.5	PASS

Test Graphs


11B Ant1 2412




11B Ant1 2442



11B Ant1 2472




11G_Ant1_2412




Date: 1.JUL.2020 16:22:33

11G_Ant1_2442




Date: 1.JUL.2020 16:24:56

11G_Ant1_2472




Date: 1.JUL.2020 16:26:38

11N20SISO_Ant1_2412




Date: 1.JUL.2020 16:30:38

11N20SISO_Ant1_2442



Date: 1.JUL.2020 16:32:57

11N20SISO_Ant1_2472



Date: 1.JUL.2020 16:34:26


Appendix B: Maximum conducted output power**Test Result**

Test Mode	Antenna	Channel	Result [dBm]	Limit[dBm]	Verdict
11B	Ant1	2412	6.27	<=30	PASS
		2417	10.02	<=30	PASS
		2442	9.02	<=30	PASS
		2472	10.73	<=30	PASS
11G	Ant1	2412	6.02	<=30	PASS
		2417	12.03	<=30	PASS
		2442	12.06	<=30	PASS
		2472	12.91	<=30	PASS
11N20SISO	Ant1	2412	12.07	<=30	PASS
		2442	11.90	<=30	PASS
		2472	12.77	<=30	PASS


Appendix C: Maximum power spectral density**Test Result**

TestMode	Antenna	Channel	Result[dBm/3kHz]	Limit[dBm/3kHz]	Verdict
11B	Ant1	2412	-14.9	<=8	PASS
		2442	-12.95	<=8	PASS
		2472	-8.68	<=8	PASS
11G	Ant1	2412	-18.8	<=8	PASS
		2442	-11.3	<=8	PASS
		2472	-12.18	<=8	PASS
11N20SISO	Ant1	2412	-12.12	<=8	PASS
		2442	-13.37	<=8	PASS
		2472	-12.77	<=8	PASS


Test Graphs




11G_Ant1_2412




11G_Ant1_2442




11G_Ant1_2472




11N20SISO Ant1 2412



11N20SISO Ant1 2442




11N20SISO Ant1 2472




Appendix D: Band edge measurements

Test Graphs




11B_Ant1_High_2472




Date: 1.JUL.2020 16:20:41

11G_Ant1_Low_2412




Date: 1.JUL.2020 16:23:28

11G_Ant1_2417




Date: 14.AUG.2020 17:01:48

11G Ant1_High 2472




Date: 1.JUL.2020 16:29:09

11N20SISO Ant1_Low 2412



Date: 1.JUL.2020 16:31:33

11N20SISO Ant1_High 2472




Date: 1.JUL.2020 16:35:30


Appendix E: Duty Cycle

Test Result

Test Mode	Antenna	Channel	Transmission Duration [ms]	Transmission Period [ms]	Duty Cycle [%]
11B	Ant1	2442	12.38	12.50	99.04
11G	Ant1	2442	2.03	10.08	20.09
11N20SISO	Ant1	2442	1.89	10.11	18.69

Test Graphs





***** END OF REPORT *****