



## RF TEST REPORT

**Applicant** Beijing Chusudu Technology Co., Ltd.  
**FCC ID** 2AQ5PAUTORINGA2  
**Product** Vehicular wireless terminal(with 4G function)  
**Brand** AutoRing  
**Model** A2  
**Report No.** R1807A0315-R4V1  
**Issue Date** October 24, 2018

TA Technology (Shanghai) Co., Ltd. tested the above equipment in accordance with the requirements in **FCC CFR47 Part 2 (2017)/ FCC CFR 47 Part 90S (2017)**. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Performed by: Jiangpeng Lan

Approved by: Kai Xu

### TA Technology (Shanghai) Co., Ltd.

No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China

TEL: +86-021-50791141/2/3

FAX: +86-021-50791141/2/3-8000



## TABLE OF CONTENT

|                                                     |    |
|-----------------------------------------------------|----|
| 1. Test Laboratory .....                            | 4  |
| 1.1. Notes of the Test Report .....                 | 4  |
| 1.2. Test facility .....                            | 4  |
| 1.3. Testing Location .....                         | 5  |
| 2. General Description of Equipment under Test..... | 6  |
| 3. Applied Standards .....                          | 7  |
| 4. Test Configuration .....                         | 8  |
| 5. Test Case Results .....                          | 9  |
| 5.1. RF Power Output .....                          | 9  |
| 5.2. Effective Radiated Power .....                 | 12 |
| 5.3. Occupied Bandwidth .....                       | 15 |
| 5.4. Emission Mask .....                            | 21 |
| 5.5. Peak-to-Average Power Ratio (PAPR).....        | 27 |
| 5.6. Frequency Stability.....                       | 29 |
| 5.7. Spurious Emissions at Antenna Terminals.....   | 32 |
| 5.8. Radiates Spurious Emission .....               | 37 |
| 6. Main Test Instruments.....                       | 44 |
| ANNEX A: EUT Appearance and Test Setup .....        | 45 |
| A.1 EUT Appearance.....                             | 45 |
| A.2 Test Setup.....                                 | 48 |

### Summary of measurement results

| No.                                                                                                                                                             | Test Type                               | Clause in FCC rules | Verdict |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------|---------------------|---------|
| 1                                                                                                                                                               | RF power output                         | 2.1046/90.635(b)    | PASS    |
| 2                                                                                                                                                               | Effective Radiated Power                | 90.635(b)           | PASS    |
| 3                                                                                                                                                               | Occupied Bandwidth                      | 2.1049/ 90.209      | PASS    |
| 4                                                                                                                                                               | Emission Masks                          | 2.1051 / 90.691     | PASS    |
| 5                                                                                                                                                               | Peak-to-Average Power Ratio             | KDB 971168 D01(5.7) | PASS    |
| 6                                                                                                                                                               | Frequency Stability                     | 2.1055 / 90.213     | PASS    |
| 7                                                                                                                                                               | Spurious Emissions at Antenna Terminals | 2.1051 / 90.691     | PASS    |
| 8                                                                                                                                                               | Radiates Spurious Emission              | 2.1053 /90.691      | PASS    |
| Date of Testing: July 8 ,2018 ~ August 1 ,2018                                                                                                                  |                                         |                     |         |
| Note: PASS: The EUT complies with the essential requirements in the standard.<br>FAIL: The EUT does not comply with the essential requirements in the standard. |                                         |                     |         |

## 1. Test Laboratory

### 1.1. Notes of the Test Report

This report shall not be reproduced in full or partial, without the written approval of **TA technology (shanghai) co., Ltd.** The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein .Measurement Uncertainties were not taken into account and are published for informational purposes only. This report is written to support regulatory compliance of the applicable standards stated above.

### 1.2. Test facility

#### **CNAS (accreditation number:L2264)**

TA Technology (Shanghai) Co., Ltd. has obtained the accreditation of China National Accreditation Service for Conformity Assessment (CNAS).

#### **FCC (Designation number: CN1179, Test Firm Registration Number: 446626)**

TA Technology (Shanghai) Co., Ltd. has been listed on the US Federal Communications Commission list of test facilities recognized to perform electromagnetic emissions measurements.

#### **IC (recognition number is 8510A)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Canada to perform electromagnetic emission measurement.

#### **VCCI (recognition number is C-4595, T-2154, R-4113, G-10766)**

TA Technology (Shanghai) Co., Ltd. has been listed by industry Japan to perform electromagnetic emission measurement.

#### **A2LA (Certificate Number: 3857.01)**

TA Technology (Shanghai) Co., Ltd. has been listed by American Association for Laboratory Accreditation to perform electromagnetic emission measurement.



### 1.3. Testing Location

Company: TA Technology (Shanghai) Co., Ltd.  
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong  
City: Shanghai  
Post code: 201201  
Country: P. R. China  
Contact: Xu Kai  
Telephone: +86-021-50791141/2/3  
Fax: +86-021-50791141/2/3-8000  
Website: <http://www.ta-shanghai.com>  
E-mail: [xukai@ta-shanghai.com](mailto:xukai@ta-shanghai.com)

## 2. General Description of Equipment under Test

### Client Information

|                      |                                                                                      |
|----------------------|--------------------------------------------------------------------------------------|
| Applicant            | Beijing Chusudu Technology Co., Ltd.                                                 |
| Applicant address    | Dongsheng Plaza A,5th Floor,8 Zhongguancun East Rd, Haidian District, Beijing, China |
| Manufacturer         | Beijing Chusudu Technology Co., Ltd.                                                 |
| Manufacturer address | Dongsheng Plaza A,5th Floor,8 Zhongguancun East Rd, Haidian District, Beijing, China |

### General Information

| EUT Description                                                   |                                                                                      |           |           |
|-------------------------------------------------------------------|--------------------------------------------------------------------------------------|-----------|-----------|
| Model                                                             | A2                                                                                   |           |           |
| Product IMEI                                                      | 863346039069490                                                                      |           |           |
| Hardware Version                                                  | V3.1                                                                                 |           |           |
| Software Version                                                  | RC108_D2_MT2_C1_BOM_V3.1_S20180622                                                   |           |           |
| Power Supply                                                      | External Power Supply                                                                |           |           |
| Antenna Type                                                      | Internal Antenna                                                                     |           |           |
| Antenna Gain                                                      | 1.0dBi                                                                               |           |           |
| Test Mode(s)                                                      | LTE Band 26;                                                                         |           |           |
| Test Modulation                                                   | QPSK 16QAM;                                                                          |           |           |
| Maximum E.R.P.                                                    | LTE Band 26:                                                                         | 13.19dBm  |           |
| Rated Power Supply Voltage                                        | 3.7V                                                                                 |           |           |
| Extreme Voltage                                                   | Minimum: 3.2V     Maximum: 4.2V                                                      |           |           |
| Extreme Temperature                                               | Lowest:- 20°C     Highest: +70°C                                                     |           |           |
| Operating Frequency Range(s)                                      | Band                                                                                 | Tx (MHz)  | Rx (MHz)  |
|                                                                   | LTE Band 26                                                                          | 814 ~ 824 | 859 ~ 869 |
| EUT Accessory                                                     |                                                                                      |           |           |
| AutoRing A2 Power Cable                                           | Manufacturer: Shenzhen GuanLiJie Technology Co.,Ltd<br>Model: AutoRing A2 Power cord |           |           |
| Camera                                                            | Manufacturer: Beijing Chusudu Technology Co., Ltd.<br>Model: MMT-AHD-H65             |           |           |
| Note: The information of the EUT is declared by the manufacturer. |                                                                                      |           |           |



### 3. Applied Standards

According to the specifications of the manufacturer, it must comply with the requirements of the following standards:

**FCC CFR47 Part 2 (2017)**

**FCC CFR 47 Part 90S (2017)**

**ANSI/TIA-603-E (2016)**

**KDB 971168 D01 Power Meas License Digital Systems v03r01**

## 4. Test Configuration

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes. EUT stand-up position (Z axis), lie-down position (X, Y axis). Receiver antenna polarization (horizontal and vertical), the worst emission was found in position (X axis, vertical polarization) and the worst case was recorded.

All mode and data rates and positions were investigated.

The following testing in LTE is set based on the maximum RF Output Power.

Test modes are chosen as the worst case configuration below for LTE Band 26

| Test items                              | Bandwidth (MHz)                                                                                                                       |   |   |    | Modulation |       | RB |     |      | Test Channel |   |   |
|-----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|---|---|----|------------|-------|----|-----|------|--------------|---|---|
|                                         | 1.4                                                                                                                                   | 3 | 5 | 10 | QPSK       | 16QAM | 1  | 50% | 100% | L            | M | H |
| RF power output                         | O                                                                                                                                     | O | O | O  | O          | O     | O  | O   | O    | O            | O | O |
| Effective Isotropic Radiated power      | O                                                                                                                                     | O | O | O  | O          | O     | O  | O   | O    | O            | O | O |
| Occupied Bandwidth                      | O                                                                                                                                     | O | O | O  | O          | O     | -  | -   | O    | O            | O | O |
| Emission Mask                           | O                                                                                                                                     | O | O | O  | O          | O     | O  | -   | O    | O            | O | O |
| Peak-to-Average Power Ratio             | O                                                                                                                                     | O | O | O  | O          | O     | -  | -   | O    | O            | O | O |
| Frequency Stability                     | O                                                                                                                                     | O | O | O  | O          | O     | O  | O   | O    | O            | O | O |
| Spurious Emissions at Antenna Terminals | O                                                                                                                                     | O | O | O  | O          | O     | O  | -   | -    | O            | O | O |
| Radiates Spurious Emission              | O                                                                                                                                     | - | O | O  | O          | -     | O  | -   | -    | O            | O | O |
| Note                                    | 1. The mark "O" means that this configuration is chosen for testing.<br>2. The mark "-" means that this configuration is not testing. |   |   |    |            |       |    |     |      |              |   |   |

## 5. Test Case Results

### 5.1. RF Power Output


#### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

#### Methods of Measurement

During the process of the testing, The EUT is controlled by the Base Station Simulator to ensure max power transmission and proper modulation.

#### Test Setup



The loss between RF output port of the EUT and the input port of the tester has been taken into consideration.

#### Limits

Part 90.635 (b) the maximum output power of the transmitter for mobile stations is 100 watts.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

## Test Results

| LTE Band 26 |            |         |           | Conducted Power(dBm)   |           |             |
|-------------|------------|---------|-----------|------------------------|-----------|-------------|
| BW          | Modulation | RB size | RB offset | Channel/Frequency(MHz) |           |             |
|             |            |         |           | 26697/814.7            | 26740/819 | 26783/823.3 |
| 1.4MHz      | QPSK       | 1       | 0         | 23.61                  | 23.58     | 23.57       |
|             |            | 1       | 2         | 23.53                  | 23.50     | 23.50       |
|             |            | 1       | 5         | 23.53                  | 23.47     | 23.52       |
|             |            | 3       | 0         | 23.49                  | 23.52     | 23.45       |
|             |            | 3       | 2         | 23.48                  | 23.41     | 23.57       |
|             |            | 3       | 3         | 23.46                  | 23.43     | 23.48       |
|             |            | 6       | 0         | 22.44                  | 22.51     | 22.50       |
|             | 16QAM      | 1       | 0         | 22.84                  | 22.46     | 22.60       |
|             |            | 1       | 2         | 22.80                  | 22.37     | 22.58       |
|             |            | 1       | 5         | 22.77                  | 22.38     | 22.56       |
|             |            | 3       | 0         | 22.53                  | 22.47     | 22.45       |
|             |            | 3       | 2         | 22.58                  | 22.48     | 22.54       |
|             |            | 3       | 3         | 22.51                  | 22.48     | 22.45       |
|             |            | 6       | 0         | 21.51                  | 21.58     | 21.55       |
| BW          | Modulation | RB size | RB offset | Channel/Frequency(MHz) |           |             |
|             |            |         |           | 26705/815.5            | 26740/819 | 26775/822.5 |
| 3MHz        | QPSK       | 1       | 0         | 23.61                  | 23.57     | 23.57       |
|             |            | 1       | 13        | 23.55                  | 23.55     | 23.52       |
|             |            | 1       | 24        | 23.52                  | 23.46     | 23.51       |
|             |            | 12      | 0         | 22.57                  | 22.60     | 22.55       |
|             |            | 12      | 6         | 22.58                  | 22.47     | 22.64       |
|             |            | 12      | 13        | 22.53                  | 22.53     | 22.55       |
|             |            | 25      | 0         | 22.51                  | 22.52     | 22.50       |
|             | 16QAM      | 1       | 0         | 22.81                  | 22.45     | 22.60       |
|             |            | 1       | 13        | 22.81                  | 22.41     | 22.60       |
|             |            | 1       | 24        | 22.76                  | 22.38     | 22.55       |
|             |            | 12      | 0         | 21.62                  | 21.59     | 21.55       |
|             |            | 12      | 6         | 21.65                  | 21.55     | 21.61       |
|             |            | 12      | 13        | 21.59                  | 21.56     | 21.55       |
|             |            | 25      | 0         | 21.52                  | 21.58     | 21.53       |
| BW          | Modulation | RB size | RB offset | Channel/Frequency(MHz) |           |             |
|             |            |         |           | 26715/816.5            | 26740/819 | 26765/822.5 |
| 5MHz        | QPSK       | 1       | 0         | 23.58                  | 23.53     | 23.54       |
|             |            | 1       | 13        | 23.54                  | 23.51     | 23.50       |



|       |            |         |           |                        |           |       |
|-------|------------|---------|-----------|------------------------|-----------|-------|
|       |            | 1       | 24        | 23.50                  | 23.45     | 23.48 |
|       |            | 12      | 0         | 22.54                  | 22.55     | 22.51 |
|       |            | 12      | 6         | 22.56                  | 22.43     | 22.61 |
|       |            | 12      | 13        | 22.50                  | 22.48     | 22.51 |
|       |            | 25      | 0         | 22.48                  | 22.47     | 22.46 |
|       | 16QAM      | 1       | 0         | 22.79                  | 22.41     | 22.55 |
|       |            | 1       | 13        | 22.77                  | 22.39     | 22.56 |
|       |            | 1       | 24        | 22.74                  | 22.35     | 22.53 |
|       |            | 12      | 0         | 21.59                  | 21.55     | 21.52 |
|       |            | 12      | 6         | 21.62                  | 21.53     | 21.58 |
|       |            | 12      | 13        | 21.56                  | 21.51     | 21.51 |
|       |            | 25      | 0         | 21.50                  | 21.54     | 21.50 |
| BW    | Modulation | RB size | RB offset | Channel/Frequency(MHz) |           |       |
|       |            |         |           | /                      | 26740/819 | /     |
| 10MHz | QPSK       | 1       | 0         | /                      | 23.56     | /     |
|       |            | 1       | 25        | /                      | 23.52     | /     |
|       |            | 1       | 49        | /                      | 22.99     | /     |
|       |            | 25      | 0         | /                      | 22.50     | /     |
|       |            | 25      | 13        | /                      | 22.61     | /     |
|       |            | 25      | 25        | /                      | 22.49     | /     |
|       |            | 50      | 0         | /                      | 22.52     | /     |
|       | 16QAM      | 1       | 0         | /                      | 23.00     | /     |
|       |            | 1       | 25        | /                      | 23.01     | /     |
|       |            | 1       | 49        | /                      | 22.76     | /     |
|       |            | 25      | 0         | /                      | 21.58     | /     |
|       |            | 25      | 13        | /                      | 21.54     | /     |
|       |            | 25      | 25        | /                      | 21.56     | /     |
|       |            | 50      | 0         | /                      | 21.54     | /     |

## 5.2. Effective Radiated Power

### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Methods of Measurement

1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
2. EUT was placed on a 0.8 meter high non-conductive stand at a 3 meter test distance from the receive antenna. A receiving antenna was placed on the antenna mast 3 meters from the EUT for emission measurements. The height of receiving antenna between 1.0m and 4.0m. Detected emissions were maximized at each frequency by rotating the EUT through 360° and adjusting the receiving antenna polarization. The radiated emission measurements of all transmit frequencies in three channels (High, Middle, Low) were measured with peak detector.
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl), the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAg) should be recorded after test.
7. The measurement results are obtained as described below:  

$$\text{Power(EIRP)} = \text{PMea} - \text{PAg} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:  


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  

$$\text{ERP} = \text{EIRP} - 2.15\text{dBi}$$

The RB allocation refers to section 5.1, using the maximum output power configuration.

## Test configuration

Below 1GHz:



## Limits

Rule Part 90.635(b) specifies that “The maximum output power of the transmitter for mobile stations is 100 watts”.

|       |                               |
|-------|-------------------------------|
| Limit | $\leq 100 \text{ W}$ (50 dBm) |
|-------|-------------------------------|

## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 1.19 \text{ dB}$

### Test Results:

The measurement is performed for both of horizontal and vertical antenna Polarization, and only the data of worst mode is recorded in this report.

| LTE Band 26     |         |                 |              |           |             |            |
|-----------------|---------|-----------------|--------------|-----------|-------------|------------|
| bandwidth       | Channel | Frequency (MHz) | Polarization | ERP (dBm) | Limit (dBm) | Conclusion |
| 1.4 MHz (QPSK)  | Low     | 814.7           | Horizontal   | 12.93     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 12.71     | 50          | Pass       |
|                 | High    | 823.3           | Horizontal   | 12.82     | 50          | Pass       |
| 3 MHz (QPSK)    | Low     | 814.7           | Horizontal   | 13.02     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 13.19     | 50          | Pass       |
|                 | High    | 823.3           | Horizontal   | 13.08     | 50          | Pass       |
| 5 MHz (QPSK)    | Low     | 815.5           | Horizontal   | 12.67     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 12.77     | 50          | Pass       |
|                 | High    | 822.5           | Horizontal   | 13.00     | 50          | Pass       |
| 10 MHz (QPSK)   | Mid     | 819             | Horizontal   | 13.05     | 50          | Pass       |
| 1.4 MHz (16QAM) | Low     | 814.7           | Horizontal   | 12.42     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 12.21     | 50          | Pass       |
|                 | High    | 823.3           | Horizontal   | 12.34     | 50          | Pass       |
| 3 MHz (16QAM)   | Low     | 814.7           | Horizontal   | 12.53     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 12.60     | 50          | Pass       |
|                 | High    | 823.3           | Horizontal   | 12.84     | 50          | Pass       |
| 5 MHz (16QAM)   | Low     | 815.5           | Horizontal   | 12.39     | 50          | Pass       |
|                 | Mid     | 819             | Horizontal   | 12.48     | 50          | Pass       |
|                 | High    | 822.5           | Horizontal   | 12.73     | 50          | Pass       |
| 10 MHz (16QAM)  | Mid     | 819             | Horizontal   | 12.80     | 50          | Pass       |

### 5.3. Occupied Bandwidth

#### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

#### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The occupied bandwidth is measured using spectrum analyzer.


RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 26 (1.4MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 26 (3MHz/5MHz).

RBW is set to 300 kHz, VBW is set to 1MHz for LTE Band 26 (10MHz).

99% power and -26dBc occupied bandwidths are recorded. Spectrum analyzer plots are included on the following pages.

#### Test Setup



#### Limits

No specific occupied bandwidth requirements in part 2.1049.

Part 90.209 (a) Each authorization issued to a station licensed under this part will show an emission designator representing the class of emission authorized. The designator will be prefixed by a specified necessary bandwidth. This number does not necessarily indicate the bandwidth occupied by the emission at any instant. In those cases where part 2.202 of this chapter does not provide a formula for the computation of necessary bandwidth, the occupied bandwidth, as defined in part 2 of this chapter, may be used in lieu of the necessary bandwidth.

#### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 624\text{Hz}$ .



## Test Result

| LTE Band 26 |            |                 |         |                 |                          |                       |
|-------------|------------|-----------------|---------|-----------------|--------------------------|-----------------------|
| RB          | Modulation | Bandwidth (MHz) | Channel | Frequency (MHz) | 99% Power Bandwidth(MHz) | -26dBc Bandwidth(MHz) |
| 100%        | QPSK       | 1.4             | 26697   | 814.7           | 1.1264                   | 1.316                 |
|             |            |                 | 26740   | 819             | 1.1213                   | 1.311                 |
|             |            |                 | 26783   | 823.3           | 1.1326                   | 1.310                 |
|             |            | 3               | 26705   | 815.5           | 2.7449                   | 3.038                 |
|             |            |                 | 26740   | 819             | 2.7404                   | 3.053                 |
|             |            |                 | 26775   | 822.5           | 2.7386                   | 3.044                 |
|             |            | 5               | 26715   | 816.5           | 4.5254                   | 5.106                 |
|             |            |                 | 26740   | 819             | 4.5404                   | 5.089                 |
|             |            |                 | 26765   | 821.5           | 4.5237                   | 5.084                 |
|             |            | 10              | 26740   | 819             | 9.0633                   | 10.200                |
|             | 16QAM      | 1.4             | 26697   | 814.7           | 1.1188                   | 1.295                 |
|             |            |                 | 26740   | 819             | 1.1295                   | 1.312                 |
|             |            |                 | 26783   | 823.3           | 1.1229                   | 1.318                 |
|             |            | 3               | 26705   | 815.5           | 2.7340                   | 3.043                 |
|             |            |                 | 26740   | 819             | 2.7536                   | 3.058                 |
|             |            |                 | 26775   | 822.5           | 2.7330                   | 3.055                 |
|             |            | 5               | 26715   | 816.5           | 4.5478                   | 5.084                 |
|             |            |                 | 26740   | 819             | 4.5263                   | 5.071                 |
|             |            |                 | 26765   | 821.5           | 4.5547                   | 5.112                 |
|             |            | 10              | 26740   | 819             | 9.0580                   | 10.090                |




## LTE Band 26 QPSK 1.4MHz CH26697



## LTE Band 26 QPSK 3MHz CH26705




## LTE Band 26 QPSK 1.4MHz CH26740



## LTE Band 26 QPSK 3MHz CH26740



## LTE Band 26 QPSK 1.4MHz CH26783



## LTE Band 26 QPSK 3MHz CH26775







## LTE Band 26 QPSK 5MHz CH26715



## LTE Band 26 QPSK 5MHz CH26740



## LTE Band 26 QPSK 5MHz CH26765



## LTE Band 26 QPSK 10MHz CH26740





## LTE Band 26 16QAM 1.4MHz CH26697



## LTE Band 26 16QAM 3MHz CH26705




## LTE Band 26 16QAM 1.4MHz CH26740




## LTE Band 26 16QAM 3MHz CH26740



## LTE Band 26 16QAM 1.4MHz CH26783



## LTE Band 26 16QAM 3MHz CH26775







## LTE Band 26 16QAM 5MHz CH26715



## LTE Band 26 16QAM 5MHz CH26740



## LTE Band 26 16QAM 5MHz CH26765



## LTE Band 26 16QAM 10MHz CH26740



## 5.4. Emission Mask

### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The band edge of the lowest and highest channels were measured. The average detector is used.

RBW is set to 15 kHz, VBW is set to 51 kHz for LTE Band 26 (1.4MHz),


RBW is set to 30 kHz, VBW is set to 100 kHz for LTE Band 26 (3MHz),

RBW is set to 51 kHz, VBW is set to 160 kHz for LTE Band 26 (5MHz),

RBW is set to 100 kHz, VBW is set to 300 kHz for LTE Band 26 (10MHz),

Spectrum analyzer plots are included on the following pages.

### Test Setup



### Limits

Rule Part 90.691(a) specifies that “ For any frequency removed from the EA licensee's frequency block by up to and including 37.5 kHz, the power of any emission shall be attenuated below the transmitter power (P) in watts by at least  $116 \log_{10}(f/6.1)$  decibels or  $50 + 10 \log_{10}(P)$  decibels or 80 decibels, whichever is the lesser attenuation, where f is the frequency removed from the center of the outer channel in the block in kilohertz and where f is greater than 12.5 kHz.”

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U=0.684\text{dB}$ .



## Test Result:


LTE Band 26 QPSK 1.4MHz CH-Low 1RB




LTE Band 26 QPSK 1.4MHz CH-High 1RB



LTE Band 26 QPSK 1.4MHz CH-Low 100%RB



LTE Band 26 QPSK 1.4MHz CH-High 100%RB



LTE Band 26 QPSK 3MHz CH-Low 1RB




LTE Band 26 QPSK 3MHz CH-High 1RB






## LTE Band 26 QPSK 3MHz CH-Low 100%RB



## LTE Band 26 QPSK 3MHz CH-High 100%RB




## LTE Band 26 QPSK 5MHz CH-Low 1RB




## LTE Band 26 QPSK 5MHz CH-High 1RB



## LTE Band 26 QPSK 5MHz CH-Low 100%RB




## LTE Band 26 QPSK 5MHz CH-High 100%RB



## LTE Band 26 QPSK 10MHz CH-Low 1RB



## LTE Band 26 QPSK 10MHz CH-Low 100%RB



## LTE Band 26 16QAM 1.4MHz CH-Low 1RB



## LTE Band 26 16QAM 1.4MHz CH-High 1RB



## LTE Band 26 16QAM 1.4MHz CH-Low 100%RB



## LTE Band 26 16QAM 1.4MHz CH-High 100%RB






## LTE Band 26 16QAM 3MHz CH-Low 1RB




## LTE Band 26 16QAM 3MHz CH-High 1RB



## LTE Band 26 16QAM 3MHz CH-Low 100%RB



## LTE Band 26 16QAM 3MHz CH-High 100%RB



## LTE Band 26 16QAM 5MHz CH-Low 1RB




## LTE Band 26 16QAM 5MHz CH-High 1RB







## LTE Band 26 16QAM 5MHz CH-Low 100%RB




## LTE Band 26 16QAM 5MHz CH-High 100%RB



## LTE Band 26 16QAM 10MHz CH-Low 1RB



## LTE Band 26 16QAM 10MHz CH-High 100%RB



## 5.5. Peak-to-Average Power Ratio (PAPR)

### Ambient condition


| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Methods of Measurement

Measure the total peak power and record as PPk. And measure the total average power and record as PAvg. Both the peak and average power levels must be expressed in the same logarithmic units (e.g., dBm). Determine the PAPR from:

$$\text{PAPR (dB)} = \text{PPk (dBm)} - \text{PAvg (dBm)}.$$

### Test Setup



### Limits

In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB in 24.232(d).

### Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 2$ ,  $U = 0.4$  dB.

**Test Results**

| Mode            | Channel | Frequency (MHz) | Peak(dBm) | Avg(dBm) | PAPR(dB) | Limit(dB) | Conclusion |
|-----------------|---------|-----------------|-----------|----------|----------|-----------|------------|
| 1.4 MHz (QPSK)  | 26697   | 814.7           | 27.43     | 22.44    | 4.99     | 13        | PASS       |
|                 | 26740   | 819             | 27.69     | 22.51    | 5.18     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.48     | 22.50    | 4.98     | 13        | PASS       |
| 3 MHz (QPSK)    | 26697   | 814.7           | 27.64     | 22.51    | 5.13     | 13        | PASS       |
|                 | 26740   | 819             | 27.83     | 22.52    | 5.31     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.82     | 22.50    | 5.32     | 13        | PASS       |
| 5 MHz (QPSK)    | 26697   | 814.7           | 27.71     | 22.48    | 5.23     | 13        | PASS       |
|                 | 26740   | 819             | 27.79     | 22.47    | 5.32     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.80     | 22.46    | 5.34     | 13        | PASS       |
| 10 MHz (QPSK)   | 26740   | 819             | 27.75     | 22.52    | 5.23     | 13        | PASS       |
| 1.4 MHz (16QAM) | 26697   | 814.7           | 27.32     | 21.51    | 5.81     | 13        | PASS       |
|                 | 26740   | 819             | 27.49     | 21.58    | 5.91     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.26     | 21.55    | 5.71     | 13        | PASS       |
| 3 MHz (16QAM)   | 26697   | 814.7           | 27.46     | 21.52    | 5.94     | 13        | PASS       |
|                 | 26740   | 819             | 27.67     | 21.58    | 6.09     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.63     | 21.53    | 6.10     | 13        | PASS       |
| 5 MHz (16QAM)   | 26697   | 814.7           | 27.44     | 21.50    | 5.94     | 13        | PASS       |
|                 | 26740   | 819             | 27.55     | 21.54    | 6.01     | 13        | PASS       |
|                 | 26783   | 823.3           | 27.56     | 21.50    | 6.06     | 13        | PASS       |
| 10 MHz (16QAM)  | 26740   | 819             | 27.51     | 21.54    | 5.97     | 13        | PASS       |

## 5.6. Frequency Stability

### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Method of Measurement

#### 1. Frequency Stability (Temperature Variation)

The temperature inside the climate chamber is varied from -30°C to +70°C in 10°C step size,

(1) With all power removed, the temperature was decreased to 0°C and permitted to stabilize for three hours.

(2) Measure the carrier frequency with the test equipment in a “call mode”. These measurements should be made within 1 minute of powering up the mobile station, to prevent significant self warming.

(3) Repeat the above measurements at 10°C increments from -30°C to +70°C. Allow at least 1.5 hours at each temperature, un-powered, before making measurements.

#### 2. Frequency Stability (Voltage Variation)


The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery-operating end point which shall be specified by the manufacturer.

This transceiver is specified to operate with an input voltage of between 3.2 V and 4.2 V, with a nominal voltage of 3.7V.

### Test setup



**Limits**

According to the Sec. 90.213.(a) Unless noted elsewhere, transmitters used in the services governed by this part must have a minimum frequency stability as specified in the following table.

Minimum Frequency Stability

[Parts per million (ppm)]

| Frequency range<br>(MHz) | Fixed and base<br>stations | Mobile stations              |                                 |
|--------------------------|----------------------------|------------------------------|---------------------------------|
|                          |                            | Over 2 watts output<br>power | 2 watts or less output<br>power |
| 809-824                  | 1.5                        | 2.5                          | 2.5                             |

Note: The EUT should meet Mobile stations limit.

**Measurement Uncertainty**

The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 3$ ,  $U = 0.01\text{ppm}$ .

## Test Result

| LTE Band 26             |         |                   |                    |               |                             |
|-------------------------|---------|-------------------|--------------------|---------------|-----------------------------|
| (QPSK, 10MHz BANDWIDTH) |         |                   |                    |               |                             |
| Condition               |         | 814               | 824                | Delta<br>(Hz) | Frequency<br>Stability(ppm) |
| Temperature             | Voltage | F low@-13dBm(MHz) | F high@-13dBm(MHz) |               |                             |
| Normal (25°C)           | Normal  | 814.4402          | 823.6078           | -3.94         | -0.00481                    |
| Extreme (70°C)          |         | 814.4414          | 823.6066           | -4.48         | -0.00547                    |
| Extreme (60°C)          |         | 814.4395          | 823.6085           | -3.65         | -0.00446                    |
| Extreme (50°C)          |         | 814.4392          | 823.6088           | 2.12          | 0.00259                     |
| Extreme (40°C)          |         | 814.4407          | 823.6076           | 4.88          | 0.00596                     |
| Extreme (30°C)          |         | 814.4398          | 823.6084           | 1.14          | 0.00139                     |
| Extreme (20°C)          |         | 814.4393          | 823.6087           | 3.62          | 0.00442                     |
| Extreme (10C)           |         | 814.4409          | 823.6071           | -3.45         | -0.00421                    |
| Extreme (0°C)           |         | 814.4458          | 823.6087           | -3.23         | -0.00394                    |
| Extreme (-10°C)         |         | 814.4395          | 823.6085           | -10.37        | -0.01266                    |
| Extreme (-20°C)         |         | 814.4401          | 823.6079           | -3.26         | -0.00398                    |
| Extreme (-30°C)         |         | 814.4400          | 823.6096           | -6.61         | -0.00807                    |
| 25°C                    | LV      | 814.4399          | 823.6085           | -8.16         | -0.00996                    |
|                         | HV      | 814.4396          | 823.6090           | -3.62         | -0.00442                    |
| (16QAM,10MHz BANDWIDTH) |         |                   |                    |               |                             |
| Condition               |         | 814               | 824                | Delta<br>(Hz) | Frequency<br>Stability(ppm) |
| Temperature             | Voltage | F low@-13dBm(MHz) | F high@-13dBm(MHz) |               |                             |
| Normal (25°C)           | Normal  | 814.4941          | 823.5271           | -2.31         | -0.00282                    |
| Extreme (70°C)          |         | 814.4929          | 823.5285           | 5.97          | 0.00729                     |
| Extreme (60°C)          |         | 814.4948          | 823.5264           | -0.19         | -0.00023                    |
| Extreme (50°C)          |         | 814.4951          | 823.5261           | -9.25         | -0.01129                    |
| Extreme (40°C)          |         | 814.4938          | 823.5276           | -1.10         | -0.00134                    |
| Extreme (30°C)          |         | 814.4947          | 823.5265           | 6.60          | 0.00806                     |
| Extreme (20°C)          |         | 814.4954          | 823.5262           | -0.73         | -0.00089                    |
| Extreme (10C)           |         | 814.4934          | 823.5278           | 5.45          | 0.00665                     |
| Extreme (0°C)           |         | 814.4943          | 823.5269           | 4.90          | 0.00598                     |
| Extreme (-10°C)         |         | 814.4948          | 823.5264           | 10.73         | 0.01310                     |
| Extreme (-20°C)         |         | 814.4942          | 823.5278           | 14.85         | 0.01813                     |
| Extreme (-30°C)         |         | 814.4942          | 823.5286           | 4.92          | 0.00601                     |
| 25°C                    | LV      | 814.4949          | 823.5265           | 6.69          | 0.00817                     |
|                         | HV      | 814.4945          | 823.5281           | 1.10          | 0.00134                     |

## 5.7. Spurious Emissions at Antenna Terminals


### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Method of Measurement

The EUT was connected to Spectrum Analyzer and Base Station Simulator via power Splitter. The measurement is carried out using a spectrum analyzer. The spectrum analyzer scans from 30MHz to the 10th harmonic of the carrier. The peak detector is used. RBW is set to 100 kHz and VBW is set to 300 kHz, Sweep is set to ATUO.

### Test setup



### Limits

Rule Part 90.691 specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log (P)$  dB.”

| Limit | -13 dBm |
|-------|---------|
|-------|---------|

### Measurement Uncertainty


The assessed measurement uncertainty to ensure 99.75% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ .

| Frequency     | Uncertainty |
|---------------|-------------|
| 100kHz-1GHz   | 0.684 dB    |
| 1GHz-12.75GHz | 1.407 dB    |


## Test Result

If disturbances were found more than 20dB below limit line, the mark is not required for the EUT.  
The signal beyond the limit is carrier.


LTE Band 26 1.4MHz CH Low 30MHz~1GHz




LTE Band 26 1.4MHz CH Low 1GHz~9GHz




LTE Band 26 1.4MHz CH Middle 30MHz~1GHz




LTE Band 26 1.4MHz CH Middle 1GHz~9GHz



LTE Band 26 1.4MHz CH High 30MHz~1GHz




LTE Band 26 1.4MHz CH High 1GHz~9GHz







## LTE Band 26 3MHz CH Low 30MHz~1GHz




## LTE Band 26 3MHz CH Low 1GHz~9GHz




## LTE Band 26 3MHz CH Middle 30MHz~1GHz




## LTE Band 26 3MHz CH Middle 1GHz~9GHz



## LTE Band 26 3MHz CH High 30MHz~1GHz




## LTE Band 26 3MHz CH High 1GHz~9GHz







## LTE Band 26 5MHz CH Low 30MHz~1GHz




## LTE Band 26 5MHz CH Low 1GHz~9GHz




## LTE Band 26 5MHz CH Middle 30MHz~1GHz




## LTE Band 26 5MHz CH Middle 1GHz~9GHz



## LTE Band 26 5MHz CH High 30MHz~1GHz




## LTE Band 26 5MHz CH High 1GHz~9GHz






## LTE Band 26 10MHz CH Middle 30MHz~1GHz



## LTE Band 26 10MHz CH Middle 1GHz~9GHz



## 5.8. Radiates Spurious Emission

### Ambient condition

| Temperature | Relative humidity |
|-------------|-------------------|
| 21°C ~25°C  | 40%~60%           |

### Method of Measurement


1. The testing follows FCC KDB 971168 v03r01 Section 5.8 and ANSI/TIA-603-E (2016).
2. The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).
3. A log-periodic antenna or double-ridged waveguide horn antenna shall be substituted in place of the EUT. The log-periodic antenna will be driven by a signal generator and the level will be adjusted till the same power value on the spectrum analyzer or receiver. The level of the spurious emissions can be calculated through the level of the signal generator, cable loss, the gain of the substitution antenna and the reading of the spectrum analyzer or receiver.
4. The EUT is then put into continuously transmitting mode at its maximum power level during the test. Set Test Receiver or Spectrum RBW=1MHz, VBW=3MHz for above 1GHz and RBW=100kHz, VBW=300kHz for 30MHz to 1GHz,, And the maximum value of the receiver should be recorded as (Pr).
5. The EUT shall be replaced by a substitution antenna. In the chamber, an substitution antenna for the frequency band of interest is placed at the reference point of the chamber. An RF Signal source for the frequency band of interest is connected to the substitution antenna with a cable that has been constructed to not interfere with the radiation pattern of the antenna. A power (PMea) is applied to the input of the substitution antenna, and adjust the level of the signal generator output until the value of the receiver reach the previously recorded (Pr). The power of signal source (PMea) is recorded. The test should be performed by rotating the test item and adjusting the receiving antenna polarization.
6. A amplifier should be connected to the Signal Source output port. And the cable should be connect between the Amplifier and the Substitution Antenna. The cable loss (Pcl) ,the Substitution Antenna Gain (Ga) and the Amplifier Gain (PAG) should be recorded after test.
7. The measurement results are obtained as described below:  

$$\text{Power(EIRP)} = \text{PMea} - \text{PAG} - \text{Pcl} + \text{Ga}$$
The measurement results are amend as described below:  


$$\text{Power(EIRP)} = \text{PMea} - \text{Pcl} + \text{Ga}$$
8. This value is EIRP since the measurement is calibrated using an antenna of known gain (2.15 dBi) and known input power. ERP can be calculated from EIRP by subtracting the gain of the dipole,  $\text{ERP} = \text{EIRP} - 2.15\text{dBi}$ .  
The modulation mode and RB allocation refer to section 5.1, using the maximum output power configuration.

## Test setup

30MHz~~~ 1GHz



Above 1GHz



## Limits

Rule Part 90.691 specifies that “The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitting power (P) by a factor of at least  $43 + 10 \log(P)$  dB.”

|       |         |
|-------|---------|
| Limit | -13 dBm |
|-------|---------|

## Measurement Uncertainty

The assessed measurement uncertainty to ensure 95% confidence level for the normal distribution is with the coverage factor  $k = 1.96$ ,  $U = 3.55$  dB.

**Test Result**

Sweep the whole frequency band through the range from 30MHz to the 10th harmonic of the carrier, the emissions below the noise floor will not be recorded in the report.

## LTE Band 26 1.4MHz CH Low

| Harmonic                                                                                                                                                     | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2                                                                                                                                                            | 1629.4          | -50.21   | 2.00            | 10.75      | vertical             | -43.61          | -13.00      | 30.61       | 45            |
| 3                                                                                                                                                            | 2444.1          | -59.88   | 2.51            | 11.05      | vertical             | -53.49          | -13.00      | 40.49       | 0             |
| 4                                                                                                                                                            | 3258.8          | -62.17   | 4.20            | 11.15      | vertical             | -57.37          | -13.00      | 44.37       | 135           |
| 5                                                                                                                                                            | 4073.5          | -58.57   | 5.20            | 11.15      | vertical             | -54.77          | -13.00      | 41.77       | 270           |
| 6                                                                                                                                                            | 4888.2          | -57.54   | 5.50            | 11.95      | vertical             | -53.24          | -13.00      | 40.24       | 180           |
| 7                                                                                                                                                            | 5702.9          | -57.50   | 5.70            | 13.55      | vertical             | -51.80          | -13.00      | 38.80       | 90            |
| 8                                                                                                                                                            | 6517.6          | -56.04   | 6.30            | 13.75      | vertical             | -50.74          | -13.00      | 37.74       | 45            |
| 9                                                                                                                                                            | 7332.3          | -51.49   | 6.80            | 13.85      | vertical             | -46.59          | -13.00      | 33.59       | 45            |
| 10                                                                                                                                                           | 8147.0          | -45.46   | 6.90            | 14.25      | vertical             | -40.26          | -13.00      | 27.26       | 0             |
| Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.<br>2.The worst emission was found in the antenna is Horizontal position. |                 |          |                 |            |                      |                 |             |             |               |

## LTE Band 26 1.4MHz CH Middle

| Harmonic                                                                                                                                                     | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2                                                                                                                                                            | 1638.0          | -51.78   | 2.00            | 10.75      | vertical             | -45.18          | -13.00      | 32.18       | 315           |
| 3                                                                                                                                                            | 2457.0          | -58.52   | 2.51            | 11.05      | vertical             | -52.13          | -13.00      | 39.13       | 225           |
| 4                                                                                                                                                            | 3346.0          | -62.84   | 4.20            | 11.15      | vertical             | -58.04          | -13.00      | 45.04       | 315           |
| 5                                                                                                                                                            | 4182.5          | -54.74   | 5.20            | 11.15      | vertical             | -50.94          | -13.00      | 37.94       | 135           |
| 6                                                                                                                                                            | 5019.0          | -55.93   | 5.50            | 11.95      | vertical             | -51.63          | -13.00      | 38.63       | 270           |
| 7                                                                                                                                                            | 5855.5          | -57.11   | 5.70            | 13.55      | vertical             | -51.41          | -13.00      | 38.41       | 315           |
| 8                                                                                                                                                            | 6692.0          | -53.52   | 6.30            | 13.75      | vertical             | -48.22          | -13.00      | 35.22       | 135           |
| 9                                                                                                                                                            | 7528.5          | -51.96   | 6.80            | 13.85      | vertical             | -47.06          | -13.00      | 34.06       | 270           |
| 10                                                                                                                                                           | 8365.0          | -47.82   | 6.90            | 14.25      | vertical             | -42.62          | -13.00      | 29.62       | 45            |
| Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.<br>2.The worst emission was found in the antenna is Horizontal position. |                 |          |                 |            |                      |                 |             |             |               |

## LTE Band 26 1.4MHz CH High

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1646.6          | -57.57   | 2.00            | 10.75      | vertical             | -50.97          | -13.00      | 37.97       | 135           |
| 3        | 2469.9          | -55.62   | 2.51            | 11.05      | vertical             | -49.23          | -13.00      | 36.23       | 270           |
| 4        | 3294.0          | -61.83   | 4.20            | 11.15      | vertical             | -57.03          | -13.00      | 44.03       | 0             |
| 5        | 4117.5          | -58.31   | 5.20            | 11.15      | vertical             | -54.51          | -13.00      | 41.51       | 315           |
| 6        | 4941.0          | -51.66   | 5.50            | 11.95      | vertical             | -47.36          | -13.00      | 34.36       | 225           |
| 7        | 5764.5          | -58.27   | 5.70            | 13.55      | vertical             | -52.57          | -13.00      | 39.57       | 135           |
| 8        | 6588.0          | -53.56   | 6.30            | 13.75      | vertical             | -48.26          | -13.00      | 35.26       | 270           |
| 9        | 7411.5          | -48.59   | 6.80            | 13.85      | vertical             | -43.69          | -13.00      | 30.69       | 180           |
| 10       | 8235.0          | -46.72   | 6.90            | 14.25      | vertical             | -41.52          | -13.00      | 28.52       | 45            |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## LTE Band 26 5MHz CH Low

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1633.0          | -50.78   | 2.00            | 10.75      | vertical             | -44.18          | -13.00      | 31.18       | 180           |
| 3        | 2449.5          | -59.62   | 2.51            | 11.05      | vertical             | -53.23          | -13.00      | 40.23       | 90            |
| 4        | 3266.0          | -61.73   | 4.20            | 11.15      | vertical             | -56.93          | -13.00      | 43.93       | 0             |
| 5        | 4082.5          | -59.03   | 5.20            | 11.15      | vertical             | -55.23          | -13.00      | 42.23       | 315           |
| 6        | 4899.0          | -58.06   | 5.50            | 11.95      | vertical             | -53.76          | -13.00      | 40.76       | 225           |
| 7        | 5715.5          | -58.13   | 5.70            | 13.55      | vertical             | -52.43          | -13.00      | 39.43       | 135           |
| 8        | 6532.0          | -56.66   | 6.30            | 13.75      | vertical             | -51.36          | -13.00      | 38.36       | 270           |
| 9        | 7348.5          | -51.32   | 6.80            | 13.85      | vertical             | -46.42          | -13.00      | 33.42       | 180           |
| 10       | 8165.0          | -49.83   | 6.90            | 14.25      | vertical             | -44.63          | -13.00      | 31.63       | 90            |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## LTE Band 26 5MHz CH Middle

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1638.0          | -51.78   | 2.00            | 10.75      | vertical             | -45.18          | -13.00      | 32.18       | 45            |
| 3        | 2457.0          | -60.41   | 2.51            | 11.05      | vertical             | -54.02          | -13.00      | 41.02       | 45            |
| 4        | 3276.0          | -61.84   | 4.20            | 11.15      | vertical             | -57.04          | -13.00      | 44.04       | 45            |
| 5        | 4095.0          | -58.92   | 5.20            | 11.15      | vertical             | -55.12          | -13.00      | 42.12       | 45            |
| 6        | 4914.0          | -57.90   | 5.50            | 11.95      | vertical             | -53.60          | -13.00      | 40.60       | 0             |
| 7        | 5733.0          | -55.72   | 5.70            | 13.55      | vertical             | -50.02          | -13.00      | 37.02       | 315           |
| 8        | 6552.0          | -55.75   | 6.30            | 13.75      | vertical             | -50.45          | -13.00      | 37.45       | 135           |
| 9        | 7371.0          | -51.32   | 6.80            | 13.85      | vertical             | -46.42          | -13.00      | 33.42       | 270           |
| 10       | 8190.0          | -48.24   | 6.90            | 14.25      | vertical             | -43.04          | -13.00      | 30.04       | 45            |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## LTE Band 26 5MHz CH High

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1643.0          | -52.37   | 2.00            | 10.75      | vertical             | -45.77          | -13.00      | 32.77       | 0             |
| 3        | 2464.5          | -58.57   | 2.51            | 11.05      | vertical             | -52.18          | -13.00      | 39.18       | 315           |
| 4        | 3386.0          | -62.34   | 4.20            | 11.15      | vertical             | -57.54          | -13.00      | 44.54       | 0             |
| 5        | 4232.5          | -58.81   | 5.20            | 11.15      | vertical             | -55.01          | -13.00      | 42.01       | 315           |
| 6        | 5079.0          | -54.11   | 5.50            | 11.95      | vertical             | -49.81          | -13.00      | 36.81       | 225           |
| 7        | 5925.0          | -58.46   | 5.70            | 13.55      | vertical             | -52.76          | -13.00      | 39.76       | 135           |
| 8        | 6772.0          | -54.18   | 6.30            | 13.75      | vertical             | -48.88          | -13.00      | 35.88       | 270           |
| 9        | 7618.5          | -49.13   | 6.80            | 13.85      | vertical             | -44.23          | -13.00      | 31.23       | 180           |
| 10       | 8465.0          | -46.22   | 6.90            | 14.25      | vertical             | -41.02          | -13.00      | 28.02       | 90            |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## LTE Band 26 10MHz CH Low

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1638.0          | -51.35   | 2.00            | 10.75      | vertical             | -44.75          | -13.00      | 31.75       | 135           |
| 3        | 2457.0          | -61.15   | 2.51            | 11.05      | vertical             | -54.76          | -13.00      | 41.76       | 270           |
| 4        | 3276.0          | -61.45   | 4.20            | 11.15      | vertical             | -56.65          | -13.00      | 43.65       | 45            |
| 5        | 4095.0          | -58.66   | 5.20            | 11.15      | vertical             | -54.86          | -13.00      | 41.86       | 45            |
| 6        | 4914.0          | -56.94   | 5.50            | 11.95      | vertical             | -52.64          | -13.00      | 39.64       | 0             |
| 7        | 5733.0          | -57.81   | 5.70            | 13.55      | vertical             | -52.11          | -13.00      | 39.11       | 315           |
| 8        | 6552.0          | -55.83   | 6.30            | 13.75      | vertical             | -50.53          | -13.00      | 37.53       | 135           |
| 9        | 7371.0          | -50.99   | 6.80            | 13.85      | vertical             | -46.09          | -13.00      | 33.09       | 270           |
| 10       | 8190.0          | -49.36   | 6.90            | 14.25      | vertical             | -44.16          | -13.00      | 31.16       | 315           |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## LTE Band 26 10MHz CH Middle

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1638.0          | -51.68   | 2.00            | 10.75      | vertical             | -45.08          | -13.00      | 32.08       | 45            |
| 3        | 2457.0          | -59.80   | 2.51            | 11.05      | vertical             | -53.41          | -13.00      | 40.41       | 0             |
| 4        | 3276.0          | -61.45   | 4.20            | 11.15      | vertical             | -56.65          | -13.00      | 43.65       | 270           |
| 5        | 4095.0          | -59.20   | 5.20            | 11.15      | vertical             | -55.40          | -13.00      | 42.40       | 180           |
| 6        | 4914.0          | -56.90   | 5.50            | 11.95      | vertical             | -52.60          | -13.00      | 39.60       | 90            |
| 7        | 5733.0          | -59.10   | 5.70            | 13.55      | vertical             | -53.40          | -13.00      | 40.40       | 45            |
| 8        | 6552.0          | -55.83   | 6.30            | 13.75      | vertical             | -50.53          | -13.00      | 37.53       | 45            |
| 9        | 7371.0          | -50.99   | 6.80            | 13.85      | vertical             | -46.09          | -13.00      | 33.09       | 0             |
| 10       | 8190.0          | -50.50   | 6.90            | 14.25      | vertical             | -45.30          | -13.00      | 32.30       | 315           |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.



## LTE Band 26 10MHz CH High

| Harmonic | Frequency (MHz) | SG (dBm) | Cable Loss (dB) | Gain (dBi) | Antenna Polarization | ERP Level (dBm) | Limit (dBm) | Margin (dB) | Azimuth (deg) |
|----------|-----------------|----------|-----------------|------------|----------------------|-----------------|-------------|-------------|---------------|
| 2        | 1638.0          | -50.76   | 2.00            | 10.75      | vertical             | -44.16          | -13.00      | 31.16       | 315           |
| 3        | 2457.0          | -60.89   | 2.51            | 11.05      | vertical             | -54.50          | -13.00      | 41.50       | 225           |
| 4        | 3276.0          | -61.45   | 4.20            | 11.15      | vertical             | -56.65          | -13.00      | 43.65       | 270           |
| 5        | 4095.0          | -59.20   | 5.20            | 11.15      | vertical             | -55.40          | -13.00      | 42.40       | 45            |
| 6        | 4914.0          | -56.90   | 5.50            | 11.95      | vertical             | -52.60          | -13.00      | 39.60       | 0             |
| 7        | 5733.0          | -61.10   | 5.70            | 13.55      | vertical             | -55.40          | -13.00      | 42.40       | 315           |
| 8        | 6552.0          | -55.10   | 6.30            | 13.75      | vertical             | -49.80          | -13.00      | 36.80       | 225           |
| 9        | 7371.0          | -51.90   | 6.80            | 13.85      | vertical             | -47.00          | -13.00      | 34.00       | 135           |
| 10       | 8190.0          | -49.80   | 6.90            | 14.25      | vertical             | -44.60          | -13.00      | 31.60       | 270           |

Note: 1.The other Spurious RF Radiated emissions level is no more than noise floor.

2.The worst emission was found in the antenna is Horizontal position.

## 6. Main Test Instruments

| Name                   | Manufacturer | Type         | Serial Number | Calibration Date | Expiration Date |
|------------------------|--------------|--------------|---------------|------------------|-----------------|
| Base Station Simulator | R&S          | CMW500       | 113824        | 2018-05-20       | 2019-05-19      |
| Power Splitter         | Hua Xiang    | SHX-GF2-2-13 | 10120101      | /                | /               |
| Spectrum Analyzer      | Agilent      | N9010A       | MY47191109    | 2018-05-20       | 2019-05-19      |
| Signal Analyzer        | R&S          | FSV30        | 100815        | 2017-12-17       | 2018-12-16      |
| EMI Test Receiver      | R&S          | ESCI         | 100948        | 2018-05-20       | 2019-05-19      |
| Signal generator       | R&S          | SMB 100A     | 102594        | 2018-05-13       | 2019-05-12      |
| Loop Antenna           | SCHWARZBECK  | FMZB1519     | 1519-047      | 2014-12-06       | 2019-12-05      |
| Trilog Antenna         | SCHWARZBECK  | VUBL 9163    | 9163-201      | 2017-11-18       | 2020-11-17      |
| Horn Antenna           | R&S          | HF907        | 100126        | 2014-12-06       | 2019-12-05      |
| Horn Antenna           | ETS-Lindgren | 3160-09      | 00102644      | 2015-01-30       | 2020-01-29      |
| Climatic Chamber       | ESPEC        | SU-242       | 93000506      | 2017-12-17       | 2020-12-16      |
| RF Cable               | Agilent      | SMA 15cm     | 0001          | /                | /               |
| Preamplifier           | R&S          | SCU18        | 102327        | 2018-05-20       | 2019-05-19      |
| Software               | R&S          | EMC32        | V9.26.0       | /                | /               |
| MOB COMMS DC SUPPLY    | Keysight     | 66319D       | MY43004105    | 2018-05-07       | 2019-05-06      |

\*\*\*\*\*END OF REPORT \*\*\*\*\*

## ANNEX A: EUT Appearance and Test Setup

### A.1 EUT Appearance




Front Side



Back Side

a: EUT



b: AutoRing A2 Power Cable






c:Camera

Picture 1 EUT and Accessory

## A.2 Test Setup



Below 1GHz



Above 1GHz

**Picture 2: Radiated Spurious Emissions Test setup**