FCC&ISED TEST REPORT

Product Name:	WIFI Module
Trade Mark:	N/A
Model No. / HVIN:	BL-R8822BU1-A
Report Number:	200302010RFC-4
Test Standards:	FCC 47 CFR Part 15 Subpart E RSS-247 Issue 2 RSS-Gen Issue 5
FCC ID:	2AQ5RWBL-8822BU1-A
IC:	24301-BLR8822BU1A
Test Result:	PASS
Date of Issue:	May 12, 2020

Prepared for:

Shenzhen KTC Commercial Display Technology CO.,LTD.
No.4023,Northern Wuhe Road,Bantian Street,Longgang District,Shenzhen City,Guangdong Province,P.R.China

Prepared by:

Shenzhen UnionTrust Quality and Technology Co., Ltd.
16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China
TEL: +86-755-2823 0888
FAX: +86-755-2823 0886

Prepared by: _____ Reviewed by: _____

Henry Lu, Team Leader — Kevin Liang, Assistant Manager

Approved by: _____ Date: May 12, 2020

Billy Li, Technical Director

Version

Version No.	Date	Description
V1.0	May 12, 2020	Original

CONTENTS

1. GENERAL INFORMATION 4
   1.1 CLIENT INFORMATION 4
   1.2 EUT INFORMATION 4
      1.2.1 GENERAL DESCRIPTION OF EUT 4
      1.2.2 DESCRIPTION OF ACCESSORIES 4
   1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD 5
   1.4 OTHER INFORMATION 6
   1.5 DESCRIPTION OF SUPPORT UNITS 7
   1.6 TEST LOCATION 7
   1.7 TEST FACILITY 7
   1.8 DEVIATION FROM STANDARDS 7
   1.9 ABNORMALITIES FROM STANDARD CONDITIONS 8
   1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER 8
   1.11 MEASUREMENT UNCERTAINTY 8
2. TEST SUMMARY 9
3. EQUIPMENT LIST 10
4. TEST CONFIGURATION 11
   4.1 ENVIRONMENTAL CONDITIONS FOR TESTING 11
      4.1.1 NORMAL OR EXTREME TEST CONDITIONS 11
      4.1.2 RECORD OF NORMAL ENVIRONMENT 11
   4.2 TEST CHANNELS 12
   4.3 EUT TEST STATUS 12
   4.4 PRE-SCAN 13
   4.5 TEST SETUP 14
      4.5.1 FOR RADIATED EMISSIONS TEST SETUP 14
      4.5.2 FOR CONDUCTED EMISSIONS TEST SETUP 15
      4.5.3 FOR CONDUCTED RF TEST SETUP 16
   4.6 SYSTEM TEST CONFIGURATION 17
   4.7 DUTY CYCLE 18
5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION 22
   5.1 REFERENCE DOCUMENTS FOR TESTING 22
   5.2 ANTENNA REQUIREMENT 22
   5.3 26 DB BANDWIDTH & OCCUPIED BANDWIDTH 23
   5.4 6 DB BANDWIDTH & OCCUPIED BANDWIDTH 35
   5.5 MAXIMUM CONDUCTED OUTPUT POWER OR E.I.R.P 43
   5.6 PEAK POWER SPECTRAL DENSITY 51
   5.7 RADIATED EMISSIONS AND BAND EDGE MEASUREMENT 68
   5.8 DYNAMIC FREQUENCY SELECTION 108
   5.9 AC POWER LINE CONDUCTED EMISSION 118

APPENDIX 1 PHOTOS OF TEST SETUP 121
APPENDIX 2 PHOTOS OF EUT CONSTRUCTIONAL DETAILS 121

1. GENERAL INFORMATION

1.1 CLIENT INFORMATION

Applicant:	Shenzhen KTC Commercial Display Technology CO.,LTD.
Address of Applicant:	No.4023,Northern Wuhe Road,Bantian Street,Longgang District,Shenzhen City,Guangdong Province,P.R.China
Manufacturer:	Shenzhen KTC Commercial Display Technology CO.,LTD.
Address of Manufacturer:	No.4023,Northern Wuhe Road,Bantian Street,Longgang District,Shenzhen City,Guangdong Province,P.R.China

1.2 EUT INFORMATION

1.2.1 General Description of EUT

Product Name:	WIFI Module		
Model No. / HVIN:	BL-R8822BU1-A		
Trade Mark:	N/A		
DUT Stage:	Production Unit		
EUT Supports Function:	2.4 GHz ISM Band:	IEEE 802.11b/g/n	
		Bluetooth V4.0	
	5 GHz U-NII Bands:	5 150 MHz to 5 250 MHz	IEEE 802.11a/n/ac
		5 250 MHz to 5 350 MHz	IEEE 802.11a/n/ac
		5 470 MHz to 5 725 MHz	IEEE 802.11a/n/ac
		5 725 MHz to 5 850 MHz	IEEE 802.11a/n/ac
Sample Received Date:	March 2, 2020		
Sample Tested Date:	March 2, 2020 to April 14, 2020		

1.2.2 Description of Accessories

Brand	Specification	Antenna Type	Connect Type	Antenna Gain
Zhongtianxun Antenna	Shielded 120mm	PCB	IPEX	2.4G BT : 2.5 dBi 2.4G WIFI : 3.05 dBi 5.2G WIFI : 4.39 dBi 5.3G WIFI : 4.68 dBi 5.6G WIFI : 5.57 dBi 5.8G WIFI : 5.68 dBi
Zhongtianxun Antenna	Shielded 550mm	PCB	IPEX	2.4G BT : 2.5 dBi 2.4G WIFI : 3.05 dBi 5.2G WIFI : 4.39 dBi 5.3G WIFI : 4.68 dBi 5.6G WIFI : 5.57 dBi 5.8G WIFI : 5.68 dBi
Zhongtianxun Antenna	Shielded 750mm	PCB	IPEX	2.4G BT : 2.5 dBi 2.4G WIFI : 3.05 dBi 5.2G WIFI : 4.39 dBi 5.3G WIFI : 4.68 dBi 5.6G WIFI : 5.57 dBi

				5.8G WIFI：5.68 dBi
Zhongtianxun Antenna	Shielded 1000mm	PCB	IPEX	2.4G BT：2.5 dBi 2.4G WIFI：3.05 dBi 5.2G WIFI：4.39 dBi 5.3G WIFI：4.68 dBi 5.6G WIFI：5.57 dBi 5.8G WIFI：5.68 dBi
Remark: The test data is gathered from a production sample (Shielded 120mm), provided by the manufacturer. The wire lengths of all antenna listed in the report is different, but the circuit and the electronic construction do not change, declared by the manufacturer. The device is investigated from radiated spurious emission and radiated band edge test under different wire lengths exploratory test. Subsequently, only the worst case (Shielded 120mm) emissions are reported.				

1.3 PRODUCT SPECIFICATION SUBJECTIVE TO THIS STANDARD

Frequency Bands:	5150 MHz to 5250 MHz (U-NII-1)
	5250 MHz to 5350 MHz (U-NII-2A)
	5470 MHz to 5725 MHz (U-NII-2C)
	5 725 MHz to 5 850 MHz (U-NII-3)
Frequency Ranges:	5180 MHz to 5240 MHz
	5260 MHz to 5320 MHz
	5500 MHz to 5700 MHz
	5 745 MHz to 5 825 MHz
Support Standards:	IEEE 802.11a/n/ac
TPC Function:	Not Support
DFS Operational mode:	Slave without radar Interference detection function
Type of Modulation:	IEEE 802.11a: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11n: OFDM(64QAM, 16QAM, QPSK, BPSK)
	IEEE 802.11ac: OFDM(256QAM, 64QAM, 16QAM, QPSK, BPSK)
Channel Spacing:	IEEE 802.11a/n-HT20/ac-VHT20: 20 MHz
	IEEE 802.11n-HT40/ac-VHT40: 40 MHz
	IEEE 802.11ac-VHT80: 80 MHz
Data Rate:	IEEE 802.11a: Up to 54 Mbps
	IEEE 802.11n-HT20: Up to MCS7
	IEEE 802.11n-HT40: Up to MCS7
	IEEE 802.11ac-VHT20: Up to MCS8
	IEEE 802.11ac-VHT40: Up to MCS9
	IEEE 802.11ac-VHT80: Up to MCS9
Number of Channels:	5150 MHz to 5250 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40)/ac-VHT40 1 for IEEE 802.11acVHT80
	5250 MHz to 5350 MHz: 4 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40)/ac-VHT40 1 for IEEE 802.11acVHT80
	5470 MHz to 5725 MHz: 11 for IEEE 802.11a/n-HT20/ac-VHT20

	5 for IEEE 802.11n-HT40/ac-VHT40 2 for IEEE 802.11ac-VHT80				
	5725 MHz to 5850 MHz: 5 for IEEE 802.11a/n-HT20/ac-VHT20 2 for IEEE 802.11n-HT40/ac-VHT40 1 for IEEE 802.11ac-VHT80				
Antenna Type:	PCB Antenna				
Antenna Gain:	5150 MHz to 5250 MHz: 4.39 dBi				
	5250 MHz to 5350 MHz: 4.68 dBi				
	5470 MHz to 5725 MHz: 5.57 dBi				
	5725 MHz to 5850 MHz: 5.68 dBi				
Maximum EIRP (dBm):		**U-NII-1**			
	IEEE 802.11a:	17.87			
	IEEE 802.11n-HT20:	16.89			
	IEEE 802.11n-HT40:	15.59			
	IEEE 802.11ac-VHT20:	16.84			
	IEEE 802.11ac-VHT40:	15.64			
	IEEE 802.11ac-VHT80:	14.78			
Maximum conducted output power (dBm):		**U-NII-1**	**U-NII-2A**	**U-NII-2C**	**U-NII-3**
	IEEE 802.11a:	13.48	13.62	13.73	11.90
	IEEE 802.11n-HT20:	12.50	12.64	12.43	10.52
	IEEE 802.11n-HT40:	11.20	10.09	12.68	10.75
	IEEE 802.11ac-VHT20	12.45	12.61	12.58	10.61
	IEEE 802.11ac-VHT40	11.25	10.27	12.73	10.85
	IEEE 802.11ac-VHT80:	10.39	9.38	11.97	11.44
Normal Test Voltage:	3.3 Vdc				

1.4 OTHER INFORMATION

Operation Frequency Each of Channel				
	U-NII-1	**U-NII-2A**	**U-NII-2C**	**U-NII-3**
IEEE 802.11a, IEEE 802.11n-HT20, IEEE 802.11ac-VHT20	**f = 5000 + 5k, k = 32 + 4n**			**f = 5000 + 5k, k = 145 + 4n**
	n = 1,…, 4	**n = 5,…, 8**	**n = 17,…, 27**	**n = 1,…, 5**
IEEE 802.11n-HT40, IEEE 802.11ac-VHT40	**f = 5000 + 5k, k = 30 + 8n**			**f = 5000 + 5k, k = 143 + 8n**
	n = 1, 2	**n = 1,…, 5**	**n = 9,…, 13**	**n = 1, 2**
IEEE 802.11ac-VHT80	**f = 5000 + 5k, k = 26 + 16n**			**f = 5000 + 5k, k = 155**
	n = 1	**n = 1, 2**	**n = 5, 6**	
Note: **f** is the operating frequency (MHz); **k** is the operating channel.				

1.5 DESCRIPTION OF SUPPORT UNITS

The EUT has been tested with associated equipment below.

1) Support Equipment

Description	Manufacturer	Model No.	Serial Number	Supplied by	FCC ID
Notebook	Lenovo	E450	SL10G10780	UnionTrust	N/A
Phone	MI	MIX 2S	N/A	UnionTrust	N/A
Wireless Home Router	SAGEMCOM	FAST5280	N/A	UnionTrust	VW3FAST5280

2) Support Cable

Cable No.	Description	Connector	Length	Supplied by
1	Antenna Cable	SMA	0.30 Meter	UnionTrust

1.6 TEST LOCATION

Shenzhen UnionTrust Quality and Technology Co., Ltd.

Address: 16/F, Block A, Building 6, Baoneng Science and Technology Park, Qingxiang Road No.1, Longhua New District, Shenzhen, China 518109
Telephone: +86 (0) 755 2823 0888
Fax: +86 (0) 755 2823 0886

1.7 TEST FACILITY

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L9069
The measuring equipment utilized to perform the tests documented in this report has been calibrated once a year or in accordance with the manufacturer's recommendations, and is traceable under the ISO/IEC/EN 17025 to international or national standards. Equipment has been calibrated by accredited calibration laboratories.

A2LA-Lab Certificate No.: 4312.01
Shenzhen UnionTrust Quality and Technology Co., Ltd. has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

ISED Wireless Device Testing Laboratories
CAB identifier: CN0032

FCC Accredited Lab.
Designation Number: CN1194
Test Firm Registration Number: 259480

1.8 DEVIATION FROM STANDARDS

None.

1.9 ABNORMALITIES FROM STANDARD CONDITIONS

None.

1.10 OTHER INFORMATION REQUESTED BY THE CUSTOMER

None.

1.11 MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

No.	Item	Measurement Uncertainty
1	Conducted emission 9KHz-150KHz	±3.8 dB
2	Conducted emission 150KHz-30MHz	±3.4 dB
3	Radiated emission 9KHz-30MHz	±4.9 dB
4	Radiated emission 30MHz-1GHz	±4.7 dB
5	Radiated emission 1GHz-18GHz	±5.1 dB
6	Radiated emission 18GHz-26GHz	±5.2 dB
7	Radiated emission 26GHz-40GHz	±5.2 dB

2. TEST SUMMARY

Test Cases			
Test Item	**Test Requirement**	**Test Method**	**Result**
Antenna Requirement	FCC 47 CFR Part 15 Subpart C Section 15.203 FCC 47 CFR Part 15 Subpart E Section 15.407(a)(1) (2) RSS-Gen Issue 5, Section 6.8	N/A	PASS
26 dB emission bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5) RSS-247 Issue 2 Section 6.2.1.2	KDB 789033 D02 v02r01 Section C.1	PASS
6 dB bandwidth	FCC 47 CFR Part 15 Subpart E Section 15.407 (e) RSS-247 Issue 2 Section 6.2.4.1	KDB 789033 D02 v02r01 Section C.2	PASS
Occupied Bandwidth	RSS-Gen Issue 5, Section 6.7	RSS-Gen Issue 5, section 6.7	PASS
Maximum conducted output power	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	PASS
Peak Power Spectral Density	FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(1)(2)(3) RSS-247 Issue 2 Section 6.2.1.1/6.2.2.1/6.2.3.1/6.2.4.1	KDB 789033 D02 v02r01 Section F	PASS
Radiated Emissions and Band Edge Measurement	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(1)(2)(3)(4)(6) FCC 47 CFR Part 15 Subpart C Section 15.209/205 RSS-247 Issue 2 Section 6.2.1.2/6.2.2.2/6.2.3.2/6.2.4.2	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	PASS
Dynamic Frequency Selection	FCC 47 CFR Part 15 Subpart E Section 15.407 (h) RSS-247 Issue 2 Section 6.3	KDB 905462 D03 Client Without DFS New Rules v01r02	PASS
AC Power Line Conducted Emission	FCC 47 CFR Part 15 Subpart E Section 15.407 (b)(6) FCC 47 CFR Part 15 Subpart C Section 15.207 RSS-Gen Issue 5, Section 8.8	ANSI C63.10-2013, Section 6.2.	PASS

For Dynamic Frequency Selection

Test Case	Result
Channel Availability Check Time	N/A[1]
U-NII Detection Bandwidth	N/A[1]
Channel Closing Transmission Time	PASS
Channel Move Time	PASS
DFS Detection Threshold	N/A[1]
Non- Occupancy Period	N/A[1]

Note:
1) The EUT is slave, NA In this whole report not applicable.

3. EQUIPMENT LIST

Radiated Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	3M Chamber & Accessory Equipment	ETS-LINDGREN	3M	N/A	Dec. 03, 2018	Dec. 03, 2021
☒	Receiver	R&S	ESIB26	100114	Nov. 24, 2019	Nov. 23, 2020
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2019	Nov. 23, 2020
☒	Loop Antenna	ETS-LINDGREN	6502	00202525	Nov. 16, 2019	Nov. 15, 2020
☒	Broadband Antenna	ETS-LINDGREN	3142E	00201566	Nov. 16, 2019	Nov. 15, 2020
☒	6dB Attenuator	Talent	RA6A5-N-18	18103001	Nov. 16, 2019	Nov. 15, 2020
☒	Preamplifier	HP	8447F	2805A02960	Nov. 24, 2019	Nov. 23, 2020
☐	Broadband Antenna (Pre-amplifier)	ETS-LINDGREN	3142E-PA	00201891	Nov. 24, 2019	Nov. 23, 2020
☐	6dB Attenuator	Talent	RA6A5-N-18	18103002	Nov. 24, 2019	Nov. 23, 2020
☐	Horn Antenna	ETS-LINDGREN	3117	00164202	Nov. 16, 2019	Nov. 15, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3117-PA	00201874	May 18, 2019	May 18, 2020
☐	Horn Antenna	ETS-LINDGREN	3116C	00200180	Jun. 23, 2019	Jun. 23, 2020
☒	Horn Antenna (Pre-amplifier)	ETS-LINDGREN	3116C-PA	00202652	Nov. 16, 2019	Nov. 15, 2020
☒	Multi device Controller	ETS-LINDGREN	7006-001	00160105	N/A	N/A
☐	Band Rejection Filter (2400MHz~2500MHz)	Micro-Tronics	BRM50702	G248	Nov. 24, 2019	Nov. 23, 2020
☒	Band Rejection Filter (5150MHz~5880MHz)	Micro-Tronics	BRM50716	G1868	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted Emission Test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	Receiver	R&S	ESR7	1316.3003K07 -101181-K3	Nov. 24, 2019	Nov. 23, 2020
☒	Pulse Limiter	R&S	ESH3-Z2	0357.8810.54	Nov. 24, 2019	Nov. 23, 2020
☒	LISN	R&S	ESH2-Z5	860014/024	Nov. 24, 2019	Nov. 23, 2020
☐	LISN	ETS-Lindgren	3816/2SH	00201088	Nov. 24, 2019	Nov. 23, 2020
☒	Test Software	Audix	e3	Software Version: 9.160323		

Conducted RF test Equipment List						
Used	Equipment	Manufacturer	Model No.	Serial Number	Cal. date (mm dd, yyyy)	Cal. Due date (mm dd, yyyy)
☒	EXA Spectrum Analyzer	KEYSIGHT	N9010A	MY51440197	Nov. 24, 2019	Nov. 23, 2020
☒	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430035	Nov. 24, 2019	Nov. 23, 2020
☐	USB Wideband Power Sensor	KEYSIGHT	U2021XA	MY55430023	Nov. 24, 2019	Nov. 23, 2020
☒	MXG X-Series RF Vector Signal Generator	KEYSIGHT	N5182B	MY51350267	Nov. 24, 2019	Nov. 23, 2020

4. TEST CONFIGURATION

4.1 ENVIRONMENTAL CONDITIONS FOR TESTING

4.1.1 Normal or Extreme Test Conditions

Environment Parameter	Selected Values During Tests		
Test Condition	Ambient		
	Temperature (°C)	Voltage	Relative Humidity (%)
NT/NV	+15 to +35	3.3	20 to 75
Remark: 1) NV: Normal Voltage; NT: Normal Temperature			

4.1.2 Record of Normal Environment

Test Item	Temperature (°C)	Relative Humidity (%)	Pressure (kPa)	Tested by
26 dB emission bandwidth	24.3	51	99.80	Swift Liu
6 dB bandwidth				
Occupied Bandwidth				
Maximum conducted output power				
Peak Power Spectral Density				
Dynamic Frequency Selection				
Radiated Emissions and Band Edge Measurement	26.8	55	100.40	Asia Yan
AC Power Line Conducted Emission	23.6	49	100.42	Bert Xiong

4.2 TEST CHANNELS

Mode	Tx/Rx Frequency	Test RF Channel Lists		
		Lowest(L)	Middle(M)	Highest(H)
IEEE 802.11a IEEE 802.11n-HT20 IEEE 802.11ac-VHT20	5150 MHz to 5250 MHz	Channel 36	Channel 44	Channel 48
		5180 MHz	5220 MHz	5240 MHz
	5250 MHz to 5350 MHz	Channel 52	Channel 60	Channel 64
		5260 MHz	5300 MHz	5320 MHz
	5470 MHz to 5725 MHz	Channel 100	Channel 116	Channel 140
		5500 MHz	5580 MHz	5700 MHz
	5725 MHz to 5850 MHz	Channel 149	Channel 157	Channel 165
		5745 MHz	5785 MHz	5825 MHz
IEEE 802.11n-HT40 IEEE 802.11ac-VHT40	5150 MHz to 5250 MHz	Channel 38	--	Channel 46
		5190 MHz	--	5230 MHz
	5250 MHz to 5350 MHz	Channel 54	--	Channel 62
		5270 MHz	--	5310 MHz
	5470 MHz to 5725 MHz	Channel 102	Channel 110	Channel 134
		5510 MHz	5550 MHz	5670 MHz
	5725 MHz to 5850 MHz	Channel 151	--	Channel 159
		5755 MHz	--	5795 MHz
IEEE 802.11ac-VHT80	5150 MHz to 5250 MHz	--	Channel 42	--
		--	5210 MHz	--
	5250 MHz to 5350 MHz	--	Channel 58	--
		--	5290 MHz	--
	5470 MHz to 5725 MHz	Channel 106	--	--
		5530 MHz	--	--
	5725 MHz to 5850 MHz	--	Channel 155	--
		--	5775 MHz	--

4.3 EUT TEST STATUS

Mode	Tx/Rx Function	Description
IEEE 802.11a/n/ac	1Tx/1Rx	1. Keep the EUT in transmitting mode with all kind of modulation and all kind of data rate.

Power Setting				
	U-NII-1	U-NII-2A	U-NII-2C	U-NII-3
IEEE 802.11a	45	45	40	40
IEEE 802.11n-HT20	43	43	38	38
IEEE 802.11n-HT40	40	40	38	38
IEEE 802.11ac-VHT20	43	43	38	38
IEEE 802.11ac-VHT40	40	40	38	38
IEEE 802.11ac-VHT80	40	40	38	40

Test Software
Test software name: REALTEK 11ac 8822 BU USB WLAN NIC Mass production kit

4.4 PRE-SCAN

Pre-Scan has been conducted to determine the worst-case mode from all possible combinations between available modulations and data rate. Following data rate was (were) selected for the final test as listed below

Mode	Worst-case data rates
IEEE 802.11a	6 Mbps
IEEE 802.11n-HT20	MCS0
IEEE 802.11n-HT40	MCS0
IEEE 802.11ac-VHT20	MCS0
IEEE 802.11ac-VHT40	MCS0
IEEE 802.11ac-VHT80	MCS0

4.5 TEST SETUP

4.5.1 For Radiated Emissions test setup

Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1GHz



4.5.2 For Conducted Emissions test setup



4.5.3 For Conducted RF test setup



Normal Environment

4.6 SYSTEM TEST CONFIGURATION

For emissions testing, the equipment under test (EUT) setup to transmit continuously to simplify the measurement methodology. Care was taken to ensure proper power supply voltages during testing. During testing, radiated emission were performed with the EUT set to transmit at the channel with highest output power as worst-case scenario. Only the worst case data were recorded in this test report.

The signal is maximized through rotation and placement in the three orthogonal axes. The antenna height and polarization are varied during the search for maximum signal level. The antenna height is varied from 1 to 4 meters. Radiated emissions are taken at three meters unless the signal level is too low for measurement at that distance. If necessary, a pre-amplifier is used and/or the test is conducted at a closer distance.

All readings are extrapolated back to the equivalent three meter reading using inverse scaling with distance. Analyzer resolution is 100 kHz or greater for frequencies below 1000 MHz. The resolution is 1 MHz or greater for frequencies above 1000 MHz. The spurious emissions more than 20 dB below the permissible value are not reported.

Radiated emission measurement were performed from the lowest radio frequency signal generated in the device which is greater than 9 kHz to the tenth harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower.

4.7 DUTY CYCLE

Test Procedure: ANSI C63.10-2013 Clause 12.2.

Test Results

Mode	Data rates (Mbps)	On Time (msec)	Period (msec)	Duty Cycle (linear)	Duty Cycle (%)	Duty Cycle Factor (dB)	1/ T Minimum VBW (kHz)	Average Factor (dB)
IEEE 802.11a	6	1.350	1.410	0.96	95.74	0.19	0.74	-0.38
IEEE 802.11n-HT20	MCS0	1.265	1.330	0.95	95.11	0.22	0.79	-0.44
IEEE 802.11n-HT40	MCS0	0.620	0.685	0.91	90.51	0.43	1.61	-0.87
IEEE 802.11ac-VHT20	MCS0	1.265	1.330	0.95	95.11	0.22	0.79	-0.44
IEEE 802.11ac-VHT40	MCS0	0.615	0.690	0.89	89.13	0.50	1.63	-1.00
IEEE 802.11ac-VHT80	MCS0	0.310	0.375	0.83	82.67	0.83	3.23	-1.65

Remark:

1) Duty cycle= On Time/ Period;
2) Duty Cycle factor = 10 * log(1/ Duty cycle);
3) Average factor = 20 $\log_{10}$ Duty Cycle.

The test plots as follows

IEEE 802.11a



IEEE 802.11n-HT20



IEEE 802.11n-HT40



IEEE 802.11ac-VHT20



IEEE 802.11ac-VHT40



IEEE 802.11ac-VHT80



5. RADIO TECHNICAL REQUIREMENTS SPECIFICATION

5.1 REFERENCE DOCUMENTS FOR TESTING

No.	Identity	Document Title
1	FCC 47 CFR Part 2	Frequency allocations and radio treaty matters; general rules and regulations
2	FCC 47 CFR Part 15	Radio Frequency Devices
3	RSS-247 Issue 2	Digital Transmission Systems (DTSs), Frequency Hopping Systems (FHSs) and Licence-Exempt Local Area Network (LE-LAN) Devices
4	RSS-Gen Issue 5	General Requirements for Compliance of Radio Apparatus
5	ANSI C63.10-2013	American National Standard for Testing Unlicesed Wireless Devices
6	KDB 789033 D02 General UNII Test Procedures New Rules v02r01	Guidelines for compliance testing of unlicensed national information infrastructure (U-NII) device part 15, subpart E
7	KDB 905462 D06 802.11 Channel Plans New Rules v02	Operation in U-NII bands -802.11 channel PLAN(§15.407)
8	KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02	Compliance measurement procedures for Unlicensed –National Information Infrastructure devices operates in the frequency bands 5250 MHz to 5350 MHz and 5470 MHz to 5725 MHz bands incorporating dynamic frequency selection
9	KDB 905462 D03 Client Without DFS New Rules v01r02	U-NII client devices without radar detection capability
10	KDB 662911 D01 Multiple Transmitter Output v02r01	Emissions Testing of Transmitters with Multiple Outputs in the Same Band

5.2 ANTENNA REQUIREMENT

Standard Requirement
15.203 requirement: An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. **15.407(a)(1) (2) requirement:** The conducted output power limit specified in paragraph (a) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (a) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power and the peak power spectral density shall be reduced by the by the amount in dB that the directional gain of the antenna exceeds 6 dBi. **RSS-Gen Issue 5, Section 6.8 requirement:** According to RSS-Gen Issue 5, Section 6.8, a transmitter can only be sold or operated with antennas with which it was certified. A transmitter may be certified with multiple antenna types. An antenna type comprises antennas having similar in-band and out-of-band radiation patterns.
EUT Antenna:
Antenna in the interior of the equipment and no consideration of replacement. The max gain of the antenna is 5.68 dBi.

5.3 26 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (a)(2)(5)
RSS-247 Issue 2 Section 6.2.1.2

Test Method: KDB 789033 D02 v02r01 Section C.1

Limit: None; for reporting purposes only.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum analyzer.

Spectrum analyzer according to the following Settings:
a) Set RBW = approximately 1 % of the emission bandwidth.
b) Set the VBW > RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Measure the maximum width of the emission that is 26 dB down from the peak of the emission. Compare this with the RBW setting of the analyzer. Readjust RBW and repeat measurement as needed until the RBW/EBW ratio is approximately 1 %.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Results: Pass

Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
IEEE 802.11a	36 (5180)	20.15	16.637
	44 (5220)	20.98	16.686
	48 (5240)	20.29	16.617
	52 (5260)	21.73	16.629
	60 (5300)	21.19	16.660
	64 (5320)	21.51	16.662
	100 (5500)	20.71	16.703
	116 (5580)	20.44	16.653
	140 (5700)	20.50	16.687
IEEE 802.11n-HT20	36 (5180)	20.97	17.710
	44 (5220)	21.02	17.730
	48 (5240)	21.25	17.712
	52 (5260)	21.12	17.745
	60 (5300)	20.83	17.710
	64 (5320)	21.69	17.717
	100 (5500)	21.32	17.635
	116 (5580)	20.82	17.777
	140 (5700)	21.02	17.731
IEEE 802.11n-HT40	38 (5190)	43.75	36.430
	46 (5230)	43.29	36.361
	54 (5270)	43.61	36.258
	62 (5310)	42.60	36.405
	102 (5510)	43.37	36.311
	110 (5550)	42.84	36.354
	134 (5670)	43.90	36.405

Mode	Channel	26 dB Bandwidth (MHz)	99% Bandwidth (MHz)
IEEE 802.11ac-VHT20	36 (5180)	20.94	17.720
	44 (5220)	20.99	17.685
	48 (5240)	21.26	17.707
	52 (5260)	21.98	17.702
	60 (5300)	21.05	17.721
	64 (5320)	21.10	17.723
	100 (5500)	20.70	17.706
	116 (5580)	21.13	17.691
	140 (5700)	21.18	17.757
IEEE 802.11ac-VHT40	38 (5190)	43.29	36.382
	46 (5230)	42.43	36.312
	54 (5270)	42.18	36.383
	62 (5310)	43.18	36.358
	102 (5510)	44.13	36.411
	110 (5550)	40.96	36.291
	134 (5670)	42.59	36.316
IEEE 802.11ac-VHT80	42 (5210)	83.00	75.649
	58 (5290)	82.69	75.732
	106 (5530)	82.27	75.552

The test plots as follows:

IEEE 802.11a

Channel 36



Channel 44



Channel 48



Channel 52



Channel 60



Channel 64



Channel 100



Channel 116



Channel 140



IEEE 802.11n-HT20

Channel 36



Channel 44



Channel 48



Channel 52



Channel 60



Channel 64



Channel 100



Channel 116



Channel 140



IEEE 802.11n-HT40

Channel 38



Channel 46



Channel 54



Channel 62



Channel 102



Channel 110



Channel 134

IEEE 802.11ac-VHT20

Channel 36



Channel 44



Channel 48



Channel 52



Channel 60



Channel 64



Channel 100



Channel 116



Channel 140



IEEE 802.11ac-VHT40

Channel 38



Channel 46



Channel 54



Channel 62



Channel 102



Channel 110



Channel 134



IEEE 802.11ac-VHT80

Channel 42



Channel 58



Channel 106



5.46 DB BANDWIDTH & OCCUPIED BANDWIDTH

Test Requirement: FCC 47 CFR Part 15 Subpart E Section 15.407 (e)
RSS-247 Issue 2 Section 6.2.4.1

Test Method: KDB 789033 D02 v02r01 Section C.2

Limit: Within the 5.725-5.85 GHz band, the minimum 6 dB bandwidth of U-NII devices shall be at least 500 kHz.

Test Procedure:

The output from the transmitter was connected to an attenuator and then to the input of the RF Spectrum Analyzer.

Spectrum analyzer according to the following Settings:

6dB Bandwidth

a) Set RBW = 100 kHz.
b) Set the video bandwidth (VBW) ≥ 3 * RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.
g) Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6 dB relative to the maximum level measured in the fundamental emission.

Occupied Bandwidth

a) Set RBW = 1% to 5% of the occupied bandwidth
b) Set the video bandwidth (VBW) ≥ 3 x RBW.
c) Detector = Peak.
d) Trace mode = max hold.
e) Sweep = auto couple.
f) Allow the trace to stabilize.

Note: The cable loss and attenuator loss were offset into measure device as an amplitude offset.

Test Setup: Refer to section 4.5.3 for details.

Instruments Used: Refer to section 3 for details

Test Mode: Transmitter mode

Test Results: Pass

Test Data: