



FCC RADIO TEST REPORT

FCC ID : 2AQ68W696S4
Equipment : 5G WWAN Module
Brand Name : Foxconn
Model Name : T99W696
Applicant : Hon Lin Technology Co., Ltd.
11F, No.32, Jihu Rd., Neihu Dist., Taipei City 114
Manufacturer : Lenovo Ireland International Limited
Viscount House, 6/7 Fitzwilliam Square East, Dublin,
D02 Y447, Ireland
Standard : FCC 47 CFR Part 2, 96

Equipment: Foxconn T99W696 tested inside of Lenovo Notebook Computer

The product was received on Jan. 05, 2026 and testing was performed from Feb. 12, 2026 to Apr. 04, 2026. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this partial report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Louis Wu

Approved by: Louis Wu

Sporton International Inc. Wensan Laboratory



Table of Contents

History of this test report.....	3
Summary of Test Result.....	4
1 General Description	5
1.1 Product Feature of Equipment Under Test.....	5
1.2 Product Specification of Equipment Under Test.....	6
1.3 Modification of EUT	6
1.4 Testing Site	6
1.5 Applied Standards	6
2 Test Configuration of Equipment Under Test	7
2.1 Test Mode	7
2.2 Connection Diagram of Test System.....	8
2.3 Support Unit used in test configuration and system	8
2.4 Frequency List of Low/Middle/High Channels	8
3 Conducted Test Items.....	10
3.1 Measuring Instruments	10
3.2 Conducted Output Power Measurement	11
3.3 EIRP and Power Density	12
4 Radiated Test Items	13
4.1 Measuring Instruments	13
4.2 Test Setup	13
4.3 Test Result of Radiated Test	14
4.4 Radiated Spurious Emission	15
5 List of Measuring Equipment.....	16
6 Measurement Uncertainty	17
Appendix A. Test Results of Conducted Test	
Appendix B. Test Results of Radiated Test	
Appendix C. Test Setup Photographs	



History of this test report

Report No.	Version	Description	Issue Date
FG5D1726D	01	Initial issue of report	Apr. 13, 2026



Summary of Test Result

Report Clause	Ref Std. Clause	Test Items	Result (PASS/FAIL)	Remark
3.2	§2.1046	Conducted Output Power	Pass	-
-	ANSI C63.26	Peak-to-Average Ratio	Pass	See Note
3.3	§96.41	Effective Isotropic Radiated Power	Pass	-
		Power Density	Pass	-
-	§2.1049	Occupied Bandwidth	Pass	See Note
-	§2.1051 §96.41	Conducted Band Edge Measurement	Pass	See Note
-	§2.1051 §96.41	Conducted Spurious Emission	Pass	See Note
-	§2.1055	Frequency Stability for Temperature & Voltage	Pass	See Note
4.4	§2.1053 §96.41	Radiated Spurious Emission	Pass	-

Remark:

1. For host device, Radiated Spurious Emission, Effective Radiated Power and Equivalent Isotropic Radiated Power are verified and comply with the limit in this test report.
2. For host device, the Conducted Output Power is no difference after compared to module (Model: Foxconn T99W696)

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacture who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Sheng Kuo**Report Producer: Aya Yang**



1 General Description

1.1 Product Feature of Equipment Under Test

Product Feature	
Equipment	5G WWAN Module
Brand Name	Foxconn
Model Name	T99W696
FCC ID	2AQ68W696S4
Sample 1	EUT with Host 1
Sample 2	EUT with Host 2
EUT Stage	Production Unit

Remark:

1. The above EUT's information was declared by manufacturer.
2. Equipment: Foxconn T99W696 tested inside of Lenovo Notebook Computer.

The product was installed into Notebook Computer (Brand Name: Lenovo, Model Name: TP00175A) during test, and the host information was recorded in the following table.

Host Information	
Host 1	Host with Amphenol Taiwan Corporation Antenna
Host 2	Host with Speed Antenna

Support band and evaluated information	
Supported band	B48, B48C
Evaluated and Tested band	B48, B48C

TDD band Power Class		
	PC3	PC2
B48 / B48C	V	-

WWAN Antenna Information				
Main Antenna	Manufacturer	Amphenol Taiwan Corporation	Peak gain (dBi)	LTE Band 48 : 0.9
	Part number	DC33002BZ00	Type	PIFA
	Manufacturer	Speed	Peak gain (dBi)	LTE Band 48 : 0.93
	Part number	DC33002C200	Type	PIFA
MIMO2 Antenna	Manufacturer	Amphenol Taiwan Corporation	Peak gain (dBi)	LTE Band 48 : 0.97
	Part number	DC33002C000	Type	PIFA
	Manufacturer	Speed	Peak gain (dBi)	LTE Band 48 : 0.97
	Part number	DC33002C300	Type	PIFA

Remark: The above EUT's information was declared by manufacturer. Please refer to Disclaimer in report summary.



1.2 Product Specification of Equipment Under Test

Product Specification is subject to this standard	
Tx Frequency	LTE Band 48: 3550 MHz ~ 3700 MHz
Rx Frequency	LTE Band 48: 3550 MHz ~ 3700 MHz
Bandwidth	LTE Band 48: 5MHz / 10MHz / 15MHz / 20MHz
Type of Modulation	QPSK / 16QAM / 64QAM / 256QAM

1.3 Modification of EUT

No modifications made to the EUT during the testing.

1.4 Testing Site

Test Site	Sporton International Inc. Wensan Laboratory	
Test Site Location	No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855	
Test Site No.	Sporton Site No.	
	TH05-HY	03CH20-HY
Test Engineer	Yuki Chen	John Chuan, David Dai and Sam Chou
Temperature (°C)	22.3~22.9	18.9~22.6
Relative Humidity (%)	53.2~55.5	63.9~70.5

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC Designation No.: TW3786

1.5 Applied Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ ANSI C63.26-2015
- ♦ FCC 47 CFR Part 2, 96
- ♦ FCC KDB 971168 Power Meas. License Digital Systems v03r01
- ♦ FCC KDB 940660 D01 Part 96 CBRS Eqpt v03
- ♦ FCC KDB 412172 D01 Determining ERP and EIRP
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to v03r01 Power Meas. License Digital Systems v03r01 with maximum output power


Modulation Type	Modulation
A	QPSK
B	16QAM
C	64QAM
D	256QAM

Test Item	Modulation Type	Bandwidth	RB Size	Channel
Conducted Power	A, B, C, D	All	1, Half, Full	L, M, H
EIRP/ ERP	A, B, C, D	All	1, Half, Full	L, M, H
RSE	A	20 MHz	1RB	Remark 5

Remark:

1. Evaluated all the transmitter signal and reporting worst-case configuration among all modulation types.
2. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst-case emissions are reported.
3. During the RSE preliminary test, the standalone mode and charging modes were verified. It is determined that the charging modes is the worst case for the official test.
4. For LTE B48 support SISO Mode Antenna Main and ENDC Antenna MIMO2, Radiated Spurious Emission is full test. Conducted test items are verified and the worst case is Antenna Main, Therefore, the report only performed Antenna Main test results.
5. Based on the module report RSE test results, verify the worst channel.

2.2 Connection Diagram of Test System



2.3 Support Unit used in test configuration and system

Item	Equipment	Brand Name	Model No.	FCC ID	Data Cable	Power Cord
1.	Earphone	Apple	N/A	N/A	Shielded, 1.2m	N/A
2.	Base Station	Anritsu	MT8821C	N/A	N/A	Unshielded, 1.8 m
3.	Base Station	Anritsu	MT8000A	N/A	N/A	Unshielded, 1.8 m

2.4 Frequency List of Low/Middle/High Channels

LTE Band 48 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	55340	55990	56640
	Frequency	3560	3625	3690
15	Channel	55315	55990	56665
	Frequency	3557.5	3625	3692.5
10	Channel	55290	55990	56690
	Frequency	3555	3625	3695
5	Channel	55265	55990	56715
	Frequency	3552.5	3625	3697.5



LTE Band 48C Channel and Frequency List_CA					
BW [MHz]	Channel/Frequency(MHz)		Lowest	Middle	Highest
20 + 20	PCC	Channel	55340	55891	56442
		Frequency	3560	3615.1	3670.2
	SCC	Channel	55538	56089	56640
		Frequency	3579.8	3634.9	3690.0
20 + 15	PCC	Channel	55340	55916	56491
		Frequency	3560	3617.6	3675.1
	SCC	Channel	55511	56087	56662
		Frequency	3577.1	3634.7	3692.2
15 + 20	PCC	Channel	55318	55893	56469
		Frequency	3557.8	3615.3	3672.9
	SCC	Channel	55489	56064	56640
		Frequency	3574.9	3632.4	3690.0
20 + 10	PCC	Channel	55340	55941	56541
		Frequency	3560	3620.1	3680.1
	SCC	Channel	55484	56085	56685
		Frequency	3574.4	3634.5	3694.5
10 + 20	PCC	Channel	55295	55896	56496
		Frequency	3555.5	3615.6	3675.6
	SCC	Channel	55439	56040	56640
		Frequency	3569.9	3630	3690
20 + 5	PCC	Channel	55340	55965	56590
		Frequency	3560	3622.5	3685
	SCC	Channel	55457	56082	56707
		Frequency	3571.7	3634.2	3696.7
5 + 20	PCC	Channel	55273	55896	56523
		Frequency	3553.3	3615.6	3678.3
	SCC	Channel	55390	56015	56640
		Frequency	3565	3627.5	3690.0


3 Conducted Test Items

3.1 Measuring Instruments

See list of measuring instruments of this test report.

3.1.1 Test Setup

3.1.2 Conducted Output Power



3.1.3 Test Result of Conducted Test

Please refer to Appendix A.



3.2 Conducted Output Power Measurement

3.2.1 Description of the Conducted Output Power Measurement

A base station simulator was used to establish communication with the EUT. Its parameters were set to transmit the maximum power on the EUT. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.2.2 Test Procedures

1. The transmitter output port was connected to base station.
2. Set EUT at maximum power through base station.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.



3.3 EIRP and Power Density

3.3.1 Description of the EIRP and Power Density Measurement

The EIRP of mobile transmitters must not exceed 23 dBm /10 megahertz for LTE Band 48.

The testing follows ANSI C63.26-2015 Section 5.2.5.5.

According to KDB 412172 D01 Power Approach,

$EIRP = P_T + G_T - LC$, where

P_T = transmitter output power in dBm

G_T = gain of the transmitting antenna in dBi

LC = signal attenuation in the connecting cable between the transmitter and antenna in dB

Device	Maximum EIRP (dBm/10 MHz)	Maximum PSD (dBm/MHz)
End User Device	23	n/a

Remark: Total channel power is complied with EIRP limit 23dBm/10MHz.

3.3.2 Test Procedures

The testing follows procedure in Section 5.2 of ANSI C63.26-2015 and KDB 940660 D01 Part 96 CBRS Eqpt v03 Section 3.2(b)(2)

Determine the EIRP by adding the effective antenna gain to the measured average conducted power level.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup


For radiated test below 30MHz




For radiated test from 30MHz to 1GHz



For radiated emissions from 1GHz to 18GHz



For radiated emissions above 18GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.

Note:

The low frequency, which started from 9 kHz to 30MHz, was pre-scanned and the result which was 20dB lower than the limit line was not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result came out very similar.



4.4 Radiated Spurious Emission

4.4.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI C63.26-2015.

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least -40dBm / MHz

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.4.2 Test Procedures

The testing follows FCC KDB 971168 D01 v03r01 Section 7 and ANSI C63.26-2015 section 5.5.7 Radiated measurement using the field strength method.

1. The EUT was placed on a turntable with 0.8 meter for frequency below 1GHz and 1.5 meter for frequency above 1GHz respectively above ground.
2. The EUT was set 3 meters from the receiving antenna mounted on the antenna tower.
3. The table was rotated 360 degrees to determine the position of the highest spurious emission.
4. The height of the receiving antenna is varied between 1m to 4m to search the maximum spurious emission for both horizontal and vertical polarizations.
5. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. To convert spectrum reading E(dBuV/m) to EIRP(dBm)
$$\text{EIRP(dBm)} = \text{Level (dBuV/m)} + 20\log(d) - 104.77,$$
where d is the distance at which field strength limit is specified in the rules
8. Field Strength Level (dBm) = Spectrum Reading (dBm) + Antenna Factor + Cable Loss + Read Level - Preamp Factor.
9. ERP (dBm) = EIRP (dBm) - 2.15
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.



5 List of Measuring Equipment

Instrument	Brand Name	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Radio Communication Analyzer	Anritsu	MT8821C	6262025341	LTE FDD/TDD LTE-2CC ULCA/DLCA	Sep. 16, 2025	Mar. 14, 2026~ Mar. 18, 2026	Sep. 15, 2026	Conducted (TH05-HY)
DC Power Supply	GW Instek	GPE-2323	GET861546	0V~64V ; 0A~6A	Jun. 03, 2025	Mar. 14, 2026~ Mar. 18, 2026	Jun. 02, 2026	Conducted (TH05-HY)
Coupler	MVE	MVE4816	#Z	0.009MHz-18G Hz	Oct. 16, 2025	Mar. 14, 2026~ Mar. 18, 2026	Oct. 15, 2026	Conducted (TH05-HY)
Spectrum Analyzer	Rohde & Schwarz	FSV40	101907	10Hz~40GHz	Aug. 25, 2025	Mar. 14, 2026~ Mar. 18, 2026	Aug. 24, 2026	Conducted (TH05-HY)
Thermal Chamber	ESPEC	SU-241	92003713	-30°C ~95°C	May. 12, 2025	Mar. 14, 2026~ Mar. 18, 2026	May. 11, 2026	Conducted (TH05-HY)
Power divider	Anritsu	K241C	2143398	9KHz~40GHz	Jun. 13, 2025	Mar. 14, 2026~ Mar. 18, 2026	Jun. 12, 2026	Conducted (TH05-HY)
Software	Sporton	LTE Conducted Test Tools	N/A	Conducted Test Item	N/A	Mar. 14, 2026~ Mar. 18, 2026	N/A	Conducted (TH05-HY)
Hygrometer	TECEP	DTM-303A	TP201996	-10 ~ 50°C / 20 ~ 95%RH	Nov. 04, 2025	Mar. 14, 2026~ Mar. 18, 2026	Nov. 11, 2026	Conducted (TH05-HY)
EMI Test Receiver	Keysight	N9038B	MY62210111	N/A	Aug. 29, 2025	Feb. 12, 2026~ Apr. 04, 2026	Aug. 28, 2026	Radiation (03CH20-HY)
Loop Antenna	Rohde & Schwarz	HFH2-Z2E	101108	9 kHz~30 MHz	Dec. 11, 2025	Feb. 12, 2026~ Apr. 04, 2026	Dec. 10, 2026	Radiation (03CH20-HY)
Preamplifier	EMEC	EM18G40G	060871	18GHz~40GHz	Aug. 25, 2025	Feb. 12, 2026~ Apr. 04, 2026	Aug. 24, 2026	Radiation (03CH20-HY)
Controller	ChainTek	3000-1	N/A	Control Turn table & Ant Mast	N/A	Feb. 12, 2026~ Apr. 04, 2026	N/A	Radiation (03CH20-HY)
Antenna Mast	ChainTek	MBS-520-1	N/A	1m~4m	N/A	Feb. 12, 2026~ Apr. 04, 2026	N/A	Radiation (03CH20-HY)
Turn Table	ChainTek	T-200-S-1	N/A	0~360 Degree	N/A	Feb. 12, 2026~ Apr. 04, 2026	N/A	Radiation (03CH20-HY)
Signal Analyzer	Keysight	N9010B	MY60240520	N/A	Dec. 10, 2025	Feb. 12, 2026~ Apr. 04, 2026	Dec. 09, 2026	Radiation (03CH20-HY)
Bilog Antenna	TESEQ	CBL 6111D&00800 N1D01N-06	55606 & 08	30MHz~1GHz	Nov. 26, 2025	Feb. 12, 2026~ Apr. 04, 2026	Nov. 25, 2026	Radiation (03CH20-HY)
Horn Antenna	SCHWARZBECK	BBHA 9120 D	02360	1GHz-18GHz	Nov. 05, 2025	Feb. 12, 2026~ Apr. 04, 2026	Nov. 04, 2026	Radiation (03CH20-HY)
SHF-EHF Horn Antenna	SCHWARZBECK	BBHA 9170	1223	18GHz-40GHz	Jul. 02, 2025	Feb. 12, 2026~ Apr. 04, 2026	Jul. 01, 2026	Radiation (03CH20-HY)
Preamplifier	COM-POWER	PAM-103	18020201	1MHz-1000MHz	Dec. 30, 2025	Feb. 12, 2026~ Apr. 04, 2026	Dec. 29, 2026	Radiation (03CH20-HY)
Amplifier	EMCI	EMC118A45SE	980792	N/A	Nov. 11, 2025	Feb. 12, 2026~ Apr. 04, 2026	Nov. 10, 2026	Radiation (03CH20-HY)
RF Cable	HUBER + SUHNER	SUCOFLEX 102	519229/2,804015/2,804027/2	N/A	Jan. 15, 2026	Feb. 12, 2026~ Apr. 04, 2026	Jan. 14, 2027	Radiation (03CH20-HY)
Hygrometer	TECEP	DTM-303A	TP211568	N/A	Oct. 21, 2025	Feb. 12, 2026~ Apr. 04, 2026	Oct. 20, 2026	Radiation (03CH20-HY)
Software	Audix	N/A	RK-002156	N/A	N/A	Feb. 12, 2026~ Apr. 04, 2026	N/A	Radiation (03CH20-HY)



6 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	6.50 dB
---	---------

Uncertainty of Radiated Emission Measurement (1 GHz ~ 6 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	4.70 dB
---	---------

Uncertainty of Radiated Emission Measurement (6 GHz ~ 18 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.70 dB
---	---------

Uncertainty of Radiated Emission Measurement (18 GHz ~ 40 GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2Uc(y)$)	5.20 dB
---	---------

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power and EIRP)

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 0.93 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
20	1	0	QPSK	20.05	20.48	20.74	21.70	0.1479
20	1	49		20.17	20.66	20.72		
20	1	99		20.07	20.60	20.77		
20	50	0		19.12	19.64	19.92		
20	50	24		19.15	19.65	19.80		
20	50	50		19.14	19.78	19.81		
20	100	0		19.14	19.61	19.86		
20	1	0	16-QAM	19.13	19.59	19.80	20.74	0.1186
20	1	49		19.17	19.62	19.74		
20	1	99		19.13	19.65	19.81		
20	50	0		18.09	18.52	18.77		
20	50	24		18.12	18.71	18.74		
20	50	50		18.11	18.69	18.87		
20	100	0		18.13	18.66	18.80		
20	1	0	64-QAM	18.12	18.64	18.66	19.77	0.0948
20	1	49		18.20	18.63	18.69		
20	1	99		18.19	18.49	18.84		
20	50	0		17.08	17.50	17.71		
20	50	24		17.16	17.68	17.67		
20	50	50		17.08	17.61	17.82		
20	100	0		17.10	17.69	17.78		
20	1	0	256-QAM	15.21	15.51	15.65	16.81	0.0480
20	1	49		15.09	15.70	15.78		
20	1	99		15.12	15.56	15.77		
20	50	0		15.11	15.54	15.79		
20	50	24		15.18	15.58	15.88		
20	50	50		15.25	15.55	15.85		
20	100	0		15.20	15.59	15.85		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 0.93 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
15	1	0	QPSK	20.02	20.45	20.79	21.72	0.1486
15	1	37		20.05	20.55	20.60		
15	1	74		20.03	20.55	20.57		
15	36	0		19.06	19.58	19.78		
15	36	20		19.08	19.62	19.73		
15	36	39		19.19	19.66	19.75		
15	75	0		19.02	19.63	19.65		
15	1	0	16-QAM	19.05	19.50	19.79	20.72	0.1180
15	1	37		19.13	19.61	19.65		
15	1	74		19.12	19.67	19.68		
15	36	0		18.04	18.44	18.63		
15	36	20		18.07	18.52	18.63		
15	36	39		18.08	18.57	18.74		
15	75	0		18.02	18.62	18.78		
15	1	0	64-QAM	18.06	18.52	18.59	19.72	0.0938
15	1	37		18.09	18.56	18.65		
15	1	74		18.11	18.46	18.79		
15	36	0		17.06	17.49	17.63		
15	36	20		17.12	17.61	17.65		
15	36	39		17.02	17.62	17.65		
15	75	0		17.11	17.49	17.73		
15	1	0	256-QAM	15.13	15.46	15.60	16.73	0.0471
15	1	37		15.09	15.66	15.80		
15	1	74		15.02	15.52	15.59		
15	36	0		15.12	15.55	15.64		
15	36	20		15.12	15.54	15.78		
15	36	39		15.28	15.43	15.76		
15	75	0		15.06	15.43	15.74		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 0.93 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
10	1	0	QPSK	20.05	20.35	20.65	21.62	0.1452
10	1	25		20.07	20.54	20.60		
10	1	49		20.08	20.38	20.69		
10	25	0		19.06	19.51	19.92		
10	25	12		19.07	19.60	19.71		
10	25	25		19.04	19.72	19.75		
10	50	0		19.04	19.58	19.63		
10	1	0	16-QAM	19.12	19.47	19.66	20.63	0.1156
10	1	25		19.11	19.61	19.70		
10	1	49		19.11	19.54	19.70		
10	25	0		18.06	18.48	18.66		
10	25	12		18.16	18.58	18.60		
10	25	25		18.08	18.54	18.68		
10	50	0		18.05	18.68	18.77		
10	1	0	64-QAM	18.04	18.43	18.54	19.67	0.0927
10	1	25		18.08	18.44	18.57		
10	1	49		18.06	18.47	18.74		
10	25	0		17.06	17.48	17.66		
10	25	12		17.08	17.55	17.64		
10	25	25		17.03	17.51	17.73		
10	50	0		17.07	17.54	17.64		
10	1	0	256-QAM	15.09	15.41	15.62	16.71	0.0469
10	1	25		15.12	15.56	15.76		
10	1	49		15.07	15.44	15.65		
10	25	0		15.10	15.53	15.68		
10	25	12		15.09	15.54	15.73		
10	25	25		15.14	15.51	15.78		
10	50	0		15.09	15.50	15.76		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48 Maximum Average Power [dBm] (GT - LC = 0.93 dB)								
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
5	1	0	QPSK	20.09	20.39	20.76	21.69	0.1476
5	1	12		20.10	20.61	20.65		
5	1	24		20.03	20.54	20.67		
5	12	0		19.03	19.43	19.89		
5	12	7		19.04	19.62	19.67		
5	12	13		19.18	19.71	19.81		
5	25	0		19.06	19.52	19.73		
5	1	0	16-QAM	19.07	19.54	19.70	20.63	0.1156
5	1	12		19.05	19.48	19.59		
5	1	24		19.02	19.57	19.64		
5	12	0		18.04	18.44	18.61		
5	12	7		18.17	18.58	18.55		
5	12	13		18.06	18.65	18.83		
5	25	0		18.13	18.60	18.73		
5	1	0	64-QAM	18.09	18.54	18.56	19.75	0.0944
5	1	12		18.05	18.44	18.66		
5	1	24		18.10	18.46	18.82		
5	12	0		17.12	17.46	17.71		
5	12	7		17.07	17.52	17.66		
5	12	13		17.02	17.55	17.78		
5	25	0		17.10	17.55	17.69		
5	1	0	256-QAM	15.04	15.43	15.70	16.72	0.0470
5	1	12		15.13	15.62	15.73		
5	1	24		15.12	15.44	15.63		
5	12	0		15.13	15.44	15.62		
5	12	7		15.08	15.51	15.79		
5	12	13		15.19	15.55	15.71		
5	25	0		15.13	15.40	15.66		
Limit	EIRP < 23dBm/10MHz			Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Appendix A. Test Results of Conducted Test

Conducted Output Power (Average power and EIRP)

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 0.93 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+20	1	99	1	0	QPSK	20.12	20.33	20.51	21.44	0.1393
20+20	1	99	1	0	16-QAM	19.79	19.96	20.18	21.11	0.1291
20+15	1	99	1	0	QPSK	20.21	20.36	20.58	21.51	0.1416
20+15	1	99	1	0	16-QAM	19.74	19.98	20.24	21.17	0.1309
15+20	1	74	1	0	QPSK	20.11	20.35	20.53	21.46	0.1400
15+20	1	74	1	0	16-QAM	19.72	19.99	20.26	21.19	0.1315
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 0.93 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
20+10	1	99	1	0	QPSK	20.16	20.41	20.71	21.64	0.1459
20+10	1	99	1	0	16-QAM	19.75	20.05	20.39	21.32	0.1355
10+20	1	49	1	0	QPSK	20.07	20.34	20.55	21.48	0.1406
10+20	1	49	1	0	16-QAM	19.71	20.01	20.30	21.23	0.1327
20+5	1	99	1	0	QPSK	20.22	20.45	20.80	21.73	0.1489
20+5	1	99	1	0	16-QAM	19.79	20.10	20.52	21.45	0.1396
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.

Part 96 LTE Band 48C_CA Maximum Average Power [dBm] (GT - LC = 0.93 dB)										
BW [MHz]	PCC		SCC		Mod	Lowest	Middle	Highest	EIRP (dBm)	EIRP (W)
	RB Size	RB Offset	RB Size	RB Offset						
5+20	1	24	1	0	QPSK	20.07	20.37	20.59	21.52	0.1419
5+20	1	24	1	0	16-QAM	19.66	19.96	20.27	21.20	0.1318
Limit	EIRP < 23dBm/10MHz					Result			Pass	

Total EIRP power is less than partial EIRP limit 23 dBm/10MHz.



Appendix B. Radiated Spurious Emission Test Data

Test Engineer :	John Chuang, David Dai and Sam Chou	Relative Humidity(%):	64.3~70.5
		Temperature(°C):	18.8~22.4

B1. Summary of each worse mode

Mode	Band	Part	Ch	Freq (MHz)	Level (dBm)	Det	Ant Factor (dB)	AmplCbl (dB)	Filter (dB)	EIRPCF (dB)	Reading (dBuV)	Limit (dBm)	Margin (dB)	Pol	Ant
1	LTE B48	Part 96	M	14464	-50.09	RMS	39.96	-22.32	0.51	-95.23	26.99	-40.00	-10.09	V	Main
3	LTE CA B48C	Part 96	M	14496	-50.40	RMS	40.08	-22.32	0.51	-95.23	26.56	-40.00	-10.40	H	Main




Ant. Main

Part 96 Mode 1


LTE B48 20M Ch55990 1RB0 QPSK

M



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1223_250702 Horizontal
: LTE B48 20M Ch55990 1RB0 QPSK

	Freq	Level	Detector	Ant	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
	MHz	dBm		Factor	1			g	dBm		
1	7232.00	-52.68	RMS	36.93	-22.57	1.00	-95.23	27.19	-40.00	-12.68	Horizontal
2	10848.00	-53.06	RMS	39.00	-22.79	0.44	-95.23	25.52	-40.00	-13.06	Horizontal
3	14464.00	-50.60	RMS	39.96	-22.32	0.51	-95.23	26.48	-40.00	-10.60	Horizontal



Site : 03CH20-HY
Condition: -40 1m BBHA9170_1223_250702 Vertical
: LTE B48 20M Ch55990 1RB0 QPSK

	Freq	Level	Detector	Ant Factor	Amp\Cb 1	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	7232.00	-54.06	RMS	36.93	-22.57	1.00	-95.23	25.81	-40.00	-14.06	Vertical
2	10848.00	-52.81	RMS	39.00	-22.79	0.44	-95.23	25.77	-40.00	-12.81	Vertical
3	14464.00	-50.09	RMS	39.96	-22.32	0.51	-95.23	26.99	-40.00	-10.09	Vertical




Ant. Main

Part 96 Mode 3

LTE CA B48C Ch55891 + Ch56089

M




Site : 03CH20-HY

Condition: -40 1m BBHA9170_1223_250702 Horizontal

: LTE Band 48 20M Ch55891 1RB99 QPSK

: LTE Band 48 20M Ch56089 1RB0 QPSK

	Freq	Level	Detector	Ant	Amp\Cb	Filter	EIRPCF	Readin	Limit	Margin	Pol
				Factor	1				g		
	MHz	dBm		dB/m	dB	dB		dBuV	dBm		
1	7248.00	-54.49	RMS	36.99	-22.53	0.98	-95.23	25.30	-40.00	-14.49	Horizontal
2	10872.00	-52.70	RMS	39.04	-22.79	0.44	-95.23	25.84	-40.00	-12.70	Horizontal
3	14496.00	-50.40	RMS	40.08	-22.32	0.51	-95.23	26.56	-40.00	-10.40	Horizontal



Site : 03CH20-HY

Condition: -40 1m BBHA9170_1223_250702 Vertical

: LTE Band 48 20M Ch55891 1RB99 QPSK

: LTE Band 48 20M Ch56089 1RB0 QPSK

	Freq	Level	Detector	Ant Factor	Amp\Cb l	Filter	EIRPCF	Readin g	Limit	Margin	Pol
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB	
1	7248.00	-54.31	RMS	36.99	-22.53	0.98	-95.23	25.48	-40.00	-14.31	Vertical
2	10872.00	-52.68	RMS	39.04	-22.79	0.44	-95.23	25.86	-40.00	-12.68	Vertical
3	14496.00	-50.54	RMS	40.08	-22.32	0.51	-95.23	26.42	-40.00	-10.54	Vertical




Ant. Main

Part 96 Mode 1

LTE B48 20M Ch55990 1RB0 QPSK

M




Site : 03CH20-HY

Condition: -40 3m HF_9120D_02360_251105 Horizontal

: LTE Band 48 20M Ch55990 1RB0 QPSK

: #1 is fundamental signal which can be ignored.

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin	Pol
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3616.25	-53.86	RMS	29.63	-25.50	0.00	-95.23	37.24	-40.00	-13.86 Horizontal



Site : 03CH20-HY

Condition: -40 3m HF_9120D_02360_251105 Vertical

: LTE Band 48 20M Ch55990 1RB0 QPSK

: #1 is fundamental signal which can be ignored.

	Freq	Level	Detector	Ant Amp\Cb Filter		EIRPCF	Readin	Limit	Margin	Pol
				Factor	1					
	MHz	dBm		dB/m	dB	dB	dB	dBuV	dBm	dB
1	3616.25	-60.05	RMS	29.63	-25.50	0.00	-95.23	31.05	-40.00	-20.05 Vertical