

FCC TEST REPORT

For

TOTEM ACOUSTIQUE INC.

Wireless Subwoofer Transmitter

Model No.: TOTEM LINK

Prepared for : TOTEM ACOUSTIQUE INC.  
Address : 9165, Champ d'Eau, St. Leonard, Quebec, H1P3M3, Canada

Prepared by : Shenzhen LCS Compliance Testing Laboratory Ltd.  
Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,  
Baoan District, Shenzhen, China

Tel : (+86)755-82591330  
Fax : (+86)755-82591332  
Web : www.LCS-cert.com  
Mail : webmaster@LCS-cert.com

Date of receipt of test sample : April 08, 2020  
Number of tested samples : 2  
Sample No. : 200403055A-1, 200403055A-2  
Serial number : Prototype  
Date of Test : April 08, 2020 ~ May 16, 2020  
Date of Report : May 20, 2020

**FCC TEST REPORT**  
**FCC CFR 47 PART 15 C(15.249)****Report Reference No.** : LCS200403055AEA

Date of Issue : May 20, 2020

**Testing Laboratory Name** : Shenzhen LCS Compliance Testing Laboratory Ltd.Address : 101, 201 Bldg A & 301 Bldg C, Juji Industrial Park Shajing Street,  
Baoan District, Shenzhen, ChinaTesting Location/ Procedure : Full application of Harmonised standards ☒  
Partial application of Harmonised standards ☐  
Other standard testing method ☐**Applicant's Name** : TOTEM ACOUSTIQUE INC.

Address : 9165, Champ d'Eau, St. Leonard, Quebec, H1P3M3, Canada

**Test Specification**

Standard : FCC CFR 47 PART 15 C(15.249)

**Test Report Form No.** : LCSEMC-1.0

TRF Originator : Shenzhen LCS Compliance Testing Laboratory Ltd.

Master TRF : Dated 2011-03

**Shenzhen LCS Compliance Testing Laboratory Ltd. All rights reserved.**

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen LCS Compliance Testing Laboratory Ltd. is acknowledged as copyright owner and source of the material. Shenzhen LCS Compliance Testing Laboratory Ltd. takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

**EUT Description** : Wireless Subwoofer Transmitter


Trade Mark : TOTEM

Model/ Type reference : TOTEM LINK


Ratings : For Adapter Input: AC 100-240V, 50/60Hz, 0.3A

For Adapter Output: DC 5V, 1A


Result : Positive

**Compiled by:**

Jayden Zhuo / Administrators

**Supervised by:**

Jin Wang / Technique principal

**Approved by:**

Gavin Liang/ Manager

## FCC -- TEST REPORT

|                                   |                               |
|-----------------------------------|-------------------------------|
| Test Report No. : LCS200403055AEA | May 20, 2020<br>Date of issue |
|-----------------------------------|-------------------------------|

|                          |                                                                                      |
|--------------------------|--------------------------------------------------------------------------------------|
| Type / Model.....        | : TOTEM LINK                                                                         |
| EUT.....                 | : Wireless Subwoofer Transmitter                                                     |
| <b>Applicant.....</b>    | <b>: TOTEM ACOUSTIQUE INC.</b>                                                       |
| Address.....             | : 9165, Champ d'Eau, St. Leonard, Quebec, H1P3M3, Canada                             |
| Telephone.....           | : /                                                                                  |
| Fax.....                 | : /                                                                                  |
| <b>Manufacturer.....</b> | <b>: TOTEM ACOUSTIQUE INC.</b>                                                       |
| Address.....             | : 9165, Champ d'Eau, St. Leonard, Quebec, H1P3M3, Canada                             |
| Telephone.....           | : /                                                                                  |
| Fax.....                 | : /                                                                                  |
| <b>Factory.....</b>      | <b>: Sonicstar (Guangzhou) Electronics Co., Ltd</b>                                  |
| Address.....             | : No.13 Taoyuan West Street, Shima, Junhe, Baiyun District, Guangzhou, 510440, China |
| Telephone.....           | : /                                                                                  |
| Fax.....                 | : /                                                                                  |

|                    |                 |
|--------------------|-----------------|
| <b>Test Result</b> | <b>Positive</b> |
|--------------------|-----------------|

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

### Revision History

| Revision | Issue Date   | Revisions     | Revised By  |
|----------|--------------|---------------|-------------|
| 000      | May 20, 2020 | Initial Issue | Gavin Liang |
|          |              |               |             |
|          |              |               |             |

## TABLE OF CONTENTS

|                                                                   |           |
|-------------------------------------------------------------------|-----------|
| <b>1. GENERAL INFORMATION .....</b>                               | <b>6</b>  |
| 1.1. DESCRIPTION OF DEVICE (EUT) .....                            | 6         |
| 1.2. HOST SYSTEM CONFIGURATION LIST AND DETAILS .....             | 6         |
| 1.3. EXTERNAL I/O CABLE .....                                     | 6         |
| 1.4. DESCRIPTION OF TEST FACILITY .....                           | 6         |
| 1.5. STATEMENT OF THE MEASUREMENT UNCERTAINTY .....               | 7         |
| 1.6. MEASUREMENT UNCERTAINTY .....                                | 7         |
| 1.7. DESCRIPTION OF TEST MODES .....                              | 7         |
| <b>2. TEST METHODOLOGY .....</b>                                  | <b>8</b>  |
| 2.1. EUT CONFIGURATION .....                                      | 8         |
| 2.2. EUT EXERCISE .....                                           | 8         |
| 2.3. GENERAL TEST PROCEDURES .....                                | 8         |
| <b>3. SYSTEM TEST CONFIGURATION .....</b>                         | <b>9</b>  |
| 3.1. JUSTIFICATION .....                                          | 9         |
| 3.2. EUT EXERCISE SOFTWARE .....                                  | 9         |
| 3.3. SPECIAL ACCESSORIES .....                                    | 9         |
| 3.4. BLOCK DIAGRAM/SCHEMATICS .....                               | 9         |
| 3.5. EQUIPMENT MODIFICATIONS .....                                | 9         |
| 3.6. TEST SETUP .....                                             | 9         |
| <b>4. SUMMARY OF TEST RESULTS .....</b>                           | <b>10</b> |
| <b>5. TEST RESULT .....</b>                                       | <b>11</b> |
| 5.1. RADIATED EMISSION MEASUREMENT .....                          | 11        |
| 5.2. 99% OCCUPIED BANDWIDTH AND 20 DB BANDWIDTH MEASUREMENT ..... | 21        |
| 5.3. AC POWER LINE CONDUCTED EMISSIONS .....                      | 23        |
| 5.4. RESULTS FOR BAND EDGE TESTING .....                          | 26        |
| 5.5. ANTENNA REQUIREMENTS .....                                   | 29        |
| <b>6. LIST OF MEASURING EQUIPMENTS .....</b>                      | <b>30</b> |
| <b>7. TEST SETUP PHOTOGRAPHS OF EUT .....</b>                     | <b>31</b> |
| <b>8. EXTERIOR PHOTOGRAPHS OF THE EUT .....</b>                   | <b>31</b> |
| <b>9. INTERIOR PHOTOGRAPHS OF THE EUT .....</b>                   | <b>31</b> |

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

|                     |                                                                                                                                |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------|
| EUT                 | : Wireless Subwoofer Transmitter                                                                                               |
| Test Model          | : TOTEM LINK                                                                                                                   |
| Power Supply        | : For Adapter Input: AC 100-240V, 50/60Hz, 0.3A<br>For Adapter Output: DC 5V, 1A                                               |
| Hardware Version    | : /                                                                                                                            |
| Software Version    | : /                                                                                                                            |
| 5.8SRD              | :                                                                                                                              |
| Frequency Range     | : 5727~5804MHz (5727, 5730, 5734, 5738, 5749, 5753, 5756, 5760,<br>5771, 5776, 5779, 5782, 5793, 5797, 5801, 5804 (Unit: MHz)) |
| Channel Number      | : 16 channels                                                                                                                  |
| Modulation Type     | : GFSK                                                                                                                         |
| Antenna Description | : Internal Antenna, 0dBi (Max.)                                                                                                |

### 1.2. Host System Configuration List and Details

| Manufacturer | Description | Model | Serial Number | Certificate |
|--------------|-------------|-------|---------------|-------------|
| --           | --          | --    | --            | --          |

### 1.3. External I/O Cable

| I/O Port Description | Quantity | Cable |
|----------------------|----------|-------|
| DC IN                | 1        | N/A   |
| INPUT Port           | 2        | N/A   |

### 1.4. Description of Test Facility

FCC Registration Number is 254912.  
Industry Canada Registration Number is 9642A.  
EMSD Registration Number is ARCB0108.  
UL Registration Number is 100571-492.  
TUV SUD Registration Number is SCN1081.  
TUV RH Registration Number is UA 50296516-001.  
NVLAP Accreditation Code is 600167-0.  
FCC Designation Number is CN5024.  
CAB identifier: CN0071.

The 3m-Semi anechoic test site fulfils CISPR 16-1-4 according to ANSI C63.4:2014 and CISPR 16-1-4:2010 SVSWR requirement for radiated emission above 1GHz.

### 1.5. Statement of the Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. To CISPR 16 – 4 “Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements” and is documented in the LCS quality system acc. To DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

### 1.6. Measurement Uncertainty

| Test Item              | Frequency Range | Uncertainty | Note |
|------------------------|-----------------|-------------|------|
| Radiation Uncertainty  | 9KHz~30MHz      | ±3.10dB     | (1)  |
|                        | 30MHz~200MHz    | ±2.96dB     | (1)  |
|                        | 200MHz~1000MHz  | ±3.10dB     | (1)  |
|                        | 1GHz~26.5GHz    | ±3.80dB     | (1)  |
|                        | 26.5GHz~40GHz   | ±3.90dB     | (1)  |
| Conduction Uncertainty | 150kHz~300MHz   | ±1.63dB     | (1)  |
| Power disturbance      | 30MHz~300MHz    | ±1.60dB     | (1)  |

(1). This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

### 1.7. Description of Test Modes

The EUT has been tested under operating condition.

This test was performed with EUT in X, Y, Z position and the worst case was found when EUT in X position.

Worst-case mode and channel used for 9 KHz-1000 MHz radiated emissions was the mode and channel with the highest output power, that was determined to be 5.8GHz mode(Low Channel).

All test modes were tested, only the result of the worst case was recorded in the report.

#### Channel List & Frequency

| Channel | Frequency(MHz) |
|---------|----------------|
| 1       | 5727           |
| 9       | 5771           |
| 16      | 5804           |

| Mode of Operations    | Transmitting Frequency (MHz) |
|-----------------------|------------------------------|
| GFSK                  | 5727                         |
|                       | 5771                         |
|                       | 5804                         |
| For Radiated Emission |                              |
| Test Mode             | TX Mode                      |

## 2. TEST METHODOLOGY

All measurements contained in this report were conducted with ANSI C63.10-2013, American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices.

The radiated testing was performed at an antenna-to-EUT distance of 3 meters. All radiated and conducted emissions measurement was performed at Shenzhen LCS Compliance Testing Laboratory Ltd.

### 2.1. EUT Configuration

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

### 2.2. EUT Exercise

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.203, 15.205, 15.207, 15.209 and 15.249 under the FCC Rules Part 15 Subpart C.

### 2.3. General Test Procedures

#### 2.3.1 Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 6.2.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using Quasi-peak and average detector modes.

#### 2.3.2 Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 6.3 of ANSI C63.10-2013

### 2.4. Test Sample

The application provides 2 samples to meet requirement;

| Sample Number          | Description                           |
|------------------------|---------------------------------------|
| Sample 1(200403055A-1) | Engineer sample – continuous transmit |
| Sample 2(200403055A-2) | Normal sample – Intermittent transmit |

### 3. SYSTEM TEST CONFIGURATION

#### 3.1. Justification

The system was configured for testing in a continuous transmits condition.

#### 3.2. EUT Exercise Software

The system was configured for testing in a continuous transmits condition and change test channels by software (SPI.exe ) provided by applicant.

#### 3.3. Special Accessories

N/A

#### 3.4. Block Diagram/Schematics

Please refer to the related document

#### 3.5. Equipment Modifications

Shenzhen LCS Compliance Testing Laboratory Ltd. has not done any modification on the EUT.

#### 3.6. Test Setup

Please refer to the test setup photo.

#### 4. SUMMARY OF TEST RESULTS

| Applied Standard: FCC Part 15 Subpart C           |                                |                      |           |
|---------------------------------------------------|--------------------------------|----------------------|-----------|
| FCC Rules                                         | Description of Test            | Test Sample          | Result    |
| §15.205(a), §15.209(a),<br>§15.249(a), §15.249(c) | Radiated Emissions Measurement | Sample 1<br>Sample 2 | Compliant |
| §15.215(c)                                        | 20 dB Bandwidth Measurement    | Sample 1             | Compliant |
| §15.205, §15.249(d)                               | Emissions at Restricted Band   | Sample 1             | Compliant |
| §15.207(a)                                        | AC Line Conducted Emissions    | Sample 2             | Compliant |
| §15.203                                           | Antenna Requirements           | Sample 1             | Compliant |

## 5. TEST RESULT

### 5.1. Radiated Emission Measurement

#### 5.1.1. Standard Applicable

1. According to §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

| Frequencies(MHz) | Field Strength(microvolts/meter) | Measurement Distance(meters) |
|------------------|----------------------------------|------------------------------|
| 0.009~0.490      | 2400/F(KHz)                      | 300                          |
| 0.490~1.705      | 24000/F(KHz)                     | 30                           |
| 1.705~30.0       | 30                               | 30                           |
| 30~88            | 100                              | 3                            |
| 88~216           | 150                              | 3                            |
| 216~960          | 200                              | 3                            |
| Above 960        | 500                              | 3                            |

2. According to §15.249 (a): Except as provided in paragraph (b) of this section, the field strength of emissions from intentional radiators operated within these frequency bands shall comply with the following:

| Fundamental frequency | Field strength of fundamental |        | Field strength of harmonics |        |
|-----------------------|-------------------------------|--------|-----------------------------|--------|
|                       | millivolts/meter              | dBuV/m | microvolts/meter            | dBuV/m |
| 902-928 MHz           | 50                            | 94     | 500                         | 54     |
| 2400-2483.5 MHz       | 50                            | 94     | 500                         | 54     |
| 5725-5875 MHz         | 50                            | 94     | 500                         | 54     |
| 24.0-24.25 GHz        | 250                           | 108    | 2500                        | 68     |

As shown in §15.35(b), for frequencies above 1000 MHz, the field strength limits in paragraphs (a) and (b) of this section are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For point-to-point operation under paragraph (b) of this section, the peak field strength shall not exceed 2500 millivolts/meter at 3 meters along the antenna azimuth

#### 5.1.2. Measuring Instruments and Setting

Please refer to section 5 of equipments list in this report. The following table is the setting of spectrum analyzer and receiver.

| Spectrum Parameter                        | Setting                                        |
|-------------------------------------------|------------------------------------------------|
| Attenuation                               | Auto                                           |
| Start Frequency                           | 1000 MHz                                       |
| Stop Frequency                            | 10th carrier harmonic                          |
| RB / VB (Emission in restricted band)     | 1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |
| RB / VB (Emission in non-restricted band) | 1MHz / 3MHz for Peak, 1 MHz / 10Hz for Average |

| Receiver Parameter     | Setting                                        |
|------------------------|------------------------------------------------|
| Attenuation            | Auto                                           |
| Start ~ Stop Frequency | 9kHz~150kHz / RB/VB 200Hz/1KHz for QP/Average  |
| Start ~ Stop Frequency | 150kHz~30MHz / RB/VB 9kHz/30KHz for QP/Average |
| Start ~ Stop Frequency | 30MHz~1000MHz / RB/VB 120kHz/1MHz for QP       |

### 5.1.3. Test Procedures

#### 1) Sequence of testing 9 kHz to 30 MHz

##### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 0.8 m height is used.
- If the EUT is a floor standing device, it is placed on the ground.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions.
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

##### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna height is 0.8 meter.
- At each turntable position the analyzer sweeps with peak detection to find the maximum of all emissions

##### Final measurement:

- Identified emissions during the premeasurement the software maximizes by rotating the turntable position (0° to 360°) and by rotating the elevation axes (0° to 360°).
- The final measurement will be done in the position (turntable and elevation) causing the highest emissions with QPK detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.

## 2) Sequence of testing 30 MHz to 1 GHz

### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a table with 0.8 m height is used, which is placed on the ground plane.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height changes from 1 to 3 meter.
- At each turntable position, antenna polarization and height the analyzer sweeps three times in peak to find the maximum of all emissions.

### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter.
- The final measurement will be done with QP detector with an EMI receiver.
- The final levels, frequency, measuring time, bandwidth, antenna height, antenna polarization, turntable angle, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

### 3) Sequence of testing 1 GHz to 18 GHz

#### Setup:

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 3 meter.
- The EUT was set into operation.

#### Premeasurement:

- The turntable rotates from 0° to 315° using 45° steps.
- The antenna is polarized vertical and horizontal.
- The antenna height scan range is 1 meter to 2.5 meter.
- At each turntable position and antenna polarization the analyzer sweeps with peak detection to find the maximum of all emissions.

#### Final measurement:

- The final measurement will be performed with minimum the six highest peaks.
- According to the maximum antenna and turntable positions of premeasurement the software maximize the peaks by changing turntable position ( $\pm 45^\circ$ ) and antenna movement between 1 and 4 meter. This procedure is repeated for both antenna polarizations.
- The final measurement will be done in the position (turntable, EUT-table and antenna polarization) causing the highest emissions with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, turntable position, EUT-table position, antenna polarization, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement with marked maximum final measurements and the limit will be stored.

#### 4) Sequence of testing above 18 GHz

**Setup:**

- The equipment was set up to simulate a typical usage like described in the user manual or described by manufacturer.
- If the EUT is a tabletop system, a rotatable table with 1.5 m height is used.
- If the EUT is a floor standing device, it is placed on the ground plane with insulation between both.
- Auxiliary equipment and cables were positioned to simulate normal operation conditions
- The AC power port of the EUT (if available) is connected to a power outlet below the turntable.
- The measurement distance is 1 meter.
- The EUT was set into operation.


**Premeasurement:**

- The antenna is moved spherical over the EUT in different polarizations of the antenna.


**Final measurement:**

- The final measurement will be performed at the position and antenna orientation for all detected emissions that were found during the premeasurements with Peak and Average detector.
- The final levels, frequency, measuring time, bandwidth, correction factor, margin to the limit and limit will be recorded. Also a plot with the graph of the premeasurement and the limit will be stored.


## 5.1.4. Test Setup Layout



Below 30MHz



Below 1GHz



Above 1GHz

Above 18 GHz shall be extrapolated to the specified distance using an extrapolation factor of 20 dB/decade from 3m to 1m.

Distance extrapolation factor =  $20 \log (\text{specific distance [3m]} / \text{test distance [1.5m]})$  (dB);  
 Limit line = specific limits (dBuV) + distance extrapolation factor [6 dB].

## 5.1.5. EUT Operation during Test

The EUT was programmed to be in continuously transmitting mode.

## 5.1.6. Results of Radiated Emissions (9 KHz~30MHz)

|               |          |                |             |
|---------------|----------|----------------|-------------|
| Temperature   | 24.6℃    | Humidity       | 54.1 %      |
| Test Engineer | Scout Wu | Configurations | Low Channel |

| Freq.<br>(MHz) | Level<br>(dBuV) | Over Limit<br>(dB) | Over Limit<br>(dB) | Remark   |
|----------------|-----------------|--------------------|--------------------|----------|
| -              | -               | -                  | -                  | See Note |

## Note:

The amplitude of spurious emissions which are attenuated by more than 20 dB below the permissible value has no need to be reported.


Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB);

Limit line = specific limits (dBuV) + distance extrapolation factor.

## 5.1.7. Results of Radiated Emissions (30MHz~1GHz)


|               |          |                |             |
|---------------|----------|----------------|-------------|
| Temperature   | 24.6℃    | Humidity       | 54.1 %      |
| Test Engineer | Scout Wu | Configurations | Low Channel |

**Low Channel**  
Horizontal:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 39.0245         | 41.96          | -17.72        | 24.24          | 40.00          | -15.76      | QP   |
| 2 * | 68.8721         | 46.70          | -20.20        | 26.50          | 40.00          | -13.50      | QP   |
| 3   | 119.8556        | 42.84          | -20.13        | 22.71          | 43.50          | -20.79      | QP   |
| 4   | 239.9874        | 39.03          | -17.05        | 21.98          | 46.00          | -24.02      | QP   |
| 5   | 492.4685        | 36.95          | -11.61        | 25.34          | 46.00          | -20.66      | QP   |
| 6   | 881.4067        | 33.84          | -5.95         | 27.89          | 46.00          | -18.11      | QP   |

Vertical:



| No. | Frequency (MHz) | Reading (dBuV) | Factor (dB/m) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Det. |
|-----|-----------------|----------------|---------------|----------------|----------------|-------------|------|
| 1   | 37.8121         | 34.10          | -18.11        | 15.99          | 40.00          | -24.01      | QP   |
| 2 * | 62.8708         | 39.43          | -18.70        | 20.73          | 40.00          | -19.27      | QP   |
| 3   | 119.8556        | 32.72          | -20.13        | 12.59          | 43.50          | -30.91      | QP   |
| 4   | 263.8190        | 31.90          | -16.35        | 15.55          | 46.00          | -30.45      | QP   |
| 5   | 408.9460        | 34.10          | -13.10        | 21.00          | 46.00          | -25.00      | QP   |
| 6   | 528.2458        | 35.29          | -10.91        | 24.38          | 46.00          | -21.62      | QP   |

Note:

- 1). Pre-scan all modes and recorded the worst case results in this report (Low Channel). Emission level (dBuV/m) = 20 log Emission level (uV/m).
- 2). Margin=Reading level + Factor - Limit

## 5.1.8. Results of Radiated Emissions (Above 1GHz)

| Field Strength Of Fundamental |      |                             |                              |                     |                    |        |
|-------------------------------|------|-----------------------------|------------------------------|---------------------|--------------------|--------|
| Frequency (MHz)               | Pol. | Measure Result (PK, dBuV/m) | Measure Result (AVG, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
| 5727                          | H    | 87.90                       | 83.15                        | 114                 | 94                 | Pass   |
| 5727                          | V    | 87.90                       | 82.55                        | 114                 | 94                 | Pass   |

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 11454     | 55.32              | 33.06          | 35.04        | 3.94         | 57.28           | 74.00        | -16.72    | Peak    | Horizontal |
| 11454     | 43.56              | 33.06          | 35.04        | 3.94         | 45.52           | 54.00        | -8.48     | Average | Horizontal |
| 11454     | 58.47              | 33.06          | 35.04        | 3.94         | 60.43           | 74.00        | -13.57    | Peak    | Vertical   |
| 11454     | 43.10              | 33.06          | 35.04        | 3.94         | 45.06           | 54.00        | -8.94     | Average | Vertical   |

| Field Strength Of Fundamental |      |                             |                              |                     |                    |        |
|-------------------------------|------|-----------------------------|------------------------------|---------------------|--------------------|--------|
| Frequency (MHz)               | Pol. | Measure Result (PK, dBuV/m) | Measure Result (AVG, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
| 5771                          | H    | 88.28                       | 84.11                        | 114                 | 94                 | Pass   |
| 5771                          | V    | 87.82                       | 83.83                        | 114                 | 94                 | Pass   |

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 11542     | 60.76              | 33.16          | 35.15        | 3.96         | 62.73           | 74.00        | -11.27    | Peak    | Horizontal |
| 11542     | 40.54              | 33.16          | 35.15        | 3.96         | 42.51           | 54.00        | -11.49    | Average | Horizontal |
| 11542     | 53.79              | 33.16          | 35.15        | 3.96         | 55.76           | 74.00        | -18.24    | Peak    | Vertical   |
| 11542     | 43.51              | 33.16          | 35.15        | 3.96         | 45.48           | 54.00        | -8.52     | Average | Vertical   |

| Field Strength Of Fundamental |      |                             |                              |                     |                    |        |
|-------------------------------|------|-----------------------------|------------------------------|---------------------|--------------------|--------|
| Frequency (MHz)               | Pol. | Measure Result (PK, dBuV/m) | Measure Result (AVG, dBuV/m) | Peak Limit (dBuV/m) | AVG Limit (dBuV/m) | Result |
| 5804                          | H    | 87.84                       | 82.68                        | 114                 | 94                 | Pass   |
| 5804                          | V    | 87.57                       | 81.90                        | 114                 | 94                 | Pass   |

| Freq. MHz | Reading Level dBuV | Ant. Fac. dB/m | Pre. Fac. dB | Cab. Loss dB | Measured dBuV/m | Limit dBuV/m | Margin dB | Remark  | Pol.       |
|-----------|--------------------|----------------|--------------|--------------|-----------------|--------------|-----------|---------|------------|
| 11608     | 56.82              | 33.26          | 35.14        | 3.98         | 58.92           | 74.00        | -15.08    | Peak    | Horizontal |
| 11608     | 42.34              | 33.26          | 35.14        | 3.98         | 44.44           | 54.00        | -9.56     | Average | Horizontal |
| 11608     | 59.55              | 33.26          | 35.14        | 3.98         | 61.65           | 74.00        | -12.35    | Peak    | Vertical   |
| 11608     | 44.06              | 33.26          | 35.14        | 3.98         | 46.16           | 54.00        | -7.84     | Average | Vertical   |

## Notes:

1. Measuring frequencies from 9k~10th harmonic (ex. 26GHz), No emission found between lowest internal used/generated frequency to 30MHz.
2. Radiated emissions measured in frequency range from 9k~10th harmonic (ex. 26GHz) were made with an instrument using Peak detector mode.
3. No emission was be recorded above 18GHz means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
4. Margin=Reading level + Factor - Limit


## 5.2. 99% Occupied Bandwidth and 20 dB Bandwidth Measurement

### 5.2.1. Standard Applicable

According to § 2.1049 and RSS-Gen section 6.7 “The occupied bandwidth or the “99% emission bandwidth” is defined as the frequency range between two points, one above and the other below the carrier frequency, within which 99% of the total transmitted power of the fundamental transmitted emission is contained. The occupied bandwidth shall be reported for all equipment in addition to the specified bandwidth required in the applicable RSSs.”

In some cases, the “x dB bandwidth” is required, which is defined as the frequency range between two points, one at the lowest frequency below and one at the highest frequency above the carrier frequency, at which the maximum power level of the transmitted emission is attenuated x dB below the maximum in band power level of the modulated signal, where the two points are on the outskirts of the in-band emission.

### 5.2.2. Block Diagram of Test Setup



### 5.2.3. Test Procedure

Use the following spectrum analyzer settings:

Span = 20MHz

RBW = 100 KHz

VBW = 300 KHz

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).

### 5.2.4. Test Result


|               |          |                |              |
|---------------|----------|----------------|--------------|
| Temperature   | 23.4℃    | Humidity       | 53.7%        |
| Test Engineer | Scout Wu | Configurations | 5.8G (GFSK ) |

| Test Mode | Channel | Frequency (MHz) | 20dB Bandwidth (kHz) | Limits        | Verdict |
|-----------|---------|-----------------|----------------------|---------------|---------|
| GFSK      | Low     | 5727            | 854.1                | Non-specified | PASS    |
|           | Middle  | 5771            | 692.3                |               |         |
|           | High    | 5804            | 638.1                |               |         |


*Remark:*

1. Test results including cable loss;
2. please refer to following plots;


## 20dB Bandwidth and 99% Bandwidth



## Low Channel- 5727MHz



## Middle Channel- 5771MHz



## High Channel- 5804MHz

### 5.3. AC Power line conducted emissions


#### 5.3.1 Standard Applicable

According to §15.207 (a): For an intentional radiator which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

| Frequency Range (MHz) | Limits (dB $\mu$ V) |          |
|-----------------------|---------------------|----------|
|                       | Quasi-peak          | Average  |
| 0.15 to 0.50          | 66 to 56            | 56 to 46 |
| 0.50 to 5             | 56                  | 46       |
| 5 to 30               | 60                  | 50       |

\* Decreasing linearly with the logarithm of the frequency

#### 5.3.2 Block Diagram of Test Setup




#### 5.3.3 Test Results

The test data please refer to following page.

|               |          |          |       |
|---------------|----------|----------|-------|
| Temperature   | 23.3°C   | Humidity | 53.7% |
| Test Engineer | Scont Wu |          |       |


**AC Conducted Emission of charge from power adapter mode @ AC 120V/60Hz (worst case)**

Line



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.3704             | 21.22             | 19.31           | 40.53            | 58.49           | -17.96         | QP     |
| 2   | 0.3712             | 6.65              | 19.31           | 25.96            | 48.47           | -22.51         | AVG    |
| 3   | 0.9465             | 15.53             | 19.28           | 34.81            | 56.00           | -21.19         | QP     |
| 4   | 1.0095             | 2.36              | 19.25           | 21.61            | 46.00           | -24.39         | AVG    |
| 5   | 1.3515             | 14.19             | 19.31           | 33.50            | 56.00           | -22.50         | QP     |
| 6   | 1.4280             | 1.42              | 19.32           | 20.74            | 46.00           | -25.26         | AVG    |
| 7   | 9.1410             | 5.83              | 19.66           | 25.49            | 60.00           | -34.51         | QP     |
| 8   | 9.5100             | -3.80             | 19.67           | 15.87            | 50.00           | -34.13         | AVG    |
| 9   | 18.7800            | 10.93             | 20.11           | 31.04            | 60.00           | -28.96         | QP     |
| 10  | 18.8970            | -4.53             | 20.10           | 15.57            | 50.00           | -34.43         | AVG    |
| 11  | 25.7145            | 7.20              | 20.09           | 27.29            | 60.00           | -32.71         | QP     |
| 12  | 25.7145            | -5.38             | 20.09           | 14.71            | 50.00           | -35.29         | AVG    |

## Neutral



| No. | Frequency<br>(MHz) | Reading<br>(dBuV) | Correct<br>(dB) | Result<br>(dBuV) | Limit<br>(dBuV) | Margin<br>(dB) | Remark |
|-----|--------------------|-------------------|-----------------|------------------|-----------------|----------------|--------|
| 1   | 0.3673             | 24.16             | 19.31           | 43.47            | 58.56           | -15.09         | QP     |
| 2   | 0.3704             | 13.22             | 19.31           | 32.53            | 48.49           | -15.96         | AVG    |
| 3   | 0.9420             | 19.69             | 19.28           | 38.97            | 56.00           | -17.03         | QP     |
| 4   | 0.9870             | 7.68              | 19.26           | 26.94            | 46.00           | -19.06         | AVG    |
| 5   | 1.4144             | 17.71             | 19.32           | 37.03            | 56.00           | -18.97         | QP     |
| 6   | 1.4144             | 7.00              | 19.32           | 26.32            | 46.00           | -19.68         | AVG    |
| 7   | 10.3200            | 10.40             | 19.71           | 30.11            | 60.00           | -29.89         | QP     |
| 8   | 10.8015            | 0.22              | 19.76           | 19.98            | 50.00           | -30.02         | AVG    |
| 9   | 18.7800            | 10.73             | 20.11           | 30.84            | 60.00           | -29.16         | QP     |
| 10  | 18.9060            | -4.72             | 20.10           | 15.38            | 50.00           | -34.62         | AVG    |
| 11  | 25.4895            | 8.46              | 20.11           | 28.57            | 60.00           | -31.43         | QP     |
| 12  | 25.8675            | -5.09             | 20.09           | 15.00            | 50.00           | -35.00         | AVG    |

\*\*\*Note: Pre-scan all modes and recorded the worst case results in this report.

Margin=Reading level + Correct - Limit


## 5.4. Results for Band edge Testing

### 5.4.1 Standard Applicable

According to FCC §15.249 (d): Emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 50 dB below the level of the fundamental or to the general radiated emission limits in §15.209, whichever is the lesser attenuation.

According to RSS-210 B.10 (b): Emissions radiated outside of the specified frequency bands, except for harmonic emissions, shall be attenuated by at least 50 dB below the level of the fundamental emissions or to the general field strength limits listed in RSS-Gen, whichever is less stringent.

### 5.4.2. Test Setup Layout



### 5.4.3. Measuring Instruments and Setting

Please refer to equipment list in this report. The following table is the setting of Spectrum Analyzer.

### 5.4.4. Test Procedures

According to ANSI C63.10:2013 Field Strength Approach (linear terms):

$$\text{eirp} = p_t \times g_t = (E \times d)^2 / 30$$

Where:

$p_t$  = transmitter output power in watts,

$g_t$  = numeric gain of the transmitting antenna (unitless),

$E$  = electric field strength in V/m,

$d$  = measurement distance in meters (m).

$$\text{erp} = \text{eirp} / 1.64 = (E \times d)^2 / (30 \times 1.64)$$

Where all terms are as previously defined.

1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator.
2. Remove the antenna from the EUT and then connect to a low loss RF cable from the antenna port to an EMI test receiver, then turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, and make sure the instrument is operated in its linear range.
3. Set both RBW and VBW of spectrum analyzer for Radiated emissions restricted band RBW=1MHz, VBW=3MHz for peak detector and RBW=1MHz, VBW=1/B for Peak detector.
4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency.
5. Repeat above procedures until all measured frequencies were complete.
6. Measure the conducted output power (in dBm) using the detector specified by the appropriate regulatory agency for guidance regarding measurement procedures for determining quasi-peak, peak, and average conducted output power, respectively).
7. Add the maximum transmit antenna gain (in dBi) to the measured output power level to determine the EIRP level (see 12.2.5 for guidance on determining the applicable antenna gain)
8. Add the appropriate maximum ground reflection factor to the EIRP level (6 dB for frequencies  $\leq 30$  MHz, 4.7 dB for frequencies between 30 MHz and 1000 MHz, inclusive and 0 dB for frequencies  $> 1000$  MHz).

9. For devices with multiple antenna-ports, measure the power of each individual chain and sum the EIRP of all chains in linear terms (e.g., Watts, mW).
10. Compare the resultant electric field strength level to the applicable regulatory limit.
11. Perform radiated spurious emission test duress until all measured frequencies were complete.


#### 5.4.5. Measuring Instruments and Setting

| GFSK      |                   |                  |                |              |          |
|-----------|-------------------|------------------|----------------|--------------|----------|
| Freq. MHz | Reading Level dBm | Antenna Gain dBi | EIRP (dBm/MHz) | Limit dBuV/m | Detector |
| 5722.5    | -29.274           | 0                | -29.274        | -27.0        | Peak     |
| 5710.9    | -32.391           | 0                | -32.391        | 10           | Peak     |
| 5679.1    | -45.978           | 0                | -45.978        | 15.6         | Peak     |
| 5663.2    | -48.649           | 0                | -48.649        | 15.6         | Peak     |
| 5806.3    | -31.099           | 0                | -31.099        | 27.0         | Peak     |
| 5820.0    | -36.300           | 0                | -36.300        | 15.6         | Peak     |
| 5825.4    | -48.972           | 0                | -48.972        | 15.6         | Peak     |
| 5868.1    | -50.186           | 0                | -50.186        | 27.0         | Peak     |


#### Remark:

1. The other emission levels were very low against the limit.
2. The average measurement was not performed when the peak measured data under the limit of average detection.
3. Detector AV is setting spectrum/receiver. RBW=1MHz/VBW=10Hz/Sweep time=Auto/Detector=Peak;
4. Since the out-of-band characteristics of the EUT transmit antenna will often be unknown, the use of a conservative antenna gain value is necessary. Thus, when determining the EIRP based on the measured conducted power, the upper bound on antenna gain for a device with a single RF output shall be selected as the maximum in-band gain of the antenna across all operating bands, or 2 dBi, whichever is greater. However, for devices that operate in multiple frequency bands while using the same transmit antenna, the highest gain of the antenna within the operating band nearest in frequency to the restricted band emission being measured may be used in lieu of the overall highest gain when the emission is at a frequency that is within 20 percent of the nearest band edge frequency, but in no case shall a value less than 2 dBi be used.
5. Please refer to following test plots;

## Test plot of Band Edge (Conducted)



## Low Channel / 5727MHz - Peak



## High Channel / 5804MHz - Peak

## 5.5. Antenna Requirements

### 5.5.1 Standard Applicable

According to antenna requirement of §15.203.

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be re-placed by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of Sections 15.211, 15.213, 15.217, 15.219, or 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with Section 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this Part are not exceeded.

And according to §15.247(4)(1), system operating in the 2400-2483.5MHz bands that are used exclusively for fixed, point-to-point operations may employ transmitting antennas with directional gain greater than 6dBi provided the maximum peak output power of the intentional radiator is reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6dBi.

### 5.5.2 Antenna Connected Construction

#### 5.5.2.1. Standard Applicable

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

#### 5.5.2.2. Antenna Connector Construction

The directional gains of antenna used for transmitting is 0dBi, and the antenna is an Internal antenna connect to PCB board and no consideration of replacement. Please see EUT photo for details.

#### 5.5.2.3. Results: Compliance.

## 6. LIST OF MEASURING EQUIPMENTS

| Item | Equipment                      | Manufacturer     | Model No.    | Serial No.      | Cal Date   | Due Date   |
|------|--------------------------------|------------------|--------------|-----------------|------------|------------|
| 1    | MXA Signal Analyzer            | Agilent          | N9020A       | MY49100060      | 2019-11-14 | 2020-11-13 |
| 2    | DC Power Supply                | Agilent          | E3642A       | N/A             | 2019-11-14 | 2020-11-13 |
| 3    | Temperature & Humidity Chamber | GUANGZHOU GOGNWN | GDS-100      | 70932           | 2019-10-09 | 2020-10-08 |
| 4    | EMI Test Software              | AUDIX            | E3           | /               | 2019-06-15 | 2020-06-14 |
| 5    | 3m Semi Anechoic Chamber       | SIDT FRANKONIA   | SAC-3M       | 03CH03-HY       | 2019-06-15 | 2020-06-14 |
| 6    | Positioning Controller         | MF               | MF-7082      | /               | 2019-06-15 | 2020-06-14 |
| 7    | Active Loop Antenna            | SCHWARZBEC K     | FMZB 1519B   | 00005           | 2019-07-25 | 2020-07-24 |
| 8    | By-log Antenna                 | SCHWARZBEC K     | VULB9163     | 9163-470        | 2019-07-25 | 2020-07-24 |
| 9    | Horn Antenna                   | SCHWARZBEC K     | BBHA 9120D   | 9120D-1925      | 2019-07-01 | 2020-06-30 |
| 10   | Broadband Horn Antenna         | SCHWARZBEC K     | BBHA 9170    | 791             | 2019-09-19 | 2020-09-18 |
| 11   | EMI Test Receiver              | R&S              | ESR 7        | 101181          | 2019-06-15 | 2020-06-14 |
| 12   | RS SPECTRUM ANALYZER           | R&S              | FSP40        | 100503          | 2019-11-14 | 2020-11-13 |
| 13   | AMPLIFIER                      | QuieTek          | QTK          | CHM/0809065     | 2019-11-14 | 2020-11-13 |
| 14   | RF Cable-R03m                  | Jye Bao          | RG142        | CB021           | 2019-06-15 | 2020-06-14 |
| 15   | RF Cable-HIGH                  | SUHNER           | SUCOFLEX 106 | 03CH03-HY       | 2019-06-15 | 2020-06-14 |
| 16   | EMI Test Receiver              | R&S              | ESPI         | 101840          | 2019-06-15 | 2020-06-14 |
| 17   | Artificial Mains               | R&S              | ENV216       | 101288          | 2019-06-15 | 2020-06-14 |
| 18   | 10dB Attenuator                | SCHWARZBEC K     | MTS-IMP-136  | 261115-001-0032 | 2019-06-15 | 2020-06-14 |

Note: All equipment is calibrated through GUANGZHOU LISAI CALIBRATION AND TEST CO.,LTD.

## **7. TEST SETUP PHOTOGRAPHS OF EUT**

Please refer to separated files for Test Setup Photos of the EUT.

## **8. EXTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for External Photos of the EUT.

## **9. INTERIOR PHOTOGRAPHS OF THE EUT**

Please refer to separated files for Internal Photos of the EUT.

-----THE END OF REPORT-----