

# TEST REPORT

Product Name : Electric Fireplace  
Model Number : 210-220, 210-234,  
210-245, 210-262  
FCC ID : 2AQ6Y-EREFLEX

Prepared for : Gazco Limited  
Address : Spitfire Avenue, Skypark, Clyst Honiton, Exeter, Devon,  
EX5 2FR, United Kingdom

Prepared by : EMTEK (DONGGUAN) CO., LTD.  
Address : -1&2F., Building 2, Zone A, Zhongda Marine Biotechnology  
Research and Development Base, No. 9, Xincheng Avenue,  
Songshanhu High-technology Industrial Development Zone,  
Dongguan, Guangdong, China

Tel : +86-0769-22807078  
Fax: +86-0769-22807079

Report Number : EDG2303130266E01502R  
Date(s) of Tests : March 13, 2023 to May 11, 2023  
Date of Issue : June 20, 2023

## TABLE OF CONTENTS

|          |                                                  |           |
|----------|--------------------------------------------------|-----------|
| <b>1</b> | <b>TEST RESULT CERTIFICATION .....</b>           | <b>3</b>  |
| <b>2</b> | <b>EUT TECHNICAL DESCRIPTION .....</b>           | <b>4</b>  |
| <b>3</b> | <b>SUMMARY OF TEST RESULT .....</b>              | <b>5</b>  |
| <b>4</b> | <b>TEST METHODOLOGY .....</b>                    | <b>6</b>  |
| 4.1      | GENERAL DESCRIPTION OF APPLIED STANDARDS .....   | 6         |
| 4.2      | MEASUREMENT EQUIPMENT USED .....                 | 6         |
| 4.3      | DESCRIPTION OF TEST MODES .....                  | 7         |
| 4.4      | TEST SOFTWARE .....                              | 7         |
| <b>5</b> | <b>FACILITIES AND ACCREDITATIONS .....</b>       | <b>8</b>  |
| 5.1      | FACILITIES .....                                 | 8         |
| 5.2      | LABORATORY ACCREDITATIONS AND LISTINGS .....     | 8         |
| <b>6</b> | <b>TEST SYSTEM UNCERTAINTY .....</b>             | <b>9</b>  |
| <b>7</b> | <b>SETUP OF EQUIPMENT UNDER TEST .....</b>       | <b>10</b> |
| 7.1      | RADIO FREQUENCY TEST SETUP 1 .....               | 10        |
| 7.2      | RADIO FREQUENCY TEST SETUP 2 .....               | 10        |
| 7.3      | CONDUCTED EMISSION TEST SETUP .....              | 11        |
| 7.4      | BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM ..... | 12        |
| 7.5      | SUPPORT EQUIPMENT .....                          | 12        |
| <b>8</b> | <b>TEST REQUIREMENTS .....</b>                   | <b>13</b> |
| 8.1      | OCCUPIED BANDWIDTH .....                         | 13        |
| 8.2      | FREQUENCY STABILITY .....                        | 15        |
| 8.3      | RADIATED SPURIOUS EMISSION .....                 | 16        |
| 8.4      | TRANSMISSION REQUIREMENT .....                   | 23        |
| 8.5      | CONDUCTED EMISSIONS TEST .....                   | 25        |
| 8.6      | ANTENNA APPLICATION .....                        | 26        |

## 1 TEST RESULT CERTIFICATION

Applicant : Gazco Limited

Address : Spitfire Avenue, Skypark, Clyst Honiton, Exeter, Devon, EX5 2FR, United Kingdom

Manufacturer : Ningbo Richen Electrical Appliance Co., Ltd.

Address : No.19 Yongdinghe Road, Xiapu, Beilun, Ningbo, 315807 Zhejiang, P.R.China

EUT : Electric Fireplace

Model Name : 210-220, 210-234, 210-245, 210-262

Trademark : N/A

Measurement Procedure Used:

| APPLICABLE STANDARDS                                          |             |
|---------------------------------------------------------------|-------------|
| STANDARD                                                      | TEST RESULT |
| FCC 47 CFR Part 2, Subpart J<br>FCC 47 CFR Part 15, Subpart C | PASS        |

The above equipment was tested by EMTEK (DONGGUAN) CO., LTD. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10 (2013) and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 2 and Part 15.231

The test results of this report relate only to the tested sample identified in this report.

Date of Test : March 13, 2023 to May 11, 2023

Prepared by : Warren Deng  
Warren deng /Engineer

Reviewer : Tim Dong  
Tim Dong /Supervisor

Approved & Authorized Signer : Sam Lv  
Sam Lv /Manager



## 2 EUT TECHNICAL DESCRIPTION

| Characteristics             | Description                                                                                                                                                                                           |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Product:</b>             | Electric Fireplace                                                                                                                                                                                    |
| <b>Model Number:</b>        | 210-220, 210-234, 210-245, 210-262<br>Note: They are similar in construction except size and LED lightings. The schematic design is identical to the PCB layout. We chose " 210-262 " for RF testing. |
| <b>Sample Number:</b>       | 1#                                                                                                                                                                                                    |
| <b>Modulation:</b>          | FSK modulation                                                                                                                                                                                        |
| <b>Operating Frequency:</b> | 433.92MHz                                                                                                                                                                                             |
| <b>Number of Channels:</b>  | 1 channel                                                                                                                                                                                             |
| <b>Max Transmit Power:</b>  | 85.11 dBuV/m                                                                                                                                                                                          |
| <b>Antenna Type :</b>       | Spring Antenna                                                                                                                                                                                        |
| <b>Antenna Gain:</b>        | 0.0 dBi                                                                                                                                                                                               |
| <b>Power supply:</b>        | AC 120V/60Hz                                                                                                                                                                                          |
| <b>Temperature Range:</b>   | -40°C ~ +85°C                                                                                                                                                                                         |
| <b>Date of Received:</b>    | March 13, 2023                                                                                                                                                                                        |

*Note: for more details, please refer to the User's manual of the EUT.*

### 3 SUMMARY OF TEST RESULT

| FCC PartClause              | Test Parameter              | Verdict | Remark |
|-----------------------------|-----------------------------|---------|--------|
| 15.231(c)                   | Occupied Bandwidth          | PASS    |        |
| 15.231(d)                   | Frequency stability         | N/A     |        |
| 15.231(b)                   | Radiated Spurious Emissions | PASS    |        |
| 15.231(b)                   | Transmission Requirement    | PASS    |        |
| 15.203                      | Antenna Requirement         | PASS    |        |
| 15.207(a)                   | Conducted Emission          | N/A     |        |
| NOTE1: N/A (Not Applicable) |                             |         |        |

#### RELATED SUBMITTAL(S) / GRANT(S):

This submittal(s) (test report) is intended for FCC ID: 2AQ6Y-EREFLEX filing to comply with Section 15.231 of the FCC Part 15, Subpart C Rules.

## 4 TEST METHODOLOGY

### 4.1 GENERAL DESCRIPTION OF APPLIED STANDARDS

According to its specifications, the EUT must comply with the requirements of the following standards:

FCC 47 CFR Part 2, Subpart J

FCC 47 CFR Part 15, Subpart C

### 4.2 MEASUREMENT EQUIPMENT USED

#### 4.2.1 Radiated Emission Test Equipment

| Equipment                | Manufacturer    | Model No.                | Serial No.   | Last Cal.  | Cal. Interval |
|--------------------------|-----------------|--------------------------|--------------|------------|---------------|
| EMI Test Receiver        | Rohde & Schwarz | ESCI                     | 101415       | 2022/05/19 | 1Year         |
| Power Amplifier          | HP              | 8447F                    | OPH64        | 2022/05/19 | 1Year         |
| Bilog Antenna            | Schwarzbeck     | VULB9163                 | 141          | 2022/05/22 | 1Year         |
| Horn antenna             | Schwarzbeck     | BBHA9120D                | 1272         | 2022/05/22 | 1Year         |
| Power Amplifier          | LUNAR EM        | LNA1G18-40               | J10100000081 | 2022/05/19 | 1Year         |
| Loop Antenna             | Schwarzbeck     | FMZB1513                 | 1513-60      | 2022/05/22 | 2 Year        |
| Signal Analyzer          | R&S             | FSV30                    | 103039       | 2022/05/19 | 1Year         |
| Bilog Antenna            | Schwarzbeck     | VULB9163                 | 141          | 2022/05/22 | 1Year         |
| Band reject Filter(50dB) | WI/DE           | WRCGV-2400(2400-2485MHz) | 2            | 2022/05/20 | 1 Year        |

#### 4.2.2 Radio Frequency Test Equipment

| Equipment                         | Manufacturer | Model No. | Serial No. | Last Cal.  | Cal. Interval |
|-----------------------------------|--------------|-----------|------------|------------|---------------|
| Wireless Connectivity Tester      | R&S          | CMW270    | 102543     | 2022/06/21 | 1Year         |
| Automatic Control Unit            | Tonscend     | JS0806-2  | 2118060480 | 2022/06/21 | 1Year         |
| Signal Analyzer                   | KEYSIGHT     | N9010B    | MY60242456 | 2022/06/21 | 1Year         |
| Analog Signal Generator           | KEYSIGHT     | N5173B    | MY61252625 | 2022/06/21 | 1Year         |
| UP/DOWN-Converter                 | R&S          | CMW-Z800A | 100274     | 2022/06/21 | 1Year         |
| Vector Signal Generator           | KEYSIGHT     | N5182B    | MY61252674 | 2022/06/21 | 1Year         |
| Frequency Extender                | KEYSIGHT     | N5182BX07 | MY59362541 | 2022/06/21 | 1Year         |
| Temperature&Humidity test chamber | ESPEC        | EL-02KA   | 12107166   | 2022/06/21 | 1 Year        |

**Remark:** Each piece of equipment is scheduled for calibration once a year.

### 4.3 DESCRIPTION OF TEST MODES

The EUT has been tested under its typical operating condition.

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner which intends to maximize its emission characteristics in a continuous normal application.

The Transmitter was operated in the normal operating mode. The TX frequency was fixed which was for the purpose of the measurements.

Test of channel included the lowest and middle and highest frequency to perform the test, then record on this report.

Pre-defined engineering program for regulatory testing used to control the EUT for staying in continuous transmitting mode is programmed.

Frequency and Channel list:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|---------|-----------------|
| 0       | 433.92          |         |                 |         |                 |

Test Frequency and Channel list:

| Lowest Frequency |                 | Middle Frequency |                 | Highest Frequency |                 |
|------------------|-----------------|------------------|-----------------|-------------------|-----------------|
| Channel          | Frequency (MHz) | Channel          | Frequency (MHz) | Channel           | Frequency (MHz) |
| 0                | 433.92          |                  |                 |                   |                 |

### 4.4 TEST SOFTWARE

| Item               | Software            |
|--------------------|---------------------|
| Radiated Emission: | EMC (Ver. EMEC-3A1) |

## 5 FACILITIES AND ACCREDITATIONS

### 5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

EMTEK (Dongguan) Co., Ltd.

-1&2F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No. 9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.10 and CISPR Publication 32.

### 5.2 LABORATORY ACCREDITATIONS AND LISTINGS

#### Site Description

#### EMC Lab.

: Accredited by CNAS, 2020.08.27  
The certificate is valid until 2024.07.05  
The Laboratory has been assessed and proved to be in compliance with  
CNAS/CL01:2018  
The Certificate Registration Number is L3150

Accredited by FCC  
Designation Number: CN1300  
Test Firm Registration Number: 945551

Accredited by A2LA, April 05, 2021  
The Certificate Registration Number is 4321.02

Accredited by Industry Canada  
The Certificate Registration Number is CN0113

#### Name of Firm

: EMTEK (Dongguan) Co., Ltd.

#### Site Location

: -1&2/F., Building 2, Zone A, Zhongda Marine Biotechnology Research and Development Base, No. 9, Xincheng Avenue, Songshanhu High-technology Industrial Development Zone, Dongguan, Guangdong, China

## 6 TEST SYSTEM UNCERTAINTY

The following measurement uncertainty levels have been estimated for tests performed on the apparatus:

| Parameter               | Uncertainty            |
|-------------------------|------------------------|
| Radio Frequency         | $\pm 1 \times 10^{-5}$ |
| Radiated Emission Test  | $\pm 2.0$ dB           |
| Occupied Bandwidth Test | $\pm 1.0$ dB           |
| Band Edge Test          | $\pm 3$ dB             |
| All emission, radiated  | $\pm 3$ dB             |
| Temperature             | $\pm 0.5$ °C           |
| Humidity                | $\pm 3$ %              |


Measurement Uncertainty for a level of Confidence of 95%



## 7 SETUP OF EQUIPMENT UNDER TEST

### 7.1 RADIO FREQUENCY TEST SETUP 1

The component's antenna ports(s) of the EUT are connected to the measurement instrument per an appropriate attenuator. The EUT is controlled by PC/software to emit the specified signals for the purpose of measurements.



### 7.2 RADIO FREQUENCY TEST SETUP 2

The test site semi-anechoic chamber has met the requirement of NSA tolerance 4 dB according to the standards: ANSI C63.10. The test distance is 3m. The setup is according to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 and CAN/CSA-CEI/IEC CISPR 22.

Below 30MHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna (loop antenna). The Antenna should be positioned with its plane vertical at the specified distance from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. The center of the loop shall be 1 m above the ground. For certain applications, the loop antenna plane may also need to be positioned horizontally at the specified distance from the EUT.


30MHz-1GHz:

The EUT is placed on a turntable 0.8 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


Above 1GHz:

The EUT is placed on a turntable 1.5 meters above the ground in the chamber, 3 meter away from the antenna. The maximal emission value is acquired by adjusting the antenna height, polarisation and turntable azimuth. Normally, the height range of antenna is 1 m to 4 m, the azimuth range of turntable is 0° to 360°, and the receive antenna has two polarizations Vertical (V) and Horizontal (H).


(a) Radiated Emission Test Set-Up, Frequency Below 30MHz



(b) Radiated Emission Test Set-Up, Frequency Below 1000MHz



(c) Radiated Emission Test Set-Up, Frequency above 1000MHz




### 7.3 CONDUCTED EMISSION TEST SETUP


The mains cable of the EUT (maybe per AC/DC Adapter) must be connected to LISN. The LISN shall be placed 0.8 m from the boundary of EUT and bonded to a ground reference plane for LISN mounted on top of the ground reference plane. This distance is between the closest points of the LISN and the EUT. All other units of the EUT and associated equipment shall be at least 0.8m from the LISN.

Ground connections, where required for safety purposes, shall be connected to the reference ground point of the LISN and, where not otherwise provided or specified by the manufacturer, shall be of same length as the mains cable and run parallel to the mains connection at a separation distance of not more than 0.1 m.

According to the requirements in Section 13.1.4.1 of ANSI C63.10-2013 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode.



#### 7.4 BLOCK DIAGRAM CONFIGURATION OF TEST SYSTEM



#### 7.5 SUPPORT EQUIPMENT

**EUT Cable List and Details**

| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
|-------------------|------------|---------------------|------------------------|
| /                 | /          | /                   | /                      |

**Auxiliary Cable List and Details**

| Cable Description | Length (m) | Shielded/Unshielded | With / Without Ferrite |
|-------------------|------------|---------------------|------------------------|
| /                 | /          | /                   | /                      |

**Auxiliary Equipment List and Details**

| Description | Manufacturer | Model | Serial Number |
|-------------|--------------|-------|---------------|
| /           | /            | /     | /             |

**Notes:**

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.
3. Unless otherwise denoted as EUT in 『Remark』 column , device(s) used in tested system is a support equipment

## 8 TEST REQUIREMENTS

### 8.1 OCCUPIED BANDWIDTH

#### 8.1.1 Applicable Standard

According to FCC Part 2.1049 and part 15.231(c)

#### 8.1.2 Conformance Limit

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20 dB down from the modulated carrier.

#### 8.1.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

#### 8.1.4 Test Procedure

The EUT was operating in transmit mode and controlled its channel. Printed out the test result from the spectrum by hard copy function.

The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.

Set to the maximum power setting and enable the EUT transmit continuously

Set RBW = 1kHz.

Set the video bandwidth (VBW) = 3kHz.

Set Span = approximately 2 to 3 times the occupied bandwidth

Set Detector = Peak.

Set Trace mode = max hold.

Set Sweep = auto couple.

The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission.

If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation.

Measure and record the results in the test report.


#### 8.1.5 Test Results

|                    |           |
|--------------------|-----------|
| Temperature:       | 20° C     |
| Relative Humidity: | 58%       |
| ATM Pressure:      | 1011 mbar |

| Operation Mode                                                                | Channel Number | Channel Frequency (MHz) | Measurement Bandwidth (kHz) | Limit (kHz) | Verdict |
|-------------------------------------------------------------------------------|----------------|-------------------------|-----------------------------|-------------|---------|
| ASK                                                                           | 0              | 433.92                  | 68.82                       | ≤1084.8     | PASS    |
| Note: Limit = 0.25% of the center frequency = 433.92 MHz * 0.25% = 1.0848 MHz |                |                         |                             |             |         |

Test Model

Occupied Bandwidth  
FSK Modulation  
Channel 0:433.92MHz



## 8.2 FREQUENCY STABILITY

### 8.2.1 Applicable Standard

According to FCC Part 2.1055 and part 15.231(d)

### 8.2.2 Conformance Limit

According to part 15.231(d), For devices operating within the frequency band 40.66-40.70 MHz, the bandwidth of the emission shall be confined within the band edges and the frequency tolerance of the carrier shall be  $\pm 0.01\%$ . This frequency tolerance shall be maintained for a temperature variation of  $-20$  degrees to  $+50$  degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new batter

### 8.2.3 Test Configuration

Test according to clause 7.1 radio frequency test setup 1

### 8.2.4 Test Procedure

Connect the EUT to frequency analyzer via the antenna connector.

EUT was placed at temperature chamber and connected to an external power supply.

Temperature and voltage condition shall be tested to confirm frequency stability.

(a) Frequency measurements shall be made at the extremes of the specified temperature range and at intervals of not more than  $10^{\circ}$  centigrade through the range. A period of time sufficient to stabilize all of the components of the oscillator circuit at each temperature level shall be allowed prior to frequency measurement. The short-term transient effects on the frequency of the transmitter due to keying (except for broadcast transmitters) and any heating element cycling normally occurring at each ambient temperature level also shall be shown. Only the portion or portions of the transmitter containing the frequency determining and stabilizing circuitry need be subjected to the temperature variation test.

(b) The frequency stability shall be measured with variation of primary supply voltage as follows:

(1) Vary primary supply voltage from 85 to 115 percent of the nominal value for other than hand carried battery equipment.

(2) For hand carried, battery powered equipment, reduce primary supply voltage to the battery operating end point, which shall be specified by the manufacturer.

### 8.2.5 Test Results

|                    |           |
|--------------------|-----------|
| Temperature:       | 26° C     |
| Relative Humidity: | 54%       |
| ATM Pressure:      | 1011 mbar |

Not applicable, the device operating without the frequency band 40.66-40.70MHz

### 8.3 RADIATED SPURIOUS EMISSION

#### 8.3.1 Applicable Standard

According to FCC Part 15.231(b) and 15.209

#### 8.3.2 Conformance Limit

According to FCC Part 15.231(b), the field strength of emissions from intentional radiators operated under this section shall not exceed the following:

| Frequencies<br>(MHz) | Field strength of fundamental<br>(microvolts/meter) |             | Field strength of spurious emissions<br>(microvolts/meter) |             |
|----------------------|-----------------------------------------------------|-------------|------------------------------------------------------------|-------------|
|                      | (uV/m)                                              | dB(uV/m)    | (uV/m)                                                     | dB(uV/m)    |
| 40.66-40.70          | 2250                                                |             | 225                                                        |             |
| 70-130               | 1250                                                |             | 125                                                        |             |
| 130-174              | 1250 to 3750*                                       |             | 125 to 375*                                                |             |
| 174-260              | 3750                                                |             | 375                                                        |             |
| <b>260-470</b>       | 3,750 to 12,500                                     | 71.48-81.93 | 3,75 to 12,50                                              | 51.48-61.93 |
| Above 470            | 12500                                               |             | 1250                                                       |             |

\* Linear interpolation

The field intensity in micro-volts per meter can then be determined by the following equation:  $FI(V/m) = 10FI(dBV/m) / 20$  The FCC specified emission limits were calculated according the EUT operating frequency and obtained by following linear interpolation equations:

(a) For fundamental frequency:

$$f_{EUT} : \text{EUT Operating Frequency Emission Limit (uV/m)}$$

$$= [f_{EUT}(\text{MHz}) - 260(\text{MHz})] \times \frac{12500(\text{uV/m}) - 3750(\text{uV/m})}{470(\text{MHz}) - 260(\text{MHz})} + 3750(\text{uV/m})$$

(b) For spurious frequencies:

$$f_{EUT} : \text{EUT Operating Frequency Emission Limit (uV/m)}$$

$$= [f_{EUT}(\text{MHz}) - 260(\text{MHz})] \times \frac{1250(\text{uV/m}) - 375(\text{uV/m})}{470(\text{MHz}) - 260(\text{MHz})} + 375(\text{uV/m})$$

Other emissions radiated outside of the specified frequency bands, except for harmonics, shall be attenuated by at least 20 dB below the level of the fundamental or comply with the radiated emissions limits specified in section 15.209(a) limit in the table below has to be followed..

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission level (dBuV/m)=20log Emission level (uV/m).

| FCC Part15 (15.231) , Subpart C |                                   |                                         |
|---------------------------------|-----------------------------------|-----------------------------------------|
| Fundamental Frequency           | Field Strength<br>Of Fundamental  | Field Strength of Spurious<br>Emissions |
| 433.92MHz                       | AV:80.82 dBuV/m at 3m<br>distance | AV:60.82 dBuV/m at 3m<br>distance       |
|                                 | PK:100.82dBuV/m at 3m<br>distance | PK:80.82 dBuV/m at 3m<br>distance       |

According to FCC Part15.205, Restricted bands

| MHz               | MHz                 | MHz           | GHz         |
|-------------------|---------------------|---------------|-------------|
| 0.090-0.110       | 16.42-16.423        | 399.9-410     | 4.5-5.15    |
| 10.495-0.505      | 16.69475-16.69525   | 608-614       | 5.35-5.46   |
| 2.1735-2.1905     | 16.80425-16.80475   | 960-1240      | 7.25-7.75   |
| 4.125-4.128       | 25.5-25.67          | 1300-1427     | 8.025-8.5   |
| 4.17725-4.17775   | 37.5-38.25          | 1435-1626.5   | 9.0-9.2     |
| 4.20725-4.20775   | 73-74.6             | 1645.5-1646.5 | 9.3-9.5     |
| 6.215-6.218       | 74.8-75.2           | 1660-1710     | 10.6-12.7   |
| 6.26775-6.26825   | 123-138             | 2200-2300     | 14.47-14.5  |
| 8.291-8.294       | 149.9-150.05        | 2310-2390     | 15.35-16.2  |
| 8.362-8.366       | 156.52475-156.52525 | 2483.5-2500   | 17.7-21.4   |
| 8.37625-8.38675   | 156.7-156.9         | 2690-2900     | 22.01-23.12 |
| 8.41425-8.41475   | 162.0125-167.17     | 3260-3267     | 23.6-24.0   |
| 12.29-12.293      | 167.72-173.2        | 3332-3339     | 31.2-31.8   |
| 12.51975-12.52025 | 240-285             | 3345.8-3358   | 36.43-36.5  |
| 12.57675-12.57725 | 322-335.4           | 3600-4400     | (2)         |
| 13.36-13.41       |                     |               |             |

According to FCC Part15.209, the level of any transmitter spurious emission in Restricted bands shall not exceed the level of the emission specified in the following table

| Restricted Frequency(MHz) | Field Strength (μV/m) | Field Strength (dBμV/m) | Measurement Distance |
|---------------------------|-----------------------|-------------------------|----------------------|
| 0.009-0.490               | 2400/F(KHz)           | 20 log (uV/m)           | 300                  |
| 0.490-1.705               | 24000/F(KHz)          | 20 log (uV/m)           | 30                   |
| 1.705-30                  | 30                    | 29.5                    | 30                   |
| 30-88                     | 100                   | 40                      | 3                    |
| 88-216                    | 150                   | 43.5                    | 3                    |
| 216-960                   | 200                   | 46                      | 3                    |
| Above 960                 | 500                   | 54                      | 3                    |

### 8.3.3 Test Configuration

Test according to clause 7.2 radio frequency test setup 2

### 8.3.4 Test Procedure

This test is required for any spurious emission that falls in a Restricted Band, as defined in Section 15.205. It must be performed with the highest gain of each type of antenna proposed for use with the EUT. Use the following spectrum analyzer settings:

The EUT was placed on a turn table which is 0.8m above ground plane.

Maximum procedure was performed on the highest emissions to ensure EUT compliance.

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for  $f \geq 1$  GHz(1GHz to 6GHz), 100 kHz for  $f < 1$  GHz(30MHz to 1GHz), 200Hz for  $f < 150$  KHz(9KHz to 150KHz), 9KHz for  $f < 30$  MHz(150KHz to 30KHz)

VBW  $\geq$  RBW

Sweep = auto

Detector function = peak

Trace = max hold

Follow the guidelines in ANSI C63.10-2013 with respect to maximizing the emission by rotating the EUT, measuring the emission while the EUT is situated in three orthogonal planes (if appropriate), adjusting the measurement antenna height and polarization, etc. A pre-amp and a high pass filter are required for this test, in order to provide the measuring system with sufficient sensitivity. Allow the trace to stabilize. The peak reading of the emission, after being corrected by the antenna factor, cable loss, pre-amp gain, etc., is the peak field strength, which must comply with the limit specified in Section 15.35(b). Submit this data.

Now set the VBW to 10 Hz, while maintaining all of the other instrument settings. This peak level, once

corrected, must comply with the limit specified in Section 15.209. If the dwell time per channel of the hopping signal is less than 100 ms, then the reading obtained with the 10 Hz VBW may be further adjusted by a “duty cycle correction factor”, derived from  $20\log(\text{dwell time}/100 \text{ ms})$ , in an effort to demonstrate compliance with the 15.209 limit. Submit this data.

Repeat above procedures until all frequency measured was complete.

- Calculation of Average factor

The output field strengths of specification in accordance with the FCC rules specify measurements with an average detector. During the test, a spectrum analyzer incorporating a peak detector was used. Therefore, a reduction factor can be applied to the resultant peak signal level and compared to the limit for measurement instrumentation incorporating an average detector.

The duty cycle is measured in 100ms or the repetition cycle period, whichever is a shorter time frame, the duty cycle is measured by placing the spectrum analyzer to set zero span at 100kHz resolution bandwidth.

Averaging factor in dB =  $20\log(\text{duty cycle})$

Where the duty factor is calculated from following formula:

Duty cycle =  $33/236 = 13.98\%$

$20\log(\text{Duty cycle}) = -17.09 \text{ dB}$



Therefore, the averaging factor is -17.09 dB.

Repeat above procedures until all frequency measured was complete.

### 8.3.5 Test Results

|                    |           |
|--------------------|-----------|
| Temperature:       | 20° C     |
| Relative Humidity: | 58%       |
| ATM Pressure:      | 1011 mbar |

## ■ Duty cycle measure



■ Spurious Emission below 30MHz(9KHz to 30MHz)

| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission<br>Level(dBuV/m) |    | Limit 3m(dBuV/m) |    | Over(dB) |    |
|----------------|-----------------|---------------------------|----|------------------|----|----------|----|
|                |                 | PK                        | AV | PK               | AV | PK       | AV |
| --             | --              | --                        | -- | --               | -- | --       | -- |

Note: the amplitude of spurious emission that is attenuated by more than 20dB below the permissible limit has no need to be reported.

Distance extrapolation factor =  $40\log(\text{Specific distance/ test distance})$  (dB);


Limit line=Specific limits(dBuV) + distance extrapolation factor

■ Radiated spurious emission

Operation Mode: 433.92MHz


| Freq.<br>(MHz) | Ant.Pol.<br>H/V | Emission Level(dBuV/m) |            |       | Limit 3m(dBuV/m) |       | Margin(dB) |        |
|----------------|-----------------|------------------------|------------|-------|------------------|-------|------------|--------|
|                |                 | PK                     | Factor(dB) | AV    | PK               | AV    | PK         | AV     |
| 433.52         | V               | 74.89                  | -17.09     | 57.80 | 100.82           | 80.82 | -25.93     | -23.02 |
| 868.08         | V               | 29.07                  | -17.09     | 11.98 | 80.82            | 60.82 | -51.75     | -48.84 |
| 1301.22        | V               | 19.81                  | -17.09     | 2.72  | 74.00            | 54.00 | -54.19     | -51.28 |
| 1737.38        | V               | 31.09                  | -17.09     | 14.00 | 74.00            | 54.00 | -42.91     | -40.00 |
| 2646.88        | V               | 27.36                  | -17.09     | 10.27 | 74.00            | 54.00 | -46.64     | -43.73 |
| 3121.81        | V               | 30.36                  | -17.09     | 13.27 | 74.00            | 54.00 | -43.64     | -40.73 |
| 3471.38        | V               | 32.79                  | -17.09     | 15.70 | 74.00            | 54.00 | -41.21     | -38.30 |
| 4339.44        | V               | 41.71                  | -17.09     | 24.62 | 74.00            | 54.00 | -32.29     | -29.38 |
| 433.52         | H               | 85.11                  | -17.09     | 68.02 | 100.82           | 80.82 | -15.83     | -12.80 |
| 868.08         | H               | 37.86                  | -17.09     | 20.77 | 80.82            | 60.82 | -22.96     | -40.05 |
| 1302.28        | H               | 25.00                  | -17.09     | 7.91  | 74.00            | 54.00 | -49.00     | -46.09 |
| 1737.38        | H               | 33.43                  | -17.09     | 16.34 | 74.00            | 54.00 | -40.57     | -37.66 |
| 3037.88        | H               | 38.39                  | -17.09     | 21.30 | 74.00            | 54.00 | -35.61     | -32.70 |
| 3471.38        | H               | 38.03                  | -17.09     | 20.94 | 74.00            | 54.00 | -35.97     | -33.06 |
| 3905.94        | H               | 36.39                  | -17.09     | 19.30 | 74.00            | 54.00 | -37.61     | -34.70 |
| 4339.44        | H               | 46.09                  | -17.09     | 29.00 | 74.00            | 54.00 | -27.91     | -25.00 |

| Project Information |                      |           |              |
|---------------------|----------------------|-----------|--------------|
| Mode:               | TX                   | Voltage:  | AC 120V/60Hz |
| Environment:        | Temp: 17°C; Humi:64% | Engineer: | Lucas Xu     |



| Freq. (MHz) | Reading (dBμV) | Meas. (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) | Det. | Height (cm) | Pol. | Turn table (deg) | Corr. (dB) | Verdict |
|-------------|----------------|----------------|----------------|-----------------|------|-------------|------|------------------|------------|---------|
| 31.94       | 59.09          | 28.35          | 40.00          | 11.65           | QPK  | 100.0       | V    | 0.0              | -30.74     | PASS    |
| 53.28       | 49.65          | 21.11          | 40.00          | 18.89           | QPK  | 100.0       | V    | 0.0              | -28.54     | PASS    |
| 704.15      | 54.05          | 33.23          | 46.00          | 12.77           | QPK  | 100.0       | V    | 0.0              | -20.82     | PASS    |
| 722.58      | 50.41          | 29.88          | 46.00          | 16.12           | QPK  | 100.0       | V    | 0.0              | -20.53     | PASS    |

| Project Information |                      |           |              |
|---------------------|----------------------|-----------|--------------|
| Mode:               | TX                   | Voltage:  | AC 120V/60Hz |
| Environment:        | Temp: 17°C; Humi:64% | Engineer: | Lucas Xu     |



| Freq. (MHz) | Reading (dBμV) | Meas. (dBμV/m) | Limit (dBμV/m) | Margin (dBμV/m) | Det. | Height (cm) | Pol. | Turn table (deg) | Corr. (dB) | Verdict |
|-------------|----------------|----------------|----------------|-----------------|------|-------------|------|------------------|------------|---------|
| 44.55       | 45.84          | 17.70          | 40.00          | 22.3            | QPK  | 100.0       | H    | 360.0            | -28.14     | PASS    |
| 56.19       | 46.24          | 17.26          | 40.00          | 22.74           | QPK  | 100.0       | H    | 360.0            | -28.98     | PASS    |
| 181.32      | 60.47          | 27.92          | 43.50          | 15.58           | QPK  | 100.0       | H    | 360.0            | -32.55     | PASS    |
| 224.00      | 56.75          | 25.91          | 46.00          | 20.09           | QPK  | 100.0       | H    | 360.0            | -30.84     | PASS    |

## 8.4 TRANSMISSION REQUIREMEN

Applicable Standard

According to FCC Part 15.231(a),

Conformance Limit

- 1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.
- 2) A transmitter activated automatically shall cease transmission within 5 seconds after activation.
- 3) Periodic transmissions at regular predetermined intervals are not permitted. However, polling or supervision transmissions, including data, to determine system integrity of transmitters used in security or safety applications are allowed if the total duration of transmissions does not exceed more than two seconds per hour for each transmitter. There is no limit on the number of individual transmissions, provided the total transmission time does not exceed two seconds per hour.

Test Configuration

Test according to clause 7.1 radio frequency test setup 2

Test Procedure

The following table is the setting of spectrum analyzer.

|                   |          |
|-------------------|----------|
| Spectrum analyzer | Setting  |
| Attenuation       | Auto     |
| Span Frequency    | 0Hz      |
| RB                | 100 kHz  |
| VB                | 300 kHz  |
| Detector          | Peak     |
| Trace             | Max hold |
| Sweep Time        | 10S      |

- a. The transmitter output (antenna port) was connected to the spectrum analyzer.
- b. Set RBW of spectrum analyzer to 100 kHz and VBW to 300 kHz, Set Detector to Peak, Trace to Max Hold.
- c. Set the span to 0Hz and the sweep time to 10s and record the value.

Test Results

|                    |           |
|--------------------|-----------|
| Temperature:       | 20° C     |
| Relative Humidity: | 58%       |
| ATM Pressure:      | 1011 mbar |

| Frequency.(MHz) | Limit (s) | Verdict |
|-----------------|-----------|---------|
| 433.92          | <5        | PASS    |



## 8.5 CONDUCTED EMISSIONS TEST

### 8.5.1 Applicable Standard

According to FCC Part 15.207(a)

### 8.5.2 Conformance Limit

| Frequency(MHz) | Conducted Emission Limit |         |
|----------------|--------------------------|---------|
|                | Quasi-peak               | Average |
| 0.15-0.5       | 66-56                    | 56-46   |
| 0.5-5.0        | 56                       | 46      |
| 5.0-30.0       | 60                       | 50      |

Note: 1. The lower limit shall apply at the transition frequencies  
2. The limit decreases in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 8.5.3 Test Configuration

Test according to clause 7.3conducted emission test setup

### 8.5.4 Test Procedure

The EUT was placed on a table which is 0.8m above ground plane.  
Maximum procedure was performed on the highest emissions to ensure EUT compliance.  
Repeat above procedures until all frequency measured were complete.

### 8.5.5 Test Results

N/A

EUT power supply is 3V battery

## 8.6 ANTENNA APPLICATION

### 8.6.1 Antenna Requirement

| Standard           | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FCC CRF Part15.203 | An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of §15.211, §15.213, §15.217, §15.219, or §15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with §15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded. |

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 8.6.2 Result

Pass

The EUT has 1 antenna: a Spring Antenna for 433.92MHz TX model, the gain is 0.0 dBi;

Note:

- ☒ Antenna uses a permanently attached antenna which is not replaceable.
- ☐ Not using a standard antenna jack or electrical connector for antenna replacement
- ☐ The antenna has to be professionally installed (please provide method of installation)

Which in accordance to section 15.203, please refer to the internal photos.

\*\*\* End of Report \*\*\*

## 声 明 Statement

1. 本报告无授权批准人签字及“检验报告专用章”无效;  
This report will be void without authorized signature or special seal for testing report.
2. 未经许可本报告不得部分复制;  
This report shall not be copied partly without authorization.
3. 本报告的检测结果仅对送测样品有效, 委托方对样品的代表性和资料的真实性负责;  
The test results or observations are applicable only to tested sample. Client shall be responsible for representativeness of the sample and authenticity of the material.
4. 本检测报告中检测项目标注有特殊符号则该项目不在资质认定范围内, 仅作为客户委托、科研、教学或内部质量控制等目的使用;  
The observations or tests with special mark fall outside the scope of accreditation, and are only used for purpose of commission, research, training, internal quality control etc.
5. 本检测报告以实测值进行符合性判定, 未考虑不确定度所带来的风险, 本实验室不承担相关责任, 特别约定、标准或规范中有明确规定的除外;  
The test results or observations are provided in accordance with measured value, without taking risks caused by uncertainty into account. Without explicit stipulation in special agreements, standards or regulations, EMTEK shall not assume any responsibility.
6. 对本检测报告若有异议, 请于收到报告之日起 20 日内提出;  
Objections shall be raised within 20 days from the date receiving the report.