



FCC ID: 2AQ8A-EKSWR1N
Report No.: TMWK2112001589KR

Page: 1 / 27
Rev.: 01

FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Enkore Smart Wall Reader Narrow

Model No.: EKS-WR1N

Trade Name: Pamex

Issued to

Pamex Inc.
4680 Vinita Court, Chino, CA, 91710, United States

Issued by

Compliance Certification Services Inc.
Wugu Laboratory
No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City, Taiwan. (R.O.C.)
Issued Date: January 26, 2022

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.

除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留90天。本報告未經本公司書面許可，不可部份複製。

This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <http://www.sgs.com.tw/Terms-and-Conditions> and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at <http://www.sgs.com.tw/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.



Report No.: TMWK2112001589KR

Page: 2 / 27

Rev.: 01

Revision History

Rev.	Issue Date	Revisions	Effect Page	Revised By
00	January 19, 2022	Initial Issue	ALL	Doris Chu
01	January 26, 2022	See the following Note Rev. (01)	P.7, P.10, P.26~P.27, A-3~A-4	Doris Chu

Rev. (01)

1. Added conduction data in section 7.4.

TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. EUT DESCRIPTION.....	5
3. TEST METHODOLOGY.....	6
3.1 EUT CONFIGURATION	6
3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS.....	6
3.3 DESCRIPTION OF TEST MODES	7
4. TEST SUMMARY.....	8
5. INSTRUMENT CALIBRATION.....	9
5.1 MEASURING INSTRUMENT CALIBRATION	9
5.2 MEASUREMENT EQUIPMENT USED	9
5.3 MEASUREMENT UNCERTAINTY	10
5.4 FACILITIES AND TEST LOCATION	10
6. SETUP OF EQUIPMENT UNDER TEST	11
6.1 SETUP CONFIGURATION OF EUT	11
6.2 SUPPORT EQUIPMENT	11
7. FCC PART 15.225 REQUIREMENTS	12
7.1 OCCUPIED BANDWIDTH(99%) AND 20 DB BANDWIDTH.....	12
7.2 FUNDAMENTAL AND RADIATED EMISSIONS	14
7.3 FREQUENCY STABILITY	23
7.4 POWERLINE CONDUCTED EMISSIONS.....	25
APPENDIX A PHOTOGRAPHS OF TEST SETUP	A-1

Report No.: TMWK2112001589KR

Page: 4 / 27

Rev.: 01

1. TEST RESULT CERTIFICATION

Applicant: Pamex Inc.
4680 Vinita Court, Chino, CA, 91710, United States

Manufacturer: ALZK Co., Ltd.
9F., No. 36, Sec. 3, Bade Rd., Songshan Dist., Taipei City,
Taiwan

Equipment Under Test: Enkore Smart Wall Reader Narrow

Trade Name: Pamex

Model No.: EKS-WR1N

Date of Test: December 29, 2021 ~ January 24, 2022


APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted
Statements of Conformity	
Determination of compliance is based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.	

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.10: 2013 and the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.225.

The test results of this report relate only to the tested sample identified in this report.

Approved by:



Sehni Hu
Supervisor

2. EUT DESCRIPTION

Product	Enkore Smart Wall Reader Narrow
Model No.	EKS-WR1N
Model Discrepancy	N/A
Trade	Pamex
Received Date	December 24, 2021
Power Supply	Power from Power supply. (12V)
Frequency Range	13.56MHz
Modulation Technique	ASK
Number of Channels	1 Channel
Antenna Requirement	Antenna type: Loop Antenna
HW Version	V0.0.2
SW Version	W1-DVT-003

Remark:

1. For more details, please refer to the User's manual of the EUT.
2. Disclaimer: Antenna information is provided by the applicant, test results of this report are applicable to the sample EUT received.

3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.10: 2013 and FCC CFR 47 Part 15.207, 15.209, 15.225.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

(a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

(b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.

3.3 DESCRIPTION OF TEST MODES

The EUT had been tested under engineering test mode condition and the EUT staying in continuous transmitting mode.

All modes and data rates were investigated and it was determined that ISO 14443A/B and ISO 18092 Type y, 106/212/424/848 kbps.

All data rates were investigated and it was determined that 106 Kbps was considered worst-case. Therefore, all testing was performed in 106 Kbps mode.

AC Power Line Conducted Emission	
Test Condition	AC Power line conducted emission for line and neutral
Power supply Mode	Mode 1: EUT power by Power Supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Radiated Emission Measurement Below 30M	
Test Condition	Radiated Emission Below 30M
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4
Worst Position	☐ Placed in fixed position. ☐ Placed in fixed position at X-Plane (E2-Plane) ☒ Placed in fixed position at Y-Plane (E1-Plane) ☐ Placed in fixed position at Z-Plane (H-Plane)

Radiated Emission Measurement Below 1G	
Test Condition	Radiated Emission Below 1G
Power supply Mode	Mode 1: EUT power by Power supply
Worst Mode	☒ Mode 1 ☐ Mode 2 ☐ Mode 3 ☐ Mode 4

Remark:

1. The worst mode was record in this test report.
2. EUT pre-scanned in three axis ,X,Y, Z and two polarity, for radiated measurement. The worst case(Y-Plane) were recorded in this report
3. AC power line conducted emission and for below 1G radiation emission were performed the EUT transmit at the highest output power channel as worse case.



Report No.: TMWK2112001589KR

Page: 8 / 27

Rev.: 01

4. TEST SUMMARY

FCC Standard Sec.	Chapter	Test Item	Result
15.203	2	Antenna Requirement	Pass
15.215	7.1	Occupied Bandwidth (99%) and 20dB Bandwidth	Pass
15.209 15.225	7.2	Radiated Emissions	Pass
15.225	7.3	Frequency Stability	Pass
15.207	7.4	AC Power-line Conducted Emission	Pass



Report No.: TMWK2112001589KR

Page: 9 / 27

Rev.: 01

5. INSTRUMENT CALIBRATION

5.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

5.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

RF Conducted Test Site					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
EXA Signal Analyzer	KEYSIGHT	N9010B	MY55460167	05/25/2021	05/24/2022
DC Power Supplies	GW Instek	SPS-3610	GPE880163	12/21/2021	12/20/2022
Thermostatic/Humidity Chamber	GWINSTEK	GTC-288MH-CC	TH160402	05/10/2021	05/09/2022
Loop Ant	COM-POWER	AL-130	121051	04/07/2021	04/06/2022
Coaxial Cable	Woken	WC12	CC003	06/28/2021	06/27/2022
Software	Radio Test Software				

3M 966 Chamber Test Site					
Equipment	Manufacturer	Model	S/N	Cal Date	Cal Due
Bilog Antenna	Sunol Sciences	JB3	A030105	07/19/2021	07/18/2022
Coaxial Cable	HUBER SUHNER	SUCOFLEX 104PEA	20995	02/24/2021	02/23/2022
Digital Thermo-Hygro Meter	WISEWIND	1206	D07	12/28/2021	12/27/2022
Loop Ant	COM-POWER	AL-130	121051	04/07/2021	04/06/2022
Pre-Amplifier	EMEC	EM330	060609	02/24/2021	02/23/2022
Spectrum Analyzer	Agilent	E4446A	US42510268	09/23/2021	09/22/2022
DC Power Supplies	GW Instek	SPS-3610	GPE880163	12/21/2021	12/20/2022
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R	N.C.R
Turn Table	CCS	CC-T-1F	N/A	N.C.R	N.C.R
Software	e3 6.11-20180413				

Report No.: TMWK2112001589KR

Page: 10 / 27

Rev.: 01

Conducted Emission Room					
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Date	Calibration Due
CABLE	EMCI	CFD300-NL	CERF	06/28/2021	06/27/2022
EMI Test Receiver	R&S	ESCI	100064	07/05/2021	07/04/2022
LISN	SCHAFFNER	NNB 41	03/10013	02/02/2021	02/01/2022
DC Power Supplies	GW Instek	SPS-3610	GPE880163	12/21/2021	12/20/2022
Software	EZ-EMC(CCS-3A1-CE-WUGU)				

Remark:

1. Each piece of equipment is scheduled for calibration once a year.
2. N.C.R. = No Calibration Request.

5.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
AC Powerline Conducted Emission	+/- 1.2575
Emission bandwidth, 6dB bandwidth	+/- 0.0014
RF output power, conducted	+/- 1.14
Power density, conducted	+/- 1.40
3M Semi Anechoic Chamber / 9kHz-30MHz	+/- 2.30
3M Semi Anechoic Chamber / 30 MHz ~1 GHz (Horizontally)	+/- 3.91
3M Semi Anechoic Chamber / 30 MHz ~1 GHz (Vertically)	+/- 4.57

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

5.4 FACILITIES AND TEST LOCATION

All measurement facilities used to collect the measurement data are located at No.11, Wugong 6th Rd., Wugu Dist., New Taipei City, Taiwan. (R.O.C.)

CAB identifier: TW1309

Test site	Test Engineer	Remark
AC Conduction Room	Jack Chen	-
Radiation	Ray Li	-
RF Conducted	Lance Chen	-

Remark: The lab has been recognized as the FCC accredited lab under the KDB 974614 D01 and is listed in the FCC public Access Link (PAL) database, FCC Registration No. :444940, the FCC Designation No.:TW1309

6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix A for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT


No.	Device Type	Brand	Model	Series No.	FCC ID
1	DC Power Source	GWINSTEK	SPS-3610	N/A	N/A

Remark:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

7. FCC PART 15.225 REQUIREMENTS

7.1 OCCUPIED BANDWIDTH(99%) AND 20 DB BANDWIDTH TEST CONFIGURATION



TEST PROCEDURE

1. Place the EUT on the table and set it in the transmitting mode.
2. Remove the antenna from the EUT and then connect a low loss RF cable from the antenna port to the spectrum analyzer.
3. Set the spectrum analyzer as RBW & VBW (RBW) shall be in the range of 1% to 5% of the actual occupied / x dB bandwidth (VBW) shall not be smaller than three times the RBW value.
4. Record the max. reading.

TEST RESULTS

No non-compliance noted.

Temperature: 18.4°C

Humidity: 48% RH

Tested by: Jack Chen

Test date: January 12, 2022

Test Condition	Frequency(MHz)	Occupied Bandwidth 99% (kHz)	20 dB Bandwidth (kHz)
NFC	13.56	1.078	0.297



Report No.: TMWK2112001589KR

Page: 13 / 27
Rev.: 01

Test Plot

20 dB Bandwidth & Occupied Bandwidth 99%



7.2 FUNDAMENTAL AND RADIATED EMISSIONS

LIMIT

According to §15.225

- (a) The field strength of any emissions within the band 13.553 – 13.567 MHz shall not exceed 15,848 microvolts / meter at 30 meters.
- (b) Within the bands 13.410 – 13.553 MHz and 13.567 -13.710 MHz, the field strength of any emissions shall not exceed 334 microvolts / meter at 30 meters.
- (c) Within the bands 13.110 – 13.410 MHz and 13.710 – 14.010 MHz the field strength of any emissions shall not exceed 106 microvolts / meter at 30 meters.
- (d) The field strength of any emissions appearing outside of the 13.110 – 14.010 MHz and shall not exceed the general radiated emission limits in §15.209.

According to §15.225, except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency (MHz)	Field Strength (µV/m at meter)	Measurement Distance (meter)
0.009 – 0.490	2400 / F (kHz)	300
0.490 – 1.705	24000 / F (kHz)	30
1.705 – 30.0	30	30
30 - 88	100**	3
88-216	150**	3
216-960	200**	3
Above 960	500	3

** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


Report No.: TMWK2112001589KR

Test Configuration

9kHz ~ 30MHz



30MHz ~ 1GHz



TEST PROCEDURE

For 9kHz ~ 30MHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, The underside of the loop should be 1 m above the ground, then find the maximum emissions
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. Set the spectrum analyzer in the following setting as:
9KHz-150KHz: RBW=200Hz / VBW=1kHz / Sweep=AUTO
150KHz-30MHz: RBW=10kHz / VBW=30kHz / Sweep=AUTO
6. Repeat above procedures until the measurements for all frequencies are complete.

For 30MHz ~ 1GHz

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

Remark :

Although these tests were performed other than open area test site, adequate comparison measurements were confirmed against 30 m open are test site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field based on KDB 414788.

Report No.: TMWK2112001589KR

Test Result of Mask

Operation Mode: TX mode

Test Date:

January 6, 2022

Temperature: 21.4°C


Tested by:

Ray Li

Humidity: 58 % RH

Polarity:

Ver.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.355	Peak	19.30	15.27	34.57	80.50	-45.93
2	13.553	Peak	41.43	15.27	56.70	90.47	-33.77
3	13.560	Peak	53.97	15.27	69.24	124.00	-54.76
4	13.567	Peak	46.41	15.27	61.68	90.47	-28.79
5	13.773	Peak	27.06	15.27	42.33	80.50	-38.17

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
4. 9kHz to 490kHz Limit(@3m) = 2400(F/kHz)+ 40*Log (300 meters/3 meters)
490kHz to 1.705MHz Limit (@3m) = 2400(F/kHz)+ 40*Log (30 meters/3 meters)
1.705MHz to 30MHz Limit (@3m) = 30 + 40*Log (30 meters/3 meters)

Report No.: TMWK2112001589KR

Test Result of Mask

Operation Mode: TX mode

Test Date:

January 6, 2022

Temperature: 21.4°C


Tested by:

Ray Li

Humidity: 58 % RH

Polarity:

Hor.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.350	Peak	24.81	15.27	40.08	80.50	-40.42
2	13.553	Peak	45.96	15.27	61.23	90.47	-29.24
3	13.560	Peak	58.53	15.27	73.80	124.00	-50.20
4	13.567	Peak	50.98	15.27	66.25	90.47	-24.22
5	13.776	Peak	28.97	15.27	44.24	80.50	-36.26

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
4. 9kHz to 490kHz Limit(@3m) = 2400(F/kHz)+ 40*Log (300 meters/3 meters)
490kHz to 1.705MHz Limit (@3m) = 2400(F/kHz)+ 40*Log (30 meters/3 meters)
1.705MHz to 30MHz Limit (@3m) = 30 + 40*Log (30 meters/3 meters)

Report No.: TMWK2112001589KR

Page: 19 / 27

Rev.: 01

Test Result of Mask

Operation Mode: TX mode


Test Date: January 6, 2022

Temperature: 21.4°C

Tested by: Ray Li

Humidity: 58 % RH

Polarity: Ground



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB
1	13.356	Peak	14.12	15.27	29.39	80.50	-51.11
2	13.553	Peak	33.91	15.27	49.18	90.47	-41.29
3	13.560	Peak	46.45	15.27	61.72	124.00	-62.28
4	13.567	Peak	38.90	15.27	54.17	90.47	-36.30
5	13.778	Peak	15.52	15.27	30.79	80.50	-49.71

Remark:

1. Radiated emissions measured were made with an instrument using peak/quasi-peak/average detector mode.
2. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with "N/A" remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
3. Margin (dB) = Result (dBuV/m) – Limit (dBuV/m).
4. 9kHz to 490kHz Limit(@3m) = 2400(F/kHz)+ 40*Log (300 meters/3 meters)
490kHz to 1.705MHz Limit (@3m) = 2400(F/kHz)+ 40*Log (30 meters/3 meters)
1.705MHz to 30MHz Limit (@3m) = 30 + 40*Log (30 meters/3 meters)

Report No.: TMWK2112001589KR

9kHz ~ 30MHz

Operation Mode: TX mode


Test Date: January 4, 2022

Temperature: 21.4°C

Tested by: Ray Li

Humidity: 58 % RH

Polarity: Hor.



No.	Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBuV	Factor dB	Actual FS dBuV/m	Limit @3m dBuV/m	Margin dB
1	1.06	Peak	29.94	13.70	43.64	67.11	-23.47
2	6.85	Peak	26.15	14.95	41.10	69.54	-28.44
3	13.30	Peak	12.87	15.28	28.15	69.54	-41.39
4	14.02	Peak	19.46	15.26	34.72	69.54	-34.82
5	23.85	Peak	19.58	14.37	33.95	69.54	-35.59
6	24.30	Peak	20.04	14.28	34.32	69.54	-35.22

Remark:

- 9kHz to 490kHz Limit(@3m) = $2400(F/\text{kHz}) + 40 \cdot \log(300 \text{ meters}/3 \text{ meters})$
490kHz to 1.705MHz Limit (@3m) = $2400(F/\text{kHz}) + 40 \cdot \log(30 \text{ meters}/3 \text{ meters})$
1.705MHz to 30MHz Limit (@3m) = $30 + 40 \cdot \log(30 \text{ meters}/3 \text{ meters})$

Report No.: TMWK2112001589KR

Page: 21 / 27
Rev.: 01

30MHz ~ 1GHz

Operation Mode: TX mode **Test Date:** January 4, 2022
Temperature: 21.4°C **Tested by:** Ray Li
Humidity: 58 % RH **Polarity:** Ver. / Hor.


Freq. MHz	Detector Mode PK/QP/AV	Spectrum Reading Level dBμV	Factor dB	Actual FS dBμV/m	Limit @3m dBμV/m	Margin dB	Polarity
59.10	Peak	54.20	-15.96	38.24	40.00	-1.76	V
173.56	Peak	41.69	-11.29	30.40	43.50	-13.10	V
316.15	Peak	37.68	-8.25	29.43	46.00	-16.57	V
419.94	Peak	38.22	-5.26	32.96	46.00	-13.04	V
827.34	Peak	29.80	1.92	31.72	46.00	-14.28	V
959.26	Peak	26.58	3.83	30.41	46.00	-15.59	V
72.68	Peak	45.96	-15.21	30.75	40.00	-9.25	H
139.61	Peak	44.26	-9.90	34.36	43.50	-9.14	H
275.41	Peak	43.62	-8.88	34.74	46.00	-11.26	H
419.94	Peak	37.53	-5.26	32.27	46.00	-13.73	H
828.31	Peak	28.57	1.95	30.52	46.00	-15.48	H
959.26	Peak	28.49	3.83	32.32	46.00	-13.68	H

Report No.: TMWK2112001589KR


Page: 22 / 27

Rev.: 01

Vertical



Horizontal



7.3 FREQUENCY STABILITY


LIMIT

According to §15.225(e)

The frequency tolerance of the carrier signal shall be maintained within $\pm 0.01\%$ of the operating frequency over a temperature variation of -20 degrees to $+50$ degrees C at normal supply voltage, and for a variation in the primary supply voltage from 85% to 115% of the rated supply voltage at a temperature of 20 degrees C. For battery operated equipment, the equipment tests shall be performed using a new battery.

Test Configuration

Temperature and Voltage Measurement (under normal and extreme test conditions)



TEST PROCEDURE

1. Turn the EUT off, and place it inside the environmental temperature chamber.
2. Set the temperature control on the chamber to the highest specified in the regulatory requirements for the type of device and allow the oscillator heater and the chamber temperature to stabilize.
3. Set the spectrum analyzer as RBW=1kHz, VBW = RBW, Span = 200kHz, Sweep = auto.
4. Turn the EUT on and record the operating frequency at startup and two, five, and ten minutes after the EUT is energized.
5. Switch off the EUT and Lower the chamber temperature by not more than 10°C and allow the temperature inside the chamber to stabilize.
6. Mark the peak frequency and measure the frequency tolerance using frequency counter function.
7. Repeat step 4 through step 6 down to the lowest specified temperature.

Report No.: TMWK2112001589KR

Page: 24 / 27
Rev.: 01

TEST RESULTS

No non-compliance noted.

Temperature: 19.4°C

Humidity: 63% RH

Tested by: Lance Chen

Test date: December 29, 2021

TEST DATA

Condition			Frequency Error (ppm)										Limit (ppm)	Result
Temperature	Modulation Mode	Test Freq.	0 min	2 min	5 min	10 min	0 min	2 min	5 min	10 min				
Normal														
T _{20°C} V _{max}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass		
T _{20°C} V _{min}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
Extreme														
T _{50°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00	100	Pass		
T _{40°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{30°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{20°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{10°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{0°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{-10°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		
T _{-20°C} V _{nom}	ASK	13.56	13.560000	13.560000	13.560000	13.560000	0.00	0.00	0.00	0.00		Pass		

Remark: V_{nom}: 12Vdc
V_{max}: 13.8Vdc
V_{min}: 10.2Vdc

7.4 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

Report No.: TMWK2112001589KR

Page: 26 / 27
Rev.: 01

TEST RESULTS

Operation Mode: Mode 1

Test Date: January 24, 2022

Temperature: 20.1°C

Tested by: Jack Chen

Humidity: 63% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB/m)	QP Result (dBuV/m)	AV Result (dBuV/m)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.1940	35.04	31.04	10.29	45.33	41.33	63.86	53.86	-18.53	-12.53	L1
0.2620	32.15	27.80	10.29	42.44	38.09	61.37	51.37	-18.93	-13.28	L1
0.2940	32.36	29.53	10.29	42.65	39.82	60.41	50.41	-17.76	-10.59	L1
0.3900	33.85	31.74	10.29	44.14	42.03	58.06	48.06	-13.92	-6.03	L1
0.4580	26.10	17.77	10.29	36.39	28.06	56.73	46.73	-20.34	-18.67	L1
13.5620	46.92	30.00	10.46	57.38	40.46	60.00	50.00	-2.62	-9.54	L1
0.1580	28.19	19.43	10.29	38.48	29.72	65.57	55.57	-27.09	-25.85	N
0.1980	35.63	30.90	10.29	45.92	41.19	63.69	53.69	-17.77	-12.50	N
0.2620	30.61	26.06	10.29	40.90	36.35	61.37	51.37	-20.47	-15.02	N
0.2940	32.37	29.50	10.29	42.66	39.79	60.41	50.41	-17.75	-10.62	N
0.3900	33.41	31.66	10.29	43.70	41.95	58.06	48.06	-14.36	-6.11	N
13.5660	40.70	24.30	10.46	51.16	34.76	60.00	50.00	-8.84	-15.24	N


Remark:

1. The measuring frequencies range between 0.15 MHz and 30 MHz.
2. The emissions measured in the frequency range between 0.15 MHz and 30MHz were made with an instrument using Quasi-peak detector and Average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10kHz. The IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9kHz.
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)
5. "-" means Quasi-peak reading value also meets average limit and measurement with the average detector is unnecessary.
6. Correction factor = LISN loss + Cable loss.


Report No.: TMWK2112001589KR

Test Plots

Conducted emissions (Line 1)



Conducted emissions (N)



- End of Test Report -