

RF Exposure Report

Project Number: 4347362

Proposal Number: 5533

Report Number: 4347362EMC03

Revision Level: 0

Client: Enovate Medical, LLC

Equipment Under Test: Bluetooth Low Energy Circuit

Model Number: P0000457

FCC ID: 2AQ9D-P0000457

Applicable Standards: 47 CFR §§ 2.1093

FCC KDB 447498 D01 General RF Exposure Guidance v06

Report issued on: 26 October 2020

Result: Exempt from SAR testing

Prepared by:



Martin Taylor, RF/EMC Engineer

Reviewed by:



Stephen Whalen, EMC Lab Manager

Remarks: This report details the results of the testing carried out on one sample, the results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This document is issued by the Company under its General Conditions of Service accessible at <http://www.sgs.com/en/Terms-and-Conditions.aspx>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein.

Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	CLIENT INFORMATION.....	3
1.2	TEST LABORATORY	3
1.3	GENERAL INFORMATION OF EUT.....	3
2	SAR EXCLUSION CALCULATIONS	4
4	REVISION HISTORY	5

1 General Information

1.1 Client Information

Name: Enovate Medical, LLC
Address: 1152 Park Avenue
City, State, Zip, Country: Murfreesboro, TN 37129, USA

1.2 Test Laboratory

Name: SGS North America, Inc.
Address: 620 Old Peachtree Road NW, Suite 100
City, State, Zip, Country: Suwanee, GA 30024, USA

Accrediting Body: A2LA
Type of lab: Testing Laboratory
Certificate Number: 3212.01

1.3 General Information of EUT

Type of Product (PMN): Bluetooth Low Energy Circuit
Model Number (HVIN): P0000457
Firmware Version (FVIN): SoftDevice 5.0.0
Host Marketing Name (HMN): Medical Cart
Serial Number: 165

FCC ID: 2AQ9D-P0000457

Frequency Range: 2402-2480MHz
Data Modes: Bluetooth Low Energy
Antenna: External Antenna (0.7dB)

Rated Voltage: 13.5Vdc
Test Voltage: 13.5Vdc

Sample Received Date: 24 July 2018
Dates of testing: 06-11 September 2018

2 SAR Exclusion Calculations

The highest output power in conjunction with the upper frequency boundary has been used to demonstrate compliance.

The distance from the BLE antenna to the closest exterior point of the Medical Cart (host) has been used as the minimum separation distance to demonstrate compliance.

This exterior point of the host is considered an Extremity application.

447498 D01 General RF Exposure Guidance v06

SAR test exclusion calculations

Section 4.3: General SAR test exclusion guidance / Section 4.3.1: Standalone SAR test exclusion considerations

	Input	Select Units
Max Power:	3.43	dBm
Min separation distance:	20	mm
Frequency, f:	2480	MHz

Value reference Number	Values used for Calculation	Reference number definition
v1	2 mW	[max. power of channel, including tune-up tolerance, mW] 'Rounded to nearest mW'
v2	20 mm	[min. test separation distance, mm] 'Rounded to nearest mm'
v3	1.575	[√f(GHz)]

- a) For 100 MHz to 6 GHz and test separation distances ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR, and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

1g Exclusion Threshold:	38.1	mW	$\leq 3 \cdot v2 / v3$
10g Exclusion Threshold:	95.3	mW	$\leq 7.5 \cdot v2 / v3$

Conclusions:	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Body applications
	The EUT max power is BELOW the threshold. SAR Testing is NOT required for Extremity applications

4 Revision History

Revision Level	Description of changes	Revision Date
Draft	--	26 October 2020
0	Initial Release	26 October 2020