


Test report No:  
2610293R.702B

## SAR Exemption Evaluation Report

|                                                |                                                                                                                       |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------|
| Product Name                                   | Wireless CR_Module                                                                                                    |
| Model and /or type reference                   | uCORDM                                                                                                                |
| Trademark                                      |                                      |
| FCC ID                                         | 2AQ9V-MS88SFA                                                                                                         |
| Applicant's name / address                     | Shanghai United Imaging Healthcare Co., Ltd.<br>No.2258 Chengbei Road, Jiading District,<br>Shanghai,201807,P.R.China |
| Test method requested, standard                | FCC 47CFR §2.1093                                                                                                     |
| Verdict Summary                                | IN COMPLIANCE                                                                                                         |
| Documented By<br>(name / position & signature) | Jun Xu/ Project Engineer<br>       |
| Approved by (name / position & signature)      | Frank He/Technical Manager<br>     |
| Date of issue                                  | 2026-02-06                                                                                                            |
| Report Version                                 | V1.0                                                                                                                  |
| Report template No                             | Template_FCC-MPE-RF-V1.0                                                                                              |

INDEX

|                                                     | page |
|-----------------------------------------------------|------|
| Competences and Guarantees.....                     | 3    |
| General conditions.....                             | 3    |
| Environmental conditions.....                       | 3    |
| Possible test case verdicts .....                   | 4    |
| Abbreviations .....                                 | 4    |
| Document History .....                              | 5    |
| Remarks and Comments .....                          | 5    |
| 1.1    General Description of the Item(s) .....     | 6    |
| 2.    RF Exposure Evaluation.....                   | 7    |
| 2.1.    Limits: KDB 447498 D04 .....                | 7    |
| 2.2.    Test Procedure .....                        | 10   |
| 2.3.    Test Result of RF Exposure Evaluation ..... | 10   |

## COMPETENCES AND GUARANTEES

DEKRA is a testing laboratory competent to carry out the tests described in this report.

In order to assure the traceability to other national and international laboratories, DEKRA has a calibration and maintenance program for its measurement equipment.

DEKRA guarantees the reliability of the data presented in this report, which is the result of the measurements and the tests performed to the item under test on the date and under the conditions stated in the report and it is based on the knowledge and technical facilities available at DEKRA at the time of performance of the test.

DEKRA is liable to the client for the maintenance of the confidentiality of all information related to the item under test and the results of the test.

The results presented in this Test Report apply only to the particular item under test established in this document.

**IMPORTANT:** No parts of this report may be reproduced or quoted out of context, in any form or by any means, except in full, without the previous written permission of DEKRA.

## GENERAL CONDITIONS

|                      |                                                                        |
|----------------------|------------------------------------------------------------------------|
| Test Location        | No. 99, Hongye Road, Suzhou Industrial Park Suzhou, 215006, P.R. China |
| Date(receive sample) | Nov. 28, 2025                                                          |
| Date (start test)    | Dec. 05, 2025                                                          |
| Date (finish test)   | Jan. 24, 2026                                                          |

1. This report is only referred to the item that has undergone the test.
2. This report does not constitute or imply on its own an approval of the product by the Certification Bodies or Competent Authorities.
3. This document is only valid if complete; no partial reproduction can be made without previous written permission of DEKRA.
4. This test report cannot be used partially or in full for publicity and/or promotional purposes without previous written permission of DEKRA.

## ENVIRONMENTAL CONDITIONS

The climatic conditions during the tests are within the limits specified by the manufacturer for the operation of the EUT and the test equipment. The climatic conditions during the tests were within the following limits:

|                       |               |
|-----------------------|---------------|
| Ambient temperature   | 15 °C – 35 °C |
| Relative Humidity air | 30% - 60%     |

If explicitly required in the basic standard or applied product / product family standard the climatic values are recorded and documented separately in this test report.

## POSSIBLE TEST CASE VERDICTS

|                                         |                 |
|-----------------------------------------|-----------------|
| Test case does not apply to test object | N/A             |
| Test object does meet requirement       | P (Pass) / PASS |
| Test object does not meet requirement   | F (Fail) / FAIL |
| Not measured                            | N/M             |

## ABBREVIATIONS

For the purposes of the present document, the following abbreviations apply:

|       |                               |
|-------|-------------------------------|
| EUT   | : Equipment Under Test        |
| QP    | : Quasi-Peak                  |
| CAV   | : CISPR Average               |
| AV    | : Average                     |
| CDN   | : Coupling Decoupling Network |
| SAC   | : Semi-Anechoic Chamber       |
| OATS  | : Open Area Test Site         |
| BW    | : Bandwidth                   |
| AM    | : Amplitude Modulation        |
| PM    | : Pulse Modulation            |
| HCP   | : Horizontal Coupling Plane   |
| VCP   | : Vertical Coupling Plane     |
| $U_N$ | : Nominal voltage             |
| $T_x$ | : Transmitter                 |
| $R_x$ | : Receiver                    |
| N/A   | : Not Applicable              |
| N/M   | : Not Measured                |

## DOCUMENT HISTORY

| Report No.    | Version | Description              | Issued Date |
|---------------|---------|--------------------------|-------------|
| 2610293R.702B | V1.0    | Initial issue of report. | 2026-02-06  |
|               |         |                          |             |
|               |         |                          |             |
|               |         |                          |             |
|               |         |                          |             |
|               |         |                          |             |

## REMARKS AND COMMENTS

1. The equipment under test (EUT) does meet the essential requirements of the stated standard(s)/test(s).
2. These test results on a sample of the device are for the purpose of demonstrating Compliance with FCC 47CFR §2.1093.
3. The measurement result is considered in conformance with the requirement if it is within the prescribed limit, It is not necessary to account the uncertainty associated with the measurement result.
4. The test results relate only to the samples tested.
5. The test report shall not be reproduced without the written approval of DEKRA Testing and Certification (Suzhou) Co., Ltd.
6. This report will not be used for social proof function in China market.
7. DEKRA declines any responsibility with the following test data provided by customer that may affect the validity of result:
  - Chapter 1.1 General Description of the Item(s);

## 1.1 General Description of the Item(s)

|                                                                 |                                                                                   |    |
|-----------------------------------------------------------------|-----------------------------------------------------------------------------------|----|
| Product Name:                                                   | Wireless CR_Module                                                                |    |
| Model Name:                                                     | uCORDM                                                                            |    |
| Trademark.:                                                     |  |    |
| FCC ID:                                                         | 2AQ9V-MS88SFA                                                                     |    |
| Power Supply:                                                   | 3.7Vdc                                                                            |    |
| Hardware Version:                                               | V01                                                                               |    |
| Software Version:                                               | V01R00P00B05_20250925                                                             |    |
| Manufacturer:                                                   | Shanghai United Imaging Healthcare Co., Ltd.                                      |    |
| Manufacturer Address:                                           | No.2258 Chengbei Road, Jiading District, Shanghai,201807,P.R.China                |    |
| Test Matrix/ IMEI:                                              | RF Conducted                                                                      | #1 |
|                                                                 | RSE                                                                               | #2 |
| Wireless specification:                                         | 2.4G SRD                                                                          |    |
| Operating frequency range(s):                                   | 2410~2475MHz                                                                      |    |
| Antenna Type:                                                   | PCB Antenna                                                                       |    |
| Antenna Gain:                                                   | 2.83 dBi                                                                          |    |
| Note: The applicant declares that the EUT is a handheld device. |                                                                                   |    |

### Remark:

As above information is provided and confirmed by the applicant. DEKRA is not liable to the accuracy, suitability, reliability or/and integrity of the information.

## 2. RF Exposure Evaluation

### 2.1. Limits: KDB 447498 D04

#### B.2 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of § 1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1 mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph § 1.1307(b)(3)(ii)(A).

The 1 mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

#### B.3 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

**TABLE B.1—THRESHOLDS FOR SINGLE RF SOURCES  
SUBJECT TO ROUTINE ENVIRONMENTAL EVALUATION**

| RF Source<br>Frequency                                                                                                                   |   |              | Minimum Distance   |   |                    | Threshold<br>ERP |
|------------------------------------------------------------------------------------------------------------------------------------------|---|--------------|--------------------|---|--------------------|------------------|
| $f_L$ MHz                                                                                                                                |   | $f_H$<br>MHz | $\lambda_L / 2\pi$ |   | $\lambda_H / 2\pi$ | W                |
| 0.3                                                                                                                                      | — | 1.34         | 159 m              | — | 35.6 m             | $1,920 R^2$      |
| 1.34                                                                                                                                     | — | 30           | 35.6 m             | — | 1.6 m              | $3,450 R^2/f^2$  |
| 30                                                                                                                                       | — | 300          | 1.6 m              | — | 159 mm             | $3.83 R^2$       |
| 300                                                                                                                                      | — | 1,500        | 159 mm             | — | 31.8 mm            | $0.0128 R^2 f$   |
| 1,500                                                                                                                                    | — | 100,000      | 31.8 mm            | — | 0.5 mm             | $19.2 R^2$       |
| Subscripts L and H are low and high; $\lambda$ is wavelength.<br>From § 1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns. |   |              |                    |   |                    |                  |

The table applies to any RF source (i.e., single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least  $\lambda/2\pi$ . The thresholds are based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of § 1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in § 1.1310 is necessary if the ERP of the device is greater than ERP<sub>20cm</sub> in Formula (B.1) [repeated from § 2.1091(c)(1) and § 1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B. 1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of  $\lambda/4$  or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

## B.4 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of  $\lambda/4$ .

As for devices with antennas of length greater than  $\lambda/4$  where the gain is not well defined, but always less than that of a half-wave dipole (length  $\lambda/2$ ), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of § 1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold  $P_{th}$  (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive).  $P_{th}$  is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases}$$

where

$$x = -\log_{10} \left( \frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and ERP<sub>20cm</sub> is per Formula (B.1).

The example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance (mm) |    |    |    |     |     |     |     |     |     |     |
|-----------------|---------------|----|----|----|-----|-----|-----|-----|-----|-----|-----|
|                 |               | 5  | 10 | 15 | 20  | 25  | 30  | 35  | 40  | 45  | 50  |
|                 | 300           | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
|                 | 450           | 22 | 44 | 67 | 89  | 112 | 135 | 158 | 180 | 203 | 226 |
|                 | 835           | 9  | 25 | 44 | 66  | 90  | 116 | 145 | 175 | 207 | 240 |
|                 | 1900          | 3  | 12 | 26 | 44  | 66  | 92  | 122 | 157 | 195 | 236 |
|                 | 2450          | 3  | 10 | 22 | 38  | 59  | 83  | 111 | 143 | 179 | 219 |
|                 | 3600          | 2  | 8  | 18 | 32  | 49  | 71  | 96  | 125 | 158 | 195 |
|                 | 5800          | 1  | 6  | 14 | 25  | 40  | 58  | 80  | 106 | 136 | 169 |

## 2.2. Test Procedure

Software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

The temperature and related humidity: 18°C and 78% RH.

## 2.3. Test Result of RF Exposure Evaluation

### B.2 Blanket 1 mW Blanket Exemption

The tune-up tolerance is 0.5 dB, the maximum power we used to calculate RF exposure is 6.95 dBm.

| Wireless Configuration | Pmax  | Pmax | Limit | Verdict        |
|------------------------|-------|------|-------|----------------|
|                        | (dBm) | (mw) | (mw)  |                |
| SRD                    | 6.95  | 4.95 | 1     | Not applicable |

Note: Bluetooth does not comply with B.2 Blanket 1 mW Blanket Exemption, we use B.4 SAR-based Exemption.

### B.4 SAR-based Exemption

The tune-up tolerance is 0.5 dB, the maximum ERP power we used to calculate RF exposure is 3.40 dBm.

| Wireless Configuration | Exposure Condition | Pmax  | Pmax | Distance | Frequency (GHz) | Calculation Result | Stand-alone Test exclusion threshold | SAR Test |
|------------------------|--------------------|-------|------|----------|-----------------|--------------------|--------------------------------------|----------|
|                        |                    | (dBm) | (mw) |          |                 | (mw)               | (mw)                                 |          |
| SRD                    | Body               | 6.95  | 4.95 | 5.00     | 2.475           | 4.95               | 7.5                                  | No       |

Note : Threshold for no SAR evaluation in 5mm is 3mW. For limb-worn devices where the 10 gram value applies, the exemption limits for routine evaluation are multiplied by a factor of 2.5. Maximum Power is 4.95mW Conducted.

Maximum Conducted Power is 6.27dBm, Maximum ERP Power = Conducted + (Antenna Gain - 2.15dB) = 6.95dBm, Therefore Maximum Conducted Power is used when evaluating SAR exemption.

Conclusion: 2.4GHz SAR was not required.

\_\_\_\_\_ The End \_\_\_\_\_