



中国认可
国际互认
检测
TESTING
CNAS L6791

TEST REPORT

Applicant: Ugreen Group Limited
Address: UGREEN Building, Longcheng Industrial Park
Longguanxi Road, Longhua, ShenZhen, China
Equipment Type: UGREEN Wireless Keyboard
Model Name: KU004 (refer to section 2.3)
Brand Name: **UGREEN**
FCC ID: 2AQI5-35727
Test Standard: 47 CFR Part 15 Subpart C
(refer to section 3.1)
Sample Arrival Date: Jan. 11, 2024
Test Date: Jan. 12, 2024 - Jan. 24, 2024
Date of Issue: Jan. 29, 2024

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

**Tested by:** Julie Zhu**Checked by:** Ye Hongji**Approved by:** Hanson Lin

(Vice General Manager)

Revision History

Version	Issue Date	Revisions
<u>Rev. 01</u>	<u>Jan. 29, 2024</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION	4
1.1	Test Laboratory	4
1.2	Test Location	4
2	PRODUCT INFORMATION	5
2.1	Applicant Information	5
2.2	Manufacturer Information	5
2.3	General Description for Equipment under Test (EUT)	5
2.4	Technical Information	6
3	SUMMARY OF TEST RESULTS	7
3.1	Test Standards	7
3.2	Verdict	7
4	GENERAL TEST CONFIGURATIONS	8
4.1	Test Environments	8
4.2	Test Equipment List	8
4.3	Test Software List	8
4.4	Measurement Uncertainty	9
4.5	Description of Test Setup	9
4.6	Measurement Results Explanation Example	12
5	TEST ITEMS	13
5.1	Antenna Requirements	13
5.2	Number of Hopping Frequency	14
5.3	Peak Output Power	15
5.4	Occupied Bandwidth	17
5.5	Carrier Frequency Separation	20

5.6	Time of Occupancy (Dwell time)	22
5.7	Conducted Spurious Emission & Authorized-band band-edge.....	24
5.8	Conducted Emission.....	28
5.9	Radiated Spurious Emission	31
5.10	Band Edge (Restricted-band band-edge).....	41
ANNEX A	TEST SETUP PHOTOS	44
1	Radiated Test Photo	44
2	Conducted Test Photo	46
3	Conducted Emissions	47
ANNEX B	EUT EXTERNAL PHOTOS.....	48
ANNEX C	EUT INTERNAL PHOTOS.....	52

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	☒ Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	☐ 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Accreditation Certificate	The laboratory is a testing organization accredited by FCC as a accredited testing laboratory. The designation number is CN1196.

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	UGREEN Group Limited
Address	URGEEN Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, Guangdong 518109, China

2.2 Manufacturer Information

Manufacturer	UGREEN Group Limited
Address	URGEEN Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, Guangdong 518109, China

2.3 General Description for Equipment under Test (EUT)

EUT Name	UGREEN Wireless Keyboard
Model Name Under Test	KU004
Series Model Name	35727, 35728, 35729, 35730, 35731, 35732, 35733, 35734, 35735, 35736, 35737, 35738, 35739
Description of Model name differentiation	All models are same with electrical parameters and internal circuit structure, but only differ in model name. (this information provided by the applicant)
Hardware Version	N/A
Software Version	N/A
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.4 Technical Information

Network and Wireless connectivity	2.4G ISM Band
-----------------------------------	---------------

The requirement for the following technical information of the EUT was tested in this report:

Modulation Technology	FHSS
Modulation Type	GFSK
Product Type	☐ Mobile ☒ Portable ☐ Fix Location
Transfer Rate	1 Mbps
Frequency Range	The frequency range used is 2402 MHz – 2480 MHz; The frequency block is 2400 MHz to 2483.5 MHz.
Number of Channel	40
Tested Channel	Low channel (2402 MHz), Middle channel (2440 MHz), High channel (2480 MHz)
Antenna Type	PCB Antenna
Antenna Gain	-2.17 dBi
Adaptive or non-adaptive	Non-Adaptive
The Max RF Output power	-0.09 dBm

Channel List

Number	Frequency (MHz)	Number	Frequency (MHz)	Number	Frequency (MHz)
1	2402(Low)	15	2430	29	2458
2	2404	16	2432	30	2460
3	2406	17	2434	31	2462
4	2408	18	2436	32	2464
5	2410	19	2438	33	2466
6	2412	20	2440(Middle)	34	2468
7	2414	21	2442	35	2470
8	2416	22	2444	36	2472
9	2418	23	2446	37	2474
10	2420	24	2448	38	2476
11	2422	25	2450	39	2478
12	2424	26	2452	40	2480(High)
13	2426	27	2454	--	--
14	2428	28	2456	--	--

Note: The modulation is GFSK with FHSS, there are total 40 channels (frequency range is 2402-2480MHz, channel step is 2MHz, totally 40 channels). In this report, the equipment select the lowest, middle and highest channel from 40 channels, Which are 2402 MHz, 2440 MHz and 2480 MHz. The more information please refer to the manufacturer's instructions.

3 SUMMARY OF TEST RESULTS

3.1 Test Standards

No.	Identity	Document Title
1	47 CFR Part 15, Subpart C	Intentional radiators of radio frequency equipment
2	ANSI C63.10-2013	American National Standard for Testing Unlicensed Wireless Devices
3 ☆	KDB 558074 D01 15.247 Meas Guidance v05r02	Guidance for compliance measurements on digital transmission system, frequency hopping spread spectrum system, and hybrid system devices operating under section 15.247 of the FCC rules

3.2 Verdict

No.	Description	FCC Part No.	Test Result	Verdict
1	Antenna Requirement	15.203	--	Pass ^{Note}
2	Number of Hopping Frequency	15.247(a)	5.2.4	Pass
3	Peak Output Power and E.I.R.P	15.247(b)	5.3.4	Pass
4	Occupied Bandwidth	15.247(a)	5.4.4	Pass
5	Hopping Frequency Separation	15.247(a)	5.5.4	Pass
6	Time of Occupancy (Dwell time)	15.247(a)	5.6.4	Pass
7	Conducted Spurious Emission& Authorized-band band-edge	15.247(d)	5.7.4	Pass
8	Conducted Emission	15.207	5.8.4	Pass
9	Radiated Spurious Emission	15.209 15.247(d)	5.9.4	Pass
10	Band Edge (Restricted-band band-edge)	15.209 15.247(d)	5.10.4	Pass

Note: The EUT has a permanently and irreplaceable attached antenna, which complies with the requirement FCC 15.203.

4 GENERAL TEST CONFIGURATIONS

4.1 Test Environments

During the measurement, the normal environmental conditions were within the listed ranges:

Relative Humidity	47% to 56%	
Atmospheric Pressure	100 kPa to 102 kPa	
Temperature	NT (Normal Temperature)	+22.1°C to +24.7°C
Working Voltage of the EUT	NV (Normal Voltage)	1.5 V

4.2 Test Equipment List

Description	Manufacturer	Model	Serial No.	Cal. Date	Cal. Due
Spectrum Analyzer	KEYSIGHT	N9020A	MY50330200	2023.05.16	2024.05.15
Spectrum Analyzer	KEYSIGHT	N9020A	MY46471071	2023.07.25	2024.07.24
Spectrum Analyzer	KEYSIGHT	N9020A	MY50531259	2023.09.05	2024.09.04
Test Antenna-Horn	SCHWARZBECK	BBHA 9120D	02460	2021.05.20	2024.05.19
Test Antenna-Horn	A-INFO	LB-180400KF	J211060273	2021.07.02	2024.07.01
Anechoic Chamber	RAINFORD	9m*6m*6m	140	2022.02.19	2024.08.15
Amplifier	COM-MV	LSCX_LNA1-12G-01	7210214	2023.09.05	2024.09.04
Amplifier	COM-MV	XKu_LNA7-18G-01	7210209	2023.09.05	2024.09.04
EMI Receiver	ROHDE&SCHWARZ	ESRP	101036	2023.09.05	2024.09.04
Test Antenna-Bi-Log	SCHWARZBECK	VULB 9168	9168-01162	2023.08.04	2024.08.03
Test Antenna-Loop	SCHWARZBECK	FMZB 1519	1519-037	2021.04.16	2024.04.15
Amplifier	COM-MV	ZT30-1000M	B2018054558	2023.12.05	2024.12.04
Anechoic Chamber	EMC Electronic Co., Ltd	20.10*11.60*7.35m	130	2021.08.15	2024.08.14
EMI Receiver	KEYSIGHT	N9010B	MY57110309	2023.09.05	2024.09.04
LISN	SCHWARZBECK	NSLK 8127	8127-687	2023.05.16	2024.05.15
Shielded Enclosure	YiHeng Electronic Co., Ltd	3.5m*3.1m*2.8m	112	2022.02.19	2025.02.18

4.3 Test Software List

Description	Manufacturer	Software Version	Serial No.	Applicable test Setup
BL410R	BALUN	V2.1.1.488	N/A	The section 4.5.1
BL410E	BALUN	V22.930	N/A	The section 4.5.2&4.5.3&4.5.4&4.5.5

4.4 Measurement Uncertainty

The following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2.

This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Parameters	Uncertainty
Occupied Channel Bandwidth	2.8%
RF output power, conducted	1.28 dB
Power Spectral Density, conducted	1.30 dB
Unwanted Emissions, conducted	1.84 dB
All emissions, radiated	5.36 dB
Temperature	0.8°C
Humidity	4%

4.5 Description of Test Setup

4.5.1. For Antenna Port Test

Conducted value (dBm) = Measurement value (dBm) + cable loss (dB)


For example: the measurement value is 10 dBm and the cable 0.5dBm used, then the final result of EUT:

Conducted value (dBm) = 10 dBm + 0.5 dB = 10.5 dBm




(Diagram 1)

4.5.2. For AC Power Supply Port Test




(Diagram 2)

4.5.3. For Radiated Test (Below 30 MHz)




(Diagram 3)

4.5.4. For Radiated Test (30 MHz-1 GHz)



(Diagram 4)

4.5.5. For Radiated Test (Above 1 GHz)



(Diagram 5)

4.6 Measurement Results Explanation Example

4.6.1 For conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

4.6.2 For radiated band edges and spurious emission test:

Per part 15.35(c), the EUT Bluetooth average emission level could be determined by the peak emission level applying duty cycle correction factor, to represent averaging over the whole pulse train.

The average level is derived from the peak level corrected with "Duty cycle correction factor".

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + Duty cycle correction factor (dB)

Duty cycle correction factor (dB) = $20 * \log (\text{Duty cycle})$.

Duty cycle = on time / 100 milliseconds

On time = dwell time * hopping number in 100 ms

For example: bluetooth with dwell time 2.9 ms and 3 hops in 100 ms, then

Duty cycle correction factor (dB) = $20 * \log ((2.9 * 3) / 100) = -21.21 \text{ dB}$

Following shows an average computation example with duty cycle correction factor = -21.21 dB, and the peak emission level is 45.61 dBuV/m.

Example:

Average Emission Level (dBuV/m) = Peak Emission Level (dBuV/m) + duty cycle correction factor (dB)
= $45.61 + (-21.21) = 24.4 \text{ (dBuV/m)}$

5 TEST ITEMS

5.1 Antenna Requirements

5.1.1 Relevant Standards

FCC §15.203 & 15.247(b)

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, § 15.213, § 15.217, § 15.219, or § 15.221. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

If directional gain of transmitting antennas is greater than 6 dBi, the power shall be reduced by the same level in dB comparing to gain minus 6 dBi. For the fixed point-to-point operation, the power shall be reduced by one dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the FCC rule.

5.1.2 Antenna Anti-Replacement Construction

The Antenna Anti-Replacement as following method:

Protected Method	Description
The antenna is embedded in the product.	The antenna is welded on the mainboard, can't be replaced by the consumer

Reference Documents	Item
Photo	Please refer to the EUT Photo documents.

5.1.3 Antenna Gain

The antenna peak gain of EUT is less than 6 dBi. Therefore, it is not necessary to reduce maximum peak output power limit.

5.2 Number of Hopping Frequency

5.2.1 Limit

FCC §15.247(a) (1) (iii)

Frequency hopping systems operating in the 2400 MHz to 2483.5 MHz bands shall use at least 15 hopping frequencies.

5.2.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.2.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = the frequency band of operation

RBW $\geq$ 1% of the span

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.2.4 Test Result



Test Data

Test Mode	Frequency Block (MHz)	Measured Channel Numbers	Min. Limit	Verdict
GFSK	2400 - 2483.5	40	15	Pass

Test Plot

GFSK 2.4 GHz ~ 2.4415 GHz

GFSK 2.4415 GHz ~ 2.4835 GHz



5.3 Peak Output Power

5.3.1 Test Limit

FCC § 15.247(b)

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels. For all other frequency hopping systems in the 2400-2483.5 MHz band: 0.125 watts.

5.3.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.3.3 Test Procedure

The Bluetooth Module operates at hopping-off test mode. The lowest, middle and highest channels are selected to perform testing to verify the conducted RF output peak power of the Module.

Use the following spectrum analyzer settings:

Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel

RBW > the 20 dB bandwidth of the emission being measured

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize.


5.3.4 Test Result

Peak Power Test Data

Channel	Measured Output Peak Power		Limit		Verdict
	dBm	mW	dBm	mW	
Low	-0.09	0.98	21	125	Pass
Middle	-0.15	0.97			Pass
High	-0.24	0.95			Pass

Test Plots

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



5.4 Occupied Bandwidth

5.4.1 Limit

FCC §15.247(a)

Measurement of the 20dB bandwidth of the modulated signal.

5.4.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.4.3 Test Procedure

Use the following spectrum analyzer settings:

Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel

RBW $\geq$ 1% of the 20 dB bandwidth

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

The EUT should be transmitting at its maximum data rate, Allow the trace to stabilize.

5.4.4 Test Result

Test Data

Test Mode	GFSK	
Channel	20 dB Bandwidth (MHz)	99% Bandwidth (MHz)
Low Channel	2.035000	1.921800
Middle Channel	2.095000	1.953600
High Channel	2.080000	1.923800

Test Plots

20 dB Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



99% Bandwidth

GFSK LOW CHANNEL



GFSK MIDDLE CHANNEL



GFSK HIGH CHANNEL



5.5 Carrier Frequency Separation

5.5.1 Limit

FCC §15.247(a)

Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater. Alternatively, Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or two-thirds of the 20 dB bandwidth of the hopping channel, whichever is greater, provided the systems operate with an output power no greater than 125 mW.

5.5.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.5.3 Test Procedure

The EUT must have its hopping function enabled. Use the following spectrum analyzer settings:

Span = wide enough to capture the peaks of two adjacent channels

Resolution (or IF) Bandwidth (RBW) $\geq$ 1% of the span

Video (or Average) Bandwidth (VBW) $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels.

5.5.4 Test Result

Test Data

Mode	Frequency separation (MHz)	2/3 of the 20 dB Bandwidth (MHz)	Verdict
GFSK	2.000	1.397	Pass

Test Plot

GFSK



5.6 Time of Occupancy (Dwell time)

5.6.1 Limit

FCC §15.247(a)

Frequency hopping systems in the 2400 MHz - 2483.5 MHz band shall use at least 15 non-overlapping channels. The average time of occupancy on any channel shall not be greater than 0.4 seconds within a period of 0.4 seconds multiplied by the number of hopping channels employed. Frequency hopping systems may avoid or suppress transmissions on a particular hopping frequency provided that a minimum of 15 channels are used.

5.6.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.6.3 Test Procedure

The average time of occupancy on any channel within the Period can be calculated with formulas:

$$\{\text{Total of Dwell}\} = \{\text{Pulse Time}\} * \{\text{Number of Hopping Frequency in Period}\}$$

$$\{\text{Period}\} = 0.4s * \{\text{Number of Hopping Frequency}\}$$

The middle channels are selected to perform testing to record the dwell time of each occupation measured in this channel, which is called Pulse Time here.


5.6.4 Test Result

Test Data


GFSK			
Pulse Width (ms)	Total of Dwell (ms)	Limit (sec)	Verdict
0.500	24.500	0.4	Pass

Test Plots

Pulse Width



Total of Dwell



5.7 Conducted Spurious Emission & Authorized-band band-edge

5.7.1 Limit

FCC §15.247(d)

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.

5.7.2 Test Setup

See section 4.5.1 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.7.3 Test Procedure

Use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious emissions (e.g., harmonics) from the lowest frequency generated in the EUT up through the 10th harmonic. Typically, several plots are required to cover this entire span.

RBW = 100 kHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

Allow the trace to stabilize

5.7.4 Test Result

Test Data

GFSK Mode:

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
Low	-36.08	-1.60	-21.60	Pass
Middle	-35.88	-2.35	-22.35	Pass
High	-35.34	-2.33	-22.33	Pass

Hopping Mode:

GFSK				
Channel	Measured Max. Out of Band Emission (dBm)	Limit (dBm)		Verdict
		Carrier Level	Calculated 20 dBc Limit	
GFSK	-35.37	-1.54	-21.54	Pass

Test Plots


GFSK LOW CHANNEL, CARRIER LEVEL




GFSK LOW CHANNEL, BAND EDGE



GFSK LOW CHANNEL, SPURIOUS 30 MHz ~ 3 GHz




GFSK LOW CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK MIDDLE CHANNEL, CARRIER LEVEL



GFSK MIDDLE CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK MIDDLE CHANNEL, SPURIOUS 3 GHz ~ 25 GHz




GFSK HIGH CHANNEL, CARRIER LEVEL




GFSK HIGH CHANNEL, BAND EDGE




GFSK HIGH CHANNEL, SPURIOUS 30 MHz ~ 3 GHz



GFSK HIGH CHANNEL, SPURIOUS 3 GHz ~ 25 GHz





GFSK HOPPING, CARRIER LEVEL



GFSK HOPPING BAND EDGE (LOW)



GFSK HOPPING BAND EDGE (HIGH)

GFSK Hopping Mode, SPURIOUS
30 MHz ~ 3 GHzGFSK Hopping Mode, SPURIOUS
3GHz ~ 25 GHz

5.8 Conducted Emission

5.8.1 Limit

FCC §15.207

For an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 Ω line impedance stabilization network (LISN).

Frequency range (MHz)	Conducted Limit (dB μ V)	
	Quai-peak	Average
0.15 - 0.50	66 to 56	56 to 46
0.50 - 5	56	46
0.50 - 30	60	50

5.8.2 Test Setup

See section 4.5.2 for test setup description for the AC power supply port. The photo of test setup please refer to ANNEX A.

5.8.3 Test Procedure

The maximum conducted interference is searched using Peak (PK), if the emission levels more than the AV and QP limits, and that have narrow margins from the AV and QP limits will be re-measured with AV and QP detectors. Tests for both L phase and N phase lines of the power mains connected to the EUT are performed. Refer to recorded points and plots below.

5.8.4 Test Result


Note ¹: The EUT was tested in connected the laptop and dongle test mode.

Note ²: Results (dBuV) = Original reading level of Spectrum Analyzer (dBuV) + Factor (dB)

Test Data and Plots

PHASE L


CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	47.93	9.78	65.89	17.96	Peak	L	Pass
1**	0.152	30.40	9.78	55.89	25.49	AV	L	Pass
2	0.192	45.78	9.77	63.95	18.17	Peak	L	Pass
2**	0.192	28.62	9.77	53.95	25.33	AV	L	Pass
3	0.492	38.48	9.99	56.13	17.65	Peak	L	Pass
3**	0.492	31.75	9.99	46.13	14.38	AV	L	Pass
4	2.414	38.03	10.26	56.00	17.97	Peak	L	Pass
4**	2.414	25.75	10.26	46.00	20.25	AV	L	Pass
5	5.758	40.96	10.49	60.00	19.04	Peak	L	Pass
5**	5.758	26.90	10.49	50.00	23.10	AV	L	Pass
6	13.476	41.32	10.58	60.00	18.68	Peak	L	Pass
6**	13.476	32.98	10.58	50.00	17.02	AV	L	Pass

PHASE N

CE Test case_FCC_CE_FCC PART 15C



No.	Frequency (MHz)	Results (dBuV)	Factor (dB)	Limit (dBuV)	Margin (dB)	Detector	Line	Verdict
1	0.152	50.60	9.78	65.89	15.29	Peak	N	Pass
1**	0.152	34.15	9.78	55.89	21.74	AV	N	Pass
2	0.176	45.65	9.78	64.67	19.02	Peak	N	Pass
2**	0.176	32.00	9.78	54.67	22.67	AV	N	Pass
3	0.204	43.79	9.77	63.45	19.66	Peak	N	Pass
3**	0.204	28.82	9.77	53.45	24.63	AV	N	Pass
4	0.492	37.50	9.99	56.13	18.63	Peak	N	Pass
4**	0.492	30.38	9.99	46.13	15.75	AV	N	Pass
5	2.228	38.06	10.06	56.00	17.94	Peak	N	Pass
5**	2.228	25.29	10.06	46.00	20.71	AV	N	Pass
6	14.142	42.75	10.76	60.00	17.25	Peak	N	Pass
6**	14.142	31.83	10.76	50.00	18.17	AV	N	Pass

5.9 Radiated Spurious Emission

5.9.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

According to FCC section 15.209 (a), except as provided elsewhere in this subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 - 30.0	30	30
30 - 88	100	3
88 - 216	150	3
216 - 960	200	3
Above 960	500	3

Note:

1. Field Strength (dBμV/m) = 20*log[Field Strength (μV/m)].
2. In the emission tables above, the tighter limit applies at the band edges.
3. For Above 1000 MHz, the emission limit in this paragraph is based on measurement instrumentation employing an average detector, measurement using instrumentation with a peak detector function, corresponding to 20dB above the maximum permitted average limit.
4. For above 1000 MHz, limit field strength of harmonics: 54dBuV/m@3m (AV) and 74dBuV/m@3m (PK).

5.9.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.9.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.9.4 Test Result

Note ¹: The symbol of "--" in the table which means not application.

Note ²: For the test data above 1 GHz, according the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.


Note ³: The EUT was tested in connected the laptop and dongle test mode.

Note ⁴: Results (dBuV/m) = Original reading level of Spectrum Analyzer (dBuV/m) + Factor (dB)

The low frequency, which started from 9 kHz to 30 MHz, was pre-scanned and the result which was 20 dB lower than the limit line per 15.31(o) was not reported.

Test Data and Plots


30 MHz to 1 GHz, ANT H



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	85.824	23.95	-27.24	40.0	16.05	Peak	300.30	200	Horizontal	Pass
2	139.901	26.23	-27.62	43.5	17.27	Peak	104.00	200	Horizontal	Pass
3	168.031	33.77	-27.18	43.5	9.73	Peak	273.10	200	Horizontal	Pass
4	231.420	27.32	-23.36	46.0	18.68	Peak	180.90	100	Horizontal	Pass
5	375.029	31.49	-19.08	46.0	14.51	Peak	132.50	100	Horizontal	Pass
6	555.886	34.48	-15.56	46.0	11.52	Peak	52.20	200	Horizontal	Pass

30 MHz to 1 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15C 30MHz-1GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	67.976	19.94	-25.86	40.0	20.06	Peak	167.90	100	Vertical	Pass
2	80.052	21.09	-28.47	40.0	18.91	Peak	250.00	200	Vertical	Pass
3	143.393	24.28	-27.80	43.5	19.22	Peak	205.10	200	Vertical	Pass
4	168.031	28.58	-27.18	43.5	14.92	Peak	171.60	200	Vertical	Pass
5	312.027	26.04	-21.30	46.0	19.96	Peak	15.00	200	Vertical	Pass
6	456.024	31.82	-17.93	46.0	14.18	Peak	205.60	100	Vertical	Pass


Test Data and Plots

Note 1: The marked spikes near 2400 MHz with circle should be ignored because they are Fundamental signal.

Note 2: The spurious from 18GHz-25GHz is noise only, do not show on the report.

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1323.900	42.65	-17.20	74.0	31.35	Peak	339.00	200	Horizontal	Pass
1**	1323.900	31.94	-17.20	54.0	22.06	AV	339.00	200	Horizontal	Pass
2	2401.700	95.92	-10.63	74.0	-21.92	Peak	266.00	100	Horizontal	N/A
2**	2401.700	93.45	-10.63	54.0	-39.45	AV	266.00	100	Horizontal	N/A
3	4816.250	47.69	-3.03	74.0	26.31	Peak	133.00	100	Horizontal	Pass
3**	4816.250	45.86	-3.03	54.0	8.14	AV	133.00	100	Horizontal	Pass
4	7205.000	58.23	0.36	74.0	15.77	Peak	133.00	100	Horizontal	N/A
4**	7205.000	54.05	0.36	54.0	-0.05	AV	133.00	100	Horizontal	N/A
5	12517.963	52.92	1.34	74.0	21.08	Peak	164.00	100	Horizontal	Pass
5**	12517.963	44.04	1.34	54.0	9.96	AV	164.00	100	Horizontal	Pass
6	16386.413	56.10	2.65	74.0	17.90	Peak	143.00	200	Horizontal	Pass
6**	16386.413	46.75	2.65	54.0	7.25	AV	143.00	200	Horizontal	Pass

GFSK LOW CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1498.600	42.60	-16.97	74.0	31.40	Peak	116.00	100	Horizontal	Pass
1**	1498.600	32.04	-16.97	54.0	21.96	AV	116.00	100	Horizontal	Pass
2	2401.700	93.23	-10.63	74.0	-19.23	Peak	0.00	150	Horizontal	N/A
2**	2401.700	91.65	-10.63	54.0	-37.65	AV	0.00	150	Horizontal	N/A
3	4804.250	53.64	-3.21	74.0	20.36	Peak	124.00	100	Horizontal	Pass
3**	4804.250	50.58	-3.21	54.0	3.42	AV	124.00	100	Horizontal	Pass
4	7205.250	57.14	0.29	74.0	16.86	Peak	105.00	100	Horizontal	N/A
4**	7205.250	51.98	0.29	54.0	2.02	AV	105.00	100	Horizontal	N/A
5	12528.175	52.81	1.28	74.0	21.19	Peak	0.00	300	Horizontal	Pass
5**	12528.175	42.58	1.28	54.0	11.42	AV	0.00	300	Horizontal	Pass
6	17434.051	56.35	5.52	74.0	17.65	Peak	249.00	300	Horizontal	Pass
6**	17434.051	46.94	5.52	54.0	7.06	AV	249.00	300	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1571.100	43.33	-17.22	74.0	30.67	Peak	164.00	300	Horizontal	Pass
1**	1571.100	32.43	-17.22	54.0	21.57	AV	164.00	300	Horizontal	Pass
2	2440.300	98.17	-10.03	74.0	-24.17	Peak	64.00	100	Horizontal	N/A
2**	2440.300	94.52	-10.03	54.0	-40.52	AV	64.00	100	Horizontal	N/A
3	4880.750	51.07	-3.74	74.0	22.93	Peak	343.00	200	Horizontal	Pass
3**	4880.750	46.51	-3.74	54.0	7.49	AV	343.00	200	Horizontal	Pass
4	7322.000	50.19	0.18	74.0	23.81	Peak	0.00	200	Horizontal	Pass
4**	7322.000	47.01	0.18	54.0	6.99	AV	0.00	200	Horizontal	Pass
5	12535.300	52.58	1.23	74.0	21.42	Peak	332.00	300	Horizontal	Pass
5**	12535.300	42.86	1.23	54.0	11.14	AV	332.00	300	Horizontal	Pass
6	16406.886	55.33	3.07	74.0	18.67	Peak	117.00	100	Horizontal	Pass
6**	16406.886	45.98	3.07	54.0	8.02	AV	117.00	100	Horizontal	Pass

GFSK MIDDLE CHANNEL 1 GHz to 18 GHz, ANT V


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1513.000	42.26	-16.87	74.0	31.74	Peak	40.00	300	Vertical	Pass
1**	1513.000	33.04	-16.87	54.0	20.96	AV	40.00	300	Vertical	Pass
2	2440.300	83.02	-10.03	74.0	-9.02	Peak	131.00	200	Vertical	N/A
2**	2440.300	82.16	-10.03	54.0	-28.16	AV	131.00	200	Vertical	N/A
3	4880.000	51.85	-3.67	74.0	22.15	Peak	285.00	200	Vertical	Pass
3**	4880.000	49.55	-3.67	54.0	4.45	AV	285.00	200	Vertical	Pass
4	7710.250	53.47	1.90	74.0	20.53	Peak	325.00	100	Vertical	Pass
4**	7710.250	45.41	1.90	54.0	8.59	AV	325.00	100	Vertical	Pass
5	11708.800	52.64	-0.46	74.0	21.36	Peak	360.00	200	Vertical	Pass
5**	11708.800	42.42	-0.46	54.0	11.58	AV	360.00	200	Vertical	Pass
6	16870.988	55.51	3.21	74.0	18.49	Peak	286.00	400	Vertical	Pass
6**	16870.988	46.37	3.21	54.0	7.63	AV	286.00	400	Vertical	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT H


RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1350.200	42.53	-16.98	74.0	31.47	Peak	293.00	200	Horizontal	Pass
1**	1350.200	32.21	-16.98	54.0	21.79	AV	293.00	200	Horizontal	Pass
2	2480.300	98.87	-11.30	74.0	-24.87	Peak	49.00	200	Horizontal	N/A
2**	2480.300	97.36	-11.30	54.0	-43.36	AV	49.00	200	Horizontal	N/A
3	4959.500	55.36	-3.55	74.0	18.64	Peak	256.00	200	Horizontal	Pass
3**	4959.500	52.71	-3.55	54.0	1.29	AV	256.00	200	Horizontal	Pass
4	7439.500	60.27	0.41	74.0	13.73	Peak	102.00	200	Horizontal	Pass
4**	7439.500	52.31	0.41	54.0	1.69	AV	102.00	200	Horizontal	Pass
5	11527.349	52.93	-0.95	74.0	21.07	Peak	19.00	400	Horizontal	Pass
5**	11527.349	42.79	-0.95	54.0	11.21	AV	19.00	400	Horizontal	Pass
6	17459.249	55.84	5.40	74.0	18.16	Peak	349.00	100	Horizontal	Pass
6**	17459.249	46.18	5.40	54.0	7.82	AV	349.00	100	Horizontal	Pass

GFSK HIGH CHANNEL 1 GHz to 18 GHz, ANT V

RE Test case_FCC Part 15C_FCC 15.247(2.4G)_1GHz-18GHz



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	1552.000	42.40	-17.20	74.0	31.60	Peak	304.00	100	Vertical	Pass
1**	1552.000	33.64	-17.20	54.0	20.36	AV	304.00	100	Vertical	Pass
2	2480.200	83.57	-11.20	74.0	-9.57	Peak	285.00	100	Vertical	N/A
2**	2480.200	82.58	-11.20	54.0	-28.58	AV	285.00	100	Vertical	N/A
3	4959.750	47.55	-3.51	74.0	26.45	Peak	282.00	200	Vertical	Pass
3**	4959.750	44.91	-3.51	54.0	9.09	AV	282.00	200	Vertical	Pass
4	7439.500	56.82	0.41	74.0	17.18	Peak	199.00	200	Vertical	Pass
4**	7439.500	52.93	0.41	54.0	1.07	AV	199.00	200	Vertical	Pass
5	11968.388	52.56	-0.22	74.0	21.44	Peak	148.00	100	Vertical	Pass
5**	11968.388	43.53	-0.22	54.0	10.47	AV	148.00	100	Vertical	Pass
6	17413.575	55.71	5.47	74.0	18.29	Peak	287.00	400	Vertical	Pass
6**	17413.575	45.96	5.47	54.0	8.04	AV	287.00	400	Vertical	Pass

5.10 Band Edge (Restricted-band band-edge)

5.10.1 Limit

FCC §15.209&15.247(d)

Radiated emission outside the frequency band attenuation below the general limits specified in FCC section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in FCC section 15.205(a), must also comply with the radiated emission limits specified in FCC section 15.209(a).

5.10.2 Test Setup

See section 4.5.3 to 4.5.5 for test setup description for the antenna port. The photo of test setup please refer to ANNEX A.

5.10.3 Test Procedure

The measurement frequency range is from 9 kHz to the 10th harmonic of the fundamental frequency. The Turn Table is actuated to turn from 0° to 360°, and both horizontal and vertical polarizations of the Test Antenna are used to find the maximum radiated power. Mid channels on all channel bandwidth verified. Only the worst RB size/offset presented.

The power of the EUT transmitting frequency should be ignored.

All Spurious Emission tests were performed in X, Y, Z axis direction. And only the worst axis test condition was recorded in this test report.

Use the following spectrum analyzer settings:

Span = wide enough to fully capture the emission being measured

RBW = 1 MHz for $f \geq 1$ GHz, 100 kHz for $f < 1$ GHz

VBW $\geq$ RBW

Sweep = auto

Detector function = peak

Trace = max hold

For measurement below 1GHz, If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported, Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

5.10.4 Test Result

Note ¹: The lowest and highest channels are tested to verify the band edge emissions. Please refer to the following the plots for emissions values.


Note ²: The test data all are tested in the vertical and horizontal antenna which the trace is max hold. So these plots have shown the worst case.

Note ³: According the ANSI C63.10-2013, where limits are specified for both average and peak (or quasi-peak) detector functions, if the peak (or quasi-peak) measured value complies with the average limit, it is unnecessary to perform an average measurement.

Note ⁴: The Level (dBuV/m) has been corrected by factor.


Test Data

GFSK LOW CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2388.750	63.10	-1.84	74.0	10.90	Peak	232.00	150	Horizontal	Pass
1**	2388.750	42.63	-1.84	54.0	11.37	AV	232.00	150	Horizontal	Pass
2	2389.950	59.06	-1.82	74.0	14.94	Peak	57.00	100	Horizontal	Pass
2**	2389.950	43.02	-1.82	54.0	10.98	AV	57.00	100	Horizontal	Pass

GFSK HIGH CHANNEL



No.	Frequency (MHz)	Results (dBuV/m)	Factor (dB)	Limit (dBuV/m)	Margin (dB)	Detector	Table (Degree)	Height (cm)	Antenna	Verdict
1	2483.530	72.97	-1.10	74.0	1.03	Peak	30.00	150	Horizontal	Pass
1**	2483.530	50.93	-1.10	54.0	3.07	AV	30.00	150	Horizontal	Pass
2	2484.220	72.99	-1.14	74.0	1.01	Peak	45.00	150	Horizontal	Pass
2**	2484.220	47.43	-1.14	54.0	6.57	AV	45.00	150	Horizontal	Pass

ANNEX A TEST SETUP PHOTOS

1 Radiated Test Photo

Below 30MHz




30MHz-1GHz




Close-up



Above 1GHz



Close-up



2 Conducted Test Photo

Conducted Test




3 Conducted Emissions

Test Photo 1



Test Photo 2



ANNEX B EUT EXTERNAL PHOTOS

FRONT VIEW OF EUT




REAR VIEW OF EUT



LEFT VIEW OF EUT



RIGHT VIEW OF EUT



TOP VIEW OF EUT



BOTTOM VIEW OF EUT



English Version



Accessory-Dongle




ANNEX C EUT INTERNAL PHOTOS


EUT UNCOVER VIEW 1



MAIN BOARD TOP VIEW



MAIN BOARD REAR VIEW



Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--