

Prüfbericht-Nr.: Test report no.:	CN263245 001	Auftrags-Nr.: Order no.:	168589306	Seite 1 von 16 Page 1 of 16	
Kunden-Referenz-Nr.: Client reference no.:	N/A	Auftragsdatum: Order date:	2025-12-16		
Auftraggeber: Client:	Ugreen Group Limited UGREEN Building, Longcheng Industrial Park, Longguanxi Road, Longhua, Shenzhen, 518000, China				
Prüfgegenstand: Test item:	3-in-1 Wireless Charger				
Bezeichnung / Typ-Nr.: Identification / Type no.:	W707				
Auftrags-Inhalt: Order content:	Test Report				
Prüfgrundlage: Test specification:	CFR Title 47 FCC Part 15: Subpart C Section 15.215 CFR Title 47 FCC Part 15: Subpart C Section 15.207 CFR Title 47 FCC Part 15: Subpart C Section 15.209				
Wareneingangsdatum: Date of sample receipt:	2025-12-18	Please refer to Photo Document			
Prüfmuster-Nr.: Test sample no.:	A004158243-001~019 A004216141-001				
Prüfzeitraum: Testing period:	2026-01-09 - 2026-03-20				
Ort der Prüfung: Place of testing:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüflaboratorium: Testing laboratory:	TÜV Rheinland (Shenzhen) Co., Ltd.				
Prüfergebnis*: Test result*:	Pass				
geprüft von: tested by:			genehmigt von: authorized by:		
Datum: Date:	2026-03-20	Signed by: Lin Lin		Ausstellungsdatum: Issue date:	2026-03-20
Stellung / Position:	Sachverständige(r)/Expert		Stellung / Position:	Sachverständige(r)/Expert	
Sonstiges / Other:	FCC ID: 2AQI5-45024				
Zustand des Prüfgegenstandes bei Anlieferung: Condition of the test item at delivery:	Prüfmuster vollständig und unbeschädigt Test item complete and undamaged				
* Legende:	P(ass) = entspricht o.g. Prüfgrundlage(n) F(ail) = entspricht nicht o.g. Prüfgrundlage(n) N/A = nicht anwendbar N/T = nicht getestet				
* Legend:	P(ass) = passed a.m. test specification(s) F(ail) = failed a.m. test specification(s) N/A = not applicable N/T = not tested				
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the above mentioned test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>					

Prüfbericht-Nr.: CN263245 001
Test report no.:

Seite 2 von 16
Page 2 of 16

Anmerkungen
Remarks

1	Alle eingesetzten Prüfmittel waren zum angegebenen Prüfzeitraum gemäß eines festgelegten Kalibrierungsprogramms unseres Prüfhauses kalibriert. Sie entsprechen den in den Prüfprogrammen hinterlegten Anforderungen. Die Rückverfolgbarkeit der eingesetzten Prüfmittel ist durch die Einhaltung der Regelungen unseres Managementsystems gegeben. Detaillierte Informationen bezüglich Prüfbedingungen, Prüfequipment und Messunsicherheiten sind im Prüflabor vorhanden und können auf Wunsch bereitgestellt werden. <i>The equipment used during the specified testing period was calibrated according to our test laboratory calibration program. The equipment fulfils the requirements included in the relevant standards. The traceability of the test equipment used is ensured by compliance with the regulations of our management system. Detailed information regarding test conditions, equipment and measurement uncertainty is available in the test laboratory and could be provided on request.</i>
2	Wie vertraglich vereinbart, wurde dieses Dokument nur digital unterzeichnet. Der TÜV Rheinland hat nicht überprüft, welche rechtlichen oder sonstigen diesbezüglichen Anforderungen für dieses Dokument gelten. Diese Überprüfung liegt in der Verantwortung des Benutzers dieses Dokuments. Auf Verlangen des Kunden kann der TÜV Rheinland die Gültigkeit der digitalen Signatur durch ein gesondertes Dokument bestätigen. Diese Anfrage ist an unseren Vertrieb zu richten. Eine Umweltgebühr für einen solchen zusätzlichen Service wird erhoben. Informationen zur Verifizierung der Authentizität unserer Dokumente erhalten Sie auf folgender Webseite: go.tuv.com/digital-signature <i>As contractually agreed, this document has been signed digitally only. TUV Rheinland has not verified and unable to verify which legal or other pertaining requirements are applicable for this document. Such verification is within the responsibility of the user of this document. Upon request by its client, TUV Rheinland can confirm the validity of the digital signature by a separate document. Such request shall be addressed to our Sales department. An environmental fee for such additional service will be charged. For information on verifying the authenticity of our documents, please visit the following website: go.tuv.com/digital-signature</i>
3	Prüfklausel mit der Note * wurden an qualifizierte Unterauftragnehmer vergeben und sind unter der jeweiligen Prüfklausel des Berichts beschrieben. Abweichungen von Prüfspezifikation(en) oder Kundenanforderungen sind in der jeweiligen Prüfklausel im Bericht aufgeführt. <i>Test clauses with remark of * are subcontracted to qualified subcontractors and described under the respective test clause in the report.</i> <i>Deviations of testing specification(s) or customer requirements are listed in specific test clause in the report.</i>
4	Die Entscheidungsregel für Konformitätserklärungen basierend auf numerischen Messergebnissen in diesem Prüfbericht basiert auf der "Null-Grenzwert-Regel" und der "Einfachen Akzeptanz" gemäß ILAC G8:2019 und IEC Guide 115:2023, es sei denn, in der auf Seite 1 dieses Berichts genannten angewandten Norm ist etwas anderes festgelegt oder vom Kunden gewünscht. Dies bedeutet, dass die Messunsicherheit nicht berücksichtigt wird und daher auch nicht im Prüfbericht angegeben wird. Zu weiteren Informationen bezüglich des Risikos durch diese Entscheidungsregel siehe ILAC G8:2019. <i>The decision rule for statements of conformity, based on numerical measurement results, in this test report is based on the "Zero Guard Band Rule" and "Simple Acceptance" in accordance with ILAC G8:2019 and IEC Guide 115:2023, unless otherwise specified in the applied standard mentioned on Page 1 of this report or requested by the customer. This means that measurement uncertainty is not taken in account and hence also not declared in the test report. For additional information to the resulting risk based of this decision rule please refer to ILAC G8:2019.</i>

Prüfbericht - Nr.: CN263245 001
Test Report No.:

Seite 3 von 16
Page 3 of 16

Test Summary

5.1.1 ANTENNA REQUIREMENT

RESULT: Pass

5.1.2 20dB BANDWIDTH

RESULT: Pass

5.1.3 FIELD STRENGTH OF FUNDAMENTAL AND HARMONICS

RESULT: Pass

5.1.4 CONDUCTED EMISSION ON AC MAINS

RESULT: Pass

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	7
2.4	CALIBRATION	7
2.5	MEASUREMENT UNCERTAINTY.....	7
2.6	LOCATION OF ORIGINAL DATA.....	7
2.7	STATUS OF FACILITY USED FOR TESTING.....	7
3	GENERAL PRODUCT INFORMATION	8
3.1	PRODUCT FUNCTION AND INTENDED USE.....	8
3.2	RATINGS AND SYSTEM DETAILS	8
3.3	INDEPENDENT OPERATION MODES	9
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	9
3.5	SUBMITTED DOCUMENTS.....	9
4	TEST SET-UP AND OPERATION MODES	10
4.1	PRINCIPLE OF CONFIGURATION SELECTION	10
4.2	TEST OPERATION AND TEST SOFTWARE.....	10
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT	10
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	10
4.5	TEST SETUP DIAGRAM	11
5	TEST RESULTS	12
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	12
5.1.1	<i>Antenna Requirement</i>	<i>12</i>
5.1.2	<i>20dB Bandwidth</i>	<i>13</i>
5.1.3	<i>Field Strength of Fundamental and Harmonics</i>	<i>14</i>
5.1.4	<i>Conducted Emission on AC Mains.....</i>	<i>15</i>
6	PHOTOGRAPHS OF THE TEST SET-UP	16
7	LIST OF TABLES.....	16

Prüfbericht - Nr.: CN263245 001
Test Report No.:

Seite 5 von 16
Page 5 of 16

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Test Results of FCC Part 15C.

Appendix B: Photographs of the Test Set-up.

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China

A2LA Certificate Number: 5162.01

FCC Accreditation Designation No.: CN1260

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

Radio Spectrum Testing (TS8997)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
Signal Analyzer	R&S	FSV 40	101441	2025-09-23	2026-09-22
OSP	R&S	OSP 150	101017	2025-10-30	2026-10-29
Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A	N/A
Test Software	R&S	WMS32 (V11.00.00)	N/A	N/A	N/A
Power Meter	R&S	NRP2	107105	2025-10-30	2026-10-29
Wideband Power Sensor	R&S	NRP-Z81	105677	2025-09-23	2026-09-22
Shielding Room	Albatross	SR1	APC17151-SR1	2024-09-14	2027-09-13
Unwanted Emission Testing (TS9975)					
Equipment	Manufacturer	Model	Serial No.	Cal. Date	Cal. until
EMI Test Receiver	R&S	ESR 7	102021	2025-09-22	2026-09-21
Signal Analyzer	R&S	FSV 40	101439	2025-09-22	2026-09-21
System Controller Interface	R&S	SCI-100	S10010038	N/A	N/A
Filterbank	R&S	Wlan	100759	2025-09-22	2026-09-21
OSP	R&S	OSP 120	102040	N/A	N/A
Pre-amplifier	R&S	SCU08F1	08320031	2025-09-22	2026-09-21
Amplifier	R&S	SCU-18F	180070	2025-09-22	2026-09-21
Amplifier	R&S	SCU40A	100475	2025-09-22	2026-09-21
Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	2024-09-28	2026-09-27
Active Loop Antenna	Schwarzbeck	FMZB 1513	302	2024-09-28	2026-09-27
Test software	R&S	EMC32 (V10.60.10)	N/A	N/A	N/A
Control PC	Dell	OptiPlex 7050	36NV9P2	N/A	N/A
3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	2024-09-14	2027-09-13

Prüfbericht - Nr.: CN263245 001
Test Report No.:Seite 7 von 16
Page 7 of 16

Conducted Emission				
Equipment	Manufacturer	Model No.	Serial No.	Cal. Until
EMI Test Receiver	R&S	ESR3	102680	2027-02-03
Artificial Mains Network	R&S	ENV216	102333	2026-07-18
Artificial Mains Network	R&S	ENV216	101445	2027-02-03
EMC32 Test Software	R&S	EMC32(Ver.10.60.20)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table

Table 2: Measurement Uncertainty

Parameter	Uncertainty (k=2)
Occupied Channel Bandwidth	± 2.08 %
All emissions, radiated	± 4.17 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.24 dB / ± 3.24 dB

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 2-3F, 101 & 102, No.2, Nuclear Power Industrial Park, Fuming Community, Fucheng Street, Longhua District, Shenzhen 518000, China is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a 3-in-1 Wireless Charger which supports wireless charging (WPT) function.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 3: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment:	3-in-1 Wireless Charger
Type Designation:	W707 Note: The W707 has two appearance colors, they are only difference in appearance color, and the other electronic and electrical parts are the same.
Product Number (P/N) code:	45025, 45025P, 45025X, 45025A, 45025B, 45025U, 45025JP, 45025ZD, 45025T, 45980, 45980P, 45980X, 45980A, 45980B, 45980U, 45980JP, 45980ZD, 45980T, 45026, 45026P, 45026X, 45026A, 45026B, 45026U, 45026JP, 45026ZD, 45026T, 45024, 45024P, 45024X, 45024A, 45024B, 45024U, 45024JP, 45024ZD, 45024T, 35028, 35028P, 35028X, 35028A, 35028B, 35028U, 35028JP, 35028ZD, 35028T
FCC ID:	2AQI5-45024
Operating Voltage:	Input: 9.0V~3.0A/12.0V~3.0A Wireless Charging Total Output Power: 25.0W Max (iPhone: 15.0W, Apple Watch/AirPods: 5.0W)
Operating Temperature Range:	-10 °C ~ +35 °C
Wireless charging output power:	Magnetic Wireless Charger: 5W / 7.5W / 10W / 15W Max. True Wireless Stereo (TWS) Wireless Charging: 5W Max. Watch Charging: 5W Max.
AC/DC Adapter:	Model: W0452 Input: 100-240Vac, 50/60Hz, 1.2A Output: 5Vdc, 3A/ 9Vdc, 3A/ 12Vdc, 3A/ 15Vdc, 3A/ 20Vdc, 2.25A
Technical Specification of WPT	
Frequency Range:	110.5 – 205 kHz & 326.5 kHz & 360kHz & 1.778MHz
Operating Frequency:	110.5 – 148.5 kHz & 326.5 kHz & 360kHz & 1.778MHz
Type of Modulation:	FSK, ASK
Antenna Type:	Induction coil
Wireless output power:	5W / 7.5W / 10W / 15W

Note: The correctness of all data provided by customer in the test report is ensured and responsible of the customer. Any misjudgment of the test results caused by the use of incorrect data provided by customer shall be borne by the customer.

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Wireless Charging, BPP, 5W (Phone)
- B. On, Wireless Charging, EPP, 7.5W (Phone)
- C. On, Wireless Charging, EPP, 10W (Phone)
- D. On, Wireless Charging, MPP, 15W (Phone)
- E. On, Wireless Charging, 5W [True Wireless Stereo (TWS)]
- F. On, Wireless Charging, 5W (Watch)
- G. On, Co-location mode (Worst case mode A~D + mode E + mode F)
- H. On, Standby mode
- I. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- | | |
|-------------------------|----------------------------------|
| - Application Form | - User Manual |
| - Operation Description | - FCC/IC Label and Location Info |

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5 & 6. All testing were performed according to the procedures in ANSI C63.10: 2020.

According to clause 3.1, all tests were performed on model W707 in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 4: List of Accessories and Auxiliary Equipment

Description	Manufacturer	Model	Remark
Wireless charge Load	YBZ	YBZ-MPP25	N/A
Watch	Apple	iWatch	N/A
Earphone	Apple	Airpods Pro2	N/A
Cell Phone	Apple	iPhone 16 Plus	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 30MHz)




Diagram of Measurement Configuration for Radiation Test (Below 1GHz)





Diagram of Measurement Configuration for Mains Conduction Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard

: FCC Part 15.203

The following describes the three ways that can be used to demonstrate compliance to Section 15.203

1. Antenna permanently attached
2. Unique (non-standard) antenna connector
3. Professional installation

According to the manufacturer declared, the EUT has one internal antenna, and the antenna is permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

Prüfbericht - Nr.: CN263245 001
Test Report No.:

Seite 13 von 16
Page 13 of 16

5.1.2 20dB Bandwidth

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.215(c)
Basic standard	: ANSI C63.10: 2020
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-01-13
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C, D, E, F, G, H
Ambient temperature	: 22 °C
Relative humidity	: 55 %
Atmospheric pressure	: 101 kPa

Note: This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN263245 001
Test Report No.:

Seite 14 von 16
Page 14 of 16

5.1.3 Field Strength of Fundamental and Harmonics

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.209 & 15.205
Basic standard : ANSI C63.10: 2020
Limits : Refer to 15.209(a)
Kind of test site : 3m Semi-anechoic Chamber

Test Setup

Date of testing : 2026-01-09 to 2026-03-13
Input voltage : AC 120V, 60Hz
Operation mode : A, B, C, D, E, F, G, H
Ambient temperature : 22 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

Note: This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix A.

Prüfbericht - Nr.: CN263245 001
Test Report No.:

Seite 15 von 16
Page 15 of 16

5.1.4 Conducted Emission on AC Mains

RESULT:

Pass

Test Specification

Test standard	: FCC Part 15.207(a)
Basic standard	: ANSI C63.10: 2020
Frequency range	: 0.15 – 30MHz
Limits	: FCC Part 15.207(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 2026-02-06 to 2026-03-20
Input voltage	: AC 120V, 60Hz
Operation mode	: A, B, C, D, E, F, G, H
Ambient temperature	: 24.0 °C
Relative humidity	: 52.1 %
Atmospheric pressure	: 101 kPa

This testing was carried out on all operation modes, but only the worst case was presented in this report.

For the measurement records, refer to the appendix A.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix B.

7 List of Tables


Table 1: List of Test and Measurement Equipment.....	6
Table 2: Measurement Uncertainty.....	7
Table 3: Technical Specification of EUT	8
Table 4: List of Accessories and Auxiliary Equipment.....	10

Appendix A: Test Results of FCC Part 15C


APPENDIX A: TEST RESULTS OF FCC PART 15C.....	1
APPENDIX A.1: TEST RESULTS OF 20DB BANDWIDTH	2
Wireless charging (7.5W).....	2
Wireless charging (10W).....	3
Wireless charging (15W).....	4
Wireless charging (TWS 5W)	5
Wireless charging (Watch 5W_326kHz)	6
Wireless charging (Watch 5W_1.778MHz).....	7
Standby mode	8
APPENDIX A.2: TEST RESULTS OF FIELD STRENGTH OF FUNDAMENTAL AND HARMONICS	9
Wireless charging (7.5W).....	9
Wireless charging (10W).....	20
Wireless charging (15W).....	31
Wireless charging (TWS 5W)	42
Wireless charging (Watch 5W_326kHz)	53
Wireless charging (Watch 5W_1.778MHz).....	64
Wireless charging (Co-location).....	69
Standby mode	74
APPENDIX A.3: TEST RESULTS OF CONDUCTED EMISSION ON AC MAINS.....	79

Appendix A.1: Test Results of 20dB Bandwidth

Wireless charging (7.5W)




Wireless charging (10W)




Date: 13.JAN.2026 08:22:50

Wireless charging (15W)




Date: 13.JAN.2026 08:34:21

Wireless charging (TWS 5W)




Date: 13.JAN.2026 08:24:46

Wireless charging (Watch 5W_326kHz)




Date: 13.JAN.2026 08:39:10

Wireless charging (Watch 5W_1.778MHz)



Date: 13.JAN.2026 08:43:58

Standby mode



Date: 13.JAN.2026 08:36:51


Appendix A.2: Test Results of Field Strength of Fundamental and Harmonics

Note: The highest waveform in the figure is Fundamental.

Wireless charging (7.5W)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004158243-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.015711	48.24	---	143.66	95.42	100.0	X	55.0	20.0
0.015711	---	41.82	123.66	81.84	100.0	X	55.0	20.0
0.037234	---	35.96	116.17	80.21	100.0	X	176.0	20.0
0.037234	43.63	---	136.17	92.54	100.0	X	176.0	20.0
0.080627	---	26.97	109.47	82.50	100.0	X	68.0	20.0
0.081264	35.50	---	129.40	93.90	100.0	X	201.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019067	46.31	---	141.98	95.67	100.0	Y	236.0	20.0
0.019125	---	39.20	121.96	82.75	100.0	Y	236.0	20.0
0.037234	44.52	---	136.17	91.65	100.0	Y	128.0	20.0
0.037234	---	36.92	116.17	79.25	100.0	Y	128.0	20.0
0.077561	---	30.43	109.80	79.37	100.0	Y	145.0	20.0
0.077966	38.43	---	129.76	91.33	100.0	Y	27.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.018951	46.94	---	142.04	95.10	100.0	Z	74.0	20.0
0.019125	---	38.52	121.96	83.43	100.0	Z	80.0	20.0
0.037234	---	35.20	116.17	80.97	100.0	Z	2.0	20.0
0.037350	43.73	---	136.15	92.42	100.0	Z	4.0	20.0
0.062402	35.31	---	131.69	96.38	100.0	Z	179.0	20.0
0.062460	---	28.55	111.68	83.13	100.0	Z	2.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.127772	---	72.42	105.47	33.05	100.0	X	95.0	20.0
0.127772	72.47	---	125.47	53.00	100.0	X	95.0	20.0
0.326450	---	58.57	97.33	38.76	100.0	X	96.0	20.0
0.326600	58.75	---	117.32	58.57	100.0	X	96.0	20.0
0.383350	51.22	---	115.93	64.71	100.0	X	93.0	20.0
0.383350	---	50.85	95.93	45.08	100.0	X	93.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.127772	---	68.72	105.47	36.75	100.0	Y	180.0	20.0
0.127772	68.80	---	125.47	56.67	100.0	Y	180.0	20.0
0.326550	---	54.49	97.32	42.84	100.0	Y	356.0	20.0
0.326600	55.00	---	117.32	62.32	100.0	Y	356.0	20.0
0.383000	48.34	---	115.94	67.60	100.0	Y	185.0	20.0
0.383300	---	47.49	95.93	48.44	100.0	Y	185.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.127772	---	63.04	105.47	42.43	100.0	Z	92.0	20.0
0.127772	63.10	---	125.47	62.37	100.0	Z	92.0	20.0
0.288450	---	35.33	98.40	63.07	100.0	Z	32.0	20.0
0.289650	39.40	---	118.36	78.96	100.0	Z	32.0	20.0
0.326550	53.69	---	117.32	63.63	100.0	Z	63.0	20.0
0.326550	---	53.38	97.32	43.94	100.0	Z	63.0	20.0
0.382750	43.10	---	115.94	72.85	100.0	Z	98.0	20.0
0.383100	---	41.36	95.94	54.57	100.0	Z	98.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.051602	42.83	113.34	70.51	100.0	X	45.0	19.9
0.127843	63.76	105.46	41.71	100.0	X	135.0	19.9
0.255353	44.20	99.46	55.26	100.0	X	62.0	19.9
0.325588	54.77	97.35	42.57	100.0	X	333.0	19.9
0.382655	45.56	95.95	50.39	100.0	X	139.0	19.9
0.404603	44.08	95.46	51.39	100.0	X	66.0	19.9
0.650427	44.70	71.35	26.65	100.0	X	333.0	19.9
0.979655	40.18	67.80	27.62	100.0	X	333.0	19.9
1.304493	36.14	65.32	29.18	100.0	X	1.0	19.9
16.940625	27.34	69.50	42.16	100.0	X	37.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.035991	43.05	116.47	73.42	100.0	Y	135.0	19.9
0.127843	68.64	105.46	36.82	100.0	Y	185.0	19.9
0.325588	55.49	97.35	41.86	100.0	Y	142.0	19.9
0.382655	48.25	95.95	47.69	100.0	Y	174.0	19.9
0.650427	45.93	71.35	25.41	100.0	Y	160.0	19.9
0.979655	40.50	67.80	27.30	100.0	Y	160.0	19.9
1.304493	36.69	65.32	28.63	100.0	Y	160.0	19.9
1.629331	33.36	63.39	30.03	100.0	Y	160.0	19.9
14.693096	28.68	69.50	40.82	100.0	Y	66.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036999	42.82	116.23	73.41	100.0	Z	222.0	19.9
0.127843	62.96	105.46	42.51	100.0	Z	83.0	19.9
0.325588	53.90	97.35	43.45	100.0	Z	52.0	19.9
0.382655	43.13	95.95	52.82	100.0	Z	52.0	19.9
0.650427	43.56	71.35	27.79	100.0	Z	52.0	19.9
0.979655	38.72	67.80	29.08	100.0	Z	57.0	19.9
1.304493	35.03	65.32	30.29	100.0	Z	52.0	19.9
4.671397	30.11	69.50	39.39	100.0	Z	164.0	20.1

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
42.771667	14.47	40.00	25.53	100.0	H	313.0	-19.5
103.558333	22.23	43.50	21.27	100.0	H	345.0	-19.0
144.028889	28.81	43.50	14.70	100.0	H	284.0	-22.4
165.800000	29.14	43.50	14.36	100.0	H	117.0	-21.5
240.005000	27.28	46.00	18.72	100.0	H	213.0	-17.7
288.020000	29.30	46.00	16.70	100.0	H	276.0	-16.6
360.015556	33.96	46.00	12.04	100.0	H	321.0	-14.6
742.518889	26.41	46.00	19.59	100.0	H	255.0	-7.2

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
44.334444	25.10	40.00	14.90	100.0	V	0.0	-19.1
77.422222	23.09	40.00	16.91	100.0	V	115.0	-23.5
144.028889	23.15	43.50	20.35	100.0	V	327.0	-22.4
288.020000	24.43	46.00	21.57	100.0	V	234.0	-16.6
360.015556	26.93	46.00	19.07	100.0	V	220.0	-14.6
432.011111	24.99	46.00	21.01	100.0	V	291.0	-13.1
504.006667	23.11	46.00	22.89	100.0	V	304.0	-11.8
896.856667	26.10	46.00	19.90	100.0	V	6.0	-4.8


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Wireless charging (10W)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004158243-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.015711	47.40	---	143.66	96.26	100.0	X	224.0	20.0
0.015711	---	41.79	123.66	81.87	100.0	X	224.0	20.0
0.037234	---	36.96	116.17	79.21	100.0	X	346.0	20.0
0.037292	44.23	---	136.16	91.93	100.0	X	346.0	20.0
0.062576	---	31.95	111.67	79.71	100.0	X	259.0	20.0
0.062634	39.32	---	131.66	92.34	100.0	X	109.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019125	---	38.27	121.96	83.69	100.0	Y	107.0	20.0
0.019241	45.81	---	141.90	96.10	100.0	Y	160.0	20.0
0.032316	45.98	---	137.40	91.42	100.0	Y	172.0	20.0
0.032490	---	39.43	117.36	77.93	100.0	Y	119.0	20.0
0.064832	41.65	---	131.36	89.71	100.0	Y	172.0	20.0
0.065006	---	34.71	111.34	76.63	100.0	Y	83.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019125	---	38.81	121.96	83.15	100.0	Z	0.0	20.0
0.019241	47.38	---	141.90	94.53	100.0	Z	0.0	20.0
0.037292	---	35.64	116.16	80.52	100.0	Z	175.0	20.0
0.037292	43.33	---	136.16	92.83	100.0	Z	175.0	20.0
0.062460	---	29.97	111.68	81.72	100.0	Z	262.0	20.0
0.062518	36.94	---	131.67	94.73	100.0	Z	262.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.131029	---	71.28	105.25	33.97	100.0	X	85.0	20.0
0.131029	71.36	---	125.25	53.89	100.0	X	85.0	20.0
0.261750	48.88	---	119.24	70.36	100.0	X	89.0	20.0
0.261950	---	47.15	99.24	52.09	100.0	X	89.0	20.0
0.326500	58.33	---	117.32	58.99	100.0	X	56.0	20.0
0.326500	---	58.11	97.32	39.21	100.0	X	56.0	20.0
0.393150	---	47.98	95.71	47.73	100.0	X	70.0	20.0
0.393450	49.20	---	115.71	66.51	100.0	X	70.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.132229	---	66.99	105.17	38.18	100.0	Y	171.0	20.0
0.132229	67.09	---	125.17	58.08	100.0	Y	171.0	20.0
0.265700	44.25	---	119.11	74.86	100.0	Y	19.0	20.0
0.265950	---	42.07	99.11	57.04	100.0	Y	19.0	20.0
0.326500	---	51.73	97.32	45.59	100.0	Y	300.0	20.0
0.326550	52.32	---	117.32	65.01	100.0	Y	300.0	20.0
0.397750	45.96	---	115.61	69.66	100.0	Y	159.0	20.0
0.398450	---	44.55	95.60	51.04	100.0	Y	159.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.133457	---	64.42	105.09	40.67	100.0	Z	86.0	20.0
0.133457	64.54	---	125.09	60.55	100.0	Z	86.0	20.0
0.267150	41.27	---	119.07	77.79	100.0	Z	129.0	20.0
0.268450	---	38.13	99.02	60.89	100.0	Z	122.0	20.0
0.326450	53.53	---	117.33	63.80	100.0	Z	68.0	20.0
0.326500	---	53.14	97.32	44.19	100.0	Z	68.0	20.0
0.402100	---	42.32	95.52	53.20	100.0	Z	75.0	20.0
0.402300	43.33	---	115.51	72.19	100.0	Z	75.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.030251	48.05	117.98	69.93	100.0	X	47.0	19.9
0.062278	42.04	111.71	69.66	100.0	X	38.0	19.9
0.093600	39.47	108.17	68.70	100.0	X	38.0	19.9
0.133281	63.75	105.10	41.35	100.0	X	99.0	19.9
0.264133	45.60	99.17	53.57	100.0	X	149.0	19.9
0.325588	54.06	97.35	43.29	100.0	X	9.0	19.9
0.400213	45.31	95.56	50.25	100.0	X	23.0	19.9
0.650427	44.27	71.35	27.08	100.0	X	297.0	19.9
0.975265	39.83	67.84	28.01	100.0	X	9.0	19.9
1.304493	35.94	65.32	29.38	100.0	X	9.0	19.9
5.470324	28.86	69.50	40.64	100.0	X	167.0	20.1

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.032466	44.63	117.36	72.74	100.0	Y	186.0	19.9
0.132274	66.94	105.17	38.23	100.0	Y	174.0	19.9
0.264133	44.87	99.17	54.29	100.0	Y	178.0	19.9
0.325588	52.88	97.35	44.47	100.0	Y	135.0	19.9
0.395824	46.07	95.65	49.58	100.0	Y	336.0	19.9
0.650427	43.46	71.35	27.89	100.0	Y	135.0	19.9
0.975265	37.84	67.84	30.00	100.0	Y	311.0	19.9
1.304493	34.03	65.32	31.29	100.0	Y	135.0	19.9
15.601765	27.92	69.50	41.58	100.0	Y	340.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037099	41.47	116.20	74.73	100.0	Z	4.0	19.9
0.133483	64.41	105.09	40.68	100.0	Z	81.0	19.9
0.264133	41.65	99.17	57.52	100.0	Z	122.0	19.9
0.325588	53.96	97.35	43.39	100.0	Z	53.0	19.9
0.400213	43.67	95.56	51.89	100.0	Z	75.0	19.9
0.650427	43.77	71.35	27.58	100.0	Z	53.0	19.9
0.979655	38.85	67.80	28.95	100.0	Z	53.0	19.9
1.304493	35.87	65.32	29.45	100.0	Z	53.0	19.9
29.064993	29.53	69.50	39.97	100.0	Z	291.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.058889	15.82	40.00	24.18	100.0	H	193.0	-18.8
100.917778	22.63	43.50	20.87	100.0	H	358.0	-19.1
144.028889	27.48	43.50	16.02	100.0	H	71.0	-22.4
187.463333	26.63	43.50	16.87	100.0	H	124.0	-19.9
240.005000	27.21	46.00	18.79	100.0	H	39.0	-17.7
288.020000	30.22	46.00	15.78	100.0	H	23.0	-16.6
360.015556	34.29	46.00	11.71	100.0	H	48.0	-14.6
890.228333	29.92	46.00	16.08	100.0	H	88.0	-4.9

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.873889	25.19	40.00	14.81	100.0	V	72.0	-21.6
78.230556	25.58	40.00	14.42	100.0	V	105.0	-23.5
143.975000	22.47	43.50	21.03	100.0	V	349.0	-22.4
288.020000	24.82	46.00	21.18	100.0	V	349.0	-16.6
360.015556	27.19	46.00	18.81	100.0	V	228.0	-14.6
948.697778	26.83	46.00	19.17	100.0	V	343.0	-4.3


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Wireless charging (15W)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004158243-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.015943	47.07	---	143.54	96.46	100.0	X	90.0	20.0
0.015943	---	40.88	123.54	82.66	100.0	X	90.0	20.0
0.036887	46.47	---	136.25	89.79	100.0	X	30.0	20.0
0.037292	---	37.93	116.16	78.23	100.0	X	9.0	20.0
0.078718	40.18	---	129.67	89.50	100.0	X	66.0	20.0
0.078834	---	29.48	109.66	80.18	100.0	X	66.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019183	47.15	---	141.93	94.78	100.0	Y	158.0	20.0
0.019183	---	39.19	121.93	82.74	100.0	Y	158.0	20.0
0.037234	49.02	---	136.17	87.15	100.0	Y	299.0	20.0
0.038739	---	39.43	115.83	76.40	100.0	Y	192.0	20.0
0.078660	---	33.28	109.68	76.40	100.0	Y	198.0	20.0
0.078834	41.33	---	129.66	88.33	100.0	Y	181.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019067	46.86	---	141.98	95.12	100.0	Z	0.0	20.0
0.019125	---	38.46	121.96	83.50	100.0	Z	171.0	20.0
0.037003	43.98	---	136.23	92.25	100.0	Z	178.0	20.0
0.037292	---	36.44	116.16	79.72	100.0	Z	184.0	20.0
0.062518	35.11	---	131.67	96.56	100.0	Z	45.0	20.0
0.062518	---	28.56	111.67	83.11	100.0	Z	45.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.326550	59.76	---	117.32	57.57	100.0	X	48.0	20.0
0.326550	---	59.61	97.32	37.72	100.0	X	48.0	20.0
0.360050	---	63.13	96.48	33.35	100.0	X	115.0	20.0
0.360100	63.29	---	116.47	53.19	100.0	X	115.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.326500	55.36	---	117.32	61.96	100.0	Y	325.0	20.0
0.326500	---	55.17	97.32	42.15	100.0	Y	325.0	20.0
0.360000	---	59.18	96.48	37.29	100.0	Y	194.0	20.0
0.360050	59.37	---	116.48	57.11	100.0	Y	194.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.326600	53.94	---	117.32	63.38	100.0	Z	65.0	20.0
0.326600	---	53.28	97.32	44.04	100.0	Z	65.0	20.0
0.360050	---	58.97	96.48	37.50	100.0	Z	23.0	20.0
0.360050	59.18	---	116.48	57.29	100.0	Z	23.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.041329	48.41	115.27	66.86	100.0	X	41.0	19.9
0.078090	43.22	109.74	66.52	100.0	X	46.0	19.9
0.325588	58.88	97.35	38.47	100.0	X	63.0	19.9
0.356316	60.18	96.57	36.39	100.0	X	135.0	19.9
0.650427	48.69	71.35	22.66	100.0	X	63.0	19.9
0.716272	42.71	70.51	27.80	100.0	X	30.0	19.9
0.979655	45.36	67.80	22.44	100.0	X	63.0	19.9
1.304493	39.54	65.32	25.78	100.0	X	34.0	19.9
2.516052	34.70	69.50	34.80	100.0	X	357.0	20.0
3.235963	32.79	69.50	36.71	100.0	X	8.0	20.0

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036898	46.47	116.25	69.78	100.0	Y	177.0	19.9
0.078493	40.75	109.70	68.95	100.0	Y	120.0	19.9
0.325588	55.48	97.35	41.87	100.0	Y	333.0	19.9
0.356316	59.35	96.57	37.22	100.0	Y	195.0	19.9
0.650427	45.28	71.35	26.06	100.0	Y	127.0	19.9
0.716272	39.69	70.51	30.82	100.0	Y	258.0	19.9
0.979655	40.77	67.80	27.02	100.0	Y	333.0	19.9
1.076228	41.57	66.99	25.42	100.0	Y	215.0	19.9
1.796140	36.05	69.50	33.45	100.0	Y	174.0	20.0
2.516052	34.83	69.50	34.67	100.0	Y	297.0	20.0
3.235963	32.71	69.50	36.79	100.0	Y	138.0	20.0
19.798324	34.18	69.50	35.32	100.0	Y	323.0	20.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036898	41.86	116.25	74.40	100.0	Z	155.0	19.9
0.325588	53.54	97.35	43.81	100.0	Z	42.0	19.9
0.356316	59.25	96.57	37.31	100.0	Z	4.0	19.9
0.650427	43.63	71.35	27.71	100.0	Z	42.0	19.9
0.720662	36.31	70.46	34.15	100.0	Z	339.0	19.9
0.975265	38.87	67.84	28.96	100.0	Z	24.0	19.9
1.076228	38.73	66.99	28.26	100.0	Z	17.0	19.9
1.304493	34.80	65.32	30.52	100.0	Z	42.0	19.9
1.800530	31.00	69.50	38.50	100.0	Z	306.0	20.0
28.735765	29.53	69.50	39.97	100.0	Z	272.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.358333	17.88	40.00	22.12	100.0	H	349.0	-18.9
78.446111	30.84	40.00	9.16	100.0	H	188.0	-23.6
115.575556	33.97	43.50	9.53	100.0	H	225.0	-20.0
147.962778	36.26	43.50	7.24	100.0	H	261.0	-22.3
246.956667	38.22	46.00	7.78	100.0	H	238.0	-17.5
338.406111	41.89	46.00	4.11	100.0	H	197.0	-15.1
742.518889	24.06	46.00	21.94	100.0	H	0.0	-7.2

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.382778	24.45	40.00	15.55	100.0	V	101.0	-21.0
78.446111	34.99	40.00	5.01	100.0	V	110.0	-23.6
150.118333	29.08	43.50	14.42	100.0	V	357.0	-22.3
313.186111	31.97	46.00	14.03	100.0	V	357.0	-15.9
873.900000	25.64	46.00	20.36	100.0	V	110.0	-5.1


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Wireless charging (TWS 5W)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004158243-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.015943	47.18	---	143.54	96.36	100.0	X	15.0	20.0
0.016001	---	40.34	123.51	83.17	100.0	X	88.0	20.0
0.037234	---	36.15	116.17	80.02	100.0	X	153.0	20.0
0.037292	44.72	---	136.16	91.44	100.0	X	153.0	20.0
0.062518	35.15	---	131.67	96.52	100.0	X	9.0	20.0
0.062518	---	29.21	111.67	82.46	100.0	X	9.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019183	46.61	---	141.93	95.32	100.0	Y	60.0	20.0
0.019183	---	38.40	121.93	83.53	100.0	Y	60.0	20.0
0.036945	43.66	---	136.24	92.58	100.0	Y	294.0	20.0
0.037234	---	36.16	116.17	80.01	100.0	Y	322.0	20.0
0.062518	36.25	---	131.67	95.42	100.0	Y	329.0	20.0
0.062518	---	29.10	111.67	82.57	100.0	Y	329.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019125	---	38.67	121.96	83.28	100.0	Z	320.0	20.0
0.019183	47.84	---	141.93	94.09	100.0	Z	320.0	20.0
0.037234	---	35.73	116.17	80.45	100.0	Z	170.0	20.0
0.037234	43.41	---	136.17	92.76	100.0	Z	170.0	20.0
0.062518	34.52	---	131.67	97.15	100.0	Z	259.0	20.0
0.062518	---	28.21	111.67	83.46	100.0	Z	259.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.147543	66.27	---	124.22	57.95	100.0	X	24.0	20.0
0.147543	---	66.08	104.22	38.14	100.0	X	24.0	20.0
0.326550	---	59.46	97.32	37.86	100.0	X	56.0	20.0
0.326550	59.68	---	117.32	57.65	100.0	X	56.0	20.0
0.442450	47.27	---	114.69	67.41	100.0	X	34.0	20.0
0.442550	---	46.37	94.68	48.32	100.0	X	34.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.147543	58.20	---	124.22	66.02	100.0	Y	112.0	20.0
0.147543	---	57.94	104.22	46.28	100.0	Y	112.0	20.0
0.326550	---	54.97	97.32	42.35	100.0	Y	159.0	20.0
0.326600	55.40	---	117.32	61.93	100.0	Y	159.0	20.0
0.442700	---	40.05	94.68	54.64	100.0	Y	102.0	20.0
0.442900	41.77	---	114.68	72.90	100.0	Y	102.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.147543	---	63.76	104.22	40.46	100.0	Z	36.0	20.0
0.147543	63.98	---	124.22	60.24	100.0	Z	36.0	20.0
0.326450	---	53.29	97.33	44.03	100.0	Z	56.0	20.0
0.326700	53.61	---	117.32	63.71	100.0	Z	56.0	20.0
0.442700	47.10	---	114.68	67.58	100.0	Z	9.0	20.0
0.442700	---	46.18	94.68	48.50	100.0	Z	9.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.035991	43.20	116.47	73.26	100.0	X	254.0	19.9
0.147583	63.65	104.22	40.57	100.0	X	266.0	19.9
0.325588	54.76	97.35	42.59	100.0	X	349.0	19.9
0.404603	44.76	95.46	50.70	100.0	X	71.0	19.9
0.439721	46.40	94.74	48.34	100.0	X	49.0	19.9
0.650427	44.92	71.35	26.43	100.0	X	349.0	19.9
0.738221	35.38	70.25	34.87	100.0	X	67.0	19.9
0.975265	40.71	67.84	27.13	100.0	X	349.0	19.9
1.304493	36.14	65.32	29.18	100.0	X	349.0	19.9
1.629331	31.42	63.39	31.98	100.0	X	302.0	19.9
10.588721	28.70	69.50	40.80	100.0	X	204.0	20.2

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037200	43.40	116.18	72.78	100.0	Y	119.0	19.9
0.147583	58.14	104.22	46.08	100.0	Y	102.0	19.9
0.325588	55.30	97.35	42.05	100.0	Y	147.0	19.9
0.439721	41.27	94.74	53.47	100.0	Y	298.0	19.9
0.650427	46.02	71.35	25.33	100.0	Y	147.0	19.9
0.979655	40.99	67.80	26.81	100.0	Y	147.0	19.9
1.304493	36.45	65.32	28.86	100.0	Y	147.0	19.9
1.629331	32.95	63.39	30.44	100.0	Y	324.0	19.9
10.917949	28.04	69.50	41.46	100.0	Y	259.0	20.2

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037301	43.11	116.16	73.05	100.0	Z	337.0	19.9
0.147583	63.94	104.22	40.28	100.0	Z	0.0	19.9
0.325588	53.53	97.35	43.81	100.0	Z	62.0	19.9
0.439721	46.92	94.74	47.82	100.0	Z	58.0	19.9
0.650427	43.37	71.35	27.97	100.0	Z	85.0	19.9
0.979655	38.82	67.80	28.98	100.0	Z	85.0	19.9
1.304493	33.84	65.32	31.48	100.0	Z	85.0	19.9
1.629331	30.83	63.39	32.56	100.0	Z	85.0	19.9
29.060603	28.13	69.50	41.37	100.0	Z	315.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
45.412222	16.31	40.00	23.69	100.0	H	314.0	-18.9
104.097222	19.52	43.50	23.98	100.0	H	176.0	-18.9
163.375000	25.39	43.50	18.11	100.0	H	152.0	-21.6
260.536667	27.01	46.00	18.99	100.0	H	54.0	-17.1
359.961667	32.69	46.00	13.31	100.0	H	54.0	-14.6
432.011111	27.88	46.00	18.12	100.0	H	83.0	-13.1
938.405000	25.67	46.00	20.33	100.0	H	306.0	-4.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.550556	24.50	40.00	15.50	100.0	V	36.0	-21.8
71.979444	19.51	40.00	20.49	100.0	V	108.0	-22.6
95.367222	20.17	43.50	23.33	100.0	V	36.0	-19.8
165.530556	15.44	43.50	28.06	100.0	V	120.0	-21.5
288.020000	18.87	46.00	27.13	100.0	V	87.0	-16.6
357.698333	28.33	46.00	17.67	100.0	V	256.0	-14.7
432.011111	21.80	46.00	24.20	100.0	V	270.0	-13.1
873.846111	27.26	46.00	18.74	100.0	V	219.0	-5.1


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Wireless charging (Watch 5W_326kHz)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004158243-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.015943	47.62	---	143.54	95.91	100.0	X	231.0	20.0
0.016001	---	41.13	123.51	82.38	100.0	X	231.0	20.0
0.037003	43.57	---	136.23	92.65	100.0	X	0.0	20.0
0.037234	---	36.07	116.17	80.11	100.0	X	115.0	20.0
0.062518	34.21	---	131.67	97.47	100.0	X	196.0	20.0
0.062518	---	27.19	111.67	84.49	100.0	X	196.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019183	---	39.43	121.93	82.50	100.0	Y	328.0	20.0
0.019241	46.77	---	141.90	95.13	100.0	Y	328.0	20.0
0.037234	44.30	---	136.17	91.87	100.0	Y	168.0	20.0
0.037292	---	35.66	116.16	80.50	100.0	Y	168.0	20.0
0.062576	---	28.75	111.67	82.92	100.0	Y	280.0	20.0
0.062691	35.21	---	131.65	96.44	100.0	Y	249.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.019125	---	38.33	121.96	83.63	100.0	Z	4.0	20.0
0.019183	47.99	---	141.93	93.94	100.0	Z	4.0	20.0
0.036251	43.03	---	136.41	93.38	100.0	Z	218.0	20.0
0.037234	---	36.38	116.17	79.79	100.0	Z	188.0	20.0
0.062402	34.71	---	131.69	96.98	100.0	Z	262.0	20.0
0.062460	---	26.87	111.68	84.81	100.0	Z	224.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.125114	---	24.79	105.65	80.86	100.0	X	149.0	20.0
0.125143	30.52	---	125.65	95.12	100.0	X	318.0	20.0
0.286650	---	39.18	98.45	59.27	100.0	X	35.0	20.0
0.287100	42.35	---	118.44	76.09	100.0	X	35.0	20.0
0.326450	50.67	---	117.33	66.66	100.0	X	35.0	20.0
0.326450	---	48.84	97.33	48.48	100.0	X	35.0	20.0
0.374750	38.60	---	116.13	77.53	100.0	X	343.0	20.0
0.375300	---	35.80	96.12	60.31	100.0	X	343.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.326450	51.24	---	117.33	66.08	100.0	Y	70.0	20.0
0.326500	---	50.91	97.32	46.41	100.0	Y	70.0	20.0
0.375600	39.22	---	116.11	76.89	100.0	Y	0.0	20.0
0.375750	---	35.12	96.11	60.98	100.0	Y	0.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin




Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Average (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.125057	30.70	---	125.66	94.95	100.0	Z	72.0	20.0
0.125057	---	25.13	105.66	80.52	100.0	Z	72.0	20.0
0.326100	41.99	---	117.34	75.34	100.0	Z	0.0	20.0
0.326550	---	40.85	97.32	56.47	100.0	Z	0.0	20.0
0.375000	38.26	---	116.12	77.86	100.0	Z	359.0	20.0
0.375350	---	34.89	96.11	61.22	100.0	Z	359.0	20.0

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036898	43.09	116.25	73.16	100.0	X	102.0	19.9
0.325588	54.23	97.35	43.12	100.0	X	26.0	19.9
0.404603	44.29	95.46	51.17	100.0	X	62.0	19.9
0.650427	43.32	71.35	28.02	100.0	X	0.0	19.9
0.975265	37.40	67.84	30.44	100.0	X	359.0	19.9
1.304493	32.87	65.32	32.45	100.0	X	350.0	19.9
28.573346	33.19	69.50	36.31	100.0	X	62.0	20.6

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037200	43.42	116.18	72.76	100.0	Y	66.0	19.9
0.325588	51.13	97.35	46.22	100.0	Y	103.0	19.9
0.650427	39.91	71.35	31.44	100.0	Y	103.0	19.9
0.979655	34.98	67.80	32.82	100.0	Y	92.0	19.9
1.357169	31.02	64.98	33.95	100.0	Y	268.0	19.9
13.714191	29.89	69.50	39.61	100.0	Y	0.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036898	40.73	116.25	75.52	100.0	Z	74.0	19.9
0.325588	42.63	97.35	54.72	100.0	Z	352.0	19.9
0.650427	34.46	71.35	36.89	100.0	Z	316.0	19.9
1.357169	31.65	64.98	33.33	100.0	Z	345.0	19.9
1.976118	29.33	69.50	40.17	100.0	Z	357.0	20.0
29.389831	32.04	69.50	37.46	100.0	Z	306.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
40.454444	17.36	40.00	22.64	100.0	H	163.0	-20.1
102.157222	19.00	43.50	24.50	100.0	H	259.0	-19.0
161.111667	26.18	43.50	17.32	100.0	H	86.0	-21.7
183.583333	25.77	43.50	17.73	100.0	H	108.0	-20.2
288.020000	25.08	46.00	20.92	100.0	H	170.0	-16.6
360.015556	28.91	46.00	17.09	100.0	H	319.0	-14.6
936.950000	26.66	46.00	19.34	100.0	H	78.0	-4.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
36.897778	35.61	40.00	4.39	100.0	V	355.0	-21.2
71.979444	20.77	40.00	19.23	100.0	V	279.0	-22.6
91.810556	19.13	43.50	24.37	100.0	V	134.0	-20.6
160.842222	18.07	43.50	25.43	100.0	V	142.0	-21.7
183.529444	17.58	43.50	25.92	100.0	V	26.0	-20.2
250.297778	18.46	46.00	27.54	100.0	V	81.0	-17.4
288.020000	19.27	46.00	26.73	100.0	V	73.0	-16.6
360.015556	27.47	46.00	18.53	100.0	V	219.0	-14.6
504.006667	23.63	46.00	22.37	100.0	V	249.0	-11.8
938.405000	27.39	46.00	18.61	100.0	V	51.0	-4.4


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Wireless charging (Watch 5W_1.778MHz)

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Charging
Order No/Sample No:	168589306/A004216141-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037099	46.74	116.20	69.47	100.0	X	315.0	19.9
0.404603	44.67	95.46	50.79	100.0	X	60.0	19.9
1.554706	48.20	63.80	15.60	100.0	X	190.0	20.0
1.774191	54.93	69.50	14.57	100.0	X	190.0	20.0
1.998066	37.26	69.50	32.24	100.0	X	190.0	20.0
29.113279	50.98	69.50	18.52	100.0	X	151.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.023805	45.94	120.06	74.12	100.0	Y	141.0	19.9
0.286081	42.08	98.47	56.39	100.0	Y	116.0	19.9
0.373875	39.44	96.15	56.70	100.0	Y	182.0	19.9
1.554706	48.64	63.80	15.16	100.0	Y	246.0	20.0
1.774191	61.58	69.50	7.92	100.0	Y	257.0	20.0
1.998066	38.46	69.50	31.04	100.0	Y	246.0	20.0
5.329853	35.21	69.50	34.29	100.0	Y	29.0	20.1
29.113279	44.57	69.50	24.93	100.0	Y	174.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037200	41.24	116.18	74.94	100.0	Z	288.0	19.9
0.220235	41.06	100.74	59.68	100.0	Z	247.0	19.8
0.373875	38.56	96.15	57.59	100.0	Z	114.0	19.9
1.554706	43.74	63.80	20.06	100.0	Z	157.0	20.0
1.774191	56.50	69.50	13.00	100.0	Z	179.0	20.0
1.998066	34.91	69.50	34.59	100.0	Z	161.0	20.0
29.113279	48.81	69.50	20.69	100.0	Z	200.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
40.454444	17.08	40.00	22.92	100.0	H	140.0	-20.1
81.032778	20.03	40.00	19.97	100.0	H	263.0	-23.4
166.015556	25.53	43.50	17.97	100.0	H	58.0	-21.5
287.966111	23.69	46.00	22.31	100.0	H	179.0	-16.6
356.458889	32.92	46.00	13.08	100.0	H	163.0	-14.7
432.011111	26.71	46.00	19.29	100.0	H	91.0	-13.1
890.713333	27.61	46.00	18.39	100.0	H	232.0	-4.9

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
35.873889	26.43	40.00	13.57	100.0	V	60.0	-21.6
60.339444	22.73	40.00	17.27	100.0	V	174.0	-19.2
91.810556	19.67	43.50	23.83	100.0	V	142.0	-20.6
162.189444	17.90	43.50	25.60	100.0	V	134.0	-21.7
288.020000	18.42	46.00	27.58	100.0	V	102.0	-16.6
360.015556	27.51	46.00	18.49	100.0	V	197.0	-14.6
504.006667	23.15	46.00	22.85	100.0	V	271.0	-11.8
938.458889	27.40	46.00	18.60	100.0	V	102.0	-4.4


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Wireless charging (Co-location)

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004216141-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.029747	47.23	118.12	70.89	100.0	X	36.0	19.9
0.127843	67.94	105.46	37.53	100.0	X	92.0	19.9
0.146072	66.53	104.31	37.78	100.0	X	314.0	19.9
0.382655	47.17	95.95	48.77	100.0	X	89.0	19.9
0.435331	48.25	94.83	46.58	100.0	X	34.0	19.9
1.554706	46.71	63.80	17.09	100.0	X	185.0	20.0
1.774191	53.67	69.50	15.83	100.0	X	185.0	20.0
1.998066	35.65	69.50	33.85	100.0	X	185.0	20.0
29.113279	45.96	69.50	23.54	100.0	X	131.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036999	46.88	116.23	69.35	100.0	Y	242.0	19.9
0.075371	40.71	110.05	69.34	100.0	Y	107.0	19.9
0.127843	65.56	105.46	39.91	100.0	Y	193.0	19.9
0.146072	58.91	104.31	45.40	100.0	Y	103.0	19.9
0.286081	43.13	98.47	55.34	100.0	Y	326.0	19.9
0.382655	45.97	95.95	49.98	100.0	Y	199.0	19.9
0.435331	42.02	94.83	52.81	100.0	Y	285.0	19.9
0.637258	37.03	71.52	34.49	100.0	Y	156.0	19.9
1.554706	48.96	63.80	14.84	100.0	Y	271.0	20.0
1.774191	60.93	69.50	8.57	100.0	Y	264.0	20.0
1.998066	38.00	69.50	31.50	100.0	Y	256.0	20.0
5.329853	34.94	69.50	34.56	100.0	Y	62.0	20.1
29.113279	47.98	69.50	21.52	100.0	Y	0.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036898	42.66	116.25	73.59	100.0	Z	78.0	19.9
0.127843	62.97	105.46	42.50	100.0	Z	91.0	19.9
0.147583	64.31	104.22	39.91	100.0	Z	21.0	19.9
0.325588	54.47	97.35	42.88	100.0	Z	156.0	19.9
0.382655	43.72	95.95	52.23	100.0	Z	92.0	19.9
0.439721	47.06	94.74	47.68	100.0	Z	3.0	19.9
0.650427	49.06	71.35	22.29	100.0	Z	153.0	19.9
0.979655	36.74	67.80	31.06	100.0	Z	153.0	19.9
1.554706	44.04	63.80	19.76	100.0	Z	178.0	20.0
1.774191	56.72	69.50	12.78	100.0	Z	185.0	20.0
29.113279	51.42	69.50	18.08	100.0	Z	13.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
40.454444	22.70	40.00	17.30	100.0	H	0.0	-20.1
70.201111	22.76	40.00	17.24	100.0	H	122.0	-22.0
134.275000	24.41	43.50	19.09	100.0	H	349.0	-22.1
163.051667	24.61	43.50	18.89	100.0	H	0.0	-21.6
319.329444	34.21	46.00	11.79	100.0	H	166.0	-15.7
566.086667	29.11	46.00	16.89	100.0	H	0.0	-10.4
936.950000	27.48	46.00	18.52	100.0	H	341.0	-4.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Charging
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
36.897778	33.27	40.00	6.73	100.0	V	88.0	-21.2
77.745556	36.49	40.00	3.51	100.0	V	150.0	-23.5
160.896111	28.04	43.50	15.46	100.0	V	348.0	-21.7
313.940556	31.47	46.00	14.53	100.0	V	358.0	-15.9
380.547222	29.93	46.00	16.07	100.0	V	172.0	-14.2
936.950000	26.18	46.00	19.82	100.0	V	110.0	-4.4


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Standby mode

EUT Information

EUT Name:	3-in-1 Wireless Charger
Model:	W707
Test Mode:	Standby
Order No/Sample No:	168589306/A004216141-001
Test Voltage:	Adaptor
Remark:	Temp 22 Humi:55%
Test Standard:	FCC Part 15C
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037099	44.88	116.20	71.33	100.0	X	320.0	19.9
0.325588	58.73	97.35	38.62	100.0	X	76.0	19.9
0.404603	43.90	95.46	51.56	100.0	X	65.0	19.9
0.650427	48.59	71.35	22.75	100.0	X	76.0	19.9
0.979655	43.44	67.80	24.36	100.0	X	76.0	19.9
1.304493	39.67	65.32	25.65	100.0	X	76.0	19.9
1.629331	34.22	63.39	29.17	100.0	X	76.0	19.9
17.138162	29.02	69.50	40.48	100.0	X	8.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Standby
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.037099	43.37	116.20	72.83	100.0	Y	20.0	19.9
0.325588	55.78	97.35	41.57	100.0	Y	138.0	19.9
0.650427	45.62	71.35	25.72	100.0	Y	138.0	19.9
0.979655	40.81	67.80	26.99	100.0	Y	138.0	19.9
1.304493	36.56	65.32	28.76	100.0	Y	138.0	19.9
1.629331	31.87	63.39	31.52	100.0	Y	138.0	19.9
16.602618	28.63	69.50	40.87	100.0	Y	224.0	20.3

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Standby
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
0.036999	40.96	116.23	75.27	100.0	Z	86.0	19.9
0.325588	54.55	97.35	42.80	100.0	Z	88.0	19.9
0.369485	38.17	96.25	58.08	100.0	Z	256.0	19.9
0.650427	43.48	71.35	27.86	100.0	Z	88.0	19.9
0.979655	38.67	67.80	29.12	100.0	Z	88.0	19.9
1.304493	34.17	65.32	31.15	100.0	Z	47.0	19.9
1.629331	30.54	63.39	32.85	100.0	Z	47.0	19.9
28.735765	28.38	69.50	41.12	100.0	Z	29.0	20.5

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Standby
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs


Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
46.005000	15.66	40.00	24.34	100.0	H	320.0	-18.8
99.355000	20.21	43.50	23.29	100.0	H	22.0	-19.2
166.500556	25.23	43.50	18.27	100.0	H	151.0	-21.5
216.024444	23.60	46.00	22.40	100.0	H	180.0	-18.7
319.814444	28.21	46.00	17.79	100.0	H	39.0	-15.7
360.015556	28.93	46.00	17.07	100.0	H	75.0	-14.6
742.518889	25.86	46.00	20.14	100.0	H	229.0	-7.2
936.950000	27.55	46.00	18.45	100.0	H	75.0	-4.4

Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

EUT Information

EUT Name: 3-in-1 Wireless Charger
Model: W707
Test Mode: Standby
Order No/Sample No: 168589306/A004158243-001
Test Voltage: Adaptor
Remark: Temp 22 Humi:55%
Test Standard: FCC Part 15C
Tested By: Kei Zhang
Reviewed By: Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
34.850000	25.38	40.00	14.62	100.0	V	218.0	-22.0
71.979444	20.06	40.00	19.94	100.0	V	294.0	-22.6
91.648889	19.41	43.50	24.09	100.0	V	132.0	-20.7
164.883889	18.51	43.50	24.99	100.0	V	100.0	-21.6
233.969444	17.97	46.00	28.03	100.0	V	285.0	-18.0
329.137222	29.95	46.00	16.05	100.0	V	358.0	-15.3
360.015556	28.23	46.00	17.77	100.0	V	188.0	-14.6
405.120556	26.76	46.00	19.24	100.0	V	100.0	-13.6
504.006667	25.63	46.00	20.37	100.0	V	254.0	-11.8
938.405000	26.90	46.00	19.10	100.0	V	67.0	-4.4


Final Result

Frequency (MHz)	QuasiPeak (dBμV/m)	Limit (dBμV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Appendix A.3: Test Results of Conducted Emission on AC Mains

EUT Information

EUT Name:	3-in-1 Wireless Charger
Order Number:	168589306 110(P02146306)
Model:	W707
Test Mode:	Wireless Charging, MPP, 15W + TWS 5W + Watch 5W
Test Voltage:	AC 120V/ 60Hz
Test Standard:	FCC Part 15 C
Test By:/Review By:	Junhua Sun/ Charlie Zha
Tem./Hum./Pressure:	24.0°C/52.1%/101kPa
Remark:	SR 3



Critical Freqs


Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150	52.6	---	66.00	13.36	L1	9.5
0.155	---	38.3	55.73	17.38	L1	9.6
0.356	40.6	---	58.81	18.24	L1	9.6
0.359	---	32.2	48.75	16.60	L1	9.6
0.687	36.9	---	56.00	19.08	L1	9.7
0.690	---	27.5	46.00	18.50	L1	9.7
1.799	---	33.6	46.00	12.45	L1	9.6
1.799	38.6	---	56.00	17.43	L1	9.6
2.518	39.5	---	56.00	16.47	L1	9.6
2.518	---	34.5	46.00	11.53	L1	9.6
4.680	38.1	---	56.00	17.92	L1	9.7
4.680	---	33.9	46.00	12.11	L1	9.7

Final Result

[illegible]

EUT Information

EUT Name: 3-in-1 Wireless Charger
Order Number: 168589306 110(P02146306)
Model: W707
Test Mode: Wireless Charging, MPP, 15W + TWS 5W + Watch 5W
Test Voltage: AC 120V/ 60Hz
Test Standard: FCC Part 15 C
Test By:/Review By: Junhua Sun/ Charlie Zha
Tem./Hum./Pressure: 24.0°C/52.1%/101kPa
Remark: SR 3



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150	---	41.1	56.00	14.91	N	9.7
0.152	54.6	---	65.86	11.23	N	9.7
0.359	---	35.8	48.75	12.98	N	9.9
0.359	42.1	---	58.75	16.66	N	9.9
0.680	---	33.2	46.00	12.84	N	9.9
0.680	42.4	---	56.00	13.55	N	9.9
1.799	---	33.2	46.00	12.78	N	9.9
1.799	40.4	---	56.00	15.58	N	9.9
3.239	---	35.2	46.00	10.81	N	9.8
3.239	42.3	---	56.00	13.67	N	9.8
4.680	43.0	---	56.00	13.02	N	9.7
4.680	---	36.4	46.00	9.59	N	9.7

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
4.680	---	36.0	46.00	9.99	1000.0	9.0	N	9.7
4.680	40.2	---	56.00	15.78	1000.0	9.0	N	9.7