

TEST REPORT

Report No.: BCTC2507165890-1E

Applicant: Ugreen Group Limited

Product Name: 3-in-1 Wireless Charger

Test Model: CD278

Tested Date: 2025-07-28 to 2025-08-19

Issued Date: 2025-08-19



Shenzhen **BCTC** Testing Co., Ltd.



FCC ID:2AQI5-CD278C

Product Name: 3-in-1 Wireless Charger

Trademark: **UGREEN**

Model/Type Reference: CD278

Prepared For: Ugreen Group Limited

Address: Ugreen Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, China

Manufacturer: Ugreen Group Limited

Address: Ugreen Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-07-28

Sample Tested Date: 2025-07-28 to 2025-08-19

Issue Date: 2025-08-19

Report No.: BCTC2507165890-1E

Test Standards: FCC Part15.209
ANSI C63.10:2013

Test Results: PASS

Tested by:



Kelsey Tan/ Project Handler

Approved by:



Zero Zhou/Reviewer

The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	4
2. Test Summary	5
3. Measurement Uncertainty	6
4. Product Information And Test Setup	7
4.1 Product Information	7
4.2 Support Equipment	7
4.3 Test Setup Configuration	8
4.4 Test Mode	9
5. Test Facility And Test Instrument Used	10
5.1 Test Facility	10
5.2 Test Instrument Used	10
6. Conducted Emissions	12
6.1 Block Diagram Of Test Setup	12
6.2 Limit	12
6.3 Test procedure	12
6.4 EUT operating Conditions	12
6.5 Test Result	13
7. Radiated Emissions	15
7.1 Block Diagram Of Test Setup	15
7.2 Limit	16
7.3 Test procedure	16
7.4 Test Result	17
8. Bandwidth Test	31
8.1 Test Procedure	31
8.2 Test Setup	31
8.3 Test Result	32
9. Antenna Requirements	35
9.1 Limit	35
9.2 Test Result	35
10. EUT Photographs	36
11. EUT Test Setup Photographs	37

(Note: N/A Means Not Applicable)

1. Version

Report No.	Issue Date	Description	Approved
BCTC2507165890-1E	2025-08-19	Original	Valid

TEC
TC
OVER
t See

2. Test Summary

The Product has been tested according to the following specifications:

No.	Test Parameter	Clause No.	Results
1	Conducted Emission	15.207	PASS
2	Radiated Emission	15.209	PASS
3	20dB Bandwidth	15.215	PASS
4	Antenna Requirement	15.203	PASS



3. Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the Product as specified in CISPR 16-4-2. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

No.	Item	Uncertainty
1	3m chamber Radiated spurious emission(30MHz-1GHz)	U=4.3dB
2	Conducted Emission (150kHz-30MHz)	U=3.2dB
3	humidity uncertainty	U=5.3%
4	Temperature uncertainty	U=0.59°C

CO., LTD.

4. Product Information And Test Setup

4.1 Product Information

Model/Type Reference: CD278

P/N code Differences: All the P/N code and test models are the same circuit and RF module, except for the sales platform.

Hardware Version: CD278-A-A4-20221024

Software Version: 0x1491

Operation Frequency: Phone:5W+7.5W: 110.1kHz-205kHz
15W: 360kHz
Airpods: 110.1kHz-205kHz
Watch:3W:326.5kHz
5W:1.778MHz

Modulation: FSK

Antenna installation: loop coil antenna

Ratings: Input: 5.0V---3.0A/9.0V---3.0A/12V---2.5A
Wireless Charging Output: 25.0W Max(iPhone:15.0W,Apple Watch/AirPods:5.0W)

Remark:

- P/N code in the below table, for marketing purpose, will be marked on the marking plate.

90326	90326P	90326X	90326A	90326B	90326U	90326JP	90326ZD	90326T
35568	35568P	35568	35568A	35568B	35568U	35568JP	35568ZD	35568T

4.2 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	3-in-1 Wireless Charger	UGREEN	CD278	N/A	EUT
E-2	Adapter	UGREEN	CD289	N/A	Auxiliary
E-3	Dummy load	N/A	DL01	N/A	Auxiliary
E-4	Wireless earphone	N/A	DL01	N/A	Auxiliary
E-5	Dummy load	N/A	DL01	N/A	Auxiliary

Notes:


1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

4.3 Test Setup Configuration

See test photographs attached in *EUT TEST SETUP PHOTOGRAPHS* for the actual connections between Product and support equipment.


Conducted Emission:

Test Mode 1, 2,3




Radiated Spurious Emission:


Test Mode 1, 2, 3




Test Mode 4, 5, 6



Test Mode 7, 8



Test Mode 9



4.4 Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

AC Mode	Mode 1	Phone:5W+ AirPods:5W+Watch:5W
	Mode 2	Phone:7.5W+ AirPods:5W+Watch:5W
	Mode 3	Phone:15W+ AirPods:5W+Watch:5W
	Mode 4	Phone:5W+ AirPods:5W+Watch:3W
	Mode 5	Phone:7.5W+ AirPods:5W+Watch:3W
	Mode 6	Phone:15W+ AirPods:5W+Watch:3W
	Mode 7	Phone:5W+Airpods:5W
	Mode 8	Phone:15W+ AirPods:5W
	Mode 9	Phone:5W+Watch:3W
	Mode 10	Phone:15W+Watch:3W
	Mode 11	Phone:5W+Watch:5W
	Mode 12	Phone:15W+Watch:5W
	Mode 13	Airpods:5W+Watch:3W
	Mode 14	Airpods:5W+Watch:5W
AC Mode	Mode 15	Phone:5W
	Mode 16	Phone:7.5W
	Mode 17	Phone:15W
	Mode 18	Watch:3W
	Mode 19	Watch:5W
	Mode 20	Airpods:5W

Note: All test mode were tested and passed, only shows the worst case mode which were recorded in this report.

5. Test Facility And Test Instrument Used

5.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583


ISED CAB identifier: CN0017

5.2 Test Instrument Used

Conducted Emissions Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
LISN	R&S	ENV216	101375	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	EMC-CON 3A1	\	\
Pulse limiter	Schwarzbeck	VTSD9561-F	01323	May 14, 2025	May 13, 2026


RF Conducted Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Power Meter	Keysight	E4419	\	May 14, 2025	May 13, 2026
Power Sensor (AV)	Keysight	E9300A	\	May 14, 2025	May 13, 2026
Signal Analyzer 20kHz-26.5GHz	Keysight	N9020A	MY49100060	May 14, 2025	May 13, 2026
Spectrum Analyzer 9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026

Radiated Emissions Test (966 Chamber01)					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
966 chamber	ChengYu	966 Room	966	May 15, 2023	May 14, 2026
Receiver	R&S	ESR3	102075	May 08, 2025	May 07, 2026
Receiver	R&S	ESRP	101154	May 14, 2025	May 13, 2026
Amplifier	Schwarzbeck	BBV9744	9744-0037	May 14, 2025	May 13, 2026
TRILOG Broadband Antenna	Schwarzbeck	VULB9163	942	May 24, 2025	May 23, 2026
Loop Antenna(9KHz -30MHz)	Schwarzbeck	FMZB1519B	00014	May 24, 2025	May 23, 2026
Amplifier	SKET	LAPA_01G1 8G-45dB	SK2021040901	May 14, 2025	May 13, 2026
Horn Antenna	Schwarzbeck	BBHA9120D	1541	May 24, 2025	May 23, 2026
Amplifier(18G Hz-40GHz)	MITEQ	TTA1840-35-HG	2034381	May 24, 2025	May 23, 2026
Horn Antenna(18G Hz-40GHz)	Schwarzbeck	BBHA9170	00822	May 24, 2025	May 23, 2026
Spectrum Analyzer9kHz-40GHz	R&S	FSP40	100363	May 14, 2025	May 13, 2026
Software	Frad	EZ-EMC	FA-03A2 RE	\	\



6. Conducted Emissions

6.1 Block Diagram Of Test Setup



6.2 Limit

Frequency (MHz)	Limit (dBuV)	
	Quas-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00

Notes:

- *Decreasing linearly with logarithm of frequency.
- The lower limit shall apply at the transition frequencies.

6.3 Test procedure

Receiver Parameters	Setting
Attenuation	10 dB
Start Frequency	0.15 MHz
Stop Frequency	30 MHz
IF Bandwidth	9 kHz


- The Product was placed on a nonconductive table 0.8 m above the horizontal ground reference plane, and 0.4 m from the vertical ground reference plane, and connected to the main through Line Impedance Stability Network (L.I.S.N).
- The RBW of the receiver was set at 9 kHz in 150 kHz ~ 30MHz with Peak and AVG detector in Max Hold mode. Run the receiver's pre-scan to record the maximum disturbance generated from Product in all power lines in the full band.
- For each frequency whose maximum record was higher or close to limit, measure its QP and AVG values and record.

6.4 EUT operating Conditions

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

6.5 Test Result

Temperature:	24.4℃	Relative Humidity:	57%RH
Pressure:	101KPa	Phase :	L
Test Mode:	Mode 3(Worst)	Test Voltage:	AC 120V/60Hz




Remark:

1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz		dB	dBuV	dBuV	dB	Detector
1		0.2310	33.29	20.04	53.33	62.41	-9.08	QP
2		0.2310	25.66	20.04	45.70	52.41	-6.71	AVG
3		0.8924	23.66	20.27	43.93	56.00	-12.07	QP
4		0.8924	9.98	20.27	30.25	46.00	-15.75	AVG
5		2.5215	23.83	20.29	44.12	56.00	-11.88	QP
6	*	2.5215	21.91	20.29	42.20	46.00	-3.80	AVG
7		3.2370	25.44	20.45	45.89	56.00	-10.11	QP
8		3.2370	21.09	20.45	41.54	46.00	-4.46	AVG
9		7.3275	27.80	20.98	48.78	60.00	-11.22	QP
10		7.3275	23.27	20.98	44.25	50.00	-5.75	AVG
11		12.6015	23.61	21.94	45.55	60.00	-14.45	QP
12		12.6015	18.75	21.94	40.69	50.00	-9.31	AVG

Temperature:	24.4℃	Relative Humidity:	57%RH
Pressure:	101KPa	Phase :	N
Test Mode:	Mode 3(Worst)	Test Voltage:	AC 120V/60Hz


Remark:


1. All readings are Quasi-Peak and Average values.
2. Factor = Insertion Loss + Cable Loss.
3. Measurement = Reading Level + Correct Factor
4. Over = Measurement - Limit

No.	Mk.	Freq. MHz	Reading Level dB	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		0.2256	34.31	20.04	54.35	62.61	-8.26	QP
2		0.2256	26.58	20.04	46.62	52.61	-5.99	AVG
3		0.3338	27.83	20.05	47.88	59.36	-11.48	QP
4		0.3338	19.90	20.05	39.95	49.36	-9.41	AVG
5		0.7313	21.03	20.26	41.29	56.00	-14.71	QP
6		0.7313	8.86	20.26	29.12	46.00	-16.88	AVG
7		3.2930	26.49	20.46	46.95	56.00	-9.05	QP
8	*	3.2930	19.78	20.46	40.24	46.00	-5.76	AVG
9		5.8358	27.06	20.81	47.87	60.00	-12.13	QP
10		5.8358	21.72	20.81	42.53	50.00	-7.47	AVG
11		14.9860	27.42	22.48	49.90	60.00	-10.10	QP
12		14.9860	16.03	22.48	38.51	50.00	-11.49	AVG


7. Radiated Emissions

7.1 Block Diagram Of Test Setup

(A) Radiated Emission Test-Up Frequency Below 30MHz



(B) Radiated Emission Test-Up Frequency 30MHz~1GHz



7.2 Limit

FCC §15.209; §15.205.

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz~1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz~30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

7.3 Test procedure

Receiver Parameter	Setting
Attenuation	Auto
9kHz~150kHz	RBW 200Hz for QP
150kHz~30MHz	RBW 9kHz for QP
30MHz~1000MHz	RBW 120kHz for QP

Below 1GHz test procedure as below:

- The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

Above 1GHz test procedure as below:


- Different between above is the test site, change from Semi- Anechoic Chamber to fully Anechoic Chamber and change form table 0.8 metre to 1.5 metre(Above 18GHz the distance is 1 meter and table is 1.5 metre).
- Test the EUT in the lowest channel ,the middle channel ,the Highest channel.

Note: Both horizontal and vertical antenna polarities were tested and performed pretest to three orthogonal axis. The worst case emissions were reported.

7.4 Test Result


9kHz-30MHz

Temperature:	24.3℃	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 5	Polarization:	Coaxial(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.1442	74.99	-7.57	67.42	104.4	-37.00	peak
2		0.2898	60.12	-7.72	52.40	98.36	-45.96	peak
3		0.1267	66.69	-7.54	59.15	105.5	-46.40	peak
4		0.3272	55.82	-7.69	48.13	97.31	-49.18	peak
5		0.2545	53.83	-7.74	46.09	99.49	-53.40	peak
6	*	0.6521	47.07	-7.41	39.66	71.32	-31.66	peak

Temperature:	24.3℃	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 5	Polarization:	Coplanar(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	0.1454	80.59	-7.57	73.02	104.3	-31.33	peak
2		0.1277	76.89	-7.54	69.35	105.4	-36.13	peak
3		0.2898	65.50	-7.72	57.78	98.36	-40.58	peak
4		0.2545	63.37	-7.74	55.63	99.49	-43.86	peak
5		0.3272	60.15	-7.69	52.46	97.31	-44.85	peak
6		0.3818	54.71	-7.65	47.06	95.97	-48.91	peak

Temperature:	24.3℃	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 15 (Phone:110.1kHz-205 kHz)	Polarization:	Coaxial(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.0662	65.29	-7.61	57.68	111.1	-53.51	peak
2		0.1454	76.29	-7.57	68.72	104.3	-35.63	peak
3		0.2898	61.04	-7.72	53.32	98.36	-45.04	peak
4		0.4347	52.18	-7.62	44.56	94.84	-50.28	peak
5		0.6521	46.71	-7.41	39.30	71.32	-32.02	peak
6	*	0.8733	44.76	-7.36	37.40	68.79	-31.39	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 15 (Phone:110.1kHz-205 kHz)	Polarization:	Coplanar(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.1267	69.91	-7.54	62.37	105.5	-43.18	peak
2		0.1454	81.92	-7.57	74.35	104.3	-30.00	peak
3		0.2898	66.58	-7.72	58.86	98.36	-39.50	peak
4		0.3272	60.02	-7.69	52.33	97.31	-44.98	peak
5		0.4347	57.13	-7.62	49.51	94.84	-45.33	peak
6	*	0.6521	49.36	-7.41	41.95	71.32	-29.37	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 17(360kHz)	Polarization:	Coaxial(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.0646	71.31	-7.58	63.73	111.4	-47.67	peak
2		0.1001	71.77	-7.49	64.28	107.6	-43.32	peak
3		0.2290	70.82	-7.76	63.06	100.4	-37.35	peak
4		0.3607	76.08	-7.67	68.41	96.46	-28.05	peak
5		0.5964	65.48	-7.47	58.01	72.10	-14.09	peak
6	*	4.1789	65.82	-7.06	58.76	69.54	-10.78	peak

Temperature:	24.3℃	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 17(360kHz)	Polarization:	Coplanar(Worst)




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Detector
		MHz	dBuV	dB	dBuV/m	dB/m	dB	
1		0.0985	72.85	-7.50	65.35	107.7	-42.39	peak
2		0.2272	70.60	-7.76	62.84	100.4	-37.64	peak
3		0.2898	71.75	-7.72	64.03	98.36	-34.33	peak
4		0.3607	77.02	-7.67	69.35	96.46	-27.11	peak
5	*	0.9318	66.31	-7.36	58.95	68.23	-9.28	peak
6		2.5895	66.27	-7.30	58.97	69.54	-10.57	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 18(326.5kHz)	Polarization:	Coaxial(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.3271	71.45	-7.69	63.76	97.31	-33.55	peak
2		0.7305	65.68	-7.36	58.32	70.34	-12.02	peak
3		3.1974	65.73	-7.24	58.49	69.54	-11.05	peak
4	*	5.5060	67.00	-7.09	59.91	69.54	-9.63	peak
5		0.0871	70.03	-7.58	62.45	108.8	-46.35	peak
6		0.1226	69.31	-7.53	61.78	105.8	-44.05	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 18(326.5kHz)	Polarization:	Coplanar(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.0610	72.13	-7.51	64.62	111.9	-47.28	peak
2		0.1514	72.00	-7.59	64.41	104.0	-39.59	peak
3		0.3272	72.45	-7.69	64.76	97.31	-32.55	peak
4		0.7304	65.68	-7.36	58.32	70.34	-12.02	peak
5		2.1314	66.51	-7.31	59.20	69.54	-10.34	peak
6	*	6.2690	68.02	-7.12	60.90	69.54	-8.64	peak

Temperature:	24.3℃	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 19(1.778MHz)	Polarization:	Coaxial(Worst)




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.1454	83.60	-7.57	76.03	104.3	-28.32	peak
2		0.2921	68.83	-7.72	61.11	98.29	-37.18	peak
3		0.4347	58.75	-7.62	51.13	94.84	-43.71	peak
4		0.9943	55.32	-7.36	47.96	67.67	-19.71	peak
5	*	1.7830	65.43	-7.33	58.10	69.54	-11.44	peak
6		4.0455	55.34	-7.06	48.28	69.54	-21.26	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 19(1.778MHz)	Polarization:	Coplanar(Worst)




No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		0.1454	80.10	-7.57	72.53	104.3	-31.82	peak
2		0.2921	61.83	-7.72	54.11	98.29	-44.18	peak
3		0.4347	57.75	-7.62	50.13	94.84	-44.71	peak
4	*	1.7830	63.93	-7.33	56.60	69.54	-12.94	peak
5		4.0455	55.34	-7.06	48.28	69.54	-21.26	peak
6		15.4257	54.40	-7.23	47.17	69.54	-22.37	peak

Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 20 (Airpods:110.1-205kHz)	Polarization:	Coaxial(Worst)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1		0.1442	74.99	-7.57	67.42	104.4	-37.00	peak
2		0.2898	60.12	-7.72	52.40	98.36	-45.96	peak
3		0.1267	66.69	-7.54	59.15	105.5	-46.40	peak
4		0.3272	55.82	-7.69	48.13	97.31	-49.18	peak
5		0.2545	53.83	-7.74	46.09	99.49	-53.40	peak
6	*	0.6521	47.07	-7.41	39.66	71.32	-31.66	peak


Temperature:	24.3°C	Relative Humidity:	53%RH
Pressure:	101 kPa	Test Voltage:	AC120V/60Hz
Test Mode:	Mode 20 (Airpods:110.1-205kHz)	Polarization:	Coplanar(Worst)



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	*	0.1454	80.59	-7.57	73.02	104.3	-31.33	peak
2		0.1277	76.89	-7.54	69.35	105.4	-36.13	peak
3		0.2898	65.50	-7.72	57.78	98.36	-40.58	peak
4		0.2545	63.37	-7.74	55.63	99.49	-43.86	peak
5		0.3272	60.15	-7.69	52.46	97.31	-44.85	peak
6		0.3818	54.71	-7.65	47.06	95.97	-48.91	peak

Between 30MHz – 1GHz

Temperature:	24.3°C	Relative Humidity:	56%RH
Pressure:	101KPa	Phase :	Horizontal
Test Mode:	Mode 1(Worst)	Test Voltage:	AC 120V/60Hz




Remark:

- Factor = Antenna Factor + Cable Loss – Pre-amplifier.
- Measurement = Reading Level + Correct Factor
- Over = Measurement - Limit

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV	dB	dBuV/m	dB/m	dB	Detector
1		46.3402	35.71	-13.32	22.39	40.00	-17.61	QP
2		78.9652	42.42	-15.96	26.46	40.00	-13.54	QP
3		143.8295	42.04	-17.25	24.79	43.50	-18.71	QP
4		202.1005	36.96	-14.35	22.61	43.50	-20.89	QP
5	*	299.3158	45.35	-12.02	33.33	46.00	-12.67	QP
6		499.4247	30.70	-7.41	23.29	46.00	-22.71	QP

Temperature:	24.3℃	Relative Humidity:	56%RH
Pressure:	101KPa	Phase :	Vertical
Test Mode:	Mode 1(Worst)	Test Voltage:	AC 120V/60Hz



Remark:

1. Factor = Antenna Factor + Cable Loss – Pre-amplifier.
2. Measurement = Reading Level + Correct Factor
3. Over = Measurement - Limit

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dB/m	Over dB	Detector
1	!	43.9658	49.61	-13.59	36.02	40.00	-3.98	QP
2	*	50.7637	49.76	-13.04	36.72	40.00	-3.28	QP
3		79.8003	46.47	-15.91	30.56	40.00	-9.44	QP
4		143.8295	53.16	-17.25	35.91	43.50	-7.59	QP
5		301.4224	44.87	-11.96	32.91	46.00	-13.09	QP
6		495.9344	37.36	-7.48	29.88	46.00	-16.12	QP

8. Bandwidth Test

8.1 Test Procedure


1. Set RBW = 1%~5% OBW.
2. Set the video bandwidth (VBW) $\geq 3 \times$ RBW.
3. Detector = Peak.
4. Trace mode = max hold.
5. Sweep = auto couple.
6. Allow the trace to stabilize.
7. Measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 20 dB relative to the maximum level measured in the fundamental emission.



8.2 Test Setup





8.3 Test Result

Frequency (kHz)	20dB bandwidth (kHz)	Result
110.1-205(Phone)	0.002	Pass
360	0.009	Pass
326.5	0.003	Pass
1778	0.003	Pass
110.1-205(Airpods)	0.002	Pass







Note: The measured signal is Cw-like. adjusting the RBW per C63.10 would not be practical since measurement bandwidth will always follow the RBW. The RBW is set to 1Hz and VBW is set to 3Hz to perform the occupied bandwidth test.

9. Antenna Requirements

9.1 Limit

For intentional device, according to FCC 47 CFR Section 15.203, An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

9.2 Test Result

The antenna used for this product is loop coil antenna.

10. EUT Photographs

NOTE: Appendix-Photographs Of EUT Constructional Details

EST
C
ED
al

11. EUT Test Setup Photographs

NOTE: Appendix-Test Photos

ING
OCLID

STATEMENT

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****

2017