

裁切线 _____ 压痕线 _____ V槽线 _____ 半穿刀 _____	辅助线 _____ 牙 刀 _____ 画 线 _____
☒ 外表面视图	☐ 内表面视图

版本	变更描述	变更日期	设计
A01	初始发行	2026/5/7	邓始景

AX1800 Wi-Fi 6 Wireless Bluetooth PCIe Adapter

Model: AX1800 Wi-Fi 6 Wireless Bluetooth PCIe Adapter

Preparation before use

Before using the product, please read the following instructions carefully to ensure correct installation and use.

- Check the package contents:**
 - 1. AX1800 Wi-Fi 6 Wireless Bluetooth PCIe Adapter
 - 2. User Manual
 - 3. Warranty Card
- Check the system requirements:**
 - 1. Operating System: Windows 10/11, macOS 10.15 or later, Linux kernel 4.18 or later
 - 2. Processor: Intel Core i3 or above
 - 3. Memory: 8GB or above
 - 4. Hard Disk: 1TB or above
- Check the installation environment:**
 - 1. The device should be installed in a well-ventilated area to avoid overheating.
 - 2. The device should be installed in a dry and clean environment to avoid moisture and dust.
- Check the power supply:**
 - 1. The device is powered by the system's power supply. No external power source is required.
- Check the network environment:**
 - 1. The device supports Wi-Fi 6 (802.11ax) and Bluetooth 5.2. Ensure the network environment is compatible.

Installation and Setup

- Unboxing and Initial Inspection:**
 - 1. Carefully unbox the product and inspect for any physical damage.
 - 2. Verify the model and specifications against the packaging.
- Physical Installation:**
 - 1. Power off the computer and unplug the power cord.
 - 2. Open the case and locate the PCIe slot.
 - 3. Insert the adapter into the slot, ensuring the gold contacts are properly seated.
 - 4. Secure the adapter with the provided screws.
 - 5. Close the case and plug the power cord back in.
- Driver Installation:**
 - 1. Download the latest drivers from the UGREEN website.
 - 2. Run the driver installation program as an administrator.
 - 3. Follow the on-screen instructions to complete the installation.
 - 4. Restart the computer after installation.
- Network Configuration:**
 - 1. Open the network settings in the operating system.
 - 2. Select the Wi-Fi or Bluetooth network to connect to.
 - 3. Enter the network credentials (SSID and password) if required.
 - 4. Save the settings and test the connection.
- Advanced Settings:**
 - 1. Access the UGREEN software interface.
 - 2. Configure advanced settings such as power management and signal boost.
 - 3. Save the settings and exit the software.

Network Adapter Installation

- Step 1: Unboxing and Initial Inspection**
 - 1. Carefully unbox the product and inspect for any physical damage.
 - 2. Verify the model and specifications against the packaging.
- Step 2: Physical Installation**
 - 1. Power off the computer and unplug the power cord.
 - 2. Open the case and locate the PCIe slot.
 - 3. Insert the adapter into the slot, ensuring the gold contacts are properly seated.
 - 4. Secure the adapter with the provided screws.
 - 5. Close the case and plug the power cord back in.
- Step 3: Driver Installation**
 - 1. Download the latest drivers from the UGREEN website.
 - 2. Run the driver installation program as an administrator.
 - 3. Follow the on-screen instructions to complete the installation.
 - 4. Restart the computer after installation.
- Step 4: Network Configuration**
 - 1. Open the network settings in the operating system.
 - 2. Select the Wi-Fi or Bluetooth network to connect to.
 - 3. Enter the network credentials (SSID and password) if required.
 - 4. Save the settings and test the connection.
- Step 5: Advanced Settings**
 - 1. Access the UGREEN software interface.
 - 2. Configure advanced settings such as power management and signal boost.
 - 3. Save the settings and exit the software.

[illegible]

备注:

1. 材质：80g 哑粉纸
2. 印刷颜色：4C+1专 PANTONE 7480C 
3. 展开尺寸：640x260mm
4. 成型尺寸：80x130 mm
5. 成型工艺：风琴折
6. 尺寸公差：± 1mm
7. 印刷偏位：≤0.5 mm
8. 套印偏位：≤0.35 mm
9. 所有成品及辅料符合欧盟包装废弃物法EU/2025/40要求，美国TPCH，欧盟REACH
10. 印刷油墨（成品）矿物油含量需满足MOSH(C16-C35)小于0.1%；
MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%。

SELECT			V							SCALE	UGREEN 绿联 深圳市绿联科技股份有限公司			
Dim TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	1:1				
0~6	0.05	0.05	0.10						0.20		物料名称: 说明书			
6~30	0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20	SHEET				
30~120	0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	1/1	产品名称		项目工程师	核准
120~300	0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30	UNIT				
300~450	0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50	mm	/		曾志彬	曾李同
450~600	0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80					
DRAFT TOLERANCE			± 0.20°		CRITICAL DIM. MARK				*					