

裁切线	辅助线
压痕线	牙 刀
V槽线	画 线
半穿刀	
■ 外表面视图	□ 内表面视图

UGREEN

680Wh | 600W

PowerRoom Portable Power Station

User Manual | Model: GS600

Contents

1. Product Overview

2. Specifications

3. Recharging Your Power Station

4. Powering Your Devices

5. App User Guide

6. Features & Operating Modes

7. FAQs

8. Troubleshooting

9. What's in the Box

10. Safety Instructions

11. Warranty Information

01

Product Overview

Product Details

LCD Display

01

Specifications

General Info

Input

Output

Working Environment Temperature

Recharging Your Power Station

Safety Precautions

02

Important Note

AC Recharging

Solar Recharging

03

Car Recharging

Powering Your Devices

Power On/Power Off

Flashlight

04

Car Charging Output | DC5521 Output

USB Output

AC Output

05

06

App User Guide

To connect the power station via mobile device, download the "UGREEN" App.

Scan the QR code to download the "UGREEN" App.

You can also search for "UGREEN" App via Apple Store or the Google Play Store.

07

Uninterrupted Power Supply (UPS)

Power Reduction Mode

0%

08

Operating Mode

Factory Reset

FAQs

Q1: What devices can be connected to the AC Output Port of the power station?

Q2: Can I recharge the power station while charging connected devices?

Q3: How do I know how long the power station can power the device?

09

Q4: Is there a fan running sound during use?

Troubleshooting

10

What's in the Box

11

Safety Instructions

Warnings

Notes for Safe Use

Transportation & Storage

12

1. Do not store or transport this power station with metal objects (screws, watches, metal tools, knives, etc.).

2. If you want to stop this power station via digital means, please discharge the power station battery to 20%-30%.

3. This power station cannot be carried on a plane. Please abide by the relevant regulations of civil aviation.

Maintenance

1. For long-term storage, please put the power station in the storage bag. Please charge and discharge at least once every 3 months (30 days) every 3-6 Mo. After storage is 6 Mo, to ensure battery health.

2. For long-term storage, please check the power station's remaining battery level. If it drops to low battery, please charge this, otherwise the battery may be damaged.

3. Please store the power station at the appropriate storage environment temperature (20°C-25°C/68°F-77°F) specified in the manual.

4. If the port of the power station is dirty, please clean with a dry cloth. Do not clean with chemicals or strong solvents.

Disclaimer

1. Please read the manual carefully, and use the power station correctly in accordance with all safety instructions in the manual. Safety and protection especially must be followed. Otherwise, please keep the manual for future reference.

2. Before using the power station, please read the power station user manual and safety instructions. Please read the power station user manual and safety instructions. UGREEN will not assume any legal responsibility for the condition of equipment used with regulations. UGREEN has the final right to interpret this manual and other related documents of this power station. The user manual is subject to update, revision, or replacement without notice. All updates can be viewed on the "UGREEN" App, or [UGREEN website](#).

Warranty Information

All data shown are based on UGREEN laboratory testing. Actual results may vary according to specific circumstances.

13

备注：

- 材质：157g双铜纸
- 印刷颜色：四色一专 ■ PANTONE 3415C
- 展开尺寸：160x960mm
- 成品尺寸：160x120mm
- 尺寸公差：±1 mm
- 印刷偏位：<=0.5 mm
- 套印偏位：<=0.35 mm
- 成型工艺：风琴折
- 所有成品及辅料符合欧盟包装指令94/62/EC,美国TPCH,欧盟REACH
- 印刷油墨（成品）矿物油含量需满足MOSH(C16-C35)小于0.1%；MOAH（1-7芳香环）小于0.1%；MOAH（3-7芳香环）小于0.0001%。

SELECT			V							SCALE	UGREEN 绿联 深圳市绿联科技有限公司								
Dim	TOL.	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL	1:1								
0~6		0.05	0.05	0.10						0.20	SHEET 1/1	物料名称: GS600 90997 美规 说明书							
6~30		0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20									
30~120		0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25									
120~300		0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30	UNIT mm	产品名称	料号	项目工程师	核准				
300~450		0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50									
450~600		0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80									
DRAFT TOLERANCE				± 0.20*		CRITICAL DIM. MARK				*		GS600 600W 智能户外电源			王帅兵	曾李同			

正面



IC Statement EN This device complies with Industry Canada licence-exempt RSS standard(s). Operation is subject to the following two conditions: (1) this device may not cause interference; (2) this device must accept any interference, including interference that may cause undesired operation of the device. FR Le présent appareil est conforme aux CNR d'Industrie Canada applicables aux appareils radio exempts de licence. L'exploitation est autorisée aux deux conditions suivantes : (1) l'appareil ne doit pas produire de brouillage ; (2) l'utilisateur de l'appareil doit accepter tout brouillage radioélectrique subi, même si le brouillage est susceptible d'en compromettre le fonctionnement.	CAN ICES-003(A) / NMB-003(A) This equipment complies with IC radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter. Cet équipement est conforme aux limites d'exposition aux rayonnements de la IC établies pour un environnement non contrôlé. Cet équipement doit être installé et fonctionner à au moins 20cm de distance d'un radiateur ou de votre corps. Cet émetteur ne doit pas être co-localisé ni fonctionner en conjonction avec une autre antenne ou un autre émetteur.	User Instruction GS600 UGREEN
--	---	--

03.BB.00000.UG.0203.15

背面

美+加拿大

FCC Statement  This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Warning: Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment. FCC Radiation Exposure Statement This equipment complies with FCC radiation exposure limits set forth for an uncontrolled environment. This transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.		This equipment should be installed and operated with minimum distance of 20 cm between the radiator and your body. This equipment has been tested and found to comply with the limits for a Class A digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference when the equipment is operated in a commercial environment. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instruction manual, may cause harmful interference to radio communications. Operation of this equipment in a residential area is likely to cause harmful interference in which case the user will be required to correct the interference at his own expense.
--	--	--