

F		E		D		C		B		A																																																																																																																																																										
裁切线 压痕线 V槽线 半穿刀 辅助线 牙刀 面线																																																																																																																																																																				
■外表面视图		■内表面视图																																																																																																																																																																		
UGREEN                    												UGREEN                    												<table><tr><th>SELECT</th><th></th><th></th><th></th><th>V</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th>SCALE</th></tr><tr><td>Dim</td><td>TOL</td><td>A</td><td>B</td><td>C</td><td>EPS</td><td>EPE</td><td>EPP</td><td>BAG</td><td>CTN</td><td>LABEL</td><td></td><td>1:1</td></tr><tr><td>0-6</td><td>0.05</td><td>0.05</td><td>0.10</td><td>0.10</td><td>0.50</td><td>0.50</td><td>0.50</td><td>3.00</td><td>0.20</td><td></td><td></td><td></td></tr><tr><td>6-30</td><td>0.10</td><td>0.15</td><td>0.20</td><td>0.50</td><td>0.50</td><td>0.50</td><td>0.50</td><td>5.00</td><td>1.00</td><td>0.25</td><td></td><td></td></tr><tr><td>30-120</td><td>0.15</td><td>0.20</td><td>0.30</td><td>0.50</td><td>0.50</td><td>0.50</td><td>0.50</td><td>10.00</td><td>1.00</td><td>0.30</td><td></td><td></td></tr><tr><td>120-300</td><td>0.20</td><td>0.30</td><td>0.40</td><td>1.00</td><td>1.00</td><td>1.00</td><td>1.00</td><td>20.00</td><td>3.00</td><td>0.80</td><td></td><td></td></tr><tr><td>300-450</td><td>0.25</td><td>0.40</td><td>0.50</td><td>2.00</td><td>2.00</td><td>2.00</td><td>2.00</td><td>30.00</td><td>4.00</td><td>1.00</td><td></td><td></td></tr><tr><td>450-600</td><td>0.30</td><td>0.50</td><td>0.60</td><td>3.00</td><td>3.00</td><td>3.00</td><td>3.00</td><td>40.00</td><td>5.00</td><td>1.20</td><td></td><td></td></tr><tr><td>DRAFT TOLERANCE</td><td></td><td></td><td></td><td>±</td><td></td><td></td><td></td><td>CRITICAL DIM. MARK</td><td></td><td></td><td></td><td></td></tr></table>												SELECT				V								SCALE	Dim	TOL	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL		1:1	0-6	0.05	0.05	0.10	0.10	0.50	0.50	0.50	3.00	0.20				6-30	0.10	0.15	0.20	0.50	0.50	0.50	0.50	5.00	1.00	0.25			30-120	0.15	0.20	0.30	0.50	0.50	0.50	0.50	10.00	1.00	0.30			120-300	0.20	0.30	0.40	1.00	1.00	1.00	1.00	20.00	3.00	0.80			300-450	0.25	0.40	0.50	2.00	2.00	2.00	2.00	30.00	4.00	1.00			450-600	0.30	0.50	0.60	3.00	3.00	3.00	3.00	40.00	5.00	1.20			DRAFT TOLERANCE				±				CRITICAL DIM. MARK					UGREEN 绿联 深圳市绿联科技股份有限公司 物料名称: 说明书 产品名称 项目工程师 核准 头戴式降噪蓝牙耳机 高玄英 陈雨霜											
SELECT				V								SCALE																																																																																																																																																								
Dim	TOL	A	B	C	EPS	EPE	EPP	BAG	CTN	LABEL		1:1																																																																																																																																																								
0-6	0.05	0.05	0.10	0.10	0.50	0.50	0.50	3.00	0.20																																																																																																																																																											
6-30	0.10	0.15	0.20	0.50	0.50	0.50	0.50	5.00	1.00	0.25																																																																																																																																																										
30-120	0.15	0.20	0.30	0.50	0.50	0.50	0.50	10.00	1.00	0.30																																																																																																																																																										
120-300	0.20	0.30	0.40	1.00	1.00	1.00	1.00	20.00	3.00	0.80																																																																																																																																																										
300-450	0.25	0.40	0.50	2.00	2.00	2.00	2.00	30.00	4.00	1.00																																																																																																																																																										
450-600	0.30	0.50	0.60	3.00	3.00	3.00	3.00	40.00	5.00	1.20																																																																																																																																																										
DRAFT TOLERANCE				±				CRITICAL DIM. MARK																																																																																																																																																												
备注:												1. 材质: 80克哑粉纸												2. 表面工艺: 过哑油												3. 印刷颜色: 4C+1专 PANTONE 3415C ■												4. 成品尺寸: 105x120mm												5. 展开尺寸: 630x240mm												6. 尺寸公差: ±1mm												7. 印刷偏移公差: ≤0.5mm												8. 套印错位: ≤0.35mm												9. 所有成品及辅料符合欧盟包装指令94/62/EC, 美国TPCH, 欧盟REACH												10. 印刷油墨 (成品) 矿物油含量需满足MOSH(C16-C35)小于0.1%; MOAH (1-7芳香环) 小于0.1%; MOAH (3-7芳香环) 小于0.0001%.																																												

4

3

2

1

4

3

2

1