



RF Exposure Estimation

1. Introduction

Product: UGREEN Studio Max5s
Model no.: HP208
FCC ID: 2AQI5-HP208

2. Limit and Guidelines on Exposure to Electromagnetic Fields

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission's guideline.

According to KDB 447498 D01 Mobile Portable RF Exposure v05r02, no SAR required if power is lower than the flowing threshold:

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$ for 1-g SAR and ≤ 7.5 for 10-g extremity SAR, where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation²⁵
- The result is rounded to one decimal place for comparison
- 3.0 and 7.5 are referred to as the numeric thresholds in the step 2 below

The test exclusions are applicable only when the minimum test separation distance is ≤ 50 mm and for transmission frequencies between 100 MHz and 6 GHz.

3. Calculation method

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot \sqrt{f(\text{GHz})} \leq 3.0$

Conducted Power + tune up tolerance = 0.47dBm+1dB= 1.40mW for BLE

Distance = 5 mm

$f = 2.402$ GHz

$[1.40/5] \cdot \text{SQRT}(2.402) = 0.434$

$0.434 \leq 3.0$

Therefore, excluded from SAR testing.

Conducted Power + tune up tolerance = 1.64dBm+1dB= 1.84mW for BR+EDR

Distance = 5 mm

$f = 2.402$ GHz

$[1.84/5] \cdot \text{SQRT}(2.402) = 0.570$

$0.570 \leq 3.0$

Therefore, excluded from SAR testing.

Note: The device does not support simultaneous BLE 2.4GHz and 2.4GHz BR/EDR, because they share the same antenna and can't transmit simultaneously. There is not simultaneous transmission possibility.




- TÜV SÜD Products Testing (Shanghai) Co., Ltd.
FCC-Registration No.: 820234 Designation Number: CN1183
ISED Company Number: 31668 CAB identifier: CN0101

Reviewed by:

Prepared by:

Tested by:

Hui Tong



Jiayi XU

Doujun XU

Hui TONG
Review Engineer

Jiayi XU
Project Engineer

Doujun XU
Test Engineer

Date: June 05, 2026

Date: June 05, 2026

Date: June 05, 2026

-----End of Test Report-----