

FCC - TEST REPORT

Report Number : **6895025176101** Date of Issue: **2026-06-30**

Model : **PB567**

Product Type : Magnetic Wireless Power Bank

Applicant : Ugreen Group Limited

Address : Ugreen Building, Longcheng Industrial Park Longguanxi Road,
Longhua 518000 ShenZhen, PEOPLE'S REPUBLIC OF CHINA

Manufacturer : Ugreen Group Limited

Address : Ugreen Building, Longcheng Industrial Park Longguanxi Road,
Longhua 518000 ShenZhen, PEOPLE'S REPUBLIC OF CHINA

Factory : Shenzhen Firststar Battery Co., Limited

Address : Building 3 and Building 5, Jinxiu Industrial Park, Xitian Community,
Gongming Sub-district, Guangming District, 518106 Shenzhen
City, PEOPLE'S REPUBLIC OF CHINA.

Test Result : ☒ **Positive** ☐ **Negative**

Total pages including
Appendices : **27**

Any use for advertising purposes must be granted in writing. This technical report may only be quoted in full. This report is the result of a single examination of the object in question and is not generally applicable evaluation of the quality of other products in regular production. For further details, please see testing and certification regulation, chapter A-3.4.

1 Table of Contents

1	Table of Contents	2
2	Details about the Test Laboratory	3
3	Description of the Equipment Under Test	4
4	Summary of Test Standards	5
5	Summary of Test Results	6
6	General Remarks	7
7	Test Setups	8
8	Systems test configuration	9
9	Technical Requirement	10
9.1	Conducted Emission Test	10
9.2	20 dB Bandwidth	15
9.3	Radiated Emission Test	17
10	Test Equipment List	26
11	System Measurement Uncertainty	27

2 Details about the Test Laboratory

Details about the Test Laboratory

Test Site 1

Company name: TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch
Company Address: Building 12 & 13, Zhiheng Wisdomland Business Park, Guankou Erlu, Nantou, Nanshan District, Shenzhen, Guangdong, China
Telephone: +86 755 8828 6998
Fax: +86 755 8828 5299
FCC Registration No.: 174744
FCC Designation Number: CN5009

3 Description of the Equipment Under Test

Product:	Magnetic Wireless Power Bank
Model no.:	PB567
P/N Code:	55450, 55450P, 55450X, 55450A, 55450B, 55450C, 55450U, 55450JP, 55450ZD
FCC ID:	2AQI5-PB567A
Rating:	USB-C(IN1) / USB-C Cable(IN2) Input: 5.0V=3.0A, 9.0V=3.0A, 12.0V=2.5A, 15.0V=2.0A; USB-C(OUT1) / USB-C Cable(OUT2) Output: 10.0V=2.25A, 5.0V=2.4A, 5.0V=3.0A, 9.0V=3.0A, 12.0V=2.5A, 15.0V=2.0A; USB-A(OUT3) Output: 10.0V=2.25A, 5.0V=2.4A, 5.0V=3.0A, 9.0V=2.0A, 12.0V= 1.5A; Wireless Charging Output: 15.0W Max; Total Output: 5.0V=1.5A+5.0W; Total Cell Capacity: 20000mAh; Battery Capacity: 10000mAh(Two Cells in Series); Rated Capacity: 11300mAh(TYP 5V2.4A); Polymer Lithium-ion Battery Rated Energy: 72.0Wh, 7.2V
RF Transmission Frequency:	111-148.5kHz, 360kHz
Antenna Type:	Coil Antenna
Modulation Type:	FSK
WPT Type:	Magnetic Induction
Description of the EUT:	The EUT is a Power Bank with WPT function. The TX and RX range is: 111-148.5kHz, BPP 5W/iPhone7.5W/Samsung10W 360kHz, iPhone15W



4 Summary of Test Standards

Test Standards	
FCC Part 15 Subpart C 10-1-2024 Edition	PART 15 - RADIO FREQUENCY DEVICES Subpart C - Intentional Radiators

All the test methods were according to ANSI C63.10 (2020).

5 Summary of Test Results

Technical Requirements					
FCC Part 15 Subpart C					
Test Condition		Test Site	Test Result		
			Pass	Fail	N/A
§15.207	Conducted emission AC power port	Site 1	☒	☐	☐
§15.215(c)	20dB bandwidth	Site 1	☒	☐	☐
§15.209	Radiated emission	Site 1	☒	☐	☐
§15.203	Antenna requirement	See note 1	☒	☐	☐

Note 1: The EUT uses an integrated coil antenna. In accordance to §15.203, it is considered sufficiently to comply with the provisions of this section.

6 General Remarks

Remarks

This submittal(s) (test report) is intended for FCC ID: 2AQI5-PB567A complies with Section 15.207, 15.209, 15.205 of the FCC Part 15, Subpart C rules.

SUMMARY:

All tests according to the regulations cited on page 5 were

■ - Performed

□ - **Not** Performed

The Equipment under Test

■ - **Fulfills** the general approval requirements.

□ - **Does not** fulfill the general approval requirements.


Sample Received Date: 2025-07-31

Testing Start Date: 2025-07-31

Testing End Date: 2025-08-30

- TÜV SÜD Certification and Testing (China) Co., Ltd. Shenzhen Branch -

Reviewed by:




John Zhang
Project Manager

Prepared by:


Hayden Hu
Project Engineer


Tested by:


Vier Ye
Test Engineer


7 Test Setups

7.1 Radiated test setups


Below 30MHz



30MHz-1GHz



7.2 AC Power Conducted test setups



8 Systems test configuration

Auxiliary Equipment Used during Test:

Description	Manufacturer	Model NO.	S/N
Adaptor	Apple	---	---
RX Full function test module	YBZ	F18/F19	---

9 Technical Requirement

9.1 Conducted Emission Test

Test Method

1. The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
2. Connect EUT to the power mains through a line impedance stabilization network (LISN).
3. All the support units are connecting to the other LISN.
4. The LISN provides 50 ohm coupling impedance for the measuring instrument.
5. Both sides of AC line were checked for maximum conducted interference.
6. The frequency range from 150 kHz to 30 MHz was searched.
7. Set the test-receiver system to Peak Detect Function and specified bandwidth (IF Bandwidth = 9kHz) with Maximum Hold Mode. Then measurement is also conducted by Average Detector and Quasi-Peak Detector Function respectively.

Limit


According to §15.207, conducted emissions limit as below:

Frequency MHz	QP Limit dB μ V	AV Limit dB μ V
0.150-0.500	66-56*	56-46*
0.500-5	56	46
5-30	60	50

*Decreasing linearly with logarithm of the frequency

Conducted Emission

Model: PB567
 Operating Condition: Wireless Power Transfer
 Test Specification: Power Line, Live
 Remark: 360kHz, 15W



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.150000	52.15	---	66.00	13.85	L1	9.60
0.254000	44.70	---	61.63	16.92	L1	9.62
0.382000	40.31	---	58.24	17.92	L1	9.63
1.142000	39.41	---	56.00	16.59	L1	9.66
2.414000	40.04	---	56.00	15.96	L1	9.69
4.446000	---	39.29	46.00	6.71	L1	9.77
7.242000	40.83	---	60.00	19.17	L1	9.88

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---		---

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Model: PB567
 Operating Condition: Wireless Power Transfer
 Test Specification: Power Line, Neutral
 Remark: 360kHz, 15W



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.382000	37.91	---	58.24	20.33	N	9.62
0.890000	38.93	---	56.00	17.07	N	9.65
1.650000	39.98	---	56.00	16.02	N	9.66
2.922000	40.48	---	56.00	15.52	N	9.70
2.922000	---	39.75	46.00	6.25	N	9.70
5.462000	40.94	---	60.00	19.06	N	9.81
12.578000	40.94	---	60.00	19.06	N	9.96

Final_Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Model: PB567
 Operating Condition: Wireless Power Transfer
 Test Specification: Power Line, Live
 Remark: 111-148.5kHz, 10W



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.250000	---	45.74	51.76	6.02	L1	10.20
0.250000	48.78	---	61.76	12.98	L1	10.20
0.498000	36.98	---	56.03	19.06	L1	10.20
0.998000	27.67	---	56.00	28.33	L1	10.21
2.370000	33.66	---	56.00	22.34	L1	10.34
7.726000	---	27.70	50.00	22.30	L1	10.54
23.426000	36.79	---	60.00	23.21	L1	11.17

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---	---	---

Remark:


Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

Conducted Emission

Model: PB567
 Operating Condition: Wireless Power Transfer
 Test Specification: Power Line, Neutral
 Remark: 111-148.5kHz, 10W



Critical Freqs

Frequency (MHz)	MaxPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
0.250000	---	46.80	51.76	4.96	N	10.20
0.250000	47.17	---	61.76	14.59	N	10.20
0.498000	37.12	---	56.03	18.91	N	10.20
2.118000	---	31.74	46.00	14.26	N	10.33
3.986000	29.37	---	56.00	26.63	N	10.37
12.710000	32.70	---	60.00	27.30	N	10.83
24.674000	39.12	---	60.00	20.88	N	11.23

Final Result

Frequency (MHz)	QuasiPeak (dBuV)	Average (dBuV)	Limit (dBuV)	Margin (dB)	Line	Corr. (dB)
---	---	---	---	---		---

Remark:

Level=Reading Level + Correction Factor

Correction Factor=Cable Loss + LISN Factor

(The Reading Level is recorded by software which is not shown in the sheet)

9.2 20 dB Bandwidth

Test Method


1. The RF output of EUT was connected to the spectrum analyzer by RF cable. The path loss was compensated to the results for each measurement.
2. Set to the maximum power setting and enable the EUT transmit continuously.
3. Use the following test receiver settings:
Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel
RBW $\geq$ 1% to 5% of the 20 dB bandwidth, VBW $\geq$ 3RBW, Sweep = auto,
Detector function = peak, Trace = max hold
4. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Measure the frequency difference of two frequencies that were attenuated 20 dB from the reference level. Record the frequency difference as the emission bandwidth. Record the results.

Limit

Intentional radiators must be designed to ensure that the 20 dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates, is contained within the frequency band designated in the rule section under which the equipment is operated.


Test Result

Frequency	F _L	F _H	20dB bandwidth	Result
kHz	kHz	kHz	kHz	
111-148.5kHz	117.4649	118.2204	0.755	Pass





Frequency	F _L	F _H	20dB bandwidth	Result
kHz	kHz	kHz	kHz	
360kHz	359.6324	360.3849	0.753	Pass



The device didn't operate in the 90-110 kHz band.

9.3 Radiated Emission Test

Test Method

1. The EUT was placed on a turn table which is 0.8m above ground plane. The table was rotated 360 degrees to determine the position of the highest radiation.
2. Set to the maximum power setting and enable the EUT transmit continuously
3. The EUT was set 3 meters away from the interference – receiving antenna, which was mounted on the top of a variable – height antenna tower.
4. The height of antenna is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
5. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.

Use the following test receiver settings According to C63.10:

For Below 9kHz-1GHz, use the following spectrum analyzer settings:

Span = wide enough to capture the peak level of the in-band emission and all spurious

9kHz -150kHz

RBW = 200Hz, VBW = 600Hz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

150kHz - 30MHz

RBW = 10 kHz, VBW = 30 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

30MHz - 1GHz

RBW = 10 kHz, VBW = 30 kHz for peak measurement, Sweep = auto, Detector function = peak, Trace = max hold.

Limit

The emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:


Frequency MHz	Field Strength $\mu\text{V/m}$	Field Strength $\text{dB}\mu\text{V/m}$	Detector	Measurement distance meters
0.009-0.490	2400/F(kHz)	48.5-13.8	QP	300
0.490-1.705	24000/F(kHz)	33.8-23.0	QP	30
1.705-30	30	29.5	QP	30
30-88	100	40	QP	3
88-216	150	43.5	QP	3
216-960	200	46	QP	3
960-1000	500	54	QP	3
Above 1000	500	54	AV	3
Above 1000	5000	74	PK	3

Note 1: Limit $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 300\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(300\text{m}/3\text{m})$ (Below 30MHz)

Note 2: Limit $3\text{m}(\text{dB}\mu\text{V/m}) = \text{Limit } 30\text{m}(\text{dB}\mu\text{V/m}) + 40\text{Log}(30\text{m}/3\text{m})$ (Below 30MHz)

Radiated emissions test (9KHz-30MHz)

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 360kHz, 15W




Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.026484	61.09	119.13	58.04	H	359.0	19.37
0.056000	59.16	112.63	53.47	H	0.0	19.41
0.088007	52.19	108.71	56.51	H	0.0	19.41
0.358950	72.50	96.50	24.01	H	300.0	19.40
0.717150	50.96	70.50	19.54	H	165.0	19.43
1.075350	50.71	66.99	16.29	H	310.0	19.45

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---		---	---

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 360kHz, 15W




Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.027612	62.25	118.77	56.52	V	155.0	19.38
0.056000	58.89	112.63	53.74	V	0.0	19.41
0.135994	51.66	104.93	53.27	V	0.0	19.41
0.358950	67.09	96.50	29.41	V	39.0	19.40
0.717150	46.90	70.50	23.60	V	91.0	19.43
1.075350	46.00	66.99	20.99	V	39.0	19.45

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---		---	---

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 111-148.5kHz,10W




Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.131341	73.79	105.23	31.44	H	63.0	19.41
0.259450	67.36	99.32	31.96	H	355.0	19.39
0.388800	54.35	95.81	41.46	H	89.0	19.40
0.518150	41.63	73.32	31.68	H	0.0	19.38
0.652475	44.93	71.32	26.39	H	82.0	19.41
2.388750	39.77	69.50	29.73	H	15.0	19.62

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---		---	---

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 111-148.5kHz, 10W



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
0.027189	69.00	118.90	49.90	V	9.0	19.37
0.054449	66.40	112.87	46.47	V	191.0	19.41
0.131764	68.10	105.20	37.10	V	145.0	19.41
0.264425	62.38	99.16	36.77	V	287.0	19.39
0.393775	49.64	95.70	46.05	V	349.0	19.40
0.518150	40.78	73.32	32.54	V	110.0	19.38

Final_Result


Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---		---	---

Remark:

- (1) within this frequency range shown "--" in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (2) Below 1GHz: Corrector factor = Antenna Factor + Cable Loss.

Radiated emissions test (30MHz-1000MHz)

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 360kHz, 15W




Critical Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
48.066250	23.04	40.00	16.96	100.0	H	0.0	20.80
103.235000	23.12	43.50	16.88	100.0	H	0.0	19.02
188.958750	25.32	43.50	18.18	200.0	H	251.0	18.12
269.711250	40.65	46.00	5.35	100.0	H	251.0	20.76
424.729375	29.32	46.00	16.68	200.0	H	2.0	24.86
597.571250	33.29	46.00	12.71	200.0	H	1.0	28.38

Final Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
269.711250	38.50	46.00	7.50	100.0	H	251.0	20.76

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 360kHz, 15W




Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
38.851250	25.56	40.00	14.44	100.0	V	259.0	18.86
58.978750	24.14	40.00	15.86	100.0	V	325.0	19.81
143.975000	23.91	43.50	19.59	100.0	V	251.0	15.27
260.617500	27.98	46.00	18.02	200.0	V	339.0	20.54
498.025000	31.02	46.00	14.98	200.0	V	0.0	26.07
770.110000	35.20	46.00	10.80	200.0	V	183.0	30.64

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 111-148.5kHz, 10W




Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
47.945000	24.87	40.00	15.13	100.0	H	234.0	18.83
106.468333	19.74	43.50	23.77	100.0	H	65.0	16.38
144.190556	19.55	43.50	23.95	200.0	H	145.0	13.30
189.403333	22.83	43.50	20.67	200.0	H	66.0	16.04
261.129444	35.88	46.00	10.12	100.0	H	234.0	18.98
430.933333	29.07	46.00	16.93	200.0	H	271.0	23.02

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---		---	---

Model: PB567
 Test Mode: Wireless Power Transfer
 Test Voltage: AC 120V/60Hz
 Remark: 111-148.5kHz, 10W



Critical_Freqs

Frequency (MHz)	MaxPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
37.113333	26.90	40.00	13.10	100.0	V	195.0	16.31
46.543889	27.02	40.00	12.98	100.0	V	340.0	18.57
71.225000	20.98	40.00	19.02	100.0	V	171.0	13.62
95.475000	21.36	43.50	22.14	100.0	V	148.0	15.87
143.975000	22.64	43.50	20.86	100.0	V	313.0	13.28
262.638333	26.99	46.00	19.01	200.0	V	298.0	18.93

Final_Result

Frequency (MHz)	QuasiPeak (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
---	---	---	---	---	---	---	---

Remark:

- (3) within this frequency range shown "--" in the table above means the reading of emissions are the noise floor or attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
- (4) Below 1GHz: Corrector factor = Antenna Factor + Cable Loss.

10 Test Equipment List

List of Test Instruments

Radiated Emission Test (9kHz-30MHz)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 7	68-4-74-19-001	102176	1	2026-4-25
Loop Antenna	Rohde & Schwarz	HFH2-Z2	68-4-80-14-006	100398	1	2026-7-17
Cable	HUBER-SUHNER	RG214	68-4-90-14-001-A21	----	----	----
3m Semi-anechoic chamber	TDK	SAC-3 #1	68-4-90-14-001	----	3	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-14-001-A10	Version10.35.02	N/A	N/A

Radiated Emission Test (30MHz-1GHz)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 26	68-4-74-14-002	101269	1	2026-4-25
Trilog Super Broadband Test Antenna	Schwarzbeck	VULB 9162	68-4-80-19-003	284	1	2026-2-11
Attenuator	Mini-circuits	UNAT-6+	68-4-81-21-002	15542	1	2026-4-19
Cable	OUQIAO	18DLB5-NMNM-7000	68-4-90-19-006-A22	----	----	----
3m Semi-anechoic chamber	TDK	SAC-3 #2	68-4-90-19-006	----	3	2026-10-25
Test software	Rohde & Schwarz	EMC32	68-4-90-19-006-A01	Version10.35.02	N/A	N/A

Conducted Emission Test (AMN)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
EMI Test Receiver	Rohde & Schwarz	ESR 3	68-4-74-14-001	101782	1	2026-4-25
LISN	Rohde & Schwarz	ENV432	68-4-87-16-001	101318	1	2026-4-25
LISN	Rohde & Schwarz	ENV4200	68-4-87-14-001	100249	1	2026-4-25
Attenuator	Shanghai Huaxiang	TS2-26-3	68-4-81-16-003	080928189	1	2026-4-19
Cable	OUQIAO	RG142	68-4-90-19-005-A20	----	----	----
Test software	Rohde & Schwarz	EMC32	68-4-90-19-005-A01	Version10.35.02	N/A	N/A
Shielding Room	TDK	CSR #2	68-4-90-19-005	----	3	2027-10-07

RF Test(FCC Part15 C)

DESCRIPTION	MANUFACTURER	MODEL NO.	EQUIPMENT ID	SERIAL NO.	CAL INTERVAL (YEAR)	CAL. DUE DATE
Signal Analyzer	Rohde & Schwarz	FSV40	68-4-74-14-004	101030	1	2026-4-18
Cable	JUNFLON	J12J103539	68-4-90-19-003-A22	----	----	----
Shielding Room	TDK	TS8997	68-4-90-19-003	----	3	2027-10-07

11 System Measurement Uncertainty

For a 95% confidence level, the measurement expanded uncertainties for defined systems, in accordance with the recommendations of ISO 17025 were:

System Measurement Uncertainty	
Test Items	Extended Uncertainty
Uncertainty for Radiated Emission in 3m chamber 9kHz-30MHz	4.69dB
Uncertainty for Radiated Emission in new 3m chamber 30MHz-1000MHz	Horizontal: 4.79dB Vertical: 5.86dB
Uncertainty for Conducted Emission in new shielding room 150kHz-30MHz	3.14dB
Uncertainty Evaluation for Carrier Frequency	4.44PPM
Uncertainty Evaluation for OBW	2.32%
Uncertainty Evaluation for Humidity	1.32%
Uncertainty Evaluation for Temperature	0.26 °C

Measurement Uncertainty Decision Rule

Determination of conformity with the specification limits is based on the decision rule according to IEC Guide 115: 2023, clause 4.3.3 and 4.

---END OF TEST REPORT---