

版本	变更日期	变更描述	结构工程	设计者
A01	2025/12/11	初始发行	段斯蓝	庄慧宇
A02	2025/12/26	初始发行	段斯蓝	庄慧宇

裁切线	辅助线
压痕线	牙刀
V槽线	画线
半穿刀	

■ 外表面视图

□ 内表面视图

Image content is truncated. The page contains multiple pages of a user manual, likely for a power bank, with sections for LED indicator, Charging Your Devices, Power Distribution, and Specifications. The text is in multiple languages, including English, Arabic, and Chinese. The page is heavily redacted with black bars.

备注:

1. 材质: 80G 哑粉纸
2. 印刷颜色: 1C
3. 成型尺寸: 60x105mm
4. 展开尺寸: 600x210mm
5. 尺寸公差: $\pm 1\text{ mm}$
6. 印刷偏位: $\leq 0.5\text{ mm}$
7. 套印偏位: $\leq 0.35\text{ mm}$
8. 成型工艺: 风琴折
9. 所有成品及辅料符合欧盟包装指令94/62/EC, 美国TPCH, 欧盟REACH
10. 印刷油墨 (成品) 矿物油含量需满足MOSH(C15-C36) 小于0.1%; MOAH (1-7芳萘环) 小于0.1%; MOAH (3-7芳萘环) 小于0.0001%

SELECT				V						SCALE	UGREEN 绿联 深圳市绿联科技股份有限公司								
Dim	TOL	A	B	C	EPS	EPE	EPP	BAG	CTN	1:1									
0~6		0.05	0.05	0.10						0.20	物料名称: 说明书								
6~30		0.10	0.15	0.20	0.50	0.50	0.50	3.00		0.20									
30~120		0.15	0.20	0.30	0.50	0.50	0.50	5.00	1.00	0.25	UNIT mm								
120~300		0.20	0.30	0.40	1.00	1.00	1.00	10.00	1.00	0.30									
300~450		0.25	0.40	0.50	2.00	2.00	2.00	15.00	2.00	0.50	产品名称								
450~600		0.30	0.50	0.60	3.00	3.00	3.00	20.00	3.00	0.80									
DRAFT TOLERANCE				± 0.20"		CRITICAL DIM. MARK				* 		移动电源		料号		项目工程师		核准	
														罗燕芳		曾爽			

