

TEST REPORT

Report No.: BCTC2507343539-2E

Applicant: Ugreen Group Limited

Product Name: 3-in-1 Magnetic Wireless Charger

Test Model: W707

Tested Date: 2025-07-23 to 2025-09-18

Issued Date: 2025-09-26

Shenzhen **BCTC** Testing Co., Ltd.



FCC ID:2AQI5-W707A

Product Name: 3-in-1 Magnetic Wireless Charger

Trademark: **UGREEN**

Model/Type Reference: W707

Prepared For: Ugreen Group Limited

Address: Ugreen Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, China

Manufacturer: Ugreen Group Limited

Address: Ugreen Building, Longcheng Industrial Park, Longguanxi Road, Longhua, ShenZhen, China

Prepared By: Shenzhen BCTC Testing Co., Ltd.

Address: 1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

Sample Received Date: 2025-07-23

Sample Tested Date: 2025-07-23 to 2025-09-18

Issue Date: 2025-09-26

Report No.: BCTC2507343539-2E

Test Standards: FCC CFR 47 part1, 1.1307(b), 1.1310
KDB 680106 D01 Wireless Power Transfer v04

Test Results: PASS

Tested by:



Kelsey Tan/ Project Handler

Approved by:



Zero Zhou/Reviewer


The test report is effective only with both signature and specialized stamp. This result(s) shown in this report refer only to the sample(s) tested. Without written approval of Shenzhen BCTC Testing Co., Ltd, this report can't be reproduced except in full. The tested sample(s) and the sample information are provided by the client.

Table Of Content

Test Report Declaration	Page
1. Version	4
2. Product Information	5
2.1 Product Information	5
2.2 Support Equipment	6
2.3 Test Mode	6
3. Test Facility And Test Instrument Used	7
3.1 Test Facility	7
3.2 Test Instrument Used	7
4. Method Of Measurement	8
4.1 Applicable Standard	8
4.2 Block Diagram Of Test Setup	8
4.3 Limit	9
4.4 Test procedure	9
4.5 Equipment Approval Considerations	10
4.6 E and H field Strength	11
5. Photographs Of Test Set-Up	12

(Note: N/A Means Not Applicable)


BCTC
BCTC
PPR
Report



1. Version

Report No.	Issue Date	Description	Approved
BCTC2507343539-2E	2025-09-26	Original	Valid

TEC
TC
OVER
t See



2. Product Information

2.1 Product Information

Model/Type Reference: W707

P/N code Differences: All the P/N code and test models are the same circuit and RF module, except for the sales platform.

Hardware Version: A1

Software Version: A1

Operation Frequency: Phone:5W+7.5W:112-148.5kHz; 15W: 360kHz
Airpods:112kHz-148.5kHz
Watch:326.5kHz; 1.778MHz

Modulation: ASK

Antenna installation: Loop Coil antenna 1 for Phone
Loop Coil antenna 2 for watch
Loop Coil antenna 3 for Airpods

Ratings: USB-C1 Input: 5.0V $\overline{=}$ 3.0A/9.0V $\overline{=}$ 3A /12.0V $\overline{=}$ 2.5A
Wireless Charging Total Output Power: 25.0W Max(iPhone:15.0W,
Apple Watch/Airpods: 5.0W)

Adapter Information: Manufacture: Ugreen Group Limited
Model No.:CD319
Input: 100-240V~ 50/60Hz 800mA Max
Output: 5.0V $\overline{=}$ 3.0A, 9.0V $\overline{=}$ 3.0A,
12.0V $\overline{=}$ 2.5A, 15V $\overline{=}$ 2.0A, 20V $\overline{=}$ 1.5A,
3.3-11.0V $\overline{=}$ 2.7A

Remark:

- P/N code in the below table, for marketing purpose, will be marked on the marking plate.

45058	45058P	45058X	45058A	45058B	45058U	45058JP	45058ZD
45024	45024P	45024X	45024A	45024B	45024U	45024JP	45024ZD
45980	45980P	45980X	45980A	45980B	45980U	45980JP	45980ZD

2.2 Support Equipment

No.	Device Type	Brand	Model	Series No.	Note
E-1	3-in-1 Magnetic Wireless Charger	UGREEN	W707	N/A	EUT
E-2	Adapter	UGREEN	CD319	N/A	EUT
E-3	Phone	APPLE	8P(5W/7.5W)	N/A	Auxiliary
E-4	Airpods	APPLE	Pro 2	N/A	Auxiliary
E-5	Watch	APPLE	S9	N/A	Auxiliary
E-6	Phone	APPLE	16 Pro Max(15W)	N/A	Auxiliary

Notes:

1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.
2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.

2.3 Test Mode

Test Mode	Description of Mode
1	EUT+ Mobile Phone 5W+ Apple Watch 3W+Airpod 5W (Battery Status: <1%)
2	EUT+ Mobile Phone 5W+ Apple Watch 3W+Airpod 5W (Battery Status: <50%)
3	EUT+ Mobile Phone 5W+ Apple Watch 3W+Airpod 5W (Battery Status: <90%)
4	EUT+ Mobile Phone 15W+ Apple Watch 5W+Airpod 5W (Battery Status: <1%)
5	EUT+ Mobile Phone 15W+ Apple Watch 5W+Airpod 5W (Battery Status: <50%)
6	EUT+ Mobile Phone 15W+ Apple Watch 5W+Airpod 5W (Battery Status: <90%)

Note: All test mode were tested and passed, only shows the worst case mode which were recorded in this report.

3. Test Facility And Test Instrument Used

3.1 Test Facility

All measurement facilities used to collect the measurement data are located at Shenzhen BCTC Testing Co., Ltd. Address:1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China. The site and apparatus are constructed in conformance with the requirements of ANSI C63.4 and CISPR 16-1-1 other equivalent standards.

FCC Test Firm Registration Number: 712850

A2LA certificate registration number is: CN1212

ISED Registered No.: 23583

ISED CAB identifier: CN0017

3.2 Test Instrument Used

EMF Test					
Equipment	Manufacturer	Model#	Serial#	Last Cal.	Next Cal.
Magnetic Amplitude and Gradient Probe System	Schmid & Partner Engineering AG	MAGPy -8H3D+E3D V2	3077	2024-12-11	2025-12-10
Magnetic Amplitude and Gradient Probe System	Schmid & Partner Engineering AG	MAGPy-DAS V2	3066	2024-12-11	2025-12-10
Software	Schmid & Partner Engineering AG	MAGPy 2.8	2.8.1	/	/


4. Method Of Measurement

4.1 Applicable Standard


According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines. According to §1.1310 and §2.1093 RF exposure is calculated. According KDB680106 D01v04: RF Exposure Wireless Charging Apps v04.

4.2 Block Diagram Of Test Setup

A:



B:



4.3 Limit

Limits for Occupational / Controlled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842 / f	4.89 / f	(900 / f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-100,000			5	6

Limits for General Population / Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/ cm ²)	Averaging Time E ² , H ² or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180 / f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-100,000			1	30

4.4 Test procedure

- The RF exposure test was performed in anechoic chamber.
- The measurement probe was placed at 0 cm surrounding the device for test setup A; and the measurement Probe was placed from 0 cm to 20 cm, in 2 cm maximum increment measured from the edge of the device For the test setup B.
- The highest emission level was recorded and compared with limit as soon as measurement of each
- The highest emission level was recorded and compared with limit as soon as measurement of each points (A, B, C, D, E , F) were completed.
- The EUT was measured according to the dictates of KDB680106 D01v04.
- Remark: The EUT's test position A, B, C, D , E and F is valid for the E and H field measurements.

4.5 Equipment Approval Considerations

The EUT does comply with item 5(b) of KDB 680106 D01v04

1) Power transfer frequency is less than 1MHz

No, the device operate in the frequency range from 112-148.5kHz, 360kHz, 326.5kHz, 1.778MHz.

2) Output power from each primary coil is less than or equal to 15 watts.

Yes, the maximum output power of the primary coil is 15W.

3) A client device providing the maximum permitted load is placed in physical contact with the transmitter.

Yes, client device is placed directly in contact with the transmitter.

4) Only § 2.1091-Mobile exposure conditions apply

Yes, the EUT is Mobile condition assessment

5) The E-field and H-field strengths, at and beyond 20 cm surrounding the device surface, are demonstrated to be less than 50% of the applicable MPE limit, per KDB 447498, Table 1.

Yes, Conform to

6) For systems with more than one radiating structure, the conditions specified in (5) must be met when the system is fully loaded (i.e., clients absorbing maximum power available), and with all the radiating structures operating at maximum power at the same time.

Yes, confirm.

4.6 E and H field Strength

We measured the H-Field Strength of 20cm, 22cm and 24cm, and recorded the test data of the worst 20cm.

Mobile: Test Mode 1 (the worst mode)

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

Test mode	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
Full Load	0.35	0.25	0.18	0.15	0.21	0.08	0.815	1.63

E-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

Test mode	Test Position A(V/m)	Test Position B(V/m)	Test Position C(V/m)	Test Position D(V/m)	Test Position E(V/m)	Test Position Top(V/m)	50% Limits Test (V/m)	Limits Test (V/m)
Full Load	2.52	2.12	1.95	1.58	1.25	1.45	307	614

Mobile: Test Mode 4 (the worst mode)

H-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT


Test mode	Test Position A(A/m)	Test Position B(A/m)	Test Position C(A/m)	Test Position D(A/m)	Test Position E(A/m)	Test Position Top(A/m)	50% Limits Test (A/m)	Limits Test (A/m)
Full Load	0.36	0.33	0.24	0.18	0.23	0.12	0.815	1.63

E-Field Strength at 20 cm surrounding the EUT and 20cm above the top surface of the EUT

Test mode	Test Position A(V/m)	Test Position B(V/m)	Test Position C(V/m)	Test Position D(V/m)	Test Position E(V/m)	Test Position Top(V/m)	50% Limits Test (V/m)	Limits Test (V/m)
Full Load	2.46	2.21	2.03	1.65	1.34	1.49	307	614

5. Photographs Of Test Set-Up

NOTE: Appendix-Test Photos



STATEMENT

1. The equipment lists are traceable to the national reference standards.
2. The test report can not be partially copied unless prior written approval is issued from our lab.
3. The test report is invalid without the "special seal for inspection and testing".
4. The test report is invalid without the signature of the approver.
5. The test process and test result is only related to the Unit Under Test.
6. Sample information is provided by the client and the laboratory is not responsible for its authenticity.
7. The quality system of our laboratory is in accordance with ISO/IEC17025.
8. If there is any objection to this test report, the client should inform issuing laboratory within 15 days from the date of receiving test report.

Address:

1-2/F., Building B, Pengzhou Industrial Park, No.158, Fuyuan 1st Road, Zhancheng, Fuhai Subdistrict, Bao'an District, Shenzhen, Guangdong, China

TEL: 400-788-9558

P.C.: 518103

FAX: 0755-33229357

Website: <http://www.chnbctc.com>

Consultation E-mail: bctc@bctc-lab.com.cn

Complaint/Advice E-mail: advice@bctc-lab.com.cn

***** END *****