



MPE Calculation

Applicant:	Ugreen Group Limited
Address:	UGREEN Building, Longcheng Industrial Park Longguanxi Road, Longhua Shenzhen
Product:	300W 8-Port GaN Desktop Fast Charger
FCC ID:	2AQI5-X783
Model No.:	X783
Reference RF report #	709502606378-00A, 709502606378-00B

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4\pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);



Calculated Data: BLE

Maximum peak output power at antenna input terminal (dBm):	4.41
Maximum peak output power at antenna input terminal (mW):	2.76
Output power tune-up tolerance (dB)	± 1.0
Maximum tune-up conducted power(dBm):	5.51
Maximum tune-up conducted power(mW):	3.48
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	3.75
Maximum Antenna Gain (numeric):	2.37
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0016
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.00

Note: The maximum tune-up conducted power (5.51 dBm) was declared by the manufacturer.

The max power density 0.0016 (mW/cm²) < 1 (mW/cm²)

Result: Compliant

Calculated Data: Wi-Fi

Maximum peak output power at antenna input terminal (dBm):	14.69
Maximum peak output power at antenna input terminal (mW):	29.44
Output power tune-up tolerance (dB)	± 1.0
Maximum tune-up conducted power(dBm):	15.69
Maximum tune-up conducted power(mW):	37.07
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	3.75
Maximum Antenna Gain (numeric):	2.37
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0175
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.00

Note: The maximum tune-up conducted power (15.59 dBm) was declared by the manufacturer.

The max power density 0.0175 (mW/cm²) < 1 (mW/cm²)

Result: Compliant

Remark: The device does not support simultaneous Wi-Fi 2.4GHz and 2.4GHz BLE, because the Wi-Fi 2.4GHz and 2.4GHz BLE share the same antenna and can't transmit simultaneously. There is not simultaneous transmission possibility.



- TÜV SÜD Products Testing (Shanghai) Co., Ltd.

FCC-Registration No.: 820234 Designation Number: CN1183

ISED Company Number: 31668 CAB identifier: CN0101

Reviewed by:

Prepared by:

Tested by:

Hui Tong

Jiayi XU

chengjie GUO

Hui TONG

Jiayi XU

Chengjie GUO

Review Engineer


Project Engineer

EMC Test Engineer

Date: 2026-07-09

Date: 2026-07-09

Date: 2026-07-09



-----End of Test Report-----