ELECTROMAGNETIC EMISSION COMPLIANCE REPORT FOR LOW-POWER, NON-LICENSED TRANSMITTER

Test Report No.	**: OT-186-RWD-014**
AGR No.	**: A184A-386**
Applicant	**: BROS&COMPANY INC.**
Address	**: A-101, InnoValley, 253, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea 13486**
Manufacturer	**: BROS&COMPANY INC.**
Address	**: A-101, InnoValley, 253, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea 13486**
Type of Equipment	**: LED Table Lamp With Bluetooth Speaker**
FCC ID.	**: 2AQIS-POUT-00101**
Model Name	**: POUT-EYES1**
Multiple Model Name:	**N/A**
Serial number	**: N/A**
Total page of Report	**: 62 pages (including this page)**
Date of Incoming	**: May 02, 2018**
Date of issue	**: June 12, 2018**

SUMMARY

The equipment complies with the regulation; ***FCC PART 15 SUBPART C Section 15.247***

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.

Reviewed by: Jae-Ho Lee / Chief Engineer
ONETECH Corp.

Approved by: Keun-Young, Choi / Vice President
ONETECH Corp.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

CONTENTS

PAGE

1. VERIFICATION OF COMPLIANCE **5**

2. TEST SUMMARY **6**

2.1 TEST ITEMS AND RESULTS 6

2.2 ADDITIONS, DEVIATIONS, EXCLUSIONS FROM STANDARDS 6

2.3 RELATED SUBMITTAL(S) / GRANT(S) 6

2.4 PURPOSE OF THE TEST 6

2.5 TEST METHODOLOGY 6

2.6 TEST FACILITY 7

3. GENERAL INFORMATION **8**

3.1 PRODUCT DESCRIPTION 8

3.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT. 8

4. EUT MODIFICATIONS **8**

5. SYSTEM TEST CONFIGURATION **9**

5.1 JUSTIFICATION 9

5.2 PERIPHERAL EQUIPMENT 9

5.3 MODE OF OPERATION DURING THE TEST 10

5.4 CONFIGURATION OF TEST SYSTEM 10

5.5 ANTENNA REQUIREMENT 10

6. PRELIMINARY TEST **11**

6.1 AC POWER LINE CONDUCTED EMISSIONS TESTS 11

6.2 GENERAL RADIATED EMISSIONS TESTS 11

7. MINIMUM 20 DB BANDWIDTH **12**

7.1 OPERATING ENVIRONMENT 12

7.2 TEST SET-UP 12

7.3 TEST EQUIPMENT USED 12

7.4 TEST DATA FOR 1 MBPS 13

7.5 TEST DATA FOR 2 MBPS 15

8. HOPPING FREQUENCY SEPARATION 17

8.1 OPERATING ENVIRONMENT 17

8.2 TEST SET-UP 17

8.3 TEST EQUIPMENT USED 17

8.4 TEST DATA FOR 1 MBPS 18

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

8.5 TEST DATA FOR 2 MBPS 19
9. NUMBER OF HOPPING CHANNELS 20
9.1 OPERATING ENVIRONMENT 20
9.2 TEST SET-UP 20
9.3 TEST EQUIPMENT USED 20
9.4 TEST DATA FOR 1 MBPS 21
9.5 TEST DATA FOR 2 MBPS 24
10. TIME OF OCCUPANCY 27
10.1 OPERATING ENVIRONMENT 27
10.2 TEST SET-UP 27
10.3 TEST EQUIPMENT USED 27
10.4 TEST DATA FOR 1 MBPS 28
10.5 TEST DATA FOR 2 MBPS 31
11. MAXIMUM PEAK OUTPUT POWER 34
11.1 OPERATING ENVIRONMENT 34
11.2 TEST SET-UP 34
11.3 TEST EQUIPMENT USED 34
11.4 TEST DATA FOR 1 MBPS 35
11.5 TEST DATA FOR 2 MBPS 38
12. 100 KHZ BANDWIDTH OUTSIDE THE FREQUENCY BAND 41
12.1 OPERATING ENVIRONMENT 41
12.2 TEST SET-UP FOR CONDUCTED MEASUREMENT 41
12.3 TEST SET-UP FOR RADIATED MEASUREMENT 41
12.4 TEST EQUIPMENT USED 41
12.5 TEST DATA FOR CONDUCTED EMISSION 42
12.5.1 Test data for 1 Mbps *42*
12.5.2 Test data for 2 Mbps *48*
12.6 Test data for Transmitting Mode radiated emission *54*
12.6.1 Radiated Emission which fall in the Restricted Band *54*
13. CONDUCTED EMISSION TEST **60**
13.1 OPERATING ENVIRONMENT 60
13.2 TEST SET-UP 60
13.3 TEST EQUIPMENT USED 60
13.4 TEST DATA FOR TRANSMITTING MODE 61

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-186-RWD-014	June 12, 2018	Initial Issue	All

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

1. VERIFICATION OF COMPLIANCE

APPLICANT	: BROS&COMPANY INC.
ADDRESS	: A-101, InnoValley, 253, Pangyo-ro, Bundang-gu, Seongnam-si, Gyeonggi-do, Korea 13486
CONTACT PERSON	: PARK KIYEOL / CEO
TELEPHONE NO	: +82-31-286-8646
FCC ID	: 2AQIS-POUT-00101
MODEL NAME	: POUT-EYES1
SERIAL NUMBER	: N/A
DATE	: June 12, 2018

EQUIPMENT CLASS	***DSS – PART 15 SPREAD SPECTRUM TRANSMITTER***
KIND OF EQUIPMENT	LED Table Lamp With Bluetooth Speaker
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	ANSI C63.10: 2013
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
EQUIPMENT WILL BE OPERATED UNDER FCC RULES PART(S)	FCC PART 15 SUBPART C Section 15.247
MODIFICATIONS ON THE EQUIPMENT TO ACHIEVE COMPLIANCE	None
FINAL TEST WAS CONDUCTED ON	3 m Semi Anechoic Chamber

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FC C Rules and Regulations. This said equipment in the configuration described in this report, shows the maximu m emission levels emanating from equipment are within the compliance requirements.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

2. TEST SUMMARY

2.1 Test items and results

SECTION	TEST ITEMS	RESULTS
15.247 (a) (1)	Carrier Frequency Separation	Met the Limit / PASS
15.247 (a) (1) (iii)	Minimum Number of Hopping Channels	Met the Limit / PASS
15.247 (a) (1) (iii)	Average Time of Occupancy	Met the Limit / PASS
15.247 (b) (1)	Maximum Peak Conducted Output Power	Met the Limit / PASS
15.247 (d)	100 kHz Bandwidth Outside the Frequency Band	Met the Limit / PASS
15.247 (d)	Radiated Emission which fall in the Restricted Band	Met the Limit / PASS
15.209	Radiated Emission Limits, General Requirement	Met the Limit / PASS
15.207	Conducted Limits	Met the Limit / PASS
15.203	Antenna Requirement	Met requirement / PASS

2.2 Additions, deviations, exclusions from standards

No additions, deviations or exclusions have been made from standard.

2.3 Related Submittal(s) / Grant(s)

Original submittal only

2.4 Purpose of the test

To determine whether the equipment under test fulfills the requirements of the regulation stated in FCC PART 15 SUBPART C Section 15.247

2.5 Test Methodology

Both conducted and radiated testing was performed according to the procedures in ANSI C63.10: 2013. Radiated testing was performed at a distance of 3 m from EUT to the antenna.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

2.6 Test Facility

The Onetech Corp. has been designated to perform equipment testing in compliance with ISO/IEC 17025.

The Electromagnetic compatibility measurement facilities are located at 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea

-. Site Filing:

VCCI (Voluntary Control Council for Interference) – Registration No. R-4112/ C-14617/ G-10666 / T-1842

IC (Industry Canada) – Registration No. Site# 3736A-3

-. Site Accreditation:

KOLAS (Korea Laboratory Accreditation Scheme) - Accreditation NO. KT085

FCC (Federal Communications Commission) - Accreditation No. KR0013

RRA (Radio Research Agency) – Designation No. KR0013

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

3. GENERAL INFORMATION

3.1 Product Description

The BROS&COMPANY INC., Model POUT-EYES1 (referred to as the EUT in this report) is a LED Table Lamp With Bluetooth Speaker. The product specification described herein was obtained from product data sheet or user's manual.

DEVICE TYPE	LED Table Lamp With Bluetooth Speaker	
OPERATING FREQUENCY	2 402 MHz ~ 2 480 MHz	
RF OUTPUT POWER	1 Mbps	-9.85 dBm
	2 Mbps	-9.65 dBm
NUMBER OF CHANNEL	79 Channels	
MODULATION TYPE	GFSK for 1 Mbps, π/4-DQPSK for 2 Mbps,	
ANTENNA TYPE	PCB Antenna	
ANTENNA GAIN	-0.58 dBi	
LIST OF EACH OSC. OR CRYSTAL. FREQ.(FREQ.>=1 MHz)	24 MHz	
RATED SUPPLY VOLTAGE	DC 5.0 V	

3.2 Alternative type(s)/model(s); also covered by this test report.

-. None

4. EUT MODIFICATIONS

-. None

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

5. SYSTEM TEST CONFIGURATION

5.1 Justification

This device was configured for testing in a typical way as a normal customer is supposed to be used. During the test, the following components were installed inside of the EUT.

DEVICE TYPE	MANUFACTURER	MODEL/PART NUMBER	FCC ID
Main Board	N/A	POUT – EYES1 V02	N/A

5.2 Peripheral equipment

Model	Manufacturer	Description	Connected to
POUT – EYES1	BROS&COMPANY INC.	POUT – EYES1	Notebook PC
G6-1121TV	HP	Notebook PC	EUT, AC/DC Adapter
PPP009C	HP	AC/DC Adapter	Notebook PC

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

5.3 Mode of operation during the test

For Bluetooth function testing, software used to control the EUT for staying in continuous transmitting and receiving mode is programmed. The EUT was set at Low Channel (2 402 MHz), Middle Channel (2 441 MHz), and High Channel (2 480 MHz) with each data transfer rate, 1 Mbps, 2 Mbps, and 3 Mbps. To get a maximum radiated emission levels from the EUT, the EUT was moved throughout the XY, XZ, and YZ planes and the worst case is "XY" axis, but the worst data was recorded in this test report.

5.4 Configuration of Test System

Line Conducted Test: The EUT was tested in a Charging & Transmitting mode. The EUT was connected to USB and the power of USB was connected to Notebook PC. All supporting equipments were connected to another LISN. Preliminary Power line Conducted Emission test was performed by using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions.

Radiated Emission Test: The EUT was tested in a Charging & Transmitting mode. Preliminary radiated emissions test were conducted using the procedure in ANSI C63.10: 2013 to determine the worse operating conditions. Final radiated emission tests were conducted at 3 m Semi Anechoic Chamber.

The turntable was rotated through 360 degrees and the EUT was tested by positioned three orthogonal planes to obtain the highest reading on the field strength meter. Once maximum reading was determined, the search antenna was raised and lowered in both vertical and horizontal polarization.

5.5 Antenna Requirement

For intentional device, according to section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

Antenna Construction:

The transmitter antenna of the EUT is a PCB Antenna, so no consideration of replacement by the user.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

6. PRELIMINARY TEST

6.1 AC Power line Conducted Emissions Tests

During Preliminary Tests, the following operating mode was investigated

Operation Mode	The Worse operating condition (Please check one only)
Transmitting Mode	X

6.2 General Radiated Emissions Tests

During Preliminary Tests, the following operating modes were investigated

Operation Mode	The Worse operating condition (Please check one only)
Transmitting mode.	X

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

7. MINIMUM 20 dB BANDWIDTH

7.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H.

7.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The resolution bandwidth is set to 10 k Hz, and peak detection was used. The 20 dB bandwidth is defined as the total spectrum over which the power i s higher than the peak power minus 20 dB.



7.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

7.4 Test data for 1 Mbps

-. Test Date : May 03, 2018

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402	668.30
Middle	2 441	665.30
High	2 480	665.30

Tested by: Min-Gu Ji / Assistant Manager



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

7.5 Test data for 2 Mbps

-. Test Date : May 03, 2018

CHANNEL	FREQUENCY (MHz)	20 dB Bandwidth (kHz)
Low	2 402	1106.90
Middle	2 441	1122.90
High	2 480	1118.90

Tested by: Min-Gu Ji / Assistant Manager



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel



High Channel

8. HOPPING FREQUENCY SEPARATION

8.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H.

8.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 10 MHz. The analyzer is set to peak hold then a pseudo-random hopping sequence of the transmitter is captured. The mar k delta function was used to measure the frequency separation between two adjacent hopping channels.



8.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

8.4 Test data for 1 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
1007.00	443.53	Separated by a minimum of 25 kHz

Tested by: Min-Gu Ji / Assistant Manager



ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

8.5 Test data for 2 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

MEASURED VLAUE (kHz)	Two-third of 20 dB Bandwidth (kHz)	LIMIT
1001.00	748.60	Separated by a minimum of 25 kHz

Tested by: Min-Gu Ji / Assistant Manager



ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

9. NUMBER OF HOPPING CHANNELS

9.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H.

9.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The frequency span is set to 100 MHz and the resolution bandwidth is set to 1 MHz. The analyzer is set to peak hold and then complete pseudo-random hopping sequence of the transmitter is captured.



9.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

9.4 Test data for 1 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
1 Mbps	79	Minimum of 15	64

Tested by: Min-Gu Ji / Assistant Manager



Total number of hopping channel: 28+30+21 = 79

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Number of hopping channel: 28



Number of hopping channel: 30

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Number of hopping channel: 21

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

9.5 Test data for 2 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

Data Transfer Rate	Measured value (Number)	Limit (Number)	Margin (Number)
2 Mbps	79	Minimum of 15	64

Tested by: Min-Gu Ji / Assistant Manager



Total number of hopping channel: 28+30+21 = 79

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Number of hopping channel: 28



Number of hopping channel: 30

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Number of hopping channel: 21

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

10. TIME OF OCCUPANCY

10.1 Operating environment

Temperature	:	24 ℃
Relative humidity	:	43 % R.H.

10.2 Test set-up

The antenna output of the EUT was connected to the spectrum analyzer. The transmitter is set to operate in its normal frequency hopping mode. The center frequency of the spectrum analyzer is set to one of hopping channels near the center of the operating band and span is set to zero Hz. The sweep time is set to display one complete pulse. The mark delta function is used to measure the duration of the pulses.



10.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

10.4 Test data for 1 Mbps

-. Test Date : May 03, 2018

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for DH1, and 5.06 times (= 1 600/4/79) for DH3, and 3.38 times (= 1 600/6/79) for DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (s)	Total Dwell Time (ms)	Limit (ms)	Test Result
DH1	0.400	10.13	31.6	128.04	400	PASS
DH3	1.670	5.060	31.6	267.03	400	
DH5	2.910	3.38	31.6	310.81	400	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.

Tested by: Min-Gu Ji / Assistant Manager

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



DH1



DH3

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



DH5

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

10.5 Test data for 2 Mbps

-. Test Date : May 03, 2018

The system makes worst case 1 600 hops per second or 1 time slot has a length of 625 μs with 79 channels.

For 2-DH1 packet type, the EUT needs 1 time slot for transmitting and 1 time slot for receiving and for 2-DH3 packet type, the EUT needs 3 times slots for transmitting and 1 time slot for receiving, and 2-DH5 packet needs 5 times slots for transmitting and 1 time slot for receiving. So The EUT has each channel for 10.13 times per second (= 1 600/2/79) for 2-DH1, and 5.06 times (= 1 600/4/79) for 2-DH3, and 3.38 times (= 1 600/6/79) for 2-DH5.

Packet Type	Pulse Time (ms)	Hops per second with channels	Period Time (s)	Total Dwell Time (ms)	Limit (ms)	Test Result
2-DH1	0.420	10.13	31.6	134.45	400	PASS
2-DH3	1.670	5.060	31.6	267.03	400	
2-DH5	2.920	3.38	31.6	311.88	400	

Total dwell time is calculated as following.

Total Dwell Time = Pulse time * Hops per second with channels * period time

Remark: See next page for an overview sweep performed with peak detector.

Tested by: Min-Gu Ji / Assistant Manager



2-DH1



2-DH3

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



2-DH5

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

11. MAXIMUM PEAK OUTPUT POWER

11.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H

11.2 Test set-up

The maximum peak output power was measured with the spectrum analyzer connected to the antenna output of the EUT. The EUT was operating in transmit mode at the appropriate center frequency.



11.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal.
■ -	FSV40	Rohde & Schwarz	Signal Analyzer	101009	Mar. 14, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

11.4 Test data for 1 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402	-11.08	21.00	32.08
MIDDLE	2 441	-10.27	21.00	31.27
HIGH	2 480	-9.85	21.00	30.85

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Min-Gu Ji / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Low Channel



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

11.5 Test data for 2 Mbps

-. Test Date : May 03, 2018

-. Test Result : Pass

CHANNEL	FREQUENCY (MHz)	MEASURED VLAUE (dBm)	LIMIT (dBm)	MARGIN (dB)
LOW	2 402	-9.77	21.00	30.77
MIDDLE	2 441	-9.65	21.00	30.65
HIGH	2 480	-9.71	21.00	30.71

Remark. Margin = Limit – Measured Value (=Receiver Reading + Cable Loss)

Tested by: Min-Gu Ji / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Low Channel



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

12. 100 kHz BANDWIDTH OUTSIDE THE FREQUENCY BAND

12.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H

12.2 Test set-up for conducted measurement

The antenna output of the EUT was connected to the spectrum analyzer. The resolution and video bandwidth is set to 100 kHz, and peak detection was used.



12.3 Test set-up for radiated measurement

The radiated emissions measurements were performed on the 3 m, open-field test site. The EUT was placed on a non-conductive turntable approximately 0.8 m above the ground plane.

The frequency spectrum from 30 kHz to 26.5 GHz was scanned and maximum emission levels at each frequency recorded. The system was rotated 360°, and the antenna was varied in the height between 1.0 m and 4.0 ms in order to determine the maximum emission levels. This procedure was performed for horizontal and vertical polarization of the receiving antenna.

12.4 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
☐ -	ESCI	Rohde & Schwarz	EMI Test Receiver	101012	Oct. 27, 2017 (1Y)
■ -	ESR	Rohde & Schwarz	EMI Test Receiver	101470	Oct. 27, 2017 (1Y)
☐ -	FSP	Rohde & Schwarz	Spectrum Analyzer	100017	Sep. 04, 2017 (1Y)
■ -	310N	Sonoma Instrument	AMPLIFIER	312544	Mar. 28, 2018 (1Y)
■ -	FSV30	Rohde & Schwarz	Signal Analyzer	101200	Oct. 26, 2017 (1Y)
■ -	SCU-18	Rohde & Schwarz	Pre-Amplifier	102346	Oct. 24, 2017 (1Y)
■ -	MA-4000XPET	Innco Systems GmbH	Antenna Master	MA4000/509	N/A
☐ -	HD100	HD GmbH	Position Controller	N/A	N/A
■ -	DT3000-3t	Innco Systems GmbH	Turn Table	N/A	N/A
☐ -	FMZB 1513	Schwarzbeck	LOOP ANTENNA	1513-235	May. 13, 2018 (2Y)
■ -	VULB9163	Schwarzbeck	TRILOG Broadband Antenna	9163-419	Aug. 05, 2016 (2Y)
■ -	BBHA9120D	Schwarzbeck	Horn Antenna	BBHA9120D295	Aug. 16, 2017 (2Y)
■ -	BBHA9170	Schwarzbeck	Horn Antenna	BBHA91700179	Jul. 28, 2017 (2Y)
■ -	BBV 9718 B	Schwarzbeck	Broadband Preamplifier	009	Mar. 16, 2018(1Y)
☐ -	83051A	Agilent	Microwave System Preamplifer	3950M00201	Mar. 15, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

12.5 Test data for conducted emission

12.5.1 Test data for 1 Mbps



Low Channel



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

12.5.2 Test data for 2 Mbps



Low Channel



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Low Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



Middle Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)



High Channel

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

12.6 Test data for Transmitting Mode radiated emission

12.6.1 Radiated Emission which fall in the Restricted Band

12.6.1.1 Test data for 1 Mbps

-. Test Date : May 05, 2018

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 3 MHz for Peak and Average Mode

-. Detector : Peak Mode(Peak), Average Mode(RMS)

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode(Low Channel and High Channel)

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)
Test Data for Low Channel									
2341.76	40.31	Peak	H	27.60	11.40	33.60	45.71	74.00	28.29
2340.80	28.43	Average	H				33.83	54.00	20.17
2362.94	39.05	Peak	V				44.45	74.00	29.55
2343.12	28.31	Average	V				33.71	54.00	20.29
Test Data for High Channel									
2492.78	40.71	Peak	H	27.80	11.40	33.60	46.31	74.00	27.69
2489.82	28.24	Average	H				33.84	54.00	20.16
2488.61	41.32	Peak	V				46.92	74.00	27.08
2492.12	28.54	Average	V				34.14	54.00	19.86

Tabulated test data for Restricted Band

Remark: “H”: Horizontal, “V”: Vertical

Tested by: Min-Gu Ji / Assistant Manager

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

12.6.1.2 Test data for 2 Mbps

-. Test Date : May 05, 2018

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 3 MHz for Peak and Average Mode

-. Detector : Peak Mode(Peak), Average Mode(RMS)

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode(Low Channel and High Channel)

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBµV/m)	Limits (dBµV/m)	Margin (dB)
Test Data for Low Channel									
2386.52	39.97	Peak	H	27.60	11.40	33.60	45.37	74.00	28.63
2341.60	28.72	Average	H				34.12	54.00	19.88
2337.37	38.96	Peak	V				44.36	74.00	29.64
2340.33	28.65	Average	V				34.05	54.00	19.95
Test Data for High Channel									
2493.97	40.33	Peak	H	27.80	11.40	33.60	45.93	74.00	28.07
2498.29	28.68	Average	H				34.28	54.00	19.72
2494.68	40.62	Peak	V				46.22	74.00	27.78
2489.55	27.99	Average	V				33.59	54.00	20.41

Tabulated test data for Restricted Band

Remark: “H”: Horizontal, “V”: Vertical

Tested by: Min-Gu Ji / Assistant Manager

12.6.2 Spurious & Harmonic Radiated Emission above 1 GHz

12.6.2.1 Test data for 1 Mbps

-. Test Date : May 05, 2018

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 3 MHz for Peak and Average Mode

-. Detector : Peak Mode(Peak), Average Mode(RMS)

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 804.00	40.55	Peak	H	31.00	16.10	32.90	54.75	74.00	19.25
	29.33	Average	H				43.53	54.00	10.47
	42.13	Peak	V				56.33	74.00	17.67
	29.35	Average	V				43.55	54.00	10.45
Test Data for Middle Channel									
4 882.00	38.42	Peak	H	31.10	16.10	33.00	52.62	74.00	21.38
	25.89	Average	H				40.09	54.00	13.91
	40.78	Peak	V				54.98	74.00	19.02
	30.26	Average	V				44.46	54.00	9.54
Test Data for High Channel									
4 960.00	39.93	Peak	H	31.20	16.10	33.10	54.13	74.00	19.87
	27.61	Average	H				41.81	54.00	12.19
	40.15	Peak	V				54.35	74.00	19.65
	29.67	Average	V				43.87	54.00	10.13

Tabulated test data for Restricted Band

Remark: “H”: Horizontal, “V”: Vertical, “*” Frequency fall in restricted band

Tested by: Min-Gu Ji / Assistant Manager

12.6.2.2 Test data for 2 Mbps

-. Test Date : May 05, 2018

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Video bandwidth : 3 MHz for Peak and Average Mode

-. Detector : Peak Mode(Peak), Average Mode(RMS)

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (GHz)	Reading (dBμV)	Detector Mode	Ant. Pol. (H/V)	Ant. Factor	Cable Loss	Amp Gain	Total (dBμV/m)	Limits (dBμV/m)	Margin (dB)
Test Data for Low Channel									
4 804.00	41.48	Peak	H	31.00	16.10	32.90	55.68	74.00	18.32
	29.29	Average	H				43.49	54.00	10.51
	41.05	Peak	V				55.25	74.00	18.75
	28.75	Average	V				42.95	54.00	11.05
Test Data for Middle Channel									
4 882.00	37.62	Peak	H	31.10	16.10	33.00	51.82	74.00	22.18
	25.12	Average	H				39.32	54.00	14.68
	37.91	Peak	V				52.11	74.00	21.89
	27.30	Average	V				41.50	54.00	12.50
Test Data for High Channel									
4 960.00	37.10	Peak	H	31.20	16.10	33.10	51.30	74.00	22.70
	25.68	Average	H				39.88	54.00	14.12
	39.18	Peak	V				53.38	74.00	20.62
	27.79	Average	V				41.99	54.00	12.01

Tabulated test data for Restricted Band

Remark: “H”: Horizontal, “V”: Vertical, “*” Frequency fall in restricted band

Tested by: Min-Gu Ji / Assistant Manager

12.6.3 Spurious Radiated Emission

12.6.3.1 Test Data for 30 MHz ~ 1 000 MHz

Humidity Level : 53 % R.H. Temperature: 24 ℃

Limits apply to : FCC CFR 47, PART 15, SUBPART C, SECTION 15.247

Result : PASSED

EUT : LED Table Lamp With Bluetooth Speaker Date: May 05, 2018

Detector : CISPR Quasi-Peak (6 dB Bandwidth: 120 kHz)



No.	FREQ [MHz]	READING QP [dBuV]	ANT FACTOR [dB]	LOSS [dB]	GAIN [dB]	RESULT [dBuV/m]	LIMIT [dBuV/m]	MARGIN [dB]	ANTENNA [cm]	TABLE [DEG]
----- Horizontal ------										
1	99.840	50.2	11.9	2.6	33.0	31.7	43.5	11.8	300	231
2	191.020	51.3	10.6	3.6	33.1	32.4	43.5	11.1	200	187
3	431.581	51.1	16.8	5.4	33.2	40.1	46.0	5.9	100	20
4	479.111	48.2	16.8	5.7	33.3	37.4	46.0	8.6	100	30
----- Vertical ------										
5	327.790	47.8	14.0	4.7	33.1	33.4	46.0	12.6	200	359

Tested by: Min-Gu Ji / Assistant Manager

12.6.3.2 Test Data for Below 30 MHz

-. Test Date : May 05, 2018

-. Resolution bandwidth : 200 Hz (from 9 kHz to 0.15 MHz), 9 kHz (from 0.15 MHz to 30 MHz)

-. Frequency range : 9 kHz ~ 30 MHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dBµV/m)	Limits (dBµV/m)	Margin (dB)
20dB less than the limit and thus not included.								

12.6.3.3 Test Data for above 1 GHz

-. Test Date : May 05, 2018

-. Resolution bandwidth : 1 MHz for Peak and Average Mode

-. Frequency range : 1 GHz ~ 26.5 GHz

-. Measurement distance : 3 m

-. Operating Condition : Highest Output Power Transmitting Mode

-. Result : PASSED

Frequency (MHz)	Reading (dBµV)	Ant. Pol. (H/V)	Ant. Factor (dB/m)	Cable Loss	Amp Gain	Emission Level(dBµV/m)	Limits (dBµV/m)	Margin (dB)
20dB less than the limit and thus not included.								

Tested by: Min-Gu Ji / Assistant Manager

13. CONDUCTED EMISSION TEST

13.1 Operating environment

Temperature : 24 ℃

Relative humidity : 45 % R.H.

13.2 Test set-up

The EUT was placed on a wooden table, 0.8 m height above the floor. Power was fed to the EUT through a 5 0 Ω / 50 μH + 5 Ω Artificial Mains Network (AMN). The ground plane was electrically bonded to the referenc e ground system and all power lines were filtered from ambient.

13.3 Test equipment used

	Model Number	Manufacturer	Description	Serial Number	Last Cal. (Interval)
■ -	ESCI	Rohde & Schwarz	EMI Test Receiver	101278	Oct. 27, 2017 (1Y)
☐ -	ESHS10	Rohde & Schwarz	EMI Test Receiver	834467/007	Mar. 29, 2018 (1Y)
☐	NSLK8128	Schwarzbeck	AMN	8128-216	Mar. 28, 2018 (1Y)
☐ -	NSLK8126	Schwarzbeck	AMN	8126-404	Apr. 04, 2018 (1Y)
☐ -	NSLK8126	Schwarzbeck	AMN	8126-479	Oct. 24, 2017 (1Y)
■	NNBM 8124	Schwarzbeck	V-LISN	05066	Oct. 24, 2017 (1Y)
■	NNBM 8124	Schwarzbeck	V-LISN	05019	Oct. 25, 2017 (1Y)
☐ -	3825/2	EMCO	AMN	9109-1869	Apr. 11, 2018 (1Y)

All test equipment used is calibrated on a regular basis.

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

13.4 Test data for Transmitting Mode

-. Test Date : May 05, 2018

-. Resolution bandwidth : 9 kHz

-. Frequency range : 0.15 MHz ~ 30 MHz

-. Tested Line : HOT LINE



NO	FREQ [MHz]	READING QP [dBuV]	READING AV [dBuV]	C.FACTOR [dB]	RESULT QP [dBuV]	RESULT AV [dBuV]	LIMIT QP [dBuV]	LIMIT AV [dBuV]	MARGIN QP [dBuV]	MARGIN AV [dBuV]	PHASE
1	0.17700	40.7	----	9.9	50.6	----	64.6	----	14.0	----	H(QP)
2	0.51200	24.9	----	9.9	34.8	----	56.0	----	21.2	----	H(QP)
3	0.89600	21.7	----	10.0	31.7	----	56.0	----	24.3	----	H(QP)
4	2.95200	17.8	----	10.1	27.9	----	56.0	----	28.1	----	H(QP)
5	7.89500	15.7	----	10.3	26.0	----	60.0	----	34.0	----	H(QP)
6	13.23000	13.3	----	10.5	23.8	----	60.0	----	36.2	----	H(QP)
7	0.17700	----	24.4	9.9	----	34.3	----	54.6	----	20.3	H(CAV)
8	0.51200	----	18.8	9.9	----	28.7	----	46.0	----	17.3	H(CAV)
9	0.89600	----	11.6	10.0	----	21.6	----	46.0	----	24.4	H(CAV)
10	2.95200	----	10.2	10.1	----	20.3	----	46.0	----	25.7	H(CAV)
11	7.89500	----	3.5	10.3	----	13.8	----	50.0	----	36.2	H(CAV)
12	13.23000	----	2.8	10.5	----	13.3	----	50.0	----	36.7	H(CAV)

It should not be reproduced except in full, without the written approval of ONETECH Corp.

ONETECH Corp.: 43-14, Jinsaegol-gil, Chowol-eup, Gwangju-si, Gyeonggi-do, 12735, Korea (TEL: 82-31-799-9500, FAX: 82-31-799-9599)

-. Tested Line : NEUTRAL LINE



NO	FREQ [MHz]	READING QP [dBuV]	READING AV [dBuV]	C.FACTOR [dB]	RESULT QP [dBuV]	RESULT AV [dBuV]	LIMIT QP [dBuV]	LIMIT AV [dBuV]	MARGIN QP [dBuV]	MARGIN AV [dBuV]	PHASE
1	0.19500	38.1	----	9.9	48.0	----	63.8	----	15.8	----	N(QP)
2	0.50500	26.8	----	9.9	36.7	----	56.0	----	19.3	----	N(QP)
3	1.41200	22.9	----	10.0	32.9	----	56.0	----	23.1	----	N(QP)
4	2.69600	17.3	----	10.1	27.4	----	56.0	----	28.6	----	N(QP)
5	5.05000	16.8	----	10.2	27.0	----	60.0	----	33.0	----	N(QP)
6	9.61500	17.5	----	10.4	27.9	----	60.0	----	32.1	----	N(QP)
7	0.19500	----	28.3	9.9	----	38.2	----	53.8	----	15.6	N(CAV)
8	0.50500	----	18.5	9.9	----	28.4	----	46.0	----	17.6	N(CAV)
9	1.41200	----	12.4	10.0	----	22.4	----	46.0	----	23.6	N(CAV)
10	2.69600	----	6.4	10.1	----	16.5	----	46.0	----	29.5	N(CAV)
11	5.05000	----	2.9	10.2	----	13.1	----	50.0	----	36.9	N(CAV)
12	9.61500	----	6.4	10.4	----	16.8	----	50.0	----	33.2	N(CAV)

Remark: Margin (dB) = Limit – Level (Result)

The emission level in above table is included the transducer factor that means insertion loss (LISN), cable loss and attenuator.

Tested by: Min-Gu Ji / Assistant Manager