FCC TEST REPORT

For

Sanho Corporation

HyperJuice 7.5W Wireless Charger

Model No.: HJ258A

Prepared For	:	Sanho Corporation
Address	:	930 Auburn Court, Fremont, California, United States, 94538
Prepared By	:	Shenzhen Anbotek Compliance Laboratory Limited
Address	:	1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102 Tel: (86) 755-26066440 Fax: (86) 755-26014772
Report Number	:	SZAWW180605005-01
Date of Test	:	Jun. 05~12, 2018
Date of Report	:	Jun. 12, 2018

Contents

1. General Information....4
1.1. Client Information....4
1.2. Description of Device (EUT)....4
1.3. Auxiliary Equipment Used During Test....4
1.4. Description of Test Modes....5
1.5. List of channels....5
1.6. Description Of Test Setup....6
1.7. Test Equipment List....7
1.8. Measurement Uncertainty....8
1.9. Description of Test Facility....8
2. Summary of Test Results....9
3. Conducted Emission Test....10
3.1. Test Standard and Limit....10
3.2. Test Setup....10
3.3. Test Procedure....10
3.4. Test Data....10
4. Radiation Spurious Emission and Band Edge....15
4.1. Test Standard and Limit....15
4.2. Test Setup....15
4.3. Test Procedure....16
4.4. Test Data....17
APPENDIX I -- TEST SETUP PHOTOGRAPH....23
APPENDIX II -- EXTERNAL PHOTOGRAPH....25
APPENDIX III -- INTERNAL PHOTOGRAPH....29

TEST REPORT

Applicant	:	Sanho Corporation
Manufacturer	:	Sanho Corporation
Product Name	:	HyperJuice 7.5W Wireless Charger
Model No.	:	HJ258A
Trade Mark	:	HyperJuice
Rating(s)	:	Input Type C: DC 5V, 3A, 15W Input QC 2.0/3.0: DC 5V/9V, 2A, 18W USB output: DC 5V, 2.1A WIRELESS output: DC 5V, 1A / DC 9V, 1.1A
Test Standard(s)	**:**	**FCC Part15 Subpart C 2017, Paragraph 15.209**
Test Method(s)	**:**	**ANSI C63.10: 2013**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with the FCC Part 15 Subpart C requirements.

This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.

Date of Test: Jun. 05~12, 2018

Prepared by: (Engineer / Oliay Yang)

Reviewer: (Supervisor / Calvin Liu)

Approved & Authorized Signer: (Manager / Tom Chen)

1. General Information

1.1. Client Information

Applicant	:	Sanho Corporation
Address	:	930 Auburn Court, Fremont, California, United States, 94538
Manufacturer	:	Sanho Corporation
Address	:	930 Auburn Court, Fremont, California, United States, 94538

1.2. Description of Device (EUT)

Product Name	:	HyperJuice 7.5W Wireless Charger	
Model No.	:	HJ258A	
Trade Mark	:	HyperJuice	
Test Power Supply	:	AC 120V, 60Hz for adapter / AC 240V, 60Hz for adapter	
Test Sample No.	:	S1, S2	
Product Description	:	Operation Frequency:	110-205KHz
		Number of Channel:	20 Channels
		Modulation Type:	MSK
		Antenna Type:	Loop Antenna
		Antenna Gain(Peak):	0 dBi
Remark: 1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.			

1.3. Auxiliary Equipment Used During Test

Adapter	:	PIQ 2.0 Output: 5V⎓ 3A/ 9V⎓ 2A/ 12V⎓ 1.5A USB-C PD Output: 5V⎓ 3A/ 9V⎓ 3A/ 15V⎓ 2A/ 20V⎓ 1.5A
Mobile Phone	:	Samsung

1.4. Description of Test Modes

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

Pretest Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20
Mode 4	Keeping TX+Charging mode

For Conducted Emission	
Final Test Mode	Description
Mode 4	Keeping TX+Charging mode

For Radiated Emission	
Final Test Mode	Description
Mode 1	CH01
Mode 2	CH10
Mode 3	CH20
Mode 4	Keeping TX+Charging mode

1.5. List of channels

Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)	Channel	Freq. (MHz)
1	0.110	6	0.135	11	0.160	16	0.185
2	0.115	7	0.140	12	0.165	17	0.190
3	0.120	8	0.145	13	0.170	18	0.195
4	0.125	9	0.150	14	0.175	19	0.200
5	0.130	10	0.155	15	0.180	20	0.205

1.6. Description Of Test Setup

CE



RE



1.7. Test Equipment List

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	Nov. 17, 2017	1 Year
2.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
3.	RF Switching Unit	Compliance Direction	RSU-M2	38303	Nov. 17, 2017	1 Year
4.	Spectrum Analysis	Agilent	E4407B	US39390582	Nov. 17, 2017	1 Year
5.	Spectrum Analysis	Agilent	N9038A	MY53227295	Nov. 17, 2017	1 Year
6.	Preamplifier	SKET Electronic	BK1G18G30D	KD17503	Nov. 17, 2017	1 Year
7.	EMI Test Receiver	Rohde & Schwarz	ESCI	100627	Nov. 17, 2017	1 Year
8.	Double Ridged Horn Antenna	Instruments corporation	GTH-0118	351600	Nov. 20, 2017	1 Year
9.	Bilog Broadband Antenna	Schwarzbeck	VULB9163	VULB 9163-289	Nov. 20, 2017	1 Year
10.	Loop Antenna	Schwarzbeck	HFH2-Z2	100047	Nov. 17, 2017	1 Year
11.	Horn Antenna	Schewarzbeck	BBHA9170	9170-375	Nov. 17, 2017	1 Year
12.	Pre-amplifier	SONOMA	310N	186860	Nov. 17, 2017	1 Year
13.	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	N/A	N/A
14.	RF Test Control System	YIHENG	YH3000	2017430	Nov. 18, 2017	1 Year
15.	Power Sensor	DAER	RPR3006W	15I00041SN045	Nov. 17, 2017	1 Year
16.	Power Sensor	DAER	RPR3006W	15I00041SN046	Nov. 17, 2017	1 Year
17.	MXA Spectrum Analysis	Agilent	N9020A	MY51170037	Nov. 18, 2017	1 Year
18.	MXG RF Vector Signal Generator	Agilent	N5182A	MY48180656	Nov. 18, 2017	1 Year
19.	Signal Generator	Agilent	E4421B	MY41000743	Nov. 18, 2017	1 Year
20.	DC Power Supply	LW	TPR-6410D	349315	Nov. 01, 2017	1 Year
21.	Constant Temperature Humidity Chamber	Sertep	ZJ-HWHS80B	ZJ-17042804	Nov. 01, 2017	1 Year

1.8. Measurement Uncertainty

Radiation Uncertainty	:	Ur = 3.9 dB (Horizontal)
		Ur = 3.8 dB (Vertical)
Conduction Uncertainty	:	Uc = 3.4 dB

1.9. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.: 184111

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registed and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 184111, July 31, 2017.

ISED-Registration No.: 8058A-1

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A-1, June 13, 2016.

Test Location

All Emissions tests were performed at Shenzhen Anbotek Compliance Laboratory Limited. at 1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.518102

2. Summary of Test Results

Standard Section	Test Item	Result
FCC Part 15, Paragraph 15.207	Conducted Emission Test	PASS
FCC Part 15, Paragraph 15.209(a)(f)	Spurious Emission	PASS

3. Conducted Emission Test

3.1. Test Standard and Limit

Test Standard	FCC Part15 Section 15.207		
Test Limit	Frequency	Maximum RF Line Voltage (dBuV)	
		Quasi-peak Level	Average Level
	150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
	500kHz~5MHz	56	46
	5MHz~30MHz	60	50
Remark: (1) *Decreasing linearly with logarithm of the frequency. (2) The lower limit shall apply at the transition frequency.			

3.2. Test Setup



3.3. Test Procedure

The EUT system is connected to the power mains through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm coupling impedance for the EUT system. Please refer the block diagram of the test setup and photographs. Both sides of AC line are checked to find out the maximum conducted emission. In order to find the maximum emission levels, the relative positions of equipment and all of the interface cables shall be changed according to FCC ANSI C63.10-2013 on Conducted Emission Measurement.

The bandwidth of test receiver (ESCI) set at 9kHz.

The frequency range from 150kHz to 30MHz is checked.

3.4. Test Data

Please to see the following pages

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Keeping TX+Charging mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Live Line

Tem.: 22.2℃ Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	33.44	19.90	53.34	65.78	-12.44	QP	
2	0.2060	28.34	19.90	48.24	63.36	-15.12	QP	
3	0.2380	26.07	19.89	45.96	62.16	-16.20	QP	
4	0.4980	19.00	19.98	38.98	56.03	-17.05	QP	
5	2.3340	14.27	20.15	34.42	46.00	-11.58	AVG	
6	6.1820	17.96	20.24	38.20	50.00	-11.80	AVG	
7	6.4540	19.96	20.25	40.21	50.00	-9.79	AVG	
8	6.7300	23.50	20.25	43.75	60.00	-16.25	QP	
9	6.7300	21.98	20.25	42.23	50.00	-7.77	AVG	
10	7.0060	23.43	20.26	43.69	60.00	-16.31	QP	
11	7.0060	22.14	20.26	42.40	50.00	-7.60	AVG	
12	7.2780	19.25	20.27	39.52	50.00	-10.48	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Keeping TX+Charging mode

Test Specification: AC 120V, 60Hz for adapter

Comment: Neutral Line

Tem.: 22.2℃ Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	34.00	19.90	53.90	65.78	-11.88	QP	
2	0.1980	29.37	19.90	49.27	63.69	-14.42	QP	
3	0.2300	26.46	19.89	46.35	62.45	-16.10	QP	
4	0.5020	19.51	19.98	39.49	56.00	-16.51	QP	
5	2.0620	14.29	20.14	34.43	46.00	-11.57	AVG	
6	2.3340	19.36	20.15	39.51	56.00	-16.49	QP	
7	2.3340	14.22	20.15	34.37	46.00	-11.63	AVG	
8	6.4540	19.26	20.25	39.51	50.00	-10.49	AVG	
9	6.7300	21.84	20.25	42.09	50.00	-7.91	AVG	
10	7.0060	23.04	20.26	43.30	60.00	-16.70	QP	
11	7.0060	21.79	20.26	42.05	50.00	-7.95	AVG	
12	7.2780	19.08	20.27	39.35	50.00	-10.65	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Keeping TX+Charging mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Live Line

Tem.: 22.2℃ Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.1539	32.20	19.90	52.10	65.78	-13.68	QP	
2	0.4780	24.51	19.97	44.48	56.37	-11.89	QP	
3	0.4780	18.75	19.97	38.72	46.37	-7.65	AVG	
4	1.1140	22.35	20.12	42.47	56.00	-13.53	QP	
5	1.7500	22.24	20.13	42.37	56.00	-13.63	QP	
6	2.0740	18.42	20.14	38.56	46.00	-7.44	AVG	
7	6.5420	22.53	20.25	42.78	50.00	-7.22	AVG	
8	6.8620	25.13	20.26	45.39	50.00	-4.61	AVG	
9	7.1820	27.67	20.26	47.93	60.00	-12.07	QP	
10	7.1820	26.60	20.26	46.86	50.00	-3.14	AVG	
11	7.5020	26.21	20.27	46.48	60.00	-13.52	QP	
12	7.5020	24.72	20.27	44.99	50.00	-5.01	AVG	

Conducted Emission Test Data

Test Site: 1# Shielded Room

Operating Condition: Keeping TX+Charging mode

Test Specification: AC 240V, 60Hz for adapter

Comment: Neutral Line

Tem.: 22.2℃ Hum.: 60%



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit dBuV	Over Limit (dB)	Detector	Remark
1	0.4820	24.80	19.97	44.77	56.30	-11.53	QP	
2	1.7620	22.78	20.14	42.92	56.00	-13.08	QP	
3	2.0820	18.24	20.14	38.38	46.00	-7.62	AVG	
4	2.4020	23.41	20.15	43.56	56.00	-12.44	QP	
5	2.4020	18.05	20.15	38.20	46.00	-7.80	AVG	
6	3.0420	22.47	20.16	42.63	56.00	-13.37	QP	
7	6.5620	23.41	20.25	43.66	50.00	-6.34	AVG	
8	6.8820	26.26	20.26	46.52	60.00	-13.48	QP	
9	6.8820	25.17	20.26	45.43	50.00	-4.57	AVG	
10	7.2020	27.11	20.27	47.38	60.00	-12.62	QP	
11	7.2020	26.18	20.27	46.45	50.00	-3.55	AVG	
12	7.5220	23.41	20.27	43.68	50.00	-6.32	AVG	

4. Radiation Spurious Emission and Band Edge

4.1. Test Standard and Limit

Test Standard	FCC Part15 C Section 15.209 and 15.205				
Test Limit	Frequency (MHz)	Field strength (microvolt/meter)	Limit (dBuV/m)	Remark	Measurement distance (m)
	0.009MHz~0.490MHz	2400/F(kHz)	-	-	300
	0.490MHz-1.705MHz	24000/F(kHz)	-	-	30
	1.705MHz-30MHz	30	-	-	30
	30MHz~88MHz	100	40.0	Quasi-peak	3
	88MHz~216MHz	150	43.5	Quasi-peak	3
	216MHz~960MHz	200	46.0	Quasi-peak	3
	960MHz~1000MHz	500	54.0	Quasi-peak	3
	Above 1000MHz	500	54.0	Average	3
		-	74.0	Peak	3

Remark:
(1)The lower limit shall apply at the transition frequency.
(2) 15.35(b), Unless otherwise specified, the limit on peak radio frequency emissions is 20dB above the maximum permitted average emission limit applicable to the equipment under test. This peak limit applies to the total peak emission level radiated by the device.

4.2. Test Setup



Figure 1. Below 30MHz



Figure 2. 30MHz to 1GHz



Figure 3. Above 1 GHz

4.3. Test Procedure

For below 1GHz: The EUT is placed on a turntable, which is 0.8m above the ground plane.
For above 1GHz: The EUT is placed on a turntable, which is 1.5m above the ground plane.
The turn table can rotate 360 degrees to determine the position of the maximum emission level. The EUT is set 3 meters away from the receiving antenna which is mounted on a antenna tower. The antenna can be moved up and down from 1 to 4 meters to find out the maximum emission level. Rotated the EUT through three orthogonal axes to determine the maximum emissions, both horizontal and vertical polarization of the antenna are set on test. The EUT is tested in 9*6*6 Chamber. The device is evaluated in xyz orientation.

For 9kHz to 150kHz, Set the spectrum analyzer as:
RBW = 200Hz, VBW =1kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 150kHz to 30MHz, Set the spectrum analyzer as:

RBW = 9KHz, VBW =30kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

For 30MHz to 1000MHz, Set the spectrum analyzer as:
RBW = 100kHz, VBW =300kHz, Detector= Quasi-Peak, Trace mode= Max hold, Sweep- auto couple.

4.4. Test Data

PASS

Test Results

(Between 9KHz – 30MHz)

Job No.:	**SZAWW180605005-01**		
Standard:	**FCC PART15 C _3m**	**Power Source:**	**AC 120V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**23.3(C)/54%RH**
Test Mode:	**Mode 4**	**Distance:**	**3m**



Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	degree (dge)
0.1107	67.89	19.63	2.59	0	90.11	126.65	-36.54	Peak	129
0.1107	58.60	19.63	2.59	0	80.82	106.65	-25.83	AV	129
0.2220	17.32	19.63	2.59	0	39.54	120.64	-81.10	Peak	233
0.2220	38.06	19.63	2.59	0	60.28	100.64	-40.36	AV	233
0.3339	42.73	19.63	2.59	0	64.95	117.11	-52.16	Peak	304
0.3339	34.66	19.63	2.59	0	56.88	97.11	-40.23	AV	304
0.5540	31.65	19.65	2.61	0	53.91	72.73	-18.82	QP	77
0.7740	23.05	19.68	2.63	0	45.36	69.83	-24.47	QP	168
0.9979	20.95	19.72	2.65	0	43.32	67.62	-24.30	QP	170

Remark：According to FCC PART 15.209 (d), the emission limits for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz, Radiated emission limits in these three bands are based on measurements employing an average detector.

(Between 30MHz –1000 MHz)

Job No.:	**SZAWW180605005-01**	**Polarization:**	**Horizontal**
Standard:	**FCC PART15 C _3m**	**Power Source:**	**AC 120V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**23.3(C)/54%RH**
Test Mode:	**Mode 4**	**Distance:**	**3m**



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.5591	38.54	-14.47	24.07	40.00	-15.93	QP	300	75	
2	56.7917	36.44	-16.82	19.62	40.00	-20.38	QP	300	142	
3	91.1746	51.39	-22.79	28.60	43.50	-14.90	QP	300	136	
4	106.3850	51.76	-20.68	31.08	43.50	-12.42	QP	300	269	
5	318.8170	48.69	-15.39	33.30	46.00	-12.70	QP	300	320	
6	414.7223	46.42	-12.52	33.90	46.00	-12.10	QP	300	351	

Job No.:	**SZAWW180605005-01**	**Polarization:**	**Vertical**
Standard:	**FCC PART15 C _3m**	**Power Source:**	**AC 120V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**23.3(C)/54%RH**
Test Mode:	**Mode 4**	**Distance:**	**3m**

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	40.5591	47.14	-13.47	33.67	40.00	-6.33	QP	300	56	
2	44.7433	43.32	-14.28	29.04	40.00	-10.96	QP	300	136	
3	101.6443	45.97	-14.74	31.23	43.50	-12.27	QP	300	167	
4	230.9068	37.29	-13.86	23.43	46.00	-22.57	QP	300	256	
5	317.7011	39.51	-14.31	25.20	46.00	-20.80	QP	300	301	
6	483.9094	40.87	-11.43	29.44	46.00	-16.56	QP	300	339	

Job No.:	**SZAWW180605005-01**	**Polarization:**	**Horizontal**
Standard:	**FCC PART15 C _3m**	**Power Source:**	**AC 240V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**23.3(C)/54%RH**
Test Mode:	**Mode 4**	**Distance:**	**3m**

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	41.2765	35.59	-14.62	20.97	40.00	-19.03	QP	300	76	
2	62.8708	36.41	-18.07	18.34	40.00	-21.66	QP	300	145	
3	100.5806	52.33	-20.76	31.57	43.50	-11.93	QP	300	256	
4	236.6447	46.46	-17.80	28.66	46.00	-17.34	QP	300	277	
5	313.2760	48.43	-16.07	32.36	46.00	-13.64	QP	300	303	
6	423.5403	45.03	-12.35	32.68	46.00	-13.32	QP	300	330	

Job No.:	**SZAWW180605005-01**	**Polarization:**	**Vertical**
Standard:	**FCC PART15 C _3m**	**Power Source:**	**AC 240V, 60Hz for adapter**
Test item:	**Radiation Test**	**Temp.(C)/Hum.(%RH):**	**23.3(C)/54%RH**
Test Mode:	**Mode 4**	**Distance:**	**3m**

No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	30.2111	50.80	-17.49	33.31	40.00	-6.69	QP	300	96	
2	40.7016	40.45	-13.50	26.95	40.00	-13.05	QP	300	110	
3	84.9995	43.65	-17.95	25.70	40.00	-14.30	QP	300	169	
4	229.2931	37.08	-13.93	23.15	46.00	-22.85	QP	300	220	
5	329.0390	39.40	-13.83	25.57	46.00	-20.43	QP	300	299	
6	483.9094	40.07	-11.43	28.64	46.00	-17.36	QP	300	330	

APPENDIX I -- TEST SETUP PHOTOGRAPH

Photo of Conducted Emission Measurement

Photo of Radiation Emission Test





APPENDIX II -- EXTERNAL PHOTOGRAPH


Anbotek
Product Safety



0 1 2 3 4 5 6 7 8

APPENDIX III -- INTERNAL PHOTOGRAPH



Anbotek
Product Safety


Anbotek
Product Safety


D258A&B-B-V2.1
2018-05-03
Anbotek
Product Safety


Anbotek
Product Safety
安博检测

---------- End of Report ----------