

BUREAU
VERITAS

Test Report No.: FM190822N030

RF EXPOSURE REPORT

Applicant	VITEC IMAGING SOLUTIONS SPA
Address	CASSOLA(VI) VIA VALSUGANA 100 CAP 36022

Manufacturer or Supplier	Golden Trees technology Co.,Ltd.
Address	NO.3 Nan Tong Blvd,Bao Long Industrial Area Long Gang District,Shenzhen,China
Product	Beamo LED Light
Brand Name	JOBY
Model	JB01579-BWW
Additional Model & Model Difference	JB01635-BWW; JB01578-BWW
Date of tests	Jul. 18, 2019 ~ Aug. 22, 2019

☒ FCC Part 2 (Section 2.1091)☒ KDB 447498 D01☒ IEEE C95.1**CONCLUSION: The submitted sample was found to COMPLY with the test requirement**Tested by Evans He
Project Engineer / EMC DepartmentApproved by David Huang
Supervisor / EMC Department*Evans He**David Huang*

Date: Aug 22, 2019

This report is governed by, and incorporates by reference, CPS Conditions of Service as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.

Bureau Veritas Shenzhen Co., Ltd.
Dongguan BranchNo. 34, Chenwulu Section, Guantai Rd., Houjie
Town, Dongguan City,
Guangdong 523942, ChinaTel: +86 769 8998 2098
Fax: +86 769 8593 1080
Email: customerservice.dg@cn.bureauveritas.com



Table of Contents

RELEASE CONTROL RECORD	3
1. CERTIFICATION.....	4
2. RF EXPOSURE LIMIT	5
3. MPE CALCULATION FORMULA.....	5
4. CLASSIFICATION	5
5. ANTENNA GAIN	6
6. CALCULATION RESULT OF MAXIMUM CONDUCTED POWER.....	6



Test Report No.: FM190822N030

RELEASE CONTROL RECORD

ISSUE NO.	REASON FOR CHANGE	DATE ISSUED
FM190822N030	Original release	Aug 22, 2019



Test Report No.: FM190822N030

1. CERTIFICATION

FCC ID:	2AQK5-BEAMO1
PRODUCT:	Beamo LED Light
BRAND NAME:	JOBY
MODEL NO.:	JB01579-BWW
ADDITIONAL NO.:	JB01635-BWW; JB01578-BWW
APPLICANT:	VITEC IMAGING SOLUTIONS SPA
STANDARDS:	FCC Part 2 (Section 2.1091)
	KDB 447498 D01
	IEEE C95.1

NOTE:

1. Additional models (see about table) are identical with the test model JB01635-BWW; JB01578-BWW except the color of the appearance and model name for trading purpose.

2. Test Lab Information:

Lab: Bureau Veritas Shenzhen Co., Ltd. Dongguan Branch

Test Lab Address: Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
South Side of Zhoushi Road, Bao'an District Shenzhen, Guangdong, 518108,
People's Republic of China



2. RF EXPOSURE LIMIT

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

FREQUENCY RANGE (MHz)	ELECTRIC FIELD STRENGTH (V/m)	MAGNETIC FIELD STRENGTH (A/m)	POWER DENSITY (mW/cm ²)	AVERAGE TIME (minutes)
LIMITS FOR GENERAL POPULATION / UNCONTROLLED EXPOSURE				
300-1500	...	...	F/1500	30
1500-100,000	...	...	1.0	30

F = Frequency in MHz

3. MPE CALCULATION FORMULA

$$P_d = (P_{out} * G) / (4 * \pi * r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

4. CLASSIFICATION

The antenna of this product, under normal use condition, is at least 20cm away from the body of the user. So, this device is classified as **Mobile Device**.



5. ANTENNA GAIN

The antennas provided to the EUT, please refer to the following table:

Transmitter Circuit	Peak Gain (dBi)	Antenna Type
Chain 0	0	Integral PCB Antenna

6. CALCULATION RESULT OF MAXIMUM CONDUCTED AV POWER

The tuned conducted Average Power (declared by client)

Mode	Frequency (MHz)	Target Power (dBm)	Tolerance (dBm)	Lower Tolerance (dBm)	Upper Tolerance (dBm)
BT_LE(GFSK)	2402-2480	0	+2	-2	2

The measured conducted Average Power

Mode	Frequency (MHz)	Averaged Power (dBm)
BT_LE(GFSK)	2480	0.85

FREQUENCY BAND (MHz)	MAX AVERAGE POWER (dBm)	ANTENNA GAIN (dBi)	DISTANCE (cm)	POWER DENSITY (mW/cm ²)	LIMIT (mW/cm ²)
2402-2480	1.65	0	20	0.00029	1.0

--- END ---